Sandboxing Agentic AI


An introduction, with 200 and 300 level detail where it helps

No Linux or Kubernetes background needed.

Agenda

1. What an AI agent is, and why the code it runs is risky
2. What a sandbox is, and how to measure one
3. Containers and virtual machines
4. The four settings that open a box, and how to close them
5. What the lab shows
6. Stronger walls, and how warm pools pay for them
7. Five questions to ask about any agent platform

What Is an AI Agent?



> An agent is a language model in a loop that can run code and use tools.

Agents: 100 to 300

100 level

An agent is a model that takes actions. It writes code or picks a tool, a program runs it, and the model reads the result and goes again until it reaches the goal.


200 level

The harness runs each tool call on real infrastructure: a shell, a filesystem, a network. Any file, credential, or address that process can reach, the model's output can reach too.

300 level

Platforms start thousands of short-lived sandboxes a day, often for many customers on the same machines. Isolation strength, start-up time, and cost pull against each other.


Prompt Injection




> ***If the model cannot reliably tell your instructions from an attacker's, where do you put the defense?***

What Is a Sandbox?

Weak sandbox: big blast radius



Good sandbox: small blast radius



> The blast radius is everything the agent could damage if it went rogue. A good sandbox keeps it to the box itself.

Sandboxes: 100 to 300

100 level

A sandbox is a fenced-off place to run code. The code can do its job inside and cannot reach anything outside. When the work is done, you throw the box away.

200 level


In practice a sandbox is a container or virtual machine plus its settings: which credentials it holds, which files it sees, which user it runs as, and where it can connect.

300 level

Design for hostile code. Assume a kernel bug exists, then ask what still stands: the runtime boundary (gVisor or a microVM), the network policy, and the identity the box carries.

Containers and Virtual Machines


Containers: apartments in one building



fast and cheap: milliseconds, hundreds per machine

a crack in the foundation reaches every flat

Virtual machines: separate houses



heavier: seconds to start, tens per machine

a problem in one house stays in that house

Kernels: 100 to 300

100 level

The kernel is the core of the operating system. Every program asks it to open files and send network traffic. Containers share one kernel; each virtual machine has its own.

200 level

A container is an ordinary process. The kernel fences it with namespaces, which limit what it can see, and cgroups, which limit what it can use. Every system call still lands in the host kernel.

300 level

The host kernel offers hundreds of system calls. Seccomp trims that list, but a bug in what remains, such as `io_uring`, can let code escape the container. gVisor and microVMs take the host kernel out of reach.

A **cgroup** (control group) is a Linux kernel feature that caps how much CPU, memory, and disk I/O a group of programs can use, and how many processes it can start. Kubernetes turns a pod's resource limits into cgroup settings on the node.

The Trade-off

	Container	Virtual machine
Start time	milliseconds	seconds
Size	megabytes	gigabytes
How many per machine	hundreds	tens
Walls	shared kernel	own kernel, hardware-enforced

Agent platforms need the speed and density of containers for thousands of boxes, and the walls of a virtual machine for the code inside them.


Kubernetes Runs the Boxes

Kubernetes runs containers across many machines.

- It decides where each container runs, and restarts or adds containers as load changes.
- It hands out credentials and permissions: who can read which secrets.
- It applies the settings that decide how strong each box is.

> Most agent platforms run on Kubernetes, so Kubernetes settings decide how strong the sandbox is.

Kubernetes Words You Will Hear



Pod: the smallest thing Kubernetes runs, one or more containers.

Replica: one identical copy of a pod. Ask for 3, and Kubernetes keeps 3 running, replacing any that die.

Kubernetes: 100 to 300

100 level

A **cluster** is a group of machines, called **nodes**. Kubernetes runs your program in **pods**, and you say how many copies, called **replicas**, you want. If one dies, Kubernetes starts another.

200 level

You describe what you want in YAML, for example a `Deployment` with `replicas: 3`, and run `kubectl apply`. A **controller** compares that with what is running and starts or stops pods until the two match.

300 level

A Kubernetes **namespace** groups objects and permissions, such as `corp-secrets`. It is a different thing from a Linux namespace, and pods in different namespaces still share nodes and kernels. A `Sandbox` is one pod with a stable name, like a `StatefulSet` with one replica.

Four Ways Out of a Default Box

A box on default settings has four ways out



None of this needs anything exotic. Security is opt-in.

Hardening: 100 to 300

100 level

Take the keys out of the box. Close the hatch to the machine's files. Run as an ordinary user, and shut the network door. The agent's code stays the same.

200 level


Set `automountServiceAccountToken: false`, drop `hostPath` and `hostPID`, run as non-root with all capabilities dropped and a read-only root filesystem, use seccomp `RuntimeDefault`, and add a default-deny egress `NetworkPolicy`.

300 level

Enforce it so nobody can forget. The Pod Security `restricted` profile rejects pods that run as root, keep capabilities, or mount host paths. A `NetworkPolicy` does nothing without a CNI that enforces it, so the lab installs Calico.

The **CNI** (Container Network Interface) is the plugin that gives each pod an IP address and connects pods to each other. It also decides whether `NetworkPolicy` rules are enforced: Calico enforces them, and kind's default plugin, kindnet, ignores them.

The Lab: Same Agent, Two Boxes




How the Secured Box Blocks Each Attack

The agent tries to	What stopped it
steal passwords with the cluster's keys	no keys in the box, and the account has no permissions
read the machine's files	the box cannot see the host's files
see other programs	the box sees only its own programs
change or install things	it runs as an ordinary user on a read-only disk
reach other systems	the network is closed except for name lookups

> Defense in depth: each setting closes one path, so one forgotten setting does not open them all.

A Ladder of Isolation

Each step up: stronger walls, slower start



The hardened container still shares the host kernel. How much start-up time would you trade to stop sharing it?

Isolation Runtimes: 100 to 300

100 level

Stronger walls take longer to put up. gVisor adds about half a second; a microVM adds a few seconds. For untrusted agent code, gVisor is a good default.


200 level

You pick the runtime per pod with one field, `runtimeClassName`. gVisor (`runsc`) runs a userspace kernel that handles the agent's system calls. Kata and Firecracker boot a small VM with its own kernel.

300 level

gVisor gives up some system-call coverage and I/O speed for a much smaller host-kernel surface, and it needs no KVM. Kata and Firecracker need `/dev/kvm`, which laptop container VMs and many cloud instances do not expose.

Warm Pools: Strong Walls Without the Wait



Warm Pools: 100 to 300

100 level

Start boxes before anyone asks for one, so an agent never waits for the slow part.

200 level

`agent-sandbox` uses three objects. A `SandboxTemplate` holds the secure recipe, a `SandboxWarmPool` keeps a set number ready, and a `SandboxClaim` is an agent's request, which takes a ready box from the pool.

300 level

Size the pool to peak demand. Too small, and agents wait for new boxes at the cold-start time. Too large, and you pay for boxes that sit idle. A claimed box leaves the pool, and the pool starts a replacement.

The `agent-sandbox` Project

An open-source Kubernetes project that makes a sandbox one object.

- One `Sandbox` replaces a dozen hand-wired settings.
- Templates make the secure settings the default, so nobody has to remember them.
- Warm pools come built in.
- The stronger runtimes plug in with one field.

> You can build all of this by hand, and one forgotten setting leaves the box open. A template applies the same secure recipe to every sandbox.

Five Questions for Any Agent Platform

1. **Keys**: does the agent hold any credentials it does not need?
2. **Host**: can it see the machine's files or other programs?
3. **Power**: does it run as an all-powerful user?
4. **Network**: what can it connect to? The answer should be almost nothing.
5. **Walls**: does it share a kernel with other customers, or have its own?

> ***If you cannot answer one of these, that is your next conversation with the platform team.***

Sandboxing Agentic AI at a glance

Lecture and lab summary · Kubernetes + kind + the agent-sandbox CRD · 100 level

The idea: an agent runs code that nobody reviewed, so the sandbox is the security boundary.

Why agents need a sandbox

Untrusted code

The agent writes code and runs it, usually before any person reads it.

Prompt injection


Hidden instructions in a web page or file can steer that code toward an attacker's goal.

Volume and sharing

Platforms start thousands of short-lived boxes, often for many customers on the same machines.

Containers and virtual machines


Container: apartments in one building



Starts in milliseconds, megabytes in size, hundreds per machine.

One kernel bug or misconfiguration can reach every app.

Virtual machine: separate houses



Starts in seconds, gigabytes in size, tens per machine.


Each guest brings its own kernel.

The lab: same agent, two boxes

The agent tries to	Plain Pod, defaults	Hardened Sandbox, and the control that stopped it
steal secrets with the cluster API token	BREACH	CONTAINED no token mounted, zero RBAC
read the node's files (cluster CA key)	BREACH	CONTAINED no hostPath mount
see every process on the node	BREACH	CONTAINED own PID namespace (no hostPID)
run as root and rewrite its own files	BREACH	CONTAINED uid 65532, read-only rootfs, all caps dropped
reach the API server or metadata service	open egress	CONTAINED deny-all egress NetworkPolicy (DNS only)

Both boxes run the same image and the same attack script. Kubernetes defaults leave every one of these paths open.

A ladder of isolation



Layer the defenses, then hide the start-up cost

Four layers

Identity: no token automount, least RBAC
Workload: non-root, caps dropped, seccomp
Network: default-deny egress
Runtime: gVisor or Kata via RuntimeClass

Warm pools



The pool starts sandboxes ahead of time. A claim gets one in under 2s instead of 10 to 30s.

Run the lab `cd lab && ./scripts/01-up.sh && ./scripts/demo.sh`

Lab and slides: github.com/omrishiv/agent-sandbox · Sandbox CRD: github.com/kubernetes-sigs/agent-sandbox · gvisor.dev · katacontainers.io

Run the Lab

```
cd lab
./scripts/01-up.sh                  # kind + Calico + the Sandbox CRD (about 4 minutes)
./scripts/02-attack-unsecured.sh    # the plain Pod: every probe breaches
./scripts/03-defend-secured.sh      # the hardened Sandbox: every probe is contained
WITH_GVISOR=1 ./scripts/01-up.sh && ./scripts/05-compare-gvisor.sh   # runc vs gVisor
./scripts/99-down.sh                # delete the cluster
```

The 200-level deck (`slides.md`) covers the same ground with the real Kubernetes settings.

- **agent-sandbox**: github.com/kubernetes-sigs/agent-sandbox
- **gVisor**: gvisor.dev · **Kata Containers**: katacontainers.io · **Firecracker**: firecracker-microvm.github.io
- **Kubernetes security**: Pod Security Standards, Network Policies, and RBAC on kubernetes.io

Glossary: The Ideas

Term	Meaning
Agent	an AI model in a loop that takes actions, such as running code or calling tools
Harness	the program around the model that runs each tool call the model asks for
Prompt injection	instructions hidden in a web page or file that steer an agent toward an attacker's goal
Sandbox	a fenced-off place to run untrusted code
Blast radius	everything the agent could damage if it went rogue
Defense in depth	several independent settings, each closing one path, so one mistake does not open them all
Container	a lightweight box for a program that shares the host's kernel
Virtual machine (VM)	a full pretend computer with its own kernel
Hypervisor	the software that runs VMs and uses the hardware to keep them apart
Warm pool	sandboxes started ahead of time so an agent does not wait for one

Glossary: Linux and Containers

Term	Meaning
Kernel	the core of the operating system; every program asks it to open files and send network traffic
System call (syscall)	one request from a program to the kernel, such as "open this file"
Namespace (Linux)	a kernel feature that limits what a process can see: other processes, files, network
cgroup (control group)	a kernel feature that caps the CPU, memory, and I/O a process can use, and how many processes it can start
seccomp	a kernel filter that blocks system calls a process should not make
Capabilities	root's powers split into about 40 pieces; the secured box drops all of them
root, non-root	root (user ID 0) can do anything; the secured box runs as user 65532
`io_uring`	a fast kernel interface for disk and network I/O, and the source of several container escapes

Glossary: Kubernetes

Term	Meaning
Cluster, node	a cluster is a group of machines run by Kubernetes; each machine is a node
Pod	the smallest unit Kubernetes runs: one or more containers that share a network address
Replica	one identical copy of a pod; you ask for a count and Kubernetes keeps that many running
Deployment, StatefulSet	objects that keep a set number of replicas running; a StatefulSet gives each one a stable name
Namespace (Kubernetes)	a named group of objects and permissions in the cluster, such as `corp-secrets`
Service account token	a credential Kubernetes mounts into a pod by default so it can call the Kubernetes API
RBAC	role-based access control: rules for what each identity may do in the Kubernetes API
`hostPath`, `hostPID`	settings that let a pod see the node's files or the node's processes
NetworkPolicy, CNI	traffic rules for a pod, and the network plugin that enforces them (Calico does, kindnet does not)
Egress, metadata service	outbound traffic, and the cloud endpoint (169.254.169.254) that hands out machine credentials

Glossary: Runtimes and `agent-sandbox`

Term	Meaning
runc	the default container runtime; its containers share the host kernel
gVisor (`runsc`)	a runtime with its own userspace kernel that handles the container's system calls
Kata Containers, Firecracker	runtimes that put each container in a small VM with its own kernel
KVM (`/dev/kvm`)	the hypervisor built into Linux; Kata and Firecracker need it
RuntimeClass	names a container runtime; `runtimeClassName` picks one for a pod
CRD, controller	a CustomResourceDefinition teaches Kubernetes a new kind of object; a controller makes the cluster match it
`Sandbox`	one sandbox: a single pod with a stable name and its own storage
`SandboxTemplate`	the secure recipe that sandboxes are built from
`SandboxWarmPool`, `SandboxClaim`	the pool of ready sandboxes, and an agent's request for one