Netflix Data Analysis and Visualization Project

Introduction

This notebook performs a comprehensive Exploratory Data Analysis (EDA) on a Netflix dataset. The goal is to uncover trends in content creation, understand distribution across countries, and categorize content for better insights.

Steps covered:

1. **Data Cleaning:** Handling missing values and duplicates.
2. **Feature Engineering:** Creating new metrics like `year_added`, `cast_count`, and `rating_category`.
3. **Exploratory Analysis:** Statistical summaries and visual inspections.

In [ ]:

```

```

In [ ]:

```

```

In [ ]:

```

```

In [ ]:

```

```

1. Environment Setup and Data Loading

In this section, we import the necessary libraries for data manipulation (`pandas`, `numpy`) and visualization (`seaborn`, `matplotlib`). We also load the raw Netflix dataset.

In [412]:

```
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
import numpy as np

from warnings import filterwarnings
filterwarnings("ignore")



df = pd.read_csv("dataset/Netflix.csv")
```

2. Initial Data Inspection

Before cleaning, we take a quick look at the first few rows of the data, its dimensions, and the data types of each column to identify potential issues.

In [413]:

```
df.head()
```

Out[413]:

	show_id	type	title	director	cast	country	date_added	release_year	rating	duration	genres
0	s1	TV Show	3%	NaN	João Miguel, Bianca Comparato, Michel Gomes, R...	Brazil	14-Aug-20	2020	TV-MA	4	International TV Shows, TV Dramas, TV Sci-Fi &...
1	s10	Movie	1920	Vikram Bhatt	Rajneesh Duggal, Adah Sharma, Indraneil Sengup...	India	15-Dec-17	2008	TV-MA	143	Horror Movies, International Movies, Thrillers
2	s100	Movie	3 Heroines	Iman Brotoseno	Reza Rahadian, Bunga Citra Lestari, Tara Basro...	Indonesia	5-Jan-19	2016	TV-PG	124	Dramas, International Movies, Sports Movies
3	s1000	Movie	Blue Mountain State: The Rise of Thadland	Lev L. Spiro	Alan Ritchson, Darin Brooks, James Cade, Rob R...	United States	1-Mar-16	2016	R	90	Comedies
4	s1001	TV Show	Blue Planet II	NaN	David Attenborough	United Kingdom	3-Dec-18	2017	TV-G	1	British TV Shows, Docuseries, Science & Nature TV

In [414]:

```
df.shape
```

Out[414]:

```
(7787, 12)
```

In [415]:

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 7787 entries, 0 to 7786
Data columns (total 12 columns):
 #   Column        Non-Null Count  Dtype 
---  ------        --------------  ----- 
 0   show_id       7787 non-null   object
 1   type          7787 non-null   object
 2   title         7787 non-null   object
 3   director      5398 non-null   object
 4   cast          7069 non-null   object
 5   country       7280 non-null   object
 6   date_added    7777 non-null   object
 7   release_year  7787 non-null   int64 
 8   rating        7780 non-null   object
 9   duration      7787 non-null   int64 
 10  genres        7787 non-null   object
 11  description   7787 non-null   object
dtypes: int64(2), object(10)
memory usage: 730.2+ KB
```

In [416]:

```
df.describe()
```

Out[416]:

	release_year	duration
count	7787.000000	7787.000000
mean	2013.932580	69.122769
std	8.757395	50.950743
min	1925.000000	1.000000
25%	2013.000000	2.000000
50%	2017.000000	88.000000
75%	2018.000000	106.000000
max	2021.000000	312.000000

In [417]:

```
df.isnull().sum()
```

Out[417]:

```
show_id            0
type               0
title              0
director        2389
cast             718
country          507
date_added        10
release_year       0
rating             7
duration           0
genres             0
description        0
dtype: int64
```

In [418]:

```
df.duplicated().sum()
```

Out[418]:

```
np.int64(0)
```

3. Data Cleaning

To ensure the quality of our analysis, we perform the following:

- **Drop Unnecessary Columns:** Removing `show_id` as it serves only as a unique identifier.
- **Impute Missing Values:** Filling gaps in `director`, `cast`, and `country` with "Unknown", and using the mode for `rating` and `date_added`.

In [419]:

```
df.drop(columns=['show_id'], inplace=True)
```

In [420]:

```
df['director'].fillna('Unknown', inplace=True)
df['cast'].fillna('Unknown', inplace=True)
df['country'].fillna('Unknown', inplace=True)
df['rating'].fillna(df['rating'].mode()[0], inplace=True)
df['date_added'].fillna(df['date_added'].mode()[0], inplace=True)
```

4. Feature Engineering

We create new features to extract more value from the existing data:

1. **Date Extraction:** Converting `date_added` to datetime objects to extract year and month.
2. **Complexity Metrics:** Calculating the number of cast members and genres per title.
3. **Categorization:** Simplifying the content ratings into broader categories: **Adult**, **Teen**, and **Kids**.
4. **Localization:** Extracting the primary country of origin from the `country` column.

In [421]:

```
df['date_added'] = pd.to_datetime(df['date_added'])

df['year_added'] = df['date_added'].dt.year
df['month_added'] = df['date_added'].dt.month
```

In [422]:

```
df.drop(columns=['date_added'], inplace=True)
```

In [423]:

```
df['cast_count'] = df['cast'].apply(lambda x: len(x.split(',')))
df['genre_count'] = df['genres'].apply(lambda x: len(x.split(',')))
```

In [424]:

```
df['duration_type'] = df['type']

df.rename(columns={'duration':'duration_value'}, inplace=True)
```

In [425]:

```
df['country_main'] = df['country'].apply(lambda x: x.split(',')[0])
```

In [426]:

```
def simplify_rating(r):
    if r in ['TV-MA','R','NC-17']:
        return "Adult"
    elif r in ['PG-13','TV-14']:
        return "Teen"
    else:
        return "Kids"

df['rating_category'] = df['rating'].apply(simplify_rating)
```

In [427]:

```
df.drop(columns=['rating'], inplace=True)
```

5. Exploratory Data Analysis & Visualization

With the data cleaned and enriched, we now move to the visualization phase. This help us identify:

- **The distribution of content types (Movies vs. TV Shows).**
- **Trends in content releases over the years.**
- **Relationship between content duration and its category.**

In [428]:

```
sns.countplot(x="type",data=df)
plt.show()
```



In [429]:

```
sns.countplot(y="month_added",data=df)
plt.show()
```



In [430]:

```
plt.figure(figsize=(10,5))
sns.countplot(y=df["year_added"])
plt.show()
```



In [ ]:

```

```

In [ ]:

```

```

In [431]:

```
df['has_director'] = df['director'].apply(lambda x: 0 if x=='Unknown' else 1)
```

In [432]:

```
sns.distplot(df["duration_value"])
```

Out[432]:

```
<Axes: xlabel='duration_value', ylabel='Density'>
```



In [433]:

```
df.corr(numeric_only=True)["duration_value"].reset_index()
```

Out[433]:

	index	duration_value
0	release_year	-0.240836
1	duration_value	1.000000
2	year_added	0.037102
3	month_added	-0.024913

index	duration_value
4 cast_count	0.096601
5 genre_count	0.092256
6 has_director	0.820335

In [434]:

```
df.corr(numeric_only=True)
```

Out[434]:

	release_year	duration_value	year_added	month_added	cast_count	genre_count	has_director
release_year	1.000000	-0.240836	0.100115	-0.009661	-0.086585	-0.052931	-0.166603
duration_value	-0.240836	1.000000	0.037102	-0.024913	0.096601	0.092256	0.820335
year_added	0.100115	0.037102	1.000000	-0.135006	0.113470	0.060552	-0.001745
month_added	-0.009661	-0.024913	-0.135006	1.000000	0.001902	-0.002332	-0.028360
cast_count	-0.086585	0.096601	0.113470	0.001902	1.000000	0.219182	0.008707
genre_count	-0.052931	0.092256	0.060552	-0.002332	0.219182	1.000000	-0.041000
has_director	-0.166603	0.820335	-0.001745	-0.028360	0.008707	-0.041000	1.000000

In [435]:

```
sns.heatmap(df.corr(numeric_only=True))
```

Out[435]:

```
<Axes: >
```



Q1] CONTENT-TYPE LABELER:

In [436]:

```
df.head()
```

Out[436]:

	type	title	director	cast	country	release_year	duration_value	genres	description	year_added
0	TV Show	3%	Unknown	João Miguel, Bianca Comparato, Michel Gomes, R...	Brazil	2020	4	International TV Shows, TV Dramas, TV Sci-Fi &...	In a future where the elite inhabit an island ...	2020
1	Movie	1920	Vikram Bhatt	Rajneesh Duggal, Adah Sharma, Indraneil Sengup...	India	2008	143	Horror Movies, International Movies, Thrillers	An architect and his wife move into a castle t...	2017
2	Movie	3 Heroines	Iman Brotoseno	Reza Rahadian, Bunga Citra Lestari, Tara Basro...	Indonesia	2016	124	Dramas, International Movies, Sports Movies	Three Indonesian women break records by becomi...	2019
3	Movie	Blue Mountain State: The Rise of Thadland	Lev L. Spiro	Alan Ritchson, Darin Brooks, James Cade, Rob R...	United States	2016	90	Comedies	New NFL star Thad buys his old teammates' belo...	2016
4	TV Show	Blue Planet II	Unknown	David Attenborough	United Kingdom	2017	1	British TV Shows, Docuseries, Science & Nature TV	This sequel to the award-winning nature series...	2018

In [ ]:

In [ ]:

LOGISTIC - REGRESSION:

In [437]:

```
# Import necessary libraries
from sklearn.model_selection import train_test_split
from sklearn.compose import ColumnTransformer
from sklearn.preprocessing import OneHotEncoder, StandardScaler
from sklearn.linear_model import LogisticRegression
from sklearn.pipeline import Pipeline
from sklearn.metrics import accuracy_score, classification_report, confusion_matrix
import pickle


num_features = ['cast_count', 'genre_count', 'duration_value']

cat_features = ['country_main', 'rating_category']

X = df[num_features + cat_features]
y = df['type']

# Split the data into train and test sets (80-20 split)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42
, stratify=y)
```

```python
num_transformer = Pipeline(steps=[
    ('scaler', StandardScaler())
])


cat_transformer = Pipeline(steps=[
    ('onehot', OneHotEncoder(drop='first', handle_unknown='ignore'))
])


preprocessor = ColumnTransformer(
    transformers=[
        ('num', num_transformer, num_features),
        ('cat', cat_transformer, cat_features)
    ])



prediction_pipeline_1 = Pipeline(steps=[
    ('preprocessor', preprocessor),
    ('classifier', LogisticRegression(random_state=42, max_iter=1000))
])


prediction_pipeline_1.fit(X_train, y_train)


y_pred = prediction_pipeline_1.predict(X_test)

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy:.4f}")
print("\nClassification Report:")
print(classification_report(y_test, y_pred, target_names=['Movie', 'TV Show']))
print("\nConfusion Matrix:")
print(confusion_matrix(y_test, y_pred))

# Save the pipeline model (similar to laptop project)
with open('netflix_type_predictor_pipeline_1.pkl', 'wb') as f:
    pickle.dump(prediction_pipeline_1, f)


# Example prediction function (like app.py in laptop project)
def predict_content_type(cast_count, genre_count, duration_value,
                         country_main, rating_category):
    # Create input DataFrame
    query_df = pd.DataFrame({
        'cast_count': [cast_count],
        'genre_count': [genre_count],
        'duration_value': [duration_value],
        'country_main': [country_main],
        'rating_category': [rating_category]
    })

    # Load the pipeline
    with open('netflix_type_predictor_pipeline_1.pkl', 'rb') as f:
        pipe = pickle.load(f)

    # Predict
    prediction = pipe.predict(query_df)[0]
    content_type = 'TV Show' if prediction == 1 else 'Movie'
    probability = pipe.predict_proba(query_df)[0]
    conf_movie = probability[0] * 100
    conf_tv = probability[1] * 100

    return f"Predicted Type: {content_type} (Confidence: {max(conf_movie, conf_tv):.2f}%)
"

# Example usage
print("\nExample Prediction:")
```

```
result = predict_content_type(cast_count=8, genre_count=3, duration_value=143,
    country_main='India', rating_category='Adult'
)
print(result)
```

```
Accuracy: 0.9961

Classification Report:
              precision    recall  f1-score   support

       Movie       1.00      0.99      1.00      1076
     TV Show       0.99      1.00      0.99       482

    accuracy                           1.00      1558
   macro avg       0.99      1.00      1.00      1558
weighted avg       1.00      1.00      1.00      1558


Confusion Matrix:
[[1070    6]
 [   0  482]]

Example Prediction:
Predicted Type: Movie (Confidence: 100.00%)
```

In [ ]:

NAIVE - BAYES (Bernoulli) :

In [438]:

```
from sklearn.naive_bayes import BernoulliNB

prediction_pipeline_2 = Pipeline(steps=[
    ('preprocessor', preprocessor),
    ('classifier', BernoulliNB(
    alpha=1.0,
    binarize=0.0,
    fit_prior=True,
    class_prior=None
))
])


prediction_pipeline_2.fit(X_train, y_train)


y_pred = prediction_pipeline_2.predict(X_test)

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy:.4f}")
print("\nClassification Report:")
print(classification_report(y_test, y_pred, target_names=['Movie', 'TV Show']))
print("\nConfusion Matrix:")
print(confusion_matrix(y_test, y_pred))

# Save the pipeline model (similar to laptop project)
with open('netflix_type_predictor_pipeline_2.pkl', 'wb') as f:
    pickle.dump(prediction_pipeline_2, f)
```

```
Accuracy: 0.8954

Classification Report:
              precision    recall  f1-score   support

       Movie       0.98      0.86      0.92      1076
     TV Show       0.76      0.96      0.85       482
```

```
    accuracy                           0.90      1558
   macro avg       0.87      0.91      0.89      1558
weighted avg       0.91      0.90      0.90      1558


Confusion Matrix:
[[930 146]
 [ 17 465]]
```

In [ ]:

```

```

KNN:

In [439]:

```
from sklearn.neighbors import KNeighborsClassifier

prediction_pipeline_3 = Pipeline(steps=[
    ('preprocessor', preprocessor),
    ('classifier', KNeighborsClassifier(
        n_neighbors=5,
        weights='uniform',
        algorithm='auto',
        metric='minkowski',
        p=2
    ))
])

prediction_pipeline_3.fit(X_train, y_train)

y_pred = prediction_pipeline_3.predict(X_test)

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy:.4f}")

print("\nClassification Report:")
print(classification_report(y_test, y_pred, target_names=['Movie', 'TV Show']))

print("\nConfusion Matrix:")
print(confusion_matrix(y_test, y_pred))

# Save the pipeline model
with open('netflix_type_predictor_knn_pipeline_3.pkl', 'wb') as f:
    pickle.dump(prediction_pipeline_3, f)
```

```
Accuracy: 0.9891

Classification Report:
              precision    recall  f1-score   support

       Movie       1.00      0.99      0.99      1076
     TV Show       0.97      1.00      0.98       482

    accuracy                           0.99      1558
   macro avg       0.98      0.99      0.99      1558
weighted avg       0.99      0.99      0.99      1558


Confusion Matrix:
[[1060   16]
 [   1  481]]
```

In [ ]:

```

```

In [ ]:

In [ ]:

In [ ]:

In [ ]:

CONCLUSION: Highest accuracy is acheived through Logistic Regression.

In [ ]:

In [ ]:

Q2] Can we build a machine learning model that predicts whether a piece of content should be produced as a Movie or a TV Show based on features like cast-size, country, and release trends?

In [440]:

```
sns.countplot(x=df["type"])
plt.show()
```



In [441]:

```
data = df.groupby("type")["genre_count"].sum().reset_index()
data
```

Out[441]:

type	genre_count

	type	genre_count
0	Movie	11546
1	TV Show	5525

In [442]:

```
data = df.groupby("type")["cast_count"].sum().reset_index()
data
```

Out[442]:

	type	cast_count
0	Movie	38738
1	TV Show	17935

In [443]:

```
trend_data = df.groupby(['release_year', 'type']).size().reset_index(name='count')

trend_data_recent = trend_data[trend_data['release_year'] >= 2000]

plt.figure(figsize=(12, 6))
sns.lineplot(data=trend_data_recent, x='release_year', y='count', hue='type', marker='o'
, linewidth=2.5)
```

Out[443]:

```
<Axes: xlabel='release_year', ylabel='count'>
```



In [444]:

```
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier, plot_tree
import matplotlib.pyplot as plt
from sklearn.preprocessing import LabelEncoder

# 1. Preprocessing categorical features
# We extract the first country and first genre to simplify the categories
df['first_country'] = df['country'].fillna('Unknown').apply (lambda x: x.split(',')[0])

# 2. Encode strings to numbers
le_country = LabelEncoder()

df['country_encoded'] = le_country.fit_transform(df['first_country'])
```

```
feature_cols = ["cast_count", "country_encoded", "release_year"]
X = df[feature_cols]
y = df["type"]


X_train , X_test , y_train, y_test = train_test_split(X,y, test_size=0.3,random_state=42
)


model = DecisionTreeClassifier(max_depth=4, random_state=42)
model.fit(X_train , y_train)


plt.figure(figsize=(30,10))
plot_tree(model,
          feature_names=feature_cols,
          class_names=["Movie", "TV Show"],
          filled=True,
          rounded=True,
          fontsize=10,
          precision=2)

plt.title("Decision Tree for Netflix Content Type Prediction", fontsize=20)
plt.show()


print("Accuracy:",model.score(X_test, y_test))
```




```
Accuracy: 0.7064612751390672
```

In [ ]:

```

```

In [445]:

```
# 1. Create a DataFrame to hold the feature names and their corresponding importance scor
es
feature_importance_df = pd.DataFrame({
    'Feature': feature_cols,
    'Importance': model.feature_importances_
}).sort_values(by='Importance', ascending=True)

# 2. Plot the Feature Importance
plt.figure(figsize=(10, 6))
plt.barh(feature_importance_df['Feature'], feature_importance_df['Importance'], color='sk
yblue')

plt.title('Feature Importance for Netflix Content Type Prediction', fontsize=16)
plt.xlabel('Importance Score', fontsize=12)
plt.ylabel('Features', fontsize=12)
plt.grid(axis='x', linestyle='--', alpha=0.7)
```

```
plt.show()

# 3. Print the values for reference
# Create the sorted dataframe and drop the old index
importance_display = feature_importance_df.sort_values(by='Importance', ascending=False)
.reset_index(drop=True)

# Display the clean table
importance_display.reset_index()
```



Out[445]:

	index	Feature	Importance
0	0	country_encoded	0.542345
1	1	release_year	0.302328
2	2	cast_count	0.155326

In [ ]:

```

```

Q3] Which countries dominate Netflix content, and how does the Movie vs TV-Show ratio change across the top 10 countries?

In [446]:

```
top10_countries = df['country_main'].value_counts().head(10).index
country_type = df[df['country_main'].isin(top10_countries)].groupby(['country_main', 'ty
pe']).size().unstack()
country_type.plot(kind='bar', stacked=True, figsize=(12,6))
plt.title('Movie vs TV Show Distribution by Top 10 Countries')
plt.show()
```





Q4] Do titles with a known director have significantly higher cast_count, genre_count, or longer duration than “Unknown” director titles?

In [447]:

```
df.groupby('has_director')[['cast_count', 'genre_count', 'duration_value']].mean().round
(2)
sns.barplot(x='has_director', y='duration_value',hue="has_director", data=df)
plt.legend(title="Has director (1-> Yes , 0-> No)) ")
plt.show()
```



In [448]:

```
df.head()
```

Out[448]:

	type	title	director	cast	country	release_year	duration_value	genres	description	year_added
0	TV Show	3%	Unknown	João Miguel, Bianca Comparato, Michel Gomes, R...	Brazil	2020	4	International TV Shows, TV Dramas, TV Sci-Fi &...	In a future where the elite inhabit an island ...	2020
1	Movie	1920	Vikram Bhatt	Rajneesh Duggal, Adah Sharma, Indraneil Sengup...	India	2008	143	Horror Movies, International Movies, Thrillers	An architect and his wife move into a castle t...	2017
2	Movie	3 Heroines	Iman Brotoseno	Reza Rahadian, Bunga Citra Lestari, Tara Basro...	Indonesia	2016	124	Dramas, International Movies, Sports Movies	Three Indonesian women break records by becomi...	2019
3	Movie	Blue Mountain State: The Rise of Thadland	Lev L. Spiro	Alan Ritchson, Darin Brooks, James Cade, Rob R...	United States	2016	90	Comedies	New NFL star Thad buys his old teammates' belo...	2016
4	TV Show	Blue Planet II	Unknown	David Attenborough	United Kingdom	2017	1	British TV Shows, Docuseries, Science & Nature TV	This sequel to the award-winning nature series...	2018

CONTENT- RECOMMENDATION SYSTEM:

In [449]:

```
import pandas as pd
import pickle

from nltk.stem.porter import PorterStemmer
from sklearn.feature_extraction.text import CountVectorizer
from sklearn.metrics.pairwise import cosine_similarity


ps = PorterStemmer()

def stem(text):
    y = [ps.stem(i) for i in text.split()]
    return " ".join(y)


new_df = df[['title']].copy()

new_df["title"] = new_df["title"].apply(stem)


cv = CountVectorizer(max_features=5000, stop_words="english")

vectors = cv.fit_transform(new_df["title"]).toarray()

class RecommendationModel:

    def __init__(self, cv, vectors, df):
        self.cv = cv
        self.vectors = vectors
        self.df = df

    def recommend(self, content):
```

```python
        stemmed_content = stem(content.lower())

        new_vector = self.cv.transform([stemmed_content]).toarray()

        distances = cosine_similarity(new_vector, self.vectors)[0]

        content_list = sorted(
            list(enumerate(distances)),
            reverse=True,
            key=lambda x: x[1]
        )[1:11] #recommend 10 movies

        print(f"\n\n\nRecommendations similar to: **{content}**\n")

        counter = 1

        for i in content_list:
            original_title = self.df.iloc[i[0]]['title']
            print(counter,")",f"• {original_title}")
            counter = counter+1


model = RecommendationModel(cv, vectors, df)



with open("content_recommendation_model.pkl", "wb") as f:
    pickle.dump(model, f)


with open("content_recommendation_model.pkl", "rb") as f:
    loaded_model = pickle.load(f)


loaded_model.recommend("Kesari 2")
loaded_model.recommend("Dune")
loaded_model.recommend("Stranger Things")
loaded_model.recommend("Article 15")
loaded_model.recommend("Dhurandhar")
loaded_model.recommend("Dhurandhar - The Revenge")
loaded_model.recommend("Dear Zindagi")
```

```
Recommendations similar to: **Kesari 2**

1 ) • 1920
2 ) • 3 Heroines
3 ) • Blue Mountain State: The Rise of Thadland
4 ) • Blue Planet II
5 ) • Blue Ruin
6 ) • Blue Streak
7 ) • Blue Valentine
8 ) • BluffMaster!
9 ) • Blurred Lines: Inside the Art World
10 ) • BNA



Recommendations similar to: **Dune**

1 ) • 1920
2 ) • 3 Heroines
3 ) • Blue Mountain State: The Rise of Thadland
4 ) • Blue Planet II
5 ) • Blue Ruin
6 ) • Blue Streak
7 ) • Blue Valentine
8 ) • BluffMaster!
9 ) • Blurred Lines: Inside the Art World
10 ) • BNA
```

Recommendations similar to: **Stranger Things**

1) • Beyond Stranger Things
2) • One Last Thing
3) • Stranger
4) • That Thing Called Tadhana
5) • THE STRANGER
6) • Cities of Last Things
7) • Little Things
8) • Most Beautiful Thing
9) • Perfect Stranger
10) • Archibald's Next Big Thing

Recommendations similar to: **Article 15**

1) • Article 15
2) • Kalel, 15
3) • 3%
4) • 1920
5) • 3 Heroines
6) • Blue Mountain State: The Rise of Thadland
7) • Blue Planet II
8) • Blue Ruin
9) • Blue Streak
10) • Blue Valentine

Recommendations similar to: **Dhurandhar**

1) • 1920
2) • 3 Heroines
3) • Blue Mountain State: The Rise of Thadland
4) • Blue Planet II
5) • Blue Ruin
6) • Blue Streak
7) • Blue Valentine
8) • BluffMaster!
9) • Blurred Lines: Inside the Art World
10) • BNA

Recommendations similar to: **Dhurandhar - The Revenge**

1) • Revenge of the Pontianak
2) • Revenger
3) • Girl's Revenge
4) • Revenge of the Green Dragons
5) • Satria Heroes: Revenge of the Darkness
6) • The Car: Road to Revenge
7) • Cats & Dogs: The Revenge of Kitty Galore
8) • 3%
9) • 1920
10) • 3 Heroines

Recommendations similar to: **Dear Zindagi**

1) • Dear Dad
2) • Dear Dracula
3) • Dear Ex
4) • Dear My Friends
5) • Dear Santa
6) • My Dear Boy
7) • My Dear Warrior
8) • Dear White People

```
9 ) • Zindagi Gulzar Hai
10 ) • Khelti Hai Zindagi Aankh Micholi
```

In [ ]:

```

```

In [ ]:

```

```