

Admin User Manual

Field	Value
Document ID	UAIL-ITDASH-ADM-001
Version	1.0
Status	Internal review
Classification	Internal
Owner	Tech-Unit IT
Last Updated	2026-07-17
Audience	Administrators and support owners

1. Audience

This guide is for administrators responsible for service uptime, collector configuration, and session recovery.

2. Login

Browse to the admin surface:

- `http://<server>:21061/login`

Use the admin password on the admin login page.

3. Admin Console Layout

The admin console is organized as tabbed views:

- Overview
- Services
- Sessions
- Sources



Admin overview

4. Overview Tab

Use Overview to:

- see how many services need attention
- see whether collector sessions need renewal
- jump directly into the affected tab

5. Services Tab

Use Services to:

- inspect PM2 service state
- see whether each service is online, warning, error, or stopped
- run start, stop, or restart actions
- trigger a full-stack restart when needed

Typical services:

- `api-gateway`
- `dashboard-ui`
- `dashboard-frontdoor-operator`
- `dashboard-frontdoor-admin`
- `nutanix-collector`
- `solarwinds-collector`
- `symphony-collector`

6. Sessions Tab

Use Sessions to validate whether the stored browser-authenticated state is actually usable against the live portal.



Admin sessions

Session states:

- `AUTH OK`
- `EXPIRED`
- `UNREACHABLE`
- `MISSING`
- `INVALID`

6.1 HSD Reauthentication

When HSD is expired:

- open the admin surface from the server itself if possible
- go to Sessions
- run `Launch Reauth on Server`
- complete the interactive Edge login on the Windows host
- wait for the helper to save the refreshed storage-state file

6.2 HSD Legacy Import

Use `Import Legacy HSD Profile` only when:

- an older authenticated Edge profile exists
- the standard interactive recovery is not the preferred path

This is an explicit recovery action, not an automatic fallback.

6.3 SolarWinds Session Recovery

Use the equivalent session actions for SolarWinds when the live validation shows expiry or invalid state.

7. Sources Tab

Use Sources to manage:

- target URLs
- collector enable or disable flags
- usernames and passwords
- poll intervals
- metadata values used by specific collectors

Current source groups:

- Nutanix primary
- SolarWinds servers
- SolarWinds networks
- Symphony primary

8. Server-Local Admin Behavior

Some actions are intentionally server-local:

- HSD interactive reauth
- HSD legacy-profile helper launch where applicable

If you open the admin portal from a remote client, those controls are hidden by design.

9. Operational Guidance

9.1 When A Card On The Dashboard Is Stale

Check:

1. Sessions tab for source authentication state
2. Services tab for collector process health
3. Sources tab for target URL or credential drift

9.2 When A Collector Is Running But Not Updating

Check:

1. the session status
2. the source endpoint configuration
3. the PM2 process logs

9.3 After Changing Credentials

- save the source settings
- restart the affected collector if needed
- validate that the next sync succeeds

10. What Admins Should Not Do

- Do not expose internal ports `3001` or `4000` to the LAN
- Do not treat expired session files as valid just because they exist
- Do not use legacy profile import as the normal HSD login path

11. Recovery Flow

