

Windows Deployment Instructions - 2026-07-15

Scope

This document describes the current deployable path for the UAIL IT Dashboard stack as it exists in this repository on 2026-07-15.

Produced Artifacts

- Installer: `deployment/installer/output/utkal-it-dashboard-setup.exe`
- Admin Console: `deployment/admin-console/release/utkal-it-admin-console-0.1.0-x64.exe`
- Staged Payload: `deployment/staging/current`
- Artifact Hashes: `deployment/release/artifact-hashes-2026-07-15.md`

Current recommendation: use the staged payload plus manual environment/bootstrap as the primary production deployment path.

Target Runtime Topology

- `dashboard-frontdoor` on `0.0.0.0:3000`
- `dashboard-ui` on `127.0.0.1:3001`
- `api-gateway` on `127.0.0.1:4000`
- collectors post only to `http://127.0.0.1:4000/api/update`
- users browse only to `http://<server>:3000`

Server Prerequisites

- Windows Server 2019 or later
- Microsoft Edge installed
- Postgres reachable from the server
- service-account connectivity to Nutanix, SolarWinds, and HSD
- local administrator access for installation and firewall changes

Recommended Production Deployment

1. Copy deployment payload

Copy `deployment/staging/current` to a fixed install path such as `C:\Apps\samixa`.

2. Create runtime data root

Create `C:\ProgramData\UAIL\itdash`.

3. Create the real environment file

In `C:\Apps\samixa\app`, create `.env` based on `.env.example`.

- `POSTGRES_URL`
- `POSTGRES_SSL`
- `POSTGRES_SECRET_PASSPHRASE`

- APP_AUTH_SECRET
- VIEWER_SESSION_DAYS
- ADMIN_SESSION_HOURS

4. Start the stack

```
cd C:\Apps\samixa\app
..\runtime\node\npm.cmd install --offline
..\runtime-tools\node_modules\.bin\pm2.cmd start ecosystem.config.js --update-env
..\runtime-tools\node_modules\.bin\pm2.cmd save
```

5. Configure startup

Preferred short-term approach: use PM2 and restore processes on boot with a Scheduled Task if PM2 startup integration is not used.

```
cd C:\Apps\samixa\app
..\runtime-tools\node_modules\.bin\pm2.cmd resurrect
```

6. Configure firewall

- Allow inbound TCP 3000 only from approved internal subnets
- Do not expose TCP 3001 or 4000

7. First browser validation

Open `http://<server>:3000/login` and validate viewer and admin login.

Admin Console Use

Portable artifact: `deployment/admin-console/release/utkal-it-admin-console-0.1.0-x64.exe`

Installed path: `C:\Apps\samixa\admin-console\Utkal IT Admin Console.exe`

- PM2-backed service status
- start, stop, restart per service
- restart full stack
- HSD and SolarWinds session import
- runtime folder access

HSD Session Recovery

1. obtain a valid Playwright storage-state JSON
2. sign in as admin
3. use the admin console or dashboard admin flow to import the session

Target file: `C:\ProgramData\UAIL\itdash\sessions\symphony\symphony-storage-state.json`

SolarWinds Session Files

- `C:\ProgramData\UAIL\itdash\sessions\solarwinds\solarwinds-servers-storage-state.json`
- `C:\ProgramData\UAIL\itdash\sessions\solarwinds\solarwinds-networks-storage-state.json`

Validation Checklist

```
cd C:\Apps\samixa\app
..\runtime-tools\node_modules\.bin\pm2.cmd status
```

- `api-gateway` online
- `dashboard-ui` online
- `dashboard-frontdoor` online
- `nutanix-collector` online
- `solarwinds-collector` online
- `symphony-collector` online

Artifact Verification

Hashes are recorded in `deployment/release/artifact-hashes-2026-07-15.md`.

Unsigned build note: current artifacts are unsigned. Windows may show SmartScreen warnings, and managed corporate endpoints may block launch depending on policy.

Current Deliverable Status

- portable admin console packaged
- installer compiled
- staged deployment payload generated
- artifact hashes generated

Operational Commands

```
cd C:\Apps\samixa\app
..\runtime-tools\node_modules\.bin\pm2.cmd status
..\runtime-tools\node_modules\.bin\pm2.cmd logs
..\runtime-tools\node_modules\.bin\pm2.cmd restart ecosystem.config.js --update-env
..\runtime-tools\node_modules\.bin\pm2.cmd save
```

Recommended path summary: use `deployment/staging/current`, deploy to `C:\Apps\samixa`, create `.env`, start with bundled PM2, expose only port `3000`, and use the packaged admin console for service control and session recovery.