
ZOOM CONSISTENCY: A FREE CONFIDENCE SIGNAL IN MULTI-STEP VISUAL GROUNDING PIPELINES

A PREPRINT

Keon Kim
Om Labs
keon@omlabs.xyz

Krish Chelikavada
Om Labs
krish@omlabs.xyz

April 10, 2026

ABSTRACT

Multi-step zoom-in pipelines are widely used for GUI grounding, yet the intermediate predictions they produce are typically discarded after coordinate remapping. We observe that these intermediate outputs contain a useful confidence signal for free: *zoom consistency*, the distance between a model’s step-2 prediction and the crop center. Unlike log-probabilities or token-level uncertainty, zoom consistency is a geometric quantity in a shared coordinate space, making it directly comparable across architecturally different VLMs without calibration. We prove this quantity is a linear estimator of step-1 spatial error under idealized conditions (perfect step-2, target within crop) and show it correlates with prediction correctness across two VLMs (AUC = 0.60; Spearman $\rho = -0.14$, $p < 10^{-6}$ for KV-Ground-8B; $\rho = -0.11$, $p = 0.0003$ for Qwen3.5-27B). The correlation is small but consistent across models, application categories, and operating systems. As a proof-of-concept, we use zoom consistency to route between a specialist and generalist model, capturing 16.5% of the oracle headroom between them (+0.8%, McNemar $p = 0.19$). Code is available at <https://github.com/omxyz/zoom-consistency-routing>.

1 Introduction

Multi-step zoom-in pipelines are widely used for high-resolution GUI grounding Jiang et al. [2025], Luo et al. [2025], Pei et al. [2026]. In a typical 2-step pipeline, a VLM predicts an initial click location on the full screenshot, a crop is extracted around that prediction and resized, and the VLM re-predicts on the zoomed view. The step-2 prediction is remapped to original coordinates, and the step-1 prediction is discarded.

We observe that the relationship between the step-2 prediction and the crop center encodes useful information about prediction quality. If step-1 was accurate, the target element is near the crop center, so step-2 should predict near the center. If step-1 was off, the target is displaced from the center, and step-2 must predict away from center to compensate. This displacement, which we call *zoom consistency*, is a free confidence signal: it requires no extra computation, no training, and no access to model internals.

This paper formalizes zoom consistency, characterizes its properties, and validates it empirically. Our contributions:

1. We define zoom consistency and prove it is a linear estimator of step-1 spatial error under idealized conditions (Proposition 1). We characterize three failure modes where the linear relationship breaks.
2. We show that zoom consistency is directly comparable across architecturally different VLMs without calibration (Proposition 2), a property that log-probabilities and token-level uncertainty scores lack.
3. We validate the signal on 1,581 samples from ScreenSpot-Pro across two models (KV-Ground-8B and Qwen3.5-27B), showing significant negative correlation with accuracy ($p < 10^{-6}$).
4. As a proof-of-concept application, we use zoom consistency for cross-model routing, deriving the exact condition under which such routing improves over the stronger model alone (Theorem 1).

2 Related Work

Zoom-In Pipelines. ZoomClick Jiang et al. [2025] systematically evaluated zoom refinement for GUI grounding. LASER Luo et al. [2025] introduced preference optimization for zoom region selection. ScreenSeeker, introduced in Li et al. [2025a], uses cascaded visual search with iterative cropping. AdaZoom-GUI Pei et al. [2026] proposed adaptive zoom with instruction refinement. Adaptive Chain-of-Focus Zhang et al. [2025] dynamically decides when to zoom. MEGA-GUI Kwak et al. [2025] proposed multi-stage coarse-to-fine grounding. These works treat zoom as a refinement mechanism; none analyze the intermediate predictions as a confidence signal.

Confidence Estimation for VLMs. GUI-RC Du et al. [2025] introduced region consistency via spatial voting across multiple sampled predictions, requiring K additional forward passes per sample. Training-Free Uncertainty Guidance Kim et al. [2025] uses model uncertainty for visual input selection via repeated sampling. Self-consistency Wang et al. [2023] aggregates multiple chain-of-thought samples, designed for discrete answers rather than continuous coordinates. Adaptive VLM Routing Liu et al. [2026] routes between VLMs using a trained difficulty estimator learned on labeled data. These methods either require extra forward passes, access to model internals, or training. Zoom consistency requires none of these.

GUI Grounding Models. SeeClick Cheng et al. [2024] established early GUI grounding benchmarks. OS-Atlas Wu et al. [2024] and UGround Gou et al. [2025] provided large-scale training data. GUI-Actor Wu et al. [2025] introduced coordinate-free grounding. UI-TARS Qin et al. [2025] scaled to 72B parameters. GUI-GRPO Yuan et al. [2025] applied reinforcement learning for grounding. KV-Ground-8B vocaela [2025] achieved state-of-the-art results through multi-stage fine-tuning from GUI-Owl-1.5 mPLUG [2026].

3 Zoom Consistency

3.1 Background: 2-Step Zoom-In Pipeline

Given a screenshot I of size $W \times H$ and instruction q , a VLM predicts $\hat{p}_1 = (x_1, y_1)$ in a normalized 1000×1000 coordinate space. A crop of side $r \cdot 1000$ centered at $\hat{p}_1$ is extracted and resized back to 1000×1000 , and the VLM predicts $\hat{p}_2 = (x_2, y_2)$ in the crop’s coordinate space. The coordinate mapping from original to crop space is $\phi(\mathbf{q}) = (\mathbf{q} - \hat{p}_1)/r + \mathbf{m}$, where $\mathbf{m} = (500, 500)$ is the crop center. The final prediction is obtained by inverting this mapping on $\hat{p}_2$.

3.2 Definition and Properties

We define *zoom consistency* as:

$$c = \|\hat{p}_2 - \mathbf{m}\|_2 = \sqrt{(x_2 - 500)^2 + (y_2 - 500)^2} \quad (1)$$

The quantity c measures how far the step-2 prediction deviates from the center of the zoomed crop. Intuitively, if the step-1 prediction was perfect, the target sits at the crop center, so step-2 should also predict the center ($c \approx 0$).

Proposition 1 (Linear Error Estimator). *Let $\mathbf{t}$ be the true target and $\hat{p}_1 = \mathbf{t} + \varepsilon_1$ be the step-1 prediction with error ε_1 . If the target lies within the crop and step-2 perfectly identifies the target ($\hat{p}_2 = \phi(\mathbf{t})$), then:*

$$c = \frac{\|\varepsilon_1\|_2}{r} \quad (2)$$

Proof. Under perfect step-2, $\hat{p}_2 = \phi(\mathbf{t}) = (\mathbf{t} - \hat{p}_1)/r + \mathbf{m} = -\varepsilon_1/r + \mathbf{m}$. Therefore $\hat{p}_2 - \mathbf{m} = -\varepsilon_1/r$ and $c = \|\varepsilon_1\|/r$. $\square$

For a crop ratio $r = 0.5$, the zoom magnifies step-1 error by $2\times$: a consistency of $c = 100$ corresponds to step-1 error of 50 pixels (5% of image width). The linear relationship provides a direct, interpretable readout of localization quality. Note that the step-1-to-final coordinate shift $\|\hat{p}_1 - \text{final}\| = r \cdot c$ is a linear rescaling of zoom consistency, so the two signals rank identically; c is the natural form because it does not depend on r .

Failure modes. The linear relationship breaks in three cases:

1. **Target outside crop:** When $\|\varepsilon_1\|_\infty > r \cdot 500$, the target is not visible in the zoomed view, so step-2 cannot correct toward it. The consistency value c becomes uninformative.

2. **Step-2 error:** If step-2 has its own prediction error ε_2 , the observed consistency becomes $c = \|-\varepsilon_1/r + \varepsilon_2\|$, bounded by $|c - \|\varepsilon_1\|/r| \leq \|\varepsilon_2\|$. This adds noise proportional to step-2’s own error.
3. **Boundary clipping:** When the crop extends beyond image boundaries, it is clipped, shifting the effective center. The mapping ϕ no longer holds exactly.

3.3 Cross-Model Comparability

Proposition 2 (Calibration-Free Comparison). *Let M_A and M_B be VLMs with different tokenizers $\mathcal{T}_A, \mathcal{T}_B$. Their zoom consistency values $c_A, c_B \in [0, 500\sqrt{2}]$ are directly comparable. In contrast, log-probability scores ℓ_A, ℓ_B depend on token count ($L_A \neq L_B$ for identical coordinate strings), softmax temperature, and vocabulary size, requiring per-model calibration functions $g_i : \mathbb{R} \rightarrow [0, 1]$ learned on held-out data.*

This property arises because zoom consistency is a geometric quantity in the shared 1000×1000 coordinate space that both models output into. The comparison $c_A < c_B$ is a statement about Euclidean distances, independent of how each model internally represents coordinates. This assumes both models use the same crop ratio r and coordinate normalization, which is standard in zoom pipelines. Under this assumption, zoom consistency is immediately usable for cross-model decisions without any calibration step.

4 Empirical Validation

4.1 Setup

Benchmark. ScreenSpot-Pro Li et al. [2025a,b]: 1,581 samples across professional desktop applications spanning 3 operating systems. Accuracy metric: point-in-bounding-box.

Models. We evaluate zoom consistency on two architecturally different VLMs: KV-Ground-8B vocaela [2025], a GUI grounding specialist fine-tuned from GUI-Owl-1.5 mPLUG [2026] (8B parameters, bf16, max_pixels = 99M), and Qwen3.5-27B Qwen Team [2026], a general-purpose VLM (AWQ-4bit via compressed_tensors). Both use 2-step zoom with $r = 0.5$ and greedy decoding. Hardware: NVIDIA H200 141GB.

Qwen accuracy note. Our Qwen3.5-27B achieves 60.9% on ScreenSpot-Pro. The official Qwen evaluation reports 70.3% for the full-precision model. The gap is likely attributable to 4-bit AWQ quantization and differences in prompting format. We use the quantized variant because full-precision 27B exceeds single-GPU memory alongside KV-Ground-8B.

4.2 Correlation with Prediction Correctness

Table 1: Zoom consistency as a confidence signal. AUC measures discriminative power for predicting correctness (lower c = more likely correct). Spearman ρ confirms significant negative correlation.

Model	AUC	Spearman ρ	p -value	n
KV-Ground-8B	0.600	−0.139	$< 10^{-6}$	1,581
KV-Ground-8B [†]	0.599	−0.123	4×10^{-5}	1,097
Qwen3.5-27B	0.588	−0.109	0.0003	1,097

The AUC exceeds 0.5 (random) for both models, confirming zoom consistency carries discriminative information about prediction correctness. The [†] row shows KV-Ground evaluated on the same 1,097-sample subset as Qwen for an apples-to-apples comparison; AUC and ρ remain similar, confirming the signal is not an artifact of sample selection. The correlation is stable under cross-validation: splitting the KV-Ground data into random halves yields $\rho = -0.118$ ($p = 9 \times 10^{-4}$) and $\rho = -0.161$ ($p = 5 \times 10^{-6}$). The Qwen sample count ($n = 1,097$) is smaller than the full benchmark because 484 samples produced unparseable coordinate outputs under AWQ-4bit quantization (88% failed at step-1). These are not random: they concentrate in CAD applications (69% failure rate) and correspond to harder samples where KV-Ground also struggles (69% accuracy vs. 85% on parseable samples). The Qwen correlation is therefore measured on an easier subset, and the true signal strength on the full distribution may be weaker.

The lowest-consistency bucket ($c < 30$) has 87.1% accuracy, 11.5 points above the highest bucket ($c \geq 250$, 75.6%). The relationship is not perfectly monotonic: the 150–250 bucket (79.8%) slightly exceeds the 80–150 bucket (76.4%), consistent with the moderate correlation strength.

Table 2: KV-Ground-8B accuracy by zoom consistency bucket.

Consistency c	n	Accuracy
< 30	464	87.1%
30–80	101	85.1%
80–150	106	76.4%
150–250	173	79.8%
≥ 250	737	75.6%

4.3 Consistency Distribution by Oracle Partition

To understand how zoom consistency relates to cross-model agreement, we partition the 1,581 samples by correctness: $\mathcal{S}_{11}$ (both correct), $\mathcal{S}_{10}$ (only KV correct), $\mathcal{S}_{01}$ (only Qwen correct), $\mathcal{S}_{00}$ (both wrong).

Table 3: Mean KV-Ground zoom consistency by oracle partition. $\mathcal{S}_{11}$ (both models correct) has substantially lower consistency than all other partitions.

Partition	n	Mean c	Median c
$\mathcal{S}_{11}$ (both correct)	883	197.1	144.0
$\mathcal{S}_{10}$ (only KV)	383	291.6	333.5
$\mathcal{S}_{01}$ (only Qwen)	79	294.1	301.0
$\mathcal{S}_{00}$ (both wrong)	236	289.9	324.0

The consistency signal cleanly separates $\mathcal{S}_{11}$ (mean $c = 197$) from all other partitions (mean $c \approx 290$). This 48% gap in mean consistency explains why the signal works: when both models agree and are correct, the specialist is confident. The challenge for routing is that $\mathcal{S}_{10}$, $\mathcal{S}_{01}$, and $\mathcal{S}_{00}$ have similar consistency distributions, making it hard to distinguish gains from losses within the disagreement set.

4.4 Signal Behavior Across Application Categories and Platforms

Table 4: Zoom consistency signal strength varies by application category. Qwen selection % shows how often the generalist has lower consistency than the specialist, reflecting domain familiarity.

Category	n	KV Acc.	Qwen lower c %
Office	230	90.0%	47.4%
Scientific	254	83.1%	36.2%
Dev	299	83.3%	35.1%
CAD	261	79.3%	13.4%
Creative	341	74.2%	38.1%
OS	196	70.9%	42.9%

The consistency signal reflects domain familiarity without any category labels. On CAD applications, where KV-Ground’s accuracy is highest, the specialist’s consistency is almost always lower (Qwen is preferred only 13.4% of the time). On consumer interfaces (Office, OS), the generalist’s consistency is competitive (42–47%), reflecting Qwen’s broader pretraining coverage.

The signal also holds across all three operating systems in the benchmark: Spearman $\rho = -0.115$ on macOS ($n = 604$), $\rho = -0.114$ on Windows ($n = 927$), and $\rho = -0.152$ on Linux ($n = 50$). The consistency gap between correct and incorrect predictions is present on every platform.

5 Application: Cross-Model Routing

As a proof-of-concept application, we use zoom consistency to route between KV-Ground-8B and Qwen3.5-72B. The router runs both models through their zoom pipelines and selects the prediction with lower consistency (closer to crop center).

```

1 def zoom_pipeline(model, image, instruction, r=0.5):
2     p1 = model(image, instruction)      # step 1: full image
3     crop = crop_and_resize(image, center=p1, ratio=r)
4     p2 = model(crop, instruction)      # step 2: zoomed crop
5     c = distance(p2, (500, 500))      # zoom consistency
6     final = remap(p2, crop_box)
7     return final, c
8
9 def route(image, instruction):
10    pred_A, c_A = zoom_pipeline(specialist, image, instruction)
11    pred_B, c_B = zoom_pipeline(generalist, image, instruction)
12    return pred_A if c_A <= c_B else pred_B

```

Figure 1: Listing: Zoom consistency routing. The consistency c (line 5) is extracted from the pipeline’s existing intermediate output. No additional forward passes are needed beyond the zoom pipelines themselves.

5.1 Oracle Decomposition

Table 5: Oracle decomposition on ScreenSpot-Pro (1,581 samples).

Partition	Samples	Fraction
Both correct ($\mathcal{S}_{11}$)	883	55.9%
Only KV correct ($\mathcal{S}_{10}$)	383	24.2%
Only Qwen correct ($\mathcal{S}_{01}$)	79	5.0%
Both wrong ($\mathcal{S}_{00}$)	236	14.9%
Oracle accuracy	1,345 / 1,581	85.1%

The oracle headroom is 79 samples (5.0%): cases where only the generalist is correct. Any routing strategy can access at most this headroom.

5.2 Routing Condition

Theorem 1 (Routing Improvement Condition). *A consistency-based router that selects $\arg \min_i c_i$ improves over the stronger model M_A alone if and only if:*

$$\underbrace{f_{01} \cdot n_{01}}_{\text{gains}} > \underbrace{(1 - f_{10}) \cdot n_{10}}_{\text{losses}} \quad (3)$$

where $f_{10} = P(\text{router picks } A \mid \mathcal{S}_{10})$ and $f_{01} = P(\text{router picks } B \mid \mathcal{S}_{01})$. Equivalently, the router’s precision in selecting B on the disagreement set $\mathcal{D} = \mathcal{S}_{10} \cup \mathcal{S}_{01}$ must exceed $1/2$.

Proof. The router’s accuracy is $a_{\pi} = (n_{11} + f_{10}n_{10} + f_{01}n_{01})/N$. The condition $a_{\pi} > a_A = (n_{11} + n_{10})/N$ reduces to $f_{01}n_{01} > (1 - f_{10})n_{10}$. $\square$

Corollary 1. *The base rate of $\mathcal{S}_{01}$ in $\mathcal{D}$ is $\pi = n_{01}/(n_{10} + n_{01})$. With $n_{10} = 383$ and $n_{01} = 79$, $\pi = 0.171$. The router must achieve a precision lift of at least $2.9\times$ the base rate.*

5.3 Routing Results

The consistency router captures 13 of 79 recoverable samples ($\eta = 16.5\%$), with 48 gains and 35 losses (net +13). Bootstrap resampling gives $P(\text{improvement} > 0) = 92.3\%$ over 10,000 resamples. McNemar’s test yields $p = 0.19$, reflecting the small absolute gain. The result is directionally consistent but does not reach conventional significance at $\alpha = 0.05$, consistent with the moderate correlation strength ($|\rho| \approx 0.13$) and the highly asymmetric disagreement set ($n_{10}/n_{01} = 4.8$).

The per-application breakdown shows the router adapts without category labels:

Table 6: Routing strategies on ScreenSpot-Pro. Only the consistency router exceeds the KV baseline.

Method	Accuracy	vs. KV	Oracle η
Consistency Router	80.9%	+0.8%	16.5%
KV-Ground-8B	80.1%	—	0%
Stage split KV $\rightarrow$ Qwen	78.7%	−1.3%	< 0
Vote agree ($d < 50$)	76.9%	−3.2%	< 0
Midpoint fusion	75.7%	−4.4%	< 0
Qwen3.5-27B only	60.9%	−19.2%	< 0
Oracle	85.1%	+5.0%	100%

Table 7: Applications with largest router effects.

Application	n	KV	Router	Δ
photoshop	51	76.5%	84.3%	+7.8%
macos.common	65	75.4%	80.0%	+4.6%
illustrator	31	83.9%	87.1%	+3.2%
blender	71	76.1%	78.9%	+2.8%
vivado	80	77.5%	76.2%	−1.3%
quartus	45	88.9%	86.7%	−2.2%
vscode	55	85.5%	81.8%	−3.6%
davinci	44	79.5%	75.0%	−4.5%

6 Discussion

6.1 Other Potential Applications

Zoom consistency is a general confidence signal. Beyond routing, it could enable:

Multi-step pipelines. In pipelines with 3+ zoom steps, zoom consistency from step k could decide whether step $k+1$ is worth the additional cost, enabling early stopping when the model is already confident.

Confidence-aware agents. GUI agents that execute multi-step workflows could use zoom consistency to flag uncertain click predictions before committing to irreversible actions, enabling human-in-the-loop confirmation on low-confidence steps.

Quality monitoring. The average zoom consistency across a batch of predictions provides a cheap, model-agnostic indicator of prediction reliability. A spike in mean c over time could signal distribution shift (e.g., a new application version with different UI layouts).

Active learning. High-consistency (low-confidence) samples are natural candidates for human annotation, potentially more informative than random sampling for improving model accuracy.

6.2 Bottlenecks in the Routing Application

The 16.5% oracle extraction rate is limited by three factors:

Weak generalist. Qwen3.5-27B (AWQ-4bit) achieves 60.9%, contributing only 79 unique wins. A generalist at 75% would increase the oracle headroom and make the minority class ($\mathcal{S}_{01}$) easier to detect.

Asymmetric risk. Losses ($\mathcal{S}_{10}$, 383 samples) outnumber gains ($\mathcal{S}_{01}$, 79 samples) by $4.8\times$. The router must be highly selective when choosing the generalist, requiring $2.9\times$ precision lift over the base rate.

Moderate correlation. $|\rho| \approx 0.13$ means zoom consistency is a noisy discriminator. The signal is strong enough to exceed the precision threshold ($57.8\% > 50\%$), but not by a wide margin.

7 Limitations

1. The signal is validated on one benchmark (ScreenSpot-Pro) with one model pair. Cross-benchmark and cross-pair generalization remains to be tested.

2. The routing application doubles inference cost (4 forward passes vs. 2) and yields a statistically modest improvement (+0.8%, McNemar $p = 0.19$).
3. The correlation between zoom consistency and correctness is moderate ($|\rho| \approx 0.13$). The signal is informative but not sufficient on its own for high-precision decisions.
4. The linear error estimator (Proposition 1) assumes the target is within the crop and step-2 is accurate. Both assumptions weaken for high step-1 error.

8 Conclusion

We identified and formalized *zoom consistency* as a free confidence signal embedded in multi-step GUI grounding pipelines. The signal is a linear estimator of step-1 spatial error (Proposition 1), correlates significantly with prediction correctness ($p < 10^{-6}$), and is comparable across models without calibration (Proposition 2). As a proof-of-concept, consistency-based routing between KV-Ground-8B and Qwen3.5-72B captures 16.5% of the oracle headroom on ScreenSpot-Pro. The modest extraction rate reflects the moderate signal strength and the asymmetric disagreement set, both quantified by our routing theorem (Theorem 1). The signal is simple, requires no training or extra computation, and may be useful beyond routing for confidence estimation, quality monitoring, and selective computation in other iterative refinement pipelines, though cross-benchmark validation remains future work.

References

- Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. SeeClick: Harnessing gui grounding for advanced visual gui agents. In *ACL*, 2024.
- Yong Du, Yuchen Yan, Fei Tang, Zhengxi Lu, Chang Zong, Weiming Lu, Shengpei Jiang, and Yongliang Shen. Test-time reinforcement learning for gui grounding via region consistency. *arXiv preprint arXiv:2508.05615*, 2025.
- Boyu Gou, Ruohan Wang, Boyuan Zheng, Yanan Xie, Cheng Chang, Yiheng Shu, Huan Sun, and Yu Su. Navigating the digital world as humans do: Universal visual grounding for gui agents. In *ICLR*, 2025.
- Zhiyuan Jiang, Shenghao Xie, Wenyi Li, Wenqiang Zu, Peihang Li, Jiahao Qiu, Siqi Pei, Lei Ma, Tiejun Huang, Mengdi Wang, and Shilong Liu. Zoom in, click out: Unlocking and evaluating the potential of zooming for gui grounding. *arXiv preprint arXiv:2512.05941*, 2025.
- Sanghan Kim, Rui Xiao, Stephan Alaniz, Yongqin Xian, and Zeynep Akata. Training-free uncertainty guidance for complex visual tasks with mllms. *arXiv preprint arXiv:2510.00705*, 2025.
- SeokJoo Kwak, Jihoon Kim, Boyoun Kim, Jung Jae Yoon, Wooseok Jang, Jeonghoon Hong, Jaeho Yang, and Yeong-Dae Kwon. Mega-gui: Multi-stage enhanced grounding agents for gui elements. *arXiv preprint arXiv:2511.13087*, 2025.
- Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. Screenspot-pro: Gui grounding for professional high-resolution computer use. *arXiv preprint arXiv:2504.07981*, 2025a.
- Kaixin Li et al. Screenspot-pro-gui-grounding: Official evaluation repository. <https://github.com/likaixin2000/ScreenSpot-Pro-GUI-Grounding>, 2025b.
- Xunzhuo Liu, Bowei He, Xue Liu, Andy Luo, Haichen Zhang, and Huamin Chen. Adaptive vision-language model routing for computer use agents. *arXiv preprint arXiv:2603.12823*, 2026.
- Tiange Luo, Lajanugen Logeswaran, Justin Johnson, and Honglak Lee. Visual test-time scaling for gui agent grounding. In *ICCV*, 2025.
- mPLUG. Gui-owl-1.5-8b-instruct. <https://huggingface.co/mPLUG/GUI-Owl-1.5-8B-Instruct>, 2026. Fine-tuned from Qwen2.5-VL-7B-Instruct for GUI grounding.
- Siqi Pei, Liang Tang, Tiaonan Duan, Long Chen, Shuxian Li, Kaer Huang, Yanzhe Jing, Yiqiang Yan, Bo Zhang, Chenghao Jiang, Borui Zhang, and Jiwen Lu. Adazoom-gui: Adaptive zoom-based gui grounding with instruction refinement. *arXiv preprint arXiv:2603.17441*, 2026.
- Yujia Qin, Yining Ye, Junjie Fang, Haoming Wang, Shihao Liang, Shizuo Tian, Junda Zhang, Jiahao Li, Yunxin Li, Shijue Huang, et al. Ui-tars: Pioneering automated gui interaction with native agents. *arXiv preprint arXiv:2501.12326*, 2025.
- Qwen Team. Qwen3.5: Towards native multimodal agents. <https://qwen.ai/blog?id=qwen3.5>, 2026.

- vocacla. Kv-ground-8b-baseguiowl1.5-0315. <https://huggingface.co/vocacla/KV-Ground-8B-BaseGui0wl1.5-0315>, 2025.
- Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2023.
- Qianhui Wu, Kanzhi Cheng, Rui Yang, Chaoyun Zhang, Jianwei Yang, Huiqiang Jiang, Jian Mu, Baolin Peng, Bo Qiao, Reuben Tan, Si Qin, Lars Liden, Qingwei Lin, Huan Zhang, Tong Zhang, Jianbing Zhang, Dongmei Zhang, and Jianfeng Gao. Gui-actor: Coordinate-free visual grounding for gui agents. *arXiv preprint arXiv:2506.03143*, 2025.
- Zhiyong Wu, Zhenyu Wu, Fangzhi Xu, Yian Wang, Qiushi Sun, Chengyou Jia, Kanzhi Cheng, Zichen Ding, Liheng Chen, Paul Pu Liang, and Yu Qiao. Os-atlas: A foundation action model for generalist gui agents. *arXiv preprint arXiv:2410.23218*, 2024.
- Xinbin Yuan, Jian Zhang, Kaixin Li, Zhuoxuan Cai, Lujian Yao, Jie Chen, Enguang Wang, Qibin Hou, Jinwei Chen, Peng-Tao Jiang, and Bo Li. Enhancing visual grounding for gui agents via self-evolutionary reinforcement learning. *arXiv preprint arXiv:2505.12370*, 2025.
- Xintong Zhang, Zhi Gao, Bofei Zhang, Pengxiang Li, Xiaowen Zhang, Yang Liu, Tao Yuan, Yuwei Wu, Yunde Jia, Song-Chun Zhu, and Qing Li. Adaptive chain-of-focus reasoning via dynamic visual search and zooming for efficient vlms. *arXiv preprint arXiv:2505.15436*, 2025.