

A student's guide to the dirac16complex numerical solutions

Installing, deriving, running and checking the five CVODE experiments of Stage 3 on
Windows, macOS and Linux

dirac16complex project (with Claude Opus 5.5)

September 2026

Contents

1	What you will compute and why	5
1.1	The question	5
1.2	The five experiments	6
1.3	What you will have at the end	7
2	How to use this guide	7
2.1	Conventions	7
2.2	Terminals	7
2.3	How this guide was tested	8
3	Installing the tools	9
3.1	What you need	9
3.2	Windows 11	10
3.3	macOS	10
3.4	Linux (Ubuntu or Debian)	11
3.5	The Python packages	11
3.6	Checking the installation	12
4	Getting the code and the solver engine	13
4.1	Choose a short folder	13
4.2	Clone the repository	13
4.3	Fetch the solver engine	13

4.4	Checking the engine	15
4.5	The three engines are not identical	15
4.6	A map of the repository	16
5	Building and testing the program	16
5.1	Build	16
5.2	The FMA note	17
5.3	Test	17
6	The mathematics you need, from zero	18
6.1	Numbers, columns and matrices	18
6.2	The field: a column of 16 complex numbers	18
6.3	Spacetime and the gamma matrices	18
6.4	Three more matrices: C, B and the chirality	20
6.5	Metric, scale factors and the vielbein	20
6.6	The covariant derivative	21
6.7	The Lagrangian and the field equation	21
6.8	From the field equation to a mode equation	22
6.9	Complex to real: the layout that CVODE sees	22
6.10	Energy, pressure, norms and the expectation-value rule	23
6.11	EXP-1: the primordial field	24
6.12	EXP-2: an 8D universe that feels the condensate	25
6.13	EXP-3: the condensate as dark energy	26
6.14	EXP-4: the quanta as dark matter	27
6.15	EXP-5: momentum along an extra time	28
6.16	How CVODE solves $u' = f(t, u)$	28
7	Running the experiments	29
7.1	The command line of the program	29
7.2	A first run into a scratch folder	30
7.3	All five experiments	31
7.4	Reproducing the committed files byte for byte	32

8	Reading the output files	32
8.1	The file format	32
8.2	EXP-1 (folder <code>exp1</code> , 29 files)	32
8.3	EXP-2 (folder <code>exp2</code> , 4 files)	33
8.4	EXP-3 (folder <code>exp3</code> , 10 run files and the analysis)	34
8.5	EXP-4 (folder <code>exp4</code> , 13 files)	35
8.6	EXP-5 (folder <code>exp5</code> , 5 files)	36
9	Checking the results with the Python checkers	37
9.1	What the checkers do	37
9.2	Checking the committed folder (the full form)	37
9.3	Checking a scratch folder (the quick form)	38
10	The Jupyter notebook	38
10.1	What it is	38
10.2	Running it headless	39
10.3	Running it interactively	40
11	The Mathematica notebook (optional)	40
12	Rebuilding the PDF documents (optional)	43
13	Changing parameters: exercises with answers	43
13.1	Tolerances decide whether the checks pass	43
13.2	Convergence	44
13.3	Predicting EXP-1 from the formulas	44
13.4	Solving the EXP-2 constraint yourself	45
13.5	From x_0 to (w_0, w_a)	45
13.6	Moving the EXP-5 turning point	47
13.7	Massless quanta are not created	48
14	Troubleshooting	48
15	Glossary	50

Abstract

This guide takes a student who has never used Rust, CVODE or this repository from an empty computer to a complete and checked reproduction of every numerical solution of Stage 3 of the `dirac16complex` project. Stage 3 consists of five experiments, EXP-1 to EXP-5. Each one integrates the field equation of `dirac16complex`, a 16-component complex Grassmann spinor field in eight dimensions with four space-like and four time-like directions, in a homogeneous background, with the CVODE solver of the pure-Rust SUNDIALS 7.8.0 port of the `rustSolveIt` engine. The guide explains in plain language what is computed and why; how to install Git, Rust, Python with `numpy`, `matplotlib`, `sympy`, `nbformat`, `nbclient` and `ipykernel`, and optionally Jupyter, the Wolfram Engine and a TeX distribution, on Windows 11 (PowerShell and Git Bash), macOS and Linux; how to fetch the code and the pinned solver engine and how to check them; how to build and test the program; the mathematics from zero, including a step-by-step derivation of each experiment's first-order system $u' = f(t, u)$ with its state vector index by index, its right-hand side and its initial data; how CVODE solves such a system; how to run each experiment, read every column of its output and check it with the independent Python checkers (162 checks), the EXP-3 analysis (10 checks), the Jupyter notebook (71 checks) and the Mathematica notebook (49 checks); how to rebuild the PDF documents; exercises with answers; troubleshooting; and a glossary. Every command in this guide was executed while it was written, from fresh clones, on Windows 11 in PowerShell 7 and in Git Bash and on Ubuntu 24.04 under WSL2. Installers, which change the computer, were not executed, and nothing was tested on macOS; Section 2.3 lists exactly what was run where. Three measured facts matter for reproduction: the three platform engines are not byte-identical; the committed results were produced with the Windows 11 engine, which also builds and reproduces every Rust output byte for byte on Linux; and the last digits of the files that Python writes (the EXP-3 analysis, the checker reports) depend on the `numpy` version and platform, which is why the tested versions are pinned in `requirements-stage3.txt` (with them these files, too, were reproduced byte for byte on Windows 11, while on Ubuntu their last digits still differ).

1 What you will compute and why

1.1 The question

Astronomers infer that most of the energy in the universe is in two forms that are not ordinary matter. **Dark matter** clusters like matter and has almost no pressure. **Dark energy** has a negative pressure and makes the expansion of the universe accelerate. A fluid is described by its energy density ρ and its pressure p , and the single number that tells the two kinds of behaviour apart is the **equation of state parameter**

$$w = \frac{p}{\rho}.$$

Radiation has $w = 1/3$, matter (dust) and dark matter have $w = 0$, and a cosmological constant has $w = -1$. The input document of this study (an e-mail on the Unite supernova compilation, kept by the author and not part of the repository) quotes the Chevallier-Polarski-Linder (CPL) form $w(a) = w_0 + w_a(1 - a)$, where a is the scale factor of the universe ($a = 1$ today), with the Unite values $w_0 = -0.861$ and $w_a = -0.60$, and a constant- w fit $w = -0.764$ about two standard deviations from -1 .

Stage 3 asks: **can the `dirac16complex` field behave like dark matter or like dark energy?**

It answers the question with numbers, not words: it solves the field equation numerically in five backgrounds and measures ρ , p and w and how they change.

A caution about the CPL form that the input document gets wrong: its table labels thawing fields “($w_a > 0$)” and freezing fields “($w_a < 0$)”, but its own formula gives $dw/da = -w_a$. A thawing field, whose w rises from -1 as the universe expands, therefore has $w_a < 0$, and a freezing field has $w_a > 0$. This guide always uses the signs that follow from the formula.

1.2 The five experiments

Experiment	Background	What CVOID integrates	Question
EXP-1	the primordial (pair-creation) field of the author’s notebook	one 16-component mode: 32 real ODEs, 26 runs	what do ρ , p and w do in that field, and what source would 8D Einstein gravity need?
EXP-2	homogeneous 8D universe solved together with 8D Einstein gravity	6 geometry ODEs and 32 spinor ODEs, 3 runs	does a self-gravitating condensate isotropise, and what w does a 3-space observer infer?
EXP-3	4D late universe with frozen extra dimensions	time, distance, spinor and $\ln \sigma$: 35 ODEs, 10 runs	can the condensate reproduce the Unite dark energy (w_0, w_a)?
EXP-4	expanding 3-space: radiation era, and de Sitter followed by radiation	32 ODEs per momentum mode, hundreds of modes	do the quanta behave like dark matter, and how many does the expansion create?
EXP-5	deflating extra times	32 ODEs, 4 runs	why must the physics be restricted to modes without momentum along the extra times?

What the committed results say, in one paragraph (the scientific document of Stage 3, DIRAC16COMPLEX_DARK_SECTOR_NUMERICS, discusses them fully): a thermal gas of the free quanta goes from radiation-like, $w = 0.3329$ at $a = 1$, to dust-like, $w = 0.0359$ at $a = 100$ (on the program’s momentum grid; 0.0361 without its cut), and expansion creates such quanta for $m > 0$ but not for $m = 0$. That is necessary for dark matter, not sufficient. As dark energy the condensate can be tuned to $w_0 = -0.861$ today, but then its tangent slope is $w_a = -4.81$, about eight times faster than Unite. Going back in time its effective mass vanishes at redshift $z = 0.026$; beyond that the one-mode approximation of the condensate is no longer valid, and its equations, followed further, give a phantom epoch, negative energy and a model universe that bounces at redshift $z = 0.388$. You will reproduce these numbers yourself in Sections 7 to 9.

1.3 What you will have at the end

1. A built program (Section 5.1) that runs the five experiments and checks itself with 69 self-checks.
2. The output files of every experiment, byte for byte identical to the committed ones under `artifacts/dirac16complex/numerics/`.
3. Independent confirmation by five Python checkers that recompute the physics from the raw spinor columns (162 checks), by the EXP-3 analysis (10 checks), by the Jupyter notebook (71 checks and 17 figures) and, optionally, by the Mathematica notebook (49 checks).
4. The understanding to change a parameter, predict the result and check the prediction.

2 How to use this guide

2.1 Conventions

- **Everything is counted from 0.** Coordinates are $x_0, \dots, x_7$, spinor components are $u_0, \dots, u_{15}$, and the first entry of a list is entry 0.
- A box like the ones below contains commands. Type or paste them one line at a time into a terminal and press Enter after each line. The prompt that your terminal prints before the cursor is not shown.
- The sentence before each box says which terminal it is for. **PowerShell** means PowerShell 7 on Windows. **Git Bash** means the bash that comes with Git for Windows. **macOS** and **Linux** mean the Terminal application with bash or zsh. Commands marked “Git Bash, macOS and Linux” are the same in all three.
- **Repository root** means the folder `Dirac_claude` that `git clone` creates; it contains `README.md`, `scripts`, `studies` and `notebooks`. Unless a box starts with a `cd` command, run it from the repository root.
- PowerShell accepts forward slashes in file arguments, so most commands look the same in both shells. Where they differ, both forms are given.
- “Expected output” shows what the command prints when everything works. Numbers of steps and check counts must match exactly; run times depend on your computer.

2.2 Terminals

- **Windows, PowerShell 7:** Start menu, type `pwsh`, press Enter. If `pwsh` is not found, install PowerShell 7 (Section 3.2) or use Windows PowerShell 5.1, called `powershell`, which is part of Windows.
- **Windows, Git Bash:** Start menu, type `Git Bash`, press Enter (installed with Git for Windows).
- **macOS:** Applications, Utilities, Terminal.

- **Linux:** your distribution's terminal (often Ctrl+Alt+T).

To change folder use `cd FOLDER`; `cd ..` goes up one level; `pwd` prints where you are; `ls` lists the folder (these four work in all shells named above).

2.3 How this guide was tested

For this edition every command box of the guide was executed by replay scripts that copy the boxes verbatim, in the order of the guide, into a new terminal session and run them in a fresh clone of the public repository (Section 4.2). The steps that the text gives in words were inserted where the text gives them: editing and restoring a source file in Section 13; the commands quoted inside sentences, such as `$LASTEXITCODE`, `git restore artifacts` and `python -m pip install -r requirements-stage3.txt`; the messages of the setup script (a second run, a different engine, a simulated interrupted download); and the remedies of Section 14. The PowerShell replay cloned commit b3e2493, the Git Bash replay commit df6b57f and the Linux replay commit e1904bb; the three contain the same Stage-3 program, checkers, notebooks and outputs. Earlier editions of this guide were tested in the same way at the commits fbec4d7 and 34b9fd4.

Platform	Shells and tools	What was executed
Windows 11 Pro for Workstations 10.0.26200, Intel Core Ultra 9 275HX, 24 cores	PowerShell 7.6.6; Git Bash (GNU bash 5.2.37, Git 2.51.2); rustc and cargo 1.91.1, rustup 1.28.2; Python 3.14.5 with numpy 2.4.6, matplotlib 3.11.0, sympy 1.14.0, nbformat 5.10.4, nbclient 0.10.2, ipykernel 7.1.0, jupyterlab 4.4.10, nbconvert 7.16.6; MiKTeX 26.5 (pdfTeX 4.27); WolframScript 1.14.0 with Wolfram 15.0.1	every command of Sections 3.2 to 14 except the installers, in both shells where both forms are given; the interactive route of Section 10.3 in a browser; the <code>linux</code> engine of Section 4.5
Ubuntu 24.04.4 LTS under WSL2 on the same computer	bash 5.2.21; Git 2.43.0; rustc and cargo 1.93.1; Python 3.12.3 in a virtual environment with the pinned packages of Section 3.5 and jupyterlab 4.6.4 with nbconvert 7.17.1; TeX Live 2023 (pdfTeX 1.40.25)	every bash command of Sections 3.4 to 14 except the installers and Section 11 (there is no WolframScript there); the <code>linux</code> engine of Section 4.5
macOS	none	nothing; the macOS commands follow the official instructions of each tool but are untested

Not executed anywhere, because they install software or change system settings: `winget install`, `xcode-select` (macOS), the rustup installer, `apt install`, the MiKTeX, MacTeX and Wolfram installers, and `wolframscript -activate`. On Windows the package identifiers were confirmed with `winget show`, and on Ubuntu the package names with the simulation `apt-get -s install`.

Three effects of the test set-up, not of the guide, should be known. Each replay used a home folder of its own, so that the folder `src` of Section 4.1 lay inside the test area; in PowerShell this was done by pointing the variable `USERPROFILE` elsewhere, and there the Wolfram front end then drew text slightly differently: four of the eight PNG figures of Section 11 differed from the committed ones in a few dozen pixels. The Git Bash replay, and a repetition in a fresh clone with the normal user profile, reproduced all eight byte for byte. The Git Bash and Linux replays cloned a commit in which this guide’s Markdown had already been edited but its PDF not yet registered, so there the guide’s own PDF build of Section 12 ended with its registry checks false; in the PowerShell replay, at a registered commit, all 14 checks passed. Finally, the computer was running other long computations during the replays, which made some runs up to five times slower than the times quoted in this guide; those were measured on the otherwise idle computer.

3 Installing the tools

3.1 What you need

Tool	Needed for	Required?
Git	downloading the code and the solver engine; comparing results	yes
Rust (rustup, rustc, cargo)	building and running the five experiments	yes
a C linker (MSVC Build Tools on Windows, Xcode Command Line Tools on macOS, build-essential on Linux)	Rust uses it to link the program	yes
Python 3.10 or newer	the checkers, the analysis, the notebook, the PDF builder	yes
numpy, matplotlib, sympy, nbformat, nbclient, ipykernel	the checkers and the notebook	yes
JupyterLab (brings nbconvert)	opening the notebook interactively and the nbconvert route	optional
Wolfram Engine or Mathematica (wolframscript)	the Mathematica cross-check notebook	optional
a TeX distribution (MiKTeX, MacTeX or TeX Live)	rebuilding the PDF documents	optional

Section 3.6 shows how to check each of them.

A computer from the last ten years is enough. The program needs only a few megabytes of memory (EXP-4, the largest run, peaked at 14 MB), and the code, the engine, the build and the scratch runs of this guide take about 250 MB of disk.

3.2 Windows 11

The tool `winget` (App Installer) is part of Windows 11. Open PowerShell. **First** install the Microsoft C++ build tools (the linker `link.exe` and the Windows SDK), which Rust on Windows needs; this step is required (the first use of `winget` may ask you to accept its source agreements, and the installer opens a progress window):

```
$id = "Microsoft.VisualStudio.2022.BuildTools"
$vs = "--wait --passive --add Microsoft.VisualStudio.Workload.VCTools"
winget install --id $id -e --override "$vs --includeRecommended"
```

Then install the other tools:

```
winget install --id Git.Git -e
winget install --id Microsoft.PowerShell -e
winget install --id Rustlang.Rustup -e
winget install --id Python.Python.3.13 -e
```

Why this order: when `winget` installs `rustup` it runs the `rustup` installer silently (`-y`), and in that mode `rustup` does not offer to install the build tools; it only warns that they are missing, and the first build then fails with `linker link.exe not found` (Section 14). This was read from the `winget` manifest and the `rustup` source, not observed on a fresh computer. If you prefer `rustup`'s own offer, install `rustup` interactively instead and accept its offer to install the Visual Studio build tools:

```
winget install --id Rustlang.Rustup -e -i
```

Optional tools:

```
winget install --id MiKTeX.MiKTeX -e
winget install --id WolframResearch.WolframEngine -e
```

After installing, **close every terminal and open a new one**, so that the new programs are found. Then make sure the stable Rust toolchain is the default (this is safe to repeat):

```
rustup default stable
```

The Wolfram Engine is free for non-commercial use but must be activated once with a Wolfram ID: run `wolframscript -activate` yourself and follow the prompts. MiKTeX installs missing LaTeX packages on first use; in MiKTeX Console you can allow it to do so without asking.

3.3 macOS

Open Terminal. Install the command line developer tools (they contain Git and the linker that Rust needs):

```
xcode-select --install
```

Install Rust with the official installer, accept the default installation, and load it into the current terminal:

```
curl --proto '=https' --tlsv1.2 -sSf https://sh.rustup.rs | sh
source "$HOME/.cargo/env"
```

Install Python 3 from <https://www.python.org/downloads/> (or with Homebrew, `brew install python`). Optional: MacTeX from <https://www.tug.org/mactex/> for the PDFs, and the Wolfram Engine from <https://www.wolfram.com/engine/> for the Mathematica notebook. The Python packages are installed in Section 3.5.

The repository's `.cargo/config.toml` asks the compiler for the x86-64 instruction FMA (Section 5.2). On Apple Silicon (arm64) fused multiply-add is part of the base instruction set. This combination was not tested; if the compiler prints a warning about the target feature `fma`, it is a warning, not an error.

3.4 Linux (Ubuntu or Debian)

Open a terminal and install Git, the compiler tools and Python with its virtual-environment module (you need administrator rights for `sudo`):

```
sudo apt update
sudo apt install -y git curl build-essential python3 python3-venv python3-pip
```

Install Rust exactly as on macOS:

```
curl --proto '=https' --tlsv1.2 -sSf https://sh.rustup.rs | sh
source "$HOME/.cargo/env"
```

Optional, for the PDFs:

```
sudo apt install -y texlive-latex-base texlive-latex-recommended lmodern
```

Other distributions have the same tools under similar package names. The Wolfram Engine for Linux is at <https://www.wolfram.com/engine/>.

3.5 The Python packages

The committed files were produced with these versions, and the byte-for-byte comparisons of this guide assume them: numpy 2.4.6, matplotlib 3.11.0, sympy 1.14.0, nbformat 5.10.4, nbclient 0.10.2 and ipykernel 7.1.0. The same list is in the file `requirements-stage3.txt` of the repository (after Section 4.2 you can also write `python -m pip install -r requirements-stage3.txt`).

Windows (PowerShell or Git Bash). Install the packages for your user:

```
python -m pip install numpy==2.4.6 matplotlib==3.11.0 sympy==1.14.0
python -m pip install nbformat==5.10.4 nbclient==0.10.2 ipykernel==7.1.0
python -m pip install jupyterlab
```

The third line is optional (interactive notebook and nbconvert). On a computer that already has the packages, pip prints **Requirement already satisfied** for each of them and changes nothing. If pip warns that a script such as `jupyter.exe` is installed in a folder that is not on PATH, this guide avoids the problem by always writing `python -m ...` (Section 14).

macOS and Linux. Recent systems refuse `pip install` outside a virtual environment (Ubuntu 24.04 prints **error: externally-managed-environment**). Create one virtual environment for this project, outside the repository, and activate it:

```
python3 -m venv ~/.venvs/dirac16
source ~/.venvs/dirac16/bin/activate
python -m pip install numpy==2.4.6 matplotlib==3.11.0 sympy==1.14.0
python -m pip install nbformat==5.10.4 nbclient==0.10.2 ipykernel==7.1.0
```

Optional: `python -m pip install jupyterlab`. If pip cannot install one of the pinned versions for your Python (the pins were installed and tested with Python 3.14.5 on Windows and Python 3.12.3 on Ubuntu 24.04), install the packages without the `==` versions, for example `python -m pip install numpy matplotlib sympy nbformat nbclient ipykernel`. Every check of this guide still passes then, but the last digits of the EXP-3 analysis files and of the checker reports can differ from the committed ones, and with a different matplotlib build the figure bytes can differ too (Sections 9.2, 10.2 and 14). The activation lasts until you close the terminal: **in every new terminal run** `source ~/.venvs/dirac16/bin/activate` again. While it is active, `python` means the Python of the environment, which is why the rest of this guide writes `python` on every platform.

3.6 Checking the installation

In any of the shells:

```
git --version
rustc --version
cargo --version
rustup show active-toolchain
python --version
python -c "import numpy, matplotlib, sympy, nbformat, nbclient, ipykernel; print('OK')"
```

Expected output (your version numbers may be newer):

```
git version 2.51.2.windows.1
rustc 1.91.1 (ed61e7d7e 2025-11-07)
cargo 1.91.1 (ea2d97820 2025-10-10)
stable-x86_64-pc-windows-msvc (default)
Python 3.14.5
OK
```

On Linux the toolchain line is `stable-x86_64-unknown-linux-gnu` (default). Optional tools (a tool that is not installed answers with a `command-not-found` message, which only means that the optional step cannot be done):

```
python -m jupyterlab --version
pdflatex --version
wolframscript -version
```

4 Getting the code and the solver engine

4.1 Choose a short folder

On Windows the linker cannot open files whose full path is longer than 260 characters, and the build creates paths about 105 characters below the repository root. Clone into a short folder such as `C:\Users\NAME\src`, not deep inside another folder (a clone at a 277-character path failed with `LNK1104: cannot open file while this guide was tested`). Also avoid folders synchronised by OneDrive or Dropbox, which lock files during the build.

PowerShell:

```
New-Item -ItemType Directory -Force -Path $HOME\src
cd $HOME\src
```

Git Bash, macOS and Linux:

```
mkdir -p ~/src
cd ~/src
```

4.2 Clone the repository

In any shell:

```
git clone https://github.com/once-ere/Dirac_claude.git
cd Dirac_claude
git log -1 --format="%h %s"
```

The last command prints the newest commit. From now on every command runs in this folder, the repository root, unless it says otherwise.

4.3 Fetch the solver engine

The numerical engine is not stored in this repository. A setup script downloads it at a pinned commit into the folder `vendor/rustSolveIt`, which Git ignores. The engine is a pure-Rust translation of SUNDIALS 7.8.0 (the solver library of Lawrence Livermore National Laboratory), published in three platform repositories:

Argument	Repository	Pinned commit
win11	https://github.com/once- ere/rustSolveIt_ Win11_SUNDIALS_7_8_0	a8fdff459adfe181 573d7924b18bffbdf378fdb3
macos	https://github.com/once- ere/rustSolveIt_ macos-silicon_SU NDIALS_7_8_0	5360157f4f616097 8f66400566c31b2a e25dd44d
linux	https://github.com/once- ere/rustSolveIt_ linux_SUNDIALS_7_8_0	6f58e02e53717a51 375bd4bc5918edc5 7088d922

The script fetches only one of them: the one named by its argument. It makes a shallow (one-commit), sparse checkout of the two folders the study needs, `sundials_rs` (the engine) and `planet_Mercury/notebook` (the notebook templates that the Jupyter notebook was adapted from), about 90 MB. Use the argument **win11 on every platform** if you want to reproduce the committed results byte for byte; Section 4.5 explains why.

PowerShell:

```
pwsh -NoProfile -File scripts/setup_solver.ps1 -Platform win11
```

If you only have Windows PowerShell 5.1, which blocks scripts by default, allow this one script for this one run:

```
powershell -ExecutionPolicy Bypass -File scripts/setup_solver.ps1 -Platform win11
```

Git Bash, macOS and Linux:

```
bash scripts/setup_solver.sh win11
```

Without an argument, `setup_solver.sh` chooses the platform's own engine (win11 in Git Bash, macos on macOS, linux on Linux), and `setup_solver.ps1` defaults to win11.

Expected output:

```
solver_platform=win11
solver_commit=a8fdff459adfe181573d7924b18bffbdf378fdb3
solver_setup=OK
```

It takes a few seconds. Running it again prints `solver_setup=ALREADY-PRESENT`. If the folder holds a different engine, the script stops with `vendor/rustSolveIt` is at ..., expected ...; remove it and rerun. If an earlier run was interrupted (for example by a network failure during the download), the folder is an incomplete checkout, and the script stops with a one-line message that says so and asks you to remove the folder and rerun (the exact text is in Section 14). In both cases delete the folder as shown in Section 4.4 and run the script again. (The PowerShell script prints these messages as a red error block and writes the folder as `vendor\rustSolveIt`.)

4.4 Checking the engine

In any shell:

```
git -C vendor/rustSolveIt rev-parse HEAD
git -C vendor/rustSolveIt sparse-checkout list
```

The first line must print the pinned commit of the table above; the second prints `planet_Mercury/notebook` and `sundials_rs`. The two crates that the study compiles are `vendor/rustSolveIt/sundials_rs/crates/sundials_core` (vectors, matrices, the deterministic mathematical functions) and `vendor/rustSolveIt/sundials_rs/crates/cvode_rs` (the CVODE integrator).

To switch to another engine, delete the folder and run the setup script again. PowerShell:

```
Remove-Item -Recurse -Force vendor/rustSolveIt
```

Git Bash, macOS and Linux:

```
rm -rf vendor/rustSolveIt
```

After a switch, rebuild the program (Section 5).

4.5 The three engines are not identical

An earlier version of the comment at the top of `scripts/setup_solver.sh` said that all three repositories vendor a byte-identical `sundials_rs`. They do not; this was measured while this guide was written, and the comment now says so. The macOS and Linux engines are identical to each other (their `sundials_rs` folders have the same Git tree, 47d654d5). The Windows 11 engine is different (tree eeaa0cad): its deterministic mathematical library `sundials_libm` is a translation of GNU C Library 2.39, while the other two use different implementations, so some elementary functions can return results that differ in the last bit. The consequences, measured:

1. With the `win11` engine the program reproduces every committed output file byte for byte, on Windows 11 and on Ubuntu 24.04 alike.
2. With the `linux` engine (the default of `setup_solver.sh` on Linux) all 69 self-checks and all 162 checker checks still pass, but 14 committed files differ in their last digits: the ten EXP-1 files with $K = 0$ (backgrounds and $K = 0$ runs) and the three EXP-2 CSV files with their `summary.json`. The same engine gives the same 14 differences on Windows, so they come from the engine, not from the operating system.
3. The Jupyter notebook asserts that the fresh program outputs are byte-identical to the files in `artifacts/dirac16complex/numerics/`, so with the `linux` or `macos` engine its gauntlet stops with `AssertionError('fresh_program_outputs_byte_identical')`. (It passes only if an earlier run of `all` with the same engine has overwritten those files; `git restore artifacts` puts the committed ones back.)

The `macos` engine was not run. Because it equals the `linux` engine, it can be expected to behave like it.

4.6 A map of the repository

Folder or file	Contents
<code>studies/dirac16complex_cosmology/</code>	the Rust program: <code>src/exp1.rs</code> to <code>src/exp5.rs</code> (one experiment each), <code>src/spinor.rs</code> (16 by 16 complex algebra), <code>src/driver.rs</code> (the CVODE driver), <code>src/generated.rs</code> (the gamma matrices), <code>src/main.rs</code> (the command line)
<code>scripts/</code>	the setup scripts, the five checkers <code>check_dirac16complex_exp1.py</code> to <code>check_dirac16complex_exp5.py</code> , the EXP-3 analysis <code>analyze_dirac16complex_exp3.py</code> , the PDF builder, the Wolfram scripts
<code>artifacts/dirac16complex/numerics/</code>	the committed outputs: <code>exp1/</code> to <code>exp5/</code> , <code>figures/</code> , <code>numerics-summary.json</code> , <code>notebook-report.json</code> , <code>mathematica-report.json</code>
<code>artifacts/dirac16complex/arbitrary-field/algebra-fixture.json</code>	the exact integer gamma matrices, the source of <code>src/generated.rs</code> and of every checker
<code>notebooks/</code>	the Jupyter notebook <code>dirac16complex_dark_sector.ipynb</code> and its tools, the Mathematica notebook <code>Dirac16ComplexDarkSector.nb</code>
<code>provenance/</code>	the documents in Markdown, LaTeX and PDF, and the registry <code>pdf-specifications.json</code>
<code>wolfram/</code>	the exact Wolfram Language packages of Stages 1 and 2
<code>tests/</code> <code>build/</code> , <code>vendor/</code> , <code>target/</code>	unittest suites of the documents and tools scratch, the engine and the compiler output; all ignored by Git

5 Building and testing the program

5.1 Build

The program is a Rust crate with its own workspace. Build it from its own folder, in release mode (optimised; debug builds are far slower). In any shell:

```
cd studies/dirac16complex_cosmology
cargo build --release
cd ../../
```

Expected output (the first build compiles the engine too and takes a few seconds on a fast computer, a minute or two on a slow one):

```

Compiling sundials_core v7.8.0 (...)
Compiling ccode_rs v7.8.0 (...)
Compiling dirac16complex_cosmology v0.1.0 (...)
Finished ... profile [optimized] target(s) in 4.98s

```

There must be no warning: the crate declares `#![deny(warnings)]`, so any warning would stop the build. The program is now at `studies/dirac16complex_cosmology/target/release/dirac16complex_cosmology.exe` on Windows and at the same path without `.exe` elsewhere.

5.2 The FMA note

The file `.cargo/config.toml` in the repository root contains

```

[build]
rustflags = ["-C", "target-feature=+fma"]

```

Cargo reads it because the crate folder lies below the repository root. It tells the compiler that the processor has the FMA instruction (fused multiply-add: $a \cdot b + c$ computed with a single rounding). The engine's deterministic mathematical functions use fused multiply-add in exactly the places where the reference library does, and with this flag each of them becomes one machine instruction instead of a call into the operating system's C library. The pinned numerical results assume it. Every x86-64 processor since Intel Haswell (2013) and AMD Piledriver (2012) has FMA. An older processor cannot run the program built this way (it would stop with an illegal-instruction error; this was not tested).

5.3 Test

The crate has 25 unit tests (Clifford relations of the generated gamma matrices, the Hamiltonian, CVODE against exact solutions, closed forms of EXP-2 and EXP-3, the EXP-4 algebra and its kink-tail integral, the output format). In any shell:

```

cd studies/dirac16complex_cosmology
cargo test --release
cd ../..

```

Expected output, among the compiler lines:

```

running 25 tests
test result: ok. 25 passed; 0 failed; 0 ignored; 0 measured; 0 filtered out

```

followed by two empty test groups (`running 0 tests`). One test deliberately makes the right-hand side fail and checks that the error is reported, so the line

```

[ERROR][rank 0][...ccode.rs:4221][cvHandleFailure] At t = 0.496781677252198,
the right-hand side routine failed in an unrecoverable manner.

```

(one line on your screen) is expected and is not a failure.

6 The mathematics you need, from zero

This section explains everything the program does, with nothing assumed beyond complex numbers and derivatives. The physics behind the field equation is derived in the documents of Stage 1 (the arbitrary gravitational field) and Stage 2 (the primordial field) in the folder **provenance/**; here we use their results.

6.1 Numbers, columns and matrices

A complex number is $z = x + iy$ with real x, y and $i^2 = -1$; its conjugate is $z^* = x - iy$ and $|z|^2 = z^*z = x^2 + y^2$. A **column** of 16 complex numbers is written

$$u = \begin{pmatrix} u_0 \\ u_1 \\ \vdots \\ u_{15} \end{pmatrix}, \quad u^\dagger = (u_0^*, u_1^*, \dots, u_{15}^*).$$

The row $u^\dagger$ (read “u dagger”) is the conjugate transpose. A 16 by 16 matrix M acts on u by $(Mu)_i = \sum_{j=0}^{15} M_{ij}u_j$, where i is the row and j the column, both counted from 0. The product $u^\dagger Mu = \sum_{i,j} u_i^* M_{ij}u_j$ is a single number; for $M = 1$ it is $u^\dagger u = \sum_i |u_i|^2$, the squared length of u . A matrix is **Hermitian** if $M^\dagger = M$; then $u^\dagger Mu$ is real. A matrix whose every row contains exactly one nonzero entry, equal to $+1$ or -1 , is a **signed permutation**: it only reorders the components of u and flips some signs.

6.2 The field: a column of 16 complex numbers

The field `dirac16complex` is $\Psi = (\Psi_0, \dots, \Psi_{15})^T$: at every point of spacetime, 16 complex components. In the quantum theory the components are Grassmann-odd, which means $\Psi_a \Psi_b = -\Psi_b \Psi_a$; this is how fermions obey the Pauli principle (a state holds at most one particle). None of the ODEs below multiplies two Grassmann numbers. Every experiment integrates the **mode amplitude** $u(t)$, an ordinary column of 16 complex numbers, and the Grassmann nature enters only in two places: the counting of states (each state occupied at most once, Section 6.14) and the expectation-value rule of Section 6.10. For a gas of free quanta in which every state is occupied at most once (EXP-4) this reading is exact mode by mode. The condensate of EXP-2 and EXP-3 is a mean-field picture: one mode at rest stands for a macroscopic density of quanta. That is an approximation in two ways. The Pauli principle allows at most 8 quanta of positive energy per momentum, so a real state of that density is a Fermi sea, with a degeneracy pressure that the one-mode picture leaves out; and the self-interaction is included only through its mean value (Hartree level).

6.3 Spacetime and the gamma matrices

Spacetime has eight coordinates $x_0, \dots, x_7$. The flat metric is

$$\eta = \text{diag}(+1, +1, +1, +1, -1, -1, -1, -1) :$$

directions 0 to 3 are space-like, directions 4 to 7 time-like. x_0 is a hidden space direction, x_1, x_2, x_3 are ordinary 3-space, x_4 is **the** time t , and x_5, x_6, x_7 are three extra time directions. We write $T = \{0, 1, 2, 3, 5, 6, 7\}$ for the seven directions other than time.

The eight **gamma matrices** $\gamma^0, \dots, \gamma^7$ are real 16 by 16 matrices with integer entries (the author's notebook calls them T16). They satisfy the Clifford relation

$$\gamma^a \gamma^b + \gamma^b \gamma^a = 2\eta^{ab} \cdot 1,$$

so $(\gamma^a)^2 = +1$ for $a = 0, \dots, 3$, $(\gamma^a)^2 = -1$ for $a = 4, \dots, 7$, and two different gamma matrices anticommute. Each of them is a signed permutation, which makes it easy to write down completely. The table gives, for each row i , the component that γ^a picks and its sign: the entry -13 in row 0 of γ^4 means $(\gamma^4 u)_0 = -u_{13}$, and $+0$ means $+u_0$.

i	γ^0	γ^1	γ^2	γ^3
0	+8	-15	+14	-13
1	+9	-14	-15	+12
2	+10	+13	-12	-15
3	+11	+12	+13	+14
4	+12	-11	+10	-9
5	+13	-10	-11	+8
6	+14	+9	-8	-11
7	+15	+8	+9	+10
8	+0	+7	-6	+5
9	+1	+6	+7	-4
10	+2	-5	+4	+7
11	+3	-4	-5	-6
12	+4	+3	-2	+1
13	+5	+2	+3	-0
14	+6	-1	+0	+3
15	+7	-0	-1	-2

i	γ^4	γ^5	γ^6	γ^7
0	-13	+14	+15	+8
1	+12	+15	-14	+9
2	+15	-12	+13	+10
3	-14	-13	-12	+11
4	+9	-10	-11	-12
5	-8	-11	+10	-13
6	-11	+8	-9	-14
7	+10	+9	+8	-15
8	+5	-6	-7	-0
9	-4	-7	+6	-1
10	-7	+4	-5	-2
11	+6	+5	+4	-3
12	-1	+2	+3	+4
13	+0	+3	-2	+5
14	+3	-0	+1	+6
15	-2	-1	-0	+7

The same matrices are stored exactly in `artifacts/dirac16complex/arbitrary-field/algebra-fixture.json` (key `gamma`, zero-based) and in `studies/dirac16complex_cosmology/src/generated.rs`. $\gamma^0, \dots, \gamma^3$ are symmetric and $\gamma^4, \dots, \gamma^7$ antisymmetric.

A check you can do by hand. Apply γ^4 twice to component 0: $(\gamma^4 u)_0 = -u_{13}$, and row 13 of γ^4 says $(\gamma^4 v)_{13} = +v_0$, so $(\gamma^4 \gamma^4 u)_0 = -(\gamma^4 u)_{13} = -u_0$. That is $(\gamma^4)^2 = -1$ in row 0, as the Clifford relation demands for a time-like direction.

6.4 Three more matrices: C, B and the chirality

- The **charge matrix** $C = \gamma^0 \gamma^1 \gamma^2 \gamma^3$ is real and symmetric with $C^2 = 1$. The **Dirac adjoint** is $\bar{\Psi} = \Psi^\dagger C$, and $S = \bar{\Psi} \Psi$ is the scalar density (the condensate).
- $B = -iC\gamma^4$ is Hermitian with $B^2 = 1$; it has the eigenvalue $+1$ eight times and -1 eight times. It defines the indefinite inner product $u^\dagger B u$ (Section 6.10).
- The **chirality** $\gamma^8 = \gamma^0 \gamma^1 \dots \gamma^7 = \text{diag}(-1, \dots, -1, +1, \dots, +1)$: components 0 to 7 have chirality -1 , components 8 to 15 chirality $+1$.

C is a signed permutation and B is i times a signed permutation:

i	C	B/i
0	-4	+9
1	-5	-8
2	-6	-11
3	-7	+10
4	-0	-13
5	-1	+12
6	-2	+15
7	-3	-14
8	+12	+1
9	+13	-0
10	+14	-3
11	+15	+2
12	+8	-5
13	+9	+4
14	+10	+7
15	+11	-6

So, for example, $(Bu)_0 = i u_9$.

6.5 Metric, scale factors and the vielbein

All five backgrounds are homogeneous: nothing depends on position, only on time. With $t = x_4$ their line element is

$$ds^2 = -dt^2 + \sum_{j \in T} \epsilon_j h_j(t)^2 dx_j^2, \quad \epsilon_j = +1 \ (j = 0, 1, 2, 3), \quad \epsilon_j = -1 \ (j = 5, 6, 7).$$

$h_j(t)$ is the **scale factor** of direction j : a distance dx_j along it is physically $h_j dx_j$ long. Its **expansion rate** is $H_j = \dot{h}_j/h_j$ (a dot is d/dt), the total rate is $\Theta = \sum_{j \in T} H_j$ and the 7-volume is $V = \prod_{j \in T} h_j$, so that $\dot{V}/V = \Theta$. The experiments group the directions: $b = h_0$ (hidden space), $a = h_1 = h_2 = h_3$ (3-space), $c = h_5 = h_6 = h_7$ (extra times), and then $\Theta = H_b + 3H_a + 3H_c$ and $V = b a^3 c^3$.

The **vielbein** (German “eight legs”) is the set of eight 1-forms $e^4 = dt$ and $e^j = h_j dx_j$; it turns the curved metric into the flat one, $ds^2 = \eta_{ab} e^a e^b$. The curved gamma matrices are $\gamma^{x^4} = \gamma^4$ and $\gamma^{x^j} = \gamma^j/h_j$: the frame matrix divided by the scale factor.

6.6 The covariant derivative

A spinor cannot be differentiated with the plain derivative $\partial_\mu = \partial/\partial x_\mu$ in a curved spacetime, because the frame in which its components are measured turns from point to point. The **covariant derivative** adds a correction, the spinor connection Ω_μ :

$$D_\mu \Psi = \partial_\mu \Psi + \Omega_\mu \Psi, \quad \Omega_\mu = \frac{1}{2} \omega_{\mu ab} S^{ab}, \quad S^{ab} = \frac{1}{4} (\gamma^a \gamma^b - \gamma^b \gamma^a),$$

summed over all ordered pairs (a, b) . The spin connection $\omega_{\mu ab}$ is fixed by the requirement that the total covariant derivative of the vielbein vanishes (the vielbein postulate); Stage 1 derives and verifies this exactly. The field equation needs only the combination $\gamma^\mu \Omega_\mu$ (summed over μ), and for a diagonal vielbein $e^b = h_b dx_b$ Stage 1 proves the formula

$$\gamma^\mu \Omega_\mu = \frac{1}{2} \sum_{b=0}^7 \frac{1}{h_b} \partial_b \ln \left(\prod_{c \neq b} h_c \right) \gamma^b.$$

In our backgrounds only $b = 4$ has a nonzero derivative ($h_4 = 1$, $\partial_4 = d/dt$), and $\prod_{c \neq 4} h_c = V$, so

$$\gamma^\mu \Omega_\mu = \frac{1}{2} \frac{d \ln V}{dt} \gamma^4 = \frac{1}{2} \Theta \gamma^4.$$

That one line is all of the curved-space geometry that enters EXP-2 to EXP-5.

6.7 The Lagrangian and the field equation

The Lagrangian density of `dirac16complex` is

$$\mathcal{L} = \sqrt{|g|} \left[\frac{1}{2} (\bar{\Psi} \gamma^\mu D_\mu \Psi - (D_\mu \bar{\Psi}) \gamma^\mu \Psi) - m \bar{\Psi} \Psi - U(\bar{\Psi} \Psi) \right], \quad U(S) = \frac{\lambda}{2} S^2,$$

with mass m and a four-fermion self-interaction of strength λ ($\lambda < 0$ is attractive). Varying it with respect to $\bar{\Psi}$ gives the field equation

$$\gamma^\mu D_\mu \Psi = M_{\text{eff}} \Psi, \quad M_{\text{eff}} = m + U'(S) = m + \lambda S.$$

M_{eff} is the effective mass: the self-interaction shifts the mass in proportion to the condensate S .

6.8 From the field equation to a mode equation

Take a plane wave with coordinate momentum k_j along the transverse directions,

$$\Psi = V^{-1/2} e^{i \sum_j k_j x_j} u(t).$$

Insert it into the field equation, one term at a time.

1. Time derivative: $\partial_t \Psi = V^{-1/2} e^{ik \cdot x} (\dot{u} - \frac{1}{2} \Theta u)$, because $\dot{V}/V = \Theta$.
2. Space derivatives: $\partial_j \Psi = ik_j \Psi$, and the curved gamma is γ^j/h_j , so these terms give $i \sum_j (k_j/h_j) \gamma^j u$ (times the common factor $V^{-1/2} e^{ik \cdot x}$).
3. Connection: $\gamma^\mu \Omega_\mu \Psi = \frac{1}{2} \Theta \gamma^4 \Psi$.

Adding them, the two Θ terms cancel exactly: that is why the factor $V^{-1/2}$ was put in front. What remains is

$$\gamma^4 \dot{u} + i \sum_{j \in T} \frac{k_j}{h_j} \gamma^j u = M_{\text{eff}} u.$$

Multiply from the left by γ^4 and use $(\gamma^4)^2 = -1$: $-\dot{u} + i \sum_j (k_j/h_j) \gamma^4 \gamma^j u = M_{\text{eff}} \gamma^4 u$. Multiply by $-i$ and rearrange:

$$i \dot{u} = h(t) u, \quad h(t) = -i M_{\text{eff}} \gamma^4 - \gamma^4 \sum_{j \in T} \frac{k_j}{h_j} \gamma^j.$$

This is a Schrödinger-type equation with the **mode Hamiltonian** $h(t)$, a 16 by 16 complex matrix. Two facts about it are used everywhere. First, $h^2 = E^2 \cdot 1$ with

$$E^2 = M_{\text{eff}}^2 + \sum_{j=0}^3 \left(\frac{k_j}{h_j} \right)^2 - \sum_{j=5}^7 \left(\frac{k_j}{h_j} \right)^2,$$

so the energies are $+E$ and $-E$, eight times each. Second, h is Hermitian exactly when $k_5 = k_6 = k_7 = 0$. This is **the good sector**: no momentum along the extra times. Then E is real and $u^\dagger u$ is conserved. With extra-time momentum E^2 can become negative, which EXP-5 studies.

6.9 Complex to real: the layout that CVODE sees

CVODE integrates real numbers. Write $u = x + iy$ with real columns x, y and $h = h_r + ih_i$ with real matrices h_r, h_i . Then $i(\dot{x} + i\dot{y}) = (h_r + ih_i)(x + iy)$; the imaginary part and the real part of this equation give

$$\dot{x} = h_r y + h_i x, \quad \dot{y} = h_i y - h_r x.$$

The program stores the spinor as 32 consecutive reals, the **state layout** used by every experiment:

State index	Quantity	CSV column
$0, \dots, 15$	$x_n = \text{Re } u_n, n = 0, \dots, 15$	u_re_0 to u_re_15
$16, \dots, 31$	$y_n = \text{Im } u_n, n = 0, \dots, 15$	u_im_0 to u_im_15

For $h = -iM\gamma^4 - \sum_j (k_j/h_j)\gamma^4\gamma^j$ the pieces are $h_i = -M\gamma^4$ and $h_r = -\sum_j (k_j/h_j)\gamma^4\gamma^j$. **A worked component.** For $k = 0$ ($h_r = 0$) the equation for state index 0 is $\dot{x}_0 = (h_i x)_0 = -M(\gamma^4 x)_0 = -M(-x_{13}) = Mx_{13}$: one multiplication. The whole right-hand side of a mode is 32 such terms plus, when $k \neq 0$, the h_r terms.

6.10 Energy, pressure, norms and the expectation-value rule

Quantising the field with respect to t gives the anticommutator $\{\Psi, \Psi^\dagger\} \propto B$. Because B has eigenvalues of both signs, the space of states carries an indefinite inner product (a Krein space). The experiments use its positive-norm quantisation, in which a one-particle state built on a normalised positive-energy mode u ($u^\dagger u = 1$) above the filled sea of negative-energy states has the **expectation-value rule**

$$\langle \Psi^\dagger M \Psi \rangle = u^\dagger B M u.$$

From it follow the three quantities per mode that every experiment computes:

$$s(u) = u^\dagger B C u = u^\dagger (-i\gamma^4) u, \quad \varepsilon(u) = u^\dagger h u, \quad p_j(u) = -\frac{k_j}{h_j} u^\dagger \gamma^4 \gamma^j u \quad (\text{no sum}),$$

the scalar density, the energy and the pressure along direction j (one uses $BC = -i\gamma^4$, since C commutes with γ^4 and $C^2 = 1$). They satisfy $\varepsilon = M_{\text{eff}} s + \sum_j p_j$. Two norms are monitored:

- the **Hilbert norm** $u^\dagger u$, conserved when h is Hermitian (good sector);
- the **Krein norm** $u^\dagger B u$, conserved always, because $h^\dagger B = B h$.

The rest eigenvector. For $k = 0$, $h = -iM\gamma^4$, and a positive-energy eigenvector obeys $-i\gamma^4 u = u$. The program's standard choice, also an eigenvector of B with eigenvalue +1, is

$$u_0 = \frac{1}{2}(e_0 - e_4 - i e_9 - i e_{13}),$$

where e_n is the column with 1 in position n . Check it with the tables: $(\gamma^4 u_0)_0 = -u_{13} = i/2$, so $(-i\gamma^4 u_0)_0 = 1/2 = (u_0)_0$; do the same for components 4, 9 and 13, and for $(B u_0)_0 = i u_9 = 1/2$. Hence $s(u_0) = u_0^\dagger u_0 = 1$ and $h u_0 = M u_0$. (The plain product $u^\dagger C u$ is not the scalar density: on the positive-energy rest states $C = B$, so $u^\dagger C u$ is +1 for u_0 but -1 for a rest state with $B = -1$, whose scalar density s is still +1.)

Energy density, pressure and w . With a density n of quanta in the mode u (the mean-field picture of Section 6.2), the energy density is $\rho = n\varepsilon - (\lambda/2)S^2$ and the pressure along j is $p_j = np_j(u) + (\lambda/2)S^2$; the mean transverse pressure is $\bar{p} = \frac{1}{7}\sum_{j\in T}p_j$ and $w = \bar{p}/\rho$. For a condensate at rest this gives $\rho = mS + \frac{\lambda}{2}S^2$ and $p = \frac{\lambda}{2}S^2$. In a real state of the same density the Pauli principle adds a degeneracy pressure, negligible only if the Fermi momentum is much smaller than m ; it is not computed here.

Kinetic and potential energy. The input document describes a scalar field with $\rho = \frac{1}{2}\dot{\phi}^2 + V$ and $p = \frac{1}{2}\dot{\phi}^2 - V$. The spinor analogues, both reported by every experiment, are the Lagrangian split $KE_L = \frac{1}{2}n\varepsilon$, $PE_L = \rho - KE_L$ (for a condensate at rest $\rho = KE_L + PE_L$ and $p = KE_L - PE_L$ exactly as for the scalar field, and $w < -1$ with $\rho > 0$ happens exactly when $KE_L < 0$) and the Hamiltonian split $PE_H = mS + U(S)$ (rest mass and interaction), $KE_H = \rho - PE_H$ (momentum energy). For a free gas $KE_L = PE_L = \rho/2$ in every mode, so the scalar-field relation $p = KE - PE$ holds only for condensates, not for a gas.

When the rule stops applying. A quantum of positive energy always has $\varepsilon > 0$, so $KE_L > 0$: no state made of such quanta has $w < -1$. In EXP-2 and EXP-3 the attractive interaction can drive $M_{\text{eff}} = m + \lambda S$ through zero. The rest mode only changes its phase, so $s(u) = 1$ stays, but its energy $\varepsilon = M_{\text{eff}}$ becomes negative: the one occupied mode has turned into a negative-energy state, and the rule above, which is for a quantum above the sea, no longer describes it. The rows with $M_{\text{eff}} < 0$ (column `M_eff` in the CSV files) contain every phantom row ($w < -1$) and every row with $\rho < 0$; the scientific document treats them as artefacts of the one-mode approximation, not as physics.

6.11 EXP-1: the primordial field

Background. The author's notebook field (Stage 2) in the warped coordinate $\zeta = \ln(\sin z)/(6H)$, $z = 6Hx_0$, with $H = 1$ and $t = x_4$:

$$ds^2 = d\zeta^2 - dt^2 + e^{2H\zeta} [e^{2a_4(t)}(dx_1^2 + dx_2^2 + dx_3^2) - e^{-2a_4(t)}(dx_5^2 + dx_6^2 + dx_7^2)].$$

3-space grows as e^{a_4} and the extra times shrink as e^{-a_4} , so the 7-volume stays constant. The profile is a primordial window, $a_4'(t) = A(1 + \tanh \frac{t-t_1}{\Delta})(1 - \tanh \frac{t-t_2}{\Delta})/4$ with $t_1 = 2$, $t_2 = 7$, $\Delta = 0.5$ and two amplitudes $A = 1$ and $A = 2$.

Reduction, step by step. Here the vielbein depends on ζ and t , so use the formula of Section 6.6 with $b = 0$ (the ζ direction, $h_0 = 1$) and $b = 4$. For $b = 0$: $\prod_{c \neq 0} h_c = e^{3(H\zeta + a_4)} e^{3(H\zeta - a_4)} = e^{6H\zeta}$, whose ζ -derivative of the logarithm is $6H$; for $b = 4$: $\prod_{c \neq 4} h_c = e^{6H\zeta}$ does not depend on t . Hence $\gamma^\mu \Omega_\mu = 3H\gamma^0$, and a_4 has dropped out. Take a wave in the hidden direction and no momentum elsewhere, $\Psi = e^{-3H\zeta} e^{iK\zeta} u(t)$. The ζ -derivative gives $\gamma^0(-3H + iK)\Psi$; the $-3H$ cancels the connection term $3H\gamma^0\Psi$ (the factor $e^{-3H\zeta}$ plays the role of $V^{-1/2}$), and what remains is

$$\gamma^4 \dot{u} = (M_{\text{eff}} - iK\gamma^0)u \quad \Longleftrightarrow \quad i\ddot{u} = hu, \quad h = -iM_{\text{eff}}\gamma^4 - K\gamma^4\gamma^0.$$

This is Section 6.8 with $k_0/h_0 = K$. Stage 2 verified the reduction exactly (Wolfram check `P_modes_exactReduction`) for $\lambda = 0$. With $\lambda \neq 0$ it holds only pointwise: the mode's scalar density is $S = S_0 s(u)/\sin z$, which depends on x_0 , so $M_{\text{eff}} = m + \lambda S$ is not the same at every x_0 , and the λ

run below treats S_0 as the local density factor at one fixed x_0 (a mean-field approximation). For the same reason the $K = 0$ state is not a homogeneous condensate: its density falls off as $1/\sin z$. Because h does not contain a_4 , the two profiles must give identical spinors; they do, bit for bit.

State, right-hand side, initial data. The state is the 32-real spinor of Section 6.9, with $h_i = -M_{\text{eff}}\gamma^4$ and $h_r = -K\gamma^4\gamma^0$; $M_{\text{eff}} = m + \lambda S_0 s(u)$ with $m = 1$. Runs: $K \in \{0, 0.5, 2\}$, four initial spinors each, $\lambda = 0$ and $S_0 = 1$, for each profile ($2 \times 3 \times 4 = 24$ runs), plus one run per profile with $\lambda = 0.5$, $S_0 = 1$, $K = 0.5$ (26 runs). The four initial spinors are the first vector of the joint eigenspace of h (energy $+E$) and B ($+1$), called **pos_Bp**; energy $+E$ with $B = -1$ (**pos_Bm**); energy $-E$ with $B = +1$ (**neg_Bp**); and a normalised generic vector **mix** with $\text{Re } u_n = 1/(1+n)$ and $\text{Im } u_n = 0.1(n^2 \bmod 7) - 0.3$ before normalisation. Eigenstates test that ρ and p are frozen; the mixture of both energy signs tests interference. The **neg_Bp** and **mix** runs are numerical controls: in the quantum theory the negative-energy states are filled by the sea, so their oscillating pressures are not physics of the field. The λ run starts on the self-consistent eigenvector with $M_* = m + \lambda S_0 M_*/\sqrt{M_*^2 + K^2}$, solved by Newton's method: $M_* = 1.4734826640642023$. Time runs from 0 to 10 with 201 samples.

Exact solution and checks. With $\lambda = 0$, h is constant and $u(t) = (\cos Et - i \sin Et h/E) u(0)$ with $E = \sqrt{M^2 + K^2}$; the program compares with it at every sample. It also records the source that 8D Einstein gravity would need for this field ($\kappa = 1$): $\rho_{\text{req}} = -3H^2(7 + a_4'^2)$, which is negative always.

6.12 EXP-2: an 8D universe that feels the condensate

Background and Einstein equations. $ds^2 = -dt^2 + b^2 dx_0^2 + a^2(dx_1^2 + dx_2^2 + dx_3^2) - c^2(dx_5^2 + dx_6^2 + dx_7^2)$ with 8D gravitational coupling $\kappa = 1$ and $m = 1$. For this metric the time-time component of Einstein's equation $G^\mu{}_\nu = \kappa T^\mu{}_\nu$ is a constraint, and the space-space components, after the trace is used, are evolution equations (the signs ϵ_j drop out of the mixed components):

$$\sum_{i < j} H_i H_j = 3H_b H_a + 3H_b H_c + 3H_a^2 + 3H_c^2 + 9H_a H_c = \kappa \rho, \quad \dot{H}_i = -H_i \Theta + \frac{\kappa(\rho - p)}{6}.$$

The sum runs over the 21 pairs of the seven transverse directions; the 6 is $D - 2$ for $D = 8$. The checker derives the Einstein tensor again from the metric, independently (check **einsteinTensorFromMetric**).

Matter. The condensate is the $k = 0$ mode: $h = -iM_{\text{eff}}\gamma^4$, $S = S_0 (V_0/V) s(u)$ with $V_0 = 1$, $M_{\text{eff}} = m + \lambda S$, $\rho = mS + \frac{\lambda}{2}S^2$, $p = \frac{\lambda}{2}S^2$, so $\rho - p = mS$ does not depend on λ .

State vector (38 reals) and right-hand side:

State index	Quantity	d/dt of it
0	$\ln b$	H_b
1	$\ln a$	H_a
2	$\ln c$	H_c
3	H_b	$-H_b \Theta + \kappa m S / 6$
4	H_a	$-H_a \Theta + \kappa m S / 6$
5	H_c	$-H_c \Theta + \kappa m S / 6$
6 to 21	$\text{Re } u_0, \dots, \text{Re } u_{15}$	$-M_{\text{eff}} \gamma^4 \text{Re } u$

State index	Quantity	d/dt of it
22 to 37	$\text{Im } u_0, \dots, \text{Im } u_{15}$	$-M_{\text{eff}} \gamma^4 \text{Im } u$

with $\Theta = H_b + 3H_a + 3H_c$, $V = \exp(\ln b + 3 \ln a + 3 \ln c)$ and S from the spinor. The spinor rows are Section 6.9 with $h_r = 0$.

Initial data and why. $\ln b = \ln a = \ln c = 0$, $H_b = 0$, $H_a = 1$, $H_c = -0.2$ (3-space expanding, extra times deflating), $u(0) = u_0$ of Section 6.10 (a positive-energy particle at rest, $s = 1$). The parameter $x_0 = \lambda S_0/(2m)$ (not the coordinate) is the interaction strength relative to the mass; runs $x_0 \in \{0, -0.4, +0.5\}$. The constraint must hold at $t = 0$: its left side is $C_0 = 3(1) + 3(0.04) + 9(-0.2) = 1.32$, the right side is $\kappa m S_0(1 + x_0)$, hence

$$S_0 = \frac{1.32}{1 + x_0}, \quad \lambda = \frac{2m x_0}{S_0} :$$

$S_0 = 1.32, 2.2, 0.88$ and $\lambda = 0, -0.363636, 1.136364$ for the three runs. The constraint is not imposed again; the program monitors it (`constraint_relative`).

Exact solution. Because $\rho - p = mS$ and SV is constant, the equations give $\ddot{V} = \frac{7}{6}\kappa m S_0$, so $V(t) = 1 + 2.4t + \alpha t^2$ with $\alpha = 7S_0/12$, and $H_i V$ grows linearly. The output times are chosen uniform in $\ln V$ from -7 (just before the backward singularity) to 18.5 (late times, $t \approx 10^4$), step 0.05 ; CVODE integrates the full 38-dimensional system without using the exact solution.

6.13 EXP-3: the condensate as dark energy

Model. The hidden and extra dimensions are frozen, so the 4D universe is an ordinary flat Friedmann universe. Units $H_0 = c = 1$ (today's expansion rate), densities in units of the critical density $3H_0^2/\kappa_4$. The independent variable is the number of e-folds $N = \ln a$ ($N = 0$ today). Since $S \propto a^{-3}$, write $\sigma = S/S_0 = a^{-3}$ and $x_0 = \lambda S_0/(2m)$ as before. From $\rho = mS + \frac{\lambda}{2}S^2 = mS_0\sigma(1 + x_0\sigma)$, normalised so that $\rho_\psi(a = 1) = \Omega_\psi$:

$$\rho_\psi = A\sigma(1 + x_0\sigma), \quad p_\psi = A x_0\sigma^2, \quad A = \frac{\Omega_\psi}{1 + x_0}, \quad w = \frac{x_0\sigma}{1 + x_0\sigma},$$

and the expansion rate

$$E^2 = \frac{H^2}{H_0^2} = \Omega_r a^{-4} + \Omega_m a^{-3} + \rho_\psi,$$

with $\Omega_r = 0.00009$, $\Omega_m = 0.305$, $\Omega_\psi = 0.69491$ (they add up to 1; these are inputs chosen by the numerical programme, the input document gives no Ω_m). Today $w_0 = x_0/(1 + x_0)$, so $x_0 = w_0/(1 - w_0)$: $w_0 = -0.861$ needs $x_0 = -0.462654$, and $w_0 = -0.764$ needs $x_0 = -0.433107$.

Change of variable. $dN = H dt = H_0 E dt$, so $d/dN = (1/(H_0 E)) d/dt$. The spinor equation $i\dot{u} = hu$ with $h = -iM_{\text{eff}}\gamma^4$ becomes $du/dN = -i(h/H_0)u/E$. The time since today is $H_0(t - t_0)$ with $d(H_0 t)/dN = 1/E$, and the comoving distance obeys $dD_C/dz = 1/E$ with $z = e^{-N} - 1$, hence $dD_C/dN = -1/(aE)$.

State vector (35 reals) and right-hand side:

State index	Quantity	d/dN of it
0	$H_0(t - t_0)$	$1/E$
1	D_C (units c/H_0)	$-1/(aE)$
2 to 17	$\text{Re } u_0, \dots, \text{Re } u_{15}$	$-(M_{\text{eff}}/H_0)\gamma^4 \text{Re } u/E$
18 to 33	$\text{Im } u_0, \dots, \text{Im } u_{15}$	$-(M_{\text{eff}}/H_0)\gamma^4 \text{Im } u/E$
34	$\ln \sigma$	$-3 +$ $2 \text{Re}(u^\dagger(-i\gamma^4) du/dN)/s(u)$

Here $a = e^N$, $\sigma = a^{-3}s(u)/s(u_0)$ is taken from the spinor, and $M_{\text{eff}}/H_0 = \mu(1 + 2x_0\sigma)/(1 + 2x_0)$, where $\mu = M_{\text{eff}}(a = 1)/H_0 \in \{3, 7\}$ is a reduced frequency. Real fermions have $m/H_0 > 10^{30}$; two small values show that ρ , p and w do not depend on the spinor's phase. Row 34 reproduces $d\sigma/dN = -3\sigma$ from the spinor's own scalar density.

Initial data and range. At $N = 0$: $H_0(t - t_0) = 0$, $D_C = 0$, $u = u_0$, $\ln \sigma = 0$. Runs $x_0 \in \{-0.462654, -0.433107, -0.3, -0.2, 0\}$ and $\mu \in \{3, 7\}$ (10 runs), integrated backward towards $a = 1/3.5$ and forward to $a = 2$. For every $x_0 < 0$ the attractive term makes ρ_ψ negative in the past and E^2 reaches 0 (a bounce) before $a = 1/3.5$, at the root a_b of $(\Omega_m + A)a^3 + \Omega_r a^2 + A x_0 = 0$; the backward run then stops just after the bounce ($N_b + 0.01$). Only $x_0 = 0$ reaches $a = 1/3.5$.

The CPL tangent. $w(a) = x_0/(a^3 + x_0)$, so $dw/da = -3a^2 x_0/(a^3 + x_0)^2$ and at $a = 1$

$$w_a = -\left.\frac{dw}{da}\right|_{a=1} = \frac{3x_0}{(1 + x_0)^2}.$$

The EXP-3 analysis (`scripts/analyze_dirac16complex_exp3.py`, numpy only, with its own Nelder-Mead minimiser) computes these tangents, least-squares CPL fits, distance-modulus fits and a fine scan over x_0 from the closed forms, and uses the CVODE D_C as a cross-check.

6.14 EXP-4: the quanta as dark matter

Background. Only 3-space expands, $b = c = 1$, $h_1 = h_2 = h_3 = a(t)$. Only momenta in 3-space are used: the momentum k_0 along the hidden direction is set to zero, an assumption (it holds for a small, compact hidden dimension) that also fixes the radiation value $w = 1/3$ (with k_0 free it would be $1/4$). A mode moving along x_1 with comoving momentum k has physical momentum $K = k/a$ and

$$h = -im\gamma^4 - K\gamma^4\gamma^1, \quad E = \sqrt{m^2 + K^2}, \quad h_i = -m\gamma^4, \quad h_r = -K\gamma^4\gamma^1.$$

Each mode is one 32-real state (Section 6.9); the right-hand side is $\dot{x} = -m\gamma^4 x - K\gamma^4\gamma^1 y$, $\dot{y} = -m\gamma^4 y + K\gamma^4\gamma^1 x$.

(a) Thermal gas. Radiation era $a(t) = (t/t_i)^{1/2}$ with $t_i = 10$, so the initial Hubble rate is $H_i = 1/(2t_i) = 0.05$; a runs from 1 to 100 (t from 10 to 10^5), with 61 samples uniform in $\ln a$. Units $m = 1$, initial temperature $T_i = 10$ (relativistic). Momentum grid: 48 Gauss-Legendre nodes k_n on $[0, 120]$ with weights w_n . Each mode starts at t_i on the positive-energy eigenvector of $h(t_i)$ with

$B = +1$. Fermi-Dirac occupation $f_n = 1/(e^{E_n/T_i} + 1) \leq 1$ (the Pauli principle), and 16 states per momentum (8 particle and 8 antiparticle states). With $W_n = \frac{16}{2\pi^2} w_n k_n^2 f_n$:

$$\rho = \frac{1}{a^3} \sum_n W_n \varepsilon_n, \quad p = \frac{1}{3a^3} \sum_n W_n p_{1,n},$$

the factor $1/3$ averaging a mode moving along x_1 over all directions. The program compares ρ and p with the kinetic-theory integrals.

(b) Pair creation. $a = e^t$ for $t < 0$ (de Sitter, $H_{\text{inf}} = 1$) joined smoothly to $a = (1 + 2t)^{1/2}$ for $t > 0$ (radiation); the integration is restarted at $t = 0$, where $\dot{H}$ jumps. Each mode starts in the vacuum when it is deep inside the horizon, at $t_0 = \ln(k/200)$ where $k/a = 200$, in the first-order adiabatic positive-frequency state, and runs until $H = 10^{-4}m$ (for $m = 0$ the $m = 0.1$ end is used). Masses $m \in \{0, 0.1, 0.5, 1, 2\}$, 64 Gauss-Legendre nodes in $\ln k$ on $[10^{-3}, 40]$. The number of created pairs per mode is $|\beta_k|^2 = |P_- u|^2/|u|^2$, the weight on the negative-energy eigenspace ($P_- = (1 - h/E)/2$), and the comoving number density is $na^3 = \frac{16}{2\pi^2} \int k^2 |\beta_k|^2 dk$. The program uses the final $|\beta_k|^2$ in the first-order adiabatic basis (column `beta2_adiabatic`), which removes the small dressing $(mKH/(4E^3))^2$ that even an unexcited mode shows in the instantaneous basis; the instantaneous-basis numbers are reported too, and the analytic tail of the spectrum beyond $k = 40$ is added as a separate correction. For $m = 0$ the mode equation is conformally invariant and nothing is created.

6.15 EXP-5: momentum along an extra time

The extra times deflate, $c = e^{-t}$ ($H = 1$), and the mode has momentum q along x_5 and none elsewhere, $m = 1$. Then $k_5/h_5 = Q(t) = q e^t$ and

$$h = -im\gamma^4 - Q(t)\gamma^4\gamma^5, \quad E^2 = m^2 - q^2 e^{2t}, \quad h_i = -m\gamma^4, \quad h_r = -Q\gamma^4\gamma^5.$$

E^2 turns negative at $t^* = \ln(m/q)$. The state is the 32-real spinor; the initial state is the positive-energy eigenvector of $h(0)$, $E_0 = \sqrt{m^2 - q^2}$, that is also an eigenvector of C with eigenvalue ± 1 (so that its Krein norm $\pm E_0/m$ is not zero). Runs $q \in \{0.05, 0.1\}$ and $C = \pm 1$, t from 0 to $t^* + 3$, 601 samples. After t^* the Hilbert norm grows like $e^{2W(t)}$ with the WKB exponent $W(t) = \sqrt{Q^2 - m^2} - m \arccos(m/Q)$, while the Krein norm stays constant. This is why the quantisation and the cosmology of EXP-1 to EXP-4 are restricted to the good sector.

6.16 How CVODE solves $u' = f(t, u)$

Every experiment hands CVODE a system $Y' = f(t, Y)$ with a start value $Y(t_0)$ and a list of output times. CVODE advances in steps $t_{n+1} = t_n + h_n$ with a **linear multistep method**, which combines the last few values of Y and f :

- **Adams-Moulton** (orders 1 to 12) is accurate for smooth, non-stiff problems. Our mode equations are oscillations ($-ih$ has purely imaginary eigenvalues in the good sector), the classic non-stiff case.

- **BDF**, backward differentiation formulas (orders 1 to 5), is stable for stiff problems, which contain fast decaying components; it damps oscillations slightly.

Both formulas are implicit: Y_{n+1} appears on both sides, $Y_{n+1} = \gamma f(t_{n+1}, Y_{n+1}) + a_n$. CVODE solves this either by **Newton’s method**, which needs the Jacobian $J = \partial f / \partial Y$ (here estimated by difference quotients and factorised as a dense matrix), or by **fixed-point iteration** $Y \leftarrow \gamma f(Y) + a_n$, which needs no Jacobian and converges when the step is small compared with the inverse rates, as it is for non-stiff problems.

After each step CVODE estimates the local error e_i of every component and accepts the step if the weighted root-mean-square $\sqrt{\frac{1}{n} \sum_i (e_i / (\text{rtol} |Y_i| + \text{atol}))^2}$ is at most 1; otherwise it retries with a smaller step. **rtol** is the relative tolerance, **atol** the absolute tolerance (important for components near zero), and **max_step** a cap on the step size. The tolerances bound the error of one step; the error at the end, the global error, accumulates and is larger (EXP-1 measured about $500 \times \text{rtol}$), which is why each experiment checks itself against exact solutions or conserved quantities.

Experiment	Method	rtol, atol	max_step	Steps	RHS calls
EXP-1	BDF + Newton + dense	1e-12, 1e-14	0.02	33866	34950
EXP-2	Adams + fixed point	1e-12, 1e-15	0.02	1779784	1781396
EXP-3	Adams + fixed point	1e-11, 1e-13	0.01	6074	10115
EXP-4	Adams + fixed point	1e-13, 1e-14	2.0	287898778	435564940
EXP-5	Adams + fixed point	1e-10, 1e-12	0.02	2548	4800

Why these settings, as measured by the study: EXP-1 at rtol 1e-10 drifts by 5e-8 to 1.2e-7 in its conserved quantities, above its 1e-8 limit (Exercise 13.1 lets you see it). EXP-2 without the step cap drifts by 1.7e-7 over $t \approx 10^4$. EXP-4 needs rtol 1e-13 because each thermal mode turns through about 10^5 radians and Adams leaks norm in proportion to steps times rtol; it chooses Adams over BDF at run time by a measured test (Adams was more accurate, 1.7e-9 against 1.8e-8, and cheaper). For EXP-3 the step cap is in units of N .

7 Running the experiments

7.1 The command line of the program

```

dirac16complex_cosmology <print-config|exp1|exp2|exp3|exp4|exp5|all>
  [--output DIR]    output root (default artifacts/dirac16complex/numerics);
                    experiment N writes into DIR/expN/
  [--rtol X]        replace every experiment’s default relative tolerance
  [--atol X]        replace every experiment’s default absolute tolerance
  [--refined]       rtol/10, atol/10, max_step/2 (convergence runs)

```

Every self-check prints `PASS - name: detail` or `FAIL - name: detail`, and the **last line** is always `SUCCESS` (exit code 0) or `FAILURE` (exit code 1). The default output folder is relative to the folder you run the program from, so **always run it from the repository root**.

Save the long program path in a variable, which lasts until you close the terminal. PowerShell:

```
$bin = ".\studies\dirac16complex_cosmology\target\release\dirac16complex_cosmology.exe"
& $bin print-config
```

Git Bash, macOS and Linux (in Git Bash the `.exe` may be left out):

```
bin=./studies/dirac16complex_cosmology/target/release/dirac16complex_cosmology
$bin print-config
```

`print-config` runs nothing; it prints the configuration. Expected output (shortened):

```
study          = dirac16complex-cosmology
engine         = sundials_rs 7.8.0 CVODE (pure Rust, vendor/rustSolveIt)
fixture        = artifacts/dirac16complex/arbitrary-field/algebra-fixture.json
fixture sha256 = 8b4f15462ca4d61ef6ec0e72f04c8a77d23ce8bcabc9b6ce19f921c90e02653b
...
exp5: default rtol = 1.00000000000000004e-10, atol = 9.9999999999999980e-13, ...
all             = exp1, exp2, exp3, exp4, exp5
SUCCESS
```

The numbers are printed with 17 significant digits, the exact decimal value of the binary number, which is why 10^{-10} appears as `1.00000000000000004e-10`.

7.2 A first run into a scratch folder

Run EXP-1 into the scratch folder `build/student` (ignored by Git, so nothing committed is touched). PowerShell:

```
& $bin exp1 --output build/student
```

Git Bash, macOS and Linux:

```
$bin exp1 --output build/student
```

Expected output (0.2 seconds):

```
== exp1 ==
PASS - exact_solution_all_runs: max |u - exp(-iht)u0| = 6.24599767338994569e-09 ...
PASS - rho_frozen_all_runs: max |rho(t) - rho(0)| = 4.19369583504192178e-09
...
PASS - lambda_run_meff_constant: max |M_eff(t) - M*| = 1.32129440721939773e-09
exp1: solver_steps=33866 rhs_evaluations=34950 files=29 verdict=SUCCESS
SUCCESS
```

The files are now in `build/student/exp1/`. To see the exit code, type `$LASTEXITCODE` in PowerShell or `echo $?` in bash right after the run: 0 means success.

7.3 All five experiments

Run the others into the same folder in the same way (`exp2` to `exp5` instead of `exp1`), or all five at once with `all`. What each prints at the end and how long it took on the test computer:

Experiment	Self-checks	Final summary line	Files	Time
exp1	10	exp1: so lver_ste ps=33866 rhs_eva luations=34950 files=29 verdict= SUCCESS	29	0.2 s
exp2	15	exp2: so lver_ste ps=1779784 rhs_evaluatio ns=1781396 files=4 verdi ct=SUCCESS	4	5 s
exp3	14	exp3: so lver_ste ps=6074 rhs_eval uations=10115 files=11 v erdict=SUCCESS	11	0.1 s
exp4	23	exp4: so lver_ste ps=287898778 rhs_evaluat ions=435564940 files=13 verdict= SUCCESS	13	72 s
exp5	7	exp5: so lver_ste ps=2548 rhs_eval uations=4800 files=5 ver dict=SUCCESS	5	0.1 s

That is 69 self-checks in total. EXP-4 integrates 288 million CVODE steps on up to 8 threads; on a computer with fewer cores expect several minutes. The times were measured on the otherwise idle

test computer; while other programs kept its cores busy, the same runs took up to five times longer (EXP-4 once needed 347 s). The line `== expN ==` starts each experiment and a single `SUCCESS` ends the whole run.

7.4 Reproducing the committed files byte for byte

The strongest check is to run everything into the default folder, over the committed files, and ask Git whether any byte changed. PowerShell:

```
& $bin all
git status --short
```

Git Bash, macOS and Linux:

```
$bin all
git status --short
```

The second command prints nothing if every file is identical to the committed one. That was the result on Windows 11 in both shells and on Ubuntu 24.04, all with the `win11` engine (80 to 90 seconds). With the `linux` or `macos` engine it lists the 14 files of Section 4.5. To put the committed files back after any experiment, in any shell:

```
git restore artifacts
```

8 Reading the output files

8.1 The file format

Every file is plain text. A CSV file has one header row of column names, then one row per sample, values separated by commas, lines ending in a single line feed. Every number is written with 18 significant digits in exponential form, for example `-2.10000000000113253e+01`, so that a repeat run can be compared byte for byte; a value that does not exist is written `nan`. Each experiment folder also contains `summary.json` with the parameters, tolerances, solver statistics, every self-check and the verdict. Open the files with any text editor or a spreadsheet, or read them with Python (Section 13 shows how).

8.2 EXP-1 (folder `exp1`, 29 files)

`background_A1.csv` and `background_A2.csv` (201 rows each) describe the field for the two profiles:

Column	Meaning
t	time $t = Hx_4$

Column	Meaning
a4, a4_prime, a4_second	the profile a_4 and its first and second derivatives
scale_3space, scale_extratime	e^{a_4} and e^{-a_4}
volume_ratio	V/V_0 (equal to 1)
theta	total expansion rate Θ (equal to 0)
rho_req	energy density that 8D Einstein gravity would need
p_req_0, p_req_1, p_req_2, p_req_3, p_req_5, p_req_6, p_req_7	required pressures along the seven transverse directions
p_mean_req, w_req	their mean and the required w

The 26 run files `run_A{1,2}_K{0,0p5,2}_{pos_Bp,pos_Bm,neg_Bp,mix}.csv` and `run_A{1,2}_K0p5_pos_Bp_lambda0p5.csv` (the letter p stands for the decimal point) have 201 rows each:

Column	Meaning
t	time
u_re_0 to u_re_15, u_im_0 to u_im_15	the state: real and imaginary parts of u
S	scalar density $S = S_0 s(u)$
M_eff	effective mass
energy_mode	$\varepsilon(u) = u^\dagger h u$
rho	energy density
p_0, p_1, p_2, p_3, p_5, p_6, p_7	pressures along the seven transverse directions
p_mean, w	mean pressure and $w = \bar{p}/\rho$
KE_L, PE_L, KE_H, PE_H	the two kinetic/potential splits
w_L	$(KE_L - PE_L)/\rho$
norm_hilbert, norm_krein	$u^\dagger u$ and $u^\dagger B u$
exact_error	distance from the exact solution

8.3 EXP-2 (folder exp2, 4 files)

`run_x0_0.csv`, `run_x0_m0p4.csv` and `run_x0_0p5.csv` (511 rows each, in increasing t : the backward branch, $t = 0$, the forward branch; m stands for minus):

Column	Meaning
t	time
ln_b, ln_a, ln_c	logarithms of the scale factors (state 0 to 2)
H_b, H_a, H_c	expansion rates (state 3 to 5)
u_re_0 to u_re_15, u_im_0 to u_im_15	the spinor (state 6 to 37)
V, Theta	7-volume and total expansion rate
s_u, S, M_eff	$s(u)$, the condensate, the effective mass
energy_mode	$u^\dagger h u$
rho, p, w	energy density, isotropic pressure, w
KE_L, PE_L, KE_H, PE_H	the two splits
constraint_residual, constraint_relative	$\sum_{i<j} H_i H_j - \kappa \rho$, absolute and divided by the sum of the absolute terms
bound	$\Theta^2 - 3H_a^2 - 2\kappa \rho$ (equal to $H_b^2 + 3H_c^2 \geq 0$ on the constraint surface)

Column	Meaning
w_eff	the w a 3-space observer infers, $-1 + \frac{\Theta}{3H_a}(1 + w)$
norm_hilbert, norm_krein	the two norms

8.4 EXP-3 (folder exp3, 10 run files and the analysis)

run_x0_{0,m0p2,m0p3,m0p433107,m0p462654}_mu{3,7}.csv, the backward and forward branches joined in increasing N :

Column	Meaning
N, a, z	e-folds, scale factor, redshift $z = 1/a - 1$
branch	-1 backward, 0 today, +1 forward
H0t, D_C	state 0 and 1: $H_0(t - t_0)$ and the comoving distance
u_re_0 to u_re_15, u_im_0 to u_im_15	state 2 to 33: the spinor
ln_sigma	state 34
E	H/H_0
q	deceleration parameter
rho_psi, p_psi, w	condensate density, pressure, w
KE_L, PE_L, KE_H, PE_H	the two splits
Omega_psi, Omega_m	density fractions ρ_ψ/E^2 and $\Omega_m a^{-3}/E^2$ at that time
cs2	sound speed squared $dp/d\rho = 2x_0\sigma/(1 + 2x_0\sigma)$
M_eff_over_H0, s_u	M_{eff}/H_0 and $s(u)$
sigma_spinor, sigma_state, sigma_analytic	σ from the spinor, from state 34, and a^{-3}
norm_hilbert, norm_krein	the two norms
eigen_leak	how far u has left the rest eigenspace
rho_closed, p_closed, w_closed	the closed forms of Section 6.13
d_L, mu_H0free	luminosity distance $(1 + z)D_C$ and $5 \log_{10} d_L$ (nan for $z \leq 0$)

The analysis writes fits.json (all fits and the Unite comparison), fits_mu_scan.csv (distance-modulus fits for x_0 from -0.49 to 0 in steps of 0.01) and fits_scan.csv (closed forms and $w(a)$ fits in steps of 0.001):

Column of fits_scan.csv	Meaning
x0	interaction parameter
w0_tangent, wa_tangent	CPL tangent at $a = 1$
a_zero, z_zero	where $\rho_\psi = 0$: $a = x_0 ^{1/3}$
a_cross, z_cross	where $w = -1$ is crossed: $a = (2 x_0)^{1/3}$
a_bounce, z_bounce	the bounce $E^2 = 0$
q0, cs2_today	deceleration and sound speed squared today
wfit_requested_defined, wfit_req	the least-squares CPL fit of $w(a)$ on
uested_w0, wfit_requested_wa	$[1/3.26, 1]$ (1 if defined, else 0 and nan)

Column of fits_scan.csv	Meaning
wfit_restricted_a_lo, wfit_restricted_w0, wfit_restricted_wa	the same fit restricted to where $w \geq -3$

8.5 EXP-4 (folder exp4, 13 files)

File	Rows	Contents
thermal_grid.csv	48	the momentum grid: node, Gauss-Legendre x and gl_weight on $[-1, 1]$, k , $weight$ on $[0, 120]$, E_i , occupation f , $mode_weight$ W_n , $beta2_sudden_start$ (the predicted free-wave amplitude)
thermal_modes.csv	2928	every thermal mode at 61 times
thermal_spin.csv	244	a second spin state for four nodes (must equal the first)
thermal_antiparticle.csv	61	a negative-energy mode (antiparticle symmetry)
thermal_adiabatic_vacuum.csv	122	two modes started in the first-order adiabatic vacuum
thermal_eos.csv	61	the gas: a , t , H , ρ , p , w , KE_H , PE_H , KE_L , PE_L , n_{a3} , the kinetic-theory $\rho_{kinetic}$, $p_{kinetic}$, $w_{kinetic}$, the deviations rel_dev_rho , rel_dev_p , and $beta2_weighted$, $beta2_max$, $beta2_adiabatic_max$, $norm_dev_max$
pair_grid.csv	64	node, x , gl_weight , k , ln_k_weight , start time $t0$
pair_modes.csv	2560	every pair-creation mode at 8 times, for the five masses
pair_antiparticle.csv	24	negative-energy modes for $m = 1$
pair_spectrum.csv	320	m , node, k , $t0$, a_end , $ \beta_k ^2$ at the start, at the joint $t = 0$ and at the end ($beta2_initial$, $beta2_kink$, $beta2_adiabatic_kink$, $beta2_end$, $beta2_adiabatic_end$) and the high- k theory $beta2_kink_tail_theory$
pair_history.csv	35	m , sample, t , a , n_{a3} , $n_{a3_adiabatic}$

File	Rows	Contents
pair_eos.csv	305	the created gas (adiabatic basis, then with the kink tail beyond $k = 40$, then in the instantaneous basis): m , a , n_{a3} , ρ_{a3} , p_{a3} , w , $n_{a3_tail_corrected}$, $\rho_{a3_tail_corrected}$, $p_{a3_tail_corrected}$, $w_{tail_corrected}$, $\rho_{a3_instantaneous}$, $p_{a3_instantaneous}$, $w_{instantaneous}$

The mode files share these columns:

Column	Meaning
m (pair files only), $node$, k	mass, grid node, comoving momentum
t , a , H , K	time, scale factor, expansion rate, physical momentum k/a
u_re_0 to u_re_15 , u_im_0 to u_im_15	the state
E , ϵ , p_1	$\sqrt{m^2 + K^2}$, $\epsilon(u)$, $p_1(u)$
s (thermal files only)	$s(u)$
$norm_hilbert$, $norm_krein$	the two norms
β_2 , $\beta_{2_adiabatic}$	$ \beta_k ^2$ in the instantaneous and in the first-order adiabatic basis

8.6 EXP-5 (folder exp5, 5 files)

run_q0p05_Cp.csv, run_q0p05_Cm.csv, run_q0p1_Cp.csv, run_q0p1_Cm.csv (601 rows each; Cp and Cm are $C = +1$ and $C = -1$):

Column	Meaning
t	time
Q	$q e^t$
E_2	$E^2 = m^2 - Q^2$
κ	WKB growth rate $\sqrt{Q^2 - m^2}$ (0 before t^* ; not the gravitational coupling)
wkb_W	WKB exponent $W(t)$
u_re_0 to u_re_15 , u_im_0 to u_im_15	the state
$norm_hilbert$, $norm_krein$, $\ln_norm_hilbert$	the norms and $\ln(u^\dagger u)$
$krein_drift$, $krein_drift_normalized$	change of $u^\dagger B u$, absolute and divided by $\max(u^\dagger u, 1)$

9 Checking the results with the Python checkers

9.1 What the checkers do

Each checker `scripts/check_dirac16complex_expN.py` uses `numpy` and the standard library only. It rebuilds the gamma matrices from the algebra fixture, recomputes every physical quantity from the state columns alone (never trusting the program's derived columns), compares with exact solutions and independent integrators, checks conservation laws and finite-difference residuals of the equations, and compares with the program's `summary.json`. Two options add two more checks:

```
--repeat DIR    run the program again into DIR; every file must be byte-identical
--refined DIR   run it again with ten times tighter tolerances; the errors must shrink
```

The checker prints `check_NAME=true` or `false` for each check, then `check_count=` and `failed_check_count=`, writes `python-check-report.json` into the experiment folder, and exits with 1 if any check failed.

9.2 Checking the committed folder (the full form)

After Section 7.4, run the EXP-3 analysis first (the EXP-3 checker also checks its `fits.json`), then the five checkers with both options, in any shell:

```
python scripts/analyze_dirac16complex_exp3.py
python scripts/check_dirac16complex_exp1.py --repeat build/repeat --refined build/refined
python scripts/check_dirac16complex_exp2.py --repeat build/repeat --refined build/refined
python scripts/check_dirac16complex_exp3.py --repeat build/repeat --refined build/refined
python scripts/check_dirac16complex_exp4.py --repeat build/repeat --refined build/refined
python scripts/check_dirac16complex_exp5.py --repeat build/repeat --refined build/refined
git status --short
```

Expected results and times on the test computer:

Script	Checks	Failed	Time
<code>analyze_dirac16complex_exp3.py</code>	10	0	5 s
<code>check_dirac16complex_exp1.py</code>	25	0	2 s
<code>check_dirac16complex_exp2.py</code>	34	0	19 s
<code>check_dirac16complex_exp3.py</code>	31	0	1 s
<code>check_dirac16complex_exp4.py</code>	51	0	3 to 7 min
<code>check_dirac16complex_exp5.py</code>	21	0	5 s

That is $25 + 34 + 31 + 51 + 21 = 162$ checker checks. The EXP-4 checker is slow because it runs EXP-4 twice more and integrates reference modes with its own Runge-Kutta and Magnus methods.

With the pinned package versions of Section 3.5, on Windows, the final Git command again printed nothing: the checker reports and the analysis files are byte-identical too. That byte identity depends on the numpy version and on the platform. With numpy 2.5.3 on Windows (measured during the review of this guide) every check still passed, but `fits.json`, `fits_scan.csv` and some `python-check-report.json` files changed in their last digits (for example `w0` of one fit from `-6.04650739995862385e-01` to `-6.04650739995862163e-01`). On Ubuntu the same happened even with the pinned versions (numpy 2.4.6 under Python 3.12.3): all 162 checks and the 10 analysis checks passed, but Git listed the three analysis files and the five `python-check-report.json` files as modified, with changes in the last digits only (a measured deviation such as `3.6716885087884066e-10` can then change in its fifth digit, because it is itself a small difference). That is expected; `git restore artifacts` puts the committed files back.

9.3 Checking a scratch folder (the quick form)

For your own runs into `build/student` (Section 7.2), point the checker at that folder with its output option; without the repeat and refined options two checks are skipped. After the EXP-1 run of Section 7.2, in any shell:

```
python scripts/check_dirac16complex_exp1.py --output build/student
```

It prints `check_count=23` and `failed_check_count=0`. The EXP-3 checker also reads the analysis, so run EXP-3, the analysis and the checker in this order. PowerShell:

```
& $bin exp3 --output build/student
python scripts/analyze_dirac16complex_exp3.py --output build/student
python scripts/check_dirac16complex_exp3.py --output build/student
```

Git Bash, macOS and Linux:

```
$bin exp3 --output build/student
python scripts/analyze_dirac16complex_exp3.py --output build/student
python scripts/check_dirac16complex_exp3.py --output build/student
```

The analysis prints `check_count=10` and the checker `check_count=29`. EXP-2, EXP-4 and EXP-5 work like EXP-1 (run the experiment into `build/student`, then its checker) and give 32, 49 and 19 checks in the quick form. If the EXP-3 checker runs before the analysis, `fits.json` is missing and it reports one check fewer (28 in the quick form, 30 in the full form).

10 The Jupyter notebook

10.1 What it is

`notebooks/dirac16complex_dark_sector.ipynb` is a Python 3 notebook of 23 cells, 8 of them code. For each experiment it runs the program into the scratch folder `build/notebook-run`, checks

that every file the program writes is byte-identical to the committed one (and that the three files of the EXP-3 analysis, whose last digits depend on the numpy version, agree value by value), recomputes the key physics from the raw spinor columns, draws 17 figures into `artifacts/dirac16complex/numerics/figures/`, and ends with a gauntlet of 71 assertions. It finds the program through the environment variable `DIRAC16_BIN` or at the release path of Section 5.1, so build the program first. Its driver is adapted, with attribution, from the rustSolveIt engine's `planet_Mercury/notebook` (Section 16).

10.2 Running it headless

The standard-library runner executes every cell in order and writes the outputs back into the notebook only if every cell succeeds. In any shell:

```
python notebooks/run_notebook.py notebooks/dirac16complex_dark_sector.ipynb
```

It prints the notebook's output while it runs (about 2 to 3 minutes) and ends with

```
PASS - prose_numbers_match_reports: 72 numbers quoted in the markdown re-read ...
ALL CHECKS PASSED
ok notebooks/dirac16complex_dark_sector.ipynb (8 cells)
1 ok, 0 failed
```

(on Windows the paths in these lines are printed with backslashes). Jupyter's own executor writes an executed copy instead. PowerShell:

```
$nb = "notebooks/dirac16complex_dark_sector.ipynb"
$opts = "--output-dir", "build/nbconvert", "--ExecutePreprocessor.timeout=3600"
python -m nbconvert --to notebook --execute $nb @opts
```

Git Bash, macOS and Linux:

```
python -m nbconvert --to notebook --execute notebooks/dirac16complex_dark_sector.ipynb \
    --output-dir build/nbconvert --ExecutePreprocessor.timeout=3600
```

`nbconvert` comes with JupyterLab (Section 3.5). Then audit both executed copies. PowerShell:

```
$copy = "build/nbconvert/dirac16complex_dark_sector.ipynb"
python notebooks/check_notebook.py $nb --also $copy
```

Git Bash, macOS and Linux:

```
python notebooks/check_notebook.py notebooks/dirac16complex_dark_sector.ipynb \
    --also build/nbconvert/dirac16complex_dark_sector.ipynb
```

Expected output:

```
ok notebooks/dirac16complex_dark_sector.ipynb: all structure and execution rules
pass (23 cells, 8 code cells, 71 gauntlet checks, 17 figures)
ok build/nbconvert/dirac16complex_dark_sector.ipynb: all structure and execution
rules pass (23 cells, 8 code cells, 71 gauntlet checks, 17 figures)
ok cross-check: both executions printed identical gauntlet results and figure hashes
```

(each result is one line on your screen). On Windows with the pinned package versions of Section 3.5, the Git check of Section 7.4 still printed nothing afterwards: the executed notebook and the 17 figures were byte-identical to the committed ones. The notebook prints no folder name, so a clone in a folder with another name gives the same bytes. With numpy 2.5.3 and matplotlib 3.11.2 on Windows the gauntlet passed as well and the figures were byte-identical, but the executed notebook differed in the lines where the analysis prints its last digits. On Ubuntu with the win11 engine and the pinned versions the gauntlet and the audit passed too, but all 17 figures and the notebook differed in their bytes (the PNG files that the same matplotlib version writes on Linux are not byte-identical to those it writes on Windows). An earlier version of the notebook compared the analysis files byte for byte and therefore stopped on Ubuntu and with numpy 2.5.3 on Windows; it now compares them value by value (relative 10^{-6}), because the Nelder-Mead fit parameters of the analysis move by up to about 10^{-7} relative from one numpy build to another. `git restore artifacts notebooks` puts the committed files back. The nbconvert route may print a `RuntimeWarning` about the Proactor event loop on Windows; it is harmless.

10.3 Running it interactively

With JupyterLab installed, in any shell:

```
python -m jupyterlab notebooks/dirac16complex_dark_sector.ipynb
```

A browser tab opens with the notebook. JupyterLab shows the folder `notebooks`, and the notebook finds the repository root by itself. If you are asked for a kernel, choose Python 3 (ipykernel). Click the first cell and press Shift+Enter repeatedly (each press runs one cell and moves to the next), or use the menu Run, Run All Cells. If no browser opens, start it like this instead and open the printed address, which begins with `http://localhost:8888/lab?token=`, yourself:

```
python -m jupyterlab --no-browser notebooks/dirac16complex_dark_sector.ipynb
```

To stop JupyterLab, press Ctrl+C twice in the terminal. The notebook is generated by `notebooks/build_dirac16complex_notebook.py`: change the builder, not the notebook, and after rebuilding run `run_notebook.py` again, because the builder writes an unexecuted notebook.

11 The Mathematica notebook (optional)

`notebooks/Dirac16ComplexDarkSector.nb` is an independent cross-check in the Wolfram Language. It loads the exact packages `wolfram/Dirac16ComplexAlgebra.wl` and `wolfram/Dirac16ComplexGeometry.wl`, derives each experiment's reduced system symbolically from the covariant field equation and compares it with the program's equations, re-integrates each experiment with `NDSolve` and




Figure 1: The EXP-3 equation of state $w(a)$ for the five values of x_0 , with the Unite CPL line and the constant $w = -0.764$ band, as the notebook draws it




Figure 2: EXP-4: the thermal gas goes from $w = 1/3$ (radiation) towards $w = 0$ (dust) as the universe expands; the CVODE mode sum agrees with kinetic theory




Figure 3: EXP-5: after t^* the Hilbert norm grows super-exponentially, following the WKB exponent $2W(t)$, while E^2 is negative

compares with the committed CSV columns, runs the program's `print-config` through `RunProcess`, draws 8 figures into `artifacts/dirac16complex/numerics/figures/mathematica/` and ends with 49 checks. It needs the built program (Section 5).

It is new work: none of the three `rustSolveIt` repositories contains a Mathematica notebook or package (no `.nb`, `.wl` or `.wls` file; each holds 294 Jupyter notebooks), which was verified by listing their full Git trees. It is modelled on the notebook `DiracTriality.nb` of the `dirac` repository (<https://github.com/once-ere/dirac>) and its build and verify scripts.

Evaluate it headless (about 4 to 7 minutes on the test computer, up to 10 minutes while other programs kept it busy), in any shell:

```
wolframscript -file scripts/verify_dirac16complex_mathematica_notebook.wls
```

Expected output at the end:

```
input_cell_count=37
failed_evaluation_count=0
message_count=0
notebook_check_count=49
failed_notebook_check_count=0
...
dirac16complex_mathematica_notebook=OK
```

It rewrites `artifacts/dirac16complex/numerics/mathematica-report.json` and the 8 figures; on Windows the Git check of Section 7.4 printed nothing afterwards. The notebook itself is generated by

```
wolframscript -file scripts/build_dirac16complex_mathematica_notebook.wls
```

which writes the same bytes again. To work with it interactively, open the `.nb` file in Mathematica (the free Wolfram Engine has no notebook window) and choose Evaluation, Evaluate Notebook; it finds the repository from the notebook's own location. The interactive route was not tested for this guide.

12 Rebuilding the PDF documents (optional)

Every document in `provenance/` is written in Markdown and converted to LaTeX and PDF by one command, which runs the converter twice, `pdflatex` three times into two fresh folders, requires warning-free logs and two byte-identical PDFs, and compares the PDF with the edition registered in `provenance/pdf-specifications.json`. For this guide, in PowerShell:

```
$guide = "provenance/DIRAC16COMPLEX_STUDENT_GUIDE.md"
python scripts/build_provenance_pdf.py --developer-layout $guide
```

Git Bash, macOS and Linux:

```
guide=provenance/DIRAC16COMPLEX_STUDENT_GUIDE.md
python scripts/build_provenance_pdf.py --developer-layout $guide
```

This guide uses the builder's developer layout (ragged table columns and breakable code); without that option the command builds a different LaTeX file and fails. **Careful:** in doing so it overwrites the committed `provenance/DIRAC16COMPLEX_STUDENT_GUIDE.tex` (the PDF is not copied). If you ran it without the option, either run it again with the option, which writes the committed bytes back, or restore the file with `git restore provenance/DIRAC16COMPLEX_STUDENT_GUIDE.tex`.

It prints one `check_NAME=true` line per check, then `check_count=14`, `failed_check_count=0` and `provenance_pdf=OK`. The other documents are built without that option, for example `python scripts/build_provenance_pdf.py provenance/DIRAC16COMPLEX_PRIMORDIAL_FIELD.md`. `pdflatex` always runs with the repository root as its working folder, because the figure paths are relative to it.

The registered PDF bytes belong to the TeX installation that registered them (MiKTeX 26.5 on Windows). With another TeX installation the document still builds warning-free and byte-identically twice, but the check `registeredSha256` is false, the PDF is not copied, and the command exits with 1; on Ubuntu with TeX Live 2023 exactly this happened (12 of 14 checks true). The builder's register option, which records a new edition in the registry, is for the maintainer of a document only.

13 Changing parameters: exercises with answers

The physical parameters are constants at the top of each file `studies/dirac16complex_cosmology/src/expN.rs`; the command line changes only the tolerances and the output folder. Always send changed runs into a scratch folder with the output option, as below, so the committed files stay intact. After editing a source file, rebuild (Section 5.1); to undo the edit, run `git restore` with the file name and rebuild again.

13.1 Tolerances decide whether the checks pass

Exercise. Run EXP-1 with `rtol 10-10` instead of `10-12`. Predict which self-checks fail.

PowerShell:

```
& $bin exp1 --output build/ex-rtol --rtol 1e-10
```

Git Bash, macOS and Linux:

```
$bin exp1 --output build/ex-rtol --rtol 1e-10
```

Answer. The run needs fewer steps (`solver_steps=18458`) and the conserved quantities drift more: `rho_frozen_all_runs` ($1.2\text{e-}7$), `pressures_and_S_frozen_eigenstate_runs`, `hilbert_norm_conserved` and `krein_norm_conserved` ($5.4\text{e-}8$) and `lambda_run_meff_constant` ($1.4\text{e-}8$) FAIL against their $1\text{e-}8$ limits, while `exact_solution_all_runs` ($7.8\text{e-}8$ against $1\text{e-}7$) still passes. The last line is **FAILURE** and the exit code is 1. The limits were set from the physics, and the default tolerance was tightened until they hold, never the other way round.

13.2 Convergence

Exercise. Run EXP-1 with the refined option (Section 7.1) into `build/ex-refined`. By how much does the distance from the exact solution shrink?

PowerShell:

```
& $bin exp1 --output build/ex-refined --refined
```

Git Bash, macOS and Linux:

```
$bin exp1 --output build/ex-refined --refined
```

Answer. The tolerances become `rtol 1e-13`, `atol 1e-15` and `max_step 0.01`, the step count grows to 57960, and the largest distance from the exact solution (`maxExactError` in `summary.json`) falls from $6.2\text{e-}9$ to $1.3\text{e-}10$: the solution converges.

13.3 Predicting EXP-1 from the formulas

Exercise. For the positive-energy eigenmode with $K = 2$ and $\lambda = 0$, predict ε , ρ , p_0 , $\bar{p}$, w , KE_L and PE_L , then read them from `run_A1_K2_pos_Bp.csv`. Hint: on an eigenmode $\varepsilon = E$ and $p_0 = K^2/E$, and only p_0 is nonzero.

The Python lines below read the first and last row. PowerShell:

```
@'
import csv
path = "artifacts/dirac16complex/numerics/exp1/run_A1_K2_pos_Bp.csv"
rows = list(csv.DictReader(open(path)))
for key in ("energy_mode", "rho", "p_0", "p_mean", "w", "KE_L", "PE_L"):
    print(key, float(rows[0][key]), float(rows[-1][key]))
'@ | python -
```

Git Bash, macOS and Linux:

```
python - <<'EOF'
import csv
path = "artifacts/dirac16complex/numerics/exp1/run_A1_K2_pos_Bp.csv"
rows = list(csv.DictReader(open(path)))
for key in ("energy_mode", "rho", "p_0", "p_mean", "w", "KE_L", "PE_L"):
    print(key, float(rows[0][key]), float(rows[-1][key]))
EOF
```

Answer. $E = \sqrt{1+4} = 2.23607 = \varepsilon = \rho$; $p_0 = K^2/E = 1.78885$; $\bar{p} = p_0/7 = 0.25555$; $w = K^2/(7E^2) = 4/35 = 0.11429$; $KE_L = PE_L = E/2 = 1.11803$. The first and last rows agree to about 10^{-9} : the field is frozen. Note that $KE_L = PE_L$ although $w \neq 0$: for a moving mode the scalar-field relation $p = KE_L - PE_L$ does not hold (Section 6.10).

13.4 Solving the EXP-2 constraint yourself

Exercise. Open `studies/dirac16complex_cosmology/src/exp2.rs` in a text editor (Notepad, TextEdit, nano or any code editor) and change the line `pub const HUBBLE_C0: f64 = -0.2`; to `-0.3`; save the file. Predict C_0 , Θ_0 , S_0 for $x_0 = 0$ and the time at which H_c changes sign. Then rebuild (Section 5.1) and run, in PowerShell:

```
& $bin exp2 --output build/ex-hc
```

or in Git Bash, macOS and Linux:

```
$bin exp2 --output build/ex-hc
```

Answer. $C_0 = 3 + 3(0.09) + 9(-0.3) = 0.57$, $\Theta_0 = 3 - 0.9 = 2.1$, $S_0 = 0.57$ (and 0.95, 0.38 for $x_0 = -0.4, 0.5$), $\alpha = 7S_0/12 = 0.3325$; $H_c V = H_{c0} + \beta t$ with $\beta = S_0/6 = 0.095$ changes sign at $t = 0.3/0.095 = 3.158$. The run gives these values in `summary.json` (keys `S0`, `constraintLhs0`, `theta0`, `alpha`, `extraTimeTurnTime`), and 14 of the 15 self-checks pass. `late_time_isotropic_dust` FAILS ($1.17e-3$ against its $1e-3$ limit): with the larger initial anisotropy, the fixed end point $V/V_0 = e^{18.5}$ is no longer late enough for the anisotropy to fall below the limit. A self-check with an a-priori limit tests the physics of the chosen parameters, not only the solver. Undo the edit with `git restore studies/dirac16complex_cosmology/src/exp2.rs` and rebuild.

13.5 From x_0 to (w_0, w_a)

Exercise. For $x_0 = -0.25$ predict w_0 , w_a , the redshift where $\rho_\psi = 0$ and the redshift of the phantom crossing $w = -1$. Then read the fine scan of the analysis.

PowerShell:

```
@'
import csv
```

```

path = "artifacts/dirac16complex/numerics/exp3/fits_scan.csv"
rows = list(csv.DictReader(open(path)))
row = [r for r in rows if abs(float(r["x0"]) + 0.25) < 1e-9][0]
for key in ("w0_tangent", "wa_tangent", "z_zero", "z_cross", "z_bounce"):
    print(key, float(row[key]))
'@ | python -

```

Git Bash, macOS and Linux:

```

python - <<'EOF'
import csv
path = "artifacts/dirac16complex/numerics/exp3/fits_scan.csv"
rows = list(csv.DictReader(open(path)))
row = [r for r in rows if abs(float(r["x0"]) + 0.25) < 1e-9][0]
for key in ("w0_tangent", "wa_tangent", "z_zero", "z_cross", "z_bounce"):
    print(key, float(row[key]))
EOF

```

Answer. $w_0 = x_0/(1 + x_0) = -1/3$; $w_a = 3x_0/(1 + x_0)^2 = -4/3$; $\rho_\psi = 0$ at $a = |x_0|^{1/3} = 0.62996$, i.e. $z = 1/a - 1 = 0.58740$; $w = -1$ where $\rho + p = 0$, at $a = (2|x_0|)^{1/3} = 0.79370$, $z = 0.25992$. The script prints -0.3333 , -1.3333 , 0.58740 , 0.25992 and the bounce $z_b = 0.74542$, which needs the cubic of Section 6.13.

Exercise. Which x_0 gives $w_0 = -0.9$, and what is its w_a ? **Answer.** $x_0 = w_0/(1 - w_0) = -0.47368$ and $w_a = -5.13$: the closer w_0 is to -1 , the faster the condensate evolves, the opposite of the slowly varying Unite fit ($w_a = -0.60$). The scan row $x_0 = -0.474$ gives $w_0 = -0.90114$, $w_a = -5.1396$.

Exercise. Now let the program itself integrate $x_0 = -0.25$. In `studies/dirac16complex_cosmology/src/exp3.rs` change the line `pub const X0_VALUES: [f64; 5] = [-0.462654, -0.433107, -0.3, -0.2, 0.0]`; so that -0.2 becomes -0.25 , and save the file. Predict what CVODE will measure for $x_0 = -0.25$: w_0 , w_a , the redshifts where $\rho_\psi = 0$ and where $w = -1$, and today's deceleration parameter $q_0 = \frac{1}{2} \sum_i \Omega_i(1 + 3w_i)$ (radiation has $w = 1/3$, matter $w = 0$). Then rebuild (Section 5.1) and run, in PowerShell:

```
& $bin exp3 --output build/ex-x0
```

or in Git Bash, macOS and Linux:

```
$bin exp3 --output build/ex-x0
```

Read what the run with $\mu = 3$ measured from its `summary.json`. PowerShell:

```

@'
import json
path = "build/ex-x0/exp3/summary.json"
runs = json.load(open(path))["runs"]
m = [r for r in runs if r["id"] == "x0_m0p25_mu3"][0]["measured"]
print("w0", m["w0"], "wa", m["waTangent"], "q0", m["q0"])
print("z_zero", m["rhoZeros"][0]["z"], "z_cross", m["phantomCrossings"][0]["z"])
print("z_q_sign_change", m["decelerationSignChanges"][0]["z"])
'@ | python -

```

Git Bash, macOS and Linux:

```
python - <<'EOF'
import json
path = "build/ex-x0/exp3/summary.json"
runs = json.load(open(path))["runs"]
m = [r for r in runs if r["id"] == "x0_m0p25_mu3"][0]["measured"]
print("w0", m["w0"], "wa", m["waTangent"], "q0", m["q0"])
print("z_zero", m["rhoZeros"][0]["z"], "z_cross", m["phantomCrossings"][0]["z"])
print("z_q_sign_change", m["decelerationSignChanges"][0]["z"])
EOF
```

Finally run the EXP-3 checker on the new folder, in any shell:

```
python scripts/check_dirac16complex_exp3.py --output build/ex-x0
```

Answer. $w_0 = -1/3$ and $w_a = -4/3$, as in the first exercise of this section; $\rho_\psi = 0$ at $z = 0.58740$ and $w = -1$ at $z = 0.25992$; and $q_0 = \frac{1}{2}(\Omega_m + 2\Omega_r) = 0.15259$, because $1 + 3w_0 = 0$: a component with $w = -1/3$ neither accelerates nor decelerates the expansion, so the matter decelerates it. The script prints $w_0 = -0.33333$, $w_a = -1.33333$ (a finite difference of the CVODE w , so its last digits differ from $-4/3$), $q_0 = 0.15259$, the two redshifts where the closed forms put them (to about 10^{-9}), and a sign change of q at $z = 0.0996$: in this model the expansion accelerated before $z = 0.0996$ and decelerates today, the reverse of the observed history. Beyond $z = 0.25992$ the effective mass is negative, so there the run is outside the one-mode picture (Section 6.10). All 14 self-checks pass. The checker prints `check_count=28` and `failed_check_count=2`: `check_parametersMatchContract` and `check_muIndependence` are false because it looks for the specified x_0 values, among which -0.2 is now missing (the μ -independence it does measure, $2.8e-9$, is far inside its $1e-8$ limit). Undo with `git restore studies/dirac16complex_cosmology/src/exp3.rs` and rebuild.

13.6 Moving the EXP-5 turning point

Exercise. In `studies/dirac16complex_cosmology/src/exp5.rs` change the line `pub const Q_VALUES: [f64; 2] = [0.05, 0.1]`; to `[0.05, 0.2]` and save. Predict t^* and the end time for $q = 0.2$. Then rebuild and run, in PowerShell:

```
& $bin exp5 --output build/ex-q
```

or in Git Bash, macOS and Linux:

```
$bin exp5 --output build/ex-q
```

Answer. $t^* = \ln(1/0.2) = \ln 5 = 1.60944$ and $t_{\text{end}} = t^* + 3 = 4.60944$. All 7 self-checks pass; the new files are `run_q0p2_Cp.csv` and `run_q0p2_Cm.csv`; `summary.json` gives `tStar 1.6094379124341003`, a final $u^\dagger u$ of 1.32×10^{16} and WKB deviations of $1.0e-3$ (leading order) and $2.4e-4$ (first order). The EXP-5 Python checker compares the parameters with the study's specification and reports the mismatch, as it should: run on `build/ex-q`, it prints `check_parametersMatchContract=false` and `failed_check_count=1` (of 19). Undo with `git restore studies/dirac16complex_cosmology/src/exp5.rs` and rebuild.

13.7 Massless quanta are not created

Exercise. Before looking, say what na^3 EXP-4 should find for $m = 0$. **Answer.** Zero: a massless spinor's mode equation is conformally invariant, and a radiation or de Sitter universe is conformally flat. The run finds $na^3 = 1.8 \times 10^{-24}$ for $m = 0$, pure roundoff, against 1.45×10^{-3} for $m = 0.1$ and 4.99×10^{-3} for $m = 0.5$ (key `nA3` of `pair.masses` in `exp4/summary.json`, the last row of column `n_a3_adiabatic` of `pair_history.csv`).

14 Troubleshooting

Symptom	Cause	What to do
LNK1104: cannot open file ...\\deps\\...rllib while linking on Windows	the path is longer than 260 characters	clone into a short folder such as <code>\$HOME\\src</code> (Section 4.1)
error: linker link.exe not found on Windows	the Microsoft C++ build tools are missing (a silent winget installation of rustup does not offer them)	install them with the first command of Section 3.2 and open a new terminal
error: linker cc not found on Linux, or a message on macOS that the command line developer tools are missing	no C linker	install <code>build-essential</code> (Section 3.4) or the Xcode command line tools (Section 3.3)
rustc or cargo not found right after installing	the terminal was opened before the installation	open a new terminal; on macOS and Linux also <code>source "\$HOME/.cargo/env"</code>
the program stops at once with an illegal-instruction error (STATUS_ILLEGAL_INSTRUCTION on Windows, SIGILL elsewhere)	the processor has no FMA, which <code>.cargo/config.toml</code> requires (Section 5.2)	use a computer with an x86-64 processor from 2013 or later
error: failed to load manifest for dependency ccode_rs, caused by failed to read ...vendor/rustSolveIt/.../Cargo.toml	the engine was not fetched	run the setup script (Section 4.3)
vendor/rustSolveIt is at ..., expected ...	the folder holds another engine	delete it and run the setup script again (Section 4.4)
vendor/rustSolveIt is an incomplete checkout (an interrupted or failed download); remove it and rerun	an earlier engine download stopped halfway	<code>Remove-Item -Recurse -Force vendor/rustSolveIt</code> (PowerShell) or <code>rm -rf vendor/rustSolveIt</code> (bash), then run the setup script again
cargo prints Blocking waiting for file lock	another cargo command is running	wait for it to finish

Symptom	Cause	What to do
error: failed to remove file ...dirac16complex_cosmology.exe, caused by Access is denied. (os error 5), on Windows	the program is still running (or an antivirus or synchronisation tool holds the file)	wait until the run has finished, then build again; work outside synchronised folders
running scripts is disabled on this system	Windows PowerShell 5.1 blocks scripts	use <code>pwsh</code> , or <code>powershell -ExecutionPolicy Bypass -File ...</code> (Section 4.3)
UnicodeEncodeError: 'charmap' codec can't encode character when Python output is redirected to a file or pipe on Windows	Python writes redirected output in the code page cp1252	make Python use UTF-8 for the session: <code>\$env:PYTHONUTF8 = "1"</code> (PowerShell) or <code>export PYTHONUTF8=1</code> (Git Bash)
jupyter or another script is not recognized, and pip warned that its folder is not on PATH	pip installed it into the per-user Scripts folder	use <code>python -m jupyterlab</code> and <code>python -m nbconvert</code> , as this guide does
error: externally-managed-environment from pip	macOS or Linux protects its system Python	use the virtual environment of Section 3.5
No module named numpy in a new terminal on macOS or Linux	the virtual environment is not active	<code>source ~/.venvs/dirac16/bin/activate</code>
No module named nbconvert	JupyterLab is not installed	<code>python -m pip install jupyterlab</code>
the Git check of Section 7.4 lists 14 changed files after all	the linux or macos engine is in use (Section 4.5)	fetch the win11 engine and rebuild; <code>git restore artifacts</code> restores the files
the notebook stops with <code>AssertionError('fresh_program_outputs_byte_identical')</code>	the same cause	the same remedy
after the checkers or the analysis, Git lists <code>fits.json</code> , <code>fits_scan.csv</code> or <code>python-check-reports.json</code> files as modified, with only last-digit changes	a numpy version other than the pinned 2.4.6 (Section 3.5), or a platform other than Windows (Section 9.2)	expected, every check still passes; on Windows install the pinned versions for byte identity; <code>git restore artifacts</code> puts the committed files back
the notebook stops with <code>AssertionError('fresh_analysis_outputs_numerically_equal')</code>	the EXP-3 analysis files differ by more than the version effects (relative 10^{-6})	rerun <code>scripts/analyze_dirac16complex_exp3.py</code> after <code>git restore artifacts</code> ; if it persists, report it, it is not a version effect
the EXP-3 checker reports 30 checks instead of 31	it ran before the analysis	run <code>analyze_dirac16complex_exp3.py</code> first

Symptom	Cause	What to do
wolframscript is not recognized	WolframScript is not installed or not on PATH	install the Wolfram Engine or Mathematica; on Windows add its folder for the session with <code>\$env:Path += ";C:\Program Files\Wolfram Research\WolframScript"</code>
wolframscript asks for a Wolfram ID or reports that the kernel is not activated	the Wolfram Engine was never activated	run <code>wolframscript -activate</code> yourself once
the PDF build lists <code>latex_warning=</code> lines and fails the check <code>logWarningFree</code>	a LaTeX package is missing or a line is too wide	read <code>build/NAME/pdf-a/NAME.log</code> ; let MiKTeX install missing packages, or install <code>texlive-latex-recommended</code> and <code>lmodern</code> on Linux
the PDF build fails only <code>registeredSha256</code> and <code>provenancePdfCopy</code>	a different TeX installation made different bytes	expected (Section 12); the PDF was still built in <code>build/NAME/pdf-a/</code>
the PDF build stops at once with <code>ERROR: pdflatex not found ...</code> (older versions of the builder printed <code>ERROR: [WinError 2] The system cannot find the file specified or No such file or directory: 'pdflatex'</code>)	no TeX distribution is installed, or pdflatex is not on PATH	install MiKTeX, MacTeX or TeX Live (Section 3) and open a new terminal
the guide's PDF build fails and <code>git status</code> lists <code>provenance/DIRAC16COMPLEX_STUDENT_GUIDE.tex</code> as modified	the build ran without the <code>developer-layout</code> option (Section 12)	run it again with that option, or <code>git restore provenance/DIRAC16COMPLEX_STUDENT_GUIDE.tex</code>

15 Glossary

- a : the scale factor of 3-space ($a = 1$ today); in EXP-2 the common scale factor of x_1, x_2, x_3 . b , c : the scale factors of the hidden space x_0 and of the extra times x_5, x_6, x_7 .
- **Adams-Moulton**: a family of implicit multistep methods for non-stiff ODEs (Section 6.16).
- **atol**, **rtol**: absolute and relative error tolerances of CVODE.
- $B = -iC\gamma^4$: the Hermitian matrix that defines the Krein inner product $u^\dagger Bu$.
- **BDF**: backward differentiation formulas, implicit multistep methods for stiff ODEs.
- $|\beta_k|^2$: the weight of a mode on the negative-energy states: the number of created particle-antiparticle pairs per mode.

- **bounce**: the moment at which $E^2 = H^2/H_0^2$ reaches 0 in EXP-3, so that the universe stops contracting backward in time.
- **byte-identical**: two files with exactly the same bytes; Git reports no change.
- $C = \gamma^0\gamma^1\gamma^2\gamma^3$: the charge matrix; $\bar{\Psi} = \Psi^\dagger C$.
- **cargo, rustc, rustup**: Rust’s build tool, compiler and toolchain installer.
- **chirality**: the eigenvalue ∓ 1 of γ^8 ; components 0 to 7 have -1 , 8 to 15 have $+1$.
- **CPL**: the parametrisation $w(a) = w_0 + w_a(1 - a)$, so $w_a = -dw/da$.
- c_s^2 : the sound speed squared $dp/d\rho$; negative means the condensate’s perturbations grow.
- **CSV**: comma-separated values, the output format of the program.
- **CVODE**: the variable-step, variable-order ODE integrator of SUNDIALS.
- D_C, d_L : comoving distance and luminosity distance $(1 + z)D_C$, in units of c/H_0 .
- **dark energy**: the component with negative pressure ($w < -1/3$) that accelerates the expansion.
- **dark matter**: pressureless ($w \approx 0$) matter that does not emit light.
- E : the mode energy, $h^2 = E^2$; in EXP-3 instead the dimensionless expansion rate H/H_0 .
- **effective mass** $M_{\text{eff}} = m + \lambda S$: the mass shifted by the self-interaction.
- $\varepsilon(u) = u^\dagger h u$: the energy of one mode.
- **engine**: the rustSolveIt folder `sundials_rs` with the crates `sundials_core` and `cvode_rs`.
- **equation of state parameter** $w = p/\rho$.
- η : the flat metric $\text{diag}(+1, +1, +1, +1, -1, -1, -1, -1)$.
- **expectation-value rule**: $\langle \Psi^\dagger M \Psi \rangle = u^\dagger B M u$ for a one-particle state on the normalised mode u .
- **FMA**: fused multiply-add, $a \cdot b + c$ with one rounding (Section 5.2).
- **fixed-point iteration, Newton’s method**: the two ways CVODE solves the implicit equation of each step.
- **freezing, thawing**: dark-energy fields whose w falls towards -1 (freezing, $w_a > 0$) or rises from -1 (thawing, $w_a < 0$) as the universe expands, with the formula-consistent signs of Section 1.1.
- **gamma matrices** γ^a : the eight 16 by 16 matrices with $\gamma^a\gamma^b + \gamma^b\gamma^a = 2\eta^{ab}$ (Section 6.3).
- **good sector**: modes without momentum along the extra times; there h is Hermitian.
- **Grassmann-odd**: anticommuting, $\Psi_a\Psi_b = -\Psi_b\Psi_a$.

- $h(t)$: the mode Hamiltonian, $i\dot{u} = hu$ (Section 6.8). h_j : the scale factor of direction j (a different symbol, always with an index).
- H_j , Θ , V : expansion rate of direction j , their sum, and the 7-volume.
- H_0 : today's expansion rate; H_{inf} : the de Sitter rate of EXP-4(b); H_i : the initial rate 0.05 of EXP-4(a).
- **Hilbert norm** $u^\dagger u$, **Krein norm** $u^\dagger Bu$.
- K : the physical momentum (k/a in EXP-4, the hidden-space momentum in EXP-1). k : comoving momentum. q , $Q = qe^t$: extra-time momentum (EXP-5).
- κ : the gravitational coupling $8\pi G$; in EXP-5 the column **kappa** is instead the WKB rate.
- KE_L , PE_L , KE_H , PE_H : the Lagrangian and Hamiltonian kinetic/potential splits (Section 6.10).
- λ : the four-fermion coupling; $U(S) = \frac{\lambda}{2}S^2$.
- **mode**: a plane-wave solution $\Psi = V^{-1/2}e^{ik \cdot x}u(t)$.
- μ : in EXP-3 the reduced frequency $M_{\text{eff}}(a=1)/H_0$; the distance modulus is written `mu_H0fre` in the CSV.
- $N = \ln a$: e-folds, the independent variable of EXP-3.
- Ω_r , Ω_m , Ω_ψ : today's density fractions of radiation, matter and the condensate.
- **phantom**: $w < -1$ with $\rho > 0$; for the condensate it happens exactly when $KE_L < 0$.
- **RHS**: the right-hand side $f(t, Y)$ of $Y' = f(t, Y)$.
- ρ , p , $\bar{p}$: energy density, pressure, mean transverse pressure.
- ρ_{req} : the energy density that 8D Einstein gravity would need to produce the primordial field (EXP-1).
- $S = \bar{\Psi}\Psi$: the scalar density (condensate); $s(u) = u^\dagger(-i\gamma^4)u$ per mode; $\sigma = S/S_0$.
- **scale factor**: the factor $h_j(t)$ that turns coordinate distance into physical distance.
- **spinor connection** Ω_μ , **covariant derivative** D_μ (Section 6.6).
- **state vector**: the real numbers CVODE integrates, laid out as in Sections 6.9 to 6.15.
- **SUNDIALS**: the SUite of Nonlinear and Differential/ALgebraic equation Solvers.
- $t^* = \ln(m/q)$: the time after which $E^2 < 0$ in EXP-5.
- **Unite**: the supernova compilation quoted in the input document ($w_0 = -0.861$, $w_a = -0.60$, constant $w = -0.764$).
- **vielbein**: the frame e^a that turns the curved metric into η .
- w_0 , w_a : the CPL parameters; w_{eff} : the w a 3-space observer infers in EXP-2.

- **WKB:** the approximation $u^\dagger u \propto e^{2W}$ with $W = \int \sqrt{Q^2 - m^2} dt$ for a slowly varying rate.
- x_0 : the hidden space coordinate, and in EXP-2 and EXP-3 also the parameter $\lambda S_0/(2m)$; the meaning is always clear from the context.
- z : the redshift $1/a - 1$; in the primordial field of EXP-1 the variable $6Hx_0$.

16 Credits, licences and verified facts

- **This repository:** GPL-3.0-or-later (see LICENSE); original notebook and physical programme: Patrick L. Nash; publication tooling derived from <https://github.com/once-ere/dirac>. See NOTICE.
- **The engine:** the pure-Rust SUNDIALS 7.8.0 port of the rustSolveIt repositories, BSD-3-Clause as declared in their Cargo manifests (published by the once-ere account; LLNL copyright for SUNDIALS); its deterministic library contains translations of GNU C Library 2.39 under LGPL-2.1-or-later (NOTICE, section 2c). It is fetched by the setup scripts, never stored in this repository.
- **The Jupyter notebook tools** `notebooks/run_notebook.py`, `notebooks/check_notebook.py` and the builder pattern are adapted, with attribution in their headers, from `planet_Mercury/notebook` of rustSolveIt (the `md()` and `code()` helpers, `find_binary()` and `run()` with the rule that the last printed line must be `SUCCESS`, a `gauntlet()` of assertions, the standard-library runner and the auditor).
- **The Mathematica notebook** is new (Section 11).
- **Verified while writing this guide:** the pinned commits and the notebook counts of the three engine repositories (294 Jupyter notebooks and no `.nb`, `.wl` or `.wls` file in each); the differences between the engines (Section 4.5); the byte-for-byte reproduction of all Rust outputs with the `win11` engine on Windows 11 and on Ubuntu 24.04; and every expected output quoted above.
- **Not established by this guide:** anything about macOS, and anything physical beyond the committed results. The scientific conclusions, with their assumptions and limits, are in `DIRAC16COMPLEX_DARK_SECTOR_NUMERICS`.