

The `posim` Command Language

Complete Grammar & Notebook Guide

physical_object_simulator

July 21, 2026

Contents

1	What is this document about?	2
2	Lexical structure (what the lexer sees)	2
2.1	Token kinds	3
2.2	Keywords	3
2.3	Magics	4
3	The grammar (what the parser accepts)	4
4	The type system (what values exist)	6
5	Command semantics	6
5.1	NEW — create an object	6
5.2	SET / GET — write and read any field	8
5.3	STEP and RUN — integrate (always via SUNDIALS)	10
5.4	METHOD — choose the integrator	10
5.5	Observables, bookkeeping, help	11
5.6	COLLIDE and CONTACTS — rigid-body collisions	11
5.7	BOX — the rigid bounding box	12
5.8	User definitions: DEF, LET, FUNCS, SHOW	13
6	The notebook (cells, editing, magics)	14
6.1	Cells	14
6.2	State is cumulative	15
6.3	Magics	15
6.4	Scripts	15
7	JupyterLab in one paragraph	15
8	The stack machine (what runs your line)	15
9	Fourteen worked examples	16
9.1	Example 1 — an eccentric Kepler orbit and the Runge–Lenz compass	16
9.2	Example 2 — a thrown ball vs. the textbook formula	16
9.3	Example 3 — cyclotron motion: expressions as arguments	17

9.4	Example 4 — the tennis-racket theorem (Dzhanibekov effect)	17
9.5	Example 5 — three bodies, then surgery with <code>DEL</code>	18
9.6	Example 6 — magnetic torque (and why ENERGY grows)	18
9.7	Example 7 — fixing a typo in an old cell with <code>%edit</code>	19
9.8	Example 8 — checking the simulator against itself	19
9.9	Example 9 — hand-built tensors and a quaternion orientation	20
9.10	Example 10 — reproducibility: <code>%save</code> , <code>%reset</code> , <code>%load</code>	20
9.11	Example 11 — watching a Kepler orbit live, then running it backward	21
9.12	Example 12 — driving the camera from the notebook	22
9.13	Example 13 — the box of shapes: every body type in a rigid, infinitely massive box	23
9.14	Example 14 — two dumbbells from a user-defined function	25

10 Error message tour 27

1 What is this document about?

posim is the front end of the `physical_object_simulator`. Instead of writing Rust code to create objects and run physics, you type short *commands* — one per line — into a *notebook*. Each command line is:

1. chopped into *tokens* by a *lexer* (like the classic Unix tool `lex/flex`);
2. checked against a *grammar* and compiled into a small program by a *parser* (like `yacc/bison`);
3. executed by a *stack machine* — a tiny computer whose only memory is a stack of values — which reads and writes the simulator exclusively through its public `get/set` functions.

You never see steps 1–3; you type a line, press Enter (or shift-enter in JupyterLab), and see the result. This document specifies exactly what you may type.

There are three ways to talk to the same language:

mode	start with	who it is for
notebook REPL	<code>cargo run</code> (or <code>posim</code>)	humans at a terminal
script	<code>posim -script file</code>	batch runs, reproducibility
machine	<code>posim -machine</code>	programs, and the JupyterLab kernel

2 Lexical structure (what the lexer sees)

A command line is a sequence of *tokens* separated by optional whitespace. Everything from a `#` to the end of the line is a *comment* and is ignored.

2.1 Token kinds

token	examples	rules
keyword	NEW, set, Run	case-insensitive; list in §2.2
identifier	obj0, position	a letter or <code>_</code> , then letters, digits, <code>_</code>
string	"ball", "dumbell10"	double-quoted, with the escapes <code>\</code> " <code>\\</code> <code>\n</code> ; strings name objects (NEW ... AS, §5.1) and are passed to user functions (§5.8)
number	2, 0.5, .5, 1e-3	64-bit float; scientific notation allowed; a leading <code>-</code> is <i>not</i> part of the number — it is the negation operator
punctuation	[] { } () , . =	brackets build vectors, braces enclose initializers, <code>.</code> builds dotted paths
operators	+ - * /	ordinary arithmetic

If the lexer meets a character it does not know (say `@`), it stops with an error naming the *column* (character position, starting at 1):

```
Err[1]: lexical error at column 10: unexpected character '@'
```

2.2 Keywords

```
NEW SET GET DEL DELETE LIST STEP RUN STEPS METHOD ADAMS BDF SPRK ENERGY COM MOMENTUM
ANGMOM LAPLACE HELP POINT SPHERE CUBOID TORUS DISK CYLINDER BOX RESET
```

and, for the graphical scene window (documented in `scene_info.pdf`; Examples 11–12 show live sessions):

```
SCENE CREATE CLOSE DESTROY TRANSLATE ROTATE ZOOM IN OUT HIDE SHOW REFRESH REDRAW START
STOP PAUSE REVERSE SET_TIME_STEP SETTIMESTEP STATUS EVENTS ALL
```

and, for rigid-body collisions (§5.6):

```
COLLIDE CONTACTS ON OFF
```

and, for named objects, session variables and user functions (§5.1, §5.8):

```
AS LET FUNCS DUMBELL
```

(DESTROY is an alias for CLOSE; SETTIMESTEP for SET_TIME_STEP; the spellings CUBE and DISC are lexer aliases for CUBOID and DISK; FUNCTIONS for FUNCS; and the single-b spelling DUMBELL for DUMBELL. `collisions` is deliberately **not** a keyword so the field path `system.collisions` keeps its own spelling. DEF is not a keyword either: a line starting DEF is a **line form** recognized before the ordinary grammar — see §3 and §5.8.)

Keywords are reserved *at the start of paths*, but **field names may reuse keyword spellings** — `obj0.momentum` and `system.method` work even though MOMENTUM and METHOD are keywords, because after a dot (or inside NEW { ... }) the parser accepts either an identifier or a keyword as a field name. The same holds for the scene keywords: making SHOW or IN reserved does not stop you from ever using those spellings as field names after a ..

2.3 Magics

A line whose first character is % is a *notebook magic* (§6.3) and is handled by the notebook itself; it never reaches the lexer.

3 The grammar (what the parser accepts)

The grammar in EBNF (Extended Backus–Naur Form: [x] means optional, {x} means zero-or-more repetitions, | separates alternatives):

```

line      := command | magic ;

command   := "NEW" shape [ "AS" (IDENT | STRING) ]
              [ "{" init { "," init } "}" ]
              (* AS registers a user
                name for the object *)

          | "SET" path "=" expr
          | "GET" path
          | "DEL" NUMBER
          | "LIST"
          | "STEP" expr              (* advance by dt      *)
          | "RUN" expr [ "STEPS" NUMBER ] (* advance by t, n outs *)
          | "METHOD" ( "ADAMS" | "BDF" | "SPRK" IDENT [ NUMBER ] )
          | "ENERGY" | "COM" | "MOMENTUM" | "ANGMOM"
          | "LAPLACE" NUMBER
          | "RESET" | "HELP"
          | "SCENE" scenecmd          (* graphical scene    *)
          | "COLLIDE" [ "ON" | "OFF" ] (* bare: report status *)
          | "CONTACTS"                (* list last contacts *)
          | "LET" IDENT "=" expr      (* session variable   *)
          | "FUNCS"                   (* list user functions *)
          | "SHOW" IDENT              (* print a function   *)
          | "BOX" [ "OFF" | expr ]    (* rigid bounding box:
              expr = inner side
              length; bare = status;
              OFF removes it      *)

          | expr ;                    (* bare expression    *)
scenecmd  := "CREATE" [ NUMBER ]      (* open window [port] *)
          | "CLOSE"                   (* aka DESTROY        *)
          | "TRANSLATE" term term [ term ] (* camera dx dy [dz] *)
          | "ROTATE" term term         (* camera dyaw dpitch *)
          | "ZOOM" ( "IN" | "OUT" | term ) (* factor > 1 zooms in *)
          | "HIDE" [ NUMBER | "ALL" ]  (* default: ALL        *)
          | "SHOW" [ NUMBER | "ALL" ]
          | "REFRESH"                  (* re-sync from state *)
          | "REDRAW"                   (* re-send full scene *)
          | "START" | "STOP" | "PAUSE" | "REVERSE"
          | "RESET"                    (* re-initialize: all
              values and the time
              return to initial;
              START re-starts    *)

          | "SET_TIME_STEP" term      (* args are term-level:
              -5 is negative five;

```

```

                                parenthesize sums *)
    | "STATUS" | "EVENTS" ;
shape := "POINT" | "SPHERE" | "CUBOID" | "TORUS" | "DISK" | "CYLINDER"
      | "DUMBBELL" ;
                                (* two solid spheres +
                                a rigid rod, one
                                rigid body *)

(* User-defined functions are a LINE FORM handled before this
   grammar: DEF name(param [= default], ...) { body } -- the body is
   newline/-separated commands using the parameters as variables;
   each body line must itself satisfy this grammar. Invocation uses
   the ordinary call syntax name(arg, ...); trailing parameters
   take their defaults. *)
init   := IDENT "=" expr ;
path   := IDENT { "." IDENT } ;
                                (* objN.field[.x|y|z|w],
                                system.field,
                                contactK.field,
                                name.field for
                                AS-registered names *)

expr   := term { ("+" | "-") term } ;
term   := unary { ("*" | "/" ) unary } ;
unary  := "-" unary | atom ;
atom   := NUMBER | STRING | "[" expr { "," expr } "]" | "(" expr ")"
      | IDENT "(" [ expr { "," expr } ] ")" (* builtin or user
                                             function call *)
      | path
      | IDENT ;
                                (* parameter / LET var *)

```

Operator precedence is the usual one: `*` and `/` bind tighter than `+` and `-`; unary minus binds tightest; parentheses override everything.

One subtlety worth learning early: GET takes *only a path*. To do arithmetic with a field, use a *bare expression*:

```

get obj0.position.x - 5      # ERROR -- GET wants just a path
obj0.position.x - 5         # OK -- bare expression

```

A second subtlety — SCENE arguments are *terms*, not full expressions. The scene commands take several numbers in a row with no commas between them. If those numbers were parsed as full expressions, `scene rotate 15 -5` would be read as *one* argument $15 - 5 = 10$ (whitespace never matters to the lexer) and the command would then be missing its second argument. So scene arguments stop one level lower in the grammar, at **term**: `-5` is negative five, `2*2` and `1/3` still work, but a sum or difference must be parenthesized:

```

scene rotate 15 -5           # yaw +15 deg, pitch -5 deg (two arguments)
scene zoom (1 + 0.5)         # a sum needs parentheses
scene translate 2*2 0 1/2     # * and / are fine unparenthesized

```

A third subtlety — bare identifiers compile and resolve at execution. An IDENT alone is an ordinary atom: the constants `pi` and `tau`, a function parameter, or a LET variable (§5.8). The name is looked up when the line *runs*, not when it parses, so a function body may use parameters

freely; a name that is bound to nothing fails at execution with an error that lists the three ways to bind one (LET, a parameter, or a registered object's `name.field` path). A call `IDENT(...)` is a builtin (`dot`, `cross`, `norm`, `normalize`, `sqrt`, `abs`, `sin`, `cos`, `exp`, `log`) when the name matches one, and a user-defined function otherwise.

4 The type system (what values exist)

Every expression evaluates to one of these *values*:

type	written as	notes
number	2, -0.5, 1e-3	64-bit float
vec3	[1, 2, 3]	exactly 3 numeric entries
quaternion	[w, x, y, z]	exactly 4 numeric entries, w first ; assigned to <code>orientation</code> it is renormalized to unit length
mat3	[[a,b,c],[d,e,f],[g,h,i]]	3 rows of 3 numbers
string	"ball"	a double-quoted literal (§2.1) — names objects (<code>NEW ... AS</code>) and feeds user functions; also produced as results like <code>obj0</code> or run summaries

Bracket literals are *shape-directed*: 3 numbers make a `vec3`, 4 numbers make a quaternion, 3 `vec3`s make a `mat3`.

Arithmetic is *type-checked*:

operation	allowed
+, -	number±number, vec3±vec3, quat±quat
*	number·number, number·vec3, number·quat, number·mat3, mat3·vec3, mat3·mat3, quat·quat (Hamilton product)
/	number/number, vec3/number
vec3*vec3	forbidden — the error tells you to use <code>dot()</code> or <code>cross()</code>

Builtins: `dot(a,b)`, `cross(a,b)`, `norm(v)` (length; also quaternions and numbers), `normalize(v)`, and scalar `sqrt` `abs` `sin` `cos` `exp` `log`. Constants: `pi`, `tau` ($= 2\pi$).

5 Command semantics

5.1 NEW — create an object

```

NEW POINT    { field = expr, ... }
NEW SPHERE   { field = expr, ... }
NEW CUBOID   { field = expr, ... }      (alias: NEW CUBE)
NEW TORUS    { field = expr, ... }
NEW DISK     { field = expr, ... }      (alias: NEW DISC)
NEW CYLINDER { field = expr, ... }
NEW DUMBELL  { field = expr, ... }      (alias: NEW DUMBELL)

NEW <shape> AS <name> { field = expr, ... }  (register a user name)

```

Creates one *physical object* and prints its handle (obj0, obj1, ..., numbered by position). Defaults: mass 1, at the origin, at rest, no charge; sphere radius 1; cuboid half-extents [1,1,1]; torus ring_radius 1, tube_radius 0.25; disk radius 1; cylinder radius 0.5, half_height 1; dumbbell m1 = 1, m2 = 1, m_rod = 0.5, r1 = 0.25, r2 = 0.25, rod_radius = 0.1, length = 1 (total mass 2.5).

Initializer fields: mass, charge, position, velocity, momentum, orientation, angular_velocity, angular_momentum, radius (spheres, disks, cylinders), half_extents (cuboids), ring_radius, tube_radius (tori — or the inner_radius + outer_radius pair, see below), height, half_height (cylinders; HEIGHT is the full height = 2·half_height), m1, m2, m_rod, r1, r2, rod_radius, length (dumbbells, see below), inertia_tensor, inverse_inertia_tensor, magnetic_moment_tensor, force, torque, id, inverse_mass.

A torus can be sized two ways: directly (ring_radius c = the radius of the circle traced by the tube's center, tube_radius a = the tube's own radius) or by the **inner_radius + outer_radius pair** (the hole's radius and the outermost radius: inner = $c - a$, outer = $c + a$). Inside a NEW initializer list the torus geometry is **deferred**: the four radius fields are collected and resolved *once*, at the end of the list — ring_radius/tube_radius are applied first, then inner_radius/outer_radius override the derived pair — and the result is validated once, against the *final* values (a bad pair fails with `torus needs 0 <= inner < outer (got inner = 2, outer = 1)`). Giving both members of the pair is therefore **genuinely order-independent**: { inner_radius = 1, outer_radius = 2 } yields ring 1.5, tube 0.5 whichever comes first, and a pair that shrinks the default torus — { outer_radius = 0.5, inner_radius = 0.2 } — works in either order too (checking each write against the half-updated default would have refused one of the two orders). inner_radius = 0 is legal — that is the **horn torus**, whose tube touches the axis — on NEW and on SET alike.

The dumbbell is ONE rigid body: two solid spheres joined by a solid rod. Its seven part fields are m1, m2, m_rod (the two sphere masses and the rod mass), r1, r2 (the sphere radii), rod_radius (alias rod_r) and length (alias len — the distance between the sphere centers). Like the torus radius pair, the part fields are **deferred**: they are collected during the initializer list and resolved *once* at its end, so they are order-independent and validated once against the final values. The constructor places the local origin at the composite **center of mass** — the sphere centers sit at $z_1 = -(m_2 + m_{\text{rod}}/2) L/M$ and $z_2 = +(m_1 + m_{\text{rod}}/2) L/M$ on the body z -axis, which makes $m_1 z_1 + m_2 z_2 + m_{\text{rod}}(z_1 + z_2)/2 = 0$ an identity — so **position** is the COM, exactly as for every other shape. The inertia tensor is the exact composite (solid-sphere $\frac{2}{5}mr^2$ terms with parallel-axis shifts, plus the rod), and the surface is the exact union of the three parts. It is the simulator's first non-centrally-symmetric shape; collisions against every other shape decompose exactly over its parts (see `collision_detection.pdf`). The part fields remain readable *and writable* after creation (§5.2).

AS registers a user name for the object. The name is a string literal (NEW SPHERE AS "ball") or a bare identifier (NEW SPHERE AS ball); a bare identifier is first resolved against a function parameter or LET variable holding a string — so a function can name the object it creates from its argument (§5.8, Example 14) — and otherwise the identifier's own spelling is the name. The reply shows both handles: obj0 as ball. Named paths then work everywhere a positional path does — ball.mass, dumbell0.position.x, in SET/GET and in bare expressions. Names are case-insensitive identifiers; system/sys and the positional spellings are refused ('system' is reserved, 'obj7' is reserved for positional paths), and so are duplicates (the name 'd' already refers to obj0 -- DEL it or pick another name). The registry follows every renumbering: DEL re-

moves the deleted object's name and shifts the names of higher-numbered objects down with their objects, and the **BOX** commands do the same when walls come and go.

Four guarantees make initializers forgiving:

1. **Order does not matter for velocities.** `velocity` and `angular_velocity` are applied *after* mass and inertia are final, so `{ velocity = [1,0,0], mass = 2 }` still yields momentum `[2,0,0]`.
2. **Inertia is computed for you.** For every extended shape the inertia tensor is recomputed from the final mass and shape (solid sphere $\frac{2}{5}mr^2$; cuboid $\frac{m}{3}(h_y^2 + h_z^2)$ etc.; torus $I_z = m(c^2 + \frac{3}{4}a^2)$, $I_{xy} = m(\frac{1}{2}c^2 + \frac{5}{8}a^2)$; disk $I_z = \frac{1}{2}ma^2$, $I_{xy} = \frac{1}{4}ma^2$; cylinder $I_z = \frac{1}{2}mr^2$, $I_{xy} = m(3r^2 + 4h^2)/12$ with h the half-height) — *unless* you supplied `inertia_tensor` yourself, in which case yours is kept.
3. **Coupled fields stay consistent** (see **SET** below).
4. **NEW is transactional.** If any initializer — or the final geometry validation — fails, the half-built object is removed before the error is reported: a failing **NEW** never leaves a ghost behind, and `system.count` and the `objN` numbering are exactly what they were before the command.

5.2 SET / GET — write and read any field

A *path* is `objN.field`, `system.field`, `contactK.field` (§5.6) or `name.field` for a name registered with **NEW** ... **AS** (§5.1), optionally followed by a component `.x .y .z` (vectors) or `.w .x .y .z` (quaternions). Component writes are safe read-modify-write operations through the full field's get/set pair. Every object also has six **component shorthands**: `.x .y .z` read and write the position components and `.vx .vy .vz` the velocity components — `ball.x` is `ball.position.x`, **SET** `ball.vx = 2` is a velocity write.

Object fields (R = readable, W = writable):

field	type	R/W	meaning
<code>id</code>	number	RW	user label (no effect on physics)
<code>mass</code>	number	RW	writing also updates <code>inverse_mass</code> ($m \leq 0 \Rightarrow 1/m := 0$)
<code>inverse_mass</code>	number	RW	writing back-computes <code>mass</code> ; 0 makes the body static
<code>charge</code>	number	RW	Coulombs
<code>position, pos</code>	vec3	RW	world position
<code>velocity, vel</code>	vec3	RW	<i>derived</i> : reads p/m , writes $p := mv$
<code>momentum</code>	vec3	RW	canonical stored linear state
<code>orientation</code>	quat	RW	renormalized on write
<code>angular_velocity</code>	vec3	RW	<i>derived</i> : $\omega = R I^{-1} R^T L$; writes $L := R I R^T \omega$
<code>angular_momentum</code>	vec3	RW	canonical stored angular state (spin)
<code>inertia_tensor</code>	mat3	RW	body frame; write updates the inverse (singular $\rightarrow$ zero inverse = cannot rotate)
<code>inverse_inertia_tensor</code>	mat3	RW	write back-computes the tensor

magnetic_moment_tensor	mat3	RW	torque $\tau = (RMR^T)B$
radius	number	RW	spheres, disks, cylinders; write recomputes inertia and keeps the shape family (a disk stays a disk, a cylinder keeps its height); a torus is refused — obj6 is a torus — set ring_radius/tube_radius or inner_radius/outer_radius instead of radius — rather than silently becoming a sphere
half_extents	vec3	RW	cuboids only; write recomputes inertia
ring_radius, tube_radius	number	RW	tori only; write recomputes inertia
inner_radius, outer_radius	number	RW	tori only, derived (inner = $c - a$, outer = $c + a$); writing one holds the other fixed; inner_radius accepts ≥ 0 (0 = the horn torus; the other radii must be > 0)
height, half_height	number	RW	cylinders only; height is the full height (= $2 \cdot \text{half_height}$); write recomputes inertia
m1, m2, m_rod	number	RW	dumbbells only: the two sphere masses and the rod mass; writing rebuilds the body — total mass, the COM offsets and the inertia tensor all follow (position is untouched; the stored momenta are preserved — momentum-canonical, like every mass write — so the velocities rescale with the new mass and inertia)
r1, r2, rod_radius	number	RW	dumbbells only: the sphere radii and the rod radius (alias rod_r); same rebuild on write
length	number	RW	dumbbells only: distance between the sphere centers (alias len); same rebuild on write
x, y, z	number	RW	every object: shorthands for position.x/.y/.z
vx, vy, vz	number	RW	every object: shorthands for velocity.x/.y/.z
boundary, shape	string	R	description of the shape
kinetic_energy, energy	number	R	$\frac{1}{2}m v ^2 + \frac{1}{2}\omega \cdot L$
force	vec3	RW	constant external force during STEP/RUN
torque	vec3	RW	constant external torque
restitution	number	RW	collision bounciness $e \in [0, 1]$ (default 1 = elastic; a pair uses $\min(e_i, e_j)$)

System fields:

field	type	R/W	meaning
<code>g_constant, g</code>	number	RW	Newton's G (default 1)
<code>softening</code>	number	RW	Plummer length ε (default 10^{-6}); forces use $(r^2 + \varepsilon^2)^{3/2}$
<code>uniform_gravity, gravity</code>	vec3	RW	constant acceleration field
<code>e_field</code>	vec3	RW	uniform E ; force qE
<code>b_field</code>	vec3	RW	uniform B ; force $qv \times B$, torque $(RMR^T)B$
<code>rtol, atol</code>	number	RW	CVODE tolerances (10^{-10} , 10^{-12})
<code>time, t</code>	number	RW	current simulation time
<code>method</code>	string	R	current integrator
<code>count, n</code>	number	R	number of objects
<code>collide</code>	number	R	1 when collision detection is on (switch with COLLIDE ON/OFF)
<code>contacts</code>	number	R	contacts recorded by the last STEP/RUN
<code>collisions</code>	number	R	running total of resolved impulses
<code>restitution_threshold</code>	number	RW	approach speeds below this bounce with $e = 0$ (default 10^{-3})
<code>contact_slop</code>	number	RW	tolerated overlap before positional projection (default 10^{-9})
<code>box</code>	number	R	inner side length of the rigid bounding box (§5.7); 0 = none. Create/remove with BOX

5.3 STEP and RUN — integrate (always via SUNDIALS)

STEP `dt` advances time by `dt`. RUN `t STEPS n` advances by `t`, stopping at `n` evenly spaced output points (default 10). Both accept full expressions (`run 2 * pi steps 8` is legal). The reply summarizes the run; `|dE/E|` is the relative change in total energy — your built-in sanity check. **All integration is performed by the pure-Rust SUNDIALS solvers**; there is no hand-rolled stepper.

5.4 METHOD — choose the integrator

METHOD ADAMS	(default; CVODE Adams-Moulton, adaptive)
METHOD BDF	(CVODE BDF -- stiff problems, fast gyration)
METHOD SPRK <table> [dt]	(ARKODE symplectic, fixed step; default dt 0.01)

Table names may be abbreviated: `leapfrog_2_2` becomes `ARKODE_SPRK_LEAPFROG_2_2`. Useful tables: `EULER_1_1`, `LEAPFROG_2_2` ($\equiv$ classic velocity Verlet), `MCLACHLAN_2_2/3_3/4_4/5_6`, `RUTH_3_3`, `YOSHIDA_6_8`.

SPRK requires a *separable* system: point-like translation only. If anything velocity-dependent or rotational is active (a `b_field`, a magnetic tensor, an external torque, a spinning rigid body), RUN refuses with an error *naming the offending feature*.

5.5 Observables, bookkeeping, help

command	prints
ENERGY	kinetic + softened pairwise potential + uniform-field potentials
COM	system center of mass
MOMENTUM	total linear momentum
ANGMOM	total angular momentum about the origin (orbital + spin)
LAPLACE n	Laplace–Runge–Lenz vector of object n about the center of mass, $k = G M_{\text{total}}$
LIST	one line per object
DEL n	removes object n (later objects renumber!)
RESET	wipes everything (not to be confused with SCENE RESET, which re-initializes only the scene window’s playback copy — see <code>scene_info.pdf</code>)
HELP	the quick-reference card

5.6 COLLIDE and CONTACTS — rigid-body collisions

COLLIDE	(report: on/off, collidable pairs, impulses so far)
COLLIDE ON	(default - collisions are detected in EVERY scene)
COLLIDE OFF	(pure point-mass/gravity studies)
CONTACTS	(list every contact of the last STEP/RUN)

When collisions are on (the default) and the system contains at least one collidable pair (spheres, cuboids, or a point against either — two points cannot collide), **STEP** and **RUN** detect impacts **during** the time step by SUNDIALS *event rootfinding*: the integrator itself lands on the instant where a pair’s signed separation crosses zero, interpolated to solver precision. At that instant an impulse acts along the **contact normal** — the line of the action–reaction force pair — and integration continues. Nothing tunnels, and the reply reports what happened.

Every contact of the last **STEP**/**RUN** is recorded and exposed to the rest of the simulation through read-only `contactK` paths:

field	type	meaning
<code>contactK.i</code> , <code>contactK.j</code>	number	the colliding pair (indices, $i < j$)
<code>contactK.t</code>	number	the event time (the root the solver landed on)
<code>contactK.point</code>	vec3	world-space contact point
<code>contactK.normal</code>	vec3	unit normal, from obji toward objj — the action–reaction line; <code>objj</code> receives $+J\hat{n}$, <code>obji</code> receives $-J\hat{n}$
<code>contactK.depth</code>	number	penetration depth at the event (≈ 0)
<code>contactK.rel_vel_n</code>	number	approach speed along the normal (negative = approaching)
<code>contactK.impulse</code>	number	scalar impulse magnitude J

Response physics (full derivation in `collision_detection.pdf`): per-object **restitution** $e \in [0, 1]$ (1 = elastic default, 0 = perfectly plastic), pair-combined as $\min(e_i, e_j)$; impulse $J = -(1 + e)(\mathbf{v}_{\text{rel}} \cdot \hat{n}) / (\hat{n}^\top K \hat{n})$ with the effective-mass matrix K including the angular terms, applied through the canonical momentum/angular-momentum setters; static bodies (`inverse_mass` = 0) are immovable walls; approach speeds below `system.restitution_threshold` settle with-

out bounce; leftover overlap beyond `system.contact_slop` is projected out. SCENE windows draw each contact normal as an arrow at the contact point (**Contacts** toolbar button or the **C** key).

5.7 BOX — the rigid bounding box

BOX <size>	(create: six static walls enclosing an inner size x size x size cube centered on the origin)
BOX OFF	(remove the box - its six walls are deleted)
BOX	(bare: report status)

BOX <size> builds a closed rigid room out of **six ordinary cuboid objects** — wall slabs behind the planes $x = \pm \text{size}/2$, $y = \pm \text{size}/2$, $z = \pm \text{size}/2$ (half-thickness $\text{size}/4$, centers at $\pm 3 \cdot \text{size}/4$, cross-sections wide enough to cover the corners) — and prints their handles:

<pre>In[2]:= box 4 Out[2]= box: inner size 4 x 4 x 4 -- six static walls obj0, obj1, obj2, obj3, obj4, obj5 with inverse_mass = 0 (infinitely massive); objects collide elastically off the inside faces</pre>
--

Infinite mass is exact, not approximate. The equations of motion never use the mass itself — only the *inverse* mass: velocity is $v = p m^{-1}$, and the collision impulse divides by $\hat{n}^\top K \hat{n} = m_i^{-1} + m_j^{-1} + (\text{angular terms})$ (§5.6). Each wall is created with `inverse_mass = 0` and a zero inverse inertia tensor, so it contributes exactly 0 to every impulse denominator and receives no state writes: bodies bounce off the inside faces elastically while the walls stay **bit-identically at rest**. One measurable consequence: system **momentum is not conserved** inside a box — the infinitely massive walls absorb it without moving (Example 13). LIST tags every wall [`wall: static, inverse_mass=0`] (and shows `mass=0` — the canonical stored quantity for a static body is the inverse).

Bookkeeping:

- GET `system.box` reads the inner side length; 0 means no box. The path is read-only — the box is created and removed by the command.
- A second BOX <size> **replaces** the existing box: the old walls are removed first and the reply notes (replacing the previous box).
- The walls are ordinary objects with ordinary indices: DEL on a wall deletes it like any other object **and dissolves the box** — `system.box` drops to 0 (five walls no longer enclose anything) — but the surviving slabs **stay tracked**: LIST keeps their [`wall: static, inverse_mass=0`] tag, and bare BOX reports `box: dissolved` (a wall was deleted; 5 tracked slab(s) remain - BOX <size> replaces them, BOX OFF removes them). The next BOX <size> removes the survivors *before* building the new box (the reply notes (replacing the previous box)) and BOX OFF simply deletes them — either way no orphan slab leaks. Wall indices are tracked through every DEL renumbering, so deleting a non-wall object never confuses the box.
- BOX OFF replies `box removed` (6 wall(s) deleted, indices renumbered) — or `box: none` if there was nothing to remove; bare BOX reports the size and wall handles, or `box: none` (BOX <size> creates one).

- A **SCENE** window draws the box as a **dashed interior wireframe**; the wall slabs themselves are not drawn as bodies. Creating a box while a window is open appends a reminder to the reply: (scene window open: SCENE REFRESH shows the box). **RESET** re-syncs an open window to the now-empty system **and clears its box wireframe and wall flags** — no stale overlay survives the wipe.

5.8 User definitions: DEF, LET, FUNCS, SHOW

DEF name(param [= default], ...)	{ body }	(define a function)
name(arg, ...)		(call it)
LET name = <expr>		(session variable)
FUNCS		(list signatures; alias: FUNCTIONS)
SHOW name		(print a function's source)

DEF is a line form, not a grammar production. A line that starts with **DEF** is recognized *before* the ordinary grammar (§3): the notebook captures everything up to the closing **}** — interactively it keeps prompting `...:=` for continuation lines until the brace closes; scripts and JupyterLab cells just keep reading — and installs the function. The **body** is a sequence of ordinary commands, separated by newlines or **;**, in which the parameters act as variables. **Every body line is syntax-checked at definition time** (a typo fails the **DEF** immediately, naming the body line), and **defaults are ordinary expressions evaluated once, at definition** (**LET** variables are visible in them).

Calling uses the ordinary call syntax **name(arg, ...)** — the same atom as **sqrt(2)**; a name that is not a builtin is looked up among your functions. Missing trailing arguments take their defaults (an argument with no default must be supplied). Each call pushes a **call frame** binding the parameters (depth cap: 32 — the language has no conditionals, so recursion could never terminate anyway) and runs the body lines through the same compile-and-execute pipeline as typed input. The call **returns the last body line's value** — if that line is a **SET**, the call prints no **Out[n]**, exactly like **SET** itself. A failing body line aborts the call and the error names the function *and* the line; lines that already ran keep their effects (each command's own guarantees still hold per line — e.g. a failing **NEW** inside a body is still transactional), so a partly-run call leaves no half-built object, only completed commands.

Editing is SHOW + re-DEF. **SHOW name** prints the definition verbatim, exactly as you typed it; redefining the same name replaces the old version and the reply appends (**redefined**). **FUNCS** lists every signature with its defaults.

LET name = expr binds a session variable (reply: **name set**). It is visible in bare expressions, in function bodies, in **DEF** defaults — and, holding a string, it can *name* things: **NEW ... AS** and named paths resolve a bare identifier through the parameter/**LET** bindings first (§5.1). Note **GET** takes only a *path* (§3), so a variable is read back as a bare expression: **g0**, not **GET g0**.

A complete session (genuine output):

```
In[1]:= let g0 = 9.81
Out[1]= g0 set
In[2]:= def drop(name, m = 1, h = 10) {
  new sphere as name { mass = m, position = [0, h, 0] }
  set system.gravity = [0, -g0, 0]
}
```

```

Out[2]= function drop(3 parameter(s)) defined -- 2 body line(s)
In[3]:= drop("ball")
In[4]:= get ball.position.y
Out[4]= 10
In[5]:= drop("pebble", 0.1, 2)
In[6]:= get pebble.mass
Out[6]= 0.1
In[7]:= func
Out[7]= drop(name, m = 1, h = 10) -- 2 body line(s); SHOW drop prints it
In[8]:= show drop
Out[8]= def drop(name, m = 1, h = 10) {
    new sphere as name { mass = m, position = [0, h, 0] }
    set system.gravity = [0, -g0, 0]
}
In[9]:= def drop(name, m = 1, h = 100) { new sphere as name { mass = m, position = [0,
    h, 0] }; set system.gravity = [0, -g0, 0] }
Out[9]= function drop(3 parameter(s)) defined -- 2 body line(s) (redefined)
In[10]:= drop("skydiver")
In[11]:= skydiver.y
Out[11]= 100
In[12]:= speed
Err[12]: unknown name 'speed' (define it with LET, pass it as a function parameter, or
    use 'speed.field' for a registered object)

```

What to notice. The function's `name` parameter holds a string, and `new sphere as name` inside the body names each created object from it — `ball`, `pebble`, `skydiver` — so one definition mints a family of named objects. `drop("ball")` used both defaults; cell 9 is the edit loop (copy cell 8's `SHOW` output, change `h`, re-DEF — note `;` separating body lines works as well as newlines); calls 3, 5 and 10 print no `Out` because the last body line is a `SET`. Cell 12 is the bare-identifier error: execution-time resolution means the message can list every way to bind a name.

Definition-time and call-time errors are specific: a reserved or builtin name is refused (`DEF: 'norm' is a builtin function and cannot be redefined`), nested `DEF` is refused, an empty body is refused, a missing non-default argument fails as `name(): missing argument 'p' (it has no default)`, too many arguments fail naming the signature, and the depth cap fails as `function call depth limit (32) exceeded`.

6 The notebook (cells, editing, magics)

6.1 Cells

Start `posim` with no arguments. You get numbered prompts, exactly like Jupyter or Mathematica:

```

In[1]:= new sphere { mass = 2, radius = 0.5 }
Out[1]= obj0
In[2]:= get obj0.inertia_tensor
Out[2]= [[0.2, 0, 0], [0, 0.2, 0], [0, 0, 0.2]]

```

Pressing **Enter** executes the cell — in a plain terminal, Enter *is* shift-enter. Commands with no interesting result (like `SET`) print no `Out[n]`. Errors print `Err[n]:` and the session continues.

6.2 State is cumulative

Like Jupyter, the notebook has one live simulator state that every cell mutates in order. Re-running an old NEW cell creates a *new* object; it does not replace the old one. To rebuild cleanly, `%reset` and replay.

6.3 Magics

magic	effect
<code>%history</code>	lists every cell with input and output; failed cells marked !
<code>%edit n <text></code>	replaces cell <i>n</i> 's input and executes it as the next cell
<code>%rerun n</code>	executes cell <i>n</i> 's input again as a new cell
<code>%save <file></code>	writes all successful non-magic inputs to a replayable script
<code>%load <file></code>	replays a script file cell by cell
<code>%reset</code>	clears the simulator (history kept)
<code>%quit, %exit</code>	leave

A plain terminal has no cursor-addressable cells (posim uses only the Rust standard library — no raw terminal mode), so backward/forward movement is by these magics. **For true click-and-edit cells with shift-enter, use the JupyterLab front end (§7).**

6.4 Scripts

`posim -script file` executes a file of command lines (blank lines and `#` comments skipped), echoing `In[n]/Out[n]`, and exits nonzero if any cell failed — good for CI.

7 JupyterLab in one paragraph

The `jupyter/` directory ships a small *wrapper kernel*: JupyterLab starts a Python shim, the shim starts `posim -machine` (a JSON request/reply protocol over stdin/stdout), and each notebook cell you shift-enter is forwarded line-by-line as `{"op": "exec", "code": ...}`. Setup and tests: `jupyter/README.md`. Everything in §§2–5 applies verbatim inside JupyterLab cells; multi-line cells run one line at a time, stopping at the first error.

8 The stack machine (what runs your line)

The parser emits *postfix instructions*; e.g. `set obj0.mass = 2 + 3 * 4` compiles to

```
Push 2
Push 3
Push 4
Mul      <- pops 3,4  pushes 12
Add      <- pops 2,12 pushes 14
Store obj0.mass <- pops 14, calls set_mass(14)
```

The machine's whole memory is a stack of typed values. Instructions: `Push`, `Load`, `Store`, `LoadIdent` (a bare identifier — parameter or LET variable, resolved at execution, §5.8), `StoreGlobal` (LET), `Add` `Sub` `Mul` `Div` `Neg`, `PackList` (literals), `Call` (builtin or user function — a user call runs

each body line through this same compile-and-execute pipeline inside a call frame), `NewObject/InitField/FinishM` (which also registers the AS name), `Delete`, `ListObjects`, `ListFns/ShowFn` (`FUNCS/SHOW`), `Step`, `Run`, `SetMethod`, `Energy`, `CenterOfMass`, `TotalMomentum`, `TotalAngularMomentum`, `Laplace`, `Reset`, `Help`. `Load/Store` go *only* through the `physical_object` get/set API — the machine cannot corrupt simulator state, and every coupled invariant (`mass↔inverse`, `inertia↔inverse`, unit quaternions) is enforced on every write. When the program ends, the top of the stack becomes `Out[n]`.

9 Fourteen worked examples

All transcripts are genuine program output.

9.1 Example 1 — an eccentric Kepler orbit and the Runge–Lenz compass

The Laplace–Runge–Lenz vector $\mathbf{A}$ points along a Kepler orbit’s major axis and is conserved *only* for a perfect $1/r^2$ force — the most delicate conservation test available. We build a “sun” so heavy the reduced problem is exact and integrate two orbits with a 4th-order *symplectic* method.

```
In[1]:= new point { mass = 1e9, position = [0, 0, 0] }
Out[1]= obj0
In[2]:= new point { mass = 1, position = [0.4, 0, 0], velocity = [0, 2, 0] }
Out[2]= obj1
In[3]:= set system.g_constant = 1e-9
In[4]:= set system.softening = 0
In[5]:= laplace 1
Out[5]= [0.5999999974000001, 0, 0]
In[6]:= method sprk mclachlan_4_4 0.001
Out[6]= method = ARKODE SPRK ARKODE_SPRK_MCLACHLAN_4_4, fixed dt = 0.001
In[7]:= run 12.6 steps 2
Out[7]= t = 12.6 (12600 solver steps, 2 snapshots, |dE/E| = 9.237e-14)
In[8]:= laplace 1
Out[8]= [0.5999999974140128, -0.00000000034051644837163053, 0]
In[9]:= get obj1.position
Out[9]= [0.3964802853115723, 0.06706198328283366, 0]
```

What to notice. `g_constant = 1e-9` makes $GM_{\text{total}} = 1$ so the orbit has period 2π . `LAPLACE 1` divided by `mk` is the *eccentricity vector*: $e = 0.6$ is read directly off `Out[5]`. After ~ 2 orbits the energy is conserved to 9×10^{-14} and $\mathbf{A}$ has rotated by only 3×10^{-10} — no spurious perihelion precession. Softening was zeroed because any $\varepsilon \neq 0$ slightly breaks the $1/r^2$ law and *would* precess the axis.

9.2 Example 2 — a thrown ball vs. the textbook formula

A projectile has the closed form $x(t) = v_x t$, $y(t) = y_0 + v_y t - \frac{1}{2}gt^2$. We fly a baseball for 6.12 s and subtract the formula *inside the notebook* using bare expressions.

```
In[1]:= new point { mass = 0.145, position = [0, 1, 0], velocity = [30, 30, 0] }
Out[1]= obj0
In[2]:= set system.gravity = [0, -9.81, 0]
In[3]:= run 6.12 steps 3
Out[3]= t = 6.12 (13 solver steps, 3 snapshots, |dE/E| = 4.740e-15)
In[4]:= get obj0.position.x
```



```

Out[4]= 183.59999999999999
In[5]:= 30 * 6.12
Out[5]= 183.6
In[6]:= obj0.position.x - 30 * 6.12
Out[6]= -0.000000000000008526512829121202
In[7]:= obj0.position.y - (1 + 30 * 6.12 - 9.81 / 2 * 6.12 * 6.12)
Out[7]= -0.00000000000004263256414560601

```

What to notice. Cells 6–7 are *bare expressions* mixing paths and arithmetic (GET itself would refuse the arithmetic). The trajectory matches the parabola to $\sim 10^{-13}$ — and the adaptive Adams integrator needed only **13 internal steps**, because for a polynomial solution its error estimator lets it take huge strides.

9.3 Example 3 — cyclotron motion: expressions as arguments

A charge in a uniform magnetic field circles with period $T = 2\pi m/(|q|B)$. We *compute* T *inside the RUN command*.

```

In[1]:= new sphere { mass = 2, radius = 0.1, charge = -1.5, velocity = [3, 0, 0] }
Out[1]= obj0
In[2]:= set system.b_field = [0, 0, 4]
In[3]:= method bdf
Out[3]= method = CVODE BDF
In[4]:= 2 * pi * 2 / (1.5 * 4)
Out[4]= 2.0943951023931953
In[5]:= run 2 * pi * 2 / (1.5 * 4) steps 8
Out[5]= t = 2.0943951023931953 (318 solver steps, 8 snapshots, |dE/E| = 1.444e-8)
In[6]:= get obj0.position
Out[6]= [0.00000000043106769672882073, 0.000000007220835657713453, 0]
In[7]:= norm(obj0.velocity)
Out[7]= 2.9999999783374913

```

What to notice. After one analytic period the particle is back at the origin to 7×10^{-9} , and `norm()` shows the speed unchanged — the magnetic force does no work. The Lorentz force $q \mathbf{v} \times \mathbf{B}$ is velocity-dependent, so the symplectic path is *not allowed* here; BDF is the right tool for fast gyration.

9.4 Example 4 — the tennis-racket theorem (Dzhanibekov effect)

A rigid body spun about its *intermediate* principal axis is unstable: a tiny wobble grows into a dramatic flip, yet energy and angular momentum stay conserved. Half-extents [0.5, 1, 2] give moments [5, 4.25, 1.25]; spinning about y (the middle value) triggers it.

```

In[1]:= new cuboid { mass = 3, half_extents = [0.5, 1, 2], angular_velocity = [0.01, 3, 0.01] }
Out[1]= obj0
In[2]:= get obj0.inertia_tensor
Out[2]= [[5, 0, 0], [0, 4.25, 0], [0, 0, 1.25]]
In[3]:= get obj0.angular_velocity
Out[3]= [0.010000000000000002, 3, 0.010000000000000002]
In[4]:= run 40 steps 4

```

```

Out[4]= t = 40 (2361 solver steps, 4 snapshots, |dE/E| = 5.605e-9)
In[5]:= get obj0.angular_velocity
Out[5]= [1.5428438559953521, 2.9947703802651175, -0.7871804456905063]
In[6]:= run 40 steps 4
Out[6]= t = 80 (2334 solver steps, 4 snapshots, |dE/E| = 5.332e-9)
In[7]:= get obj0.angular_velocity
Out[7]= [0.020666590902422656, 2.9999548562146483, 0.013346831306280834]
In[8]:= get obj0.angular_momentum
Out[8]= [0.05, 12.75, 0.0125]

```

What to notice. At $t = 40$ the wobble has exploded ($\omega_x \approx 1.54$, mid-flip); by $t = 80$ the body has completed the flip and returned to a clean spin. Throughout, the world-frame angular momentum (Out[8]) is exactly the initial $I\omega = [0.05, 12.75, 0.0125]$ — the solver integrates the full quaternion + angular-momentum state with energy error $\sim 5 \times 10^{-9}$.

9.5 Example 5 — three bodies, then surgery with DEL

```

In[1]:= new point { mass = 1, position = [1, 0, 0], velocity = [0, 1, 0] }
Out[1]= obj0
In[2]:= new point { mass = 4, position = [-1, 0, 0], velocity = [0, -0.25, 0] }
Out[2]= obj1
In[3]:= new point { mass = 256, position = [0, 8, 0], velocity = [0, 0, 0] }
Out[3]= obj2
In[4]:= set system.g_constant = 0.001
In[5]:= momentum
Out[5]= [0, 0, 0]
In[6]:= com
Out[6]= [-0.011494252873563218, 7.846743295019157, 0]
In[7]:= run 3 steps 3
Out[7]= t = 3 (84 solver steps, 3 snapshots, |dE/E| = 3.141e-10)
In[8]:= list
Out[8]= obj0: point, mass=1, charge=0, pos=[0.9936356911262184, 3.022315903943394, 0]
obj1: point, mass=4, charge=0, pos=[-0.9972663866755148, -0.7330950497234504, 0]
obj2: point, mass=256, charge=0, pos=[-0.000017852126656859762, 7.999648688652149, 0]
In[9]:= del 2
Out[9]= deleted obj2; 2 object(s) remain (indices renumbered)
In[10]:= list
Out[10]= obj0: point, mass=1, charge=0, pos=[0.9936356911262184, 3.022315903943394, 0]
obj1: point, mass=4, charge=0, pos=[-0.9972663866755148, -0.7330950497234504, 0]
In[11]:= momentum
Out[11]= [0.0021430470372574067, 0.061528401914275554, 0]

```

What to notice. Cells 1–3 chose velocities so the initial total momentum is exactly zero ($1 \cdot 1 + 4 \cdot (-0.25) = 0$), and it stays zero through the run. Deleting the heavy body removes its momentum: the remainder (Out[11]) is what the surviving pair carries — conservation applies to the system you keep. DEL renumbers later objects.

9.6 Example 6 — magnetic torque (and why ENERGY grows)

magnetic_moment_tensor M couples the world B field to torque $\tau = (RMR^T)B$. Unlike everything else, this coupling is *not derived from a potential*, so total energy is *expected* to change.

```

In[1]:= new sphere { mass = 1, radius = 0.5, magnetic_moment_tensor = [[0.2, 0, 0], [0,
    0.2, 0], [0, 0, 0.2]] }
Out[1]= obj0
In[2]:= set system.b_field = [0, 0.5, 0]
In[3]:= get obj0.angular_momentum
Out[3]= [0, 0, 0]
In[4]:= energy
Out[4]= 0
In[5]:= run 4 steps 4
Out[5]= t = 4 (214 solver steps, 4 snapshots, |dE/E| = 8.000e-1)
In[6]:= get obj0.angular_momentum
Out[6]= [0, 0.400000000000000085, 0]
In[7]:= get obj0.angular_velocity
Out[7]= [0, 4.0000000000000009, 0]
In[8]:= energy
Out[8]= 0.80000000000000035

```

What to notice. Constant torque $\tau = MB = 0.2 \times 0.5 = 0.1$ about y gives $L(t) = 0.1t$: after 4 s, $L = 0.4$ exactly (the ODE is linear, so the solver nails it). Sphere inertia $= 0.4 \cdot 1 \cdot 0.25 = 0.1$, so $\omega = L/I = 4$ and the rotational energy $\frac{1}{2}\omega L = 0.8$ matches Out[8]. The reported $|dE/E| = 8e-1$ is not an error — it honestly reports that the torque pumped energy in.

9.7 Example 7 — fixing a typo in an old cell with %edit

```

In[1]:= new sphere { mass = 20, radius = 0.5 }
Out[1]= obj0
In[2]:= set obj0.velocity = [1, 0, 0]
In[3]:= get obj0.momentum
Out[3]= [20, 0, 0]
In[4]:= %edit 1 new sphere { mass = 2, radius = 0.5 }
In[4]:= new sphere { mass = 2, radius = 0.5 }
Out[4]= obj1
In[5]:= %history
In[1]:= new sphere { mass = 2, radius = 0.5 }
Out[1]= obj0
In[2]:= set obj0.velocity = [1, 0, 0]
In[3]:= get obj0.momentum
Out[3]= [20, 0, 0]
In[4]:= new sphere { mass = 2, radius = 0.5 }
Out[4]= obj1

```

What to notice. `%edit 1 ...` rewrites cell 1's stored input and re-executes it as the next cell — like editing a Jupyter cell and shift-entering again. Because state is cumulative, the re-executed NEW made a *second* object; the fat `obj0` is still there. For a clean rebuild use `%reset + %rerun` or `%load`; when a field tweak suffices, `set obj0.mass = 2`. `%history` shows the *edited* input but the *original* outputs — an audit trail of what actually ran.

9.8 Example 8 — checking the simulator against itself

```

In[1]:= new point { mass = 2, position = [1, 0, 0], velocity = [0, 3, 0] }

```

```

Out[1]= obj0
In[2]:= cross(obj0.position, obj0.momentum)
Out[2]= [0, 0, 6]
In[3]:= angmom
Out[3]= [0, 0, 6]
In[4]:= dot(obj0.position, obj0.velocity)
Out[4]= 0
In[5]:= norm(cross(obj0.position, obj0.momentum)) / (norm(obj0.position) * norm(obj0.
momentum))
Out[5]= 1

```

What to notice. Cell 2 computes $L = r \times p$ by hand and cell 3 confirms **ANGMOM** agrees. Cell 4 proves $r \perp v$; cell 5 computes $|r \times p|/(|r||p|) = \sin \theta = 1$ — the angle between r and p is 90° — inside one nested expression.

9.9 Example 9 — hand-built tensors and a quaternion orientation

```

In[1]:= new cuboid { mass = 1, inertia_tensor = [[2, 0, 0], [0, 3, 0], [0, 0, 4]],
orientation = [0.7071067811865476, 0, 0, 0.7071067811865476] }
Out[1]= obj0
In[2]:= get obj0.inverse_inertia_tensor
Out[2]= [[0.5, 0, 0], [0, 0.3333333333333333, 0], [0, 0, 0.25]]
In[3]:= set obj0.angular_velocity = [0, 2, 0]
In[4]:= get obj0.angular_momentum
Out[4]= [0.00000000000000004440892098500628, 4.0000000000000002, 0]
In[5]:= get obj0.orientation
Out[5]= quat[w=0.7071067811865476, x=0, y=0, z=0.7071067811865476]

```

What to notice. Because `inertia_tensor` appears in the initializer, the analytic inertia is **not** recomputed — your `diag(2,3,4)` is kept, with the inverse maintained automatically. The quaternion $[w, x, y, z] = [\sqrt{1/2}, 0, 0, \sqrt{1/2}]$ is a 90° rotation about z , so setting the *world* angular velocity $[0, 2, 0]$ exercises the full $L = (RIR^T)\omega$ transformation. By hand: rotating `diag(2,3,4)` by 90° about z swaps the x and y moments, so $RIR^T = \text{diag}(3, 2, 4)$, the world- y moment is 2, and $L = [0, 4, 0]$ — exactly `Out[4]` (up to 4×10^{-16} of floating-point dust).

9.10 Example 10 — reproducibility: %save, %reset, %load

```

In[1]:= new sphere { mass = 2, radius = 0.5, velocity = [1, 0, 0] }
Out[1]= obj0
In[2]:= set system.gravity = [0, -9.81, 0]
In[3]:= step 0.5
Out[3]= t = 0.5 (advanced by 0.5, 12 solver steps)
In[4]:= %save session.posim
saved 3 cell(s) to session.posim
In[5]:= %reset
system reset
In[6]:= list
Out[6]= (no objects)
In[7]:= %load session.posim
In[7]:= new sphere { mass = 2, radius = 0.5, velocity = [1, 0, 0] }
Out[7]= obj0

```

```

In[8]:= set system.gravity = [0, -9.81, 0]
In[9]:= step 0.5
Out[9]= t = 0.5 (advanced by 0.5, 12 solver steps)
In[10]:= get obj0.velocity
Out[10]= [1, -4.905000000000001, 0]

```

What to notice. %save writes only the successful, non-magic inputs — a clean, replayable script. After %reset, %load replays it and the state is bit-identical ($v_y = -9.81 \cdot 0.5 = -4.905$). The same file runs headlessly via `posim -script`. The machine mode speaks the same language over JSON:

```

$ printf '%s\n' '{"op":"exec","code":"new point { mass = 1, velocity = [0, 1, 0] }"}' \
                '{"op":"get","path":"obj0.momentum"}' \
                '{"op":"set","path":"obj0.mass","value":5}' \
                '{"op":"get","path":"obj0.momentum"}' | posim --machine
{"display":"obj0","ok":true,"result":"obj0"}
{"display":"[0, 1, 0]","ok":true,"result":[0.0,1.0,0.0]}
{"display":"","ok":true,"result":null}
{"display":"[0, 1, 0]","ok":true,"result":[0.0,1.0,0.0]}

```

Changing the mass did **not** change the momentum — momentum is the canonical stored state; the *velocity* is what changed. That final subtlety is the union design showing through the wire protocol.

9.11 Example 11 — watching a Kepler orbit live, then running it backward

The same two-body setup as Example 1 — but this time we *watch* it. SCENE CREATE opens the scene window in the browser; SCENE START sets it in motion; SCENE REVERSE runs the movie backward.

```

In[1]:= new point { mass = 1e9, position = [0, 0, 0] }
Out[1]= obj0
In[2]:= new point { mass = 1, position = [0.4, 0, 0], velocity = [0, 2, 0] }
Out[2]= obj1
In[3]:= set system.g_constant = 1e-9
In[4]:= set system.softening = 0
In[5]:= scene create 7878
Out[5]= scene window created: http://127.0.0.1:7878/
(opened in your browser; if no window appeared, open that address yourself)
showing 2 entities; SCENE START begins the evolution -- HELP lists all scene commands
In[6]:= scene set_time_step 0.005
Out[6]= scene time step dt = 0.005
In[7]:= scene start
Out[7]= scene playback: running
In[8]:= scene pause
Out[8]= scene playback: paused
In[9]:= scene status
Out[9]= scene: http://127.0.0.1:7878/ (1 window(s) connected)
mode = paused, t = 0.4550000000000003, dt = 0.005, steps = 91, history = 91 frame(s)
entities = 2 (hidden: none)
camera: yaw = -60°, pitch = 55°, dist = 12, target = [0, 0, 0]
In[10]:= scene reverse
Out[10]= scene playback: reversing

```

```

In[11]:= scene status
Out[11]= scene: http://127.0.0.1:7878/ (1 window(s) connected)
mode = reversing, t = 0.15500000000000005, dt = 0.005, steps = 91, history = 31 frame(s
)
entities = 2 (hidden: none)
camera: yaw = -60°, pitch = 55°, dist = 12, target = [0, 0, 0]
In[12]:= scene events
Out[12]= window connected (1 total)
In[13]:= scene close
Out[13]= scene closed (http://127.0.0.1:7878/)

```

What to notice. Between In[7] and In[8] a few real seconds passed while the orbit ran in the window — playback happens on a background thread at ~ 30 frames per second, so **the notebook prompt never blocks**: cell 9’s STATUS shows the *playback copy* has advanced 91 steps to $t \approx 0.455$ while your notebook state still sits untouched at $t = 0$ (that is the “playback copy” design: the window animates its own synchronized copy of your system, so GET `system.time` here would still print 0). After REVERSE (cell 10), the status in cell 11 shows time flowing *backward* ($t \approx 0.155$) and the history buffer draining ($91 \rightarrow 31$ frames): each reversed frame is an exact recorded snapshot, so the rewind retraces the orbit bit-for-bit. Cell 12 drains the asynchronous event queue — the window announced itself when the browser connected. In JupyterLab you would not even need cell 12: events surface on their own as [scene] ... lines (§7).

9.12 Example 12 — driving the camera from the notebook

Every gesture the mouse can make in the window has a command twin, so a *script* can compose the exact view you want — useful for repeatable demonstrations and screenshots.

```

In[1]:= new sphere { mass = 3, radius = 0.6, position = [2, 0, 0] }
Out[1]= obj0
In[2]:= new cuboid { mass = 1, half_extents = [0.4, 0.3, 0.2], position = [-2, 0, 1] }
Out[2]= obj1
In[3]:= scene create 7878
Out[3]= scene window created: http://127.0.0.1:7878/
(opened in your browser; if no window appeared, open that address yourself)
showing 2 entities; SCENE START begins the evolution -- HELP lists all scene commands
In[4]:= scene translate 2 0
Out[4]= camera target = [2, 0, 0]
In[5]:= scene rotate 30 -10
Out[5]= camera yaw = -30°, pitch = 45°
In[6]:= scene zoom in
Out[6]= camera distance = 9.6
In[7]:= scene zoom 2
Out[7]= camera distance = 4.8
In[8]:= scene zoom out
Out[8]= camera distance = 5.999999999999999
In[9]:= scene hide 0
Out[9]= 1 object(s) hidden
In[10]:= scene show all
Out[10]= 0 object(s) hidden
In[11]:= scene redraw
Out[11]= scene redraw queued for every window
In[12]:= scene status

```

```

Out[12]= scene: http://127.0.0.1:7878/ (0 window(s) connected)
mode = stopped, t = 0, dt = 0.01, steps = 0, history = 0 frame(s)
entities = 2 (hidden: none)
camera: yaw = -30°, pitch = 45°, dist = 5.999999999999999, target = [2, 0, 0]
In[13]:= scene close
Out[13]= scene closed (http://127.0.0.1:7878/)

```

What to notice. The camera is an **orbit camera**: it circles a *look-at point* at a *distance*, aimed by *yaw* (compass direction) and *pitch* (elevation). TRANSLATE 2 0 moves the look-at point onto the sphere (this is what the arrow keys do in the window); ROTATE 30 -10 adds 30° of yaw to the default -60° and -10° of pitch to the default 55° (this is what left-dragging does); the three zooms multiply the distance by 1/1.25, then 1/2, then 1.25 — watch the arithmetic: $12 \rightarrow 9.6 \rightarrow 4.8 \rightarrow 6$ (this is the mouse wheel). HIDE 0 blanks the sphere out of every connected window without deleting anything — SHOW ALL brings it back. Because this transcript ran headless, cell 12 reports 0 window(s) connected — the commands work regardless, and any window that connects later receives the composed view. Note also the two-argument form `scene translate 2 0`: the optional `dz` defaulted to 0, and -10 in cell 5 was one negative argument, not a subtraction (scene arguments are *terms* — the second subtlety of §3).

9.13 Example 13 — the box of shapes: every body type in a rigid, infinitely massive box

The finale scene: BOX 4 builds the rigid room (§5.7) and one of every shape goes inside ($R = 1$, $M = 1$) — a **torus** (mass M , inner radius 1, outer radius 2), a **point** (M , the only mover: $v = (100, 200, 100)$), a **sphere** ($2M$, $r = \frac{1}{2}$), an ideal zero-thickness **disk** ($2M/3$, $r = 1$), a **cube** ($5M/3$, side 1) and a **cylinder** ($2M$, $r = \frac{1}{2}$, height $3/2$). An axis-aligned torus of outer radius 2 would *exactly inscribe* the 4-box (its outer equator touching four walls), so the torus is tilted with its axis along $(1, 1, 1)/\sqrt{3}$: its extent per axis is $1.5\sqrt{2/3} + 0.5 \approx 1.7247 < 2$ — clearance 0.2753. The other positions are random, drawn by a documented LCG ($x \leftarrow 1664525x + 1013904223 \bmod 2^{32}$, seed 20260724, sequential rejection at ≥ 0.05 separation) — see `scripts/collisions/11_box_of_shapes.posim`, the script this transcript replays.

```

In[1]:= set system.g_constant = 0
In[2]:= box 4
Out[2]= box: inner size 4 x 4 x 4 -- six static walls obj0, obj1, obj2, obj3, obj4,
        obj5 with inverse_mass = 0 (infinitely massive); objects collide elastically off
        the inside faces
In[3]:= new torus { mass = 1, inner_radius = 1, outer_radius = 2, orientation =
        [0.888073833977115, -0.325057583671868, 0.325057583671868, 0] }
Out[3]= obj6
In[4]:= new point { mass = 1, position = [1.406590, -0.995859, 0.569601], velocity =
        [100, 200, 100] }
Out[4]= obj7
In[5]:= new sphere { mass = 2, radius = 1/2, position = [1.424704, 1.367496, -0.493612]
        }
Out[5]= obj8
In[6]:= new disk { mass = 2/3, radius = 1, position = [-0.677386, -1.041493,
        -1.091679], orientation = [0.900447102352677, 0.307567078752479,
        -0.307567078752479, 0] }
Out[6]= obj9

```

```

In[7]:= new cuboid { mass = 5/3, half_extents = [0.5, 0.5, 0.5], position = [1.074397,
    0.816223, 1.102099] }
Out[7]= obj10
In[8]:= new cylinder { mass = 2, radius = 1/2, height = 3/2, position = [-1.027024,
    -1.403890, -0.485619], orientation = [0.968912421710645, 0, 0.247403959254523, 0] }
Out[8]= obj11
In[9]:= list
Out[9]= obj0: cuboid he=[1, 4, 4], mass=0, charge=0, pos=[3, 0, 0] [wall: static,
    inverse_mass=0]
obj1: cuboid he=[1, 4, 4], mass=0, charge=0, pos=[-3, 0, 0] [wall: static, inverse_mass
    =0]
obj2: cuboid he=[4, 1, 4], mass=0, charge=0, pos=[0, 3, 0] [wall: static, inverse_mass
    =0]
obj3: cuboid he=[4, 1, 4], mass=0, charge=0, pos=[0, -3, 0] [wall: static, inverse_mass
    =0]
obj4: cuboid he=[4, 4, 1], mass=0, charge=0, pos=[0, 0, 3] [wall: static, inverse_mass
    =0]
obj5: cuboid he=[4, 4, 1], mass=0, charge=0, pos=[0, 0, -3] [wall: static, inverse_mass
    =0]
obj6: torus ring=1.5 tube=0.5, mass=1, charge=0, pos=[0, 0, 0]
obj7: point, mass=1, charge=0, pos=[1.40659, -0.995859, 0.569601]
obj8: sphere r=0.5, mass=2, charge=0, pos=[1.424704, 1.367496, -0.493612]
obj9: disk r=1, mass=0.6666666666666666, charge=0, pos=[-0.677386, -1.041493,
    -1.091679]
obj10: cuboid he=[0.5, 0.5, 0.5], mass=1.6666666666666667, charge=0, pos=[1.074397,
    0.816223, 1.102099]
obj11: cylinder r=0.5 h=1.5, mass=2, charge=0, pos=[-1.027024, -1.40389, -0.485619]
In[10]:= collide
Out[10]= collisions ON (51 collidable pair(s); 0 impulse(s) so far)
In[11]:= get obj0.inverse_mass
Out[11]= 0
In[12]:= get obj6.inertia_tensor
Out[12]= [[1.28125, 0, 0], [0, 1.28125, 0], [0, 0, 2.4375]]
In[13]:= energy
Out[13]= 30000
In[14]:= momentum
Out[14]= [100, 200, 100]
In[15]:= run 0.1 steps 100
Out[15]= t = 0.1 (2121 solver steps, 100 snapshots, |dE/E| = 2.040e-10, 119 collision(s)
    ) -- CONTACTS lists them)
In[16]:= energy
Out[16]= 29999.999993880127
In[17]:= momentum
Out[17]= [146.48911126803657, 102.1478121131382, 46.01601291636828]
In[18]:= get system.collisions
Out[18]= 119
In[19]:= get system.box
Out[19]= 4

```

What to notice. Cell 3 sizes the torus by the order-independent `inner_radius + outer_radius` pair; cell 8 uses `height = 3/2` — the *full* height, so `half_height` reads 0.75. COLLIDE counts **51 collidable pairs**: 12 objects make 66 pairs, minus the 15 wall–wall pairs (two static bodies

can never collide). Out[12] is the torus's analytic inertia diag(1.28125, 1.28125, 2.4375) — exactly $I_{xy} = m(\frac{1}{2}c^2 + \frac{5}{8}a^2)$, $I_z = m(c^2 + \frac{3}{4}a^2)$ for $c = 1.5$, $a = 0.5$. The energy starts at $E_0 = \frac{1}{2} \cdot 1 \cdot |v|^2 = 30000$ **exactly** and, after **119 collisions** in 0.1s, is conserved to $|dE/E| = 2.040 \times 10^{-10}$ — but momentum went from (100, 200, 100) to (146.49, 102.15, 46.02): **not conserved**, because the infinitely massive walls absorb momentum without moving — the physical signature of infinite mass. Along the way the point particle can *thread the torus hole* and passes through the ideal zero-thickness disk (a measure-zero contact) — the ball-vs-anything collision tier is exact SDF geometry, not an approximation — while every finite-size body bounces off both. The walls end the run bit-identically at rest.

9.14 Example 14 — two dumbbells from a user-defined function

The two-release finale: a user function (§5.8) that builds **named dumbbells** (§5.1), called twice to launch a pair of tumbling dumbbells at each other, off-center and spinning. No walls this time — so *all three* conserved quantities must survive the collisions. The script is scripts/collisions/12_two_dumbbells.p this transcript replays it.

```
In[1]:= set system.g_constant = 0
In[2]:= def create_dumbbell(name, m1 = 1, m2 = 1, m_rod = 0.5, r1 = 0.25, r2 = 0.25,
    rod_radius = 0.1, length = 1, position = [0, 0, 0], velocity = [0, 0, 0],
    angular_velocity = [0, 0, 0]) {
    new dumbbell as name { m1 = m1, m2 = m2, m_rod = m_rod, r1 = r1, r2 = r2, rod_radius
        = rod_radius, length = length, position = position, velocity = velocity,
        angular_velocity = angular_velocity }
}
Out[2]= function create_dumbbell(11 parameter(s)) defined -- 1 body line(s)
In[3]:= create_dumbbell("dumbell0", 1, 2, 0.5, 0.25, 0.25, 0.1, 1, [-2, 0.15, 0], [1.5,
    0, 0], [0, 0, 0.6])
Out[3]= obj0 as dumbell0
In[4]:= create_dumbbell("dumbell1", 2, 1, 0.4, 0.3, 0.2, 0.08, 1.2, [2, -0.15, 0],
    [-1.5, 0, 0], [0.4, 0, 0])
Out[4]= obj1 as dumbell1
In[5]:= list
Out[5]= obj0: dumbell1 r1=0.25 r2=0.25 rod_r=0.1 len=1, mass=3.5, charge=0, pos=[-2,
    0.15, 0]
obj1: dumbell1 r1=0.3 r2=0.2 rod_r=0.08 len=1.2, mass=3.4, charge=0, pos=[2, -0.15, 0]
In[6]:= get dumbell0.m1
Out[6]= 1
In[7]:= get dumbell1.m_rod
Out[7]= 0.39999999999999999
In[8]:= get dumbell0.vx
Out[8]= 1.5
In[9]:= energy
Out[9]= 7.865310611764706
In[10]:= momentum
Out[10]= [0.150000000000000036, 0, 0]
In[11]:= angmom
Out[11]= [0.4443030588235295, 0, -1.5059999999999998]
In[12]:= run 3 steps 60
Out[12]= t = 3 (3861 solver steps, 60 snapshots, |dE/E| = 9.463e-11, 2 collision(s) --
    CONTACTS lists them)
In[13]:= energy
```

```

Out[13]= 7.865310611020375
In[14]:= momentum
Out[14]= [0.15000000000000036, 0, 0]
In[15]:= angmom
Out[15]= [0.44430305882373156, -0.000000000000009547918011776346, -1.505999999999855]
In[16]:= get system.collisions
Out[16]= 2

```

What to notice. Cell 2 is one DEF whose single body line does everything: `new dumbbell as name { ... }` forwards all eleven parameters, and because `name` arrives as a string ("dumbell10", "dumbell11"), each call registers the name it was given — `Out[3]/Out[4]` show both handles, `LIST` shows the part geometry, and cells 6–8 read the parts and the `.vx` shorthand through the names. (`Out[7]` reads 0.4 back as 0.3999999999999999: the parts are stored as mass *fractions* of the total, so one reconstruction rounding step shows through — 15 correct digits.) Then the physics: two tumbling, asymmetric rigid bodies meet off-center, collide **twice** (cell 16), and every conserved quantity survives the real CVODE event handling. Energy: 7.865310611764706 → 7.865310611020375 — the run banner prints $|dE/E| = 9.463e-11$. Momentum: [0.15000000000000036, 0, 0] **bit-identical**. Angular momentum about the origin — the delicate one, orbital $r \times p$ plus spin, exchanged between the two at every off-center impact: conserved to $\sim 10^{-13}$ per component (`Out[11]` vs. `Out[15]`), because the part-wise exact narrow phase applies the action–reaction impulse pair at one shared contact point. Contrast Example 13: there the infinitely massive walls absorbed momentum; here, with no walls, E , P and L all hold at solver precision.

10 Error message tour

you type	you get
get obj7.mass (no obj7)	no object obj7
get obj0.bogus	unknown object field 'bogus' -- see HELP for the field list
[1,0,0] * [0,1,0]	cannot multiply vec3 by vec3 (for vec3*vec3 use dot()/cross())
set = 3	parse error at column 5: expected a path root ('objN' or 'system'), found '='
run 1 under SPRK with $B \neq 0$	SPRK method requires a separable Hamiltonian: magnetic field B must be zero ... use METHOD ADAMS or BDF
bogusname	unknown name 'bogusname' (define it with LET, pass it as a function parameter, or use 'bogusname.field' for a registered object)
get d.m1 (only ball is registered)	no object named 'd' (registered names: ["ball"]); NEW ... AS <name> creates one; positional paths are objN.field, contactK.field, system.field)
new sphere as d (name taken)	the name 'd' already refers to obj0 -- DEL it or pick another name
new sphere as system	'system' is reserved
show nosuch	no user function 'nosuch' -- FUNCS lists the defined ones

Every error names the column or the exact field/feature at fault, and never aborts the session.