

fp-tools: A Reproducible Platform for ATAC-seq Footprinting and Regulatory Motif Analysis

Yaoxiang Li ¹ and Chunling Yi ^{1,*}

¹ Department of Oncology, Lombardi Comprehensive Cancer Center, Georgetown University Medical Center, Georgetown University, Washington, DC, USA; yl814@georgetown.edu (Y.L.); cy232@georgetown.edu (C.Y.)

* Correspondence: cy232@georgetown.edu (C.Y.)

Abstract

ATAC-seq footprinting enables near-base-resolution inference of transcription-factor (TF) occupancy across the genome. However, the field lacks a computationally efficient, user-friendly, and integrated platform that accepts both bulk and single-cell ATAC-seq data, supports both de novo motif discovery and matching to public motif databases, and generates interactive and publication-ready visual outputs. Here, we present fp-tools, a Python package that builds on the widely used ATAC-seq footprinting framework TOBIAS. We substantially improve computational efficiency across key steps, including Tn5 bias correction, footprint calling, and motif matching. In addition, fp-tools introduces de novo motif discovery, replicate-aware differential footprinting, and aggregation analysis, features not provided as native TOBIAS workflows. We further streamline a single-cell ATAC-seq footprinting workflow, provide interactive visualization of analysis results, and implement a graphical user interface (GUI) that enables code-free execution of all package commands. Using public bulk ATAC-seq replicates and single-cell datasets, we demonstrate that fp-tools quantitatively recovers cell-type-specific TF-binding patterns and identifies de novo binding motifs that are not captured by existing public motif databases. Together, fp-tools provides an efficient, accessible, and comprehensive platform for TF footprint analysis across bulk and single-cell ATAC-seq studies.

Keywords: ATAC-seq; transcription factor footprinting; chromatin accessibility; motif analysis; pseudobulk ATAC-seq; replicate-aware reporting; reproducibility; command-line bioinformatics

1. Introduction

Chromatin accessibility profiling by the assay for transposase-accessible chromatin using sequencing (ATAC-seq) has become a standard readout of active regulatory DNA [1]. Within accessible regions, sequence-specific transcription factors (TFs) can protect bound DNA from transposition, producing local cut-site depletions, or “footprints,” with increased accessibility in nearby flanks. Detecting these motif-centered cut-site patterns supports inference of TF occupancy, differential regulatory activity between conditions, and interpretation of non-coding regulatory variants. Earlier footprinting and occupancy models, including CENTIPEDE, Wellington, PIQ, and DeFCoM, established the value of combining sequence information with chromatin accessibility profile shape for TF-binding-site inference [2–5].

Despite this progress, practical ATAC-seq footprinting remains difficult to run as a complete and reproducible analysis. Widely used tools such as TOBIAS [6] and HINT-ATAC [7] provide enzymatic bias correction and footprint scoring for bulk ATAC-seq data.

Received:

Accepted:

Published:

Copyright: © 2026 by the authors.

Submitted to *BioMedInformatics* for possible open access publication under the terms and conditions of the

[Creative Commons Attribution \(CC BY\)](https://creativecommons.org/licenses/by/4.0/) license.

Multiscale and nucleosome-aware approaches, including the PRINT/scPrinter family [8], extend footprint modeling across different scales of chromatin protection. Supervised TF-binding-site predictors such as maxATAC [9] and sequence-to-profile models such as ChromBPNet [10] provide complementary prediction frameworks. Motif-discovery and motif-comparison tools, including MEME/STREME [11,12] and Tomtom [13], are commonly used after peak or footprint selection, and curated databases such as JASPAR [14] remain central for known-motif matching. These tools are valuable, but they are typically assembled through separate command interfaces, file conventions, report formats, and visualization steps.

This fragmentation creates a practical barrier for many applied studies. A complete analysis must connect ATAC-seq input processing, Tn5 sequence-bias correction, footprint scoring, motif matching, optional de novo motif discovery, differential footprint analysis, aggregate visualization, and publication-ready reporting. Single-cell ATAC-seq adds another difficulty: sparse per-cell fragments usually need to be aggregated into cell-type, cluster, or neighborhood-level profiles before footprinting can be interpreted. For many biology laboratories, the limiting step is therefore not one missing algorithm, but the absence of an efficient platform that connects these steps and preserves the analysis record.

We developed `fp-tools` to address this need. The package builds on the widely used TOBIAS ATAC-seq footprinting framework and keeps its interpretable motif-centered footprint logic, while improving speed and usability around the core analysis. Compared with TOBIAS, `fp-tools` adds de novo motif preparation and matching, replicate-aware differential footprint reports, pseudobulk single-cell ATAC-seq support, interactive HTML reports, editable SVG outputs, and a graphical user interface for code-free execution of the same command-compatible workflows.

Here, we describe the `fp-tools` implementation and evaluate it with public bulk ATAC-seq replicates and public single-cell ATAC-seq datasets. We focus on practical improvements to established ATAC-seq footprinting: connecting common TF-footprinting tasks into one auditable analysis that can be run from the command line, saved YAML files, or the GUI.

2. Materials and Methods

2.1. Package Architecture and Core Workflows

`fp-tools` accelerates the main signal-processing steps used in ATAC-seq footprinting. The core analysis includes Tn5 sequence-bias correction, footprint scoring over corrected signal, motif-anchored differential analysis, and aggregate visualization around TFBS or region sets. These steps use shared region, signal, motif, and sample-label conventions, so the output of one step can be used directly by the next. YAML configuration files provide a reproducible way to save and rerun the same analysis without changing the underlying methods.

Following the signal model popularized by TOBIAS [6], `fp-tools` treats base-resolution, bias-corrected cut-site profiles as the primary footprinting signal. This design preserves the familiar bulk ATAC footprinting interpretation: the biological signal is a corrected center-versus-flank cut-site contrast at motif or candidate sites. After bias correction, `fp-tools` can additionally rescale corrected cut-site tracks before footprint scoring by matching the 95th percentile of signal over shared background regions to an across-sample target, usually the median. This robust q95 scaling reduces sample-to-sample signal-level variation before footprint scoring while being less sensitive to rare extreme bins than full quantile matching. The package keeps this signal definition while recording sample labels, input manifests, reusable configuration, replicate summaries, and report outputs. For

footprint calling, let x_i denote corrected Tn5 cut-site signal around candidate position p . The default footprint score is a center-versus-flank contrast,

$$F(p) = \frac{1}{|L| + |R|} \left(\sum_{i \in L} x_i + \sum_{i \in R} x_i \right) - \frac{1}{|C|} \sum_{i \in C} x_i,$$

where C is the protected center and L and R are flanking windows. Larger values therefore correspond to the expected footprint pattern: fewer cuts at the putative bound site and more cuts in nearby accessible flanks.

2.2. De Novo Motif Discovery Preparation

The de novo motif-discovery module begins from candidate footprint intervals, which may be produced by footprint calling or provided as input. For each candidate interval j with center p_j , strand a_j , and flank size h , it exports a candidate-centered sequence

$$S_j = G[p_j - h, p_j + h],$$

reverse-complementing the sequence when strand information indicates the negative strand. The module records the input intervals, genome build, flank width, software versions, and MEME, DREME, STREME [11,12,15] or optional Tomtom [13] settings needed to reproduce each run. STREME was designed for accurate motif discovery from enriched sequence sets [12]. Discovered motifs can be analyzed as an independent motif set or matched to a known database such as JASPAR 2026 [14] and appended to the known motif set for downstream differential footprint analysis. In this design, candidate FASTA export, motif discovery, motif comparison, and database augmentation become part of the recorded footprint analysis.

2.3. Pseudobulk Fragment Aggregation

The pseudobulk module groups single-cell ATAC fragments by a metadata column, such as cell type, cluster, donor, or treatment. Let F_b be the multiset of fragments assigned to barcode b , and let $g(b)$ be its group label. The pseudobulk fragment collection for group k is the concatenated multiset

$$F_k = \text{concat}_{b:g(b)=k}(F_b),$$

so repeated fragments and fragment multiplicity are preserved. Groups that pass specified cell-count and fragment-count filters are written as bulk-like fragment files with manifest records. When genome sizes are supplied, `fp-tools` can also emit CPM-normalized cut-site bigWigs,

$$y_{k,t} = 10^6 \frac{c_{k,t}}{\sum_u c_{k,u}},$$

where $c_{k,t}$ is the cut-site count for group k at genomic position t . These tracks support motif-centered aggregate profiles matched to the bulk ATAC-seq analysis path. The full pseudobulk route writes pseudo-paired BAMs from grouped fragments and then runs correction, scoring, motif-aware comparison, and plotting with the same conventions used for bulk ATAC-seq.

For cell-level marker visualization, `fp-tools` also computes K-nearest-neighbor (KNN)-smoothed footprint signatures from single-cell fragments. For each marker TF, motif centers are scanned inside the selected accessible-bin universe. Fragment cut sites are counted in a ± 100 bp window around those motif centers for each barcode. Each cell is assigned a local neighborhood profile by summing its 75 nearest neighbors in the single-cell embedding, and a flank-minus-center footprint-signature score is computed from that

neighborhood profile. Scores are oriented so that the expected marker cell type has the positive direction and then standardized per TF for UMAP display. These KNN-smoothed signatures summarize local, motif-centered cut-site patterns across neighboring cells, while full ATAC-corrected footprint tracks are computed from the grouped pseudobulk profiles.

2.4. Replicate-aware Differential Footprint Analysis

The differential footprint module supports both single-sample contrasts and replicate-supported comparisons. It retains conventional motif-centered footprint-score logic while adding repeated condition labels, replicate-level summaries, and replicate-aware testing. Repeated condition names, for example `-cond-names Bcell Bcell Tcell Tcell`, define biological replicate groups while preserving the original differential-footprint output structure. Let $x_{c,r,i}$ be the footprint score at site or background position i for replicate r of condition c .

For one-sample versus one-sample contrasts, `diff-footprints` uses the motif-site versus background-distribution comparison of the standard TOBIAS-style report. Candidate sites are grouped by motif, site-level changes at motif sites are compared with matched background changes, and p-values are adjusted across motifs within each contrast.

For replicate-supported comparisons, `fp-tools` generalizes this comparison to multiple samples per condition. Footprint scores are computed for each replicate on the same peak and motif-site universe; motif-site and background distributions are then summarized at the condition level before reporting the same change, log-fold-change, p-value, and adjusted q-value columns. The report also includes replicate counts, condition means, SDs, and SE summaries, so the additional samples contribute to a more stable estimate rather than being collapsed outside the analysis.

Quantile normalization remains an optional comparison-stage adjustment. In single-sample contrasts, sample-quantile normalization provides the conventional two-sample score-distribution matching. In replicate-supported comparisons, condition-quantile normalization averages background distributions within each condition, fits one normalization factor per condition, and applies that factor to the replicates before condition summaries are computed. This option is used as a sensitivity adjustment; the main replicate-aware extension is the explicit use of replicate-level motif scores.

When per-sample motif-score matrices are available, `fp-tools` further applies empirical-Bayes variance moderation across motifs, following the moderated testing framework of Smyth [16]. This replicate-supported view estimates condition effects from the per-sample motif scores and moderates the per-motif variance across the motif set before computing adjusted differential-footprint statistics.

2.5. Public Data Processing and Evaluation

The bulk replicate demonstration uses true biological replicates from the Buenrostro et al. ATAC-seq study [1]: GM12878/B-cell samples SRR891268 and SRR891269, and day-1 CD4 T-cell samples SRR891275 and SRR891276. Reads were trimmed with `fastp` [17], aligned with `Bowtie2` [18], processed with `SAMtools` [19] and `BEDTools` [20], and peaks were called with `MACS3` using the `MACS` model-based peak-calling framework [21]. Problematic genomic regions were filtered using the ENCODE blacklist [22]. Replicate peaks were merged into a common peak universe, bias-corrected, q95-scaled over shared background regions, footprint-called, and analyzed by differential footprint comparison. The analysis used JASPAR 2026 CORE vertebrates non-redundant motifs [14] for known-motif scanning. Exact command-line parameters and software versions are recorded in source TSV files in the manuscript `tables` directory and summarized in Tables S1 and S2.

Public inputs are organized as versioned TSV manifests that record source URLs, accessions, assemblies, checksums, local paths, and analysis labels. Discovery and download scripts query public repositories such as ENCODE [23] for released human GRCh38 ATAC-seq records and write resumable download reports. The manuscript evaluation combines compact regression inputs, public bulk ATAC replicates, de novo motif-preparation examples, and public PBMC single-cell ATAC examples. For each analysis, command-line parameters, software versions, resolved input manifests, source tables, and generated figure inputs are kept with the manuscript resources so the reported examples can be rerun and audited.

2.6. Reproducibility Engineering

The package includes unit tests for numerical helpers and CLI behavior, plus automated output checks for footprint calling, differential footprint analysis, and aggregate plotting, with an opt-in slow check for bias correction. Continuous integration runs the suite on compact reference inputs, builds source and wheel artifacts, and verifies the installed console scripts. The repository also includes `environment.yml`, a Dockerfile, release metadata, and Make targets for testing, building, and manuscript checks. These choices follow FAIR-oriented research-software principles and established bioinformatics environment practices [24–26]. Analysis scripts record random seeds, tool versions, command lines, and resolved manifests alongside the corresponding outputs. Figure source tables and editable figure files are retained with the manuscript resources for auditability.

3. Results

We evaluated `fp-tools` for command stability, local runtime and memory behavior, and biological plausibility in public bulk and single-cell ATAC-seq examples.

3.1. A Unified, Reproducible Footprinting Platform

`fp-tools` consolidates the core ATAC-seq footprinting steps into one command-compatible analysis. Bias correction, footprint calling, differential footprint analysis, and aggregate visualization share region and signal conventions, reducing the need for file-format conversion between steps. YAML configuration records the same analysis in a machine-readable form for reruns and batch processing (Figure 1).

3.2. Interactive Interfaces and Report Review

In addition to direct command-line execution, `fp-tools` provides browser-based interfaces for configuring analyses and reviewing results. The GUI writes reusable YAML configurations that remain compatible with command-line execution and provides guided panels for the same core commands shown in the documentation (Figure 6). Differential-footprint and aggregate-batch runs also produce self-contained HTML reports with embedded compressed data, searchable motif controls, editable group colors, synchronized aggregate profiles, and SVG export for publication-ready editing.

3.3. Tested Output Stability

The package includes automated checks that run core commands on compact reference inputs and compare key summary outputs for footprint calling, differential footprint analysis, and aggregate plotting. Additional checks exercise public command-line entry points and saved YAML configurations. Together, these tests help ensure that updates preserve the expected behavior of the main workflows and shared input/output conventions.




Figure 1. Overview of the fp-tools ATAC-seq footprinting platform. Bulk ATAC-seq BAM/fragments and single-cell ATAC fragments with annotations enter a shared command-oriented analysis. The analysis supports Tn5 bias correction, footprint calling, motif matching against curated databases, de novo motif discovery, replicate-aware differential footprint analysis, aggregate footprint visualization, and pseudobulk single-cell footprint analysis.

3.4. De Novo Motif Discovery Complements Database-based Motif Analysis

The de novo motif-preparation path converts candidate footprint intervals into centered FASTA files, runs MEME, DREME, or STREME, optionally compares discovered motifs with a known database using Tomtom, and writes TSV/HTML summaries with inline consensus logos. This extends the TOBIAS-style known-motif path by adding a recorded handoff from footprint candidates to motif discovery; it does not change the center-versus-flank footprint scoring model. The module can be run alone to discover recurring patterns in candidate intervals, or after known-motif scanning to find motifs that are absent from the selected database.

We tested whether candidate-derived motifs add information beyond a fixed database using a 3-vs-3 public ENCODE K562 versus HepG2 ATAC-seq comparison [23]. Candidate footprints were called from bias-corrected cut-site tracks, condition-specific candidate FASTA files were exported with 75 bp flanks, and STREME was run reciprocally with K562

candidates against HepG2 controls and HepG2 candidates against K562 controls. These discovered motifs were then used in two modes. In de novo-only mode, the candidate-derived motifs were tested as their own motif set. In supplement mode, the same motifs were appended to a known motif database before running the sample-quantile-normalized differential-footprint analysis.

The full JASPAR 2026 vertebrate non-redundant set contained 1019 motifs, and the reciprocal STREME runs contributed 500 candidate-derived motifs from both ENCODE cell lines. We interpret this run as a site-recovery test of how far de novo-only discovery can cover database-supported footprints and complement a curated motif database. In de novo-only mode, recovery was measured as base-pair overlap after merging the bound-site windows produced by the de novo scan and the corresponding JASPAR-supported scan. By this operational metric, discovered motifs recovered 84.0% of merged JASPAR-supported bound-site-window base pairs across the K562/HepG2 comparison, while 16.0% remained unique to the full JASPAR scan. The de novo-only scan also introduced candidate-derived bound-site windows corresponding to 6.0% of the de novo-only merged window base pairs.

In supplement mode, discovered motifs are appended to known motifs before the same motif-aware differential footprint analysis. As a sensitivity test, we constructed a K562/HepG2-focused restricted JASPAR 2026 set with 867 motifs by removing common erythroid/K562 and liver/HepG2 motif families, then reran the comparison with and without the de novo motifs. In the interactive report, the restricted database yielded 92 display-priority motif families according to the highlighted report-selection flag; adding the 500 de novo motifs increased this browsing set to 153 families, including 24 de novo-derived motifs. Because highlighted is not a multiple-testing-corrected significance label, these counts are treated only as report-prioritization output. This sensitivity test illustrates the intended use case: when a chosen motif database is incomplete or conservative, candidate-derived motifs can be evaluated alone and can also be carried into the same differential footprint report as database-supported motifs (Figure 2).

A representative K562 versus HepG2 differential footprint report is shown in Figure 3. The report combines selected motif logos, top differential motif rankings, a volcano summary, and replicate-level aggregate footprint profiles in one browser-review view.

3.5. Replicate-aware Differential Footprint Analysis

The replicate-aware analysis reports differential footprint effect sizes, replicate support, and uncertainty summaries while keeping each comparison anchored to a common peak and motif-site universe. In the Buenrostro example, B-cell and T-cell replicates were scanned on the merged peak set before comparison, so no additional peak alignment step was needed at the reporting stage.

Repeated condition names define biological replicate groups. In one-sample contrasts, the report uses the motif-site versus background-distribution comparison. When multiple samples are available, motif scores are first aggregated per sample and then analyzed with empirical-Bayes variance moderation across motifs [16]. The replicate-supported output reports condition means, replicate counts, SD and SE summaries, moderated statistics, and adjusted q-values alongside the original motif-background comparison.

As a biological consistency check for the same 2-vs-2 Buenrostro comparison, we inspected aggregate corrected cut-site profiles for a small illustrative set selected for visible center depletion and known or plausible immune relevance. BACH2 showed a B/GM12878-biased aggregate pattern in this dataset, although it is not B-cell exclusive because it is also reused in T-cell states. JUNB and ATF7 showed stronger T-cell center depletion; JUNB is an AP-1 family regulator of T-cell differentiation [27], and ATF7 is included as a




Figure 2. De novo motif discovery and validation summary. (A) Candidate footprint or BED intervals are converted into centered FASTA sequences, analyzed with MEME/DREME/STREME, and summarized as motif tables and reports. (B) Merged site-window coverage compares shared and de novo-only motif-supported intervals in K562 and HepG2. (C,D) Representative K562 and HepG2 de novo motifs show footprint-like normalized cut-site aggregate profiles centered on motif instances.

strong aggregate example in this dataset rather than as a lineage-specific marker. IRF4 is included because TCR signaling can drive graded IRF4 expression in T cells [28], although its aggregate depletion is modest here. We treat these panels as a biological sanity check rather than a marker-classification benchmark; a more negative center-versus-flank profile indicates stronger footprint-like protection at motif centers.

3.6. Single-cell ATAC Fragments Support Pseudobulk Footprinting

We evaluated pseudobulk aggregation using the public 10x Genomics PBMC granulocyte-depleted Multiome dataset [29]. Using the official 10x ATAC fragments and GEX graph clusters, we assigned 11,898 annotated cells to broad immune groups and retained seven groups comprising 11,611 cells after requiring at least 300 cells and 50,000 fragments: B cells, CD4 T cells, NK/cytotoxic T cells, CD14 monocytes, FCGR3A monocytes, dendritic cells, and a mixed myeloid group. The prepared figure inputs used chromosomes chr1–chr22 plus chrX. The retained pseudobulks contained 13.6 to 144.0 million counted




Figure 3. Interactive differential footprint report for K562 versus HepG2. The browser report view summarizes selected differential motifs, motif logos, top differential footprint-score bar plots, a volcano plot, and replicate-level motif-centered aggregate profiles. Blue indicates HepG2-biased footprint scores and red indicates K562-biased footprint scores.

fragments per group and were written as indexed fragment files plus CPM-normalized cut-site bigWigs.

The full pseudobulk-footprints route uses the same grouped fragments to emit pseudo-paired BAMs, run `atac-correct` with zero read shifting, score corrected footprint tracks, and optionally run `motif-aware diff-footprints` and aggregate plotting. Raw CPM cut-site tracks provide QC and chromatin-context signal alongside corrected footprint scores. Compared with preparing pseudobulk inputs outside the footprinting analysis and then running TOBIAS, `fp-tools` records barcode grouping, pseudobulk QC, correction, footprint scoring, motif-aware comparison, and aggregate plotting in one analysis route. This pseudobulk analysis is complementary to established single-cell chromatin-accessibility ecosystems such as ArchR and Signac and to motif-activity baselines such as chromVAR [30–32].

The pseudobulk footprint result table was also used to prioritize marker TFs for cell-level visualization. We summarized the three broad-cell pairwise comparisons as volcano plots and labeled only predeclared marker TFs from the two cell types included in each comparison when the differential-footprint direction matched the expected lineage direction. Third-lineage markers and opposite-direction markers were not annotated.

We also applied the per-cell KNN visualization layer to the public 10x Genomics 5k PBMC single-cell ATAC dataset [33]. This example used the Cell Ranger ATAC 2.0.0 fragment dataset, broad B-cell, monocyte, and T/NK annotations derived from the single-cell embedding, and motif-centered marker scores for PAX5, CEBPB, TCF7, and four additional high-change marker TFs from the pairwise pseudobulk screen: CEBPA, SPIB, ZBTB7B, and POU2F2. For each cell, the plotted value is a KNN-smoothed footprint-signature score derived from local motif-centered cut-site profiles. We summarize these scores as a marker-by-cell-type heatmap and as UMAP projections for one representative marker from each broad cell type. The expected marker directions were recovered: PAX5 and POU2F2 showed B-cell-associated signal, CEBPB and CEBPA showed monocyte-associated signal, and TCF7 and ZBTB7B showed T/NK-associated signal; SPIB is included as an additional high-change B-cell marker from the pseudobulk screen (Figure 4).

3.7. Evaluation and Figure Reproducibility

Manifests, schema validation, engineering-runtime recording, and figure scripts provide an executable path from public inputs to publication-ready outputs. These resources verify stable outputs on compact fixtures and public-data subsets, support the bulk, de novo, pseudobulk, replicate-aware, and report examples, and keep sample, parameter, motif, region, and signal-track choices auditable.

The evaluation pipeline writes resolved manifests, software versions, parameters, and plotting tables next to generated figures. Representative local engineering measurements summarize runtime and peak memory for one local comparison using the same input bundle and command-level outputs (Figure 5). The browser GUI keeps the same command-first structure while making example loading, YAML review, run history, and report inspection accessible to researchers who do not routinely work at the command line (Figure 6).

4. Discussion

`fp-tools` is a practical extension of motif-centered ATAC-seq footprinting and regulatory motif analysis. Its strengths are consistent interfaces across bias correction, footprint calling, differential footprint analysis, and aggregate visualization; automated output checks; explicit replicate-aware summaries; and integrated de novo motif preparation and pseudobulk aggregation using the same region, motif, and signal conventions (Table 1).




Figure 4. Single-cell footprinting summary in public PBMC5k single-cell ATAC data. **(A)** KNN-smoothed per-cell footprint-signature heatmap for selected marker TFs and top cell-type-specific motif signatures across B cells, monocytes, and T/NK cells. **(B)** UMAP projections show broad cell-type annotations and representative marker footprint-signature z-scores. Positive values indicate the marker-oriented footprint-signature direction after per-TF standardization; ATAC-corrected footprint tracks are computed from grouped pseudobulk profiles.

These features address a common practical problem: footprint scoring, motif interpretation, and report generation are often handled by separate scripts or tools.

The closest comparison is TOBIAS, which established a widely used ATAC footprinting workflow for bias correction, footprint scoring, motif-aware differential analysis, and aggregate visualization. fp-tools keeps the same interpretable bias-corrected center-versus-flank signal model and improves the surrounding analysis layer: faster core operations, consistent modern command names, reusable YAML execution, report and SVG




Figure 5. Representative local engineering comparison. (A) Runtime and (B) peak memory are summarized for one local analysis run comparing TOBIAS and fp-tools on the same analysis bundle. These measurements are included as an engineering check, not as an exhaustive cross-tool benchmark.




Figure 6. Browser GUI for command-compatible footprinting analyses. The GUI provides sidebar access to core commands, guided configuration panels, example loading, YAML preview, run-history review, and report/output inspection while preserving CLI-compatible configuration files.

export, explicit replicate-reporting modes, de novo motif-preparation handoff, pseudobulk single-cell aggregation, GUI access, and tested example outputs.

Table 1. Qualitative scope comparison across widely used ATAC-seq regulatory-analysis tools. ✓, documented native support; ○, partial, indirect, or adjacent support; NA, outside the tool’s primary scope. The table summarizes analysis scope from public documentation and primary publications; it is not a performance benchmark and should be read with the different goals of each tool in mind. TOBIAS is the closest core footprinting comparator; the fp-tools columns emphasize added analysis and usability components around that motif-centered model.

Feature	fp-tools	TOBIAS	HINT-ATAC	PRINT/scPrinter	ChromBPNet	max ATAC
Bulk ATAC footprinting	✓	✓	✓	✓	○	NA
Tn5 bias correction	✓	✓	✓	✓	✓	NA
Footprint calling	✓	✓	✓	✓	NA	NA
Motif-aware differential analysis	✓	✓	○	○	NA	NA
De novo motif preparation	✓	NA	NA	✓	○	NA
scATAC/pseudobulk support	✓	○	○	✓	○	○
Replicate-aware reporting	✓	○	○	○	NA	NA
Visualization/reporting	✓	✓	○	✓	✓	○
YAML/batch execution	✓	NA	NA	NA	NA	NA

Other regulatory-analysis tools address adjacent but distinct questions. Deep sequence-to-profile models such as ChromBPNet learn sequence determinants of chromatin profiles

and are well suited for occupancy and variant-effect analyses [10], while accessibility-based frameworks such as diffTF estimate differential TF activity from changes in open chromatin [34]. These approaches are complementary to motif-centered footprinting. The role of `fp-tools` is to make interpretable ATAC-seq footprint analysis easier to run end to end: corrected cut-site signals, motif matching, de novo motif preparation, pseudobulk single-cell analysis, replicate-aware reporting, GUI execution, and publication-ready reports are kept within one reproducible workflow.

5. Conclusions

We presented `fp-tools`, a Python platform that unifies ATAC-seq footprinting with motif-discovery preparation, pseudobulk aggregation, and replicate-aware reporting. By pairing tested commands with public-data manifests, source tables, and reproducible figure generation, the package supports standardized and auditable regulatory-genomics analysis. Future work will add larger whole-genome transfer studies, direct external-tool comparisons, multiscale and nucleosome-aware validation, and stronger hierarchical differential-binding models.

Author Contributions: Conceptualization, Y.L. and C.Y.; methodology, Y.L.; software, Y.L.; validation, Y.L.; formal analysis, Y.L.; investigation, Y.L.; data curation, Y.L.; writing, original draft preparation, Y.L.; writing, review and editing, Y.L. and C.Y.; visualization, Y.L.; supervision, C.Y.; project administration, C.Y.; funding acquisition, C.Y. All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Institutional Review Board Statement: Not applicable. This study used only publicly available, de-identified datasets and did not involve new experiments on humans or animals.

Informed Consent Statement: Not applicable.

Data Availability Statement: `fp-tools` is openly available in the public GitHub repository [oncologylab/fp-tools](https://github.com/oncologylab/fp-tools). The repository contains the manifests, schemas, analysis scripts, figure generators, source tables, and small result tables used in this manuscript. Public input data are obtained from the ENCODE Project [23], the 10x Genomics PBMC Multiome example [29], the 10x Genomics PBMC5k single-cell ATAC example [33], and motif databases such as JASPAR [14] using the included download and preparation scripts. The computational environment is documented in `environment.yml` and the repository Dockerfile.

Acknowledgments: The authors thank the ENCODE Project Consortium and the maintainers of the open-source tools referenced in this work for making their data and software publicly available.

Conflicts of Interest: The authors declare no conflicts of interest.

Appendix

384

Table S1. Primary analysis parameters used for the public ATAC and pseudobulk workflows. The complete source table is provided in the Supplementary Materials as “Primary analysis parameters”.

Step	Parameters
Public input data	Bulk ATAC analyses use Buenrostro B-cell/T-cell FASTQs and ENCODE K562/HepG2 replicate tracks. Pseudobulk examples use public granulocyte-depleted 10x PBMC Multiome and PBMC5k scATAC fragment datasets. Motif analyses use JASPAR 2026 CORE vertebrate non-redundant motifs.
FASTQ preprocessing	Paired-end adapter detection and trimming with <code>fastp</code> ; HTML and JSON QC reports written for each sample.
Alignment and BAM processing	Reads aligned to hg38 with <code>bowtie2 -very-sensitive -X 2000</code> ; proper pairs retained with <code>samtools view -f 2 -F 2828 -q 30</code> ; BAMs sorted, fixed with <code>fixmate -m</code> , duplicate-marked with <code>markdup -r</code> , indexed, and summarized with <code>flagstat/idxstats</code> . Mitochondrial and nonstandard contigs excluded; hg38 blacklist v2 regions subtracted;
Blacklist and peak set	MACS3 paired-end peaks called at q-value 0.01 and merged across replicates into one analysis peak set.
Bias correction and footprint scores	<code>atac-correct</code> run on filtered BAMs with merged peaks and blacklist regions using default Tn5-bias settings; corrected cut-site tracks q95-scaled over shared background regions for multi-sample analyses; <code>call-footprints -score footprint</code> run with default footprint and flank windows.
Differential footprint analysis	Buenrostro and ENCODE replicate footprint tracks analyzed with repeated condition labels, JASPAR 2026 motifs, and replicate reporting enabled. One-sample contrasts use motif-site versus background-distribution comparison; replicate-supported analyses use empirical-Bayes variance moderation on per-sample aggregated motif scores.
De novo motif validation	ENCODE K562/HepG2 candidate footprints exported as condition-level FASTA files with ± 75 bp flanks; reciprocal STREME 5.5.9 runs used <code>-dna -nmotifs 250</code> ; Tomtom 5.5.9 matched discovered motifs to JASPAR 2026; de novo motifs were evaluated alone and as additions to known motif sets.
Pseudobulk PBMC analysis	10x PBMC fragments grouped by broad immune labels, retaining groups with at least 300 cells and 50,000 fragments. The full <code>pseudobulk-footprints</code> route writes pseudo-BAMs, runs ATAC correction with zero read shifting for fragment-derived pseudobulk BAMs, and emits footprint-score tracks, motif-aware differential results, and aggregate plots. The PBMC5k example uses broad B-cell/monocyte/T-NK labels, marker sites, pairwise volcano plots, and KNN-smoothed footprint-signature UMAPs.

Table S2. Software and resource versions used for manuscript analyses. The complete source table is provided in the Supplementary Materials as “Software and resource versions”.

Tool or resource	Version	Role
bedtools	2.31.1	Region sorting, merging, and blacklist subtraction
Biopython	1.87	Sequence and motif-related utilities
bowtie2	2.5.5	hg38 read alignment
Cell Ranger ARC	2.0.0	Source processing for the public 10x PBMC Multiome dataset
Cell Ranger ATAC	2.0.0	Source processing for the public 10x PBMC5k scATAC dataset
fastp	1.3.3	Paired-end FASTQ adapter detection, trimming, and QC
fp-tools	0.1.7	ATAC correction, footprint calling, motif matching, differential footprint analysis, pseudobulk utilities, and plotting helpers
hg38 blacklist	v2	Artifact-region filtering for processed bulk ATAC alignments
hg38 reference genome	GRCh38/hg38	Read alignment and sequence extraction
htslib	1.23.1	SAM/BAM/VCF I/O backend used by samtools
JASPAR CORE vertebrates	2026 non-redundant	Known motif database for differential footprint analysis
MACS3	3.0.4	ATAC-seq peak calling in paired-end mode
matplotlib	3.10.9	Manuscript figure rendering
MEME Suite, STREME, and Tomtom	5.5.9	De novo motif discovery and discovered-motif matching
NumPy	2.4.6	Numerical arrays and benchmark/figure calculations
pandas	2.3.3	Tabular processing for benchmark, manifest, and figure builders
pyBigWig	0.3.25	bigWig signal reading and writing
pysam	0.23.3	BAM and genomic interval I/O
Python	3.12.3	Runtime for analyses, figure builders, and provenance extraction
samtools	1.23.1	BAM filtering, sorting, fixmate, duplicate marking, indexing, and QC summaries
SciPy	1.17.1	Statistical and interpolation utilities

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

1. Buenrostro, J.D.; Giresi, P.G.; Zaba, L.C.; Chang, H.Y.; Greenleaf, W.J. Transposition of native chromatin for fast and sensitive epigenomic profiling of open chromatin, DNA-binding proteins and nucleosome position. *Nature Methods* **2013**, *10*, 1213–1218. <https://doi.org/10.1038/nmeth.2688>.
2. Pique-Regi, R.; Degner, J.F.; Pai, A.A.; Gaffney, D.J.; Gilad, Y.; Pritchard, J.K. Accurate inference of transcription factor binding from DNA sequence and chromatin accessibility data. *Genome Research* **2011**, *21*, 447–455. <https://doi.org/10.1101/gr.112623.110>.
3. Piper, J.; Elze, M.C.; Cauchy, P.; Cockerill, P.N.; Bonifer, C.; Ott, S. Wellington: a novel method for the accurate identification of digital genomic footprints from DNase-seq data. *Nucleic Acids Research* **2013**, *41*, e201. <https://doi.org/10.1093/nar/gkt850>.
4. Sherwood, R.I.; Hashimoto, T.; O'Donnell, C.W.; Lewis, S.; Barkal, A.A.; van Hoff, J.P.; Karun, V.; Jaakkola, T.; Gifford, D.K. Discovery of directional and nondirectional pioneer transcription factors by modeling DNase profile magnitude and shape. *Nature Biotechnology* **2014**, *32*, 171–178. <https://doi.org/10.1038/nbt.2798>.
5. Quach, B.; Furey, T.S. DeFCoM: analysis and modeling of transcription factor binding sites using a motif-centric genomic footprinter. *Bioinformatics* **2017**, *33*, 956–963. <https://doi.org/10.1093/bioinformatics/btw740>.
6. Bentsen, M.; Goymann, P.; Schultheis, H.; Klee, K.; Petrova, A.; Wiegandt, R.; Fust, A.; Preussner, J.; Kuenne, C.; Braun, T.; et al. ATAC-seq footprinting unravels kinetics of transcription factor binding during zygotic genome activation. *Nature Communications* **2020**, *11*, 4267. <https://doi.org/10.1038/s41467-020-18035-1>.

7. Li, Z.; Schulz, M.H.; Look, T.; Begemann, M.; Zenke, M.; Costa, I.G. Identification of transcription factor binding sites using ATAC-seq. *Genome Biology* **2019**, *20*, 45. <https://doi.org/10.1186/s13059-019-1642-2>.
8. Hu, Y.; Horlbeck, M.A.; Zhang, R.; Ma, S.; Shrestha, R.; Kartha, V.K.; Duarte, F.M.; Hock, C.; Savage, R.E.; Labade, A.; et al. Multiscale footprints reveal the organization of cis-regulatory elements. *Nature* **2025**, *638*, 779–786. <https://doi.org/10.1038/s41586-024-08443-4>.
9. Cazares, T.A.; Rizvi, F.W.; Iyer, B.; Chen, X.; Kotliar, M.; Bejjani, A.T.; Wayman, J.A.; Donmez, O.; Wronowski, B.; Parameswaran, S.; et al. maxATAC: Genome-scale transcription-factor binding prediction from ATAC-seq with deep neural networks. *PLoS Computational Biology* **2023**, *19*, e1010863. <https://doi.org/10.1371/journal.pcbi.1010863>.
10. Pampari, A.; Shcherbina, A.; Kvon, E.Z.; Kosicki, M.; Nair, S.; Kundu, S.; Kathiria, A.S.; Risca, V.I.; Hundenborn, K.; Zhou, Y.; et al. ChromBPNet: bias factorized, base-resolution deep learning models of chromatin accessibility reveal cis-regulatory sequence syntax, transcription factor footprints and regulatory variants. *bioRxiv* **2024**. Preprint, <https://doi.org/10.1101/2024.12.25.630221>.
11. Bailey, T.L.; Johnson, J.; Grant, C.E.; Noble, W.S. The MEME Suite. *Nucleic Acids Research* **2015**, *43*, W39–W49. <https://doi.org/10.1093/nar/gkv416>.
12. Bailey, T.L. STREME: accurate and versatile sequence motif discovery. *Bioinformatics* **2021**, *37*, 2834–2840. <https://doi.org/10.1093/bioinformatics/btab203>.
13. Gupta, S.; Stamatoyannopoulos, J.A.; Bailey, T.L.; Noble, W.S. Quantifying similarity between motifs. *Genome Biology* **2007**, *8*, R24. <https://doi.org/10.1186/gb-2007-8-2-r24>.
14. Ovek Baydar, D.; Rauluseviciute, I.; Aronsen, D.R.; Blanc-Mathieu, R.; Bonthuis, I.; de Beukelaer, H.; Ferenc, K.; Jegou, A.; Kumar, V.; Lemma, R.B.; et al. JASPAR 2026: expansion of transcription factor binding profiles and integration of deep learning models. *Nucleic Acids Research* **2026**, *54*, D184–D193. <https://doi.org/10.1093/nar/gkaf1209>.
15. Bailey, T.L. DREME: motif discovery in transcription factor ChIP-seq data. *Bioinformatics* **2011**, *27*, 1653–1659. <https://doi.org/10.1093/bioinformatics/btr261>.
16. Smyth, G.K. Linear models and empirical Bayes methods for assessing differential expression in microarray experiments. *Statistical Applications in Genetics and Molecular Biology* **2004**, *3*, Article 3. <https://doi.org/10.2202/1544-6115.1027>.
17. Chen, S.; Zhou, Y.; Chen, Y.; Gu, J. fastp: an ultra-fast all-in-one FASTQ preprocessor. *Bioinformatics* **2018**, *34*, i884–i890. <https://doi.org/10.1093/bioinformatics/bty560>.
18. Langmead, B.; Salzberg, S.L. Fast gapped-read alignment with Bowtie 2. *Nature Methods* **2012**, *9*, 357–359. <https://doi.org/10.1038/nmeth.1923>.
19. Li, H.; Handsaker, B.; Wysoker, A.; Fennell, T.; Ruan, J.; Homer, N.; Marth, G.; Abecasis, G.; Durbin, R.; 1000 Genome Project Data Processing Subgroup. The Sequence Alignment/Map format and SAMtools. *Bioinformatics* **2009**, *25*, 2078–2079. <https://doi.org/10.1093/bioinformatics/btp352>.
20. Quinlan, A.R.; Hall, I.M. BEDTools: a flexible suite of utilities for comparing genomic features. *Bioinformatics* **2010**, *26*, 841–842. <https://doi.org/10.1093/bioinformatics/btq033>.
21. Zhang, Y.; Liu, T.; Meyer, C.A.; Eeckhoute, J.; Johnson, D.S.; Bernstein, B.E.; Nussbaum, C.; Myers, R.M.; Brown, M.; Li, W.; et al. Model-based Analysis of ChIP-Seq (MACS). *Genome Biology* **2008**, *9*, R137. <https://doi.org/10.1186/gb-2008-9-9-r137>.
22. Amemiya, H.M.; Kundaje, A.; Boyle, A.P. The ENCODE Blacklist: Identification of Problematic Regions of the Genome. *Scientific Reports* **2019**, *9*, 9354. <https://doi.org/10.1038/s41598-019-45839-z>.
23. The ENCODE Project Consortium. An integrated encyclopedia of DNA elements in the human genome. *Nature* **2012**, *489*, 57–74. <https://doi.org/10.1038/nature11247>.
24. Wilkinson, M.D.; Dumontier, M.; Aalbersberg, I.J.; et al. The FAIR Guiding Principles for scientific data management and stewardship. *Scientific Data* **2016**, *3*, 160018. <https://doi.org/10.1038/sdata.2016.18>.
25. Gruening, B.; Dale, R.; Sjoedin, A.; Chapman, B.A.; Rowe, J.; Tomkins-Tinch, C.H.; Valieris, R.; Koester, J. Bioconda: sustainable and comprehensive software distribution for the life sciences. *Nature Methods* **2018**, *15*, 475–476. <https://doi.org/10.1038/s41592-018-0046-7>.

26. Ewels, P.A.; Peltzer, A.; Fillinger, S.; Patel, H.; Alneberg, J.; Wilm, A.; Garcia, M.U.; Di Tommaso, P.; Nahnsen, S. The nf-core framework for community-curated bioinformatics pipelines. *Nature Biotechnology* **2020**, *38*, 276–278. <https://doi.org/10.1038/s41587-020-0439-x>.
27. Katagiri, T.; Kameda, H.; Nakano, H.; Yamazaki, S. Regulation of T cell differentiation by the AP-1 transcription factor JunB. *Immunological Medicine* **2021**, *44*, 197–203. <https://doi.org/10.1080/25785826.2021.1872838>.
28. Conley, J.M.; Gallagher, M.P.; Rao, A.; Berg, L.J. Activation of the Tec Kinase ITK Controls Graded IRF4 Expression in Response to Variations in TCR Signal Strength. *Journal of Immunology* **2020**, *205*, 335–345. <https://doi.org/10.4049/jimmunol.1900853>.
29. 10x Genomics. PBMC from a healthy donor, granulocytes removed through cell sorting, single cell multiome ATAC + gene expression. 10x Genomics public dataset, Cell Ranger ARC 2.0.0, 2021. ATAC fragments, peak calls, TF-analysis tables, and gene-expression clustering outputs downloaded from 10x Genomics sample files. Available online: <https://www.10xgenomics.com/datasets/pbmc-from-a-healthy-donor-granulocytes-removed-through-cell-sorting-10-k-1-standard-2-0-0> (accessed on 22 June 2026).
30. Granja, J.M.; Corces, M.R.; Pierce, S.E.; et al. ArchR is a scalable software package for integrative single-cell chromatin accessibility analysis. *Nature Genetics* **2021**, *53*, 403–411. <https://doi.org/10.1038/s41588-021-00790-6>.
31. Stuart, T.; Srivastava, A.; Madad, S.; Lareau, C.; Satija, R. Single-cell chromatin state analysis with Signac. *Nature Methods* **2021**, *18*, 1333–1341. <https://doi.org/10.1038/s41592-021-01282-5>.
32. Schep, A.N.; Wu, B.; Buenrostro, J.D.; Greenleaf, W.J. chromVAR: inferring transcription-factor-associated accessibility from single-cell epigenomic data. *Nature Methods* **2017**, *14*, 975–978. <https://doi.org/10.1038/nmeth.4401>.
33. 10x Genomics. 5k Peripheral Blood Mononuclear Cells (PBMCs) from a Healthy Donor (Next GEM v1.1). 10x Genomics public dataset, Cell Ranger ATAC 2.0.0, 2021. Single-cell ATAC fragments and Cell Ranger ATAC outputs for the atac_pbmc_5k_nextgem dataset. Available online: <https://www.10xgenomics.com/datasets/5-k-peripheral-blood-mononuclear-cells-pbm-cs-from-a-healthy-donor-next-gem-v-1-1-1-1-standard-2-0-0> (accessed on 22 June 2026).
34. Berest, I.; Arnold, C.; Reyes-Palomares, A.; Palla, G.; Rasmussen, K.D.; Giles, H.; Bruch, P.M.; Binder, H.; Guenther, T. Quantification of differential transcription factor activity and multiomics-based classification into activators and repressors: diffTF. *Cell Reports* **2019**, *29*, 3147–3159.e12. <https://doi.org/10.1016/j.celrep.2019.10.106>.