Intro to ML
Naïve Bayes

Radoslav Neychev
Vladislav Goncharenko

girafe ai

MIPT, fall 2025

Outline


1. ML and AI overview
2. What is Machine Learning
3. Thesaurus and notation
4. Datasets
5. Exploratory data analysis
6. Maximum Likelihood Estimation
7. Some Machine Learning problems
8. Naïve Bayes classifier
9. Machine learning libraries

ML and AI overview

girafe ai

01

Natural Language Processing



Basics:

- Text vectorization
- Language models
- Recurrent Neural Networks
- Attention module


Natural Language Processing

Some achievements:

- Machine translation
- Texts classification
- Texts generation



Computer Vision



Basics:

- Classical CV (filters, border detectors)
- Convolutional Neural Networks


Computer Vision

Some achievements:

- Object detection
- Semantic segmentation
- Generative models










Reinforcement Learning




Basics:

- Q-learning
- DQN
- REINFORCE

Reinforcement Learning

Achievements:


- Alpha Go
- OpenAI Five
- DeepMind Star Craft 2








Machine Learning on Graphs






Basics:

- Random graphs
- Small world model
- Graphs convolutions


Machine Learning on Graphs

Some achievements:

- Communities detection
- Recommender systems




Machine Learning applications




Physics Informed Machine Learning

Great overview of physics informed models
https://www.youtube.com/watch?v=JoFW2uSd3Uo&list=PLMrJAkhIeNNQ0BaKuBKY43k4xMo6NSbBa




What is AI and ML for you



What is Machine Learning?

girafe
ai

02




[Youtube video]

Terms around ML

There are different words that occur in similar contexts, but mean different things:

- Artificial Intelligence
- Machine Learning
- Deep Learning
- Data Science
- Big Data



Artificial Intelligence




Any system that perceives its environment and takes actions that maximize its chances of achieving its goals. Wikipedia



The electric kettle is already part of Skynet!

Machine Learning


The study of computer algorithms that improve automatically through experience and by the use of data. Wikipedia



Machine Learning is the field of study that gives computers the ability to learn without being explicitly programmed
– Arthur Samuel (1959)

The most important distinguishing feature of machine learning is the statistical nature of the models.

Andrej Karpathy on software development https://www.youtube.com/watch?v=LCEmiRjPEtQ




Machine Learning vs Traditional Programming

Deep Learning

A specific type of models that has shown high results in many applied tasks in the last decade


One of the key success factors is compatibility with modern computing systems (GPUs), simplicity and flexibility of the architecture of a particular model




Data Science

An interdisciplinary field that uses scientific methods, processes, algorithms and systems to extract knowledge and insights from structured and unstructured data, and apply knowledge and actionable insights from data across a broad range of application domains. Wikipedia

That is, it is the application of mathematical methods to data to extract useful information (so-called insights)



Big Data




Source: Hilbert, M., & López, P. (2011). The World's Technological Capacity to Store, Communicate, and Compute Information. *Science*, 332(6025), 60 –65. http://www.martinhilbert.net/WorldInfoCapacity.html

A field that treats ways to analyze, systematically extract information from, or otherwise deal with data sets that are too large or complex to be dealt with by traditional data-processing application software. Wikipedia


The main distinguishing feature is the processing of a hitherto unprecedented amount of information and the development of methods for the effective processing of such data for a variety of purposes

Relation of terms and spheres




Data
Knowledge

Long before the ML




Isaac Newton




Johannes Kepler

Long before the ML



Eratosthenes

What it is actually



ML thesaurus

girafe
ai

03

ML thesaurus



Denote the ***dataset***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

ML thesaurus



Observation (or datum, or data point) is one piece of information.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

In many cases the **observations** are supposed to be ***i.i.d.***

- ***independent***
- ***identically distributed***

ML thesaurus

Feature (or predictor) represents some special property.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

ML thesaurus



These all are features

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

ML thesaurus



These all are features

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

ML thesaurus



These all are features

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

ML thesaurus



These all are features

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

ML thesaurus



And even the name is a ***feature***

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

ML thesaurus



The **feature matrix or design matrix** contains all the observations and their features

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

Features can even be multidimensional, we will discuss it later in this course

Matrix notation: features

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

Feature matrix is usually denoted as $X \in R^{n \times p}$

where n is number of objects in dataset and p is number of properties

ML thesaurus

Target represents the information we are interested in.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

*Target can be either a **number** (real, integer, etc.) – for **regression** problem*

ML thesaurus



Target represents the information we are interested in.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

*Or a **label** – for **classification** problem*

ML thesaurus



Target represents the information we are interested in.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Target (passed)
John	22	5	4	Brown	English	5	TRUE
Aahna	17	4	5	Brown	Hindi	4	TRUE
Emily	25	5	5	Blue	Chinese	5	TRUE
Michael	27	3	4	Green	French	5	TRUE
Some student	23	3	3	NA	Esperanto	2	FALSE

Mark can be treated as a label too (due to finite number of labels: 1 to 5)

Further here we will work with the numerical target (mark)

Matrix notation: target

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)
John	22	5	4	Brown	English	5
Aahna	17	4	5	Brown	Hindi	4
Emily	25	5	5	Blue	Chinese	5
Michael	27	3	4	Green	French	5
Some student	23	3	3	NA	Esperanto	2

Target matrix is usually denoted as $Y \in R^n$

where n is number of objects in dataset

ML thesaurus

The ***prediction*** contains values we predicted using some ***model***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	4.5
Aahna	17	4	5	Brown	Hindi	4	4.5
Emily	25	5	5	Blue	Chinese	5	5
Michael	27	3	4	Green	French	5	3.5
Some student	23	3	3	NA	Esperanto	2	3

One could notice that prediction just averages of Statistics and Python marks. So our ***model*** can be represented as follows:

$$\hat{\text{mark}}_{ML} = \frac{1}{2}\text{mark}_{Statistics} + \frac{1}{2}\text{mark}_{Python}$$

ML thesaurus



The ***prediction*** contains values we predicted using some ***model***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	1
Aahna	17	4	5	Brown	Hindi	4	5
Emily	25	5	5	Blue	Chinese	5	2
Michael	27	3	4	Green	French	5	4
Some student	23	3	3	NA	Esperanto	2	3

Different models can provide different predictions (even not meaningful):

$$\hat{\text{mark}}_{ML} = \text{random}(\text{integer from } [1; 5])$$

ML thesaurus



The ***prediction*** contains values we predicted using some ***model***.

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	1
Aahna	17	4	5	Brown	Hindi	4	5
Emily	25	5	5	Blue	Chinese	5	2
Michael	27	3	4	Green	French	5	4
Some student	23	3	3	NA	Esperanto	2	3

Different models can provide different predictions.

*Usually some **hypothesis** lies beneath the model choice.*

ML thesaurus

Loss function measures the error rate of our model.

Square deviation	Target (mark)	Predicted (mark)
16	5	1
1	4	5
9	5	2
1	5	4
1	2	3

- ***Mean Squared Error*** (where **y** is vector of targets):

$$MSE(\mathbf{y}, \hat{\mathbf{y}}) = \frac{1}{N}\|\mathbf{y} - \hat{\mathbf{y}}\|_2^2 = \frac{1}{N}\sum_i (y_i - \hat{y}_i)^2$$

ML thesaurus

Loss function measures the error rate of our model.

Absolute deviation	Target (mark)	Predicted (mark)
4	5	1
1	4	5
3	5	2
1	5	4
1	2	3

- ***Mean Absolute Error*** (where **y** is vector of targets):

$$MAE(\mathbf{y}, \hat{\mathbf{y}}) = \frac{1}{N}\|\mathbf{y} - \hat{\mathbf{y}}\|_1 = \frac{1}{N}\sum_i |y_i - \hat{y}_i|$$

ML thesaurus



To learn something, our ***model*** needs some degrees of freedom:

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	4.5
Aahna	17	4	5	Brown	Hindi	4	4.5
Emily	25	5	5	Blue	Chinese	5	5
Michael	27	3	4	Green	French	5	3.5
Some student	23	3	3	NA	Esperanto	2	3

$$\hat{\text{mark}}_{ML} = w_1 \cdot \text{mark}_{Statistics} + w_2 \cdot \text{mark}_{Python}$$

ML thesaurus

To learn something, our ***model*** needs some degrees of freedom:

Name	Age	Statistics (mark)	Python (mark)	Eye color	Native language	Target (mark)	Predicted (mark)
John	22	5	4	Brown	English	5	4.447
Aahna	17	4	5	Brown	Hindi	4	4.734
Emily	25	5	5	Blue	Chinese	5	5.101
Michael	27	3	4	Green	French	5	3.714
Some student	23	3	3	NA	Esperanto	2	3.060

$$\hat{\text{mark}}_{ML} = w_1 \cdot \text{mark}_{Statistics} + w_2 \cdot \text{mark}_{Python}$$

Main concepts



- Dataset (both X and Y)
  - Design matrix (only X)
  - Feature matrix (only X)
- Observation
  - object
  - datum
  - row of X
- Feature
  - column of X
- Target
  - Label
  - Y vector
- Model
- Prediction

Datasets
and where to find them

girafe
ai

04

Datasets search



Nowadays there are tons of data available on the Internet.

It covers most of the cases you can think of.

So the main problem is to search for the right one!

Let’s overview some ways to collect datasets.


Google dataset search

https://datasetsearch.research.google.com/

Contains main info about dataset

and links to sources.

Not all datasets are easily available



Kaggle

https://www.kaggle.com/datasets



Datasets

Explore, analyze, and share quality data. Learn more about data types, creating, and collaborating.

+ New Dataset | Your Work

Search datasets | Filters


All datasets | Computer Science | Education | Classification | Computer Vision | NLP | Data Visualization | Pre-Trained Model

Trending Datasets

See All



2023 Air Quality Data for CBSAs
Nikki Perry · Updated 20 hours ago
Usability **10.0** · 166 kB
16



Smite Item Statistics Data
Matt OP · Updated a day ago
Usability **10.0** · 15 kB
1 File (CSV)
16




Machine Learning Engineer Salary in 2024
Chopper53 · Updated 21 hours ago
Usability **10.0** · 110 kB
1 File (CSV)
8



FuelConsumption
Krupa Dharamshi · Updated a month ago
Usability **10.0** · 6 kB
1 File (CSV)
15


Hugging Face

https://huggingface.co/datasets



Papers with code (RIP)

https://paperswithcode.com/datasets




UCI ML repository

https://archive.ics.uci.edu/

Historical source of datasets.

Most of them collected in 90s and 00s.


We use some of them in this course.



Chatbots

Nowadays it is very good idea to give some chatbot a task to perform deep research on datasets availability on your topic for you.

Example for 3D cancer segmentation.




Standardization initiative

Croissant dataset standard

https://mlcommons.org/working-groups/data/croissant/


https://research.google/blog/croissant-a-metadata-format-for-ml-ready-datasets/



Remarkable datasets



- Fisher's irises
- Boston house prices (cancelled)
- Breast cancer
- MNIST
  - 1990s
  - 10k of 28*28 images
  - 10 classes
  - notMNIST
  - FashionMNIST
- ImageNet
  - 2010s
  - 14m of 224*224 images
  - 1000 classes



ML competitions



https://mlcontests.com/state-of-machine-learning-competitions-2024/

Exploratory data analysis (EDA)

girafe ai

05


Dataset analysis

Before you build any model it's important to analyse data you have with various methods because all the models depend on data and its structure.


See Anscombe's quartet for example:

four datasets that have nearly identical simple descriptive statistics, yet have very different distributions and appear very different when graphed

This process is called
Exploratory Data Analysis (EDA)



Steps of EDA



https://www.geeksforgeeks.org/what-is-exploratory-data-analysis/

Categorical features encoding



Great overview

https://github.com/Dyakonov/PZAD/blob/master/2020/PZAD2020_042featureengineering_07.pdf

Whole ebook on feature engineering https://feaz-book.com/

Maximum Likelihood Estimation

girafe ai

06

Parametric and nonparametric models

Nonparametric statistics is a type of statistical analysis that makes minimal assumptions about the underlying distribution of the data being studied. Often these models are infinite-dimensional, rather than finite dimensional, as is parametric statistics.

Nonparametric statistics can be used for descriptive statistics or statistical inference. Nonparametric tests are often used when the assumptions of parametric tests are evidently violated.

© Common knowledge site

Likelihood maximization



Consider the most simple case of discrete features and target.

Denote dataset X, Y generated by distribution with parameter θ

Likelihood of a parameter is defined as probability of sampling this particular data in case underlying distribution is defined by this parameter.

Maximization of likelihood means we choose the most probable parameters having this particular dataset

$$L(\theta|X,Y) = P(X,Y|\theta) \rightarrow \max_{\theta}$$

Note that likelihood is not probability function of θ

i.i.d. property



We can employ i.i.d property of data samples to split probability of the whole dataset into independent problems

$$P(X, Y|\theta) = \prod_i P(x_i, y_i|\theta)$$

Then we apply logarithm function to both parts of equation above

$$\log P(X, Y|\theta) = \sum_i \log P(x_i, y_i|\theta)$$

The latter expression is easier to operate with:
later we will predict log-probability of each object directly

Importance of iid and example of non iid data

Log-likelihood equivalence


Since logarithm is a convex function on an open set, it preserves maximum of expression when applied, so that

$$L(\theta|X,Y) \rightarrow \max_{\theta}$$

and

$$\log L(\theta|X,Y) \rightarrow \max_{\theta}$$

have the same solutions in terms of θ



Maximum Likelihood formula

$$\hat{\theta} = \arg\max_{\theta} L(\theta|X, Y)$$

is called maximum likelihood estimation of model parameters.

In optimization theory functions are usually minimized, so the same problem could be reformulated using **Negative Log-Likelihood (NLL)** loss

$$\hat{\theta} = \arg\min_{\theta} -\sum_{i} \log P(x_i, y_i|\theta)$$

Continuous parameter set



Here we formulate MLE in terms of probability which means we assume finite number of parameter values.

Defining MLE for infinite parameters set is left as easy exercise for you.
(Mostly replace summation with integral)

$$\hat{\theta} = \arg\min_{\theta} -\sum_{i} \log P(x_i, y_i|\theta)$$

Not only MLE



Generally in statistics plenty of ways to estimate parameters exist:

- Maximum likelihood estimators
- Bayes estimators
- Method of moments estimators
- Cramér–Rao bound
- Maximum a posteriori (MAP or EM algorithm)
- Particle filter
- Markov chain Monte Carlo (MCMC)
- Kalman filter, and its various derivatives
- Wiener filter

see https://en.wikipedia.org/wiki/Estimation_theory#Estimators
https://en.wikipedia.org/wiki/Estimator
https://en.wikipedia.org/wiki/Expectation%E2%80%93maximization_algorithm

Useful materials on MLE



- Nice video explanation
  - https://www.youtube.com/watch?v=YevSE6bRhTo
- Textual intro to MLE
  - https://www.statlect.com/fundamentals-of-statistics/maximum-likelihood
  - https://www.statlect.com/fundamentals-of-statistics/maximum-likelihood-algorithm

Machine Learning problems overview


girafe ai

07


Taxonomy of ML problems

- Supervised
  - true answers are given
- Unsupervised
  - no true answers
- Semi-supervised
- Self-supervised
- Reinforced
- Generative
- etc...

There's no full and non-intersecting taxonomy of ML tasks, but terms above are used in practice




Practical problem setup



Problems covered in this course

- Regression problem



Estimated (or predicted) Y value for observation i

Estimate of the regression intercept


Estimate of the regression slope

Value of X for observation i

$$\hat{Y}_i = b_0 + b_1 X_i$$


Problems covered in this course

- Regression problem
- Classification problem



Problems covered in this course

- Regression problem
- Classification problem
- Dimensionality reduction
- Clustering
- Anomaly detection



Naïve Bayes classifier


girafe ai

08

Bayesian statistics

is built around idea of distributions (not outcomes) as a central entity.

Short bayesian statistics intro: part 1, part 2



Bayes' theorem

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$

or, in our case

$$P(y_i = C_k|\mathbf{x}_i) = \frac{P(\mathbf{x}_i|y_i = C_k)P(y_i = C_k)}{P(\mathbf{x}_i)}$$

Naïve Bayes classifier

$\mathbf{x}_i \in \mathbb{R}^p \quad y_i \in \{C_1, \ldots, C_K\}$ for K-class classification

$$P(y_i = C_k | \mathbf{x}_i) = \frac{P(\mathbf{x}_i | y_i = C_k) P(y_i = C_k)}{P(\mathbf{x}_i)}$$

Naïve assumption: **features are *independent***

Naive assumption

$$P(y_i = C_k|\mathbf{x}_i) = \frac{P(\mathbf{x}_i|y_i = C_k)P(y_i = C_k)}{P(\mathbf{x}_i)}$$

features are independent

$$P(\mathbf{x}_i|y_i = C_k) = \prod_{l=1}^{p} P(x_i^l|y_i = C_k)$$

Naïve Bayes prediction

$$P(y_i = C_k|\mathbf{x}_i) = \frac{P(\mathbf{x}_i|y_i = C_k)P(y_i = C_k)}{P(\mathbf{x}_i)}$$

Optimal class label:

$$C^* = \arg\max_k P(y_i = C_k|\mathbf{x_i})$$

To find maximum we even do not need the denominator

But we need it to get probabilities

Continuous features



to deal with them we need to introduce parametric likelihood of the features we decompose. Then we fit parameters on training set and use them to predict density for particular point.

Typical distributions include:

- Gaussian
- Multinomial
- Bernoulli

$$P(x_i \mid y) = \frac{1}{\sqrt{2\pi\sigma_y^2}} \exp\left(-\frac{(x_i - \mu_y)^2}{2\sigma_y^2}\right)$$

Practical example

No	Statistics	Python	Target: Machine Learning
1	5	5	5
2	5	3	5
3	3	4	4
4	4	3	4
5	4	5	3
6	2	3	3

Class	Prob
5	0.33
4	0.33
3	0.33

feature	feature value	target	P
Statistics	2	5	0
Statistics	3	5	0
Statistics	4	5	0
Statistics	5	5	1

Machine learning libraries

girafe ai

09

Sklearn



is the biggest library of ML methods implemented in one place.

Despite it is great tool for learning, it is not made for production
e.g. see https://alexanderdyakonov.wordpress.com/2021/03/04/ml-scikit-learn/

During this course we will give you tools which can be used for contemporary problems.

Sklearn is not made for production!!! Don’t use for real life tasks!!!!

Pandas



is very handful tool but it is quite slow.

For better experience you can get alternatives:

- Polars (highly recommended!)
  - https://stackoverflow.com/questions/77881942/whats-the-polars-equivalent-to-the-pandas-iloc-method
- dask
- cudf
- swifter

How to store data?



Straightforward solution is a .csv file. But it has many disadvantages such as filesize, sequential reading and others.

Better alternatives:

- parquet (supported by pandas and others) - column based
- feather - column based
- ORC
- hdf5 - scientific format for datasets

References

girafe
ai

Great resources on machine learning



- [ru] https://alexanderdyakonov.wordpress.com/
- [ru] https://github.com/esokolov/ml-course-hse
- [en] https://cs231n.stanford.edu/
- [ru] https://education.yandex.ru/handbook/ml
- [ru] http://iitp.ru/upload/publications/6256/vyugin1.pdf
- [en, ru] https://github.com/rasbt/python-machine-learning-book-3rd-edition
- [en, ru] https://mlcourse.ai/book/index.html
- [en] https://datatalks.club/events.html
- https://www.classcentral.com/
  - huge collection of open courses
- [en] https://www.youtube.com/@statquest/videos
  - https://statquest.org/video-index/
-

Books



- Pattern Recognition and Machine Learning, Christopher Bishop
- Machine Learning: A probabilistic perspective, Kevin Murphy
- Machine Learning, Tom Mitchell
- The Elements of Statistical Learning: Data Mining, Inference and Prediction, Trevor Hastie, Robert Tibshirani, Jerome Friedman
- High-Dimensional Probability, Roman Vershynin
- The Hundred-Page Machine Learning Book
- Introduction to Machine Learning, Laurent Younes https://arxiv.org/abs/2409.02668
- В.В.Вьюгин Математические основы теории машинного обучения и прогнозирования http://iitp.ru/upload/publications/6256/vyugin1.pdf
- Николенко С. И. Машинное обучение: основы

Takeouts



- To find parameters use MLE
- Remember the i.i.d. property
- The first dimension of a dataset corresponds to the number of objects
- The second (and so on) to the features/time/...
- Even the naïve assumptions may be suitable in some cases
- Simple models provide great baselines

Revise

1. ML and AI overview
2. Thesaurus and notation
3. Maximum Likelihood Estimation
4. Some Machine Learning problems
    a. Classification
    b. Regression
    c. Dimensionality reduction
5. Naïve Bayes classifier

Thanks for attention!

Questions?



