

FL JKE C9970

* NOT 188A

COLOR INDICATES THE YEAR IT WAS
TESTED ON A(1188A TEST SET) BLUE 0 or 5
ORANGE 1 or 6 / GREEN 2 or 7
BROWN 3 or 8 / SLATE 4 or 9

3 RINGS PROTECT FROM
ARCING DC CURRENT

FLASH GUARD

TEST DATE LABEL (LEFT SIDE)

BELT CLIP

MAGNETIC LOCKING SWITCH

WEIGHT = 1LB

THUMB STOP KEEPS THUMB FROM
SLIPPING PAST

NO METAL TO METAL CONTACT BETWEEN
YOU AND THE OBJECT YOU ARE TESTING
WILL HOLD READING AS LONG AS
BUTTON IS PRESSED FOR READINGS
OUT OF LINE OF SIGHT

VOLTAGE INDICATING
LED'S RED = HAZARD
GREEN = SAFE

IF DAMAGED DO NOT USE!!

WILL LEAVE YOU OPEN FOR A
HIT - IF YOUR THUMB SLIPS
PAST ONTO FLASH GUARD

CHECKS INTERNAL CIRCUITRY/OPERATION:
PUT ONE FINGER ON SCREW AND ONE ON
TIP - RED LED SHOULD FLASH

CHECK CONTACT (SCREW)
(LEFT SIDE)

CARBIDE
PROBE
TIP

USED WITH B BOND TO
TEST FOR DC VOLTAGE

GROUND POST (RIGHT SIDE)

CHECK CONTACT (LEFT SIDE)

CARBON IMPREGNATED CAP

ATTACHMENT KNOB FOR WIDU CORD
USED TO REMOVE VOLTAGE
INDUCED UPON THE BODY
OF THE USER

GOLD = CTC COMMUNICATION TECHNOLOGY CORP

CTC HAS PROPER TIGHTENING MARKS TO
PREVENT OVERTIGHTENING

9VOLT
ALKALINE

EVEREADY BATTERY

#522A

FOR PROPER FIT

SILVER = WESTERN
ELECTRIC

VOLTAGE RANGES
DC 6 - 2000 VOLTS
AC 50 - 20,000 VOLTS

O RING GASKET TO KEEP OUT MOISTURE