

MANHOLE SCENARIO

- Check, the type of job assignment, prints and materials needed
- Call for detail
- Make sure you have all necessary safety items for the type of work to be performed.
- Motor Vehicle Circle Check
 - At least 2 chocks, 10 cones and one man working sign.
 - Everything is secured on the truck
 - Check all lights in turn signals and beacons
 - Check tires
 - Check for any oil or water leaks under your truck
 - Check wipers and washer fluid
 - Adjust and check mirrors
 - Get in - make sure you have all of your forms and IDs
 - Check inspection sticker
 - Fill out DVIR , Hours Grid & DOT Log
 - Put seatbelt on
 - Have second man back you out
 - Approach the stop sign and stop
 - Blow horn
 - Check both sides and signal
 - Take the safest and most direct route to your job
 - Drive by work area taking note of:
 - Traffic , Time of Day , Weather Conditions , Road Conditions and Local Laws
- ***** One way street , 35 mph , manhole 3' from curb , slight incline near gas station *****
- Test and wear hard hat , safety glasses and gloves
- Place metal sign 350' from manhole and cones every 35' thereafter.
- Park truck past manhole , set park break , turn wheels to left and chock both back wheels
- Test 188A and Explosimeter
- Check manhole cover with 188A
- Crack cover with hook bar , with back straight facing traffic , lift and slide cover away from opening
- Set manhole tub and rack in place GUARD RAIL
- ***** water in manhole , gas station near by *****
- Check for sheen on water (yes - clean up with inhibitor beads after testing for gas)
- Pump water into storm drain , away from traffic
- Remove cotton filter and replace with inhibitor filter (recheck using 5-10-10)
- Purge meter then test for gas***** 5 % gas reading *****
- Purge manhole in accordance with time on chart for cf indicated on manhole tag
- Retest for gas ***** none *****
- Remove sampling hose from meter and attach to MH rack
- Strap meter on and enter manhole facing traffic using three point contact
- Test all: ducts corners and cracks for gas - carefully watching needle in case it blows
- Test bonds , cables and grounds with 188A
- No gas reading is safe if it cannot be controlled with blower
- Bend a second right angle in the blower hose to ventilate MH
- Normal times for retesting gas is every 2 hours , after breaks and shift changes ; however that would be cut in half due to initial gas reading , half again if tent was being used.