

GANs in action

AutoEncoder, GAN, DCGAN

한병찬

Generative model


1.AutoEncoder

2.Variational AutoEncoder

3.GAN

4.DCGAN


AE



AE


```
encoder = tf.keras.models.Sequential([  
    tf.keras.layers.Input(shape=(28, 28)),  
    tf.keras.layers.Flatten(),  
    tf.keras.layers.Dense(512, activation='relu'),  
    tf.keras.layers.Dense(256, activation='relu'),  
    tf.keras.layers.Dense(32)  
])
```

```
decoder = tf.keras.models.Sequential([  
    tf.keras.layers.Input(shape=(32, )),  
    tf.keras.layers.Dense(256, activation='relu'),  
    tf.keras.layers.Dense(512, activation='relu'),  
    tf.keras.layers.Dense(784),  
    tf.keras.layers.Reshape((28, 28), input_shape=(784, ))  
])
```




```
AE = tf.keras.models.Sequential([  
    encoder,  
    decoder  
])
```

AE





VAE



VAE

```
x = tf.keras.layers.Input(shape=(784, ))
h = tf.keras.layers.Dense(256, activation='relu')(x)
z_mean = tf.keras.layers.Dense(2)(h)
z_log_var = tf.keras.layers.Dense(2)(h)
z = tf.keras.layers.Lambda(sampling)([z_mean, z_log_var])

encoder = tf.keras.Model(x, [z_mean, z_log_var, z])
```



```
output_combined = decoder(encoder(x)[2])

VAE = tf.keras.Model(x, output_combined)
VAE.add_loss(tf.reduce_mean(kl_loss)/784.)
```

```
input_decoder = tf.keras.layers.Input(shape=(2, ))
decoder_h = tf.keras.layers.Dense(256, activation='relu')(input_decoder)
x_decoded = tf.keras.layers.Dense(784, activation='sigmoid')(decoder_h)

decoder = tf.keras.Model(input_decoder, x_decoded)
```

VAE

$$Z \sim N(\mu, \sigma^2) \longrightarrow z'(\text{latent vector}) = \mu + \sigma \odot \epsilon \quad (\epsilon \sim N(0, 1))$$

```
def sampling(args):  
    z_mean, z_log_var = args  
    epsilon = tf.random.normal(shape=(tf.shape(z_mean)[0], 2), mean=0.0, stddev=1.0)  
    return z_mean + tf.exp(z_log_var/2)*epsilon
```

쿨백-라이블러 발산


📖 17개 언어 ▼

위키백과, 우리 모두의 백과사전.


쿨백-라이블러 발산(Kullback-Leibler divergence, **KLD**)은 두 **확률분포**의 차이를 계산하는 데에 사용하는 함수로, 어떤 이상적인 분포에 대해, 그 분포를 근사하는 다른 분포를 사용해 샘플링을 한다면 발생할 수 있는 **정보 엔트로피** 차이를 계산한다. 상대 엔트로피(relative entropy), 정보 획득량(information gain), 인포메이션 다이버전스(information divergence)라고도 한다. 정보이론에서는 상대 엔트로피, 기계학습의 **결정 트리**에서는 정보 획득량을 주로 사용한다.

```
kl_loss = -0.5*tf.reduce_sum(1 + z_log_var - tf.exp(z_log_var) - tf.square(z_mean), axis=-1)
```


VAE




AE




Latent Space

VAE



GAN



GAN

$$\text{Binary Cross Entropy} = -\frac{1}{N} \sum_{i=1}^N y_i \cdot \log(\hat{y}_i) + (1 - y_i) \cdot \log(1 - \hat{y}_i)$$

$$\text{Objective Function} \quad \min_G \max_D V(D, G) = \mathbb{E}_{\mathbf{x} \sim p_{\text{data}}(\mathbf{x})} [\log D(\mathbf{x})] + \mathbb{E}_{\mathbf{z} \sim p_{\mathbf{z}}(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))].$$

$$\text{Discriminator: } D(x) \rightarrow 1, \quad D(G(z)) \rightarrow 0$$

$$\text{Generator: } D(G(z)) \rightarrow 1$$

GAN

```
img_rows = 28
img_cols = 28
img_channels = 1
img_shape = (img_rows, img_cols, img_channels)

latent_dim = 100

generator = tf.keras.models.Sequential([
    tf.keras.layers.Input(shape=(latent_dim, )),
    tf.keras.layers.Dense(128, activation='leaky_relu'),
    tf.keras.layers.Dense(int(np.prod(img_shape)), activation='tanh'),
    tf.keras.layers.Reshape(img_shape)
])

discriminator = tf.keras.models.Sequential([
    tf.keras.layers.Input(shape=img_shape),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(128, activation='leaky_relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])

discriminator.compile(loss='binary_crossentropy', optimizer='adam', metrics=['accuracy'])

discriminator.trainable = False
GAN = tf.keras.models.Sequential([
    generator,
    discriminator
])
GAN.compile(loss='binary_crossentropy', optimizer='adam')
```

```
real = np.ones((batch_size, 1))
fake = np.zeros((batch_size, 1))


for iteration in range(iterations):
    idx = np.random.randint(0, X_train.shape[0], batch_size)
    imgs = X_train[idx]

    z = np.random.normal(0, 1, (batch_size, 100))
    gen_imgs = generator.predict(z)
    d_loss_real = discriminator.train_on_batch(imgs, real)
    d_loss_fake = discriminator.train_on_batch(gen_imgs, fake)
    d_loss, accuracy = 0.5*np.add(d_loss_real, d_loss_fake)


    z = np.random.normal(0, 1, (batch_size, 100))
    gen_imgs = generator.predict(z)

    g_loss = GAN.train_on_batch(z, real)
```


GAN




(a)



(b)



(c)



(d)

GAN



DCGAN

```
generator = tf.keras.models.Sequential([
    tf.keras.layers.Input(shape=(latent_dim, )),
    tf.keras.layers.Dense(128, activation='leaky_relu'),
    tf.keras.layers.Dense(int(np.prod(img_shape)), activation='tanh'),
    tf.keras.layers.Reshape(img_shape)
])


discriminator = tf.keras.models.Sequential([
    tf.keras.layers.Input(shape=img_shape),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(128, activation='leaky_relu'),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
```



```
generator = tf.keras.models.Sequential([
    tf.keras.layers.Input(shape=(latent_dim, )),
    tf.keras.layers.Dense(256*7*7),
    tf.keras.layers.Reshape((7, 7, 256)),
    tf.keras.layers.Conv2DTranspose(128, kernel_size=3, strides=2, padding='same'),
    tf.keras.layers.BatchNormalization(),
    tf.keras.layers.LeakyReLU(alpha=0.01),
    tf.keras.layers.Conv2DTranspose(64, kernel_size=3, strides=1, padding='same'),
    tf.keras.layers.BatchNormalization(),
    tf.keras.layers.LeakyReLU(alpha=0.01),
    tf.keras.layers.Conv2DTranspose(1, kernel_size=3, strides=2, padding='same'),
    tf.keras.layers.Activation('tanh')
])

discriminator = tf.keras.models.Sequential([
    tf.keras.layers.Input(shape=img_shape),
    tf.keras.layers.Conv2D(32, kernel_size=3, strides=2, padding='same'),
    tf.keras.layers.LeakyReLU(alpha=0.01),
    tf.keras.layers.Conv2D(64, kernel_size=3, strides=2, padding='same'),
    tf.keras.layers.LeakyReLU(alpha=0.01),
    tf.keras.layers.Conv2D(128, kernel_size=3, strides=2, padding='same'),
    tf.keras.layers.LeakyReLU(alpha=0.01),
    tf.keras.layers.Flatten(),
    tf.keras.layers.Dense(1, activation='sigmoid')
])
```


DCGAN



DCGAN

