

COMPLETE 1:1 TRUE-SCALE PCB FABRICATION SHEET • COPPER ETCH MASKS & DRILL TEMPLATE (REV 2.1)

The diagram illustrates the PCB layout for the HX711 carrier board. It features several key components and connections:

- Mechanical Features:** Four M3 mounting holes are located at the corners of the board.
- Power and Grounding:**
 - A 12V input connector labeled **12V_IN**.
 - A 5V servo motor connector labeled **5V_SERVO**.
 - A power ground connection labeled **POWER SVGND**.
- Sensors and Indicators:**
 - A temperature indicator labeled **TE_IND**.
 - A voltage divider component labeled **VCPIC311**.
- Digital and Analog Connections:**
 - Digital signal pins labeled **D0 - D13 | GND | AREF | SD(A) | SCL**.
 - Common digital signal pins labeled **COMMON D0 - D7**.
 - Analog signal pins labeled **ANALOG A0-A7** and **ANALOG A8-A15**.
- HX711 Carrier Header:** A specific header for the HX711 module, labeled **HX711 CARRIER HEADER (VCC, DO(UT/ST), SCK(SL), GND)**.
- Capacitors:** Several capacitors are shown, labeled **C1**, **C2**, and **C3**.
- Other Labels:** Various other labels indicate specific functions or components, such as **F_ENTR**, **F_EXIT**, **F_MID**, **F_TOP**, **M_ENTR**, **M_EXIT**, **M_MID**, **M_TOP**, **PP_TOP**, and **PP_EXIT**.

100.0 mm TRUE SCALE CALIBRATION RULER (MEASURE WITH CALIPER BEFORE ETCHING)

DRILL BIT APERTURES & HOLE SIZES:

- 3.0mm (Ø3 Drill): 5x Holes (Chassis Mounting Standoffs)
- 4.0mm (Ø.085 inch): 7x Holes (16x 5.0mm Screw Terminals: TB1, TB2, TB3)
- 1.0mm (Ø.040 inch): 52x Holes (Jedynski Page 1500 Header Sockets)
- 0.8mm (Ø.031 inch): 22x Holes (27.0V 2.0mm Shrouded Ultrasonic Wafers)
- 0.8mm (Ø.031 inch): 6x Holes (1000µF Low-ESR Polar. Capacitors: C1, C2, C3)
- 0.8mm (Ø.031 inch): 22x Holes (PC27 Opto Utl. Servos: S_0901-6, H0711)
- 0.8mm (Ø.031 inch): 10x Vias (Center-Layer Copper: Silliconizing Vias)