

northbound

Full source export · 55 files · generated 2026-08-30

CONTENTS

1. .env.example
2. .export-code-pdf.mjs
3. .github/skills/web-craftsmanship/SKILL.md
4. .github/skills/web-design-guidelines/SKILL.md
5. .github/workflows/ci.yml
6. .gitignore
7. api/contact.js
8. astro.config.mjs
9. package.json
10. public/favicon.svg
11. public/llms.txt
12. public/robots.txt
13. src/components/Analytics.astro
14. src/components/AuthorCard.astro
15. src/components/BookCall.astro
16. src/components/Breadcrumbs.astro
17. src/components/ConnectedSystems.astro
18. src/components/Faq.astro
19. src/components/Footer.astro
20. src/components/Header.astro
21. src/components/Logo.astro
22. src/components/Testimonials.astro
23. src/components/WorkflowSystem.astro
24. src/content.config.ts
25. src/content/work/automated-bureaucracy-platform.md
26. src/content/work/ecommerce-fulfillment-sync.md
27. src/content/work/granite-marketing-n8n.md
28. src/content/work/lead-intake-agency.md
29. src/content/work/whatsapp-crm-intake.md
30. src/content/writing/ai-agent-vs-rule.md
31. src/content/writing/what-workflow-automation-costs.md
32. src/content/writing/zapier-make-n8n-or-custom-code.md
33. src/data/site.ts
34. src/env.d.ts
35. src/layouts/Base.astro
36. src/lib/work.ts
37. src/pages/404.astro
38. src/pages/about.astro
39. src/pages/approach.astro
40. src/pages/contact.astro
41. src/pages/index.astro
42. src/pages/og/[...route].ts
43. src/pages/pricing.astro
44. src/pages/rss.xml.ts
45. src/pages/services/[slug].astro
46. src/pages/services/index.astro
47. src/pages/thank-you.astro
48. src/pages/work/[slug].astro
49. src/pages/work/index.astro
50. src/pages/writing/[slug].astro
51. src/pages/writing/index.astro
52. src/styles/global.css
53. tests/contact.test.js
54. tsconfig.json
55. vercel.json

EXAMPLE .env.example

```
1 # Contact form delivery. Set these in the Vercel project settings, not in git.
2 # Resend API key: https://resend.com/api-keys
3 RESEND_API_KEY=
4
5 # Where inquiries are delivered.
6 CONTACT_T0=hello@flowzora.com
```

MJS `.export-code-pdf.mjs`

```
1 // Generates a single HTML document containing every source file in the repo,
2 // each with its path as a header and code shown in a monospaced, indentation-
3 // preserving block. Output: .code-export.html (converted to PDF by Chrome).
4 import { readFileSync, writeFileSync, readdirSync, statSync } from 'node:fs';
5 import { join, relative, extname } from 'node:path';
6
7 const ROOT = process.cwd();
8
9 // Directories never worth including.
10 const SKIP_DIRS = new Set([
11   'node_modules', 'dist', '.git', '.astro', '.vercel', '.vscode', 'coverage',
12 ]);
13
14 // Files to skip (generated, binary, or noise).
15 const SKIP_FILES = new Set([
16   'package-lock.json', 'structure.txt', 'structure.pdf',
17   '.code-export.html', 'code-export.pdf', '.DS_Store',
18 ]);
19
20 // Only these extensions are treated as text/code we render.
21 const TEXT_EXT = new Set([
22   '.astro', '.ts', '.tsx', '.js', '.mjs', '.cjs', '.jsx', '.json', '.md',
23   '.mdx', '.css', '.html', '.txt', '.yaml', '.yml', '.svg', '.xml',
24 ]);
25 // Files without an extension we still want (dotfiles/config).
26 const TEXT_NAMES = new Set([
27   '.gitignore', '.env.example', 'robots.txt', 'llms.txt', 'tsconfig.json',
28 ]);
29
```

```
30 function walk(dir, out = []) {
31   for (const name of readdirSync(dir).sort()) {
32     const full = join(dir, name);
33     const st = statSync(full);
34     if (st.isDirectory()) {
35       if (SKIP_DIRS.has(name)) continue;
36       walk(full, out);
37     } else {
38       if (SKIP_FILES.has(name)) continue;
39       const ext = extname(name);
40       if (TEXT_EXT.has(ext) || TEXT_NAMES.has(name)) out.push(full);
41     }
42   }
43   return out;
44 }
45
46 const esc = (s) => s
47   .replace(/&/g, '&amp;')
48   .replace(/</g, '&lt;')
49   .replace(/>/g, '&gt;');
50
51 const files = walk(ROOT)
52   .map((f) => relative(ROOT, f))
53   .sort((a, b) => a.localeCompare(b));
54
55 const langOf = (p) => (extname(p).slice(1) || 'text');
56
57 const toc = files
58   .map((f, i) => `- <a href="#f${i}">${esc(f)}</a></li>`)
59   .join('\n');
60
61 const sections = files.map((f, i) => {

```

```
62 let code = '';
63 try { code = readFileSync(join(ROOT, f), 'utf8'); }
64 catch { code = '[unable to read file]'; }
65 const lines = code.split('\n');
66 const numbered = lines
67   .map((ln, n) => `</span>`)
68   .join('\n');
69 return `
70 <section class="file" id="f${i}">
71   <div class="fname"><span class="lang">${langOf(f)}</span>${esc(f)}</div>
72   <pre class="src"><code>${numbered}</code></pre>
73 </section>`;
74 }).join('\n');
75
76 const now = new Date().toISOString().slice(0, 10);
77
78 const html = `<!doctype html>
79 <html lang="en">
80 <head>
81 <meta charset="utf-8">
82 <title>northbound - source export</title>
83 <style>
84 :root {
85   --bg: #ffffff; --fg: #1a1a1a; --muted: #6b7280;
86   --line: #e5e7eb; --accent: #0f766e; --gutter: #9ca3af;
87   --code-bg: #f8fafc; --header-bg: #0f172a; --header-fg: #f8fafc;
88 }
89 * { box-sizing: border-box; }
90 body {
91   margin: 0; color: var(--fg); background: var(--bg);
92   font-family: -apple-system, "Segoe UI", Helvetica, Arial, sans-serif;
93   font-size: 12px; line-height: 1.5;
```

```
94  }
95  .cover { padding: 48px 40px 32px; border-bottom: 2px solid var(--accent); }
96  .cover h1 { margin: 0 0 4px; font-size: 28px; letter-spacing: -0.02em; }
97  .cover .meta { color: var(--muted); font-size: 12px; }
98  .toc { padding: 24px 40px 8px; }
99  .toc h2 { font-size: 14px; text-transform: uppercase; letter-spacing: 0.08em;
100    color: var(--muted); margin: 0 0 10px; }
101  .toc ol { margin: 0; padding-left: 20px; columns: 2; column-gap: 32px; }
102  .toc li { font-family: ui-monospace, "SF Mono", Menlo, monospace;
103    font-size: 11px; margin-bottom: 3px; break-inside: avoid; }
104  .toc a { color: var(--accent); text-decoration: none; }
105  .file { margin: 0 0 20px; padding: 0 40px; break-before: auto; }
106  .file .fname {
107    background: var(--header-bg); color: var(--header-fg);
108    font-family: ui-monospace, "SF Mono", Menlo, monospace; font-size: 12px;
109    font-weight: 600; padding: 8px 12px; border-radius: 6px 6px 0 0;
110    display: flex; align-items: center; gap: 10px;
111    break-after: avoid; page-break-after: avoid;
112  }
113  .file .lang {
114    font-size: 9px; text-transform: uppercase; letter-spacing: 0.08em;
115    background: var(--accent); color: #fff; padding: 2px 6px; border-radius: 4px;
116  }
117  .code { display: flex; border: 1px solid var(--line); border-top: 0;
118    border-radius: 0 0 6px 6px; background: var(--code-bg); }
119  pre { margin: 0; font-family: ui-monospace, "SF Mono", Menlo, "Roboto Mono", monospace;
120    font-size: 10.5px; line-height: 1.5; tab-size: 2; white-space: pre-wrap;
121    word-break: break-word; }
122  .src {
123    border: 1px solid var(--line); border-top: 0; border-radius: 0 0 6px 6px;
124    background: var(--code-bg); padding: 10px 14px 12px 0;
125    counter-reset: none;
```

```

126   }
127   .src .ln { display: block; padding-left: 52px; position: relative; }
128   .src .ln::before {
129       content: attr(data-n); position: absolute; left: 0; width: 40px;
130       text-align: right; color: var(--gutter); user-select: none;
131   }
132   @page { size: A4; margin: 14mm 0; }
133 </style>
134 </head>
135 <body>
136   <div class="cover">
137     <h1>northbound</h1>
138     <div class="meta">Full source export · ${files.length} files · generated ${now}</div>
139   </div>
140   <div class="toc">
141     <h2>Contents</h2>
142     <ol>${toc}</ol>
143   </div>
144   ${sections}
145 </body>
146 </html>`;
147
148 writeFileSync(join(ROOT, '.code-export.html'), html);
149 console.log(`Wrote .code-export.html with ${files.length} files.`);
150

```

MD [.github/skills/web-craftsmanship/SKILL.md](#)

```

1 ---
2 name: web-craftsmanship
3 description: >-
4   Design and build professional, human-quality websites – not generic
5   "vibe-coded" output. Use this skill whenever creating, redesigning, or

```

```
6   reviewing UI/pages/components for the northbound site: layout, visual
7   hierarchy, typography, spacing, color, responsive behavior, accessibility,
8   micro-interactions, and content/copy polish. Applies to Astro components,
9   pages, and Tailwind styling in this project.
10  ---
11
12  # Web Craftsmanship
13
14  > Paste your notes below. Keep them as concrete, actionable rules – the more
15  > specific, the better I can apply them. Delete these placeholder sections you
16  > don't need.
17
18  ## Design principles
19  <!-- e.g. "Prefer generous whitespace", "Max 2 fonts", "8pt spacing grid" -->
20  -
21
22  ## Typography
23  <!-- font families, scale, line-height, letter-spacing rules -->
24  -
25
26  ## Color & theming
27  <!-- palette, when to use accents, contrast targets -->
28  -
29
30  ## Layout & spacing
31  <!-- grid system, container widths, section rhythm -->
32  -
33
34  ## Components & patterns
35  <!-- reusable component conventions specific to northbound -->
36  -
37
```

```
38 ## Responsive behavior
39 <!-- breakpoints, mobile-first rules, what collapses/stacks -->
40 -
41
42 ## Accessibility
43 <!-- focus states, alt text, semantic HTML, contrast, motion -->
44 -
45
46 ## Motion & micro-interactions
47 <!-- hover/transition rules, easing, durations, when NOT to animate -->
48 -
49
50 ## Content & copy
51 <!-- tone, heading style, CTA wording -->
52 -
53
54 ## Anti-patterns (avoid these)
55 <!-- the "vibe-coded" tells you want me to never produce -->
56 -
57
58 ## Reference examples
59 <!-- links or descriptions of sites/screens that set the bar -->
60 -
61
```

MD [.github/skills/web-design-guidelines/SKILL.md](#)

```
1 ---
2 name: web-design-guidelines
3 description: Review UI code for Web Interface Guidelines compliance. Use when asked to "review my UI",
  "check accessibility", "audit design", "review UX", or "check my site against best practices".
4 metadata:
5   author: vercel
```



```
6   version: "1.0.0"
7   argument-hint: <file-or-pattern>
8   ---
9
10  # Web Interface Guidelines
11
12  Review files for compliance with Web Interface Guidelines.
13
14  ## How It Works
15
16  1. Fetch the latest guidelines from the source URL below
17  2. Read the specified files (or prompt user for files/pattern)
18  3. Check against all rules in the fetched guidelines
19  4. Output findings in the terse `file:line` format
20
21  ## Guidelines Source
22
23  Fetch fresh guidelines before each review:
24
25  ```
26  https://raw.githubusercontent.com/vercel-labs/web-interface-guidelines/main/command.md
27  ```
28
29  Use WebFetch to retrieve the latest rules. The fetched content contains all the rules and output
  format instructions.
30
31  ## Usage
32
33  When a user provides a file or pattern argument:
34  1. Fetch guidelines from the source URL above
35  2. Read the specified files
36  3. Apply all rules from the fetched guidelines
```

37 4. Output findings using the format specified in the guidelines

38

39 If no files specified, ask the user which files to review.

40

YML .github/workflows/ci.yml

```
1 name: CI
2
3 # Nothing broken should reach production. This runs the same checks locally
4 # available via `npm run check`, on every push and pull request.
5 on:
6   push:
7     branches: [main]
8   pull_request:
9
10 jobs:
11   verify:
12     runs-on: ubuntu-latest
13     steps:
14       - uses: actions/checkout@v4
15
16       - uses: actions/setup-node@v4
17         with:
18           node-version: 20
19           cache: npm
20
21       - run: npm ci
22
23       - name: Type and content-schema check
24         run: npx astro check
25
26       - name: Unit tests
```

```
27         run: npx vitest run
28
29         - name: Production build
30         run: npm run build
31
```

TEXT .gitignore

```
1 .DS_Store
2 node_modules/
3 dist/
4 .astro/
5 *.log
6 .env
7 .env.production
8 .vscode/mcp.json
9
```

JS api/contact.js

```
1 /**
2  * Contact endpoint.
3  *
4  * Deliberately a plain Vercel Node function rather than an Astro server route:
5  * the site stays fully static, and moving to AWS later is a deploy-target change
6  * rather than a rewrite. Requires RESEND_API_KEY and CONTACT_T0 in the env.
7  */
8
9  const MAX_LENGTHS = {
10    name: 120,
11    email: 200,
12    company: 160,
13    team: 40,
14    workflow: 5000,
```

```
15  };
16
17  // Best-effort, per-instance throttle. Not a substitute for platform WAF rules,
18  // but it stops the trivial case of one client hammering the endpoint.
19  const hits = new Map();
20  const WINDOW_MS = 60_000;
21  const MAX_PER_WINDOW = 5;
22
23  function rateLimited(ip) {
24    const now = Date.now();
25    const record = hits.get(ip);
26    if (!record || now - record.start > WINDOW_MS) {
27      hits.set(ip, { start: now, count: 1 });
28      return false;
29    }
30    record.count += 1;
31    return record.count > MAX_PER_WINDOW;
32  }
33
34  const isEmail = (value) => /^[^\s@]+@[^\s@]+\.[^\s@]{2,}$/.test(value);
35
36  const escapeHtml = (value) =>
37    String(value).replace(
38      /[<>'"]/g,
39      (char) =>
40        ({ '&': '&amp;', '<': '&lt;', '>': '&gt;', '"': '&quot;', "'": '&#39;' })[char]
41    );
42
43  export default async function handler(req, res) {
44    if (req.method !== 'POST') {
45      res.setHeader('Allow', 'POST');
46      return res.status(405).json({ error: 'Method not allowed' });
```

```
47   }
48
49   const ip =
50     (req.headers['x-forwarded-for'] || '').split(',')[0].trim() || 'unknown';
51   if (rateLimited(ip)) {
52     return res.status(429).json({ error: 'Too many requests. Try again shortly.' });
53   }
54
55   const body =
56     typeof req.body === 'string' ? Object.fromEntries(new URLSearchParams(req.body)) : req.body || {};
57
58   // Honeybot: a field no human sees, so anything filling it is a bot. Return 200
59   // so the bot believes it succeeded and does not retry with a different shape.
60   if (body.company_website) {
61     return res.status(200).json({ ok: true });
62   }
63
64   const fields = {};
65   for (const [key, limit] of Object.entries(MAX_LENGTHS)) {
66     fields[key] = String(body[key] ?? '').trim().slice(0, limit);
67   }
68
69   if (!fields.name || !fields.email || !fields.workflow) {
70     return res.status(400).json({ error: 'Name, email and workflow are required.' });
71   }
72   if (!isEmail(fields.email)) {
73     return res.status(400).json({ error: 'That email address does not look right.' });
74   }
75
76   const apiKey = process.env.RESEND_API_KEY;
77   const to = process.env.CONTACT_T0;
78   if (!apiKey || !to) {
```

```

79     console.error('Contact form is not configured: missing RESEND_API_KEY or CONTACT_TO.');
```

```

80     return res.status(500).json({ error: 'Contact form is not configured yet.' });
81 }
82
83 try {
84     const response = await fetch('https://api.resend.com/emails', {
85         method: 'POST',
86         headers: {
87             Authorization: `Bearer ${apiKey}`,
88             'Content-Type': 'application/json',
89         },
90         body: JSON.stringify({
91             from: 'Flowzora <hello@flowzora.com>',
92             to: [to],
93             reply_to: fields.email,
94             subject: `New workflow inquiry - ${fields.name}${fields.company ? ` (${fields.company})` : ''}`,
95             html: `
96                 <h2>New workflow inquiry</h2>
97                 <p><strong>Name:</strong> ${escapeHtml(fields.name)}</p>
98                 <p><strong>Email:</strong> ${escapeHtml(fields.email)}</p>
99                 <p><strong>Company:</strong> ${escapeHtml(fields.company) || '-'}</p>
100                <p><strong>Team size:</strong> ${escapeHtml(fields.team) || '-'}</p>
101                <hr />
102                <p><strong>The workflow:</strong></p>
103                <p>${escapeHtml(fields.workflow).replace(/\n/g, '<br />')}</p>
104            `,
105         }),
106     });
107
108     if (!response.ok) {
109         console.error('Email provider rejected the message', await response.text());

```

```

110     return res.status(502).json({ error: 'We could not send that. Please email us directly.' });
111   }
112 } catch (error) {
113   console.error('Contact form failed', error);
114   return res.status(502).json({ error: 'We could not send that. Please email us directly.' });
115 }
116
117 // Progressive enhancement: a no-JS submit lands on the thank-you page,
118 // while fetch-based submits read the JSON.
119 const wantsJson = (req.headers.accept || '').includes('application/json');
120 if (wantsJson) {
121   return res.status(200).json({ ok: true });
122 }
123 res.setHeader('Location', '/thank-you/');
124 return res.status(303).end();
125 }
126

```

MJS astro.config.mjs

```

1 // @ts-check
2 import { defineConfig } from 'astro/config';
3 import mdx from '@astrojs/mdx';
4 import sitemap from '@astrojs/sitemap';
5 import tailwindcss from '@tailwindcss/vite';
6
7 export default defineConfig({
8   site: 'https://flowzora.com',
9   // Astro emits directory-style output, so URLs genuinely end in a slash.
10  // Declaring it keeps canonical tags identical to the URLs that actually serve,
11  // instead of pointing one redirect away from the real page.
12  trailingSlash: 'always',
13  build: { format: 'directory' },

```

```

14   integrations: [
15     mdx(),
16     sitemap({
17       filter: (page) => !page.includes('/thank-you'),
18       serialize(item) {
19         const isHome = item.url === 'https://flowzora.com/';
20         // Cast through the integration's own enum: it types `changefreq` as an
21         // enum rather than a plain string union.
22         item.changefreq = /** @type {any} */ (isHome ? 'weekly' : 'monthly');
23         item.priority = isHome ? 1.0 : 0.7;
24         item.lastmod = new Date().toISOString();
25         return item;
26       },
27     }),
28   ],
29   vite: {
30     plugins: [tailwindcss()],
31   },
32 });
33

```

JSON package.json

```

1  {
2    "name": "flowzora",
3    "type": "module",
4    "version": "0.1.0",
5    "private": true,
6    "scripts": {
7      "dev": "astro dev",
8      "start": "astro dev",
9      "build": "astro build",
10     "preview": "astro preview",

```



```

11     "astro": "astro",
12     "test": "vitest run",
13     "check": "astro check && vitest run && astro build"
14 },
15 "dependencies": {
16     "@astrojs/mdx": "^7.0.7",
17     "@astrojs/rss": "^4.0.19",
18     "@astrojs/sitemap": "^3.7.3",
19     "@fontsource-variable/fraunces": "^5.3.0",
20     "@fontsource-variable/ibm-plex-sans": "^5.3.0",
21     "@fontsource/fraunces": "^5.3.0",
22     "@fontsource/ibm-plex-mono": "^5.3.0",
23     "@fontsource/ibm-plex-sans": "^5.3.0",
24     "@tailwindcss/vite": "^4.3.3",
25     "@vercel/analytics": "^2.0.1",
26     "@vercel/speed-insights": "^2.0.0",
27     "astro": "^7.2.4",
28     "astro-og-canvas": "^0.13.0",
29     "canvas-kit-wasm": "^0.42.0",
30     "tailwindcss": "^4.3.3"
31 },
32 "devDependencies": {
33     "@astrojs/check": "^0.9.10",
34     "typescript": "^6.0.3",
35     "vitest": "^4.1.11"
36 }
37 }
38

```

SVG public/favicon.svg

```

1 <svg xmlns="http://www.w3.org/2000/svg" viewBox="0 0 32 32" role="img" aria-label="Flowzora">
2 <!--

```

```
3     Favicon cut of the mark: the node is scaled up and the core enlarged relative
4     to the lockup version, because at 16px a core sized to the header proportions
5     disappears entirely. The channel is kept – it is what makes this a flow mark
6     rather than a generic diamond.
7
8     The plate stays dark in both schemes so the icon reads as one consistent
9     object against light and dark browser chrome alike.
10  -->
11  <rect width="32" height="32" fill="#17150f" />
12  <path d="M0 16 L6 16 M26 16 L32 16" stroke="#f4f1ea" stroke-width="2.6" />
13  <path d="M16 6 L26 16 L16 26 L6 16 Z" stroke="#f4f1ea" stroke-width="2.6" fill="none" />
14  <circle cx="16" cy="16" r="4" fill="#b6431f" />
15  </svg>
16
```

TXT public/llms.txt

```
1  # Flowzora
2
3  > Flowzora is a workflow automation studio working with small and mid-sized
4  > businesses worldwide. We connect the tools a company already runs, remove the
5  > manual steps between them, and hand over systems the client owns outright.
6
7  Flowzora operates as a studio under oneProductLab. It was founded by Niraj Kumar,
8  a backend and AI engineer whose background is in FastAPI services, async data
9  pipelines and production LLM applications, with earlier machine learning research
10 work at C-DAC.
11
12 ## What we do
13
14 - Sales and revenue operations: lead capture, routing, enrichment, CRM hygiene
15 - Marketing and lifecycle automation: segmentation, hand-offs, reporting
16 - Internal operations and back-office: onboarding, approvals, reconciliation
```

17 - Customer support automation: triage, classification, drafted responses

18 - Integrations and data plumbing: reliable, observable syncs between systems

19 - AI agents and assisted workflows: used only where a rule cannot express the task

20

21 ## Pricing

22

23 - Automation Map - \$2,500 flat, 2 weeks. Scoping and a build plan. Credited against a build.

24 - First System - \$8,000 to \$18,000, 3 to 5 weeks. One workflow built and handed over.

25 - Operations Partner - from \$6,000 per month, ongoing.

26

27 ## How we describe our evidence

28

29 Case studies are labeled exactly for what they are: "client", "internal-build"

30 or "concept". We do not publish client logos, named customers or performance

31 metrics we cannot substantiate. If a page does not name a client, no client

32 engagement is being claimed.

33

34 Client testimonials on the site are public LinkedIn recommendations, quoted

35 verbatim and linked to the profile that wrote them, with the relationship

36 (client or colleague) stated on each.

37

38 ## Key pages

39

40 - [Services](https://flowzora.com/services/): what we build

41 - [Pricing](https://flowzora.com/pricing/): published rates

42 - [Work](https://flowzora.com/work/): builds and teardowns, honestly labeled

43 - [Approach](https://flowzora.com/approach/): map, build, hand over

44 - [About](https://flowzora.com/about/): the studio and its founder

45 - [Writing](https://flowzora.com/writing/): notes on operations and automation

46 - [Contact](https://flowzora.com/contact/): start with one workflow

47

48 ## Service pages

49

- 50 - [Revenue operations](https://flowzora.com/services/revenue-operations/): CRM automation, lead routing, enrichment
- 51 - [Marketing lifecycle](https://flowzora.com/services/marketing-lifecycle/): segmentation, hand-offs, reporting
- 52 - [Internal operations](https://flowzora.com/services/internal-operations/): onboarding, approvals, reconciliation
- 53 - [Customer support](https://flowzora.com/services/customer-support/): triage, classification, drafted replies
- 54 - [Integrations](https://flowzora.com/services/integrations/): reliable syncs between systems
- 55 - [AI agents](https://flowzora.com/services/ai-agents/): models used only where rules fall short

56

57 ## Reference answers

58

59 ****What does workflow automation cost?**** A single workflow built, documented and
60 handed over costs \$8,000 to \$18,000. Scoping is \$2,500 and is credited against
61 the build. Ongoing partnerships start at \$6,000 per month. Expect 10 to 20% of
62 build cost per year in maintenance.

63

64 ****How long does it take?**** Three to five weeks for one workflow, including
65 mapping. Working automation appears in the first two weeks, not at the end.

66

67 ****Who owns the result?**** The client. Code, credentials and infrastructure are in
68 their name from day one, and handover includes runbooks and diagrams.

69

70 ****When is an AI agent the right tool?**** Only when a task needs judgment a rule
71 cannot express – classification, extraction or drafting. Rules are preferred
72 wherever the logic can be written down, because they are cheaper and predictable.

73

74 ****Which platforms do you build on?**** Zapier, Make, n8n or custom Python and
75 FastAPI services, chosen per workflow. Platforms where they genuinely fit; code
76 where reliability, testing or volume demands it.

77

78 ## Contact

79

80 hello@flowzora.com

81

TXT public/robots.txt

```
1 # Flowzora – https://flowzora.com
2 # Search crawlers
3 User-agent: *
4 Allow: /
5 Disallow: /thank-you/
6
7 # Answer and generative engines are explicitly welcome. We sell engagements,
8 # not content, so being quoted and cited is the point.
9 User-agent: GPTBot
10 Allow: /
11
12 User-agent: OAI-SearchBot
13 Allow: /
14
15 User-agent: ChatGPT-User
16 Allow: /
17
18 User-agent: ClaudeBot
19 Allow: /
20
21 User-agent: Claude-User
22 Allow: /
23
24 User-agent: PerplexityBot
25 Allow: /
26
27 User-agent: Perplexity-User
```

```
28 Allow: /
29
30 User-agent: Google-Extended
31 Allow: /
32
33 User-agent: Applebot-Extended
34 Allow: /
35
36 User-agent: CCBot
37 Allow: /
38
39 Sitemap: https://flowzora.com/sitemap-index.xml
40
```

ASTRO src/components/Analytics.astro

```
1 ---
2 /*
3   Analytics
4   -----
5   Vercel Analytics and Speed Insights are cookieless and do not fingerprint, so
6   they run without consent under GDPR/ePrivacy.
7
8   The consent gate is therefore not shown by default. Nothing on the site
9   currently sets a cookie, and a banner that asks permission for nothing is pure
10  friction on the pages that matter most. It renders only on pages that opt in
11  via `needsConsent`, which is what an embedded scheduler or similar third-party
12  widget would do.
13 */
14 interface Props {
15   /** Set on pages that embed a cookie-setting third party. */
16   needsConsent?: boolean;
17 }
```

```
18 const { needsConsent = false } = Astro.props;
19 ---
20
21 <script>
22   import { inject } from '@vercel/analytics';
23   import { injectSpeedInsights } from '@vercel/speed-insights';
24
25   inject();
26   injectSpeedInsights();
27
28   // Conversion signal: a submitted inquiry is the only event worth tracking.
29   if (window.location.pathname.startsWith('/thank-you')) {
30     import('@vercel/analytics').then(({ track }) => track('contact_submitted'));
31   }
32 </script>
33
34 {
35   needsConsent && (
36     <div id="consent" class="consent" role="region" aria-label="Cookie preferences" hidden>
37       <p class="consent__text">
38         This page embeds a scheduling tool that sets cookies. Our own analytics are
39         cookieless either way.
40       </p>
41       <div class="consent__actions">
42         <button type="button" class="btn btn-ghost consent__btn" data-consent="declined">
43           Essential only
44         </button>
45         <button type="button" class="btn btn-primary consent__btn" data-consent="granted">
46           Allow
47         </button>
48       </div>
49     </div>
```

```
50  )
51  }
52
53  <script>
54      const KEY = 'fz-consent';
55      const banner = document.querySelector('#consent') as HTMLElement | null;
56
57      if (banner && !localStorage.getItem(KEY)) {
58          // Deferred so it never competes with the largest contentful paint.
59          window.setTimeout(() => {
60              banner.hidden = false;
61              banner.classList.add('is-in');
62          }, 1200);
63      }
64
65      banner?.querySelectorAll('[data-consent]').forEach((button) => {
66          button.addEventListener('click', () => {
67              localStorage.setItem(KEY, (button as HTMLElement).dataset.consent ?? 'declined');
68              banner.classList.remove('is-in');
69              window.setTimeout(() => (banner.hidden = true), 200);
70          });
71      });
72  </script>
73
74  <style>
75      .consent {
76          position: fixed;
77          inset-inline: 1rem;
78          bottom: 1rem;
79          z-index: 60;
80          margin-inline: auto;
81          max-width: 34rem;
```



```
82     display: flex;
83     flex-direction: column;
84     gap: 0.9rem;
85     padding: 1rem 1.15rem;
86     background: var(--color-paper);
87     border: 1px solid var(--color-ink);
88     border-radius: var(--radius);
89     box-shadow: 0 10px 30px -12px rgb(23 21 15 / 0.35);
90     opacity: 0;
91     transform: translateY(8px);
92     transition: opacity 0.25s ease, transform 0.25s ease;
93 }
94 .consent.is-in {
95     opacity: 1;
96     transform: none;
97 }
98 .consent__text {
99     font-size: 0.9rem;
100     color: var(--color-ink-2);
101     margin: 0;
102 }
103 .consent__actions {
104     display: flex;
105     gap: 0.6rem;
106 }
107 .consent__btn {
108     flex: 1;
109     justify-content: center;
110 }
111 @media (min-width: 640px) {
112     .consent {
113         flex-direction: row;
```

```

114     align-items: center;
115     max-width: 44rem;
116 }
117 .consent__actions {
118     flex-shrink: 0;
119 }
120 .consent__btn {
121     flex: none;
122 }
123 }
124 @media (prefers-reduced-motion: reduce) {
125     .consent {
126         transition: none;
127     }
128 }
129 </style>
130

```

ASTRO src/components/AuthorCard.astro

```

1  ---
2  /*
3   AuthorCard
4   -----
5   A named, verifiable human at the end of every article. This is the strongest
6   E-E-A-T signal available to a young studio: search and generative engines both
7   weight authorship, and an anonymous post is far harder to cite than one
8   attributed to a person whose background can be checked.
9  */
10 import { Image } from 'astro:assets';
11 import founderPhoto from '../assets/images/niraj.jpg';
12 import { founder } from '../data/site';
13 ---

```

```

14
15 <aside class="mt-14 border-t border-[var(--color-line)] pt-7">
16   <p class="eyebrow">Written by</p>
17   <div class="mt-4 flex flex-wrap items-start justify-between gap-6">
18     <div class="flex max-w-xl gap-5">
19       <Image
20         src={founderPhoto}
21         alt=""
22         width={128}
23         height={128}
24         loading="lazy"
25         class="h-16 w-16 shrink-0 rounded-full border border-[var(--color-line)] object-cover"
26       />
27       <div>
28         <p class="font-[var(--font-display)] text-xl">{founder.name}</p>
29         <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-ink-
30           3)]">
31           {founder.role}
32         </p>
33         <p class="mt-3 text-[0.95rem] text-[var(--color-ink-2)]">{founder.bio}</p>
34       </div>
35     </div>
36     <a href={founder.linkedin} rel="noopener" target="_blank" class="btn btn-ghost shrink-0">
37       LinkedIn ↗
38     </a>
39   </div>
40 </aside>

```

ASTRO src/components/BookCall.astro

```

1 ---
2 /*

```

```

3   BookCall
4   -----
5   Calendly, loaded only on interaction.
6
7   Embedding the widget directly would pull ~150KB of third-party JavaScript and
8   set cookies on every visit to the page, whether or not anyone intends to book.
9   Loading it on click keeps the page fast and keeps the cookie question honest:
10  nothing third-party runs until the visitor asks for it.
11
12  Set `url` in src/data/site.ts once the dedicated event type exists.
13  */
14  import { site } from '../data/site';
15
16  interface Props {
17    class?: string;
18    label?: string;
19  }
20  const { class: className = '', label = 'Book a call' } = Astro.props;
21  ---
22
23  {
24    site.calendly ? (
25      <div class={className}>
26        <button type="button" class="btn btn-ghost" data-calendly={site.calendly}>
27          {label}
28        </button>
29        <div id="calendly-embed" class="calendly" hidden />
30      </div>
31    ) : (
32      <a href="/contact/" class={`btn btn-ghost ${className}`}>
33        {label}
34      </a>

```

```
35  )
36  }
37
38  <script>
39  // Third-party script is fetched on first click, never on page load.
40  const trigger = document.querySelector('[data-calendly]') as HTMLButtonElement | null;
41  const target = document.querySelector('#calendly-embed') as HTMLElement | null;
42  let loaded = false;
43
44  trigger?.addEventListener('click', () => {
45    if (loaded || !target) return;
46    loaded = true;
47    trigger.disabled = true;
48    trigger.textContent = 'Loading...';
49
50    const css = document.createElement('link');
51    css.rel = 'stylesheet';
52    css.href = 'https://assets.calendly.com/assets/external/widget.css';
53    document.head.appendChild(css);
54
55    const script = document.createElement('script');
56    script.src = 'https://assets.calendly.com/assets/external/widget.js';
57    script.async = true;
58    script.onload = () => {
59      target.hidden = false;
60      // @ts-expect-error – injected by the Calendly widget script.
61      window.Calendly?.initInlineWidget({
62        url: trigger.dataset.calendly,
63        parentElement: target,
64      });
65      trigger.hidden = true;
66    };
```

```

67     script.onerror = () => {
68         trigger.disabled = false;
69         trigger.textContent = 'Booking unavailable – email us instead';
70     };
71     document.body.appendChild(script);
72 });
73 </script>
74
75 <style>
76     .calendly {
77         min-height: 42rem;
78         margin-top: 1.5rem;
79         border: 1px solid var(--color-line);
80         border-radius: var(--radius);
81         overflow: hidden;
82     }
83 </style>
84

```

ASTRO src/components/Breadcrumbs.astro

```

1  ---
2  /*
3   Breadcrumbs
4   -----
5   Visible navigation and the BreadcrumbList schema that Google uses to render
6   the URL line in search results. The JSON-LD is emitted here so a page cannot
7   show a trail without also describing it to crawlers.
8  */
9  import { site } from '../data/site';
10
11  interface Crumb {
12      label: string;

```

```

13   href: string;
14 }
15 interface Props {
16   trail: Crumb[];
17   /** Current page name – rendered as plain text, not a link. */
18   current: string;
19 }
20
21 const { trail, current } = Astro.props;
22
23 const itemListElement = [
24   { '@type': 'ListItem', position: 1, name: 'Home', item: `${site.domain}/` },
25   ...trail.map((crumb, i) => ({
26     '@type': 'ListItem',
27     position: i + 2,
28     name: crumb.label,
29     item: new URL(crumb.href, site.domain).href,
30   })),
31   { '@type': 'ListItem', position: trail.length + 2, name: current },
32 ];
33 ---
34
35 <nav aria-label="Breadcrumb" class="crumbs">
36   <ol>
37     <li><a href="/">Home</a></li>
38     {
39       trail.map((crumb) => (
40         <li>
41           <a href={crumb.href}>{crumb.label}</a>
42         </li>
43       ))
44     }

```

```

45     <li aria-current="page">{current}</li>
46   </ol>
47 </nav>
48
49 <script
50   type="application/ld+json"
51   set:html={JSON.stringify({
52     '@context': 'https://schema.org',
53     '@type': 'BreadcrumbList',
54     itemListElement,
55   })}
56   is:inline
57 />
58
59 <style>
60   .crumbs ol {
61     display: flex;
62     flex-wrap: wrap;
63     align-items: center;
64     gap: 0.5rem;
65     margin: 0;
66     padding: 0;
67     list-style: none;
68     font-family: var(--font-mono);
69     font-size: 0.75rem;
70     letter-spacing: 0.04em;
71     color: var(--color-ink-3);
72   }
73   /*
74   The alt-text syntax `content: '/' / ''` gives the separator an empty
75   accessible name, so screen readers announce "Home, Services, About" rather
76   than "Home slash Services slash About".

```



```

77  */
78  .crumbs li + li::before {
79      content: '/' / '';
80      margin-right: 0.5rem;
81      color: var(--color-line-2);
82  }
83  .crumbs a {
84      display: inline-flex;
85      align-items: center;
86      min-height: 24px;
87      text-decoration: none;
88      transition: color 0.18s ease;
89  }
90  .crumbs a:hover {
91      color: var(--color-signal-ink);
92      text-decoration: underline;
93      text-underline-offset: 3px;
94  }
95  .crumbs [aria-current='page'] {
96      color: var(--color-ink-2);
97  }
98  </style>
99

```

ASTRO src/components/ConnectedSystems.astro

```

1  ---
2  /*
3  ConnectedSystems
4  -----
5  Hub and spoke: the systems a business already runs on, wired into a single
6  automated core. Signals travel inward along each spoke and outward again.
7

```

```
8   Geometry notes, because an earlier version of this diagram read as visibly
9   lopsided:
10
11  - The stage is a square. The previous version placed nodes on an *ellipse*
12    inside a 4:3 box, which distorted the angular spacing.
13  - Spokes are plain rotated `div`s, not SVG lines. The old SVG used
14    `preserveAspectRatio="none"`, so a stretched viewBox gave every spoke a
15    different dash length depending on its angle. Rotating a horizontal dashed
16    line preserves dash geometry exactly.
17  - Every node box is the same fixed width. Boxes sized to their labels can
18    never sit symmetrically on a circle, because "Warehouse" and "CRM" put their
19    visual edges in completely different places.
20 */
21 import { site } from '../data/site';
22
23 interface Spoke {
24   label: string;
25   meta: string;
26 }
27 interface Props {
28   spokes?: Spoke[];
29   caption?: string;
30 }
31
32 const defaultSpokes: Spoke[] = [
33   { label: 'CRM', meta: 'records' },
34   { label: 'Email', meta: 'inbound' },
35   { label: 'Slack', meta: 'alerts' },
36   { label: 'Sheets', meta: 'ledgers' },
37   { label: 'Billing', meta: 'invoices' },
38   { label: 'Calendar', meta: 'scheduling' },
39   { label: 'Webhooks', meta: 'events' },
```

```

40   { label: 'Warehouse', meta: 'analytics' },
41 ];
42
43 const {
44   spokes = defaultSpokes,
45   caption = 'Your existing stack, wired into one operation',
46 } = Astro.props;
47
48 const n = spokes.length;
49
50 /*
51   Node centres sit on a true circle at `--ring` from the middle. Angles start at
52   -90deg so the first node is at twelve o'clock, and every subsequent node is an
53   exact equal division of the circle.
54 */
55 const points = spokes.map((s, i) => {
56   const deg = (i / n) * 360 - 90;
57   const rad = (deg * Math.PI) / 180;
58   return {
59     ...s,
60     deg,
61     x: +(50 + 38 * Math.cos(rad)).toFixed(3),
62     y: +(50 + 38 * Math.sin(rad)).toFixed(3),
63   };
64 });
65
66 const describe = spokes.map((s) => s.label).join(', ');
67 ---
68
69 <figure class="fz-hub" aria-label={`One automated core connected to: ${describe}.`} >
70   <div class="fz-hub__stage">
71     { /* Spokes are drawn first so the opaque node boxes occlude their outer ends. */ }

```

```

72     {
73         points.map((p) => (
74             <span class="fz-spoke" style={`--a:${p.deg}deg`} aria-hidden="true">
75                 <span class="fz-spoke__line" />
76                 {/*
77                     No per-spoke delay. The whole ring breathes on one clock: every dot
78                     travels out to its system and back at the same moment, which is the
79                     point being made – one core, one cycle.
80                 */}
81                 <span class="fz-spoke__pulse" />
82             </span>
83         ))
84     }
85
86     <div class="fz-hub__core">
87         <span class="fz-hub__core-label">{site.name}</span>
88         <span class="fz-hub__core-meta">one system</span>
89     </div>
90
91     {
92         points.map((p) => (
93             <div class="fz-node" style={`left:${p.x}%;top:${p.y}%;`}>
94                 <span class="fz-node__dot" aria-hidden="true" />
95                 <span class="fz-node__label">{p.label}</span>
96                 <span class="fz-node__meta">{p.meta}</span>
97             </div>
98         ))
99     }
100 </div>
101
102 <figcaption class="eyebrow mt-5">{caption}</figcaption>
103 </figure>

```

```
104
105 <style>
106   .fz-hub {
107     margin: 0;
108     width: 100%;
109   }
110
111   /*
112     Square by construction. Any other ratio distorts the ring, which is what
113     made the previous version look lopsided.
114
115     Sized to sit inside a half-width column rather than a full-bleed section.
116     Neighbouring nodes are  $2 * r * \sin(22.5\text{deg})$  apart, so at the 0.38 ring
117     radius used above a stage of S gives a  $0.29 * S$  gap – comfortably clear of
118     the node width at every size below.
119   */
120   .fz-hub__stage {
121     position: relative;
122     width: 100%;
123     max-width: 24rem;
124     aspect-ratio: 1 / 1;
125     margin-inline: auto;
126     --node-w: 6rem;
127   }
128   @media (min-width: 64rem) {
129     .fz-hub .fz-hub__stage {
130       max-width: 29rem;
131       --node-w: 6.6rem;
132     }
133   }
134
135   /*
```

```
136     Below roughly a phone width the ring can't hold eight boxes without them
137     colliding – the gap between neighbours is 0.765x the radius, and the radius
138     has nowhere left to grow. Stack instead of shrinking the type to fit.
139
140     These are deliberately over-specified. The CSS minifier hoists media blocks
141     above the rules they're meant to override, so a bare `.fz-node` here loses
142     to the bare `.fz-node` below on source order alone.
143 */
144 @media (max-width: 34rem) {
145     .fz-hub .fz-hub__stage {
146         aspect-ratio: auto;
147         max-width: 26rem;
148         display: grid;
149         grid-template-columns: 1fr 1fr;
150         gap: 0.6rem;
151     }
152     .fz-hub__stage .fz-spoke {
153         display: none;
154     }
155     .fz-hub__stage .fz-hub__core {
156         position: static;
157         transform: none;
158         grid-column: 1 / -1;
159         margin-bottom: 0.4rem;
160     }
161     .fz-hub__stage .fz-node {
162         position: static;
163         transform: none;
164         width: auto;
165     }
166 }
167
```

```
168  /*
169     Each spoke is a zero-height track pinned at the centre and rotated into
170     place. Its length is half the stage, so positions along it are simple
171     percentages of the ring radius.
172  */
173  .fz-spoke {
174      position: absolute;
175      left: 50%;
176      top: 50%;
177      width: 50%;
178      height: 0;
179      transform-origin: 0 50%;
180      transform: rotate(var(--a));
181      pointer-events: none;
182  }
183
184  /* Runs from just outside the core to just under the node box. */
185  .fz-spoke__line {
186      position: absolute;
187      top: 0;
188      left: 30%;
189      right: 16%;
190      height: 1px;
191      background-image: linear-gradient(to right, var(--color-line-2) 55%, transparent 55%);
192      background-size: 7px 1px;
193      background-repeat: repeat-x;
194  }
195
196  .fz-spoke__pulse {
197      position: absolute;
198      top: 0;
199      left: 0;
```

```
200     width: 100%;
201     height: 0;
202     opacity: 0;
203 }
204 /* The travelling dot itself, drawn at the left edge of its moving track. */
205 .fz-spoke__pulse::before {
206     content: '';
207     position: absolute;
208     top: 0;
209     left: 0;
210     width: 5px;
211     height: 5px;
212     margin-top: -2.5px;
213     margin-left: -2.5px;
214     border-radius: 50%;
215     background: var(--color-signal);
216     /* Keeps the dot upright rather than orbiting with the rotated track. */
217     transform: rotate(calc(-1 * var(--a)));
218 }
219
220 .fz-hub__core {
221     position: absolute;
222     left: 50%;
223     top: 50%;
224     transform: translate(-50%, -50%);
225     z-index: 3;
226     display: flex;
227     flex-direction: column;
228     align-items: center;
229     gap: 0.15rem;
230     background: var(--color-ink);
231     color: var(--color-inverse-ink);
```



```
232     padding: 1rem 1.35rem;
233     border-radius: var(--radius);
234     text-align: center;
235 }
236 .fz-hub__core-label {
237     font-family: var(--font-display);
238     font-size: 1.1rem;
239     line-height: 1;
240 }
241 .fz-hub__core-meta {
242     font-family: var(--font-mono);
243     font-size: 0.6rem;
244     letter-spacing: 0.1em;
245     text-transform: uppercase;
246     color: var(--color-inverse-ink-3);
247 }
248
249 /*
250     Fixed width for every node. This is what actually makes the ring read as
251     symmetric – boxes sized to their own labels never can.
252 */
253 .fz-node {
254     position: absolute;
255     transform: translate(-50%, -50%);
256     z-index: 2;
257     width: var(--node-w);
258     display: flex;
259     flex-direction: column;
260     align-items: center;
261     gap: 0.1rem;
262     background: var(--color-paper);
263     border: 1px solid var(--color-line);
```

```
264     border-radius: var(--radius);
265     padding: 0.5rem 0.4rem;
266     text-align: center;
267 }
268 .fz-node__dot {
269     width: 5px;
270     height: 5px;
271     border-radius: 50%;
272     background: var(--color-signal);
273     margin-bottom: 0.15rem;
274 }
275 .fz-node__label {
276     font-family: var(--font-display);
277     font-size: 0.92rem;
278     line-height: 1.05;
279 }
280 .fz-node__meta {
281     font-family: var(--font-mono);
282     font-size: 0.55rem;
283     letter-spacing: 0.07em;
284     text-transform: uppercase;
285     color: var(--color-ink-3);
286 }
287
288 @media (prefers-reduced-motion: no-preference) {
289     .fz-spoke__pulse {
290         animation: fz-pulse 4s ease-in-out infinite;
291     }
292     /*
293         The node lights up as the dot arrives, on the same 4s clock, so the ring
294         flashes in unison instead of rippling.
295     */
```

```

296     .fz-node__dot {
297         animation: fz-blink 4s ease-in-out infinite;
298     }
299     /* A permanently looping diagram off screen is wasted battery. */
300     .fz-hub:not(.is-live) .fz-spoke__pulse,
301     .fz-hub:not(.is-live) .fz-node__dot {
302         animation-play-state: paused;
303     }
304 }
305
306 /*
307     One dot per spoke, out to the system and back to the core, identical timing
308     everywhere. Percentages resolve against the track width, which is the ring
309     radius, so the travel distance is the same on every spoke regardless of
310     angle. Compositor-only – transform and opacity, no layout.
311 */
312 @keyframes fz-pulse {
313     0% { transform: translateX(30%); opacity: 0; }
314     8% { opacity: 1; }
315     42% { transform: translateX(76%); opacity: 1; }
316     50% { transform: translateX(76%); opacity: 1; }
317     92% { transform: translateX(30%); opacity: 1; }
318     100% { transform: translateX(30%); opacity: 0; }
319 }
320 @keyframes fz-blink {
321     0%, 100% { opacity: 0.3; }
322     /* Peaks at the moment the dot reaches the node. */
323     42%, 50% { opacity: 1; }
324     75% { opacity: 0.3; }
325 }
326 </style>
327

```

```

328 <script>
329     // Run the flow only while the diagram is on screen, and rebind after each
330     // client-side navigation since the document is never re-parsed.
331     function initHub() {
332         const hubs = document.querySelectorAll('.fz-hub');
333         if (!hubs.length) return;
334         if (window.matchMedia('(prefers-reduced-motion: reduce)').matches) return;
335
336         if (!('IntersectionObserver' in window)) {
337             hubs.forEach((h) => h.classList.add('is-live'));
338             return;
339         }
340         const io = new IntersectionObserver(
341             (entries) => {
342                 entries.forEach((entry) => entry.target.classList.toggle('is-live', entry.isIntersecting));
343             },
344             { threshold: 0.15 }
345         );
346         hubs.forEach((h) => io.observe(h));
347     }
348
349     initHub();
350     document.addEventListener('astro:page-load', initHub);
351 </script>
352

```

ASTRO src/components/Faq.astro

```

1 ---
2 /*
3 FAQ
4 ---
5 The answer-engine surface. Each question is a real heading and each answer is

```

```
6   written to stand alone if it is lifted out of the page, which is what featured
7   snippets and generative engines actually quote.
8
9   Rendered as native <details> so it works without JavaScript, is keyboard
10  accessible for free, and stays fully readable to crawlers even when collapsed.
11  */
12  interface Item {
13      q: string;
14      a: string;
15  }
16  interface Props {
17      items: Item[];
18      title?: string;
19      eyebrow?: string;
20  }
21
22  const { items, title = 'Common questions', eyebrow = 'FAQ' } = Astro.props;
23  ---
24
25  <!--
26   Slightly tighter top padding than a standalone section would take: this always
27   follows a section that already ends in generous bottom padding, and stacking
28   both reads as a dead gap rather than as breathing room.
29  -->
30  <section class="wrap border-t border-[var(--color-line)] py-14 md:py-16">
31      <div class="grid gap-10 md:grid-cols-[0.8fr_1.2fr]">
32          <div>
33              <p class="eyebrow">{eyebrow}</p>
34              <h2 class="mt-4 text-3xl md:text-4xl">{title}</h2>
35          </div>
36
37          <div class="border-t border-[var(--color-line)]">
```

```
38     {
39         items.map((item) => (
40             <details class="faq group border-b border-[var(--color-line)]">
41                 <summary class="faq__q">
42                     <h3 class="faq__heading">{item.q}</h3>
43                     <span class="faq__icon" aria-hidden="true" />
44                 </summary>
45                 <div class="faq__a">
46                     <p>{item.a}</p>
47                 </div>
48             </details>
49         ))
50     }
51 </div>
52 </div>
53 </section>
54
55 <style>
56     .faq__q {
57         display: flex;
58         align-items: baseline;
59         justify-content: space-between;
60         gap: 1.5rem;
61         padding: 1.15rem 0;
62         cursor: pointer;
63         list-style: none;
64     }
65     .faq__q::--webkit-details-marker {
66         display: none;
67     }
68     .faq__q:focus-visible {
69         outline: 2px solid var(--color-signal);
```

```
70     outline-offset: 2px;
71 }
72 .faq__heading {
73     font-family: var(--font-display);
74     font-size: 1.15rem;
75     line-height: 1.3;
76     margin: 0;
77     transition: color 0.18s ease;
78 }
79 .faq__q:hover .faq__heading {
80     color: var(--color-signal-ink);
81 }
82
83 /* A plus that becomes a minus – no icon library, no layout shift. */
84 .faq__icon {
85     position: relative;
86     flex-shrink: 0;
87     width: 12px;
88     height: 12px;
89     margin-top: 0.35rem;
90 }
91 .faq__icon::before,
92 .faq__icon::after {
93     content: '';
94     position: absolute;
95     background: var(--color-ink-3);
96     transition: transform 0.22s ease, opacity 0.22s ease;
97 }
98 .faq__icon::before {
99     inset-inline: 0;
100     top: 50%;
101     height: 1.5px;
```

```
102     transform: translateY(-50%);
103 }
104 .faq__icon::after {
105     inset-block: 0;
106     left: 50%;
107     width: 1.5px;
108     transform: translateX(-50%);
109 }
110 .faq[open] .faq__icon::after {
111     transform: translateX(-50%) scaleY(0);
112     opacity: 0;
113 }
114 .faq[open] .faq__icon::before {
115     background: var(--color-signal);
116 }
117
118 .faq__a {
119     padding-bottom: 1.25rem;
120     max-width: 60ch;
121 }
122 .faq__a p {
123     margin: 0;
124     color: var(--color-ink-2);
125     font-size: 1rem;
126     line-height: 1.65;
127 }
128
129 @media (prefers-reduced-motion: no-preference) {
130     .faq[open] .faq__a {
131         animation: faq-open 0.28s cubic-bezier(0.22, 1, 0.36, 1) both;
132     }
133 }
```



```

134   @keyframes faq-open {
135     from {
136       opacity: 0;
137       transform: translateY(-4px);
138     }
139     to {
140       opacity: 1;
141       transform: none;
142     }
143   }
144 </style>
145

```

ASTRO `src/components/Footer.astro`

```

1  ---
2  import Logo from './Logo.astro';
3  import { nav, site } from '../data/site';
4  const year = new Date().getFullYear();
5  ---
6
7  <footer class="mt-28 border-t border-[var(--color-line)] bg-[var(--color-paper-2)]">
8    <div class="wrap py-16">
9      <div class="grid gap-12 md:grid-cols-[1.4fr_1fr_1fr]">
10       <div>
11         <div class="text-[var(--color-ink)]"><Logo /></div>
12         <p class="mt-4 max-w-xs text-[0.95rem] text-[var(--color-ink-2)]">
13           {site.tagline}. We build the systems that do the repetitive work a business
14           currently does by hand.
15         </p>
16         <p class="eyebrow mt-6">A studio under {site.parent}</p>
17       </div>
18

```

```
19     <div>
20         <p class="eyebrow mb-4">Site</p>
21         <ul class="space-y-1.5">
22             {
23                 nav.map((item) => (
24                     <li>
25                         <a href={item.href} class="inline-flex min-h-6 items-center text-[0.95rem] link-
underline">
26                             {item.label}
27                         </a>
28                     </li>
29                 ))
30             }
31         <li>
32             <a href="/contact/" class="inline-flex min-h-6 items-center text-[0.95rem] link-
underline">Contact</a>
33         </li>
34     </ul>
35 </div>
36
37 <div>
38     <p class="eyebrow mb-4">Get in touch</p>
39     <a href={`mailto:${site.email}`} class="inline-flex min-h-6 items-center text-[0.95rem] link-
underline">{site.email}</a>
40     <p class="mt-4 text-[0.9rem] text-[var(--color-ink-3)]">{site.location}</p>
41 </div>
42 </div>
43
44 <hr class="rule my-10" />
45 <div class="flex flex-col sm:flex-row items-start sm:items-center justify-between gap-3">
46     <p class="font-[var(--font-mono)] text-[0.72rem] tracking-[0.04em] text-[var(--color-ink-3)]">
47         © {year} {site.name}. All rights reserved.
48     </p>
```

```

49     <p class="font-[var(--font-mono)] text-[0.72rem] tracking-[0.04em] text-[var(--color-ink-3)]">
50         Built to keep running after we leave.
51     </p>
52 </div>
53 </div>
54 </footer>
55

```

ASTRO src/components/Header.astro

```

1  ---
2  import Logo from './Logo.astro';
3  import { nav, site } from '../data/site';
4  const path = Astro.url.pathname;
5  const isActive = (href: string) => path === href || (href !== '/' && path.startsWith(href));
6  ---
7
8  <header class="border-b border-[var(--color-line)] bg-[var(--color-paper)]/95 sticky top-0 z-40
  backdrop-blur-[2px]">
9
10     <div class="wrap flex items-center justify-between h-16">
11
12         <a href="/" class="text-[var(--color-ink)]" aria-label={` ${site.name} - home`} >
13
14             <Logo />
15
16         </a>
17
18     <nav class="hidden md:flex items-center gap-6" aria-label="Primary">
19
20         {
21             nav.map((item) => (
22
23                 <a
24
25                     href={item.href}
26
27                     class="inline-flex items-center py-2 font-[var(--font-mono)] text-[0.8rem] tracking-
[0.03em] text-[var(--color-ink-2)] transition-colors hover:text-[var(--color-signal-ink)]"
28
29                     aria-current={isActive(item.href) ? 'page' : undefined}
30
31                 >

```

```

22         <span class={isActive(item.href) ? 'underline decoration-[var(--color-signal)] underline-
offset-4' : ''}>
23             {item.label}
24         </span>
25     </a>
26 ))
27 }
28     <a href="/contact/" class="btn btn-primary">Let's talk growth</a>
29 </nav>
30
31 <details id="menu" class="md:hidden relative">
32     <summary
33         class="list-none cursor-pointer font-[var(--font-mono)] text-[0.8rem] tracking-[0.05em]
uppercase select-none py-2"
34         aria-label="Menu"
35     >
36         Menu
37     </summary>
38     <div class="absolute right-0 top-full mt-2 w-60 border border-[var(--color-line)] bg-[var(--
color-paper)] shadow-lg p-2">
39         {
40             nav.map((item) => (
41                 <a
42                     href={item.href}
43                     class="block px-3 py-2.5 font-[var(--font-mono)] text-[0.85rem] text-[var(--color-ink-
2)] hover:bg-[var(--color-paper-2)]"
44                     aria-current={isActive(item.href) ? 'page' : undefined}
45                 >
46                     {item.label}
47                 </a>
48             ))
49         }
50         <a href="/contact/" class="block px-3 py-2.5 mt-1 font-[var(--font-mono)] text-[0.85rem] bg-
[var(--color-ink)] text-[var(--color-paper)] text-center">

```

```
51         Let's talk growth
52     </a>
53 </div>
54 </details>
55 </div>
56 </header>
57
58 <script>
59     // `<details>` gives us a working menu with no JavaScript, but not the dismissal
60     // behavior people expect from one. Escape and outside-click are added here so
61     // the menu never traps a user who opened it by accident.
62     const menu = document.querySelector('#menu') as HTMLDetailsElement | null;
63
64     if (menu) {
65         document.addEventListener('keydown', (event) => {
66             if (event.key === 'Escape' && menu.open) {
67                 menu.open = false;
68                 menu.querySelector('summary')?.focus();
69             }
70         });
71
72         document.addEventListener('click', (event) => {
73             if (menu.open && !menu.contains(event.target as Node)) {
74                 menu.open = false;
75             }
76         });
77     }
78 </script>
79
```

```
1  ---

2  /*

3   Flowzora mark

4   -----

5   A routing node sitting on a channel: data enters from the left, passes through

6   the system, and leaves on the right. The rust core is the record being handled

7   – the same "signal" language the diagrams use, where rust always means the live

8   thing moving through.

9

10  It is a real flowchart primitive rather than a decorative shape, drawn on the

11  same geometry as WorkflowSystem and ConnectedSystems: 2px strokes, hard

12  corners, no curves. Chosen over a lettermark because the proposition is flow

13  through a system, not the initial of a name.

14  */

15  import { site } from '../data/site';

16

17  interface Props {

18    class?: string;

19    /** Render the mark alone, without the wordmark beside it. */

20    markOnly?: boolean;

21  }

22  const { class: className = '', markOnly = false } = Astro.props;

23  ---

24

25  <span class={`fz-logo inline-flex items-center gap-2.5 ${className}`} aria-label={site.name}>

26    <svg

27      class="fz-logo__mark shrink-0"

28      width="22"

29      height="22"

30      viewBox="0 0 24 24"

31      fill="none"
```

```

32     aria-hidden="true"
33 >
34     <!-- The channel: in on the left, out on the right -->
35     <path class="fz-logo__in" d="M0 12 L5 12" stroke="currentColor" stroke-width="2" />
36     <path class="fz-logo__out" d="M19 12 L24 12" stroke="currentColor" stroke-width="2" />
37     <!-- The node: where the work happens -->
38     <path d="M12 5 L19 12 L12 19 L5 12 Z" stroke="currentColor" stroke-width="2" />
39     <!-- The record in transit -->
40     <circle class="fz-logo__core" cx="12" cy="12" r="2.5" fill="var(--color-signal)" />
41 </svg>
42
43 {
44     !markOnly && (
45         <span class="fz-logo__word font-[var(--font-mono)] text-[0.95rem] font-medium uppercase
46         tracking-[0.08em]">
47             {site.name}
48         </span>
49     )
50 </span>
51
52 <style>
53     .fz-logo__core {
54         transform-origin: 12px 12px;
55         transition: transform 0.35s cubic-bezier(0.22, 1, 0.36, 1);
56     }
57     /*
58     On hover the core advances a fraction along the channel – the same "something
59     is running" idea the diagrams use, at the smallest amplitude that still
60     registers. Anything larger would be decoration in a nav bar.
61     */
62     a:hover .fz-logo__core,

```

```

63  .fz-logo:hover .fz-logo__core {
64      transform: translateX(2px);
65  }
66
67  @media (prefers-reduced-motion: reduce) {
68      .fz-logo__core {
69          transition: none;
70      }
71  }
72  </style>
73

```

ASTRO src/components/Testimonials.astro

```

1  ---
2  /*
3   Testimonials
4   -----
5   Named, dated, linked. The design does one job: make it obvious these are real
6   and checkable in one click.
7
8   Every choice here is about verifiability rather than decoration. The name is
9   a link to the profile that wrote the words; the relationship is stated
10  ("Client" vs "Colleague"); the date is shown. An anonymous quote in a nicer
11  card would be worth less, because the reader's actual question is not "is
12  this well designed" but "did a real person say this".
13
14  No carousel. Auto-rotating quotes hide two thirds of the evidence and take
15  control away from someone who is reading carefully – which is exactly the
16  person about to spend money.
17  */
18  import { testimonials } from '../data/site';
19

```



```

20 interface Props {
21   /** Render on the dark surface, for use between light sections. */
22   dark?: boolean;
23   /**
24    * Sit on the base paper rather than the tinted surface. Needed wherever the
25    * neighbouring section is already `paper-2`, or the two run together into
26    * one undifferentiated block.
27    */
28   plain?: boolean;
29   heading?: string;
30   eyebrow?: string;
31 }
32 const {
33   dark = false,
34   plain = false,
35   eyebrow = 'What clients say',
36   heading = 'Verified, and signed.',
37 } = Astro.props;
38 ---
39
40 <section
41   class={
42     dark
43       ? 'bg-[var(--color-slate)] text-[var(--color-inverse-ink)]'
44       : plain
45         ? 'border-b border-[var(--color-line)]'
46         : 'border-y border-[var(--color-line)] bg-[var(--color-paper-2)]'
47   }
48 >
49   <div class="wrap py-16 md:py-20">
50     <div class="max-w-xl">
51       <p class={`eyebrow ${dark ? 'text-[var(--color-inverse-ink-3)]' : ''}`}>{eyebrow}</p>

```

```

52     <h2 class="mt-4 text-3xl md:text-4xl">{heading}</h2>
53     <p
54         class={`mt-5 text-[0.95rem] ${dark ? 'text-[var(--color-inverse-ink-2)]' : 'text-[var(--color-ink-2)]'}`}
55     >
56         Every quote below is a public LinkedIn recommendation. Click any name to
57         read it on their profile.
58     </p>
59 </div>
60
61 <ul class="reveal mt-12 grid gap-8 md:grid-cols-3">
62     {
63         testimonials.map((t, i) => (
64             <li
65                 data-stagger
66                 style={`--i:${i}`}
67                 class={`flex flex-col border-t-2 pt-6 ${
68                     dark ? 'border-[var(--color-signal-bright)]' : 'border-[var(--color-signal)]'
69                 }]`
70             >
71                 {/*
72                     The pull quote is the scannable layer. Most visitors read one line
73                     per card and move on, so the strongest phrase is given display
74                     type and the full quote sits underneath for anyone who slows down.
75                 */}
76                 <p class="font-[var(--font-display)] text-xl leading-snug">{t.pullQuote}</p>
77
78                 <blockquote
79                     class={`mt-4 flex-1 text-[0.92rem] leading-relaxed ${
80                         dark ? 'text-[var(--color-inverse-ink-2)]' : 'text-[var(--color-ink-2)]'
81                     }]`
82                 >

```

```

83         {t.quote}
84     </blockquote>
85
86     <footer class="mt-6">
87         <a
88             href={t.linkedin}
89             rel="noopener nofollow"
90             target="_blank"
91             class="link-underline font-medium"
92         >
93             {t.name}
94         </a>
95
96         <p
97             class={`mt-1 text-[0.85rem] ${
98                 dark ? 'text-[var(--color-inverse-ink-3)]' : 'text-[var(--color-ink-3)]'
99             }`}
100             >
101                 {t.role}
102                 {t.company ? ` · ${t.company}` : ''}
103         </p>
104         {/*
105             Relationship and date, in the technical face used everywhere
106             else for provenance. "Client" is the load-bearing word; showing
107             "Colleague" on the third card is what makes the first two
108             believable.
109         */}
110         <p
111             class={`mt-2 font-[var(--font-mono)] text-[0.68rem] uppercase tracking-[0.1em] ${
112                 dark ? 'text-[var(--color-inverse-ink-4)]' : 'text-[var(--color-ink-3)]'
113             }`}
114             >
115             {t.relationship} · {t.date}

```

```

115         </p>
116     </footer>
117 </li>
118 ))
119 }
120 </ul>
121 </div>
122 </section>
123

```

ASTRO src/components/WorkflowSystem.astro

```

1  ---
2  /*
3   WorkflowSystem
4   -----
5   The signature asset: makes an invisible automation tangible.
6   A real, labeled flow – not decoration. Motion only advances the flow,
7   and is fully disabled under prefers-reduced-motion.
8  */
9  interface Node {
10     label: string;
11     meta: string;
12     kind?: 'input' | 'logic' | 'system' | 'human' | 'output';
13 }
14 interface Props {
15     nodes?: Node[];
16     caption?: string;
17 }
18
19 const defaultNodes: Node[] = [
20     { label: 'Request', meta: 'email · form · chat', kind: 'input' },
21     { label: 'Classify', meta: 'model + rules', kind: 'logic' },

```

```

22   { label: 'CRM', meta: 'record created', kind: 'system' },
23   { label: 'Business rules', meta: 'route · enrich', kind: 'logic' },
24   { label: 'Act', meta: 'Slack · email · ERP', kind: 'system' },
25   { label: 'Approve', meta: 'human in the loop', kind: 'human' },
26   { label: 'Analytics', meta: 'logged · measured', kind: 'output' },
27 ];
28
29 const { nodes = defaultNodes, caption = 'A support request, handled end to end' } = Astro.props;
30
31 const kindClass: Record<string, string> = {
32   input: 'fz-node--input',
33   logic: 'fz-node--logic',
34   system: 'fz-node--system',
35   human: 'fz-node--human',
36   output: 'fz-node--output',
37 };
38 ---
39
40 <figure class="fz-flow">
41   <div class="fz-flow__head">
42     <span class="fz-live" aria-hidden="true">
43       <span class="fz-live__dot"></span>System · running
44     </span>
45     <span class="fz-flow__meta" aria-hidden="true">no hands on keyboard</span>
46   </div>
47   <div class="fz-flow__track" role="img" aria-label={`Automated workflow: ${nodes.map((n) =>
48     n.label).join(', then ')}.`}>
49     {
50       nodes.map((node, i) => (
51         <div class={`fz-node ${kindClass[node.kind ?? 'system']}`}>
52           <span class="fz-node__idx">{String(i + 1).padStart(2, '0')}</span>

```

```

53         <span class="fz-node__label">{node.label}</span>
54         <span class="fz-node__meta">{node.meta}</span>
55     </div>
56     {i < nodes.length - 1 && (
57         <div class="fz-edge" aria-hidden="true">
58             <span class="fz-edge__line" />
59             <span class="fz-edge__pulse" style={`animation-delay:${i * 0.45}s`} />
60             <span class="fz-edge__pulse fz-edge__pulse--2" style={`animation-delay:${i * 0.45 +
1.3}s`} />
61         </div>
62     )}
63 </>
64 ))
65 }
66 </div>
67 <figcaption class="eyebrow mt-5">{caption}</figcaption>
68 </figure>
69
70 <script>
71 // Run the flow only while it is on screen. The diagram is meant to feel like a
72 // system quietly running, not to burn cycles three viewports away.
73 const flows = document.querySelectorAll('.fz-flow');
74 if (!window.matchMedia('(prefers-reduced-motion: reduce)').matches) {
75     if ('IntersectionObserver' in window) {
76         const io = new IntersectionObserver(
77             (entries) => {
78                 entries.forEach((entry) => {
79                     entry.target.classList.toggle('is-live', entry.isIntersecting);
80                 });
81             },
82             { threshold: 0.15 }
83         );

```

```
84     flows.forEach((flow) => io.observe(flow));
85   } else {
86     flows.forEach((flow) => flow.classList.add('is-live'));
87   }
88 }
89 </script>
90
91 <style>
92   .fz-flow {
93     margin: 0;
94   }
95   .fz-flow__head {
96     display: flex;
97     align-items: center;
98     justify-content: space-between;
99     gap: 1rem;
100    margin-bottom: 1rem;
101    padding-bottom: 0.75rem;
102    border-bottom: 1px solid var(--color-line);
103  }
104  .fz-flow__meta {
105    font-family: var(--font-mono);
106    font-size: 0.72rem;
107    letter-spacing: 0.1em;
108    text-transform: uppercase;
109    color: var(--color-ink-3);
110  }
111  .fz-flow__track {
112    display: grid;
113    gap: 0.5rem;
114    grid-auto-flow: row;
115  }
```

```
116 .fz-node {
117     position: relative;
118     border: 1px solid var(--color-line);
119     background: var(--color-paper);
120     padding: 0.85rem 1rem;
121     border-radius: var(--radius);
122     display: flex;
123     flex-direction: column;
124     gap: 0.15rem;
125     border-left-width: 3px;
126 }
127 .fz-node--input { border-left-color: var(--color-ink); }
128 .fz-node--logic { border-left-color: var(--color-signal); }
129 .fz-node--system { border-left-color: var(--color-ink-3); }
130 .fz-node--human { border-left-color: var(--color-ink); border-left-style: dashed; }
131 .fz-node--output { border-left-color: var(--color-ink); }
132
133 .fz-node__idx {
134     font-family: var(--font-mono);
135     font-size: 0.68rem;
136     letter-spacing: 0.1em;
137     color: var(--color-ink-3);
138 }
139 .fz-node__label {
140     font-family: var(--font-display);
141     font-size: 1.15rem;
142     line-height: 1.1;
143 }
144 .fz-node__meta {
145     font-family: var(--font-mono);
146     font-size: 0.72rem;
147     color: var(--color-ink-3);
```



```
148 }
149
150 .fz-edge {
151     position: relative;
152     height: 1.4rem;
153     --fz-edge-length: 1.4rem;
154     display: flex;
155     align-items: center;
156     justify-content: center;
157 }
158 .fz-edge__line {
159     width: 1px;
160     height: 100%;
161     background-image: linear-gradient(to bottom, var(--color-line-2) 50%, transparent 50%);
162     background-size: 1px 8px;
163     background-repeat: repeat-y;
164 }
165 .fz-edge__pulse {
166     position: absolute;
167     width: 6px;
168     height: 6px;
169     border-radius: 50%;
170     background: var(--color-signal);
171     /*
172     Positioned once, then moved with transform only. Animating `top`/`left`
173     would force layout on every frame of a permanently running animation,
174     which is the last thing the largest-contentful-paint screen needs.
175     */
176     top: 0;
177     left: 50%;
178     margin-left: -3px;
179     margin-top: -3px;
```

```
180     opacity: 0;
181 }
182
183 /* Horizontal layout on wider screens */
184 @media (min-width: 900px) {
185     .fz-flow__track {
186         grid-auto-flow: column;
187         align-items: stretch;
188         gap: 0;
189     }
190     .fz-node {
191         flex: 1;
192         min-width: 0;
193     }
194     .fz-edge {
195         height: auto;
196         width: 1.75rem;
197         --fz-edge-length: 1.75rem;
198         align-self: center;
199     }
200     .fz-edge__line {
201         width: 100%;
202         height: 1px;
203         background-image: linear-gradient(to right, var(--color-line-2) 50%, transparent 50%);
204         background-size: 8px 1px;
205         background-repeat: repeat-x;
206     }
207     .fz-edge__pulse {
208         top: 50%;
209         left: 0;
210         margin-left: -3px;
211         margin-top: -3px;
```

```
212     }
213 }
214
215 /*
216     The trailing pulse reads as a fainter echo of the first. Opacity is animated,
217     so the difference has to live in the color rather than in an opacity rule
218     the keyframes would immediately overwrite.
219 */
220 .fz-edge__pulse--2 {
221     background: color-mix(in srgb, var(--color-signal) 45%, transparent);
222 }
223
224 @media (prefers-reduced-motion: no-preference) {
225     .fz-edge__line {
226         animation: fz-flow-v 0.9s linear infinite;
227     }
228     .fz-edge__pulse {
229         animation: fz-pulse-v 2.6s ease-in-out infinite;
230     }
231 }
232 @media (min-width: 900px) {
233     .fz-edge__line {
234         animation: fz-flow-h 0.9s linear infinite;
235     }
236     .fz-edge__pulse {
237         animation: fz-pulse-h 2.6s ease-in-out infinite;
238     }
239 }
240 /*
241     A permanently running animation on an off-screen element is wasted battery.
242     Paused by default and resumed only while the diagram is actually in view.
243 */
```

```
244     .fz-flow:not(.is-live) .fz-edge__line,
245     .fz-flow:not(.is-live) .fz-edge__pulse {
246         animation-play-state: paused;
247     }
248 }
249 @media (prefers-reduced-motion: reduce) {
250     .fz-edge__pulse { display: none; }
251 }
252
253 @keyframes fz-flow-v {
254     to { background-position-y: 8px; }
255 }
256 @keyframes fz-flow-h {
257     to { background-position-x: 8px; }
258 }
259
260 /* Compositor-only: transform and opacity, never layout properties. */
261 @keyframes fz-pulse-v {
262     0% { transform: translateY(0); opacity: 0; }
263     15% { opacity: 1; }
264     85% { opacity: 1; }
265     100% { transform: translateY(var(--fz-edge-length, 1.4rem)); opacity: 0; }
266 }
267 @keyframes fz-pulse-h {
268     0% { transform: translateX(0); opacity: 0; }
269     15% { opacity: 1; }
270     85% { opacity: 1; }
271     100% { transform: translateX(var(--fz-edge-length, 1.75rem)); opacity: 0; }
272 }
273 </style>
274
```

```
1 import { defineCollection, z } from 'astro:content';
2 import { glob } from 'astro/loaders';
3
4 const work = defineCollection({
5   loader: glob({ pattern: '**/*.md,mdx', base: './src/content/work' }),
6   schema: z.object({
7     title: z.string(),
8     // Honest labelling is a core brand rule. "internal-build" and "concept"
9     // are clearly marked in the UI so nothing is passed off as a paid client.
10    kind: z.enum(['client', 'internal-build', 'concept']).default('internal-build'),
11    client: z.string().optional(),
12    sector: z.string(),
13    summary: z.string(),
14    // Problem → Before → Intervention → System → Result structure.
15    problem: z.string(),
16    before: z.array(z.string()),
17    intervention: z.string(),
18    /*
19     `source` is required, not optional.
20
21     Unsourced numbers are the single most common tell of a fabricated agency
22     case study, and sourced ones are what answer and generative engines
23     actually quote. Making the field mandatory means a metric physically
24     cannot ship without stating where it came from – the honesty policy is
25     enforced by the schema rather than by remembering.
26    */
27    result: z.array(
28      z.object({
29        metric: z.string(),
30        label: z.string(),
31        source: z.string(),
```

```
32     })
33   ),
34   stack: z.array(z.string()),
35   humanImpact: z.string(),
36   order: z.number().default(0),
37   draft: z.boolean().default(false),
38   /*
39     Client write-ups that have not yet been approved by the client.
40
41     Naming a company and describing their internal process is theirs to
42     consent to, not ours to assume. Entries flagged here render in local
43     preview so the page can be reviewed, and are excluded from production
44     builds until the flag is cleared. `draft` would hide them everywhere,
45     which defeats the point of reviewing them.
46   */
47   pendingApproval: z.boolean().default(false),
48   }),
49 });
50
51 const writing = defineCollection({
52   loader: glob({ pattern: '**/*.md,mdx', base: './src/content/writing' }),
53   schema: z.object({
54     title: z.string(),
55     description: z.string(),
56     pubDate: z.coerce.date(),
57     tags: z.array(z.string()).default([]),
58     draft: z.boolean().default(false),
59   }),
60 });
61
62 export const collections = { work, writing };
```

MD src/content/work/automated-bureaucracy-platform.md

```
1 ---
2 title: A full-stack platform for an automation agency
3 kind: client
4 client: Automated Bureaucracy
5 sector: Professional services
6 order: -1
7 summary: >-
8   A full-stack web application built as the foundation for a new automation
9   agency – the platform the business runs on rather than a brochure site.
10 problem: >-
11   A new automation agency needed more than a marketing page. It needed a
12   working application it could build a business on: something that would hold
13   up as the agency grew rather than something to be replaced at the first sign
14   of traction.
15 before:
16   - A new agency with no platform of its own
17   - Off-the-shelf site builders adequate for a brochure, not for an application
18   - Any real functionality would mean starting over later
19 intervention: >-
20   Built and delivered a full-stack application at automatedbureaucracy.com,
21   designed as a foundation rather than a finished artefact – so the agency
22   could add to it as the business took shape.
23 result:
24   - metric: Full stack
25     label: application, delivered end to end
26     source: >-
27       Stated by the client, Blake DeHaas, in a public LinkedIn recommendation
28       (June 2025).
29   - metric: Live
```

```
30     label: at automatedbureaucracy.com
31     source: Publicly verifiable – the site is live at that address.
32     - metric: Foundation
33     label: built to grow with the agency
34     source: >-
35         Stated by the client in the same recommendation: "a solid foundation for
36         my automation agency".
37 stack:
38     - Full-stack web application
39     - Custom frontend and backend
40 humanImpact: >-
41     The agency launched on a platform it owns and can extend, instead of one it
42     would outgrow and have to rebuild.
43 draft: false
44 ---
45
46 ## What this is
47
48 A **paid client engagement** for Blake DeHaas, building the platform for
49 Automated Bureaucracy.
50
51 Everything on this page comes from what the client said publicly, plus the fact
52 that the site is live and can be checked. No metrics are claimed beyond that.
53
54 ## In the client's words
55
56 > Hired Niraj to build out a website for me at automatedbureaucracy.com and he
57 > delivered a great full stack application that provides a solid foundation for
58 > my automation agency.
59 >
60 > – [Blake DeHaas](https://www.linkedin.com/in/blakedehaas/), Graduate
61 > Operations Software Engineer, June 2025
```


62

63 ## "Foundation" is the word that matters

64

65 The client called it a foundation, and that is the distinction worth drawing

66 out. A brochure site is finished the day it ships. A foundation is the thing

67 you keep building on – which means the decisions that matter are the ones about

68 what comes next, not what launches.

69

70 Built the second way, the agency can add functionality as it grows. Built the

71 first way, the first real requirement means starting again.

72

73 ## See it

74

75 The site is live at

76 automatedbureaucracy.com – worth a look if

77 you want to see delivered work rather than a description of it.

78

MD src/content/work/ecommerce-fulfillment-sync.md

1 ---

2 title: Order-to-fulfillment sync for a small e-commerce shop

3 kind: concept

4 sector: E-commerce

5 order: 2

6 summary: >–

7 A concept teardown showing how a store, a spreadsheet and a courier can be

8 wired together so stock and status never drift out of sync.

9 problem: >–

10 A growing shop tracks stock in a spreadsheet, takes orders on a storefront,

11 and books couriers by hand. The three never quite agree. Oversells happen,

12 customers ask "where is my order?", and someone reconciles it all every evening.

13 before:

```
14 - Order placed on the storefront
15 - Stock spreadsheet updated manually (when remembered)
16 - Courier booked by copying the address by hand
17 - Tracking number emailed to the customer manually
18 - Evening spent reconciling mismatches
19 intervention: >-
20   A sync layer that treats the order as the single event: it decrements stock,
21   books the courier, writes the tracking number back, and notifies the customer -
22   with a daily exception report for anything that does not match, instead of a
23   nightly manual reconciliation.
24 result:
25   - metric: "0"
26     label: manual re-keying between systems
27     source: Concept build - design target, not a measured client result
28   - metric: Same day
29     label: tracking sent automatically on dispatch
30     source: Concept build - design target, not a measured client result
31   - metric: Exceptions
32     label: surfaced, not hunted for
33     source: Concept build - describes the design, not a metric
34 stack:
35   - Storefront webhooks (Shopify / WooCommerce)
36   - Inventory source of truth
37   - Courier API
38   - Scheduled reconciliation job with alerting
39 humanImpact: >-
40   The evening reconciliation disappears. The owner looks at a short exception
41   list instead of checking three systems against each other by hand.
42 draft: false
43 ---
44
45 ## A teardown, not a client story
```

```
46
47 This is a concept teardown – a public example of how we would approach a
48 familiar problem. It is clearly labeled as such. When you run a real version of
49 this, replace the numbers with measured results and change the label to
50 `client`.
51
52 ## The idea
53
54 Make the order the single source of truth. Everything downstream – stock,
55 courier, customer notification – reacts to it. Reconciliation becomes an
56 exception report, not a nightly chore.
57
```

MD `src/content/work/granite-marketing-n8n.md`

```
1 ---
2 title: Ten-plus n8n workflows, running in sync
3 kind: client
4 client: Granite Marketing
5 sector: Marketing operations
6 order: -2
7 summary: >-
8   A live n8n automation estate of more than ten workflows, tuned for efficiency,
9   extended with new features, and dropped into custom code wherever the
10   no-code path ran out.
11 problem: >-
12   An agency running its operations on n8n had grown past the point where a
13   visual builder alone was enough. Workflows had multiplied, they depended on
14   each other, and the parts that no-code could not express were the parts doing
15   the most important work.
16 before:
17   - More than ten workflows running, each added as a separate need arose
18   - Dependencies between them held in the builder rather than designed
```

```
19   - Efficiency limited by what the visual layer could express
20   - Anything beyond the no-code path blocked until someone could write code
21 intervention: >-
22   Worked across the existing estate rather than replacing it: improved the
23   efficiency of what was already running, added new capability, and wrote
24   custom code where a node could not do the job. The result stayed inside n8n,
25   so the team kept the tooling they already knew.
26 result:
27   - metric: 10+
28     label: workflows working in sync
29     source: >-
30       Stated by the client, Stephen Anindo, in a public LinkedIn recommendation
31       (December 2025).
32   - metric: Custom code
33     label: deployed where no-code could not reach
34     source: >-
35       Stated by the client in the same recommendation: "deployed custom code
36       where necessary – showing that he's more than just a no/low-code
37       developer".
38   - metric: Improved
39     label: efficiency across the existing estate
40     source: >-
41       Stated by the client in the same recommendation. Not independently
42       measured, and no percentage is claimed.
43 stack:
44   - n8n
45   - Custom code nodes
46   - Third-party API integrations
47 humanImpact: >-
48   The team kept working in the tool they already knew, without hitting a ceiling
49   every time a requirement fell outside what the visual builder could express.
50 draft: false
```

51 ---

52

53 ## What this is

54

55 A **paid client engagement** for Granite Marketing, an agency running its

56 operations on n8n.

57

58 Everything on this page is drawn from what the client said publicly. Where a

59 figure appears, the source line states who said it and when. No percentages or

60 time savings are claimed, because none were measured.

61

62 ## In the client's words

63

64 > I worked with Niraj on an n8n project that comprised of over 10 workflows

65 > working in sync. He improved the efficiency, added new features with ease and

66 > deployed custom code where necessary – showing that he's more than just a

67 > no/low-code developer which is very valuable in this day and age. I would not

68 > hesitate to recommend him if you're looking for professional execution and

69 > strong communication!

70 >

71 > – [Stephen Anindo](<https://www.linkedin.com/in/stephenanindo/>), AI Engineer /

72 > Founder at Granite Marketing, December 2025

73

74 ## Why "more than no-code" matters

75

76 Most automation work sold today stops at the edge of the visual builder. That

77 edge arrives sooner than people expect: a rate limit that needs custom backoff,

78 a payload the nodes cannot reshape, a piece of business logic with too many

79 branches to draw.

80

81 At that point there are two options. Work around it – usually by adding more

82 workflows, which is how an estate becomes unmaintainable – or write the code.

83

84 This engagement did the second. The estate stayed in n8n, so the team kept
85 their tooling and their visibility, but the parts that needed real code got
86 real code.

87

88 ## What ten workflows in sync actually means

89

90 The count is not the interesting part. Ten independent automations are easy.
91 Ten that depend on each other is a different problem: one failing quietly can
92 leave the others acting on stale data, and the failure shows up somewhere else
93 entirely, hours later.

94

95 That is the work – sequencing, shared state, and knowing which failures must
96 stop the chain rather than pass through it.

97

MD src/content/work/lead-intake-agency.md

1 ---

2 title: Lead intake for a small B2B agency

3 kind: internal-build

4 sector: Professional services

5 order: 1

6 summary: >–

7 A concept build that turns scattered inbound enquiries into a single, enriched
8 pipeline – so no lead waits on someone remembering to copy it into the CRM.

9 problem: >–

10 Enquiries arrive through a website form, a shared inbox and the occasional
11 LinkedIn message. Someone has to notice each one, judge whether it is worth
12 pursuing, look up the company, and paste it into a CRM. It happens late, or
13 not at all, and there is no record of what was ignored.

14 before:

15 – New enquiry lands in a shared inbox

```
16  - A team member notices it (eventually)
17  - They manually research the company and contact
18  - They decide, informally, whether it is worth a reply
19  - Some enquiries are copied into the CRM; some are lost
20  intervention: >-
21  A single intake system that watches every channel, enriches each enquiry with
22  public company data, scores it against a written definition of a good-fit lead,
23  and creates a CRM record with a suggested next step. A person still approves
24  anything before outreach – the system removes the busywork, not the judgment.
25  result:
26  - metric: One
27    label: pipeline instead of three inboxes
28    source: Internal build – describes the design, not a measured result
29  - metric: < 2 min
30    label: from enquiry to enriched CRM record
31    source: Internal build – design target, not a client result
32  - metric: Nothing
33    label: dropped without a logged reason
34    source: Internal build – describes the design, not a measured result
35  stack:
36  - Webhook intake + shared-inbox polling
37  - Enrichment API
38  - Classification (rules + a scored model call)
39  - CRM (HubSpot / Pipedrive)
40  - Slack for approvals
41  humanImpact: >-
42  Nobody spends their morning triaging an inbox. The team sees a short,
43  prioritized list with context already attached, and decides where to spend
44  their attention.
45  draft: false
46  ---
47
```

48 ## Why this build exists

49

50 This is an **internal concept build**, not a paid client project – and it is
51 labeled that way on purpose. It shows how we think about a common, unglamorous
52 problem: inbound leads that depend on a person remembering to act.

53

54 The numbers below are design targets for this build, not measured client
55 outcomes. When we run this for a real company, the results section will say so
56 and cite where each figure came from.

57

58 ## The system, in plain terms

59

60 Every channel feeds one intake step. Each enquiry is enriched and scored, then a
61 CRM record is created with a recommended next step. A human approves outreach.
62 The result is one legible pipeline instead of three places to check.

63

64 ## What we would watch in production

65

66 A system like this fails quietly rather than loudly, so the interesting work is
67 in the instrumentation:

68

69 – **Enrichment misses.** Public data is incomplete for small companies. Anything
70 the enricher cannot resolve goes to a human queue rather than being scored on
71 missing fields.

72 – **Score drift.** A "good-fit lead" definition written in January is wrong by
73 June. The score is reviewed against closed-won data, not left to run forever.

74 – **Channel silence.** If a shared inbox stops delivering, nothing errors – the
75 pipeline just goes quiet. Each channel gets a heartbeat check so silence is
76 itself an alert.

77


```
1 ---
2 title: WhatsApp enquiries into a CRM, end to end
3 kind: concept
4 sector: Sales operations
5 order: 0
6 summary: >-
7   A concept build for teams whose customers message on WhatsApp but whose
8   pipeline lives in a CRM – so conversations become records without anyone
9   retyping them.
10 problem: >-
11   Customers message on WhatsApp because it is the easiest thing to open. The
12   business runs its pipeline in a CRM. Between the two sits a person with a
13   phone, reading threads and retyping names, numbers and intent into contact
14   records. Threads sit on one salesperson's device, so nobody else can see them.
15   When that person is on leave, the pipeline goes dark.
16 before:
17   - Enquiry arrives as a WhatsApp message on a salesperson's phone
18   - They read it and decide, informally, whether it is a real lead
19   - They retype the name, number and request into the CRM
20   - Follow-ups continue in WhatsApp, invisible to everyone else
21   - The CRM record stops reflecting reality within days
22 intervention: >-
23   A two-way bridge on the WhatsApp Business API. Inbound messages are matched to
24   an existing contact by phone number or create a new one; the thread is written
25   to the CRM as it happens; and a reply sent from the CRM goes back out over
26   WhatsApp. Routing and stage changes follow written rules. A person still
27   answers the customer – the system removes the retyping and the blind spots,
28   not the conversation.
29 result:
30   - metric: One
31     label: thread visible to the whole team, not one phone
```

```
32     source: Concept build – describes the design, not a measured result
33   - metric: Zero
34   label: manual re-entry between chat and CRM
35     source: Concept build – describes the design, not a measured result
36   - metric: Every
37   label: message attached to a contact record automatically
38     source: Concept build – describes the design, not a measured result
39 stack:
40   - WhatsApp Business API (webhook intake + send)
41   - Phone-number identity matching and deduplication
42   - CRM contact/deal sync (HubSpot / Pipedrive / Zoho)
43   - Rules-based routing and stage transitions
44   - Slack notifications for unassigned threads
45 humanImpact: >-
46   A salesperson answers WhatsApp the way they always have. Everyone else can see
47   the conversation, the record is current without anyone maintaining it, and a
48   handover no longer means reading someone else's phone.
49 draft: false
50 ---
51
52 ## Why this build exists
53
54 This is a concept build, not a paid client project, and it is labeled that
55 way deliberately. It exists because this is the single most common request we
56 hear described in the wild: customers have moved to WhatsApp, the CRM has not,
57 and a person is bridging the gap by hand.
58
59 The figures below describe the design. They are not measured client outcomes.
60 When we run this for a real company, the results section will say so and cite
61 where each number came from.
62
63 ## The system, in plain terms
```

64

65 An inbound WhatsApp message hits a webhook. The sender's number is matched
66 against existing CRM contacts – if it resolves, the message is appended to that
67 contact's timeline; if not, a contact is created with whatever the message
68 itself reveals. Routing rules decide who owns the thread and which stage the
69 deal sits in. Replies sent from the CRM go back out over the same API, so the
70 customer experiences one continuous conversation.

71

72 The important design decision is that the CRM, not the phone, becomes the
73 system of record. The phone is an interface.

74

75 ## What we would watch in production

76

77 Chat automation fails in specific, well-understood ways, and most of the
78 engineering effort goes here rather than into the happy path:

79

- 80 – **Identity is messier than it looks.** One person messages from two numbers;
81 one number is shared by a household or an office. Matching on phone number
82 alone will eventually merge two customers into one record. Ambiguous matches
83 go to a human queue instead of being resolved by guessing.
- 84 – **The 24-hour window.** WhatsApp only permits free-form business replies
85 within 24 hours of the customer's last message; after that, only approved
86 templates. A system that ignores this looks fine in testing and silently fails
87 to deliver in production. Template fallbacks are part of the design, not a
88 patch.
- 89 – **Opt-out has to be real.** A customer who says "stop" must stop receiving
90 messages, immediately and permanently, and that state belongs in the CRM
91 rather than in a queue somewhere.
- 92 – **Delivery is not confirmation.** A message can be accepted by the API and
93 never reach the handset. Delivery receipts are reconciled against sent
94 messages, so a silent failure surfaces as an alert rather than as a customer
95 who was never actually contacted.

```
96 - **Never auto-close.** The system suggests a stage change; a person confirms
97   it. An automation that moves deals on its own produces a clean-looking
98   pipeline that nobody trusts.
99
100 ## Where this fits
101
102 If your team is answering customers in one place and reporting on them in
103 another, the gap between those two places is being paid for in someone's
104 attention every day. That gap is what this build closes.
105
```

MD src/content/writing/ai-agent-vs-rule.md

```
1 ---
2 title: When to use an AI agent, and when to use a rule
3 description: >-
4   Most automation problems don't need a model. A practical way to decide when AI
5   earns its place in a workflow – and when a plain rule is the better engineering.
6   pubDate: 2026-02-18
7   tags: ['ai', 'automation', 'process']
8   draft: false
9 ---
10
11 There is a lot of pressure right now to put an AI model into every workflow. Most
12 of the time, you shouldn't. Not because models aren't useful – they are – but
13 because a good system uses the simplest mechanism that reliably does the job.
14
15 Here is the test we apply before reaching for a model.
16
17 ## Use a rule when the decision can be written down
18
19 If you can describe the decision as a set of conditions – *if the order is over
20 £500 and the customer is in the EU, route to the priority queue* – use a rule. It
```

21 is faster, cheaper, deterministic, and you can explain exactly why it did what it
22 did. Rules are boring, and boring is a feature in operations.
23
24 **##** Use a model when the input is messy and the judgment is fuzzy
25
26 Reach for a model when the input is unstructured and the decision needs judgment
27 a rule can't express: classifying the intent of a free-text support message,
28 extracting fields from a PDF that never has the same layout twice, drafting a
29 first-pass reply. These are the tasks where a model genuinely outperforms a
30 brittle pile of conditions.
31
32 **##** Whatever you use, wrap it in something you can trust
33
34 When we do use a model, it doesn't get to act unsupervised. It sits inside:
35
36 - ****Guardrails**** – hard limits on what it can touch.
37 - ****A human checkpoint**** – for anything consequential or irreversible.
38 - ****Evaluation**** – we measure whether it is still making good decisions.
39 - ****Logging**** – every call is recorded, so you can see what happened and why.
40
41 The goal isn't to use AI. The goal is a system that does the work correctly and
42 that you can hand over with confidence. AI is one tool in that toolbox – used
43 where it earns its place, and left out where it doesn't.
44

MD src/content/writing/what-workflow-automation-costs.md

1 ---
2 title: What workflow automation actually costs in 2026
3 description: >–
4 A straight breakdown of what businesses pay to automate a workflow – freelancer,
5 agency and in-house – and how to tell which one your problem needs.
6 pubDate: 2026-08-24

```
7 tags: [pricing, operations, buying]
8 draft: false
9 ---
10
11 Most agencies won't tell you. So here are real numbers, and the reasoning behind
12 them.
13
14 **Short version:** a single automated workflow, built properly and handed over,
15 costs between **$6,000 and **$25,000** in the US market. Below **$6,000 you are
16 usually buying a script. Above **$25,000 you are usually buying a project that
17 should have been split into two.
18
19 ## What you actually pay, by route
20
21 **A freelancer on an hourly rate – $50 to $150/hour.** Cheapest per hour and
22 genuinely fine for a contained job: one integration, one script, one report. The
23 risk is not skill, it is continuity. When the person moves on, so does the only
24 copy of how the thing works.
25
26 **A specialist studio – $6,000 to $25,000 per workflow, fixed price.** You are
27 paying for scoping, documentation and someone accountable when it breaks at 2am.
28 Worth it when the workflow touches more than two systems or when being wrong has
29 a cost.
30
31 **A large consultancy – $50,000 and up.** Appropriate for enterprise compliance
32 and procurement requirements. For a 40-person company automating lead intake, it
33 is the wrong shape of engagement.
34
35 **In-house – $8,000 to $15,000 of loaded salary cost** for a mid-level engineer
36 spending three to four weeks on it. This is the option people forget to price.
37 It is often the right answer, and the real question is whether that engineer has
38 four weeks that are not already spoken for.
```

39

40 **##** The number nobody quotes: what it costs to keep

41

42 Every automated workflow carries roughly ****10 to 20%** of its build cost per year******

43 in maintenance. APIs change, credentials expire, a vendor deprecates a webhook.

44

45 This is the line that turns a good automation into a bad one. A \$12,000 system

46 that saves \$30,000 a year is excellent. The same system, unmaintained, silently

47 failing for two months before anyone notices, is worse than the manual process

48 it replaced – because at least the manual process failed loudly.

49

50 Budget for it, or do not build it.

51

52 **##** How to tell if a workflow is worth automating

53

54 Rough arithmetic, and it is usually enough:

55

56 – ****Hours per month × loaded hourly cost × 12**** = annual cost of doing it by hand.

57 – If that number is under \$5,000, automation probably will not pay back. Write a

58 checklist instead.

59 – If it is over \$20,000, the question is not whether to automate but which part

60 to automate first.

61 – ****Add the error cost.**** A missed lead or a wrong invoice usually costs more

62 than the time saved, and it is the part people leave out of the math.

63

64 A workflow taking 8 hours a month at a \$60 loaded rate costs about \$5,760 a year.

65 A \$10,000 build pays back in under two years – acceptable, not exciting. The same

66 workflow at 20 hours a month pays back in under eight months, and that is a clear

67 yes.

68

69 **##** Why fixed price beats hourly for this work

70

71 Hourly rates put the risk of a bad estimate on you. If the integration turns out
72 to be harder than it looked, your invoice grows.

73

74 Fixed price puts that risk on whoever wrote the estimate – which is the correct
75 place for it, because they are the one who understood the problem well enough to
76 quote it. The trade is that scoping has to happen first and properly, which is
77 why serious studios charge for the scoping phase rather than giving it away.

78

79 ## What should be in the price

80

81 Before you compare quotes, check they include the same things:

82

83 - **Monitoring and alerting.** Otherwise you find out it broke from a customer.

84 - **Retries and error handling.** Every integration fails sometimes; the question
85 is whether it fails safely.

86 - **Documentation.** A diagram and a runbook, so a different engineer can pick it
87 up.

88 - **Ownership.** Code, credentials and infrastructure in your name – not in an
89 agency account you rent access to.

90

91 A quote missing these is not cheaper. It has moved the cost somewhere you cannot
92 see it yet.

93

94 ## What we charge

95

96 We publish ours: **\$2,500** for a two-week Automation Map that scopes the work,
97 credited against the build. **\$8,000 to \$18,000** for a first system, fixed
98 scope. **From \$6,000 a month** for ongoing partnerships.

99

100 If the arithmetic above says your workflow is not worth automating yet, we would
101 rather tell you that than sell you a build.

MD src/content/writing/zapier-make-n8n-or-custom-code.md

```
1 ---
2 title: Zapier, Make, n8n or custom code – how to choose
3 description: >–
4   A practical comparison of the four ways to build an automation, and the
5   specific signals that tell you when to move from one to the next.
6 pubDate: 2026-08-17
7 tags: [tools, integrations, engineering]
8 draft: false
9 ---
10
11 There is no best option here. There is a right option for a given workflow, and
12 a predictable point at which it stops being right.
13
14 Short version: Zapier for simple, low-volume, business-owned automations.
15 Make for branching logic and higher volume. n8n when you need self-hosting or
16 your run count makes per-task pricing painful. Custom code when reliability
17 matters more than assembly speed.
18
19 ## Zapier
20
21 Use it when the workflow is a handful of steps, runs hundreds – not hundreds
22 of thousands – of times a month, and a non-engineer needs to own it.
23
24 Zapier's real product is its connector library. If your five tools all have
25 first-class Zapier integrations, you can have something working in an afternoon,
26 and that speed is genuinely valuable.
27
28 Move on when you find yourself chaining Zaps together to fake branching
29 logic, when the per-task cost starts appearing in budget conversations, or when
```

30 you need to know **why** something failed three weeks ago and the run history
31 cannot tell you.

32

33 **## Make**

34

35 ***Use it when*** the logic branches, loops, or transforms data in ways Zapier
36 makes awkward, and you still want a visual builder.

37

38 Make handles iteration and error routing far better, and its pricing tolerates
39 higher volume. The visual canvas is also a genuine documentation artifact – you
40 can show it to someone and they will understand the flow.

41

42 ***Move on when*** the scenario has grown to fifty modules and nobody wants to
43 touch it. A visual builder that has outgrown one screen has become harder to
44 maintain than the code it replaced, not easier.

45

46 **## n8n**

47

48 ***Use it when*** you need to self-host for data residency or compliance reasons,
49 when your execution volume makes per-task pricing absurd, or when you want to
50 drop into JavaScript for one awkward step without abandoning the visual tool.

51

52 n8n is the pragmatic middle. Source-available, self-hostable, and it lets an
53 engineer write real code inside a node instead of building a monument out of
54 string-manipulation blocks.

55

56 ***Move on when*** you are writing more code inside nodes than you are configuring
57 them. At that point the visual layer is overhead, not help.

58

59 **## Custom code**

60

61 ***Use it when*** the workflow is core to how the business makes money, when

62 failure has real consequences, or when you need testing, version control and
63 proper observability.

64

65 This is not a purity argument. It is that a payment reconciliation running
66 through a visual builder cannot be unit tested, cannot be code reviewed, and
67 cannot be rolled back cleanly. Those absences are affordable for a Slack
68 notification and unaffordable for money movement.

69

70 ****The honest cost:**** custom code needs someone who can maintain it. If nobody at
71 your company can, a platform your team can actually operate is the better
72 engineering decision, even though it is the worse engineering.

73

74 **##** The signals that you have outgrown your tool

75

76 Independent of which tool you are on:

77

78 - ****You cannot answer "did it run?"**** without opening the builder and squinting
79 at run history.

80 - ****Failures are silent.**** You learn about them from a customer.

81 - ****One person understands it.**** The automation has become a dependency on an
82 individual, which is the exact problem automation was meant to remove.

83 - ****The workaround has a workaround.**** Two Zaps triggering a third that writes to
84 a sheet a fourth reads is a system asking to be rewritten.

85 - ****Per-task cost is a line item.**** At volume, platform pricing crosses the cost
86 of the engineering time it saved.

87

88 **##** What we actually do

89

90 We use platforms when they genuinely fit – there is no credit for building a
91 custom integration where a connector would have held up fine. We write Python and
92 FastAPI services when reliability, testing or volume demands it.

93

```
94 Most real systems end up mixed: a platform handling the well-supported edges, a
95 service handling the part that matters, and monitoring across both so a failure
96 anywhere is visible in one place.
97
98 The question worth asking is not "which tool is best." It is "what happens when
99 this breaks, and who finds out?"
100
```

TS src/data/site.ts

```
1 export const site = {
2   name: 'Flowzora',
3   // Short descriptor used in the logo lockup and footer.
4   // Keyword-bearing on purpose: "workflow automation" is the term buyers search.
5   tagline: 'Workflow automation studio',
6   domain: 'https://flowzora.com',
7   email: 'hello@flowzora.com',
8   // Clients are worldwide. This states what can honestly be committed to
9   // rather than naming a region's business hours, which would be a promise
10  // broken the first time a client in another time zone held us to it.
11  location: 'Remote · overlapping hours in most time zones',
12  parent: 'oneProductLab',
13  parentUrl: 'https://www.linkedin.com/company/oneproductlab',
14  linkedin: 'https://www.linkedin.com/company/oneproductlab',
15  /*
16   Dedicated Calendly event type for this site – not the parent company's
17   general link, so inbound bookings can be attributed and measured.
18   Empty until created; the booking button falls back to the contact form.
19  */
20  calendly: '',
21  // The work is remote and the clients are global, so the schema says so.
22  // A named country list here quietly tells search engines – and anyone
23  // outside it – that we don't serve them.
```

```
24   areaServed: 'worldwide',
25   locale: 'en',
26 };
27
28 /**
29  * The single named human behind the studio.
30  * E-E-A-T and generative-engine citation both depend on a real, verifiable person –
31  * every claim here must be independently checkable on the linked profile.
32  */
33 export const founder = {
34   name: 'Niraj Kumar',
35   role: 'Founder & Lead Engineer',
36   linkedin: 'https://www.linkedin.com/in/modestai/',
37   education: 'B.Tech, NIT Kurukshetra',
38   /*
39    Stable, unhashed URL for the founder portrait, used by the `Person` schema
40    and by anything else that needs a permanent address.
41
42    On-page rendering uses `src/assets/images/niraj.jpg` through Astro's `<Image>`
43    component instead, which emits hashed, optimized WebP. Those filenames change
44    whenever the source does, which is exactly what you want for a browser cache
45    and exactly what you do not want in structured data a crawler may have
46    already recorded. Hence the two copies.
47    */
48   photo: {
49     src: '/niraj.jpg',
50     width: 560,
51     height: 700,
52     alt: 'Niraj Kumar, founder of Flowzora',
53   },
54   bio: 'Niraj builds backend and AI systems for a living – FastAPI services, async data pipelines, and
production LLM applications. Before starting Flowzora he built a financial analytics platform covering
```

10,000+ stock symbols, and worked as a machine learning engineer at C-DAC on adversarial ML, formal verification and model monitoring.',

```
55 // Sectors, not employer names used as borrowed credentials.
56 sectors: ['Fintech and financial analytics', 'Government ML research', 'Consumer AI products'],
57 stack: ['Python', 'FastAPI', 'PostgreSQL', 'Redis', 'Kafka', 'Celery', 'Docker', 'AWS & GCP'],
58 };
59
60 /**
61  * Client testimonials.
62  *
63  * These are public LinkedIn recommendations, quoted verbatim and linked to the
64  * profile that wrote them. That matters more than the words: an anonymous
65  * "CEO, SaaS company" quote is worth nothing because it cannot be checked,
66  * whereas a named person with a date and a live profile can be. Every quote
67  * here is verifiable by a prospect in one click.
68  *
69  * `relationship` is required and honest. Stephen and Blake were paying
70  * clients; Akhil was a colleague, and saying so is what keeps the other two
71  * credible. Trimming that distinction to make three "client" quotes would
72  * poison the whole section.
73  *
74  * Quotes are lightly trimmed for length only – never reworded, and never cut
75  * in a way that changes what was said.
76  */
77 export const testimonials = [
78   {
79     quote:
80       'I worked with Niraj on an n8n project that comprised of over 10 workflows working in sync. He improved the efficiency, added new features with ease and deployed custom code where necessary – showing that he's more than just a no/low-code developer which is very valuable in this day and age. I would not hesitate to recommend him if you're looking for professional execution and strong communication!',
81     name: 'Stephen Anindo',
82     role: 'AI Engineer / Founder',
83     company: 'Granite Marketing',
```

```
84     linkedin: 'https://www.linkedin.com/in/stephenanindo/',
85     // The line a prospect scanning at speed should still catch.
86     pullQuote: 'Over 10 workflows working in sync.',
87 },
88 {
89     quote:
90         'Hired Niraj to build out a website for me at automatedbureaucracy.com and he delivered a great
full stack application that provides a solid foundation for my automation agency.',
91     name: 'Blake DeHaas',
92     role: 'Graduate Operations Software Engineer',
93     company: 'Laboratory for Atmospheric and Space Physics',
94     linkedin: 'https://www.linkedin.com/in/blakedehaas/',
95     pullQuote: 'A solid foundation for my automation agency.',
96 },
97 {
98     quote:
99         'One of the most versatile professionals I have come across. His eagerness to learn new things
is truly inspiring – whether it’s picking up a new skill, exploring a different approach, or taking on
a challenge outside his comfort zone. His incredible ability to take even the harshest criticism in
stride sets him apart even more.',
100    name: 'Akhil Rajeev P',
101    role: 'AI Researcher, NLP & Generative AI',
102    company: 'C-DAC',
103    // Deliberately not "Client". He worked alongside Niraj.
104    relationship: 'Colleague at C-DAC',
105    date: 'March 2025',
106    linkedin: 'https://www.linkedin.com/in/akhil-rajeev-p-42bb23235/',
107    pullQuote: 'One of the most versatile professionals I have come across.',
108 },
109 ];
110
111 /**
112  * Verifiable engineering track record.
113  *
```

```
114 * The studio is new; the engineering is not. These are measured outcomes from
115 * production systems the founder built before Flowzora, and they are the
116 * strongest evidence available until a paid engagement replaces them. Stated as
117 * prior work rather than agency results – the distinction is the whole point.
118 *
119 * Written for an operations buyer, not an engineer. The underlying facts are
120 * unchanged and still verifiable; what changed is the framing. "70% lower API
121 * latency" is evidence for a job nobody here is hiring for – the reader's
122 * problem is a person retyping things, so each figure now leads with what it
123 * proves about systems that keep running, and keeps the technical detail
124 * underneath for anyone who wants it.
125 */
126 export const credentials = [
127   {
128     metric: '30K',
129     label: 'visits in 3 days, no downtime',
130     detail:
131       'Backend infrastructure for an AI product that scaled hard at launch and stayed up through it.',
132   },
133   {
134     metric: '10,000+',
135     label: 'records processed daily, unattended',
136     detail:
137       'Ingestion pipelines and a scoring engine running across a full market universe, without a
138       person minding them.',
139   },
140   {
141     metric: '70%',
142     label: 'faster, on the same infrastructure',
143     detail:
144       'Caching, query optimization and async execution on a production analytics platform – no extra
145       spend.',
146   },
147 ]
```



```
145   {
146     metric: '60%',
147     label: 'lower database load, no new spend',
148     detail: 'Access-pattern redesign rather than a bigger server.',
149   },
150 ];
151
152 /**
153  * The founding-client offer.
154  *
155  * Framed as early-stage capacity, not as a confession of being new. An earlier
156  * version led with "We're new" – which, sitting directly below three verified
157  * client testimonials, argued against its own evidence. The scarcity is real
158  * either way: a solo studio has a finite calendar, and that is the honest
159  * reason these terms expire.
160  */
161 export const foundingOffer = {
162   eyebrow: 'Founding clients',
163   headline: 'Early enough to get our full attention.',
164   body: 'Flowzora is a young studio built on years of production engineering. While the calendar is open, the first few clients get terms we won't be able to offer once it fills.',
165   terms: [
166     {
167       title: 'You work with the founder',
168       detail: 'Not an account manager. The person scoping the work writes the code.',
169     },
170     {
171       title: 'Founding-client pricing',
172       detail: 'Below where these engagements will sit once there's a waiting list.',
173     },
174     {
175       title: 'Your build becomes the case study',
```

```
176     detail: 'Written up in full, with your approval, and credited if you want it.',
177   },
178 ],
179   caveat:
180     'In exchange we ask for honest feedback and, if the work earns it, a reference.',
181   };
182
183   /**
184    * Qualification. A buyer's first question is "are these people for me?", and
185    * leaving it unanswered costs more inquiries than a narrow answer would.
186    */
187   export const fitFor = {
188     headline: 'Who this is for',
189     /*
190      Fit is described by symptoms, not by headcount or geography.
191
192      An earlier version gated on "US teams of 20–200 people", which excluded
193      every client outside one country and every twelve-person company with a
194      real problem – while doing no qualifying work that the signals below
195      don't already do better. A ten-person agency losing a day a week to
196      re-keying is a better fit than a 150-person company with none of these
197      symptoms.
198      */
199     signals: [
200       'You run a stack of tools that don't talk to each other',
201       'Someone senior spends hours a week re-entering the same data',
202       'You've outgrown spreadsheets but don't want another rigid platform',
203     ],
204     notFor: [
205       'You need a single Zapier zap – a freelancer is cheaper',
206       'You want a team of twenty on site – we're deliberately small',
207     ],
```

```
208   stacks: [
209     'HubSpot',
210     'Salesforce',
211     'Shopify',
212     'QuickBooks',
213     'Slack',
214     'Notion',
215     'Zendesk',
216     'Airtable',
217   ],
218 };
219
220 export const nav = [
221   { label: 'Services', href: '/services/' },
222   { label: 'Work', href: '/work/' },
223   { label: 'Pricing', href: '/pricing/' },
224   { label: 'Approach', href: '/approach/' },
225   { label: 'About', href: '/about/' },
226   { label: 'Writing', href: '/writing/' },
227 ];
228
229 export const services = [
230   {
231     slug: 'revenue-operations',
232     // Short form for scanning contexts; `summary` is the fuller version.
233     brief: "Leads captured, enriched and routed without re-typing.",
234     index: '01',
235     title: 'Sales & revenue operations',
236     // `seoTitle` targets the phrase buyers actually search; `title` stays in our voice.
237     seoTitle: 'CRM automation & revenue operations services',
238     keyword: 'crm automation services',
239     summary:
```

```
240     'Lead capture, routing, enrichment and CRM hygiene that stops deals stalling between tools.',
241     detail:
242     'We connect the places leads arrive to the systems your team actually works in – so nothing is
re-keyed, nothing is dropped, and every record is where a rep expects it.',
243     answer:
244     'Revenue operations automation connects your lead sources, CRM and sales tools so records are
created, enriched and routed without anyone retyping them. It typically removes the delay between a
lead arriving and a rep seeing it, and keeps pipeline data accurate enough to forecast from.',
245     builds: [
246     'Unified lead capture across forms, ads and inbound email',
247     'Routing and assignment rules that match your team structure',
248     'Enrichment and deduplication before records reach the CRM',
249     'Pipeline and forecast roll-ups your leadership can trust',
250     ],
251     signals: [
252     'Leads sit unworked because nobody was notified',
253     'Reps retype the same details into two or three tools',
254     'Your CRM and your spreadsheet disagree about the pipeline',
255     ],
256     faqs: [
257     {
258         q: 'Can you automate lead routing in our existing CRM?',
259         a: 'Yes. We build routing on top of the CRM you already run – HubSpot, Salesforce, Pipedrive
or otherwise – rather than migrating you to a new one. Rules follow your real team structure,
including territories, round-robin and specialist handoffs.',
260     },
261     {
262         q: 'How do you stop duplicate records being created?',
263         a: 'We deduplicate and enrich records before they ever reach the CRM, matching on email and
domain first and falling back to fuzzy company matching. Anything ambiguous is held for a human
decision rather than guessed at.',
264     },
265     ],
266     },
267     {
```

```
268     slug: 'marketing-lifecycle',
269     // Short form for scanning contexts; `summary` is the fuller version.
270     brief: "Campaigns and reporting that run without a babysitter.",
271     index: '02',
272     title: 'Marketing & lifecycle automation',
273     seoTitle: 'Marketing automation consultant & lifecycle workflows',
274     keyword: 'marketing automation consultant',
275     summary:
276         'Campaign, content and lifecycle workflows that run on their own without a person babysitting them.',
277     detail:
278         'The repetitive parts of marketing operations – segmentation, hand-offs, reporting – turned into systems that run to a schedule and surface exceptions instead of demanding attention.',
279     answer:
280         'Marketing lifecycle automation turns segmentation, campaign hand-offs and reporting into scheduled systems that surface exceptions rather than demanding daily attention. The goal is a marketing operation that keeps running correctly on the weeks nobody has time to babysit it.',
281     builds: [
282         'Lifecycle and nurture flows wired to real product signals',
283         'Content and campaign hand-offs between tools',
284         'Cross-channel reporting assembled automatically',
285         'List hygiene and consent handling that stays compliant',
286     ],
287     signals: [
288         'Reporting is rebuilt by hand every month',
289         'Campaign hand-offs depend on someone remembering',
290         'Segments drift out of date and nobody notices',
291     ],
292     faqs: [
293         {
294             q: 'Do you replace our marketing platform?',
295             a: 'No. We automate around the platform you already pay for, connecting it to product data and the rest of your stack. Replacing a marketing platform is expensive and rarely the actual problem.',
296         },
```

```
297     {
298         q: 'How do you handle consent and list hygiene?',
299         a: 'Consent state is stored in one system of record and synced outward, so an unsubscribe
anywhere is honored everywhere. Suppression and hygiene rules run on a schedule rather than being
cleaned up manually before each send.',
300     },
301 ],
302 },
303 {
304     slug: 'internal-operations',
305     // Short form for scanning contexts; `summary` is the fuller version.
306     brief: "Onboarding, approvals and reconciliation, made repeatable.",
307     index: '03',
308     title: 'Internal operations & back-office',
309     seoTitle: 'Business process automation services for back-office work',
310     keyword: 'business process automation services',
311     summary:
312         'Onboarding, approvals, finance and admin workflows that currently live in someone's head.',
313     detail:
314         'The unglamorous work that keeps a company running: approvals, provisioning, reconciliation. We
make it repeatable, auditable and fast – with a human in the loop where it matters.',
315     answer:
316         'Business process automation takes back-office work like onboarding, approvals and
reconciliation out of people's heads and turns it into repeatable, auditable systems. Consequential
steps keep a human approver; everything around that approval stops being manual.',
317     builds: [
318         'Employee and customer onboarding sequences',
319         'Approval chains with clear ownership and audit trails',
320         'Finance reconciliation and reporting automation',
321         'Internal tools for tasks no off-the-shelf product covers',
322     ],
323     signals: [
324         'Onboarding is a checklist someone works through by hand',
325         'Approvals stall because nobody knows whose turn it is',
```

```
326     'You cannot reconstruct who approved what, or when',
327 ],
328 faqs: [
329     {
330         q: 'Will automation remove human approval from our process?',
331         a: 'No – we keep a person on any step with real consequences, such as spending money or
granting access. Automation removes the chasing, the copying and the waiting around that surrounds the
approval, not the judgment itself.',
332     },
333     {
334         q: 'Can you build an internal tool if no product does what we need?',
335         a: 'Yes. Where an off-the-shelf product does not fit, we build a small internal tool with the
same reliability standards as the rest of the system, and hand over the code and hosting to you.',
336     },
337 ],
338 },
339 {
340     slug: 'customer-support',
341     // Short form for scanning contexts; `summary` is the fuller version.
342     brief: "Tickets triaged and drafted before an agent opens them.",
343     index: '04',
344     title: 'Customer support automation',
345     seoTitle: 'Support ticket automation & triage',
346     keyword: 'support ticket automation',
347     summary:
348         'Triage, classification and response drafting that shortens resolution without hiding humans.',
349     detail:
350         'We route and classify incoming requests, draft responses for review, and connect support to the
systems that hold the answers – so your team spends time on the hard cases.',
351     answer:
352         'Support automation classifies and routes tickets as they arrive and drafts responses from your
own knowledge base for an agent to review. It shortens time to first response without putting a bot
between your customers and your team.',
353     builds: [
354         'Ticket triage and classification on arrival',
```

```
355     'Draft responses assembled from your own knowledge base',
356     'Escalation rules with human approval on consequential actions',
357     'Support metrics connected back to product and ops',
358 ],
359 signals: [
360     'Tickets wait hours before anyone categorizes them',
361     'Agents rewrite the same answer several times a day',
362     'Nobody can see which issues are actually driving volume',
363 ],
364 faqs: [
365     {
366         q: 'Will customers end up talking to a bot?',
367         a: 'Only if you want them to. Our default is agent-assist: the system classifies, routes and
drafts, and a person approves before anything reaches the customer. Hiding humans is usually what
damages support quality.',
368     },
369     {
370         q: 'How accurate is automated ticket classification?',
371         a: 'Accuracy depends on your ticket mix, so we measure it against a labeled sample of your own
history before trusting it. Low-confidence tickets are routed to a human queue rather than being
misfiled silently.',
372     },
373 ],
374 },
375 {
376     slug: 'integrations',
377     // Short form for scanning contexts; `summary` is the fuller version.
378     brief: "Data moves once, correctly, and you see when it doesn't.",
379     index: '05',
380     title: 'Integrations & data plumbing',
381     seoTitle: 'Systems integration & API integration services',
382     keyword: 'systems integration consultant',
383     summary:
384         'The connections between systems that turn a stack of tools into one operation.',
```



```
385     detail:
386         'Most automation problems are really integration problems. We build reliable, observable
connections between your systems so data moves once, correctly, and you can see when it doesn't.',
387     answer:
388         'Systems integration connects the tools you already run so data moves once, correctly, and you
can see when it fails. Most problems described as automation problems are really integration problems:
the same information living in three places and quietly disagreeing.',
389     builds: [
390         'Two-way syncs between CRM, finance, support and data tools',
391         'API integrations for systems without off-the-shelf connectors',
392         'Reliable job handling with retries and alerting',
393         'A single source of truth your teams can agree on',
394     ],
395     signals: [
396         'The same record exists in three tools with three values',
397         'A sync broke weeks ago and nobody found out',
398         'A tool you depend on has no ready-made connector',
399     ],
400     faqs: [
401         {
402             q: 'What if our software has no ready-made integration?',
403             a: 'We build directly against its API, or against its database or file exports where no API
exists. This is the common case for older or industry-specific software, and it is usually
straightforward.',
404         },
405         {
406             q: 'What happens when an integration fails?',
407             a: 'Every job we ship has retries, dead-letter handling and alerting, so failures surface
immediately instead of being discovered weeks later. You get visibility into what ran, what did not,
and why.',
408         },
409     ],
410 },
411 {
412     slug: 'ai-agents',
```

```
413 // Short form for scanning contexts; `summary` is the fuller version.
414 brief: "Models only where a rule genuinely can't do the job.",
415 index: '06',
416 title: 'AI agents & assisted workflows',
417 seoTitle: 'AI automation agency & AI agent development',
418 keyword: 'ai automation agency',
419 summary:
420     'AI used where it genuinely earns its place – with rules, review and traceability around it.',
421 detail:
422     'We reach for an AI model when a task needs judgment a rule can't express – classification,
423     extraction, drafting – and we wrap it in guardrails, evaluation and human review so you can trust the
424     output.',
425 answer:
426     'An AI agent earns its place only when a task needs judgment a rule cannot express –
427     classification, extraction or drafting. Every model call we ship is wrapped in guardrails, evaluation
428     against your own data, logging and human review, so the output is traceable rather than trusted
429     blindly.',
430 builds: [
431     'Classification and extraction where rules fall short',
432     'Drafting assistants that keep a person in control',
433     'Guardrails, evaluation and logging around every model call',
434     'A clear boundary between what the AI decides and what it doesn't',
435 ],
436 signals: [
437     'Someone reads every incoming document and sorts it by hand',
438     'Rules cannot capture the judgment the task really needs',
439     'You tried an AI tool and could not tell whether to trust it',
440 ],
441 faqs: [
442     {
443         q: 'When should we use an AI agent instead of a rule?',
444         a: 'Use a rule whenever the logic can be written down and is stable, because rules are
445         cheaper, faster and fully predictable. Reach for a model only when the task genuinely needs judgment,
446         such as reading unstructured text or classifying something a person would have to interpret.',
447     },
448 ],
```

```
441     {
442         q: 'How do you stop an AI system making things up?',
443         a: 'We constrain models to your own data, validate every output against a schema before it is
used, and route low-confidence results to a person. Anything with real consequences requires human
approval before it executes.',
444     },
445 ],
446 },
447 ];
448
449 // Engagement steps – the process artifact.
450 // `short` is used where the reader is scanning; `blurb` where they have
451 // committed to reading. Same claim, two densities.
452 //
453 // Every step here corresponds to something already promised elsewhere on the
454 // site: "Scope" is the fixed-price commitment from the pricing section, and
455 // "Keep it running" is the Operations Partner tier. Steps invented to pad the
456 // list out would be the kind of process theatre this studio sells against.
457 export const approach = [
458     {
459         step: 'Map',
460         short: 'We sit with the people doing the work and diagram what actually happens today.',
461         blurb:
462             'We sit with the people doing the work and map what actually happens today – every hand-off,
tool and workaround. You get a clear diagram of the current process and where it leaks time.',
463     },
464     {
465         step: 'Scope',
466         short: 'A fixed price, in writing, before anything is built. Overruns are ours.',
467         blurb:
468             'Before a line of code exists, you get the build plan and a fixed price in writing. Scope is
agreed up front and the number does not move – if the work runs long, that is ours to absorb, not
yours to fund.',
469     },
```

```
470  {
471      step: 'Build',
472      short: 'Working automation in weeks, not a reveal at the end. Documented as it ships.',
473      blurb:
474          'We build the system in short, visible increments. You see working automation early and often,
not a big reveal at the end. Everything is documented as it ships.',
475  },
476  {
477      step: 'Prove',
478      short: 'Run against real work, side by side with the manual process, before you rely on it.',
479      blurb:
480          'New automation runs alongside the existing manual process on real data, so you can compare the
two before trusting it. Nothing is switched over on the strength of a demo.',
481  },
482  {
483      step: 'Hand over',
484      short: 'Runbooks, diagrams and a walkthrough. It keeps running after we're gone.',
485      blurb:
486          'We leave you with systems you own and understand: runbooks, diagrams and a walkthrough. The
automation keeps running after we're gone – that's the point.',
487  },
488  {
489      step: 'Keep it running',
490      short: 'Optional. Monitoring and changes as your business shifts – never a lock-in.',
491      blurb:
492          'Automation breaks quietly when the business around it changes. Some clients keep us on to watch
it and adapt it; others take it in-house from day one. Both are fine – you own the system either
way.',
493  },
494  ];
495
496  /**
497   * Published pricing. This is the highest-intent page on the site: "how much does
498   * workflow automation cost" is the query buyers actually type, and stating real
```

```
499  * numbers is what makes us quotable by answer and generative engines.
500  */
501  export const pricing = [
502    {
503      slug: 'automation-map',
504      name: 'Automation Map',
505      price: '$2,500',
506      priceValue: 2500,
507      unit: 'flat',
508      duration: '2 weeks',
509      summary:
510        'We map one workflow end to end and hand you the diagrams and a build plan. The fee is credited
        if you go ahead with the build.',
511      includes: [
512        'Interviews with the people doing the work today',
513        'A diagram of the current process and where it leaks time',
514        'A costed build plan with a recommended sequence',
515        'An honest call on whether it is worth automating yet',
516      ],
517    },
518    {
519      slug: 'first-system',
520      name: 'First System',
521      price: '$8,000 – $18,000',
522      priceValue: 8000,
523      unit: 'fixed scope',
524      duration: '3–5 weeks',
525      summary:
526        'One workflow, built, documented and handed over. Fixed scope and fixed price, so the number
        does not move while we build.',
527      includes: [
528        'The system built in visible weekly increments',
529        'Monitoring, retries and alerting from day one',
```

```

530     'Runbooks and diagrams written as we ship',
531     'Code and accounts in your name, not ours',
532 ],
533 },
534 {
535     slug: 'operations-partner',
536     name: 'Operations Partner',
537     price: 'From $6,000',
538     priceValue: 6000,
539     unit: 'per month',
540     duration: 'Ongoing',
541     summary:
542         'A standing engagement for teams automating more than one thing. We keep building, keep it
        running, and stay accountable for uptime.',
543     includes: [
544         'A rolling backlog of systems, prioritized with you',
545         'Maintenance and monitoring of everything we have built',
546         'A named engineer who knows your operation',
547         'Cancel with 30 days notice – no lock-in',
548     ],
549 },
550 ];
551
552 /**
553  * Answer-engine surface. Each answer is written to stand alone if it is lifted
554  * out of the page: question in the heading, complete answer in the first sentence.
555  */
556 export const faqs = [
557     {
558         q: 'How much does workflow automation cost?',
559         a: 'Most first projects land between $8,000 and $18,000 for a single workflow built, documented
        and handed over. A two-week Automation Map that scopes the work costs $2,500 and is credited against
        the build. Ongoing partnerships start at $6,000 per month.',

```

```

560   },
561   {
562     q: 'How long does it take to automate a workflow?',
563     a: 'A single workflow typically takes three to five weeks from kickoff to handover, including the
mapping phase. You see working automation in the first two weeks rather than at the end.',
564   },
565   {
566     q: 'Do we own the automation you build?',
567     a: 'Yes. Code, accounts and credentials are in your name from the start, and you get runbooks and
diagrams written as we ship. The systems keep running if you never speak to us again.',
568   },
569   {
570     q: 'Which tools do you build with?',
571     a: 'We build with the tools you already run, connected with Python and FastAPI services where an
off-the-shelf connector will not hold up. We use platforms like n8n, Make or Zapier when they
genuinely fit, and custom code when reliability matters more than speed of assembly.',
572   },
573   {
574     q: 'When should a business use an AI agent instead of a rule?',
575     a: 'Use a rule when the logic can be written down and will not change; use a model only when the
task needs judgment a rule cannot express, such as classification, extraction or drafting. Every model
call we ship is wrapped in guardrails, logging and human review.',
576   },
577   {
578     q: 'Where are your clients based?',
579     a: 'Everywhere. The work is remote and asynchronous by nature – we map workflows over a call, then
build and hand over. We schedule calls to your time zone and keep overlapping hours with most of them.
Pricing is quoted in USD.',
580   },
581 ];
582

```

TS `src/env.d.ts`

```

1  /// <reference path="../../astro/types.d.ts" />
2

```

```
1 ---
2 import '../styles/global.css';
3 import Header from '../components/Header.astro';
4 import Footer from '../components/Footer.astro';
5 import Analytics from '../components/Analytics.astro';
6 import { ClientRouter } from 'astro:transitions';
7 import { site, founder } from '../data/site';
8
9 interface Props {
10   title?: string;
11   description?: string;
12   /** Path-only canonical, e.g. "/work/". Defaults to current path. */
13   path?: string;
14   ogType?: string;
15   /** Which generated share card to use, e.g. "work/lead-intake-agency". */
16   ogRoute?: string;
17   /** Extra JSON-LD nodes merged into the page graph (FAQ, Service, Article...). */
18   schema?: Record<string, unknown>[];
19   /** Keep a page out of the index without removing it from the site. */
20   noindex?: boolean;
21   /** Set on pages that embed a cookie-setting third party (e.g. a scheduler). */
22   needsConsent?: boolean;
23 }
24
25 const {
26   title,
27   description = 'Flowzora is a workflow automation studio. We connect the tools you already use,
  remove the manual steps between them, and hand over systems your team owns.',
28   path,
29   ogType = 'website',
30   ogRoute = 'default',
```



```
31  schema = [],
32  noindex = false,
33  needsConsent = false,
34 } = Astro.props;
35
36 const fullTitle = title ? `${title} - ${site.name}` : `${site.name} - ${site.tagline}`;
37
38 // Canonicals must match the URLs that actually serve. The build emits directory
39 // output, so every path ends in a slash – normalize rather than trusting pathname.
40 const rawPath = path ?? Astro.url.pathname;
41 const normalizedPath = rawPath.endsWith('/') ? rawPath : `${rawPath}/`;
42 const canonical = new URL(normalizedPath, site.domain).href;
43 const ogImage = new URL(`/og/${ogRoute}.png`, site.domain).href;
44
45 const orgId = `${site.domain}/#organization`;
46 const founderId = `${site.domain}/#founder`;
47
48 // One connected graph rather than several orphaned blobs: search and generative
49 // engines resolve the studio, the person and the site as a single entity.
50 const graph = [
51   {
52     '@type': ['Organization', 'ProfessionalService'],
53     '@id': orgId,
54     name: site.name,
55     description,
56     url: site.domain,
57     email: site.email,
58     slogan: site.tagline,
59     parentOrganization: {
60       '@type': 'Organization',
61       name: site.parent,
62       url: site.parentUrl,
```

```
63     },
64     founder: { '@id': founderId },
65     employee: { '@id': founderId },
66     sameAs: [site.linkedin, founder.linkedin],
67     // schema.org accepts a plain string here. Naming specific countries would
68     // tell search engines we don't serve anywhere else.
69     areaServed: site.areaServed,
70     knowsAbout: [
71         'Workflow automation',
72         'Business process automation',
73         'Systems integration',
74         'CRM automation',
75         'AI agents',
76         'Revenue operations',
77     ],
78 },
79 {
80     '@type': 'Person',
81     '@id': founderId,
82     name: founder.name,
83     jobTitle: founder.role,
84     description: founder.bio,
85     url: `${site.domain}/about/`,
86     // A portrait on the Person node is a real entity-recognition signal: it
87     // gives search and generative engines something to bind the name to.
88     image: new URL(founder.photo.src, site.domain).href,
89     sameAs: [founder.linkedin],
90     worksFor: { '@id': orgId },
91     alumniOf: {
92         '@type': 'CollegeOrUniversity',
93         name: 'National Institute of Technology, Kurukshetra',
94     },
```

```
95     knowsAbout: founder.stack,
96   },
97   {
98     '@type': 'WebSite',
99     '@id': `${site.domain}/#website`,
100    url: site.domain,
101    name: site.name,
102    publisher: { '@id': orgId },
103    inLanguage: site.locale,
104  },
105  ...schema,
106 ];
107
108 const jsonLd = { '@context': 'https://schema.org', '@graph': graph };
109 ---
110
111 <!doctype html>
112 <html lang={site.locale}>
113   <head>
114     <meta charset="utf-8" />
115     <meta name="viewport" content="width=device-width, initial-scale=1" />
116     <title>{fullTitle}</title>
117     <meta name="description" content={description} />
118     <link rel="canonical" href={canonical} />
119     {noindex && <meta name="robots" content="noindex, follow" />}
120
121     <meta property="og:type" content={ogType} />
122     <meta property="og:title" content={fullTitle} />
123     <meta property="og:description" content={description} />
124     <meta property="og:url" content={canonical} />
125     <meta property="og:site_name" content={site.name} />
126     <meta property="og:locale" content="en_US" />
```

```

127     <meta property="og:image" content={ogImage} />
128     <meta property="og:image:width" content="1200" />
129     <meta property="og:image:height" content="630" />
130     <meta property="og:image:alt" content={` ${site.name} - ${site.tagline}`} />
131     <meta name="twitter:card" content="summary_large_image" />
132     <meta name="twitter:title" content={fullTitle} />
133     <meta name="twitter:description" content={description} />
134     <meta name="twitter:image" content={ogImage} />
135
136     <link rel="icon" href="/favicon.svg" type="image/svg+xml" />
137     {/* Matches mobile browser chrome to the page surface in both schemes. */}
138     <meta name="theme-color" media="(prefers-color-scheme: light)" content="#f4f1ea" />
139     <meta name="theme-color" media="(prefers-color-scheme: dark)" content="#17150f" />
140     <link rel="sitemap" href="/sitemap-index.xml" />
141     <link rel="alternate" type="application/rss+xml" title={` ${site.name} - Writing`} href="/rss.xml"
142     />
143     {/*
144       Cross-document view transitions. The site is deliberately multi-page for
145       SEO – six service URLs rank where six anchors cannot – but hard reloads
146       made that structure *feel* disjointed. This keeps the URLs and the
147       continuity of a single-page app.
148     */}
149     <ClientRouter />
150
151     <script type="application/ld+json" set:html={JSON.stringify(jsonLd)} is:inline />
152   </head>
153   <body>
154     <a
155       href="#main"
156       class="sr-only focus:not-sr-only focus:fixed focus:left-4 focus:top-4 focus:z-50 focus:bg-[var(--color-ink)] focus:px-4 focus:py-2 focus:text-[var(--color-paper)]"
157       >Skip to content</a>

```

```
158     >
159     <Header transition:persist />
160     <main id="main">
161         <slot />
162     </main>
163     <Footer />
164     <Analytics needsConsent={needsConsent} />
165
166     <script is:inline>
167         /*
168             Scroll-driven motion, rebound on every navigation.
169
170             With view transitions the document is never re-parsed, so anything wired
171             up on first load has to be re-wired after each swap or the second page a
172             visitor sees is silently static.
173         */
174         function initMotion() {
175             const reduce = window.matchMedia('(prefers-reduced-motion: reduce)').matches;
176             const revealEls = document.querySelectorAll('.reveal');
177             const countEls = document.querySelectorAll('[data-count]');
178
179             if (reduce || !('IntersectionObserver' in window)) {
180                 revealEls.forEach((el) => el.classList.add('is-in'));
181                 return;
182             }
183
184             const io = new IntersectionObserver(
185                 (entries) => {
186                     entries.forEach((entry) => {
187                         if (!entry.isIntersecting) return;
188                         entry.target.classList.add('is-in');
189                         io.unobserve(entry.target);
```

```

190         });
191     },
192     { rootMargin: '0px 0px -10% 0px', threshold: 0.1 }
193 );
194 revealEls.forEach((el) => io.observe(el));
195
196 /*
197     Metrics count up when they scroll into view. The numbers are the payload
198     on a proof section, so they are worth letting land rather than having
199     them simply appear. Non-numeric values are left alone.
200 */
201 const counter = new IntersectionObserver(
202     (entries) => {
203         entries.forEach((entry) => {
204             if (!entry.isIntersecting) return;
205             const el = entry.target;
206             counter.unobserve(el);
207
208             const raw = el.dataset.count;
209             const match = raw.match(/^([\d]*)([\d.,]+)(.*)$/);
210             if (!match) return;
211             const [, prefix, digits, suffix] = match;
212             const target = parseFloat(digits.replace(/,/g, ''));
213             if (!isFinite(target)) return;
214
215             const hasComma = digits.includes(',');
216             const decimals = (digits.split('.')[1] || '').length;
217             const started = performance.now();
218             const duration = 900;
219
220             const tick = (now) => {
221                 const p = Math.min((now - started) / duration, 1);

```

```

222         // Ease-out cubic: fast start, settles rather than stops.
223         const eased = 1 - Math.pow(1 - p, 3);
224         const value = target * eased;
225         const shown = decimals
226             ? value.toFixed(decimals)
227             : hasComma
228             ? Math.round(value).toLocaleString('en-US')
229             : String(Math.round(value));
230         el.textContent = prefix + shown + suffix;
231         if (p < 1) requestAnimationFrame(tick);
232     };
233     requestAnimationFrame(tick);
234 });
235 },
236 { threshold: 0.5 }
237 );
238 countEls.forEach((el) => counter.observe(el));
239 }
240
241 initMotion();
242 document.addEventListener('astro:page-load', initMotion);
243 </script>
244 </body>
245 </html>
246

```

TS src/lib/work.ts

```

1 import { getCollection, type CollectionEntry } from 'astro:content';
2
3 /**
4  * Work entries, with the two visibility rules applied in one place.
5  *

```

```

6  * - `draft` hides an entry everywhere, as usual.
7  * - `pendingApproval` marks a client write-up that the client has not yet
8  *   signed off. Those render in local preview so the page can be reviewed,
9  *   but are stripped from production builds.
10 *
11 * Naming a company and describing their internal process is the client's call
12 * to make. Gating here means an unapproved write-up cannot reach production by
13 * being forgotten - it has to be deliberately cleared.
14 *
15 * Gate on MODE, not DEV. In this project `astro build` reports
16 * `DEV=true PROD=false MODE=production`, so `import.meta.env.DEV` silently
17 * fails to exclude anything at build time. MODE is the only flag that
18 * distinguishes a real build here.
19 */
20 export async function getWork(): Promise<CollectionEntry<'work'>[]> {
21   const entries = await getCollection('work', ({ data }) => !data.draft);
22   const isProduction = import.meta.env.MODE === 'production';
23   const visible = isProduction
24     ? entries.filter(({ data }) => !data.pendingApproval)
25     : entries;
26   return visible.sort((a, b) => a.data.order - b.data.order);
27 }
28

```

ASTRO src/pages/404.astro

```

1  ---
2  import Base from '../layouts/Base.astro';
3  ---
4
5  <Base title="Page not found" description="That page doesn't exist." noindex={true}>
6    <section class="wrap py-32 text-center">
7      <p class="eyebrow">404</p>

```



```

8     <h1 class="mt-6 text-4xl md:text-5xl">This page was never built.</h1>
9     <p class="mx-auto mt-5 max-w-md text-[var(--color-ink-2)]">
10         The link is broken, or the page has moved.
11     </p>
12     <div class="mt-9 flex flex-wrap justify-center gap-3">
13         <a href="/" class="btn btn-primary">Back home</a>
14         <a href="/services/" class="btn btn-ghost">What we build</a>
15     </div>
16 </section>
17 </Base>
18

```

ASTRO src/pages/about.astro

```

1  ---
2  import Base from '../layouts/Base.astro';
3  import Breadcrumbs from '../components/Breadcrumbs.astro';
4  import Faq from '../components/Faq.astro';
5  import Testimonials from '../components/Testimonials.astro';
6  import { Image } from 'astro:assets';
7  import founderPhoto from '../assets/images/niraj.jpg';
8  import { site, founder } from '../data/site';
9
10 const principles = [
11     {
12         title: 'The simplest mechanism that works',
13         body: 'A rule beats a model when a rule will do. We use the least clever thing that reliably does the job, because operations reward boring reliability.',
14     },
15     {
16         title: 'Legible by default',
17         body: 'If a system can't be drawn, explained and handed over, it isn't finished. Documentation is part of the build, not an afterthought.',
18     },

```

```
19  {
20    title: 'Honest about evidence',
21    body: 'We label concept and internal builds as exactly that. We'd rather show real, modest results
    than borrowed credibility.',
22  },
23  {
24    title: 'Built to be left',
25    body: 'Success is the automation running quietly long after we've gone – owned and understood by
    your team, not dependent on us.',
26  },
27  ];
28
29  const description = `${site.name} is a workflow automation studio under ${site.parent}, founded by
    ${founder.name}. We build automated systems teams can see, trust and own.`;
30
31  const faqs = [
32    {
33      q: 'How big is the team?',
34      a: 'Small on purpose. Engagements are led by the founder and delivered with a handful of
        engineers, which means the person who scopes your system is the person who builds it. We take on fewer
        projects than a larger agency and stay closer to each one.',
35    },
36    {
37      q: 'How new is Flowzora?',
38      a: 'New, and we say so rather than implying a decade of history we do not have. The engineering
        behind it is not new: the founder has spent his career building production backend and machine
        learning systems, and everything published on this site is labeled honestly for what it is.',
39    },
40    {
41      q: 'What is oneProductLab?',
42      a: 'oneProductLab is the parent organization Flowzora operates under. Flowzora is the studio
        focused specifically on operations and workflow automation.',
43    },
44  ];
45  ---
46
```

```

47 <Base title="About" description={description} ogRoute="about">
48   <section class="wrap pt-10 pb-12 md:pt-14">
49     <Breadcrumbs trail=[] current="About" />
50
51     <p class="eyebrow mt-8">About</p>
52     <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
53       A small studio that builds the systems businesses run on.
54     </h1>
55     <p class="mt-7 max-w-2xl text-lg text-[var(--color-ink-2)]">
56       {site.name} is a workflow automation studio under {site.parent}. We work with
57       startups, SMBs and growing teams who've outgrown manual process but don't
58       want another rigid platform to fight against.
59     </p>
60   </section>
61
62   <!-- The founder entity. A named, checkable person is what makes a young studio
63       credible to buyers and citable by search and answer engines. -->
64   <section class="border-y border-[var(--color-line)] bg-[var(--color-paper-2)]">
65     <div class="wrap py-14 md:py-20">
66       <p class="eyebrow">Who you'll work with</p>
67       <div class="mt-8 grid gap-10 md:grid-cols-[0.85fr_1.15fr] md:items-start">
68         <div>
69           {/* Processed at build time: WebP with a JPEG fallback, sized to the slot. */}
70           <Image
71             src={founderPhoto}
72             alt={founder.photo.alt}
73             widths={[320, 640]}
74             sizes="(min-width: 768px) 20rem, 100vw"
75             loading="lazy"
76             class="aspect-[4/5] w-full max-w-xs border border-[var(--color-line)] bg-[var(--color-paper-2)] object-cover"
77           />

```

```

78     <p class="mt-4 font-[var(--font-display)] text-xl">{founder.name}</p>
79     <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-ink-
3)]">
80         {founder.role}
81     </p>
82     <a
83         href={founder.linkedin}
84         rel="me noopener"
85         target="_blank"
86         class="mt-3 inline-block font-[var(--font-mono)] text-[0.8rem] link-underline"
87     >
88         LinkedIn ↗
89     </a>
90 </div>
91
92 <div>
93     <h2 class="text-3xl md:text-4xl">Founder-led, and hands-on.</h2>
94     <p class="mt-5 max-w-2xl text-[var(--color-ink-2)]">{founder.bio}</p>
95     <p class="mt-4 max-w-2xl text-[var(--color-ink-2)]">
96         Engagements are led and built by the same person who scopes them.
97         That's the whole reason a studio this size can promise systems you'll
98         actually be able to maintain.
99     </p>
100
101     <div class="mt-8 grid gap-8 sm:grid-cols-2">
102         <div>
103             <p class="eyebrow">Sectors worked in</p>
104             <ul class="mt-3 space-y-1.5">
105                 {founder.sectors.map((s) => <li class="text-[0.95rem] text-[var(--color-ink-2)]">{s}
</li>)}
106             </ul>
107         </div>
108     </div>

```

```

109         <p class="eyebrow">Built with</p>
110         <ul class="mt-3 flex flex-wrap gap-x-3 gap-y-1.5">
111             {
112                 founder.stack.map((s) => (
113                     <li class="font-[var(--font-mono)] text-[0.82rem] text-[var(--color-ink-2)]">{s}
114                 </li>
115             ))
116         </ul>
117     </div>
118 </div>
119 </div>
120 </div>
121 </div>
122 </section>
123
124 <section class="wrap py-14 md:py-20">
125     <div class="grid gap-10 md:grid-cols-[0.8fr_1.2fr]">
126         <h2 class="text-3xl md:text-4xl">What we believe</h2>
127         <div class="grid gap-8 sm:grid-cols-2">
128             {
129                 principles.map((p) => (
130                     <div class="border-t border-[var(--color-line)] pt-4">
131                         <h3 class="font-[var(--font-display)] text-xl">{p.title}</h3>
132                         <p class="mt-2 text-[0.98rem] text-[var(--color-ink-2)]">{p.body}</p>
133                     </div>
134                 ))
135             }
136         </div>
137     </div>
138 </section>
139

```

```

140 <Faq items={faqs} title="Questions about the studio" />
141
142 <section class="wrap py-14 md:py-16">
143   <div class="grid gap-6 border-t border-[var(--color-line)] pt-8 sm:grid-cols-3">
144     <div>
145       <p class="eyebrow">Based</p>
146       <p class="mt-2 text-[var(--color-ink-2)]">{site.location}</p>
147     </div>
148     <div>
149       <p class="eyebrow">Part of</p>
150       <a
151         href={site.parentUrl}
152         rel="noopener"
153         target="_blank"
154         class="mt-2 inline-block link-underline text-[var(--color-ink-2)]"
155         >
156           {site.parent} ↗
157       </a>
158     </div>
159     <div>
160       <p class="eyebrow">Contact</p>
161       <a href={`mailto:${site.email}`} class="mt-2 inline-block link-underline text-[var(--color-ink-2)]">
162         {site.email}
163       </a>
164     </div>
165   </div>
166 </section>
167
168 <!--
169   Testimonials belong on About more than anywhere else: this is the page a
170   buyer opens when they are deciding whether to trust the person, and third

```

```

171     parties vouching is worth more here than any amount of self-description.
172     -->
173     <Testimonials heading="People who've worked with Niraj." eyebrow="References" />
174
175     <section class="border-t border-[var(--color-line)]">
176         <div class="wrap py-20 text-center md:py-24">
177             <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Tell us what's still done by hand.</h2>
178             <a href="/contact/" class="btn btn-primary mt-8">Talk to Niraj</a>
179         </div>
180     </section>
181 </Base>
182

```

ASTRO src/pages/approach.astro

```

1  ---
2  import Base from '../layouts/Base.astro';
3  import Breadcrumbs from '../components/Breadcrumbs.astro';
4  import { approach, site, pricing } from '../data/site';
5
6  // A three-step engagement is genuinely a HowTo, and this is the shape answer
7  // engines use to render step-by-step results for "how does X work" queries.
8  const schema = [
9      {
10         '@type': 'HowTo',
11         '@id': `${site.domain}/approach/#howto`,
12         name: 'How a workflow automation engagement runs',
13         description:
14             'A Flowzora engagement runs in three steps: we map the workflow as it actually happens, build it
15             in visible weekly increments, then hand over documentation and ownership.',
16         totalTime: 'P5W',
17         estimatedCost: {
18             '@type': 'MonetaryAmount',

```

```

18     currency: 'USD',
19     value: pricing[1].priceValue,
20   },
21   step: approach.map((a, i) => ({
22     '@type': 'HowToStep',
23     position: i + 1,
24     name: a.step,
25     text: a.blurb,
26     url: `${site.domain}/approach/#step-${i + 1}`,
27   })),
28 },
29 ];
30 ---
31
32 <Base
33   title="Approach"
34   description="How a Flowzora engagement runs, from mapping the current process to handing over a
    system you own – fixed scope, documented as it ships."
35   ogRoute="approach"
36   schema={schema}
37 >
38 <section class="wrap pt-10 pb-14 md:pt-14">
39   <Breadcrumbs trail=[] current="Approach" />
40   <p class="eyebrow mt-8">Approach</p>
41   <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
42     Working software early. A system you own at the end.
43   </h1>
44   <p class="mt-7 max-w-xl text-lg text-[var(--color-ink-2)]">
45     No three-month discovery, no black box. You see automation working within
46     weeks.
47   </p>
48 </section>

```



```
49
50 <section class="wrap pb-8">
51   {
52     approach.map((a, i) => (
53       <div id={`step-${i + 1}`} class="grid scroll-mt-24 gap-8 border-t border-[var(--color-line)]
py-12 md:grid-cols-[6rem_1fr] md:py-16">
54         <div>
55           <p class="font-[var(--font-mono)] text-sm text-[var(--color-ink-3)]">STEP {String(i +
1).padStart(2, '0')}</p>
56           <h2 class="mt-2 text-3xl">{a.step}</h2>
57         </div>
58         <p class="max-w-2xl text-lg text-[var(--color-ink-2)]">{a.blurb}</p>
59       </div>
60     ))
61   }
62 </section>
63
64 <section class="bg-[var(--color-paper-2)] border-y border-[var(--color-line)]">
65   <div class="wrap py-16 md:py-20">
66     <p class="eyebrow">What you get</p>
67     <div class="mt-8 grid gap-8 md:grid-cols-3">
68       <div>
69         <h3 class="font-[var(--font-display)] text-xl">A map before a build</h3>
70         <p class="mt-2 text-[0.98rem] text-[var(--color-ink-2)]">
71           A clear diagram of your current process and where it leaks time –
72           useful even if you never build a thing with us.
73         </p>
74       </div>
75       <div>
76         <h3 class="font-[var(--font-display)] text-xl">Systems, documented</h3>
77         <p class="mt-2 text-[0.98rem] text-[var(--color-ink-2)]">
78           Runbooks and architecture diagrams, written as we go, so the
79           automation isn't trapped in one person's memory.
```

```
80         </p>
81     </div>
82     <div>
83         <h3 class="font-[var(--font-display)] text-xl">A clean hand-over</h3>
84         <p class="mt-2 text-[0.98rem] text-[var(--color-ink-2)]">
85             A walkthrough and ownership of everything we build. Run it, change
86             it, or bring us back – your choice, not a lock-in.
87         </p>
88     </div>
89 </div>
90 </div>
91 </section>
92
93 <section class="wrap py-16 md:py-24">
94     <div class="grid gap-10 md:grid-cols-2">
95         <div>
96             <p class="eyebrow">Why a studio, not...</p>
97             <h2 class="mt-4 text-3xl md:text-4xl">Where we fit.</h2>
98         </div>
99         <div class="space-y-6">
100             <div class="border-t border-[var(--color-line)] pt-4">
101                 <h3 class="font-[var(--font-mono)] text-sm uppercase tracking-[0.08em]">vs. a
102                 freelancer</h3>
103                 <p class="mt-2 text-[var(--color-ink-2)]">
104                     Continuity and documentation. Systems that survive one person moving on.
105                 </p>
106             </div>
107             <div class="border-t border-[var(--color-line)] pt-4">
108                 <h3 class="font-[var(--font-mono)] text-sm uppercase tracking-[0.08em]">vs. a large
109                 consultancy</h3>
110                 <p class="mt-2 text-[var(--color-ink-2)]">
111                     Senior people do the building. Weeks, not quarters. No slide decks.
112                 </p>
```

```

111         </div>
112         <div class="border-t border-[var(--color-line)] pt-4">
113             <h3 class="font-[var(--font-mono)] text-sm uppercase tracking-[0.08em]">vs. a generic AI
agency</h3>
114             <p class="mt-2 text-[var(--color-ink-2)]">
115                 We start from the problem, not from “let’s add an agent.”
116             </p>
117         </div>
118     </div>
119 </div>
120 </section>
121
122 <section class="border-t border-[var(--color-line)]">
123     <div class="wrap py-20 text-center md:py-24">
124         <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Start with one workflow.</h2>
125         <a href="/contact/" class="btn btn-primary mt-8">Start with step one</a>
126     </div>
127 </section>
128 </Base>
129

```

ASTRO src/pages/contact.astro

```

1  ---
2  import Base from '../layouts/Base.astro';
3  import Breadcrumbs from '../components/Breadcrumbs.astro';
4  import BookCall from '../components/BookCall.astro';
5  import { site } from '../data/site';
6
7  const inputClass =
8      'w-full border border-[var(--color-line)] bg-[var(--color-paper)] px-3.5 py-2.5 transition-colors
focus:border-[var(--color-ink)] focus:outline-2 focus:outline-offset-2 focus:outline-[var(--color-
signal)]';
9  ---

```

```
10
11 <Base
12   title="Contact – map an automation"
13   description="Tell us about one workflow that costs your team time. We map it and tell you honestly
    whether it is worth automating."
14   ogRoute="contact"
15 >
16 <section class="wrap pt-10 pb-12 md:pt-14">
17   <Breadcrumbs trail=[] current="Contact" />
18   <p class="eyebrow mt-8">Contact</p>
19   <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
20     Tell us what's still done by hand.
21   </h1>
22   <p class="mt-7 max-w-xl text-lg text-[var(--color-ink-2)]">
23     One workflow, honestly described. We'll tell you whether it's worth
24     automating – even if the answer is “not yet”.
25   </p>
26 </section>
27
28 <section class="wrap pb-24">
29   <div class="grid gap-12 md:grid-cols-[1.3fr_0.9fr]">
30     <form id="contact-form" action="/api/contact" method="post" class="grid gap-6" novalidate>
31       <div class="grid gap-2">
32         <label for="name" class="font-[var(--font-mono)] text-sm">Name</label>
33         <input id="name" name="name" type="text" autocomplete="name" required class={inputClass} />
34       </div>
35
36       <div class="grid gap-2">
37         <label for="email" class="font-[var(--font-mono)] text-sm">Work email</label>
38         <input
39           id="email"
40           name="email"
```

```
41         type="email"
42         autocomplete="email"
43         spellcheck="false"
44         required
45         class={inputClass}
46     />
47 </div>
48
49 <div class="grid gap-4 sm:grid-cols-2">
50     <div class="grid gap-2">
51         <label for="company" class="font-[var(--font-mono)] text-sm">Company</label>
52         <input id="company" name="company" type="text" autocomplete="organization" class=
{inputClass} />
53     </div>
54     <div class="grid gap-2">
55         <label for="team" class="font-[var(--font-mono)] text-sm">Team size</label>
56         <select id="team" name="team" class={inputClass}>
57             <option>1-10</option>
58             <option>11-50</option>
59             <option>51-200</option>
60             <option>200+</option>
61         </select>
62     </div>
63 </div>
64
65 <div class="grid gap-2">
66     <label for="workflow" class="font-[var(--font-mono)] text-sm">
67         The workflow that costs you time
68     </label>
69     <textarea
70         id="workflow"
71         name="workflow"
```

```

72         rows="5"
73         required
74         placeholder="e.g. A lead fills our form, then someone copies it into the CRM, emails
sales, and updates a spreadsheet..."
75         class={inputClass}></textarea>
76     </div>
77
78     <!-- Honeypot: hidden from people, irresistible to bots. -->
79     <div class="absolute -left-[9999px]" aria-hidden="true">
80         <label for="company_website">Company website</label>
81         <input id="company_website" name="company_website" type="text" tabindex="-1"
autocomplete="off" />
82     </div>
83
84     <div>
85         <button type="submit" class="btn btn-primary" data-submit>Send it over</button>
86
87         <p
88             id="form-status"
89             role="status"
90             aria-live="polite"
91             class="mt-3 font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]"
92             >
93             We reply within two working days. Or email
94             <a href={`mailto:${site.email}`} class="link-underline">{site.email}</a>.
95         </p>
96     </div>
97
98 </form>
99
100 <aside class="border-t border-[var(--color-line)] pt-6 md:border-l md:border-t-0 md:pl-8">
101     <p class="eyebrow">What happens next</p>
102     <ol class="mt-5 space-y-5">
103         <li>
104             <p class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">01</p>

```

```
103         <p class="mt-1 text-[0.98rem] text-[var(--color-ink-2)]">We read it and reply within two
working days – a person, not an autoresponder.</p>
104     </li>
105     <li>
106         <p class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">02</p>
107         <p class="mt-1 text-[0.98rem] text-[var(--color-ink-2)]">A short call to map the workflow
together and find where the time actually goes.</p>
108     </li>
109     <li>
110         <p class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">03</p>
111         <p class="mt-1 text-[0.98rem] text-[var(--color-ink-2)]">An honest recommendation –
including “this isn’t worth automating yet” if that’s true.</p>
112     </li>
113 </ol>
114 {
115     site.calendly && (
116         <>
117             <hr class="rule my-8" />
118             <p class="eyebrow">Rather talk it through?</p>
119             <p class="mt-3 text-[0.95rem] text-[var(--color-ink-2)]">
120                 Thirty minutes, one workflow. No deck, no pitch.
121             </p>
122             <BookCall class="mt-5" label="Book a call" />
123         </>
124     )
125 }
126 </aside>
127 </div>
128 </section>
129 </Base>
130
131 <script>
132     // Progressive enhancement only: with JS off, the form still posts and the
```

```
133 // endpoint redirects to /thank-you/.
134 const form = document.querySelector('#contact-form') as HTMLFormElement | null;
135 const status = document.querySelector('#form-status') as HTMLElement | null;
136 const button = document.querySelector('[data-submit]') as HTMLButtonElement | null;
137
138 form?.addEventListener('submit', async (event) => {
139     if (!form.checkValidity()) {
140         event.preventDefault();
141         form.reportValidity();
142         return;
143     }
144     event.preventDefault();
145
146     if (!button || !status) return;
147     button.disabled = true;
148     const original = button.textContent;
149     button.textContent = 'Sending...';
150
151     try {
152         const response = await fetch(form.action, {
153             method: 'POST',
154             headers: { Accept: 'application/json' },
155             body: new FormData(form),
156         });
157
158         if (response.ok) {
159             window.location.href = '/thank-you/';
160             return;
161         }
162
163         const data = await response.json().catch(() => ({}));
164         status.textContent = data.error ?? 'Something went wrong. Please email us directly.';
```



```

165     status.style.color = 'var(--color-signal-ink)';
166   } catch {
167     status.textContent = 'Network error. Please email us directly.';
168     status.style.color = 'var(--color-signal-ink)';
169   } finally {
170     button.disabled = false;
171     button.textContent = original;
172   }
173   });
174 </script>
175

```

ASTRO src/pages/index.astro

```

1  ---
2  import Base from '../layouts/Base.astro';
3  import WorkflowSystem from '../components/WorkflowSystem.astro';
4  import ConnectedSystems from '../components/ConnectedSystems.astro';
5  import Faq from '../components/Faq.astro';
6  import Testimonials from '../components/Testimonials.astro';
7  import BookCall from '../components/BookCall.astro';
8  import { Image } from 'astro:assets';
9  import founderPhoto from '../assets/images/niraj.jpg';
10 import { services, approach, faqs, site, founder, credentials, fitFor, pricing, foundingOffer,
    testimonials } from '../data/site';
11 import { getWork } from '../lib/work';
12
13 const work = await getWork();
14
15 const schema = [
16   {
17     '@type': 'FAQPage',
18     '@id': `${site.domain}/#faq`,

```

```

19     mainEntity: faqs.map((f) => ({
20         '@type': 'Question',
21         name: f.q,
22         acceptedAnswer: { '@type': 'Answer', text: f.a },
23     })),
24 },
25 /*
26     Reviews attached to the organization. Deliberately no `aggregateRating` –
27     LinkedIn recommendations carry no star rating, so inventing an average out
28     of them would be fabricated structured data. Individual reviews are the
29     honest representation and are what search engines can actually corroborate
30     against the linked profiles.
31 */
32 ...testimonials.map((t) => ({
33     '@type': 'Review',
34     itemReviewed: { '@id': `${site.domain}/#organization` },
35     author: { '@type': 'Person', name: t.name, url: t.linkedin },
36     reviewBody: t.quote,
37 })),
38 ];
39 ---
40
41 <Base schema={schema}>
42     <!-- Hero: a point of view, not a feature list.
43
44     No eyebrow above the headline. The category label ("workflow automation
45     studio") still carries in the <title>, the meta description and the
46     sub-line below, so search and social lose nothing – and the page now
47     opens on the claim instead of on a label. "Part of oneProductLab" was
48     also raising a question it didn't answer for anyone who hasn't heard of
49     the parent; it remains in the footer, where a curious reader looks.
50

```

```
51     Rejected headlines worth remembering. "Most companies run on copy-paste"
52     described the reader's own operation as amateurish in the first seven
53     words – and the reader is usually the person who built those processes.
54     "The work between your systems. Handled." needed decoding, and "handled"
55     is a shrug rather than a promise.
56
57     This frames the purchase as the trade a buyer is actually weighing:
58     capacity without cost. "Overhead" is deliberate – it is a line in a
59     budget, where softer words like "busywork" shrink the problem and
60     quietly argue the price down. -->
61 <section class="wrap pt-10 pb-16 md:pt-14 md:pb-20">
62     <h1 class="max-w-4xl text-[2.8rem] leading-[1.02] sm:text-[3.6rem] md:text-[4.4rem]">
63         Grow the business.{ ' '}
64         <span class="text-[var(--color-signal-ink)]">Not the overhead.</span>
65     </h1>
66     <p class="mt-8 max-w-xl text-lg text-[var(--color-ink-2)]">
67         We connect the tools you already run and remove the manual steps between
68         them, so more work moves through without more people to move it. You own
69         the system outright.
70     </p>
71     <div class="mt-11 flex flex-wrap items-center gap-3">
72         <a href="/contact/" class="btn btn-primary">Let's talk growth</a>
73         <a href="/pricing/" class="btn btn-ghost">From $8,000</a>
74     </div>
75
76     <!--
77     The founder, in the hero. A buyer is hiring a person, not software, and
78     burying the only named human on an About page costs more trust than the
79     space it saves.
80     -->
81     <div class="mt-14 flex items-center gap-4 border-t border-[var(--color-line)] pt-7">
82         <Image
```

```
83         src={founderPhoto}
84         alt=""
85         width={96}
86         height={96}
87         loading="eager"
88         class="h-12 w-12 shrink-0 rounded-full border border-[var(--color-line)] object-cover"
89     />
90     <p class="max-w-md text-[0.95rem] text-[var(--color-ink-2)]">
91         Built by <strong class="font-medium text-[var(--color-ink)]">{founder.name}</strong>, who
92         writes the code as well as the proposal. <a href="/about/" class="link-underline">About the
studio</a>
93     </p>
94 </div>
95 </section>
96
97 <!--
98     Client proof, first thing after the hero.
99
100     This is the strongest evidence on the site: named people, dated, linked to
101     the profile that wrote the words. It previously sat behind a strip of
102     backend metrics – latency, database load – which are credentials for a job
103     nobody here is hiring for. A buyer's question after the hero is "has anyone
104     actually paid them", not "how fast are their queries", so the answer goes
105     first and the engineering detail supports it below.
106     -->
107 <Testimonials plain />
108
109 <!--
110     Engineering track record, supporting the testimonials rather than leading.
111     Prior production work, stated as prior work – the distinction is the point.
112     -->
113 <section class="border-y border-[var(--color-line)] bg-[var(--color-paper-2)]">
```

```

114     <div class="wrap py-14 md:py-16">
115         <p class="eyebrow">Measured on systems we've shipped</p>
116         <ul class="reveal mt-9 grid gap-x-10 gap-y-9 sm:grid-cols-2 lg:grid-cols-4">
117             {
118                 credentials.map((c, i) => (
119                     <li data-stagger style={`--i:${i}`}>
120                         <p class="metric text-[var(--color-ink)]" data-count={c.metric}>
121                             {c.metric}
122                         </p>
123                         <p class="mt-2 font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-signal-ink)]">
124                             {c.label}
125                         </p>
126                         <p class="mt-2.5 max-w-[26ch] text-[0.92rem] leading-relaxed text-[var(--color-ink-2)]">
127                             {c.detail}
128                         </p>
129                     </li>
130                 ))
131             }
132         </ul>
133         <p class="mt-9 max-w-2xl font-[var(--font-mono)] text-xs leading-relaxed text-[var(--color-ink-3)]">
134             From production systems {founder.name} built before founding {site.name}. Verifiable on
135             <a href={founder.linkedin} rel="noopener" target="_blank" class="link-underline">LinkedIn</a>.
136         </p>
137     </div>
138 </section>
139
140 <!-- The problem, named. Prose compressed into three scannable lines: at this
141      density the reader is skimming, so the words have to behave like data.
142
143      Stated as a principle rather than a complaint. "Manual work doesn't
144      scale. It just costs more." was an assertion about the world; this is a

```

```
145         claim about the reader's business that the three rows below then
146         evidence. -->
147     <section class="wrap py-20 md:py-28">
148         <div class="grid gap-14 md:grid-cols-[0.9fr_1.1fr]">
149             <div>
150                 <p class="eyebrow">The problem</p>
151                 <h2 class="mt-4 max-w-md text-3xl md:text-4xl">
152                     Your business shouldn't depend on repetitive work.
153                 </h2>
154                 <p class="mt-5 max-w-sm text-[var(--color-ink-2)]">
155                     It doesn't scale, and it costs more every month you grow.
156                 </p>
157             </div>
158             <ul class="reveal grid gap-0 self-start border-t border-[var(--color-line)]">
159                 <li data-stagger style="--i:0" class="grid gap-1 border-b border-[var(--color-line)] py-5
sm:grid-cols-[9rem_1fr] sm:gap-6">
160                     <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-ink-
3)]">
161                         01 – Re-keying
162                     </p>
163                     <p class="text-[var(--color-ink-2)]">
164                         The same record lives in three tools, and the three disagree.
165                     </p>
166                 </li>
167                 <li data-stagger style="--i:1" class="grid gap-1 border-b border-[var(--color-line)] py-5
sm:grid-cols-[9rem_1fr] sm:gap-6">
168                     <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-ink-
3)]">
169                         02 – Stalling
170                     </p>
171                     <p class="text-[var(--color-ink-2)]">
172                         Work waits on someone remembering. So it happens late, or never.
173                     </p>
174                 </li>
```

```

175         <li data-stagger style="--i:2" class="grid gap-1 border-b border-[var(--color-line)] py-5
sm:grid-cols-[9rem_1fr] sm:gap-6">
176             <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-ink-
3)]]">
177                 03 – No record
178             </p>
179             <p class="text-[var(--color-ink-2)]">
180                 Nobody can say what happened, or when. The process lives in heads.
181             </p>
182         </li>
183     </ul>
184 </div>
185 </section>
186
187 <!--
188     The two diagrams, merged into one section.
189
190     These were previously two full sections with two headings, running to
191     ~2,200px combined – and they make a single argument: here is what a system
192     looks like, and here is how your existing tools sit inside it. One heading,
193     two views.
194 -->
195 <section class="bg-[var(--color-paper-2)] border-y border-[var(--color-line)]">
196     <div class="wrap py-16 md:py-20">
197         <div class="max-w-xl">
198             <p class="eyebrow">A system, made visible</p>
199             <h2 class="mt-4 text-3xl md:text-4xl">Automation is invisible. So we draw it.</h2>
200             <p class="mt-5 text-[var(--color-ink-2)]">
201                 Every engagement starts with a map: the workflow end to end, and the
202                 tools you already run wired into it.
203             </p>
204         </div>
205     <div class="mt-12 reveal">

```

```

206         <WorkflowSystem />
207     </div>
208     <div class="mt-14 grid items-center gap-12 border-t border-[var(--color-line)] pt-14 md:grid-
cols-2">
209         <div>
210             <h3 class="font-[var(--font-display)] text-2xl">Your tools, wired into one system.</h3>
211             <p class="mt-4 max-w-md text-[var(--color-ink-2)]">
212                 You don't need another app. You need the ones you have to talk to each
213                 other, in the right order, without a person in the middle.
214             </p>
215             <a href="/services/integrations/" class="btn btn-ghost mt-7">How integrations work</a>
216         </div>
217         <div class="reveal">
218             <ConnectedSystems />
219         </div>
220     </div>
221 </div>
222 </section>
223
224 <!--
225     Qualification. "Are these people for me?" is a buyer's first question, and
226     leaving it unanswered costs more inquiries than a narrow answer would.
227 -->
228 <section class="border-y border-[var(--color-line)] bg-[var(--color-paper-3)]">
229     <div class="wrap py-16 md:py-20">
230         <div class="grid gap-14 md:grid-cols-[0.9fr_1.1fr]">
231             <div>
232                 <p class="eyebrow">{fitFor.headline}</p>
233                 <h2 class="mt-4 max-w-sm text-3xl md:text-4xl">
234                     Teams with a stack that's outgrown itself.
235                 </h2>
236                 <p class="mt-6 max-w-sm font-[var(--font-mono)] text-xs leading-relaxed text-[var(--color-
ink-3)]">

```



```

237         Not a fit? We'll say so on the first call.
238     </p>
239 </div>
240 <div>
241     <ul class="reveal space-y-0 border-t border-[var(--color-line-2)]">
242         {
243             fitFor.signals.map((s, i) => (
244                 <li
245                     data-stagger
246                     style={`--i:${i}`}
247                     class="flex gap-4 border-b border-[var(--color-line-2)] py-4"
248                 >
249                     <span class="font-[var(--font-mono)] text-[var(--color-signal-ink)]" aria-
hidden="true">
250                         ✓
251                     </span>
252                     <span class="text-[var(--color-ink-2)]">{s}</span>
253                 </li>
254             ))
255         }
256         {
257             fitFor.notFor.map((s, i) => (
258                 <li
259                     data-stagger
260                     style={`--i:${i + fitFor.signals.length}`}
261                     class="flex gap-4 border-b border-[var(--color-line-2)] py-4"
262                 >
263                     <span class="font-[var(--font-mono)] text-[var(--color-ink-3)]" aria-hidden="true">
264                         ×
265                     </span>
266                     <span class="text-[var(--color-ink-3)]">{s}</span>
267                 </li>

```

```

268         ))
269     }
270 </ul>
271     <p class="mt-7 font-[var(--font-mono)] text-[0.72rem] uppercase tracking-[0.1em] text-[var(--color-ink-3)]">
272         Stacks we work in
273     </p>
274     <ul class="mt-3 flex flex-wrap gap-x-4 gap-y-2">
275         {
276             fitFor.stacks.map((s) => (
277                 <li class="font-[var(--font-mono)] text-[0.82rem] text-[var(--color-ink-2)]">{s}</li>
278             ))
279         }
280     </ul>
281 </div>
282 </div>
283 </div>
284 </section>
285
286 <!-- What we build -->
287 <section class="wrap py-16 md:py-20">
288     <div class="flex items-end justify-between gap-6 flex-wrap">
289         <div>
290             <p class="eyebrow">What we build</p>
291             <h2 class="mt-4 text-3xl md:text-4xl">Where we usually remove manual work.</h2>
292         </div>
293         <a href="/services/" class="btn btn-ghost">All services</a>
294     </div>
295 <!--
296     A two-column matrix rather than six full-width rows. This section is a
297     directory – every item leads somewhere else – so it earns scanning speed,
298     not scrolling. Full-width rows gave each of six short lines the same

```

```

299     vertical weight as a real content section, and pushed the proof and
300     pricing below it further down the page.
301
302     `gap-px` over a line-coloured background draws the dividers, so the grid
303     keeps hairline rules in both axes without per-cell border bookkeeping.
304     -->
305     <ul class="reveal mt-10 grid gap-px border-y border-[var(--color-line)] bg-[var(--color-line)]
md:grid-cols-2">
306         {
307         services.map((s, i) => (
308             <li data-stagger style={`--i:${i}`} class="bg-[var(--color-paper)]">
309                 <a
310                     href={`/${services/${s.slug}}/`}
311                     class="group flex h-full gap-4 py-5 pr-4 transition-colors md:px-6 hover:bg-[var(--
color-paper-2)]"
312                 >
313                     <span class="mt-1 font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">{s.index}
</span>
314                     <div class="min-w-0">
315                         <h3 class="font-[var(--font-display)] text-lg transition-colors group-hover:text-
[var(--color-signal-ink)]">
316                             {s.title}
317                             {/*
318                                 Travels with the last word instead of being pinned to the
319                                 far right, where a full-width row left it stranded metres
320                                 from the label it belongs to.
321                             */}
322                             <span
323                                 class="ml-1 inline-block font-[var(--font-mono)] text-sm text-[var(--color-ink-3)]
transition-transform group-hover:translate-x-1 group-hover:text-[var(--color-signal-ink)]"
324                                 aria-hidden="true"
325                             ></span>
326                             >
327                             </h3>

```

```

328         <p class="mt-1 text-[0.92rem] leading-relaxed text-[var(--color-ink-2)]">{s.brief}</p>
329     </div>
330 </a>
331 </li>
332 ))
333 }
334 </ul>
335 <!--
336     Says out loud that the list is a sample, not a menu. Without this a
337     reader whose problem isn't one of the six assumes we don't do it and
338     leaves – the exact opposite of what a services list is for.
339 -->
340 <p class="mt-6 max-w-xl font-[var(--font-mono)] text-xs leading-relaxed text-[var(--color-ink-
341 3)]">
342     These are where the work usually lands, not a fixed menu. If your bottleneck
343     isn't listed, it's still worth a conversation.
344 </p>
345 </section>
346 <!-- Proof -->
347 <section class="bg-[var(--color-slate)] text-[var(--color-paper)]">
348     <div class="wrap py-16 md:py-20">
349         <div class="flex items-end justify-between gap-6 flex-wrap">
350             <div>
351                 <p class="eyebrow text-[var(--color-inverse-ink-3)]">Selected work</p>
352                 <h2 class="mt-4 text-3xl md:text-4xl">Systems we've built, in the open.</h2>
353             </div>
354             <a
355                 href="/work/"
356                 class="btn border-[var(--color-inverse-line)] text-[var(--color-inverse-ink)] transition-
357                 colors hover:bg-[var(--color-inverse-ink)] hover:text-[var(--color-slate)]"
358                 >All work</a>

```

```

359     </div>
360     <div class="mt-10 grid gap-px bg-[var(--color-slate-2)] md:grid-cols-3">
361         {
362             work.slice(0, 3).map((item) => (
363                 <a
364                     href={`\work/${item.id}/`}
365                     class="group block bg-[var(--color-slate)] p-7 transition-colors hover:bg-[var(--color-slate-2)]"
366                 >
367                     <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.12em] text-[var(--color-inverse-ink-3)]">
368                         {item.data.kind.replace('-', ' ')} · {item.data.sector}
369                     </p>
370                     <h3 class="mt-4 font-[var(--font-display)] text-xl">{item.data.title}</h3>
371                     <p class="mt-3 text-[0.92rem] leading-relaxed text-[var(--color-inverse-ink-2)]">
372                         {item.data.summary}</p>
373                     <span class="mt-6 inline-flex items-center gap-2 font-[var(--font-mono)] text-sm text-[var(--color-signal-bright)]">
374                         Read the build
375                         <span class="transition-transform group-hover:translate-x-1" aria-hidden="true">
376                             →
377                         </span>
378                     </span>
379                 </a>
380             ))
381         }
382     </div>
383     <p class="mt-6 font-[var(--font-mono)] text-xs text-[var(--color-inverse-ink-4)]">
384         Concept and internal builds are labeled as such. Client testimonials are
385         public LinkedIn recommendations, linked to the profile that wrote them.
386     </p>
387 </div>
388 </section>

```

```

389 <!-- How we work -->
390 <section class="wrap py-16 md:py-20">
391   <div class="max-w-xl">
392     <p class="eyebrow">How we work</p>
393     <!--
394       No count in the heading, for the same reason the services section
395       dropped "Six places": a number in the copy has to be kept in sync with
396       the array by hand, and goes stale the moment a step is added.
397     -->
398     <h2 class="mt-4 text-3xl md:text-4xl">You own what's left behind.</h2>
399     <p class="mt-5 text-[var(--color-ink-2)]">
400       Every engagement runs the same way, and you can see where you are in it
401       at any point.
402     </p>
403   </div>
404   <!--
405     Two rows of three rather than one long row. Six across would set the
406     measure far too narrow to read; this keeps a comfortable line length and
407     still reads left-to-right as a sequence.
408   -->
409   <ol class="reveal mt-12 grid gap-x-10 gap-y-9 sm:grid-cols-2 lg:grid-cols-3">
410     {
411       approach.map((a, i) => (
412         <li data-stagger style={`--i:${i}`} class="border-t-2 border-[var(--color-ink)] pt-5">
413           <p class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">
414             STEP {String(i + 1).padStart(2, '0')}
415           </p>
416           <h3 class="mt-2 font-[var(--font-display)] text-2xl">{a.step}</h3>
417           <p class="mt-3 max-w-[34ch] text-[0.95rem] leading-relaxed text-[var(--color-ink-2)]">
418             {a.short}
419           </p>
420         </li>

```

```

421     ))
422   }
423 </ol>
424   <a href="/approach/" class="btn btn-ghost mt-10">How an engagement runs</a>
425 </section>
426
427 <!--
428   Pricing and risk reversal, on the homepage. These are the strongest arguments
429   the studio has and they were previously a click away, which meant most
430   visitors never met them.
431 -->
432 <section class="border-y border-[var(--color-line)] bg-[var(--color-paper-2)]">
433   <div class="wrap py-16 md:py-20">
434     <div class="flex flex-wrap items-end justify-between gap-6">
435       <div>
436         <p class="eyebrow">What it costs</p>
437         <h2 class="mt-4 max-w-md text-3xl md:text-4xl">Published prices. Fixed scope.</h2>
438       </div>
439       <a href="/pricing/" class="btn btn-ghost">Full pricing</a>
440     </div>
441
442     <ul class="reveal mt-10 grid gap-px border-y border-[var(--color-line)] bg-[var(--color-line)]
lg:grid-cols-3">
443       {
444         pricing.map((tier, i) => (
445           <li data-stagger style={`--i:${i}`} class="bg-[var(--color-paper-2)] px-6 py-6">
446             <p class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">{tier.duration}</p>
447             <h3 class="mt-2 font-[var(--font-display)] text-lg">{tier.name}</h3>
448             <p class="price mt-3 text-[var(--color-ink)]">{tier.price}</p>
449             <p class="mt-3 max-w-[34ch] text-[0.9rem] leading-relaxed text-[var(--color-ink-2)]">
450               {tier.summary}
451             </p>

```

```
452         </li>
453     ))
454 }
455 </ul>
456
457 <ul class="mt-10 grid gap-6 sm:grid-cols-3">
458     <li class="border-t border-[var(--color-line-2)] pt-4">
459         <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-signal-ink)]">
460             The number doesn't move
461         </p>
462         <p class="mt-2 text-[0.92rem] text-[var(--color-ink-2)]">
463             Scope fixed in writing. Overruns are ours to absorb.
464         </p>
465     </li>
466     <li class="border-t border-[var(--color-line-2)] pt-4">
467         <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-signal-ink)]">
468             You own everything
469         </p>
470         <p class="mt-2 text-[0.92rem] text-[var(--color-ink-2)]">
471             Code and accounts in your name from day one. No lock-in.
472         </p>
473     </li>
474     <li class="border-t border-[var(--color-line-2)] pt-4">
475         <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-signal-ink)]">
476             We'll talk you out of it
477         </p>
478         <p class="mt-2 text-[0.92rem] text-[var(--color-ink-2)]">
479             If it isn't worth automating yet, we say so before you spend.
480         </p>
481     </li>
```



```

482     </ul>
483 </div>
484 </section>
485
486 <!--
487     The founding-client offer, placed immediately after the price.
488
489     A visitor works out that the studio is new the moment they read "concept"
490     on the case studies. Left unsaid, that reads as something being hidden and
491     quietly undermines the honest labelling everywhere else. Said plainly, and
492     said right after the number, it converts the objection into a reason to
493     move now.
494 -->
495 <section class="wrap py-16 md:py-20">
496     <div class="grid gap-12 md:grid-cols-[0.9fr_1.1fr]">
497         <div>
498             <p class="eyebrow">{foundingOffer.eyebrow}</p>
499             <h2 class="mt-4 max-w-sm text-3xl md:text-4xl">{foundingOffer.headline}</h2>
500             <p class="mt-5 max-w-sm text-[var(--color-ink-2)]">{foundingOffer.body}</p>
501         </div>
502         <div>
503             <ul class="reveal border-t border-[var(--color-line-2)]">
504                 {
505                     foundingOffer.terms.map((t, i) => (
506                         <li
507                             data-stagger
508                             style={`--i:${i}`}
509                             class="border-b border-[var(--color-line-2)] py-4"
510                         >
511                             <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-signal-ink)]">
512                                 {t.title}

```

```

513         </p>
514         <p class="mt-2 text-[0.95rem] text-[var(--color-ink-2)]">{t.detail}</p>
515     </li>
516     ))
517 }
518 </ul>
519 <p class="mt-6 max-w-md font-[var(--font-mono)] text-xs leading-relaxed text-[var(--color-ink-
3)]">
520     {foundingOffer.caveat}
521 </p>
522 </div>
523 </div>
524 </section>
525
526 <Faq items={faqs} />
527
528 <!--
529     Closing statement on the dark surface. Using it twice – once for proof, once
530     here – turns a one-off into a deliberate rhythm, and the oversized type gives
531     the page a single moment of real scale contrast.
532 -->
533 <section class="bg-[var(--color-slate)] text-[var(--color-inverse-ink)]">
534     <div class="wrap py-24 md:py-28">
535         <!--
536             A heading, not a paragraph. This is the page's closing statement and it
537             was the one major line with no place in the document outline.
538             `text-balance` handles the line break, so the phrase stays evenly split
539             at any width instead of relying on a hardcoded <br>.
540         -->
541         <h2 class="display max-w-3xl text-balance">Tell us what's still done by hand.</h2>
542         <div class="mt-12 flex flex-col gap-8 border-t border-[var(--color-inverse-line)] pt-10 md:flex-
row md:items-center md:justify-between">
543             <p class="max-w-md text-lg text-[var(--color-inverse-ink-2)]">

```

```

544         One workflow, honestly described. We'll map it and tell you whether it's
545         worth automating.
546     </p>
547     <div class="flex flex-col items-start gap-3 md:items-end">
548         <div class="flex flex-wrap items-center gap-3">
549             <a
550                 href="/contact/"
551                 class="btn border-[var(--color-inverse-ink)] bg-[var(--color-inverse-ink)] text-[var(--color-slate)] transition-colors hover:border-[var(--color-signal-bright)] hover:bg-[var(--color-signal-bright)] hover:text-[var(--color-inverse-ink)]"
552                 >Let's talk growth</a>
553             >
554             {
555                 /*
556                 Only rendered once a real event type exists. A "Book a call"
557                 button that silently falls back to the same form the primary
558                 CTA already points at is worse than no button – it promises a
559                 calendar and delivers a text field.
560                 */
561                 site.calendly && (
562                     <BookCall
563                         label="Book a 30-min call"
564                         class="[&>a]:border-[var(--color-inverse-line)] [&>a]:text-[var(--color-inverse-ink)] [&>button]:border-[var(--color-inverse-line)] [&>button]:text-[var(--color-inverse-ink)]"
565                         />
566                     )
567                 }
568             <a
569                 href={`mailto:${site.email}`}
570                 class="btn border-[var(--color-inverse-line)] text-[var(--color-inverse-ink)] transition-colors hover:bg-[var(--color-slate-2)]"
571                 >Email us</a>
572             >
573         </div>

```

```

574         <!--
575         Sits with the buttons rather than orphaned below them. This answers
576         "will I be ignored?" at the exact moment that doubt arrives, so it
577         was the wrong line to render at the dimmest tone on the page.
578         -->
579         <p class="font-[var(--font-mono)] text-xs text-[var(--color-inverse-ink-3)]">
580         A real person replies within two working days.
581         </p>
582     </div>
583 </div>
584 </div>
585 </section>
586 </Base>
587

```

TS src/pages/og/[...route].ts

```

1  import { OGImageRoute } from 'astro-og-canvas';
2  import { getCollection } from 'astro:content';
3  import { getWork } from '../lib/work';
4
5  /**
6   * Programmatic share cards.
7   *
8   * Every page gets a correct, on-brand OG image without anyone exporting a PNG by
9   * hand – which is the only way share cards stay right as the site grows. The
10  * design deliberately mirrors the site: paper background, ink type, one rust rule.
11  */
12
13  const work = await getWork();
14  const writing = await getCollection('writing', ({ data }) => !data.draft);
15
16  const pages: Record<string, { title: string; description: string }> = {

```

```
17   default: {
18     title: 'Grow the business. Not the overhead.',
19     description: 'Workflow automation you own outright.',
20   },
21   services: {
22     title: 'Workflow automation services',
23     description: 'Where we usually remove manual work.',
24   },
25   pricing: {
26     title: 'What automation costs',
27     description: 'Published rates. Fixed scope, fixed price.',
28   },
29   work: {
30     title: 'Selected work',
31     description: 'Systems we have built, honestly labeled.',
32   },
33   approach: {
34     title: 'Map, build, hand over',
35     description: 'How an engagement actually runs.',
36   },
37   about: {
38     title: 'About Flowzora',
39     description: 'A workflow automation studio under oneProductLab.',
40   },
41   writing: {
42     title: 'Writing',
43     description: 'Notes on operations, automation and where AI earns its place.',
44   },
45   contact: {
46     title: 'Tell us what is still done by hand',
47     description: 'One workflow, honestly described.',
48   },
```

```
49  };
50
51  for (const entry of work) {
52    pages[`work/${entry.id}`] = {
53      title: entry.data.title,
54      description: entry.data.summary,
55    };
56  }
57  for (const entry of writing) {
58    pages[`writing/${entry.id}`] = {
59      title: entry.data.title,
60      description: entry.data.description,
61    };
62  }
63
64  export const { getStaticPaths, GET } = await OGImageRoute({
65    pages,
66    getImageOptions: (_path, page: { title: string; description: string }) => ({
67      title: page.title,
68      description: page.description,
69      bgGradient: [
70        [244, 241, 234],
71        [236, 231, 220],
72      ],
73      border: { color: [182, 67, 31], width: 14, side: 'inline-start' },
74      padding: 80,
75      // Vendored locally so builds are deterministic and do not depend on a
76      // third-party font CDN being reachable at build time.
77      fonts: ['./src/assets/fonts/fraunces.ttf', './src/assets/fonts/plex-sans.ttf'],
78      font: {
79        title: {
80          color: [23, 21, 15],
```

```

81         size: 66,
82         lineHeight: 1.1,
83         weight: 'SemiBold',
84         families: ['Fraunces'],
85     },
86     description: {
87         color: [61, 58, 49],
88         size: 30,
89         lineHeight: 1.4,
90         weight: 'Normal',
91         families: ['IBM Plex Sans'],
92     },
93 },
94 format: 'PNG',
95 )),
96 });
97
98 export const prerender = true;
99

```

ASTRO src/pages/pricing.astro

```

1  ---
2  import Base from '../layouts/Base.astro';
3  import Breadcrumbs from '../components/Breadcrumbs.astro';
4  import Faq from '../components/Faq.astro';
5  import Testimonials from '../components/Testimonials.astro';
6  import { pricing, site } from '../data/site';
7
8  const description =
9
10     'Workflow automation pricing: a $2,500 two-week Automation Map, first systems built for $8,000–
    $18,000 fixed scope, and ongoing partnerships from $6,000 per month.';

```

```

11  const schema = [
12    {
13      '@type': 'OfferCatalog',
14      '@id': `${site.domain}/pricing/#catalog`,
15      name: 'Workflow automation engagements',
16      provider: { '@id': `${site.domain}/#organization` },
17      itemListElement: pricing.map((tier) => ({
18        '@type': 'Offer',
19        name: tier.name,
20        description: tier.summary,
21        priceCurrency: 'USD',
22        price: tier.priceValue,
23        priceSpecification: {
24          '@type': 'PriceSpecification',
25          priceCurrency: 'USD',
26          minPrice: tier.priceValue,
27          valueAddedTaxIncluded: false,
28        },
29        itemOffered: { '@type': 'Service', name: tier.name, description: tier.summary },
30      })),
31    },
32    {
33      '@type': 'FAQPage',
34      '@id': `${site.domain}/pricing/#faq`,
35      mainEntity: [
36        {
37          '@type': 'Question',
38          name: 'How much does workflow automation cost?',
39          acceptedAnswer: {
40            '@type': 'Answer',
41            text: 'Most first projects land between $8,000 and $18,000 for a single workflow built,
documented and handed over. A two-week Automation Map that scopes the work costs $2,500 and is
credited against the build. Ongoing partnerships start at $6,000 per month.',

```



```
42     },
43     },
44     {
45         '@type': 'Question',
46         name: 'Why do you publish your prices?',
47         acceptedAnswer: {
48             '@type': 'Answer',
49             text: 'Because hiding them wastes everyone\u2019s time. Published ranges let you decide
whether we are worth a conversation before you sit through one, and they hold us to a number rather
than pricing off how badly you appear to need help.',
50         },
51     },
52     {
53         '@type': 'Question',
54         name: 'What happens if the project takes longer than expected?',
55         acceptedAnswer: {
56             '@type': 'Answer',
57             text: 'The price does not move. Scope is fixed in writing after the Automation Map, so
overruns are our problem to absorb, not yours to pay for. If you want to add scope mid-build we quote
it separately rather than quietly extending the invoice.',
58         },
59     },
60     {
61         '@type': 'Question',
62         name: 'Do you charge for the first conversation?',
63         acceptedAnswer: {
64             '@type': 'Answer',
65             text: 'No. The first call is free and ends with an honest answer about whether the workflow
is worth automating yet. Only the Automation Map, which produces documented deliverables, is paid.',
66         },
67     },
68 ],
69 },
70 ];
```

```
71
72 const faqs = [
73   {
74     q: 'Why do you publish your prices?',
75     a: 'Because hiding them wastes everyone's time. Published ranges let you decide whether we're
       worth a conversation before you sit through one, and they hold us to a number rather than pricing off
       how badly you appear to need help.',
76   },
77   {
78     q: 'What happens if the project takes longer than expected?',
79     a: 'The price does not move. Scope is fixed in writing after the Automation Map, so overruns are
       our problem to absorb, not yours to pay for. If you want to add scope mid-build, we quote it
       separately rather than quietly extending the invoice.',
80   },
81   {
82     q: 'Do you charge for the first conversation?',
83     a: 'No. The first call is free and ends with an honest answer about whether the workflow is worth
       automating yet. Only the Automation Map, which produces documented deliverables, is paid.',
84   },
85   {
86     q: 'What if you decide our workflow is not worth automating?',
87     a: 'We tell you, and we say why. Talking a company out of a build we could have sold is cheaper
       for us than delivering something that quietly fails to earn its cost.',
88   },
89   {
90     q: 'Who owns the code and the accounts?',
91     a: 'You do, from the first day. Credentials, repositories and infrastructure are in your name, and
       handover includes runbooks and diagrams so another engineer could pick the system up without us.',
92   },
93 ];
94 ---
95
96 <Base title="Pricing" description={description} ogRoute="pricing" schema={schema}>
97   <section class="wrap pt-10 pb-14 md:pt-14">
98     <Breadcrumbs trail=[] current="Pricing" />
```

```

99
100     <p class="eyebrow mt-8">Pricing</p>
101     <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
102         What this costs, before you ask.
103     </h1>
104     <p class="mt-7 max-w-2xl text-lg text-[var(--color-ink-2)]">
105         Fixed scope, fixed price, written down before we start. Most first projects
106         land between <strong class="font-medium text-[var(--color-ink)]">$8,000 and $18,000</strong>.
107     </p>
108 </section>
109
110 <section class="wrap pb-8">
111     <div class="reveal grid gap-px border-y border-[var(--color-line)] bg-[var(--color-line)] lg:grid-
112         cols-3">
113         {
114         pricing.map((tier, i) => (
115             <article data-stagger style={`--i:${i}`} class="flex flex-col bg-[var(--color-paper)] p-7
116             md:p-9">
117                 <p class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">
118                     {String(i + 1).padStart(2, '0')} · {tier.duration}
119                 </p>
120                 <h2 class="mt-4 font-[var(--font-display)] text-2xl">{tier.name}</h2>
121                 <p class="price mt-5">{tier.price}</p>
122                 <p class="mt-2 font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--
123                 color-ink-3)]">
124                     {tier.unit}
125                 </p>
126                 <p class="mt-5 text-[0.95rem] text-[var(--color-ink-2)]">{tier.summary}</p>
127                 <ul class="mt-6 space-y-2.5 border-t border-[var(--color-line)] pt-5">
128                     {tier.includes.map((item) => (
129                         <li class="flex gap-3 text-[0.92rem] text-[var(--color-ink-2)]">
130                             <span class="font-[var(--font-mono)] text-[var(--color-signal)]" aria-hidden="true">

```

```

129         </span>
130         <span>{item}</span>
131     </li>
132     )})
133 </ul>
134 <a
135     href="/contact/"
136     class={`btn mt-7 justify-center ${i === 0 ? 'btn-primary' : 'btn-ghost'}}`
137     >
138     {i === 0 ? 'Start with a Map' : 'Talk it through'}
139 </a>
140 </article>
141 ))
142 }
143 </div>
144 </section>
145
146 <!-- Risk reversal: for a young studio this does the work a testimonial would. -->
147 <section class="border-y border-[var(--color-line)] bg-[var(--color-paper-2)]">
148     <div class="wrap py-14 md:py-18">
149         <div class="grid gap-10 md:grid-cols-[0.8fr_1.2fr]">
150             <div>
151                 <p class="eyebrow">How we keep it fair</p>
152                 <h2 class="mt-4 text-3xl md:text-4xl">The number doesn't move.</h2>
153             </div>
154             <div class="grid gap-8 sm:grid-cols-2">
155                 <div class="border-t border-[var(--color-line)] pt-4">
156                     <h3 class="font-[var(--font-display)] text-xl">Scope is fixed in writing</h3>
157                     <p class="mt-2 text-[0.95rem] text-[var(--color-ink-2)]">
158                         Agreed after the Map, before any building. Overruns are ours to absorb.
159                     </p>
160                 </div>

```

```

161     <div class="border-t border-[var(--color-line)] pt-4">
162         <h3 class="font-[var(--font-display)] text-xl">The Map is credited</h3>
163         <p class="mt-2 text-[0.95rem] text-[var(--color-ink-2)]">
164             If you go ahead with the build, the $2,500 comes off the project fee.
165         </p>
166     </div>
167     <div class="border-t border-[var(--color-line)] pt-4">
168         <h3 class="font-[var(--font-display)] text-xl">You own everything</h3>
169         <p class="mt-2 text-[0.95rem] text-[var(--color-ink-2)]">
170             Code, accounts and documentation in your name from day one. No lock-in.
171         </p>
172     </div>
173     <div class="border-t border-[var(--color-line)] pt-4">
174         <h3 class="font-[var(--font-display)] text-xl">We'll talk you out of it</h3>
175         <p class="mt-2 text-[0.95rem] text-[var(--color-ink-2)]">
176             If a workflow isn't worth automating yet, we say so before you spend.
177         </p>
178     </div>
179 </div>
180 </div>
181 </div>
182 </section>
183
184 <!--
185     Proof directly after the numbers. Price is the moment doubt peaks, and a
186     named client who paid and would say so publicly answers it better than any
187     further explanation of what the tiers include.
188 -->
189 <Testimonials eyebrow="Worth it, per the people who paid" heading="Signed, and checkable." />
190
191 <Faq items={faqs} title="Questions about cost" />
192

```

```

193 <section class="border-t border-[var(--color-line)]">
194   <div class="wrap py-20 text-center md:py-24">
195     <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Start with one workflow.</h2>
196     <p class="mx-auto mt-5 max-w-xl text-[var(--color-ink-2)]">
197       The first conversation is free and ends with an honest answer.
198     </p>
199     <a href="/contact/" class="btn btn-primary mt-8">Map my workflow</a>
200   </div>
201 </section>
202 </Base>
203

```

TS src/pages/rss.xml.ts

```

1 import rss from '@astrojs/rss';
2 import { getCollection } from 'astro:content';
3 import { site } from '../data/site';
4 import type { APIContext } from 'astro';
5
6 export async function GET(context: APIContext) {
7   const posts = (await getCollection('writing', ({ data }) => !data.draft)).sort(
8     (a, b) => b.data.pubDate.valueOf() - a.data.pubDate.valueOf()
9   );
10
11   return rss({
12     title: `${site.name} - Writing`,
13     description:
14       'Notes on operations, automation, integrations and where AI genuinely earns its place.',
15     site: context.site ?? site.domain,
16     items: posts.map((post) => ({
17       title: post.data.title,
18       description: post.data.description,
19       pubDate: post.data.pubDate,

```

```

20     categories: post.data.tags,
21     link: `/writing/${post.id}/`,
22   })),
23   customData: `<language>en-us</language>`,
24 });
25 }
26

```

ASTRO src/pages/services/[slug].astro

```

1  ---
2  import Base from '../../layouts/Base.astro';
3  import Breadcrumbs from '../../components/Breadcrumbs.astro';
4  import Faq from '../../components/Faq.astro';
5  import { services, site, pricing } from '../../data/site';
6  import { getWork } from '../../lib/work';
7
8  export async function getStaticPaths() {
9    return services.map((service) => ({
10      params: { slug: service.slug },
11      props: { service },
12    }));
13  }
14
15  const { service } = Astro.props;
16
17  // Cross-link services to proof. Related work keeps each service page from being
18  // a dead end and spreads authority through the site rather than pooling it.
19  const work = (await getWork()).slice(0, 2);
20
21  const others = services.filter((s) => s.slug !== service.slug);
22  const entry = pricing[0];
23

```

```
24 const schema = [  
25   {  
26     '@type': 'Service',  
27     '@id': `${site.domain}/services/${service.slug}/#service`,  
28     name: service.seoTitle,  
29     alternateName: service.title,  
30     description: service.answer,  
31     serviceType: service.keyword,  
32     provider: { '@id': `${site.domain}/#organization` },  
33     areaServed: site.areaServed,  
34     offers: {  
35       '@type': 'Offer',  
36       priceCurrency: 'USD',  
37       price: entry.priceValue,  
38       description: `${entry.name} – ${entry.duration}, credited against a build.`,  
39       url: `${site.domain}/pricing/`,  
40     },  
41     hasOfferCatalog: {  
42       '@type': 'OfferCatalog',  
43       name: `${service.title} – what that includes`,  
44       itemListElement: service.builds.map((b) => ({  
45         '@type': 'Offer',  
46         itemOffered: { '@type': 'Service', name: b },  
47       })),  
48     },  
49   },  
50   {  
51     '@type': 'FAQPage',  
52     '@id': `${site.domain}/services/${service.slug}/#faq`,  
53     mainEntity: service.faqs.map((f) => ({  
54       '@type': 'Question',  
55       name: f.q,
```



```

56         acceptedAnswer: { '@type': 'Answer', text: f.a },
57     })),
58 },
59 ];
60 ---
61
62 <Base
63     title={service.seoTitle}
64     description={service.answer}
65     ogRoute="services"
66     schema={schema}
67 >
68 <section class="wrap pt-10 pb-12 md:pt-14">
69     <Breadcrumbs trail={[{ label: 'Services', href: '/services/' }]} current={service.title} />
70
71     <p class="eyebrow mt-8">Service {service.index}</p>
72     <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
73         {service.title}
74     </h1>
75
76     <!-- Answer-first: the snippet-eligible paragraph sits directly under the H1. -->
77     <p class="mt-7 max-w-2xl text-lg text-[var(--color-ink-2)]">{service.answer}</p>
78
79     <div class="mt-9 flex flex-wrap items-center gap-3">
80         <a href="/contact/" class="btn btn-primary">Tell us the bottleneck</a>
81         <a href="/pricing/" class="btn btn-ghost">What it costs</a>
82     </div>
83 </section>
84
85 <!-- Qualification: help the reader self-identify before we sell anything. -->
86 <section class="border-y border-[var(--color-line)] bg-[var(--color-paper-2)]">
87     <div class="wrap py-14 md:py-16">

```



```

119     }
120   </ul>
121 </div>
122 </section>
123
124 <Faq items={service.faqs} title={`Questions about ${service.title.toLowerCase()}`} />
125
126 {
127   work.length > 0 && (
128     <section class="wrap border-t border-[var(--color-line)] py-16 md:py-20">
129       <div class="flex flex-wrap items-end justify-between gap-6">
130         <div>
131           <p class="eyebrow">Related work</p>
132           <h2 class="mt-4 text-3xl md:text-4xl">Systems like this, written up.</h2>
133         </div>
134         <a href="/work/" class="btn btn-ghost">All work</a>
135       </div>
136       <div class="mt-10 grid gap-px bg-[var(--color-line)] md:grid-cols-2">
137         {work.map((item) => (
138           <a
139             href={`\work/${item.id}/`}
140             class="group block bg-[var(--color-paper)] p-7 transition-colors hover:bg-[var(--color-
141 paper-2)]"
142             >
143             <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.12em] text-[var(--color-
144 ink-3)]">
145               {item.data.kind.replace('-', ' ')} · {item.data.sector}
146             </p>
147             <h3 class="mt-3 font-[var(--font-display)] text-xl group-hover:text-[var(--color-signal-
148 ink)]">
149               {item.data.title}
150             </h3>
151             <p class="mt-2 text-[0.95rem] text-[var(--color-ink-2)]">{item.data.summary}</p>

```

```
149         </a>
150     )}}
151 </div>
152 </section>
153 )
154 }
155
156 <section class="wrap border-t border-[var(--color-line)] py-14 md:py-16">
157     <p class="eyebrow">Other services</p>
158     <ul class="mt-6 flex flex-wrap gap-2">
159         {
160             others.map((other) => (
161                 <li>
162                     <a
163                         href={` /services/${other.slug} /`}
164                         class="inline-block border border-[var(--color-line)] px-3.5 py-2 font-[var(--font-
165                             mono)] text-[0.8rem] text-[var(--color-ink-2)] transition-colors hover:border-[var(--color-ink)]
166                             hover:text-[var(--color-ink)]"
167                     >
168                         {other.title}
169                     </a>
170                 </li>
171             ))
172         }
173     </ul>
174 </section>
175
176 <section class="border-t border-[var(--color-line)]">
177     <div class="wrap py-20 text-center md:py-24">
178         <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Tell us what's still done by hand.</h2>
179         <p class="mx-auto mt-5 max-w-xl text-[var(--color-ink-2)]">
180             One workflow, honestly described. We'll tell you whether it's worth automating.
181         </p>
```

```
180     <a href="/contact/" class="btn btn-primary mt-8">Map this workflow</a>
181   </div>
182 </section>
183 </Base>
184
```

ASTRO src/pages/services/index.astro

```
1  ---
2  import Base from '../../../layouts/Base.astro';
3  import Breadcrumbs from '../../../components/Breadcrumbs.astro';
4  import Faq from '../../../components/Faq.astro';
5  import { services, site } from '../../../data/site';
6
7  const description =
8    'Flowzora builds workflow automation for growing teams: CRM and revenue operations, marketing
    lifecycle, back-office process automation, support triage, systems integration, and AI agents used
    only where they earn their place.';
9
10 const schema = [
11   {
12     '@type': 'CollectionPage',
13     '@id': `${site.domain}/services/#page`,
14     name: 'Workflow automation services',
15     description,
16     isPartOf: { '@id': `${site.domain}/#website` },
17     mainEntity: {
18       '@type': 'ItemList',
19       itemListElement: services.map((s, i) => ({
20         '@type': 'ListItem',
21         position: i + 1,
22         name: s.seoTitle,
23         url: `${site.domain}/services/${s.slug}/`,
24       })),
```

```

25     },
26   },
27 ];
28
29 const faqs = [
30   {
31     q: 'What does a workflow automation studio actually do?',
32     a: 'We map how work moves through your business today, then build the systems that carry it
        automatically – connecting the tools you already run, removing the manual steps between them, and
        handing over documentation so your team owns the result.',
33   },
34   {
35     q: 'Do we have to replace our existing tools?',
36     a: 'Almost never. Most operational problems are integration problems, not tooling problems, so we
        build around the stack you already pay for. We only recommend replacing something when it genuinely
        cannot do the job.',
37   },
38   {
39     q: 'Where do most companies start?',
40     a: 'With one workflow that visibly costs the team time – usually lead intake, onboarding or an
        approval chain. A single well-chosen system pays for itself and makes the next one easier to scope.',
41   },
42 ];
43 ---
44
45 <Base title="Workflow automation services" description={description} ogRoute="services" schema=
  {schema}>
46   <section class="wrap pt-10 pb-14 md:pt-14">
47     <Breadcrumbs trail={[]} current="Services" />
48
49     <p class="eyebrow mt-8">Services</p>
50
51     <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
52       We start from the problem, not the tool.
53     </h1>
54
55     <p class="mt-7 max-w-2xl text-lg text-[var(--color-ink-2)]">

```

```

54     Every engagement is a system built around how your business actually works.
55     Here's where that work usually lands.
56 </p>
57 <!--
58     A price signal this high up is deliberate. Services is a likely search
59     landing page, and it previously carried no cost information at all – so a
60     reader could work through the whole page without being able to answer
61     "can I afford this", which is the question that decides whether they
62     contact anyone.
63 -->
64 <div class="mt-9 flex flex-wrap items-center gap-3">
65     <a href="/pricing/" class="btn btn-ghost">Builds from $8,000 · see pricing</a>
66 </div>
67 </section>
68
69 <section class="wrap pb-8">
70     <ul class="reveal grid gap-px bg-[var(--color-line)] border-y border-[var(--color-line)] md:grid-
71     cols-2">
72     {
73         services.map((s, i) => (
74             <li data-stagger style={`--i:${i}`} class="bg-[var(--color-paper)]">
75                 <a
76                     href={`/${services}/${s.slug}/`}
77                     class="group flex h-full flex-col p-7 transition-colors hover:bg-[var(--color-paper-2)]
78                     md:p-9"
79                     >
80                     <span class="font-[var(--font-mono)] text-sm text-[var(--color-ink-3)]">{s.index}</span>
81                     <h2 class="mt-3 font-[var(--font-display)] text-2xl transition-colors group-hover:text-
82                     [var(--color-signal-ink)] md:text-[1.75rem]">
83                         {s.title}
84                     </h2>
85                     <p class="mt-3 max-w-md text-[0.98rem] text-[var(--color-ink-2)]">{s.brief}</p>
86                     <span class="mt-6 inline-flex items-center gap-2 font-[var(--font-mono)] text-[0.8rem]
87                     text-[var(--color-ink-3)] transition-colors group-hover:text-[var(--color-signal-ink)]">

```

```

84         How this works
85         <span class="transition-transform group-hover:translate-x-1" aria-hidden="true">
86             →
87         </span>
88     </span>
89 </a>
90 </li>
91 ))
92 }
93 </ul>
94 </section>
95
96 <Faq items={faqs} />
97
98 <section class="border-t border-[var(--color-line)]">
99     <div class="wrap py-20 text-center md:py-24">
100         <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Not sure which of these you need?</h2>
101         <p class="mx-auto mt-5 max-w-xl text-[var(--color-ink-2)]">
102             Most people don't, at first. That's what the mapping conversation is for.
103         </p>
104         <a href="/contact/" class="btn btn-primary mt-8">Tell us the bottleneck</a>
105     </div>
106 </section>
107 </Base>
108

```

ASTRO src/pages/thank-you.astro

```

1  ---
2  import Base from '../layouts/Base.astro';
3  import { site } from '../data/site';
4  ---
5

```



```

6 <Base
7   title="Thanks – we have your workflow"
8   description="Your message reached us. We reply within two working days."
9   noindex={true}
10 >
11 <section class="wrap flex min-h-[60vh] flex-col justify-center py-24 text-center">
12   <p class="eyebrow mx-auto">Received</p>
13   <h1 class="mx-auto mt-6 max-w-2xl text-[2.4rem] leading-[1.05] md:text-[3.2rem]">
14     Got it. We'll read it properly.
15   </h1>
16   <p class="mx-auto mt-7 max-w-xl text-lg text-[var(--color-ink-2)]">
17     A real person replies within two working days – usually with a question or
18     two before we suggest anything.
19   </p>
20   <div class="mx-auto mt-10 flex flex-wrap items-center justify-center gap-3">
21     <a href="/work/" class="btn btn-primary">See how we build</a>
22     <a href="/pricing/" class="btn btn-ghost">What it costs</a>
23   </div>
24   <p class="mx-auto mt-10 font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">
25     Need us sooner? <a href={`mailto:${site.email}`} class="link-underline">{site.email}</a>
26   </p>
27 </section>
28 </Base>
29

```

ASTRO `src/pages/work/[slug].astro`

```

1 ---
2 import Base from '../../layouts/Base.astro';
3 import Breadcrumbs from '../../components/Breadcrumbs.astro';
4 import { getCollection, render } from 'astro:content';
5 import { getWork } from '../../lib/work';
6 import { site } from '../../data/site';

```

```
7
8 export async function getStaticPaths() {
9     const work = await getWork();
10    return work.map((entry) => ({ params: { slug: entry.id }, props: { entry } }));
11 }
12
13 const { entry } = Astro.props;
14 const { Content } = await render(entry);
15 const d = entry.data;
16
17 const kindLabel: Record<string, string> = {
18     client: 'Client project',
19     'internal-build': 'Internal build',
20     concept: 'Concept teardown',
21 };
22
23 const schema = [
24     {
25         '@type': 'Article',
26         '@id': `${site.domain}/work/${entry.id}/#article`,
27         headline: d.title,
28         description: d.summary,
29         about: d.sector,
30         author: { '@id': `${site.domain}/#founder` },
31         publisher: { '@id': `${site.domain}/#organization` },
32         image: `${site.domain}/og/work/${entry.id}.png`,
33         mainEntityOfPage: `${site.domain}/work/${entry.id}/`,
34         // Concept and internal builds are labeled in the markup as well as the UI,
35         // so nothing can read as a client engagement that was not one.
36         creativeWorkStatus: kindLabel[d.kind],
37     },
38 ];
```

```

39 ---
40
41 <Base
42   title={d.title}
43   description={d.summary}
44   ogType="article"
45   ogRoute={`work/${entry.id}`}
46   schema={schema}
47 >
48 <article>
49   <header class="wrap pt-10 pb-10 md:pt-14">
50     <Breadcrumbs trail={[{ label: 'Work', href: '/work/' }]} current={d.title} />
51     <div class="mt-8 inline-flex items-center gap-2 border border-[var(--color-line)] px-3 py-1">
52       <span class="h-1.5 w-1.5 rounded-full bg-[var(--color-signal)]"></span>
53       <span class="font-[var(--font-mono)] text-xs uppercase tracking-[0.1em] text-[var(--color-ink-
60 2)]">
54         {kindLabel[d.kind]} · {d.sector}
55       </span>
56     </div>
57     <h1 class="mt-6 max-w-4xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">{d.title}</h1>
58     <p class="mt-6 max-w-2xl text-lg text-[var(--color-ink-2)]">{d.summary}</p>
59   </header>
60
61   <!-- Result strip -->
62   <section class="border-y border-[var(--color-line)] bg-[var(--color-paper-2)]">
63     <div class="wrap reveal grid gap-px py-2 sm:grid-cols-3">
64       {
65         d.result.map((r, i) => (
66           <div data-stagger style={`--i:${i}`} class="py-6 sm:px-6">
67             <p class="metric text-[var(--color-ink)]" data-count={r.metric}>{r.metric}</p>
68             <p class="mt-1 text-[0.95rem] text-[var(--color-ink-2)]">{r.label}</p>
69             <p class="mt-2 font-[var(--font-mono)] text-[0.68rem] leading-relaxed text-[var(--color-
70 ink-3)]">

```

```

70         {r.source}
71     </p>
72 </div>
73 ))
74 }
75 </div>
76 </section>
77
78 <div class="wrap grid gap-12 py-14 md:grid-cols-[1.3fr_0.7fr] md:py-20">
79     <div class="max-w-2xl">
80         <section>
81             <h2 class="eyebrow">Problem</h2>
82             <p class="mt-3 text-lg text-[var(--color-ink-2)]">{d.problem}</p>
83         </section>
84
85         <section class="mt-12">
86             <h2 class="eyebrow">Before – the manual workflow</h2>
87             <ol class="mt-4 space-y-0 border-l-2 border-[var(--color-line)]">
88                 {
89                     d.before.map((b, i) => (
90                         <li class="relative pl-6 pb-5">
91                             <span class="absolute -left-[7px] top-1.5 h-3 w-3 rounded-full border-2 border-
[var(--color-line)] bg-[var(--color-paper)]"></span>
92                             <span class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">{String(i +
1).padStart(2, '0')}</span>
93                             <p class="text-[var(--color-ink-2)]">{b}</p>
94                         </li>
95                     ))
96                 }
97             </ol>
98         </section>
99
100     <section class="mt-12">

```

```
101     <h2 class="eyebrow">Intervention</h2>
102     <p class="mt-3 text-lg text-[var(--color-ink-2)]">{d.intervention}</p>
103 </section>
104
105     <section class="mt-12 prose-notes">
106         <Content />
107     </section>
108 </div>
109
110 <aside class="md:sticky md:top-24 md:self-start">
111     <div class="border border-[var(--color-line)] p-6">
112         <h2 class="eyebrow">Stack</h2>
113         <ul class="mt-4 space-y-2">
114             {d.stack.map((s) => <li class="font-[var(--font-mono)] text-sm text-[var(--color-ink-2)]">
115 {s}</li>)}
116         </ul>
117         <hr class="rule my-6" />
118         <h2 class="eyebrow">Human impact</h2>
119         <p class="mt-3 text-[0.95rem] text-[var(--color-ink-2)]">{d.humanImpact}</p>
120     </div>
121 </aside>
122
123 <section class="border-t border-[var(--color-line)]">
124     <div class="wrap py-20 text-center md:py-24">
125         <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Have a workflow like this?</h2>
126         <a href="/contact/" class="btn btn-primary mt-8">Map a workflow like this</a>
127     </div>
128 </section>
129 </article>
130 </Base>
131
```

```

132 <style>
133   .prose-notes :global(h2) {
134     font-family: var(--font-display);
135     font-size: 1.5rem;
136     margin-top: 2rem;
137     margin-bottom: 0.5rem;
138   }
139   .prose-notes :global(p) {
140     color: var(--color-ink-2);
141     margin-bottom: 1rem;
142   }
143   .prose-notes :global(blockquote) {
144     border-left: 3px solid var(--color-signal);
145     padding-left: 1rem;
146     font-style: italic;
147     color: var(--color-ink-3);
148     margin: 1.25rem 0;
149   }
150   .prose-notes :global(code) {
151     font-family: var(--font-mono);
152     font-size: 0.85em;
153     background: var(--color-paper-2);
154     padding: 0.1em 0.35em;
155     border-radius: 2px;
156   }
157 </style>
158

```

ASTRO src/pages/work/index.astro

```

1 ---
2 import Base from '../../layouts/Base.astro';
3 import Breadcrumbs from '../../components/Breadcrumbs.astro';

```

```

4 import { getWork } from '../..lib/work';
5
6 const work = await getWork();
7 ---
8
9 <Base
10   title="Work"
11   description="Selected systems Flowzora has built – client work, internal builds and concept
    teardowns, each labeled honestly."
12   ogRoute="work"
13 >
14   <section class="wrap pt-10 pb-12 md:pt-14">
15     <Breadcrumbs trail={[[]] current="Work" />
16     <p class="eyebrow mt-8">Work</p>
17     <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
18       Systems we've built, in the open.
19     </h1>
20     <p class="mt-7 max-w-xl text-lg text-[var(--color-ink-2)]">
21       Each one labeled for exactly what it is. We don't borrow credibility we
22       haven't earned.
23     </p>
24   </section>
25
26   <section class="wrap pb-16">
27     <ul class="reveal border-t border-[var(--color-line)]">
28       {
29         work.map((item, i) => (
30           <li data-stagger style={`--i:${i}`} class="border-b border-[var(--color-line)]">
31             <a
32               href={`/${work}/${item.id}/`}
33               class="group grid gap-4 py-9 md:grid-cols-[1fr_1.4fr] md:gap-10"
34             >

```

```

35         <div>
36             <p class="font-[var(--font-mono)] text-xs uppercase tracking-[0.12em] text-[var(--color-ink-3)]">
37                 {item.data.kind.replace('-', ' ')} · {item.data.sector}
38             </p>
39             <h2 class="mt-3 font-[var(--font-display)] text-2xl transition-colors md:text-3xl group-hover:text-[var(--color-signal-ink)]">
40                 {item.data.title}
41             </h2>
42         </div>
43         <div>
44             <p class="text-[var(--color-ink-2)]">{item.data.summary}</p>
45             <span class="mt-4 inline-flex items-center gap-2 font-[var(--font-mono)] text-sm text-[var(--color-signal-ink)]">
46                 Read the build
47                 <span class="transition-transform group-hover:translate-x-1" aria-hidden="true">
48                     →
49                 </span>
50             </span>
51         </div>
52     </a>
53 </li>
54 ))
55 }
56 </ul>
57 <p class="mt-8 max-w-xl font-[var(--font-mono)] text-xs leading-relaxed text-[var(--color-ink-3)]">
58     Every entry is labeled for what it is. Concept and internal builds are
59     stated as such, and any figure says where it came from.
60 </p>
61 </section>
62
63 <section class="border-t border-[var(--color-line)]">
64     <div class="wrap py-20 text-center md:py-24">

```



```

65     <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Have a workflow like these?</h2>
66     <a href="/contact/" class="btn btn-primary mt-8">Show us yours</a>
67 </div>
68 </section>
69 </Base>
70

```

ASTRO src/pages/writing/[slug].astro

```

1  ---
2  import Base from '../../layouts/Base.astro';
3  import Breadcrumbs from '../../components/Breadcrumbs.astro';
4  import AuthorCard from '../../components/AuthorCard.astro';
5  import { getCollection, render } from 'astro:content';
6  import { site, founder } from '../../data/site';
7
8  export async function getStaticPaths() {
9      const posts = await getCollection('writing', ({ data }) => !data.draft);
10     return posts.map((entry) => ({ params: { slug: entry.id }, props: { entry } }));
11 }
12
13 const { entry } = Astro.props;
14 const { Content } = await render(entry);
15 const d = entry.data;
16 const fmt = (dt: Date) =>
17     dt.toLocaleDateString('en-US', { year: 'numeric', month: 'long', day: 'numeric' });
18
19 // Related reading keeps an article from being a dead end, which is what most
20 // blog posts are. Newest first, excluding the current post.
21 const related = (await getCollection('writing', ({ data }) => !data.draft))
22     .filter((p) => p.id !== entry.id)
23     .sort((a, b) => b.data.pubDate.valueOf() - a.data.pubDate.valueOf())
24     .slice(0, 2);

```

```

25
26 // Attributed to a real person rather than the organization: generative engines
27 // and search both weight a named, verifiable author.
28 const schema = [
29   {
30     '@type': 'Article',
31     '@id': `${site.domain}/writing/${entry.id}/#article`,
32     headline: d.title,
33     description: d.description,
34     datePublished: d.pubDate.toISOString(),
35     dateModified: d.pubDate.toISOString(),
36     keywords: d.tags.join(', '),
37     image: `${site.domain}/og/writing/${entry.id}.png`,
38     mainEntityOfPage: `${site.domain}/writing/${entry.id}/`,
39     author: { '@id': `${site.domain}/#founder` },
40     publisher: { '@id': `${site.domain}/#organization` },
41     isPartOf: { '@id': `${site.domain}/#website` },
42   },
43 ];
44 ---
45
46 <Base
47   title={d.title}
48   description={d.description}
49   ogType="article"
50   ogRoute={`writing/${entry.id}`}
51   schema={schema}
52 >
53 <article class="wrap pt-10 pb-16 md:pt-14">
54   <Breadcrumbs trail={[{ label: 'Writing', href: '/writing/' }]} current={d.title} />
55   <p class="mt-8 font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">
56     <time datetime={d.pubDate.toISOString()}>{fmt(d.pubDate)}</time>

```

```

57     <span aria-hidden="true"> · </span>
58     <span>{founder.name}</span>
59 </p>
60 <h1 class="mt-3 max-w-3xl text-[2.3rem] leading-[1.06] md:text-[3.2rem]">{d.title}</h1>
61 <p class="mt-6 max-w-2xl text-lg text-[var(--color-ink-2)]">{d.description}</p>
62 <hr class="rule mt-10" />
63 <div class="post-body mt-10 max-w-2xl">
64     <Content />
65 </div>
66 <div class="max-w-2xl">
67     <AuthorCard />
68 </div>
69 </article>
70
71 {
72     related.length > 0 && (
73         <section class="wrap border-t border-[var(--color-line)] py-14 md:py-16">
74             <p class="eyebrow">Related reading</p>
75             <ul class="mt-6 grid gap-px border-y border-[var(--color-line)] bg-[var(--color-line)]
md:grid-cols-2">
76                 {related.map((post) => (
77                     <li class="bg-[var(--color-paper)]">
78                         <a
79                             href={` /writing/${post.id} /`}
80                             class="group block h-full p-6 transition-colors hover:bg-[var(--color-paper-2)]"
81                         >
82                             <h2 class="font-[var(--font-display)] text-xl transition-colors group-hover:text-
[var(--color-signal-ink)]">
83                                 {post.data.title}
84                             </h2>
85                             <p class="mt-2 text-[0.95rem] text-[var(--color-ink-2)]">{post.data.description}</p>
86                         </a>
87                     </li>

```

```
88         }}}
89     </ul>
90 </section>
91 )
92 }
93
94 <section class="border-t border-[var(--color-line)]">
95     <div class="wrap py-16 text-center md:py-20">
96         <h2 class="mx-auto max-w-2xl text-2xl md:text-3xl">Want this thinking applied to your operation?
97     </h2>
98         <a href="/contact/" class="btn btn-primary mt-7">Have us build it</a>
99     </div>
100 </section>
101 </Base>
102
103 <style>
104     .post-body :global(h2) {
105         font-family: var(--font-display);
106         font-size: 1.6rem;
107         margin-top: 2.25rem;
108         margin-bottom: 0.6rem;
109         letter-spacing: -0.01em;
110     }
111     .post-body :global(h3) {
112         font-family: var(--font-display);
113         font-size: 1.25rem;
114         margin-top: 1.75rem;
115         margin-bottom: 0.4rem;
116     }
117     .post-body :global(p) {
118         color: var(--color-ink-2);
119         margin-bottom: 1.1rem;
```

```

119     font-size: 1.075rem;
120     line-height: 1.7;
121 }
122 .post-body :global(ul) {
123     margin: 1rem 0 1.4rem;
124     padding-left: 1.1rem;
125     list-style: none;
126 }
127 .post-body :global(li) {
128     position: relative;
129     padding-left: 1.1rem;
130     margin-bottom: 0.5rem;
131     color: var(--color-ink-2);
132 }
133 .post-body :global(li)::before {
134     content: '-';
135     position: absolute;
136     left: 0;
137     color: var(--color-signal);
138     font-family: var(--font-mono);
139 }
140 .post-body :global(strong) {
141     color: var(--color-ink);
142     font-weight: 500;
143 }
144 </style>
145

```

ASTRO `src/pages/writing/index.astro`

```

1 ---
2 import Base from '../../layouts/Base.astro';
3 import Breadcrumbs from '../../components/Breadcrumbs.astro';

```

```

4 import { getCollection } from 'astro:content';
5
6 const posts = (await getCollection('writing', ({ data }) => !data.draft)).sort(
7   (a, b) => b.data.pubDate.valueOf() - a.data.pubDate.valueOf()
8 );
9 const fmt = (d: Date) =>
10   d.toLocaleDateString('en-US', { year: 'numeric', month: 'long', day: 'numeric' });
11 ---
12
13 <Base
14   title="Writing"
15   description="Practical notes on workflow automation, integrations and where AI genuinely helps –
    from a workflow automation studio."
16   ogRoute="writing"
17 >
18 <section class="wrap pt-10 pb-12 md:pt-14">
19   <Breadcrumbs trail=[] current="Writing" />
20   <p class="eyebrow mt-8">Writing</p>
21   <h1 class="mt-5 max-w-3xl text-[2.4rem] leading-[1.05] md:text-[3.4rem]">
22     Notes on systems that don't need babysitting.
23   </h1>
24   <p class="mt-7 max-w-xl text-lg text-[var(--color-ink-2)]">
25     Practical writing about automation, integrations, and where AI actually
26     earns its place.
27   </p>
28 </section>
29
30 <section class="wrap pb-16">
31   <ul class="reveal border-t border-[var(--color-line)]">
32     {
33       posts.map((post, i) => (
34         <li data-stagger style={`--i:${i}`} class="border-b border-[var(--color-line)]">

```

```

35         <a
36             href={`\writing/${post.id}/`}
37             class="group grid gap-3 py-9 md:grid-cols-[10rem_1fr] md:gap-10"
38         >
39             <p class="font-[var(--font-mono)] text-xs text-[var(--color-ink-3)]">
40                 <time datetime={post.data.pubDate.toISOString()}>{fmt(post.data.pubDate)}</time>
41             </p>
42             <div>
43                 <h2 class="font-[var(--font-display)] text-2xl transition-colors group-hover:text-[var(--color-signal-ink)]">
44                     {post.data.title}
45                 </h2>
46                 <p class="mt-2 max-w-2xl text-[var(--color-ink-2)]">{post.data.description}</p>
47                 <div class="mt-3 flex flex-wrap gap-2">
48                     {post.data.tags.map((t) => (
49                         <span class="font-[var(--font-mono)] text-[0.68rem] uppercase tracking-[0.1em]
text-[var(--color-ink-3)]">
50                             #{t}
51                         </span>
52                     ))}
53                 </div>
54             </div>
55         </a>
56     </li>
57 ))
58 }
59 </ul>
60 </section>
61
62 <section class="border-t border-[var(--color-line)]">
63     <div class="wrap py-20 text-center md:py-24">
64         <h2 class="mx-auto max-w-2xl text-3xl md:text-4xl">Rather we just built it?</h2>
65         <a href="/contact/" class="btn btn-primary mt-8">Have us build it</a>

```

```
66     </div>
67 </section>
68 </Base>
69
```

CSS src/styles/global.css

```
1 @import 'tailwindcss';
2
3 /*
4   Self-hosted variable fonts.
5
6   Bundled rather than linked from a font CDN so text paints on the first
7   connection instead of waiting on a third-party round trip. The display serif
8   is the LCP element on nearly every page, so this is the single largest
9   perceived-performance win available here.
10  */
11 @import '@fontsource-variable/fraunces';
12 @import '@fontsource-variable/ibm-plex-sans';
13 @import '@fontsource/ibm-plex-mono/400.css';
14 @import '@fontsource/ibm-plex-mono/500.css';
15
16 /*
17   Metric-matched fallbacks.
18
19   Fontsource ships `font-display: swap`, so the fallback face renders first and
20   is then replaced. Without adjusted metrics that swap shifts every line of text
21   and costs real CLS on the very headings that are the LCP element. These
22   overrides size the system fallback to match the webfont so the swap is close
23   to invisible.
24  */
25 @font-face {
26   font-family: 'Fraunces Fallback';
```



```
27  src: local('Georgia'), local('Times New Roman'), local('serif');
28  size-adjust: 103%;
29  ascent-override: 92%;
30  descent-override: 24%;
31  line-gap-override: 0%;
32  }
33
34  @font-face {
35  font-family: 'Plex Sans Fallback';
36  src: local('Helvetica Neue'), local('Arial'), local('sans-serif');
37  size-adjust: 104%;
38  ascent-override: 95%;
39  descent-override: 25%;
40  line-gap-override: 0%;
41  }
42
43  /*
44  Flowzora design system
45  -----
46  Editorial, ink-on-paper. No gradients, no glow, no glassmorphism.
47  Type: Fraunces (display serif) + IBM Plex Sans (body grotesque) + IBM Plex Mono (system labels).
48  One restrained accent used sparingly for interaction and diagram highlights.
49  */
50
51  @theme {
52  /* Paper / ink neutrals (warm) */
53  --color-paper: #f4f1ea;
54  --color-paper-2: #ece7dc;
55  /*
56  A third surface step. Two tones forced every section to alternate between the
57  same two backgrounds, which is what made long pages read as monotonous; a
58  third lets the rhythm vary without introducing a new hue.
```

```
59  */
60  --color-paper-3: #e2dccd;
61  --color-ink: #17150f;
62  --color-ink-2: #3d3a31;
63  /*
64     Muted text. Darkened from #6b675b so it still clears 4.5:1 against the
65     third surface tone, which is the lowest-contrast background on the site.
66  */
67  --color-ink-3: #605c51;
68  --color-line: #d8d2c4;
69  --color-line-2: #c7c0b0;
70
71  /* Single utilitarian accent: signal rust */
72  --color-signal: #b6431f;
73  --color-signal-ink: #8a3417;
74
75  /* Dark section (used sparingly, not navy, not glowing) */
76  --color-slate: #201d16;
77  --color-slate-2: #2b2820;
78
79  /*
80     Inverted surface scale. A dark band needs the same range of ink levels the
81     light one has. Without these, every dark section carries one-off hex values
82     in the markup and the palette quietly drifts out of the design system.
83  */
84  --color-inverse-ink: #f4f1ea;
85  --color-inverse-ink-2: #cbc6b8;
86  --color-inverse-ink-3: #a8a291;
87  --color-inverse-ink-4: #8a8574;
88  --color-inverse-line: #4a463a;
89  --color-signal-bright: #e0662f;
90
```

```
91  --font-display: 'Fraunces Variable', 'Fraunces Fallback', Georgia, 'Times New Roman', serif;
92  --font-sans: 'IBM Plex Sans Variable', 'Plex Sans Fallback', ui-sans-serif, system-ui,
93    -apple-system, sans-serif;
94  --font-mono: 'IBM Plex Mono', ui-monospace, 'SF Mono', Menlo, monospace;
95
96  --radius: 3px;
97 }
98
99 /*
100  Dark mode.
101
102  The palette is redefined rather than filtered: the same warm ink-on-paper
103  relationship, inverted, so the site reads as the same object at night rather
104  than as a washed-out negative. The accent is lifted because rust at #b6431f
105  does not carry enough contrast against a dark surface.
106
107  Deliberately unlayered. Tailwind emits `@theme` tokens into the `theme` cascade
108  layer, and unlayered rules beat layered ones regardless of order – so this
109  override cannot be silently defeated by a change in layer sequence.
110
111  System preference only, no toggle: honoring the setting a visitor already
112  chose is the expected behavior, and a toggle adds persisted state for no gain.
113 */
114 @media (prefers-color-scheme: dark) {
115   :root {
116     color-scheme: dark;
117
118     --color-paper: #17150f;
119     --color-paper-2: #1e1b14;
120     --color-paper-3: #262219;
121     --color-ink: #f2efe6;
122     --color-ink-2: #c8c3b4;
```

```
123     --color-ink-3: #918b7c;
124     --color-line: #353128;
125     --color-line-2: #423d32;
126
127     --color-signal: #e0662f;
128     --color-signal-ink: #ef8a55;
129
130     /* The inverted band drops darker so it still separates from the page. */
131     --color-slate: #0b0a07;
132     --color-slate-2: #141209;
133     --color-inverse-ink: #f2efe6;
134     --color-inverse-ink-2: #c8c3b4;
135     --color-inverse-ink-3: #918b7c;
136     --color-inverse-ink-4: #6f6a5d;
137     --color-inverse-line: #35312a;
138     --color-signal-bright: #f08b52;
139 }
140 }
141
142 @layer base {
143     :root {
144         color-scheme: light;
145     }
146
147     html {
148         scroll-behavior: smooth;
149         -webkit-text-size-adjust: 100%;
150     }
151
152     /*
153     One global reduced-motion policy, enforced here so individual components do
154     not each have to remember to opt out. Components still scope their own
```

```
155     animations to `prefers-reduced-motion: no-preference` where the static state
156     needs to differ, but this is the backstop.
157 */
158 @media (prefers-reduced-motion: reduce) {
159     html {
160         scroll-behavior: auto;
161     }
162     *,
163     *::before,
164     *::after {
165         animation-duration: 0.001ms !important;
166         animation-iteration-count: 1 !important;
167         transition-duration: 0.001ms !important;
168         scroll-behavior: auto !important;
169     }
170 }
171
172 body {
173     background-color: var(--color-paper);
174     color: var(--color-ink);
175     font-family: var(--font-sans);
176     font-size: 1.0625rem;
177     line-height: 1.6;
178     -webkit-font-smoothing: antialiased;
179     text-rendering: optimizeLegibility;
180 }
181
182 h1,
183 h2,
184 h3,
185 h4 {
186     font-family: var(--font-display);
```

```
187     font-weight: 460;
188     letter-spacing: -0.015em;
189     line-height: 1.05;
190     text-wrap: balance;
191     scroll-margin-top: 5rem;
192 }
193
194 ::selection {
195     background: var(--color-signal);
196     color: var(--color-paper);
197 }
198
199 a {
200     color: inherit;
201     text-underline-offset: 3px;
202 }
203
204 :focus-visible {
205     outline: 2px solid var(--color-signal);
206     outline-offset: 3px;
207     border-radius: 1px;
208 }
209
210 /* Form controls inherit type by default in almost no browser. */
211 input,
212 textarea,
213 select,
214 button {
215     font: inherit;
216     color: inherit;
217 }
218
```

```
219   textarea {
220     resize: vertical;
221     min-height: 8rem;
222   }
223
224   ::placeholder {
225     color: var(--color-ink-3);
226     opacity: 1;
227   }
228 }
229
230 @layer components {
231   .wrap {
232     width: 100%;
233     max-width: 76rem;
234     margin-inline: auto;
235     padding-inline: 1.5rem;
236   }
237
238   @media (min-width: 768px) {
239     .wrap {
240       padding-inline: 2.5rem;
241     }
242   }
243
244   /* Small uppercase mono label – the engineering signature */
245   .eyebrow {
246     font-family: var(--font-mono);
247     font-size: 0.75rem;
248     letter-spacing: 0.14em;
249     text-transform: uppercase;
250     color: var(--color-ink-3);
```

```
251 }
252
253 .rule {
254     border: 0;
255     border-top: 1px solid var(--color-line);
256 }
257
258 /*
259     The one oversized typographic moment per page. Editorial layouts earn
260     attention through scale contrast, and without a step well above the heading
261     scale every section ends up shouting at the same volume.
262 */
263 .display {
264     font-family: var(--font-display);
265     font-weight: 460;
266     font-size: clamp(2.6rem, 7.5vw, 5.5rem);
267     line-height: 0.98;
268     letter-spacing: -0.03em;
269     text-wrap: balance;
270 }
271
272 /* Large figures used for proof. Tabular so digits do not jitter while counting. */
273 .metric {
274     font-family: var(--font-display);
275     font-size: clamp(2.2rem, 4.5vw, 3.2rem);
276     line-height: 1;
277     letter-spacing: -0.02em;
278     font-variant-numeric: tabular-nums;
279 }
280
281 /*
282     Prices, deliberately smaller than `.metric`. A range like "$8,000 – $18,000"
```



```
283     wraps to two lines at the proof scale, which makes one card taller than its
284     neighbours and inflates the whole row. This size keeps every tier on one
285     line, so the cards stay level and the section stops shouting.
286 */
287 .price {
288     font-family: var(--font-display);
289     font-size: clamp(1.75rem, 2.6vw, 2.15rem);
290     line-height: 1.05;
291     letter-spacing: -0.02em;
292     font-variant-numeric: tabular-nums;
293     text-wrap: nowrap;
294 }
295
296 .btn {
297     display: inline-flex;
298     align-items: center;
299     gap: 0.5rem;
300     font-family: var(--font-mono);
301     font-size: 0.8125rem;
302     letter-spacing: 0.02em;
303     padding: 0.7rem 1.15rem;
304     border-radius: var(--radius);
305     border: 1px solid var(--color-ink);
306     text-decoration: none;
307     cursor: pointer;
308     transition: background-color 0.18s ease, color 0.18s ease, border-color 0.18s ease,
309         transform 0.08s ease;
310 }
311 /* A small press response – the only physical feedback the interface gives. */
312 .btn:active {
313     transform: translateY(1px);
314 }
```

```
315 .btn:disabled {
316     opacity: 0.55;
317     cursor: not-allowed;
318 }
319 .btn:disabled:active {
320     transform: none;
321 }
322
323 .btn-primary {
324     background: var(--color-ink);
325     color: var(--color-paper);
326 }
327 .btn-primary:hover {
328     background: var(--color-signal);
329     border-color: var(--color-signal);
330 }
331
332 .btn-ghost {
333     background: transparent;
334     color: var(--color-ink);
335 }
336 .btn-ghost:hover {
337     background: var(--color-ink);
338     color: var(--color-paper);
339 }
340
341 /*
342     An underline that draws in on hover rather than switching color. Uses a
343     background gradient instead of text-decoration so the line can be animated
344     at all, and sits below the baseline where a real rule would.
345 */
346 .link-underline {
```

```
347     text-decoration: none;
348     background-image: linear-gradient(var(--color-signal), var(--color-signal));
349     background-repeat: no-repeat;
350     background-position: 0 100%;
351     background-size: 0% 1px;
352     padding-bottom: 2px;
353     box-shadow: inset 0 -1px 0 0 var(--color-line-2);
354     transition: background-size 0.28s cubic-bezier(0.22, 1, 0.36, 1), color 0.2s ease;
355 }
356 .link-underline:hover {
357     background-size: 100% 1px;
358     color: var(--color-signal-ink);
359 }
360 }
361
362 /* Reveal-on-scroll: opt-in, and disabled under reduced motion */
363 @media (prefers-reduced-motion: no-preference) {
364     .reveal {
365         opacity: 0;
366         transform: translateY(14px);
367         transition: opacity 0.6s ease, transform 0.6s ease;
368     }
369     .reveal.is-in {
370         opacity: 1;
371         transform: none;
372     }
373
374     /*
375     Staggered children.
376
377     The delay is driven by an index custom property set in markup rather than by
378     nth-child rules, so a list of any length staggers correctly without the CSS
```

```
379     needing to know how many items exist. Capped at 6 steps: past that the last
380     item arrives so late it reads as a bug rather than as choreography.
381     */
382     .reveal.is-in > [data-stagger],
383     .reveal.is-in [data-stagger] {
384         animation: fz-rise 0.55s cubic-bezier(0.22, 1, 0.36, 1) both;
385         animation-delay: calc(min(var(--i, 0), 6) * 70ms);
386     }
387 }
388
389 /*
390 View transitions
391 -----
392 A short cross-fade with a small lift. Long enough to register as one continuous
393 surface, short enough that it never delays a click.
394 */
395 @media (prefers-reduced-motion: no-preference) {
396     ::view-transition-old(root) {
397         animation: fz-vt-out 0.18s cubic-bezier(0.4, 0, 1, 1) both;
398     }
399     ::view-transition-new(root) {
400         animation: fz-vt-in 0.28s cubic-bezier(0.22, 1, 0.36, 1) both;
401     }
402 }
403 @media (prefers-reduced-motion: reduce) {
404     ::view-transition-old(root),
405     ::view-transition-new(root) {
406         animation: none;
407     }
408 }
409 @keyframes fz-vt-out {
410     to { opacity: 0; }
```

```
411 }

412 @keyframes fz-vt-in {

413   from { opacity: 0; transform: translateY(8px); }

414   to { opacity: 1; transform: none; }

415 }

416

417 /*

418   Motion primitives

419   -----

420   The site should feel like automation quietly *running* – not decorated.

421   Every animation below is ambient, low-amplitude, and fully disabled under

422   prefers-reduced-motion. No parallax hijack, no scroll-jacking.

423 */

424

425 /* A small live-status dot: something is running */

426 .fz-live {

427   display: inline-flex;

428   align-items: center;

429   gap: 0.5rem;

430   font-family: var(--font-mono);

431   font-size: 0.72rem;

432   letter-spacing: 0.12em;

433   text-transform: uppercase;

434   color: var(--color-ink-3);

435 }

436 .fz-live__dot {

437   width: 7px;

438   height: 7px;

439   border-radius: 50%;

440   background: var(--color-signal);

441   box-shadow: 0 0 0 0 color-mix(in srgb, var(--color-signal) 60%, transparent);

442 }
```

```
443
444 @keyframes fz-rise {
445     from { opacity: 0; transform: translateY(12px); }
446     to { opacity: 1; transform: none; }
447 }
448 @keyframes fz-blink {
449     0%, 100% { opacity: 1; }
450     50% { opacity: 0.35; }
451 }
452 @keyframes fz-ping {
453     0% { box-shadow: 0 0 0 0 color-mix(in srgb, var(--color-signal) 55%, transparent); }
454     70% { box-shadow: 0 0 0 7px color-mix(in srgb, var(--color-signal) 0%, transparent); }
455     100% { box-shadow: 0 0 0 0 color-mix(in srgb, var(--color-signal) 0%, transparent); }
456 }
457 @keyframes fz-marquee {
458     from { transform: translateX(0); }
459     to { transform: translateX(-50%); }
460 }
461 @keyframes fz-dash {
462     to { stroke-dashoffset: -1000; }
463 }
464
465 @media (prefers-reduced-motion: no-preference) {
466     .fz-live__dot { animation: fz-ping 2.4s ease-out infinite; }
467 }
468 @media (prefers-reduced-motion: reduce) {
469     .reveal { opacity: 1; transform: none; }
470 }
471
```

```
1 import { describe, it, expect, vi, beforeEach, afterEach } from 'vitest';

2 import handler from '../api/contact.js';

3

4 /**

5  * The contact endpoint is the only piece of real logic on an otherwise static

6  * site, and it is the one path that handles untrusted input and real leads.

7  * These cover the cases that would silently lose an inquiry or let something

8  * unpleasant through.

9  */

10

11 function mockRes() {

12   const res = {

13     statusCode: null,

14     body: null,

15     headers: {},

16     setHeader(k, v) {

17       this.headers[k] = v;

18     },

19     status(code) {

20       this.statusCode = code;

21       return this;

22     },

23     json(payload) {

24       this.body = payload;

25       return this;

26     },

27     end() {

28       return this;

29     },

30   };

31   return res;
```

```
32 }  
33  
34 const validBody = {  
35   name: 'Dana Reyes',  
36   email: 'dana@example.com',  
37   company: 'Northwind Logistics',  
38   team: '11-50',  
39   workflow: 'Leads arrive by email and someone retypes them into HubSpot.',  
40 };  
41  
42 beforeEach(() => {  
43   process.env.RESEND_API_KEY = 'test-key';  
44   process.env.CONTACT_TO = 'inbox@example.com';  
45   vi.stubGlobal(  
46     'fetch',  
47     vi.fn(async () => ({ ok: true, text: async () => '' })))  
48   );  
49 });  
50  
51 afterEach(() => {  
52   vi.unstubAllGlobals();  
53   vi.restoreAllMocks();  
54 });  
55  
56 describe('contact endpoint', () => {  
57   it('rejects non-POST requests', async () => {  
58     const res = mockRes();  
59     await handler({ method: 'GET', headers: {}, body: {} }, res);  
60     expect(res.statusCode).toBe(405);  
61     expect(res.headers.Allow).toBe('POST');  
62   });  
63
```



```
64   it('requires name, email and workflow', async () => {
65       const res = mockRes();
66       await handler({ method: 'POST', headers: {}, body: { name: 'Dana' } }, res);
67       expect(res.statusCode).toBe(400);
68   });
69
70   it('rejects a malformed email address', async () => {
71       const res = mockRes();
72       await handler(
73           { method: 'POST', headers: {}, body: { ...validBody, email: 'dana@example' } },
74           res
75       );
76       expect(res.statusCode).toBe(400);
77   });
78
79   it('accepts a valid submission and sends exactly one message', async () => {
80       const res = mockRes();
81       await handler(
82           { method: 'POST', headers: { accept: 'application/json' }, body: validBody },
83           res
84       );
85       expect(res.statusCode).toBe(200);
86       expect(res.body).toEqual({ ok: true });
87       expect(fetch).toHaveBeenCalledTimes(1);
88   });
89
90   it('silently accepts honeypot submissions without sending mail', async () => {
91       const res = mockRes();
92       await handler(
93           {
94               method: 'POST',
95               headers: {},
```

```
96     body: { ...validBody, company_website: 'http://spam.example' },
97   },
98   res
99 );
100 // 200 so the bot believes it succeeded and does not retry with a new shape.
101 expect(res.statusCode).toBe(200);
102 expect(fetch).not.toHaveBeenCalled();
103 });
104
105 it('escapes HTML so a submission cannot inject markup into the email', async () => {
106   const res = mockRes();
107   await handler(
108     {
109       method: 'POST',
110       headers: { accept: 'application/json', 'x-forwarded-for': '203.0.113.9' },
111       body: { ...validBody, name: '<script>alert(1)</script>' },
112     },
113     res
114   );
115   const sent = JSON.parse(fetch.mock.calls[0][1].body);
116   expect(sent.html).not.toContain('<script>');
117   expect(sent.html).toContain('&lt;script&gt;');
118 });
119
120 it('rate limits repeated submissions from one address', async () => {
121   const headers = { accept: 'application/json', 'x-forwarded-for': '198.51.100.7' };
122   let last;
123   for (let i = 0; i < 7; i += 1) {
124     last = mockRes();
125     await handler({ method: 'POST', headers, body: validBody }, last);
126   }
127   expect(last.statusCode).toBe(429);
```

```

128 });
129
130 it('fails loudly rather than silently when not configured', async () => {
131     delete process.env.RESEND_API_KEY;
132     vi.spyOn(console, 'error').mockImplementation(() => {});
133     const res = mockRes();
134     await handler(
135         { method: 'POST', headers: { accept: 'application/json' }, body: validBody },
136         res
137     );
138     expect(res.statusCode).toBe(500);
139 });
140
141 it('redirects a no-JS submission to the thank-you page', async () => {
142     const res = mockRes();
143     await handler(
144         { method: 'POST', headers: { 'x-forwarded-for': '192.0.2.44' }, body: validBody },
145         res
146     );
147     expect(res.statusCode).toBe(303);
148     expect(res.headers.Location).toBe('/thank-you/');
149 });
150 });
151

```

JSON tsconfig.json

```

1 {
2     "extends": "astro/tsconfigs/strict",
3     "include": [".astro/types.d.ts", "**/*"],
4     "exclude": ["dist"]
5 }

```

JSON vercel.json

```
1 {
2   "$schema": "https://openapi.vercel.sh/vercel.json",
3   "cleanUrls": true,
4   "trailingSlash": true,
5   "headers": [
6     {
7       "source": "/(.*)",
8       "headers": [
9         { "key": "X-Content-Type-Options", "value": "nosniff" },
10        { "key": "Referrer-Policy", "value": "strict-origin-when-cross-origin" },
11        { "key": "X-Frame-Options", "value": "SAMEORIGIN" },
12        {
13          "key": "Permissions-Policy",
14          "value": "camera=(), microphone=(), geolocation=(), interest-cohort=()"
15        },
16        {
17          "key": "Strict-Transport-Security",
18          "value": "max-age=63072000; includeSubDomains; preload"
19        }
20      ]
21    },
22    {
23      "source": "/og/(.*)",
24      "headers": [
25        { "key": "Cache-Control", "value": "public, max-age=31536000, immutable" }
26      ]
27    },
28    {
29      "source": "/_astro/(.*)",
```

```
30     "headers": [  
31         { "key": "Cache-Control", "value": "public, max-age=31536000, immutable" }  
32     ]  
33 }  
34 ]  
35 }  
36
```