FOUR MFS20D




California C.A.R.B three star rating for ultra-low emissions.

Specifications			
Туре		Four Stroke	
Maximum output	KW (PS)	14.7 (20)	
Maximum operating range	r/min	5400-6100	
Fuel consumption at W.O.T	L/Hr (ga l /Hr)	6.2 (1.64)	
Number of cylinder		2	
Bore x Stroke	mm (in)	61x60 (2.40x2.36)	
Displacement	ml (Cu in)	351 (21.41)	
Engine lubrication system		Trochoid pump	
Starting system		Manual or Electric starter	
Spark plug		NGK DCPR6E	
Ignition timing	degree	BTDC5°- BTDC35°	
Alternator output		12V 145W 12A	
Engine oil		Tohatsu 4-Stroke Engine Oil	
Engine oil capacity	L (qt)	1 (1.06)	
Fuel tank capacity	L (ga l)	12 (3.17)	
Speed control		Twist grip type or Remote control	
Gear reduction ratio		2.15 (13:28)	
Emission Compliance		EU & EPA & CARB 3-Star	

Specifications and descriptions are subject to change without notice.

Dimensions



Dry Weig	ht (kg	g/lb	os)

Model	MF	EF	EP	EFT	EPT
Transom S:	52.0 (115)	55.5 (122)	54.5 (120)	62.5 (138)	61.5 (136)
Transom L:	53.5 (118)	57.0 (126)	56.0 (123)	64.0 (141)	63.0 (139)

Dimensions (mm/in)

Model	Α	В	С
Transom S:	1085 (42.7)	413 (16.3)	740 (29.1)
Transom L:	1235 (48.6)	562 (22.1)	876 (34.5)

Standard & Optional Equipments					
Туре	S/L	EFS/L	EPS/L	EFTS/EFTL	EPTS/L
Electric Starter	-	•	•	•	•
Manual Recoil Starter	•	•	•	•	•
Decompression Release	•	•	•	•	•
Engine Stop Switch Lanyard	•	•	•	•	•
Alternator	•	•	•	•	•
Rectifier	\circ	•	•	•	•
Power Tilt	-	-	-	•	•
Transom	15/20	15/20	15/20	15/20	15/20
Propeller	•	•	•	•	•
Analog Tachometer	-	-	0	-	0
Analog Trim Meter	-	-	-	-	0
Remote Control Box	-	-	•	-	•
12L (3.1 Gal) Plastic Fuel Tank	•	•	•	•	•
Tool Kit	•	•	•	•	•
Emergency Starter Rope	•	•	•	•	•
Spare Spark Plug	•	•	•	•	•
Owners Manual	•	•	•	•	•

StandardOptional



2-Cylinder



Alternator



Charging System (Electric Model)



Thermostat



Manual Start Back-Up



Throttle Friction



Front Shift Control



Simple Steering Friction Lever



Power Tilt



High Solid Paint Coating



Dual Water Intake