

Introduction	AUTHENTICATION			AUTHENTICATION SNAP	
	OAuth2.0	Signature	Headers	OAuth2.0 (SNAP)	Signature (SNAP)

Introduction

API Updated: March 17th, 2025

- New API: QRIS CPM

Try our APIs using Sandbox. We provide sandbox with dummy and static datas. All the parameter value that can be used to try our sandbox are written on the blue box in this [Documentation](#).

AUTHENTICATION

OAuth2.0

BCA APIs is using OAuth 2.0 as the authorization framework. To get the access token, you need to be authorized by `client_id` and `client_secret`. To learn more about the OAuth 2.0 authorization framework, you can read the [RFC6749 Documentation](#).

`client_secret` and `client_id` are used for authentication using OAuth 2.0. You can generate `client_id` and `client_secret` after sign in and create application.

Do not share your `client_secret`!
This token act like password, keep it secret and secure, should anyone obtain this information, immediately reset or revoke your **`client_secret`**.

Access Token

`access_token` is an opaque string token that identify the user of the API. This token is required each time an application call API. There are several way to obtain an `access_token`, which will be described bellow.

Access token must be stored in a secure storage!
Since access_token is portable which mean that once its obtained any request with valid credentials will be considered valid, any agent (mobile device, web browser, or server) could call API requests.

Obtaining Access Token

Access token can be obtained in many way, depend on the grant_type of the application. To access all the services in this sandbox, you will need the access token with grant_type = client_credentials.

Client Credentials Grant

client_credentials grant will provide application access to API without requiring any user credential. Any call requested using access_token obtained using this method are made on behalf of the application instead of the user.

This grant type is designed to be used by server to server call. In order to obtain access_token a request must be made with following specification

Request

Setting	Value
HTTP Method	POST
Path	/api/oauth/token
Host	sandbox.bca.co.id

Request Headers

Name	Format	Mandatory	Description
Authorization	Basic base64(client_id:client_secret)	Yes	
Content-Type	application/x-www-form-urlencoded	Yes	

Request

Field	Data Type	Mandatory	Description
grant_type	String	Yes	value = client_credentials

Result of the request will contains following information:

Response

Field	Data Type	Description
access_token	String	your access_token

token_type	String	default is Bearer
expires_in	String	access_token validity, in seconds
scope	String	application scope/permission granted to application

EXAMPLE

Request



```
1 Request sample
2 curl https://api.klikbca.com/api/oauth/token \
3 -H "Content-Type: application/x-www-form-urlencoded" \
4 -H "Authorization: Basic
5 jk5ZTkyYzgtYzAzNC00YmNhLWE0OTAtYWM4NGl0YTZiMjQxOjNmYWlwNGl1LWM4ODctNGZmM
6 i05OGNkLTE1YjJmYTcyNzA1NA==" \
7 -d "grant_type=client_credentials"
```

EXAMPLE

Response



```
1 Response sample
2 {
3   "access_token":"2YotnFZFEjr1zCsicMWpAA",
4   "token_type":"bearer",
5   "expires_in":3600,
6   "scope":"resource.WRITE resource.READ"
7 }
```

Signature

Signature is used by BCA to verify that your request is not altered by attackers.

The outline of the HMAC validation process is as follows:

1. Retrieve Timestamp from HTTP Header (X-BCA-Timestamp)
2. Retrieve the API Key from HTTP Header (X-BCA-Key)
3. Lookup the API Secret corresponding to the received key in internal store
4. Retrieve client HMAC from HTTP Header lowercase hexadecimal format (X-BCA-Signature)
5. Calculate HMAC using the API Secret as the HMAC secret key
6. Compare client HMAC with calculated HMAC

If HMAC hash comparison is invalid API Gateway will return a HTTP 400 error code with "HMAC Mismatch" message.

API Key and API Secret are used for hashing HMAC. You can generate API Key and API Secret after sign in and create application.

Generate Signature

SHA-256 HMAC is used to generate the signature with your API secret as the key.

Signature = HMAC-SHA256(apiSecret, StringToSign)

The StringToSign will be a colon-separated list derived from some request data as below:

StringToSign =
HTTPMethod+":"+RelativeUrl+":"+AccessToken+":"+Lowercase(HexEncode(SHA-
256(RequestBody)))+":"+Timestamp

For GET request (with no RequestBody), you still need to calculate SHA-256 of an empty string.

Details about the data used to derived The StringToSign is explained in the next sections.

HTTP Method

- HTTP Method is HTTP Method such as GET, POST, PUT, PATCH, DELETE.
- HTTP Method must be given in upper case.

Relative URL

- Relative URL is the URL after the hostname & port number.
- Relative URL also includes the query string and must begin with a slash character. Example

Timestamp

The timestamp must be presented in ISO8601 format (yyyy-MM-ddTHH:mm:ss.SSSTZD)

Format	Description
yyyy	four-digit year
MM	two-digit month (01=January, etc.)
dd	two-digit day of month (01 through 31)
T	literal 'T' as date and time separator
HH	two digits of hour (00 through 23) (am/pm NOT allowed)
mm	two digits of minute (00 through 59)
s	two digits of second (00 through 59)
SSS	three digits representing millisecond (000 through 999)
TZD	time zone designator (+hh:mm or -hh:mm)

Request



Response



Headers

To successfully communicate with BCA Banking API, you **must provide** the following headers **in every API request**:

Name	Type	Description
Authorization	Alphanumeric	OAuth2.0 Token Format value: Bearer {access_token}
Content-Type	Alphanumeric	Content of your request body e.g. application/json
Origin	url	Origin domain e.g. yourdomain.com
X-BCA-Key	Alphanumeric	Your API Key generated by BCA
X-BCA-Timestamp	yyyy-MM-ddTHH:mm:ss.SSSTZD (ISO 8601)	Timestamp generated by merchant in ISO 8601 e.g. "2016-02-03T10:00:00.000+07:00"
X-BCA-Signature	Alphanumeric	Signature, please refer to section above

Request



Response



AUTHENTICATION SNAP

OAuth2.0 (SNAP)

The BCA Corporate Banking API is using OAuth 2 as the authorization framework. To access all the services you'll need the access token with `grantType=client_credentials`. To get the access token, you need to be authorized by `client_id`. To learn more about the OAuth 2 authorization framework you can read the [rfc6749](https://tools.ietf.org/html/rfc6749) documentation (<https://tools.ietf.org/html/rfc6749>).

```
POST /openapi/v1.0/access-token/b2b HTTP/1.1
Host: server.example.com
X-TIMESTAMP : DateTime with timezone, which follows the ISO-8601 standard
X-CLIENT-KEY : client_id
X-SIGNATURE : Signature Asymmetric
Content-Type : application/json
{
  "grantType": "client_credentials"
}
```

OAuth2.0 (SNAP)

Request



```
1  curl https://sandbox.bca.co.id/openapi/v1.0/access-token/b2b \
2  -H "X-TIMESTAMP: 2022-04-21T17:34:52+07:00" \
3  -H "X-CLIENT-KEY: 123" \
4  -H "X-SIGNATURE:
5  cJCDsRIf8FIXGs28uVFhxBuRhGv/xEnMOxargNqkTwvgMqDMdyEfwqQ2PIFz891K0LE81dgN
6  b2CEsJrGAG7tRTur68A0YEHpx8iXXWHD40+iSCgBa8o3QsVBB1ryP1d8FV+dMEeixUKw08fh
7  QCsN1vqlJhPyZFkg2r3Sr8h+dzG4t7ldr7fTkO7wvEFT4LG9kTAEDqPNPW1P8bZqdHZUe6VD
8  zqlUWO12Zu2wHofuzRjvXXVYDm1/lwhDmdJqVrvi9g8L5/PmLnzGkjcnIJlpBGYYkGE0eA25
9  bOdJEWdaklQjQDrFg+G8PI4EnY3PXW1/u7ZwGU13mVy1kvUw801Yw==" \
10 -H "Content-Type: application/json" \
11 -d "{
12   "grantType": "client_credentials"
13 }
```

OAuth2.0 (SNAP)

Response



```

1  {
2  "responseCode": "2007300",
3  "responseMessage": "Successful",
4  "accessToken": "7t4tbXnlyn4NABRn0FAhB69CRhxghlPPfPK2I9quE29I4D4k5DLH57",
5  "tokenType": "bearer",
6  "expiresIn": "900"
7  }

```

Signature (SNAP)

Signature Asymmetric

Signature asymmetric is used by BCA to verify that your access token request is not altered by attackers.

The outline of the RSA validation process is as follows:

1. Retrieve Timestamp from HTTP Header (X-TIMESTAMP)
2. Retrieve the Client Key form HTTP Header (X-CLIENT-KEY)
3. Retrieve client RSA signature value in base64 from HTTP Header (X-SIGNATURE)
4. Generate StringToSign from Client ID and Timestamp
5. Validate RSA signature using the Public Key, clear text (stringToSign), and signature value

If RSA signature validation is failed, API Gateway will return a HTTP 401 error code together with the following error message on JSON format:

```

{
  "responseCode" : "4017300",
  "responseMessage" : "Unathorized. [Signature]"
}

```

If the RSA signature validation is passed, the signature is considered valid.

Generate Signature Asymmetric

SHA256withRSA is used to generate the signature with your Private Key as the key

```
X-SIGNATURE = SHA256withRSA(PrivateKey, StringToSign)
```

Note = X-SIGNATURE should be encoded by Base64

The StringToSign will be a colon-separated list derived from some request data as below :

```
StringToSign = client_ID+"|" +X-TIMESTAMP
```

Details about the data used to derived The StringToSign is explained in the next sections.

Note : **Partner need to send their public key in x.509 format for BCA to use when verifying signature**

Sample public key in x.509 format :

```

-----BEGIN PUBLIC KEY-----
MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEAomV+Vm1xIRXanmh108Kusls7SSKec0oCejtc9QG
Obpd4RnQ+7gihm2k6etnSNP7b+XrpY+fBkiQNaBlinii9M10kW9Bhf/M9GH/edL3lqnzDNSi7tcoQgnO7h8x
mzLNWHTjtR6bkrdsBS5dry6htotaF5KXomuoYgztCdGDOa0W20aeLzYSXloW7s/Ay5ylXt0xaXTII3/bmez
leguFPnwQQzq5EqZFWIUZvutDi+f2I9rTRYOFb64y+VAF+mnIbEovGqsPEeF/p97YWxcY7CWm8NsT0IwBVOt
kmEI967Brz5yvEOBf5bJgVodi6mNVsN1ki0MCitIhYO8shcE7eUilQIDAQAB

```

```
-----END PUBLIC KEY-----
```

Signature Symmetric

Signature is used by BCA to verify that your open api service request is not altered by attackers.

The outline of the HMAC validation process is as follows:

1. Retrieve Timestamp from HTTP Header (X-TIMESTAMP)
2. Lookup the Client Secret corresponding to the received key in internal store
3. Retrieve client HMAC from HTTP Header lowercase base64 format (X-SIGNATURE)
4. Calculate HMAC using the Client Secret as the HMAC secret key
5. Compare client HMAC with calculated HMAC

If HMAC hash comparison is invalid API Gateway will return a HTTP 401 error code together with the following error message on JSON format:

```
{
  "responseCode" : "401xx00",
  "responseMessage" : " Unauthorized. [Signature]",
  "data" : {}
}
```

Note : xx -> customize to each service code

If the HMAC calculation is successful and the calculated value matches the value received from the client, the signature is considered valid.

Generate Signature Symmetric

SHA-512 HMAC is used to generate the signature with your Client Secret as the key.

```
X-SIGNATURE = HMAC-SHA512(ClientSecret, StringToSign)
```

Note = X-SIGNATURE should be encoded by Base64

The StringToSign will be a colon-separated list derived from some request data as below :

```
StringToSign = HTTPMethod+":"+RelativeUrl+":"+AccessToken+":"+
Lowercase(HexEncode(SHA-256(MinifyJson(RequestBody))))+":"+Timestamp
```

HexEncode are optional to use, use it if the SHA-256 returns a binary stream.

Details about the data used to derived The StringToSign is explained in the next sections.

HTTP Method

- HTTP Method is HTTP Method such as GET, POST, PUT, PATCH, DELETE.
- HTTP Method must be given in upper case.

Relative URL

- Relative URL is the URL after the hostname & port number.
- Relative URL also includes the query string and must begin with a slash character. Example :

Full URL	Relative URL
https://example.com/api/v2/sample? param1=value	/api/v2/sample?param1=value1&pa ram2=value2
https://example.com or https://example.com/	/

- The Relative URL must be URI-encoded according to the following rules:
 1. Do not URI-encode forward slash (/) if it was used as path component.
 2. Do not URI-encode question mark (?), equals sign (=), and ampersand (&) if they were used as query string component: as separator between the path and query string, between query parameter and its value, and between each query parameter and value pairs.
 3. Do not URI-encode these characters: A-Z, a-z, 0-9, hyphen (-), underscore (_), period (.), and tilde (~) which are defined as unreserved characters in RFC 3986. As for RFC 3986, means that comma that appear in the value of query params or path params should be encoded too when generating Signature.
 4. Percent-encode all other characters not meeting the above conditions using the format: %XY, where X and Y are hexadecimal characters (0-9 and uppercase A-F). For example, the space character must be encoded as %20 (not using '+', as some encoding schemes do) and extended UTF-8 characters must be in the form %XY%ZA%BC.
- The query string parameters must be re-ordered according to the following rules:

Sorted by parameter name lexicographically

If there are two or more parameters with the same name, sort them by parameter values.

Relative URL	Sorted Relative URL
/api/v2/sample?A-param=value1&Zparam=value2&B-param=value3	/api/v2/sample?A-param=value1&Bparam=value3&Z-param=value2

AccessToken

- AccessToken is an OAuth 2 access token retrieved from the HTTP "Authorization" header.
- AccessToken has a validity time of 900 seconds

RequestBody

- RequestBody need to be hashed with SHA-256.
- Before hashed with SHA-256, RequestBody must to convert to MinifyJSON (remove whitespace except for the key or value json)
- If the RequestBody is empty, set it to empty string. .

Timestamp

The timestamp must be presented in ISO8601 format (YYYY-MM-DDThh:mm:ssTZD)

YYYY = four-digit year

MM = two-digit month (01=January, etc.)

DD = two-digit day of month (01 through 31)

T = literal 'T' as date and time separator

hh = two digits of hour (00 through 23) (am/pm NOT allowed)

mm = two digits of minute (00 through 59)

ss = two digits of second (00 through 59)

TZD = time zone designator (Z or +hh:mm or -hh:mm)

Headers (SNAP)

1. Headers

To successfully communicate with BCA Banking Open API, you must provide the following headers in every API request :

Request

Name	Type	Length	Mandatory	Description
Authorization	AN	N/A	Y	Represents access_token of a request, String starts with keyword “Bearer” followed by accessToken
Content-Type	AN	16 (Fixed Length)	Y	Content of you request body e.g. application/json
X-TIMESTAMP	yyyy-MMddThh:mi:ssTZD (ISO 8601)	25 (Fixed Length)	Y	Client’s current local time in yyyy-MM-ddTHH:mm:ssTZD format
X-SIGNATURE	AN	N/A	Y	Signature Symmetric, please refer to Signature section
ORIGIN		N/A	N	Origin Domain www.yourdomain.com
X-EXTERNAL-ID		36 (Max Length)	Y	Numeric String Reference number that should be unique in the same day

Errors

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)
400	4007300	Invalid field format [clientId/clientSecret/grantType]
400	4007300	Unauthorized. [Connection not allowed]
400	4007301	Invalid field format [X-TIMESTAMP]
400	4007302	Invalid mandatory field [X-CLIENT-KEY]
401	4017300	Unauthorized. [Signature]
401	4017300	Unauthorized. [Unknown client]
504	5047300	Timeout

API SERVICES

Business Debit Card

1. Change Business Debit Card Status API

This service is used to update status BDC card.

Additional Headers and URI Params:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's Identifier using WSID = 95411
X-PARTNER-ID	Header	String(36)	Max	Y	Partner ID (company code)
X-EXTERNAL-ID	Header	String(36)	Max	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
cardNumber	String (16)	Fixed	Y	Numeric	Filled with card number of BDC
blockType	String (1)	Fixed	Y	Alphanumeric	Block Type for the BDC O: Open half block H: Half Block B: Full Block Fill with capital letters
reasonCode	String (1)	Fixed	Y	Alphanumeric	Reason of doing card status change H: Hilang (Lost) R: Tertelan (Swallowed) O: Others Fill with capital letters

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code to identify transaction status (success or failed) Format: AAABBCC AAA: HTTP Code BB: Service Code CC: Case Code

					Service Code API BDC Update Status: US Example: 200US00 – Successful
responseMessage	String (150)	Max	Y	Alphanumeric	Response description Example: Successful
responseData	Object		Y		
cardNumber	String (16)	Fixed	Y	Numeric	Card Number for the BDC If error will be filled with '_'
cardStatus	String (1)	Fixed	Y	Alphanumeric	Status of BDC If error will be filled with '_'

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
200	200US00	Successful	Transaction successful.
400	400US00	Bad Request	General request failed error
400	400US01	Invalid Field Format {Field}	Field does not match the format.
401	401US00	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.
401	401US01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/ Token is Invalid.
403	403US01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
403	403US07	Card Blocked	Card Status = H (Half Blocked / B (Blocked) / C (Closed)
403	403US15	Transaction Not Permitted. [Reason]	Card is already closed or active.
404	404US11	Invalid Card	Card number is not found.
409	409US00	Conflict	X-EXTERNAL-ID duplicate.
500	500US01	Internal Server Error	Unknown internal server failure, please retry the process again.

504

504IC00

Timeout

Your transaction timeout.

```
curl -X POST https://sandbox.bca.co.id/openapi/bdc/v1.0/update-status
```

Request



```
1  -H 'Content-type:application/json'
2  -H 'Authorization:Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpviJbU1mMU4a11MNDZ7Sg5u9a'
3  -H 'X-TIMESTAMP:2023-12-25T13:59:21+08:00'
4  -H 'X-
SIGNATURE:85be817c55b2c135157c7e89f52499bf0c25ad6eeeb04a986e8c862561b19a5'
5  -H 'ORIGIN:www.hostname.com'
6  -H 'Content-type:application/json'
7  -H 'CHANNEL-ID:95411'
8  -H 'X-PARTNER-ID:012345'
9  -H 'X-EXTERNAL-ID:01234506022024001'
10 -d '
11 {
12   "cardNumber": "1234567890123456",
13   "blockType": "B",
14   " ... ..
```

```
curl -X POST https://sandbox.bca.co.id/openapi/bdc/v1.0/update-status
```

Response



```
1  Response Sample
2  -H 'Content-type:application/json'
3  -H 'X-TIMESTAMP:2020-12-18T14:48:30+07:00'
4  {
5    "responseCode": "200US00",
6    "responseMessage": "Successful",
7    "responseData":
8      {
9        "cardNumber": "1234567890123456",
10       "cardStatus": "B"
11     }
12  }
```

2. Data Business Debit Card Inquiry API

This service is used to inquiry data BDC card.

Additional Headers and URI Params:

Field	Params Type	Data Type	Length Type	Mandatory	Description
-------	-------------	-----------	-------------	-----------	-------------

CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's Identifier using WSID = 95411
X-PARTNER-ID	Header	String(36)	Max	Y	Partner ID (company code)
X-EXTERNAL-ID	Header	String(36)	Max	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
bankCardToken	String(16)	Fixed	Y	Numeric	Filled with card number of BDC

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code to identify transaction status (success or failed) Format: AAABBCC AAA: HTTP Code BB: Service Code CC: Case Code Service Code API BDC Setting Limit: SL Example: 200SL00 – Successful
responseMessage	String (150)	Max	Y	Alphanumeric	Response description Example: Successful
responseData	Object		Y		
accountNo	String (32)	Fixed	N	Numeric	Account Number for the BDC If error will be filled with '_'
name	String (140)	Max	N	Alphanumeric	Name of the card holder If error will be filled with '_'

accountInfos	Array		N		
balanceType	String (70)	Max	N	Alphanumeric	The balance type of BDC If error will be filled with '_'
amount	Object		N		
value	String (16,2)	Max	Y	ISO4217	The amount value of limit If error will be filled with '_'
currency	String (3)	Fixed	Y	Alphanumeric	The currency used for the limit If error will be filled with '-'
additionalInfo	Object		N		Additional Information
cardNumber	String (16)	Fixed	N	Numeric	Card Number of BDC If error will be filled with '_'
factType	String (2)	Fixed	N	Alphanumeric	Type of account (Primary/Secondary) PF: Primary SE: Secondary If error will be filled with '_'
totalAccount	String (2)	Fixed	N	Numeric	Total number of Account 01 - 05 BDC only 01 If error will be filled with '_'
lanId	String (1)	Fixed	N	Numeric	Language Code 01: English 02: Indonesia If error will be filled with '_'
openDate	String (8)	Fixed	N	Numeric	Card Open Date If error will be filled with '_'
prodDate	String (8)	Fixed	N	Numeric	Card Production Date If error will be filled with '_'
closeDate	String (8)	Fixed	N	Numeric	Card Close Date If error will be filled with '_'

expiryDate	String (4)	Fixed	N	Numeric	Card Expiry Date If error will be filled with '_'
embName	String (28)	Max	N	Alphanumeric	Company Name If error will be filled with '_'
addr1	String (30)	Max	N	Alphanumeric	Address If error will be filled with '_'
addr2	String (30)	Max	N	Alphanumeric	Address If error will be filled with '_'
addr3	String (30)	Max	N	Alphanumeric	Address If error will be filled with '_'
birthDate	String (8)	Fixed	N	Numeric	Birth Date of Card Holder If error will be filled with '_'
branchCode	String (4)	Fixed	N	Numeric	Coordinator Branch Code If error will be filled with '_'
empCode	String (1)	Fixed	N	Alphanumeric	Code to specify. N: Normal F: Free If error will be filled with '_'
chargeFlag	String (1)	Fixed	N	Alphanumeric	Flag to determine if the card have been billed. U: Unpaid P: Paid If error will be filled with '_'
type	String (1)	Fixed	N	Numeric	Filled with the type of debit card. 0 : MAGNETIC STRIPE 1 : NSICCS/GPN FISIK 2 : MASTERCARD FISIK 3 : GPN DIGITAL 4 : MASTERCARD DIGITAL 5 : GPN CONTACTLESS 6 : MASTERCARD CONTACTLESS

					If error will be filled with '_'
deptCode	String (5)	Fixed	N	Numeric	Card co-brand code BDC = 0 (Conventional Card) If error will be filled with '_'
stockBranchCode	String (4)	Fixed	N	Numeric	Filled with the card stock branch code If error will be filled with '_'
customerCode	String (1)	Fixed	N	Alphanumeric	Flag to determine PRIO/ SOLI card, conventional debit card, or BDC BDC = T If error will be filled with '_'
customField	String (22)	Max	N	Alphanumeric	Name embossed on BDC If error will be filled with '_'
cardStatus	String (1)	Fixed	N	Alphanumeric	Card current status O: Open B: Blocked H: Half-Blocked C: Closed If error will be filled with '_'
corpId	String (6)	Fixed	N	Numeric	Company Code If error will be filled with '_'
outstanding	String (1)	Fixed	N	Numeric	Outstanding status of debit card For BDC will be filled with '0' If error will be filled with '_'
sendFlag	String (1)	Fixed	N	Alphanumeric	Flag to determine where the card will be sent. B: Branch H: Home BDC will be filled with 'B' If error will be filled with '_'

idNumber	String (16)	Fixed	N	Numeric	Customer ID number If error will be filled with '_'
customerId	String (12)	Fixed	N	Numeric	Field is not used If error will be filled with '_'
maidenName	String (28)	Max	N	Alphanumeric	Mother's maiden name If error will be filled with '_'
corpType	String (1)	Fixed	N	Alphanumeric	BDC card type P: Petty Cash D: Deposit L: Loyalty If error will be filled with '_'
uniqueKey	String (20)	Fixed	N	Alphanumeric	Customer Unique Key If error will be filled with '_'
limitUsage	String (16,2)	Max	N	ISO 4217	Amount of limit usage of BDC If error will be filled with '_'
limitNextDate	String (8)	Fixed	N	Numeric	Time of next limit reset If error will be filled with '_'
limitExpiryDate	String (8)	Fixed	N	Numeric	Limit expiry date If error will be filled with '_'
phone	String (15)	Max	N	Numeric	Phone Number If error will be filled with '_'
email	String (50)	Max	N	Alphanumeric	Email Address If error will be filled with '_'
desc	String (25)	Max	N	Alphanumeric	Notes If error will be filled with '_'
logonId	String (8)	Max	N	Alphanumeric	Filled with user ID If error will be filled with '_'

reasonCode	String (1)	Fixed	N	Alphanumeric	Card status change reason H: Hilang (Lost) R: Tertelan (Swallowed) O: Lain-lain (Others) If error will be filled with '_'
resetType	String (1)	Fixed	N	Alphanumeric	Limit reset type N: No Reset D: Reset by Date X: Reset by Day If error will be filled with '_'
resetPeriod	String (3)	Fixed	N	Numeric	Limit reset period If error will be filled with '_'
phoneEcomm	String (15)	Max	N	Alphanumeric	Ecommerce Phone Number If error will be filled with '_'

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
200	200IC00	Successful	Transaction successful.
400	400IC00	Bad Request	General request failed error
400	400IC01	Invalid Field Format {Field}	Field does not match the format.
401	401IC00	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.
401	401IC01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.
403	40ICL01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
404	404IC11	Invalid Card	Card number is not found.
409	409IC00	Conflict	X-EXTERNAL-ID duplicate.
500	500IC01	Internal Server Error	Unknown internal server failure, please retry the process again.

504	504IC00	Timeout	Your transaction timeout.
------------	---------	---------	---------------------------

	Type	Type	Type		
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's Identifier using WSID = 95411
X-PARTNER-ID	Header	String(36)	Max	Y	Partner ID (company code)
X-EXTERNAL-ID	Header	String(36)	Max	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
transactionId	String(14)	Fixed	Y	Numeric	Transaction identifier
effectiveDate	String(8)	Fixed	Y	Numeric	Effective date of limit setting Guide: Fill with today's date
accountNumber	String(10)	Fixed	Y	Numeric	Account Number of the BDC
cardType	String (1)	Fixed	Y	Alphanumeric	BDC type: L: Loyalty P: Petty Cash D: Deposit Fill with capital letters
recurringType	String (1)	Fixed	Y	Alphanumeric	Recurring type of BDC limit N: No Reset (can be used by card type 'P' & 'L') D: Reset by Date (can be used by card type 'P') X: Reset by Day (can be used by card type 'P' & 'D') Fill with capital letters
recurringPeriod	String (3)	Max	Y	Numeric	Periodic time for BDC limit card type D = '1' card type L = '000' card type P = '000' if recurring type 'N' '1' - '31' if recurring type 'D' free number if recurring type 'X'

cardNumber	String (16)	Fixed	Y	Numeric	Card Number for the BDC
expiryLimit	String (8)	Fixed	Y	Numeric	Limit Expiration Date Guide: Fill with today's date or bigger
limitAmount	String (13)	Max	Y	Alphanumeric	Limit Amount of BDC Guide: 1. Fill with numerical value -> change the amount limit of BDC 2. Fill with space -> does not change the amount limit of BDC 3. Fill with other value (alphabetical letters/ special characters) -> Error
uniqueKey	String (20)	Max	Y	Alphanumeric	Customer Unique Key Guide: For new BDC card : 1. Fill with different unique key from other BDC cards For existing BDC card, existing unique key will be replaced with the inserted value and may be filled with: 1. Same unique key as previous card limit setting, or 2. Different unique key from previous card limit setting
cardholder	String (35)	Max	N	Alphanumeric	Name of Card Holder of BDC
idNumber	String (16)	Fixed	N	Alphanumeric	ID Number of the Card Holder of BDC
phoneNumber	String (15)	Max	N	Alphanumeric	Phone Number of the Card Holder of BDC
emailAddress	String (50)	Max	N	Alphanumeric	Email Address of the Card Holder of BDC

description	String (25)	Max	N	Alphanumeric	Detail information
processType	String (1)	Fixed	Y	Alphanumeric	Limit Setting Process Type S: Single Process B: Bulk Process Can only use 'S' Fill with capital letters

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code to identify transaction status (success or failed) Format: AAABBCC AAA: HTTP Code BB: Service Code CC: Case Code Service Code API BDC Setting Limit: SL Example: 200SL00 – Successful
responseMessage	String (150)	Max	Y	Alphanumeric	Response description Example: Successful
responseData	Object		Y		
transactionId	String (14)	Fixed	Y	Numeric	Transaction identifier on service provider system. Must be filled upon successful transaction. If error will be filled with '_'
updateDateTime	String (14)	Fixed	Y	Numeric	Date and Time of the transaction If error will be filled with '_'
cardNumber	String (16)	Fixed	Y	Numeric	Card Number for the BDC If error will be filled with '_'

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
200	200SL00	Successful	Transaction successful.
400	400SL00	Bad Request	General request failed error
400	400SL01	Invalid Field Format {Field}	Field does not match the format.
401	401SL00	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.
401	401SL01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.
403	403SL01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
403	403SL02	Exceeds Transaction Amount Limit	Transaction limit exceeds BDC Card limit.
403	403SL07	Card Blocked	Card Status = H (Half Blocked) / B (Blocked) / C (Closed)
403	403SL08	Card Expired	Card is expired.
403	403SL15	Transaction Not Permitted. [Reason]	recurringType or recurringPeriod does not match the format.
404	404SL11	Invalid Card	Card number is not found.
404	404SL11	Invalid Customer uniqueKey	uniqueKey not unique.
404	404SL11	Invalid Account	Account number is not found.
409	409SL00	Conflict	X-EXTERNAL-ID duplicate.
500	500SL01	Internal Server Error	Unknown internal server failure, please retry the process again.
504	504SL00	Timeout	Your transaction timeout.


```
curl -X POST https://sandbox.bca.co.id/openapi/bdc/v1.0/setting-limit
```

Request



```
1  -H 'Content-type:application/json'
2  -H 'Authorization:Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpvlJbU1mMU4a11MNDZ7Sg5u9a'
3  -H 'X-TIMESTAMP:2023-12-25T13:59:21+08:00'
4  -H 'X-
SIGNATURE:85be817c55b2c135157c7e89f52499bf0c25ad6eeebe04a986e8c862561b19a5'
5  -H 'ORIGIN:www.hostname.com'
6  -H 'CHANNEL-ID:95411'
7  -H 'X-PARTNER-ID:012345'
8  -H 'X-EXTERNAL-ID:01234506022024001'
9  -d '
10 {
11   "transactionId": "12345600098765",
12   "effectiveDate": "01022024",
13   "accountNumber": "1234567890",
14   "cardNumber": "6019006012345678"
```

```
curl -X POST https://sandbox.bca.co.id/openapi/bdc/v1.0/setting-limit
```

Response



```
1  -H 'Content-type:application/json'
2  -H 'X-TIMESTAMP:2020-12-18T14:48:30+07:00'
3  {
4    "responseCode": "200SL00",
5    "responseMessage": "Successful",
6    "responseData": {
7      "transactionId": "12345600098765",
8      "updateDateTime": "10022024",
9      "cardNumber": "6019006012345678"
10   }
11 }
```

Informasi Rekening

1. Notification Account Statement Offline

Service for BCA to send notification that File Statement is ready to download.

This feature is not yet available to be accessed via Sandbox

Request:

Field	DataType	Mandatory	Description
-------	----------	-----------	-------------

RequestID	String(21)	Y	ID for every request
AccountNumber	String(10)	Y	Requested Account Number
StartDate	String(10)	Y	Statement start date. Format: yyyy-MM-dd
EndDate	String(10)	Y	Statement end date. Format: yyyy-MM-dd

Response:

Field	DataType	Description
RequestID	String	Statement request ID
ResponseWS	String	Response from Co-Partner

NOTIFICATION ACCOUNT STATEMENT OFFLINE

Request



```
1 POST https://www.copartners.com/bca/async/statement
2
3 -H "X-Pass-Signature:b9125ab10816f6929d214c96ffca77dfd5a1ea13856362b85eeae70155"
4 -d "{
5   "RequestID": "h2hauto014_0000000551",
6   "AccountNumber": "0613004197",
7   "StartDate": "2019-02-20",
8   "EndDate": "2019-02-20",
9 }"
```

NOTIFICATION ACCOUNT STATEMENT OFFLINE

Response



```
1 {
2   "RequestID": "h2hauto014_0000000551",
3   "ResponseWS": "1",
4 }
```

2. Notifikasi Rekening Dana Nasabah

Retrieve information of Account Statement of Investor Account for being debited or credited.

This feature is not yet available to be accessed via Sandbox

Request:

Field	DataType	Mandatory	Description
ExternalReference	String(32)	Y	Alphanumeric. Unique reference number for the request sent.
SeqNumber	String(14)	Y	Numeric. Identifier for the transaction.
AccountNumber	String(10)	Y	Numeric. The investor account number.
Currency	String(3)	Y	Currently always set to IDR
TxnDate	String(15)	Y	Numeric. In format "mmddyyyy hhmmss".
TxnType	String(4)	Y	Refer to table Transaction Type
TxnCode	String(1)	Y	D/C indicate debit or credit transaction.
AccountDebit	String(23)	Y	Numeric. The debited account (source of fund).
AccountCredit	String(23)	Y	Numeric. The credited account (transfer destination account).
TxnAmount	String(13.2)	Y	Numeric. Money nominal of the transfer.
OpenBalance	String(13.2)	Y	Numeric. Possible signed amount with - / + symbol.
CloseBalance	String(13.2)	Y	Numeric. Possible signed amount with - / + symbol.
TxnDesc	String(90)	Y	Any description.

Result of the request will contains following information:

No.	Transaction Type	Transaction Code	Description
1.	NTRF	D	Fund Transfer from KlikBCA Bisnis MFTS – Auto collection from KlikBCA Bisnis
		C	Fund Transfer from KlikBCA Bisnis, KlikBCA Individu, m-BCA, BCA by Phone, ATM, ATM Kiosk MFTS – Auto credit from KlikBCA Bisnis Cash deposit, Fund Transfer, Credit Note from Branch

Deposit Clearing			
2.	NINT	C	Interest Giro Service
3.	NREV	D	Credit Reversal
4.	NKOR	D	Debit Correction
		C	Credit Correction
5.	NTAX	D	Tax
6.	NCHG	D	Admin Fee

When Transaction Type (TxnType) value is NREV, the value of External Reference (ExternalReference) will be the same with the reversed transaction (the original transaction with same ExternalReference number but TxnType is NTRF).

Response:

Field	Data Type	Description
ResponseWS	String	Flag received status. 0 : request successfully accepted and no internal error 1 : request unsuccessfully accepted and or some internal error occurred

NOTIFICATION FOR SECURITIES

Request



```
1 POST https://www.somesecurities.com/bca/investor-account/statement
2 {
3   "ExternalReference": "AAABBBCCDDDEEEE1234567890123456",
4   "SeqNumber": "10023",
5   "AccountNumber": "5421036985",
6   "Currency": "IDR",
7   "TxnDate": "08252017 143801",
8   "TxnType": "NTRF",
9   "TxnCode": "C",
10  "AccountDebit": "1704000420",
11  "AccountCredit": "5421036985",
12  "TxnAmount": "200000.00",
13  "OpenBalance": "-150000.00",
14  "CloseBalance": "+50000.00",
15  ...
```

NOTIFICATION FOR SECURITIES

Response



```
1 {  
2   "ResponseWS": "0"  
3 }
```

3. Request Mutasi Rekening Bulk

You can get your bulk statement in form of file for a period up to 7 days. Your Request must contain following information:

This feature is not yet available to be accessed via Sandbox

Headers

Field	DataType	Mandatory	Description
ChannelID	String(5)	Y	Channel Identification Number (Ex: 95051 for KlikBCA Bisnis)
CredentialID	String(10)	Y	Your Channel Identity (ex: Your KlikBCA Bisnis CorporateID)

Payload

Field	DataType	Mandatory	Description
AccountNumber	String(10)	Y	Account Number
StartDate	String(10)	Y	Start Date of the account statement that you wants to get. Format: yyyy-MM-dd
EndDate	String(10)	Y	End Date of the account statement that you wants to get. Format: yyyy-MM-dd

Response

Field	DataType	Description
RequestID	String(21)	Statement request ID
TransactionDate	String(10)	Transcation date. Format: yyyy-MM-dd

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
404	ESB-07-271	Tidak ada transaksi	No transaction
400	ESB-07-279	Tanggal awal lebih kecil dari tanggal buka rekening	Start date less than account open date
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	parameter input tidak valid	Invalid input parameter
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
400	ESB-14-015	Content Type tidak valid	Invalid Content Type
400	ESB-14-016	Format JSON tidak valid	Invalid JSON format
403	ESB-14-019	Koneksi tidak diperbolehkan	Connection not allowed
400	ESB-14-020	Request tidak valid	Invalid Request
400	ESB-14-021	API Key Tidak Valid	API Key Invalid
400	ESB-14-022	API Key/API Secret tidak cocok	API Key/API Secret mismatch
400	ESB-82-001	Field [FieldName] harus diisi	Missing mandatory field [FieldName]
400	ESB-82-002	Corporate Id tidak valid	Invalid CorporateID
400	ESB-82-003	TransactionID tidak unik	TransactionID not unique
400	ESB-82-004	TransactionDate tidak valid	Invalid TransactionDate

403	ESB-82-006	Nominal transaksi melebihi batas maksimum	Max amount transaction is exceeded
400	ESB-82-008	Rekening perusahaan tidak valid	Company account invalid
400	ESB-82-009	CurrencyCode tidak valid	Invalid CurrencyCode
400	ESB-82-010	Format TransactionID tidak valid	Invalid TransactionID format
400	ESB-82-011	Amount tidak valid	Invalid Amount
400	ESB-82-012	Panjang karakter data input tidak valid	Invalid input length
400	ESB-82-013	Tipe data input tidak valid	Invalid data type
400	ESB-82-014	AccountNumber tidak valid	Invalid AccountNumber
403	ESB-82-015	Min Max Amount Exceeded	Min Max Amount Exceeded
403	ESB-82-018	Rekening Dormant	Account Dormant
402	ESB-82-019	Saldo tidak cukup	Insufficient fund
400	ESB-82-020	Tipe rekening tidak valid	Invalid account type
403	ESB-82-021	Rekening tidak dapat melakukan transaksi	Account cannot do transaction
404	ESB-82-022	Rekening tutup	Account closed
500	ESB-82-023	Transaksi gagal	Transaction failed
504	ESB-82-024	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
500	ESB-82-025	Sedang diproses, silakan periksa mutasi rekening	In progress, please check your account statement
500	ESB-82-026	Lewat batas waktu cut off	Cut off time is exceeded
400	ESB-99-009	Field [FieldName] harus diisi	Missing mandatory field [FieldName]
403	ESB-99-075	KeyID tidak ditemukan	KeyID is not found
403	ESB-99-089	Transaksi berhasil sebagian	Transaction success partially
400	ESB-99-112	Input string JSON tidak valid	Invalid JSON string input
400	ESB-99-113	Transaksi ditolak	Transaction rejected

400	ESB-99-128	Panjang field [FieldName] melebihi ketentuan	Field [FieldName] exceed limit
400	ESB-99-128	Total input [FieldName] melebihi ketentuan	Total [FieldName] input exceed limit
400	ESB-99-156	ChannelType tidak valid	ChannelType is not valid
400	ESB-99-156	AccountNumber Tidak Valid	Invalid AccountNumber
400	ESB-99-157	Transaksi ditolak	Transaction rejected
400	ESB-99-158	Tanggal berakhir lebih besar dari tanggal hari ini	End date more than today
400	ESB-99-158	Tanggal mulai lebih besar dari tanggal hari ini	Start date more than today
400	ESB-99-158	Maksimal mutasi rekening yang dipilih 31 hari yang lalu	Maximal account statement 31 days ago
400	ESB-99-158	Tanggal mulai lebih besar dari tanggal berakhir	Start date more than end date
404	ESB-99-127	Transaksi tidak ditemukan	Transaction not found
400	ESB-99-197	Nama atau nomor rekening tidak sesuai	Account name/number does not match
400	ESB-99-284	[FieldName] tidak valid	Invalid [FieldName]
500	ESB-99-999	Sistem sedang tidak tersedia	System unavaliabile

GET /banking/offline/corporates/accounts/{AccountNumber}/filestatements

Request



```
1 GET /banking/offline/corporates/accounts/0201245680/filestatements?
  StartDate=2016-06-24&EndDate=2016-06-24 HTTP/1.1
2 Host: sandbox.bca.co.id
3 Authorization: Bearer [access_token]
4 Content-Type: application/json
5 Origin: [yourdomain.com]
6 X-BCA-Key: [api_key]
7 X-BCA-Timestamp: [timestamp]
8 X-BCA-Signature: [signature]
```


GET /banking/offline/corporates/accounts/{AccountNumber}/filestatements

Response



```
1 {  
2   "RequestID": "ABCDEFGHIJ_0000000752",  
3   "ResponseWS": "Request Account Statement Berhasil Diterima dan Sedang  
4   Diproses",  
5 }
```

4. SNAP Banking Balance Inquiry

This service is used to inquiry account balance.

Additional Headers and URI Params

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String (32)	Max	Y	Corporate ID

Payload

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String(64)	Max	Y	-	Transaction identifier on service customer system
accountNo	String(16)	Max	Y	Numeric	Registered account number in KlikBCA Bisnis. For BCA, length account number is 10 digit

Result of the request will contains following information:

Response

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code

responseMessage	String (150)	Max	Y	-	Response description
referenceNo	String (64)	Max	Y (When the transaction is successful)	Numeric	Transaction identifier on service provider system. Unique each day from BCA. Must be filled upon successful transaction. With format as follows : yymmddHH (from timestamp, 8 digit) xx (prefix menu, 2 digit) sequence number (8 digit)
partnerReferenceNo	String (64)	Max	Y	-	Transaction identifier on service customer system. *according to the request input
accountNo	String (32)	Max	N	Numeric	Send by BCA according to the request input. Registered account number in KlikBCA Bisnis. For BCA, length account number is 10 digit.
name	String (140)	Max	N	Alphanumeric	Send by BCA. Customer account name
accountInfos	Array of object				Starting and ending balance before the first/ last transaction.
amount	Object		Y		Send by BCA. Net amount of the transaction

value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
floatAmount	Object		N		Send by BCA. Amount of deposit that is not effective yet (due to holiday, etc)
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
holdAmount	Object		N		Send by BCA. Hold amount that cannot be used
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
availableBalance	Object		Y		Send by BCA. Account balance that can be used for financial transaction

value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217

Error

HTTP Code	Error Code	Error Message (Indonesian)
400	4001100	Bad request
400	4001101	Invalid Mandatory Field {Field}
400	4001102	Invalid Field Format {Field}
401	4011100	Unauthorized. [Reason]
401	4011101	Invalid token (B2B)
403	4031101	Feature Not Allowed
403	4031118	Inactive Account
404	4041111	Invalid Account
409	4091100	Conflict
500	5001100	General Error
504	5041100	Timeout

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/balance-inquiry
```

Request



```
1 -H 'CHANNEL-ID':'95051'
2 -H 'X-PARTNER-ID': 'KBBABCINDO'
3 -d '{
4   "partnerReferenceNo": "202010290000000000000001",
5   "accountNo": "1234567890"
6 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/balance-inquiry
```

Response



```
1 {
2   "responseCode": "2001100",
3   "responseMessage": "Successful",
4   "referenceNo": "202010297777000000000009",
5   "partnerReferenceNo": "202010290000000000000001",
6   "accountNo": "1234567890",
7   "name": "ANDHIKA",
8   "accountInfos": {
9     "amount": {
10      "value": "100000.00",
11      "currency": "IDR"
12    },
13     "floatAmount": {
14      "value": "500000.00",
15      "currency": "IDR"
16    }
17   }
18 }
```

5. SNAP Banking Bank Statement

This service is used to inquiry account statement.

Additional Headers and URI Params

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String (32)	Max	Y	Corporate ID

Payload

Field	DataType	Length Type	Mandatory	Format	Description
partnerReferenceNo	String(64)	Max	Y	-	Transaction identifier on service customer system
accountNo	String(16)	Max	Y	Numeric	Registered account number KlikBCA Bisnis. For BCA, account number is 10 digits
fromDateTime	Date (25)	Max	Y	ISODateTime ISO-8601	Starting time range Default : NOW (DESCENDING) or NOW -1 year (ASCENDING) (must be filled YYYYMMDDT00:00:00+) For BCA, only provide date NOW - 31 days
toDateTime	Date (25)	Max	Y	ISODateTime ISO-8601	Ending time range Default : NOW (DESCENDING) or NOW - 1 year (ASCENDING) (must be filled YYYYMMDDT00:00:00+) For BCA, only provide date NOW - 31 days

Account mutations appear in the order of the newest transaction to the oldest transaction.
The maximum number of mutations that can be withdrawn in 1x request is 9000.
If fromDateTime and toDateTime are inputted on the request for a holiday date, then the mutation that will be displayed is the mutation from the request date to the date of the next working day.

Result of the request will contains following information:

Response

Field	DataType	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String (150)	Max	Y	-	Response description
referenceNo	String (64)	Max	Y (When the transaction is successful)	Numeric	Transaction identifier on service provider system. Unique each day from BCA Must be filled upon successful transaction

					With format as follows : yymmddHH (from timestamp, 8 digit) xx (prefix menu, 2 digit) sequence number (8 digit)
partnerReferenceNo	String (64)	Max	Y	-	Transaction identifier on service customer system *according to the request input
balance	Array of object				Starting and ending balance before the first/ last transaction.
amount	Object		Y		Amount of balance
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
dateTime	String(25)	Max	Y	ISODateTime 8601	Timestamp of the balance
startingBalance	Object		N		Starting and ending balance before the first/ last transaction

value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
dateTime	String(25)	Max	Y	ISODateTime 8601	Timestamp of the balance
endingBalance	Object		N		Starting and ending balance before the first/ last transaction
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
dateTime	String(25)	Max	Y	ISODateTime 8601	Timestamp of the balance
totalCreditEntries	Object		N		Total transaction amount with type = CREDIT
numberOfEntries	String (5)	Max	Y	Numeric	Number of entries for credit transaction
amount	Object		Y		Amount of balance
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value

					Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
totalDebitEntries	Object		N		Total transaction amount with type =DEBIT
numberOfEntries	String (5)	Max	Y	Numeric	Number of entries for credit transaction
amount	Object		Y		Amount of balance
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
detailData	Array of object				
endAmount	Object		Y		Net amount of the transaction
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
amount	Object		Y		
value	String(16.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with

					format value Numeric (13.2)
currency	String(3)	Fixed	Y	Alphanumeric	Currency ISO 4217
transactionDate	String (25)	Fixed	Y	ISO8601	Transaction date
remark	String (256)	Max	Y	-	Remark / transaction description. For BCA, remark is 36 digit divided in 2 field (remark 1 with 18 digit and remark 2 with 18 digit). Filled with data from txn_name and trailer 1-6
type	String (6)	Fixed	Y	Alphanumeric	Transaction type CREDIT/DEBIT

Error

HTTP Code	Error Code	Error Message (Indonesian)
400	4001402	Invalid Mandatory Field {Field}
400	4001402	Invalid Field Format {Field}
401	4011400	Unauthorized. [Reason]
401	4011401	Invalid token (B2B)
403	4031401	Feature Not Allowed
404	4041411	Invalid Account
409	4091400	Conflict
429	4291400	Too Many Requests
500	5001400	General Error
504	5041400	Timeout

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/bank-statement
```

Request



```
1 -H 'CHANNEL-ID':'95051'  
2 -H 'X-PARTNER-ID': 'KBBABCINDO'  
3 -d '  
4 {  
5   "partnerReferenceNo": "202010290000000000000001",  
6   "accountNo": "1234567890",  
7   "fromDateTime": "2021-04-21T00:00:00+07:00",  
8   "toDateTime": "2021-04-21T00:00:00+07:00"  
9 }'
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/bank-statement
```

Response



```
1 {  
2   "responseCode": "2001400",  
3   "responseMessage": "Successful",  
4   "referenceNo": "202010297777000000000009",  
5   "partnerReferenceNo": "202010290000000000000001",  
6   "balance": [  
7     {  
8       "amount": {  
9         "value": "500000.00",  
10        "currency": "IDR",  
11        "dateTime": "2020-12-19T16:03:45+07:00"  
12      },  
13      "startingBalance": {  
14        "value": "500000.00",  
15        "currency": "IDR"
```

Pembukaan Rekening Online

1. BCA Account Opening Notification

This service is used for BCA account opening approval notification.

This feature is not yet available to be accessed via Sandbox

Recommended Specification:

Type	Recommendation
Android	OS version 8.0+ dan Google Chrome version 75+
iOS	OS version 12.0+ dan Safari version 12+

Request Headers:

Field	Data Type	Mandatory	Description
X-Pass-Signature	String	Y	This is a header field, use to replace the “Pass” field on everybody payload that contains signature. This field occurred on every BCA request to Copartner’s API. Notes: the field name “X-Pass-Signature” can be replaced with any other name depends on BCA’s company partner’s specification.

Payload (Form Data):

Field	Data Type	Mandatory	Description
application_id	String (36)	Y	ID Submission Form created by prospective customers
user_id	String (50)	Y	Prospective customer ID of each merchant This user ID is sent from the merchant when they want to generate a token
status_date	String (19)	Y	date and time when the poll was success / rejected Format : YYYY-MM-DD HH:MM:SS
created_date	String (19)	Y	The date when the initial form submission process
modified_date	String (19)	Y	The date in case of data change such as updating of eform numbers or other things will automatically update

			the date
status_id	int	Y	Open account status code Code : 0, 1
status_name	String (15)	Y	type of account opening status. depends on the status_id 0 = REJECTED 1 = SUCCESS
nomor_rekening	String (10)	N	if the customer agrees to the provision of the account to a third party, the customer's account number will be sent

Result of the request will contains following information:

Response:

Field	Data Type	Description
Status	String (7)	The push notification process is success or failed
Message	String (8)	Response from Co-Partner ("Berhasil")

https://www.copartners.com/bca/open-account/notification

Request



```
1 POST https://www.copartners.com/bca/open-account/notification
2 -H "X-Pass-Signature: b9125ab10816f6929d214c96ffca77dfd5a1ea13856362b85eeae70155"
3 -d "{
4   "user_id":"DD6DC0C5-17ED-4731-8600-B63EEDB126D9",
5   "application_id":"7C73063B-93EA-4F57-A3bE-2A1F1773DB4F",
6   "status_date":"2020-08-05 11:03:56",
7   "created_date":"2020-03-18 09:03:57",
8   "modified_date":"2020-08-11 11:16:01",
9   "status_id":"1",
10  "status_name":"SUCCESS",
11  "nomor_rekening":"1234567890"
12 }"
```

https://www.copartners.com/bca/open-account/notification

Response



```
1 {  
2   "Status": "Success",  
3   "Message": "Berhasil"  
4 }
```

2. BCA Account Opening Status

This service is used for BCA account opening status update for Co-Partners.

This feature is not yet available to be accessed via Sandbox

Recommended Specification:

Type	Recommendation
Android	OS version 8.0+ dan Google Chrome version 75+
iOS	OS version 12.0+ dan Safari version 12+

Request Headers and URI Params:

Field	Params Type	Data Type	Mandatory	Description
channel-id	Header	String	Y	WSID bcacoid (95171)
credential-id	Header	String(36)	Y	Registered Merchant ID at bca.co.id
application-id	Header	String(36)	Y	Application ID that sent from bca.co.id to merchant when successfully submitted form (before uploading document and video call)

Result of the request will contains following information:

Response:

Field	Data Type	Description
merchant_id	String	Merchant ID

application_id	String (36)	Application ID
status_name	String (15)	Transaction Status
status_id	int	Status ID 0 = Rejected 1 = Success 2 = Retry 3 = On-Lock
created_date	String (19)	The date when the initial form submission process
modified_date	String (19)	The date in case of data change such as updating of eform numbers or other things will automatically update the date
status_date	String (19)	Status Date
nomor_rekening	String (10)	Account Number (If the Customer does not check Account Number Approval, then the Account_Number field will display an empty string (""))

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)	Description
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch	400
400	ESB-14-002	Permintaan tidak valid	Invalid request	400
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp	400
400	ESB-14-004	parameter input tidak valid	Invalid input parameter	400
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance	500
504	ESB-14-007	Timeout	Timeout	504
401	ESB-14-008	Client_Id/Client_Secret / Grant_Type tidak valid	Invalid Client_Id/ Client_Secret / Grant_Type	401
401	ESB-14-009	Tidak berhak	Unauthorized	401
404	ESB-14-011	Service tidak tersedia	Service doesn't exist	404

401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service	401
401	ESB-14-014	ChannelID/CredentialID tidak valid	Invalid ChannelID/ CredentialID	401
403	ESB-14-019	Koneksi tidak diperbolehkan	Connection not allowed	403
400	ESB-14-021	API Key tidak valid	Invalid API Key	400
400	ESB-14-022	API Key/API Secret tidak cocok	API Key/API Secret mismatch	400
400	WBF-04-001	Header Application Id tidak ada	Header Application Id tidak ada	Get Open Account Approval Status
400	WBF-04-002	Header Credential ID tidak ada	Header Credential ID tidak ada	Get Open Account Approval Status
400	WBF-04-003	Credential ID / Application Id Value tidak sesuai	Credential ID / Application Id Value tidak sesuai	Get Open Account Approval Status
400	WBF-04-004	Data dengan Credential ID dan Application Id tersebut tidak ditemukan	Data dengan Credential ID dan Application Id tersebut tidak ditemukan	Get Open Account Approval Status
400	WBF-04-005	Header Client Id tidak ada	Header Client Id tidak ada	Get Open Account Approval Status
400	WBF-04-006	Data dengan Client ID tersebut tidak ditemukan	Data dengan Client ID tersebut tidak ditemukan	Get Open Account Approval Status
400	WBF-99-991	ex.Message	ex.Message	Pesan global dari sistem
400	WBF-99-992	messages	messages	Pesan global dari sistem

/open-account/marketplace/status

Request



```
1 curl -X GET https://sandbox.bca.co.id/open-account/marketplace/status
2 -H
3 'credentialid': F90338EA-853B-4512-AE58-0E72BE2E88ED',
4 'application-id': 'C5276A67-711E-468EBB14-01861D2746C6',
5 'channel-id': '95171'
```

/open-account/marketplace/status

Response



```
1 {
2   "merchant_id": "F90338EA-853B-4512-AE58-0E72BE2E88ED",
3   "application_id": "5F7D49A6-E3F7-493A-B255-5906D4E65FD2",
4   "status_name": "SUCCESS",
5   "status_id": "1",
6   "created_date": "2020-08-05 10:28:21",
7   "modified_date": "2020-08-05 11:03:56",
8   "status_date": "2020-08-05 11:03:56",
9   "nomor_rekening": "0842378425"
10 }
11
12 Response Berhasil dan tanpa menampilkan Nomor Rekening
13 {
14   "merchant_id": "F90338EA-853B-4512-AE58-0E72BE2E88ED",
15   "application_id": "5F7D49A6-E3F7-493A-B255-5906D4E65FD2",
16   "status_name": "SUCCESS",
17   "status_id": "1",
18   "created_date": "2020-08-05 10:28:21",
19   "modified_date": "2020-08-05 11:03:56",
20   "status_date": "2020-08-05 11:03:56",
21   "nomor_rekening": "0842378425"
```

3. BCA Account Opening Webform

This service is used for Open Account Marketplace.

This feature is not yet available to be accessed via Sandbox

Recommended Specification:

Type	Recommendation
Android	OS version 8.0+ dan Google Chrome version 75+
iOS	OS version 12.0+ dan Safari version 12+

Request Headers and URI Params:

Field	Params Type	Data Type	Mandatory	Description
-------	-------------	-----------	-----------	-------------

channel-id	Header	String	Y	WSID bcacoid (95171)
credential-id	Header	String(36)	Y	Registered Merchant ID at bca.co.id

Payload (Form Data):

Field	Data Type	Mandatory	Description
user_id	String (50)	Y	Registered User Merchant ID
application_id	String (36)	Conditional	Application ID Not mandatory if activity_code = '01', application_id = "" Mandatory if activity_code = '02', application_id sent from web-view to merchant when successfully submitted form
activity_code	String (2)	Y	Activity Code '01' = web-view access (consumer profile) '02' = mobile-browser access (open account document and video call capture)
email	String (100)	N	Merchant Email
mobile_phone	String (15)	N	Merchant Mobile Phone
full_name	String (100)	N	Merchant Full Name

Result of the request will contains following information:

Response:

Field	Data Type	Description
verification_id	String (36)	Verification ID
applicant_id	String (36)	Applicant ID
url_pageview	String	URL Pageview
application_id	String (40)	Hanya dikirim jika Activity code = 02 Kode unik khusus yang berfungsi sebagai reference code sesi pemrek

yang dimasking untuk diinfokan ke copartner

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)	Description
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch	400
400	ESB-14-002	Permintaan tidak valid	Invalid request	400
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp	400
400	ESB-14-004	parameter input tidak valid	Invalid input parameter	400
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance	500
504	ESB-14-007	Timeout	Timeout	504
401	ESB-14-008	Client_Id/Client_Secret / Grant_Type tidak valid	Invalid Client_Id/ Client_Secret / Grant_Type	401
401	ESB-14-009	Tidak berhak	Unauthorized	401
404	ESB-14-011	Service tidak tersedia	Service doesn't exist	404
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service	401
401	ESB-14-014	ChannelID/CredentialID tidak valid	Invalid ChannelID/ CredentialID	401
403	ESB-14-019	Koneksi tidak diperbolehkan	Connection not allowed	403
400	ESB-14-021	API Key tidak valid	Invalid API Key	400
400	ESB-14-022	API Key/API Secret tidak cocok	API Key/API Secret mismatch	400
400	WBF-03-001	The {field-name} field is required.	The {field-name} field is required.	Generate Merchant Token
400	WBF-03-002	Parameter header Credential ID tidak ditemukan	Parameter header Credential ID tidak ditemukan	Generate Merchant Token
400	WBF-03-003	Credential ID Value tidak sesuai	Credential ID Value tidak sesuai	Generate Merchant Token

400	WBF-03-004	Credential ID tidak terdaftar	Credential ID tidak terdaftar	Generate Merchant Token
400	WBF-03-005	Application Id tidak sesuai	Application Id tidak sesuai	Generate Merchant Token
400	WBF-03-006	Application Id tidak ditemukan	Application Id tidak ditemukan	Generate Merchant Token
400	WBF-03-007	Application Id ditolak / berhasil / sedang proses	Application Id ditolak / berhasil / sedang proses	Generate Merchant Token
400	WBF-03-008	Merchant Id dan App Data Id tidak sesuai	Merchant Id dan App Data Id tidak sesuai	Generate Merchant Token
400	WBF-03-009	Telah mencapai batas akses maksimum halaman ini.	Telah mencapai batas akses maksimum halaman ini.	Generate Merchant Token
400	WBF-99-991	ex.Message	ex.Message	Pesan global dari sistem
400	WBF-99-992	messages	messages	Pesan global dari sistem

/open-account/marketplace/merchants/tokens/generator

Request



```
1 curl -X POST https://sandbox.bca.co.id/open-account/marketplace/merchants/tokens/
generator
2 -H 'credential-id':'F90338EA-853B4512-AE58-OE72BE2E88ED', 'channel-id':'95171'
3 -d
4 'user_id=123456789&application_id=&activity_code=01&email=maiuw@gmail.com&mobile_ph
5 one=08128084423&full_name=8196047056'
```

/open-account/marketplace/merchants/tokens/generator

Response



```
1  Response (if ActivityCode = 01)
2  {
3    "verification_id": "cdec3c69-f549-4b91-bccf-25a3dad2de5a",
4    "applicant_id": "117f6c7e-ceec-4fde-ab4d-6b628230ed59",
5    "url_pageview": "http://10.20.212.217:2007/applyonline/bukarekening/form1?
6    MerchantId=F90338EA-853B-4512-AE58-0E72BE2E88ED&ApplicantId=117f6c7e-ceec-4fde-
7    ab4d6b628230ed59&VerificationId=cdec3c69-f549-4b91-bccf-25a3dad2de5a"
8    "application_id": null
9  }
10
11 Response (if ActivityCode = 02)
12 {
13   "verification_id": "cdec3c69-f549-4b91-bccf-25a3dad2de5a",
14   "applicant_id": "117f6c7e-ceec-4fde-ab4d-6b628230ed59",
15   "url_pageview": "http://10.20.212.217:2007/applyonline/bukarekening/form1?
16   MerchantId=F90338EA-853B-4512-AE58-0E72BE2E88ED&ApplicantId=117f6c7e-ceec-4fde-
17   ab4d6b628230ed59&VerificationId=cdec3c69-f549-4b91-bccf-25a3dad2de5a"
```

Virtual Account untuk Biller

1. SNAP Virtual Account Inquiry

This service is used to VA BillPresentment.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)		Y	Channel' Identifier using WSID BCA Virtual Account (95231)
X-PARTNER-ID	Header	String(32)		Y	Partner ID using Company Code VA
X-EXTERNAL-ID	Header	String (36)		Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Mandatory	Description
partnerServiceId	String (8)	Y	Derivative of XPARTNER-ID, similar to company code 8 digit left padding space " "

customerNo	String (20)	Y	Unique number (up to 20 digits)
virtualAccountNo	String (28)	Y	partnerServiceId (8 digit left padding space “ ”) + customerNo (up to 20 digit)
trxDateInit	Date (25)	N	BCA internal system datetime with timezone, which follows the ISO-8601 standard
channelCode	Numeric (4)	N	Channel code based on ISO 18245
inquiryRequestId	String (128)	Y	Unique identifier for this inquiry. Generated by BCA.
additionalInfo	Object	N	Optional. Additional Information for custom use. Refer to Appendix B for complete list of additionalInfo for Virtual Account

Result of the request will contains following information:

Response:

Field	Data Type	Mandatory	Description
responseCode	String (7)	Y	Mandatory in BCA. Response code from Partner, refer to Appendix A for list of response code
responseMessage	String (150)	Y	Mandatory in BCA. Response message from Partner, refer to Appendix A for list of response code
virtualAccountData	Object	Y	
inquiryStatus	String (2)	N	Mandatory in BCA. Status of inquiry, refer to Notes for status values
inquiryReason	Object	N	Mandatory in BCA. Reason for inquiry Status multi language
english	String (64)	N	Reason for inquiry Status in English
indonesia	String (64)	N	Reason for inquiry Status in Bahasa
partnerServiceId	String (8)	Y	Mandatory in BCA. Derivative of X-PARTNER-ID, similar to company code, 8 digit left padding space “ ”
customerNo	String (20)	Y	Mandatory in BCA. Unique number (up to 20 digits).

virtualAccountNo	String (28)	Y	Mandatory in BCA. partnerServiceId (8 digit left padding space “ ”) + customerNo (up to 20 digit)
virtualAccountName	String (255)	Y	Mandatory in BCA. Customer name
inquiryRequestId	String (128)	Y	Mandatory in BCA. From Inquiry Request
totalAmount	Object	N	Mandatory in BCA.
value	String (16.2) ISO 4217	Y	Transaction Amount. Total Amount with 2 decimal
currency	String (3)	Y	Currency
subCompany	String (5)	N	Mandatory in BCA. Partner's product code (sub company code). Mandatory for non-multibills transaction.
billDetails	Array of Objects	N	Array with maximum 24 Objects
billNo	String (18)	N	Customer bill number generated by Partner
billDescription	Object	N	Bill Description
english	String (18)	N	Bill Description in English
indonesia	String (18)	N	Bill Description in Bahasa
billSubCompany	String (5)	C	Bill sub company code
billAmount	Object	N	Amount specific to bill number
value	String (16.2) ISO 4217	Y	Transaction Amount
currency	String (3)	Y	
additionalInfo	Object	N	Optional. Additional information for custom use. Refer to Appendix B for complete list of additionalInfo for Virtual Account
freeTexts	Array of Objects	N	Optional. Array with maximum 9 objects. freeTexts field in inquiry bill should not be greater than 5
english	String (18)	N	Will be shown in Channel

indonesia	String (18)	N	Will be shown in Channel
additionalInfo	Object	N	Optional. Additional information for custom use. Refer to Appendix B for complete list of additionalInfo for Virtual Account

- Note :
- The final status of inquiry response is not determined by responseCode and responseMessage.
 - Status of inquiry will be defined in inquiryStatus and inquiryReason field to be displayed to channel's screen. This field may vary with these values:
00 = Success inquiry, detail bill returned
01 = Failed inquiry, partner must defined reason for this status in InquiryReason field.
 - BCA will continue to check the inquiryStatus and inquiryReason if the responseCode received is 2002400 and 2022400.
 - If the response code is not either 2002400 or 2022400, BCA will on consider the response as failed transaction and will be rejected.
 - If the inquiryStatus and inquiryReason field are empty, BCA will consider it a failed transaction and will be rejected.
 - If virtualAccountName length > 30, channel will display first 30 characters.
 - If any amount field value > 13.2 digit length, BCA will consider it a failed inquiry and error message will be displayed in channel.
 - currency of totalAmount and billAmount must be the same. currency field may vary with these values: IDR, USD, SGD
 - For multi bills transaction, totalAmount field value can be 0, but for non-multi bills transaction totalAmount field value should be total amount of all the detail bills provided.
 - For non multi bills transaction with single settlement, billDetails is optional. If billDetails available then billSubCompany field in billDetails must match with subCompany field value.
 - For multi bills and non multi bills transaction with multi settlements,
• billSubCompany & billAmount field is mandatory
• billSubCompany field value must be different for each bill number, used for multiple settlements needs. Product Name and Admin Fee from subCompany 00000 would be used and shown in channel.
 - billNo and billDescription field value are defined by co-partner and will be displayed in BCA channel's screen
 - subCompany and billSubCompany value must be registered in BCA, else transaction will be rejected.
 - freeTexts field defined by partner and will be displayed in channel's screen. This field must be defined in two languages, The occurrences for freeTexts field in inquiry bill should not be greater than 5.
 - feeAmount field will be ignored. feeAmount will refer to company profile data registered in BCA's system.
 - virtualAccountTrxType will be ignored. will refer to company profile data (bill type: YV/ NV/YF) registered in BCA's system.
 - billDetails should not be greater than 5
 - channelCode field may vary with these values based on ISO 18245:
• 6010 = Teller (Financial institutions - manual cash disbursements)
• 6011 = eBanking (Financial institutions - automated cash disbursements)
 - inquiryRequestId is unique from BCA for each transaction.
 - the usage of additional info is to be discussed with BCA first.

Expected Response from Partner.

Scenario	responseCode	responseMessage	inquiryStatus
Access Token Invalid	4012401	"Invalid Token (B2B)"	-
Unauthorized . Signature	4012400	"Unauthorized. [Signature]"	-
Unauthorized . stringToSign	4012400	"Unauthorized. [Signature]"	-
Unauthorized . Unknown Client	4012400	"Unauthorized. [Unknown client]"	-
Missing Mandatory Field {} ..., etc	4002402	"Invalid Mandatory Field {.....}"	01
Invalid Field Format {} .., etc	4002401	"Invalid Field Format {.....}"	01
Cannot use the same X-EXTERNAL-ID	4092400	"Conflict"	01
Input no Virtual Account Valid	2002400	"Success"	01
Input no Virtual Account Valid sudah lunas	4042414	"Paid Bill"	01
Input no Virtual Account Valid kadaluarsa	4042419	"Invalid Bill/Virtual Account"	01
Input no Virtual Account tidak terdaftar	4042412	"Invalid Bill/Virtual Account [Reason]"	01
Request Parsing Error	4002400	"Bad Request"	01
Response Parsing Error	4002400	"Bad Request"	01

```
curl -X POST https://copartners.com/openapi/v1.0/transfer-va/inquiry
```

Request



```
1 -H 'CHANNEL-ID': '95231'
2 -H 'X-PARTNER-ID': '12345'
3 -H 'X-EXTERNAL-ID': '123456789012345678901234567890123456'
4 -d '
5 {
6   "partnerServiceId": "12345",
7   "customerNo": "123456789012345678",
8   "virtualAccountNo": "12345123456789012345678",
9   "trxDateInit": "2022-02-12T17:29:57+07:00",
10  "channelCode": 6011,
11  "additionalInfo": {},
12  "inquiryRequestId": "202202110909311234500001136962"
13 }
```

```
curl -X POST https://copartners.com/openapi/v1.0/transfer-va/inquiry
```

Response



```
1 Sample for single settlement (non multi bills) transaction:
2
3 {
4   "responseCode": "2002400",
5   "responseMessage": "Successful",
6   "virtualAccountData":
7   {
8     "inquiryStatus": "00",
9     "inquiryReason": {
10      "english": "Success",
11      "indonesia": "Sukses"
12    },
13     "partnerServiceId": "12345",
14     "customerNo": "123456789012345678",
15     "virtualAccountNo": "12345123456789012345678"
```

2. SNAP Virtual Account Inquiry Status

This service is used to VA Payment Status.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel' Identifier using WSID BCA Virtual Account (95231)

X-PARTNER-ID	Header	String(5)	Fixed	Y	Partner ID using Company Code VA
X-EXTERNAL-ID	Header	String (36)	Max	Y	Numeric String reference number that should be unique in the same day

Payload:

Field	Data Type	Data Type	Mandatory	Format	Description
partnerServiceId	String (8)	Fixed	Y		Derivative of X-PARTNER-ID, similar to company code. It must be 8 characters, using space padding “ ” on the left if it doesn’t reach 8 characters.
customerNo	String (18)	Max	Y		Unique number (up to 18 digits)
virtualAccountNo	String (26)	Max	Y		partnerServiceId (8 digit left padding space “ ”) + customerNo (up to 18 digit).
inquiryRequestId	String (30)	Fixed	Y		Unique identifier for this inquiry. Generated by BCA.
additionalInfo	Object		N		Optional. Additional Information for custom use. Refer to Appendix B for complete list of additionalInfo for Virtual Account

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y		Response code refer to Appendix A.The final status of payment flag is not determined by responseCode and responseMessage.
responseMessage	String (150)	Max	Y		Response message

				refer to Appendix A.
virtualAccountData	Object		Y	-
paymentFlagStatus	String (2)	Fixed	y	Status for Payment Flag defined by Partner. This field may vary with these values: - 00 = Success payment flag. - 01 = Reject payment flag by partner. - 02 = Timeout payment flag between switcher to partner. If company's reconciliation type is reversal or force settle, transaction with status 02 will be considered as success transaction. - 03 = Pending between BCA and the partner. If the payment flag process is not yet completed and the partner performs an inquiry within that time frame, the transaction with status 03 will be delivered to the partner
paymentFlagReason	Object		Y	Reason for Payment Status multi language.
english	String (200)	Max	Y	Reason for Payment Status in English
indonesia	String (200)	Max	Y	Reason for Payment Status in Bahasa
partnerServiceId	String (8)	Fixed	Y	Derivative of X-PARTNER-ID, similar to company code, 8 digit left padding space " " on the left if

					it doesn't reach 8 characters
customerNo	String (18)	Max	Y		Unique number (up to 18 digits).
virtualAccountNo	String (26)	Max	Y		partnerServiceId (8 digit left padding space " ") + customerNo (up to 26 digit)
inquiryRequestId	String (30)	Fixed	Y		Unique identifier from Inquiry.
paymentRequestId	String (30)	Fixed	Y		Unique identifier from Payment (if payment happened). This value must be same with inquiryRequestId
paidAmount	Object		Y		Total amount paid by customer through BCA
value	String (13.2)	Max	Y	Numeric	Paid amount with 2 decimals
currency	String (3)	Fixed	Y	ISO-4217	Currency
paidBills	String (6)	Fixed	N		Hexadecimal format of binary of flag of paid bills.
totalAmount	Object		Y		-
value	String (13.2)	Max	Y	Numeric	Total amount paid by customer through BCA
currency	String (3)	Fixed	Y	ISO-4217	Currency
trxDateTime	Date (25)	Fixed	N		BCA internal system datetime with timezone, which follows the ISO-8601 standard.
transactionDate	Date (25)	Fixed	Y	ISODateTime ISO-8601	Payment datetime when the payment happened.

referenceNo	String (11)	Fixed	C	Numeric	Payment auth code generated by BCA. Mandatory for single bill transaction.
paymentType	String (1)	Fixed	N		Type of payment.
flagAdvise	String (1)	Fixed	N		Status is this a retry notification
billDetails	Array of Objects		C		Array with maximum 24 Objects. Mandatory for multi bills and non multi bills transaction with multi settlements.
billCode	String (2)	Fixed	N		Bill code for Customer choose.
billNo	String (18)	Fixed	Y		Bill number from Partner.
billName	String (20)	Max	N		Bill number from Partner.
billShortName	String (10)	Max	N		Bill Name to shown to.
billDescription	Object		Y		Bill Description
english	String (18)	Max	Y		Bill Description in English
indonesia	String (18)	Max	Y		Bill Description in Bahasa
billSubCompany	String (5)	Fixed	Y		Partner's product code
billAmount	Object		Y		Nominal inputted by Customer with 2 decimal.
value	String (13.2)	Max	Y	Numeric	Transaction Amount. Total Amount from Inquiry with 2 decimals.
currency	String (3)	Fixed	Y	ISO-4217	Currency.
additionalInfo	Object		N		Optional. Additional information for

					customer use for each bil. Refer to Appendix B for complete list of additionalInfo for Virtual Account
billReferenceNo	String (11)	Fixed	Y	Numeric	Bill auth code generated by BCA.
status	String (2)	Fixed	Y		Payment status for specific Bill.
reason	Object		Y		Reason for Payment Status for specific Bill multi language.
english	String (64)	Max	Y		Reason for Payment Status for specific Bill in English.
indonesia	String (64)	Max	Y		Reason for Payment Status for specific Bill in Bahasa.
freeTexts	Array of Objects		N		Array with maximum 9 Objects.
english	String (32)	Max	N		Will be shown in Channel
indonesia	String (32)	Max	N		Will be shown in Channel
additionalInfo	Object		N		Additional information for custom use. Refer to Appendix B for complete list of additionalInfo for Virtual Account

Notes : • Payment status result is available only if the payment flag transaction has been made

Appendix A: Expected Response from Partner

HTTP Code	responseCode	responseMessage	Condition
200	2002600	Success	Success

HTTP Code	responseCode	responseMessage	Condition
400	4002600	Bad Request	General request error
400	4002601	Invalid Field Format {field name}	The data you entered does not match the format requirements
400	4002602	Invalid Mandatory Field {field name}	Mandatory field should be fulfilled
401	4012600	Unauthorized. [Reason]	Invalid Signature/Unknown Client/ Connection Not Allowed/Invalid API/ Company is not authorized
401	4012601	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid
404	4042601	Transaction Not Found	Transaction Not Found
409	4092600	Conflict	Cannot use same X-EXTERNAL-ID in the same day
500	5002601	Internal Server Error	Unknown Internal Server Failure. Please retry the process again
504	5042600	Timeout	Timeout

Appendix B: Additional Info

Field	Name		Data Type	Mandatory	
1	additionalInfo		Object	FALSE	
	additionalInfo1		Object	FALSE	
	1.1	label	Object	TRUE	
		1.1.1	english	String(50)	TRUE
		1.1.2	indonesia	String(50)	TRUE
		1.2	value	Object	TRUE
	1.2.1		english	String(200)	TRUE
	1.2.2		indonesia	String(200)	TRUE
2	additionalInfo2		Object	FALSE	
	2.1	label	Object	TRUE	

Field	Name		Data Type	Mandatory
	2.1.1	english	String(50)	TRUE
	2.1.2	indonesia	String(50)	TRUE
	2.2	value	Object	TRUE
	2.2.1	english	String(200)	TRUE
	2.2.2	indonesia	String(200)	TRUE
3	additionalInfo3		Object	FALSE
	3.1	label	Object	TRUE
	3.1.1	english	String(50)	TRUE
	3.1.2	indonesia	String(50)	TRUE
	3.2	value	Object	TRUE
	3.2.1	english	String(200)	TRUE
	3.2.2	indonesia	String(200)	TRUE
4	additionalInfo4		Object	FALSE
	4.1	label	Object	TRUE
	4.1.1	english	String(50)	TRUE
	4.1.2	indonesia	String(50)	TRUE
	4.2	value	Object	TRUE
	4.2.1	english	String(200)	TRUE
	4.2.2	indonesia	String(200)	TRUE
5	additionalInfo5		Object	FALSE
	5.1	label	Object	TRUE
	5.1.1	english	String(50)	TRUE
	5.1.2	indonesia	String(50)	TRUE
	5.2	value	Object	TRUE
	5.2.1	english	String(200)	TRUE

Field	Name		Data Type	Mandatory	
6	5.2.2	indonesia	String(200)	TRUE	
	additionalInfo6		Object	FALSE	
	6.1	label	Object	TRUE	
		6.1.1	english	String(50)	TRUE
		6.1.2	indonesia	String(50)	TRUE
	6.2	value	Object	TRUE	
		6.2.1	english	String(200)	TRUE
		6.2.2	indonesia	String(200)	TRUE
		additionalInfo7		Object	FALSE
	7	7.1	label	Object	TRUE
7.1.1			english	String(50)	TRUE
7.1.2			indonesia	String(50)	TRUE
additionalInfo7			Object	FALSE	
7.2		value	Object	TRUE	
		7.2.1	english	String(200)	TRUE
		7.2.2	indonesia	String(200)	TRUE
		additionalInfo8		Object	FALSE
8	8.1	label	Object	TRUE	
		8.1.1	english	String(50)	TRUE
		8.1.2	indonesia	String(50)	TRUE
		additionalInfo8		Object	FALSE
	8.2	value	Object	TRUE	
		8.2.1	english	String(200)	TRUE
		8.2.2	indonesia	String(200)	TRUE
		additionalInfo9		Object	FALSE
9	9.1	label	Object	TRUE	
		9.1.1	english	String(50)	TRUE


```
curl -X POST https://sandbox.bca.co.id/openapi/v2.0/transfer-va/status
```

Response



```
1  "Sample for single settlement (non multi bills) transaction"
2
3  -H 'Content-type:application/json'
4  -H 'X-TIMESTAMP: 2024-08-21T14:48:30+07:00'
5  {
6    "responseCode": "2002600",
7    "responseMessage": "Success",
8    "virtualAccountData": {
9      "paymentFlagStatus": "00",
10     "paymentFlagReason": {
11       "indonesia": "Transaksi Berhasil",
12       "english": "Transaction Success"
13     },
14     "partnerServiceId": " 12345",
15     "partnerServiceId": "12345678901234567890"
```

3. SNAP Virtual Account Payment

This service is used to VA Payment Flag.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel' Identifier using WSID BCA Virtual Account (95231)
X-PARTNER-ID	Header	String(8)	Max	Y	Partner ID using Company Code VA
X-EXTERNAL-ID	Header	String (36)	Max	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerServiceId	String (8)	Fixed	Y		Derivative of X-PARTNER-ID, similar to company code. It must be 8 character, using space padding " " on

					the left if it doesn't reach 8 characters.
customerNo	String (18)	Max	Y		Unique number (up to 18 digits)
virtualAccountNo	String (26)	Max	Y		partnerServiceId (8 digit left padding space “ ”) + customerNo (up to 18 digit)
virtualAccountName	String (30)	Max	Y		Customer name
virtualAccountEmail	String (255)	Max	N		Customer email
virtualAccountPhone	String (30)	Max	N		Customer's phone number Format: 62xxxxxxxxx
trxId	String (64)	Fixed	N		Unique identifier generated by Partner Mandatory if payment comes from the Create VA Request.
paymentRequestId	String (30)	Fixed	Y		Unique identifier generated by BCA. If payment comes from the Inquiry process, this value must be the same with inquiryRequestId.
channelCode	Numeric (4)	Fixed	Y	ISO-18245	Channel code field may vary with these values: 6000 = Others 6010 = Teller (Financial institutions - manual cash disbursements) 6011 = ATM 6012 = EDC 6013 = Autodebet 6014 = Internet Banking 6015 = Oneklik 6016 = myBCA (Mobil and Website) 6017 = Mobile Banking 6018 = Other Bank 6019 = Cardless

					6020 = Shared Biller
hashedSourceAccountNo	String (32)	Fixed	N		Source account number in hash
sourceBankCode	String (3)	Fixed	N		Source account bank code
paidAmount	Object		Y		Total amount paid by customer through BCA.
value	String (13.2)	Max	Y	Numeric	Paid Amount with 2 decimal
currency	String (3)	Fixed	Y	ISO-4217	Currency
cumulativePaymentAmount	Object		N		-
value	String (13.2)	Max	Y	Numeric	Transaction Amount
currency	String (3)	Fixed	Y	ISO-4217	Currency
paidBills	String (6)	Max	N		Hexadecimal format of binary of flag of paid bills
totalAmount	Object		Y		-
value	String (13.2)	Max	Y	Numeric	Total amount paid by customer through BCA.
currency	String (3)	Fixed	Y	ISO-4217	Currency
trxDateTime	Date (25)	Fixed	Y	ISO-8601	BCA internal system datetime with timezone, which follows the ISO-8601 standard
referenceNo	String (11)	Fixed	C		Payment auth code generated by BCA. Mandatory for non-multi bill transaction.
journalNum	String (6)	Fixed	N		Sequence journal number

paymentType	String (1)	Fixed	N	Type of Payment
flagAdvise	String (1)	Fixed	Y	Retry flag notification This field may vary with these values: N = new request for payment flag (as default value). Y = advice request (retry flag) for payment flag.
subCompany	String (5)	Fixed	C	Sub Company code generated by Partner Mandatory for non-multi bill transaction with single settlement.
billDetails	Array of Objects		C	Array with maximum Objects. Mandatory for multi bills and non multi bills transaction with multi settlement
billCode	String (2)	Fixed	N	From Inquiry Respons
billNo	String (18)	Max	Y	From Inquiry Respons
billName	String (20)	Max	N	From Inquiry Respons
billShortName	String (10)	Max	N	From Inquiry Respons
billDescription	JSON Object		Y	From Inquiry Respons
english	String (18)	Max	Y	From Inquiry Respons
indonesia	String (18)	Max	Y	From Inquiry Respons
billSubCompany	String (5)	Fixed	Y	From Inquiry Respons
billAmount	Objects		Y	-

value	String (13.2)	Max	Y	Numeric	Transaction Amount. From Inquiry Respons
currency	String (3)	Fixed	Y	ISO-4217	Currency
additionalInfo	Object		N		From Inquiry Respons
billReferenceNo	String (11)	Fixed	Y	Numeric	Generated by BCA
freeTexts	Array of Objects		N		From Inquiry Respons
english	String (32)	Max	Y		From Inquiry Respons
indonesia	String (32)	Max	Y		From Inquiry Respons
additionalInfo	Object		N		Optional. Additional information for custom use. Refer to Appendix B for complete list of additionalInfo for Virtual Account

- Notes :
- paymentRequestID corresponds to inquiryRequestID for each transaction (one pair of inquiry and payment)
 - For both multi bills and non-multi bills transactions, the totalAmount and paidAmount field value contain the total amount paid by customer through BCA.
 - Currency must be same for totalAmount, billAmount, and paidAmount. currency field may vary with these values: IDR, SGD, USD.
 - For multi bills and non multi bills transaction with multi settlements,
 - billDetails is mandatory.
 - billReferenceNo field value must be different for each billDetails.
 - For multi bills transaction, BCA will return only bills that customer choose to pay in payment flag request to partner.

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y		Response code from Partner, refer to Appendix A for list of response code

responseMessage	String (150)	Max	Y		Response message from Partner, refer to Appendix A for list of response code
virtualAccountData	Object		Y		-
paymentFlagReason	Object		Y		Reason for Payment Status multi language
english	String (200)	Max	Y		Reason for inquiry status in English
indonesia	String (200)	Max	Y		Reason for inquiry status in Bahasa
partnerServiceId	String (8)	Fixed	Y		Derivative of X-PARTNER-ID, similar to company code. It must be 8 character, using space padding " " on the left if it doesn't reach 8 characters.
customerNo	String (18)	Max	Y		Unique number (up to 18 digit)
virtualAccountNo	String (26)	Max	Y		partnerServiceId (8 digit left padding space " ") + customerNo (up to 18 digit)
virtualAccountName	String (30)	Max	Y		Customer name
paymentRequestId	String (30)	Fixed	Y		From Payment Request
paidAmount	Object		Y		Total amount paid by customer through BCA.
value	String (13.2)	Max	Y	Numeric	Transaction Amount. From Payment Request
currency	String (3)	Fixed	Y	ISO-4217	Currency
totalAmount	Object		Y		-

value	String (13.2)	Max	Y	Numeric	Total amount paid by customer through BCA.
currency	String (3)	Fixed	Y	ISO-4217	Currency
trxDateTime	Date (25)	Fixed	Y	ISODateTime ISO-8601	From Payment Request
referenceNo	String (11)	Fixed	C	Numeric	From Payment Request. Mandatory for non-multi bill transaction.
paymentFlagStatus	String (2)	Fixed	Y		Status for Payment Flag defined by Partner to be displayed to BCA's Channel screen. This field may vary with these values: - 00 = Success payment flag - 01 = Reject payment flag by partner, partner must define reason for this status in paymentFlagReason field values in two languages. - 02 = Timeout payment flag between switcher to partner. If company's reconciliation type is reversal or force settle, transaction with status 02 will be considered as success transaction. Payment flag status other than 00,01,02 will be considered as 01.
billDetails	Array of Objects		C		Array with maximum 5 Objects. Mandatory for multi bills and non multi bills transaction

					with multi settlements.
billerReferenceId	String (11)	Fixed	Y	Numeric	From Payment Request. This field value must be the same with billerReferenceNo from payment request
billNo	String (18)	Max	Y		From Inquiry Response
billDescription	Object		Y		From Inquiry Response
english	String (18)	Max	Y		From Inquiry Response
indonesia	String (18)	Max	Y		From Inquiry Response
billSubCompany	String (5)	Fixed	Y		From Inquiry Response
billAmount	Object		Y		From Inquiry Response
value	String (13.2)	Max	Y	Numeric	Transaction Amount. From Payment Request
currency	String (3)	Fixed	Y	ISO-4217	Currency
additionalInfo	Object		N		Additional Information for custom use in each bill. Refer to Appendix B for complete list of additionalInfo for Virtual Account
status	String (2)	Fixed	Y		Payment status for specific Bill
reason	Object		Y		Reason for Payment Status for specific Bill multi language
english	String (64)	Max	Y		Reason for Payment Status for specific Bill in English

indonesia	String (64)	Max	Y	Reason for Payment Status for specific Bill in Bahasa
freeTexts	Array of Objects		N	Optional. Array with maximum 9 Objects and will be displayed in channel's screen. This field must be defined in two languages.
english	String (32)	Max	Y	Will be shown in Channel
indonesia	String (32)		Y	Will be shown in Channel
additionalInfo	Object		N	Additional Information for custom use. Refer to Appendix B for complete list of additionalInfo for Virtual Account

Notes:

- The length of the characters sent must not exceed the number stated in the technical documentation.
- If the response code is not either 2002500, 2022500, or 4042518, BCA will consider the response as a failed transaction and will be rejected.
- BCA will continue to check the paymentFlagStatus and paymentFlagReason field if the responseCode received is 2002500, 2022500, or 4042518.
- If a system error occurs and causes BCA to send a double flagging request with the same X-EXTERNAL-ID and paymentRequestId, then the partner can send responseCode "4042518" and responseMessage "Inconsistent Request", with paymentFlagStatus and paymentFlagReason according to the results of the first request.
- The final status of payment flag response is not determined by responseCode and responseMessage.
- For responseCode, paymentFlagStatus and status inside billDetails, this is condition for timeout:

responseCode	paymentFlagStatus	Status inside billDetails	Final Status
N	N	N	Timeout
N	Y	Y	Timeout
Y (Success)	N	N	Timeout
Y (Failed)	N	N	Failed

- For multi bills and non multi bills transaction with multi settlement:
 - billDetails is mandatory.
 - paymentFlagStatus field shows the final status for all bills.

- Status and reason defined in billDetails must be the same for all bills and contain the same status and reason as paymentFlagStatus and paymentFlagReason field.
- Multi settlements is available for fixed bill and variable bill type.
- For multi settlement both fixed and variable bill types:
 - for fixed bill type, The settlement is processed based on the billAmount within the billDetails object from the payment flag request sent by BCA.
 - for variable bill type, The settlement is processed based on the billAmount field within the billDetails object from the payment flag response sent by the Company Partner. The billDetails object can be sent in random order and customized according to Company Partner needs. The total sum of billAmount across all bill details must match the paidAmount from the payment flag request sent by BCA. If these amounts do not match, the funds will be settled to the default sub-company code (00000) based on data recorded in BCA.
- currency must be the same for totalAmount, billAmount, and paidAmount. The currency field may vary with these values: IDR, SGD, USD.
- If BCA sends a flagging request with the same X-EXTERNAL-ID but a different paymentRequestId, then the partner can send responseCode "4092500" and responseMessage "Conflict".
- The usage of additional info is to be discussed with BCA first.

Appendix A: Expected Response from Partner

Scenario	responseCode	responseMessage	paymentFlagStatus
Access Token Invalid	4012501	"Invalid Token (B2B)"	-
Unauthorized. Signature	4012500	"Unauthorized. [reason]"	-
Unauthorized. stringToSign	4012500	"Unauthorized. [reason]"	-
Unauthorized. Unknown Client	4012500	"Unauthorized. [reason]"	-
Missing Mandatory Field {} ..., etc	4002502	"Invalid Mandatory Field (field name)"	01
Invalid Field Format {} ..., etc	4002501	"Invalid Field Format (field name)"	01
Cannot use the same X-EXTERNAL-ID	4092500	"Conflict"	01
The inputted Virtual Account Number is Valid	2002500	"Successful"	00
The inputted Virtual Account Number Has Been Paid	4042514	"Paid Bill"	01
The inputted Virtual Account Number Has Been Expired	4042519	"Invalid Bill/Virtual Account"	01

Scenario	responseCode	responseMessage	paymentFlagStatus
The inputted Virtual Account Number is Unregistered	4042512	"Invalid Bill/Virtual Account [Reason]"	01
The amount in not as expected	4042513	"Invalid amount"	01
Duplicate X-EXTERNAL-ID and paymentRequestId	4042518	"Inconsistent Request"	00/01
Request Parsing Error	4002500	"Bad Request"	01
Response Parsing Error	4002500	"Bad Request"	01

Appendix B: Additional Info

Field	Name	Data Type	Mandatory
1	additionalInfo	Object	FALSE
	additionalInfo1	Object	FALSE
	1.1	label	TRUE
	1.1.1	english	TRUE
	1.1.2	indonesia	TRUE
	1.2	value	TRUE
	1.2.1	english	TRUE
	1.2.2	indonesia	TRUE
	2	additionalInfo2	FALSE
	2.1	label	TRUE
2	2.1.1	english	TRUE
	2.1.2	indonesia	TRUE
	2.2	value	TRUE
	2.2.1	english	TRUE
	2.2.2	indonesia	TRUE
	3	additionalInfo3	FALSE
	3.1	label	TRUE

Field	Name		Data Type	Mandatory
	3.1.1	english	String(50)	TRUE
	3.1.2	indonesia	String(50)	TRUE
	3.2	value	Object	TRUE
	3.2.1	english	String(200)	TRUE
	3.2.2	indonesia	String(200)	TRUE
4	additionalInfo4		Object	FALSE
	4.1	label	Object	TRUE
	4.1.1	english	String(50)	TRUE
	4.1.2	indonesia	String(50)	TRUE
	4.2	value	Object	TRUE
	4.2.1	english	String(200)	TRUE
	4.2.2	indonesia	String(200)	TRUE
5	additionalInfo5		Object	FALSE
	5.1	label	Object	TRUE
	5.1.1	english	String(50)	TRUE
	5.1.2	indonesia	String(50)	TRUE
	5.2	value	Object	TRUE
	5.2.1	english	String(200)	TRUE
	5.2.2	indonesia	String(200)	TRUE
6	additionalInfo6		Object	FALSE
	6.1	label	Object	TRUE
	6.1.1	english	String(50)	TRUE
	6.1.2	indonesia	String(50)	TRUE
	6.2	value	Object	TRUE
	6.2.1	english	String(200)	TRUE

Field	Name		Data Type	Mandatory
9	6.2.2	indonesia	String(200)	TRUE
	additionalInfo9		Object	FALSE
	9.1	label	Object	TRUE
	9.1.1	english	String(50)	TRUE
	9.1.2	indonesia	String(50)	TRUE
	9.2	value	Object	TRUE
	9.2.1	english	String(200)	TRUE
	9.2.2	indonesia	String(200)	TRUE
	additionalInfo10		Object	FALSE
	10.1	label	Object	TRUE
10	10.1.1	english	String(50)	TRUE
	10.1.2	indonesia	String(50)	TRUE
	10.2	value	Object	TRUE
	10.2.1	english	String(200)	TRUE
	10.2.2	indonesia	String(200)	TRUE


```
1 "Sample for single settlement (non multi bills) transaction"
2
3 -H 'Content-Type: application/json'
4 -H 'Authorization: Bearer
5 gp9HjjEj813Y9JGoqwOeOPWbnt4CUpvIJbU1mMU4a11MNDZ7Sg5u9a'
6 -H 'X-TIMESTAMP: 2023-12-25T13:59:21+08:00'
7 -H 'X-SIGNATURE:
8 85be817c55b2c135157c7e89f52499bf0c25ad6eeeb04a986e8c862561b19a5'
9 -H 'ORIGIN: www.hostname.com'
10 -H 'CHANNEL-ID': '95231'
11 -H 'X-PARTNER-ID': '12345'
12 -H 'X-EXTERNAL-ID': '123456789012345678901234567890123456'
13 -d '
14 {
```

```
1 "Sample for single settlement (non multi bills) transaction"
2
3 -H 'Content-Type: application/json'
4 -H 'X-TIMESTAMP: 2023-12-25T13:59:21+08:00'
5 {
6   "responseCode": "2002500",
7   "responseMessage": "Successful",
8   "virtualAccountData": {
9     "paymentFlagReason": {
10       "english": "Success",
11       "indonesia": "Sukses"
12     },
13     "partnerServiceId": "12345",
14     "customerNo": "123456789012345678",
15     "virtualAccountNo": "100151001567890100156789"
```

This service is used to VA transfer BillPresentment.

Field	Params Type	Data Type	Length Type	Mandatory	Description
-------	-------------	-----------	-------------	-----------	-------------

CHANNEL-ID	Header	String(5)	Y	Channel' Identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String(32)	Y	Partner ID using Corporate ID KlikBCA Bisnis
X-EXTERNAL-ID	Header	String (32)	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit) In BCA, virtualAccountNo max length is 26 (partnerServiceId(8 digits)+customerNo(18 digits)).

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String (150)	Max	Y	-	Response message description
virtualAccountData	Object		Y		
virtualAccountNo	String (28)	Max	Y	Alphanumeric	partnerServiceId (8 digit left padding space) + customerNo (up to 20 digits)
virtualAccountName	String (255)	Max	Y	Alphanumeric	Customer name

totalAmount	Array of Objects		N		
value	String (16.2)	Max	Y		Send by BCA. Total amount with 2 decimal In BCA, totalAmount max length is 13.2 digits.
currency	String (3)	Fixed	Y	ISO-4217	Send by BCA. Currency of amount based on ISO 4217
billDetails	Array of Objects		N		Array with maximum 24 Objects
billDescription	Object		N		Send by BCA. Bill Description
english	String (18)	Max	N	Alphanumeric	Send by BCA. Bill Description in English
indonesia	String (18)	Max	N	Alphanumeric	Send by BCA Bill Description in Bahasa
billAmount	Array of Objects		N		
value	String (16.2)		N		Send by BCA. Transaction amount. Nominal inputted by Customer with 2 decimal In BCA, billAmount max length is 13.2 digits.
currency	String (3)	Max	Y	ISO-4217	Currency
additionalInfo	String	Max	N	Alphanumeric	Additional information for custom use for each bill
freeTexts	String		N		Send by BCA. Array with maximum 25 objects

english	String (32)	Max	N	Alphanumeric	Will be shown in Channel
indonesia	String (32)	Max	N	Alphanumeric	Will be shown in Channel
virtualAccountTrxType	String (1)	Fixed	N		Type of Virtual Account that send by BCA is the highlighted transaction type. 1. Closed Payment (C): Tagihan muncul, harus dibayar sesuai tagihan (Fixed Bill) 2. Open Payment (O): Tagihan tidak muncul (No Bill) 3. Partial (I): Sisa tagihan 4. Minimum (M): Dibayar hanya sekali dengan nominal minimum namun tidak boleh lebih kecil dari tagihan. 5. Maximum (L): Dibayar hanya sekali, tidak boleh lebih besar dari tagihan, dan tagihan muncul 6. Open Minimum (N): Dibayar berkali2 dengan nominal minimum namun tidak boleh lebih kecil dari tagihan dan muncul tagihannya. 7. Open Maximum (X): Dibayar berkali2 dengan nominal maksimum (cumulative) namun tidak boleh lebih besar dari tagihan dan muncul tagihannya. 8. Bill Variable (V): Bisa dibayar sekail, bisa lebih besar / lebih kecil dari tagihan, dan tagihan

					muncul. 9. Multi Bill Variable (W)
feeAmount	Array of Object		N		
value	String (16.2)	Max	Y		Send by BCA. Nominal inputted by customer with 2 decimal. In BCA, totalAmount max length is 13.2 digits.
currency	String (3)	Fixed	Y	ISO-4217	Currency
productName	String (30)	Max	N	Alphanumeric	Send by BCA. Product category

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
400	4003200	Bad request
400	4003201	Invalid Field Format {field name}
400	4003202	Invalid Mandatory Field {field name}
401	4013200	Invalid token (B2B)
401	4013201	Unauthorized. [Reason]
403	4033201	Feature Not Allowed
404	4043212	Invalid Bill
404	4043214	Paid Bills
409	4093211	Conflict
429	4293200	Too Many Requests
500	5003200	General Error
500	5003200	Internal Server Error
504	5043200	Timeout

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-va/inquiry-intrabank
```

Request



```
1  -H 'CHANNEL-ID': '95051'
2  -H 'X-PARTNER-ID': '1234567890'
3  -H 'X-EXTERNAL-ID': '41807553358950093184162180797837'
4  -d '
5  {
6    "virtualAccountNo" : "0008899912345678901234567890",
7    "amount" : {
8      "value" : "50000.00",
9      "currency" : "IDR"
10   }
11  }'
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-va/inquiry-intrabank
```

Response



```
1  {
2    "responseCode": "2003200",
3    "responseMessage": "Successful",
4    "virtualAccountData": {
5      "virtualAccountNo": "0008899912345678901234567890",
6      "virtualAccountName": "Jokul Doe",
7      "totalAmount": {
8        "value": "88000.00",
9        "currency": "IDR"
10     },
11     "billDetails": [
12       {
13         "billDescription": {
14           "english": "Maintenance",
15           "indonesian": "Pemeliharaan"
```

2. SNAP Virtual Account Notification Payment to VA from Intrabank

This service is used to Notification VA transfer.

Additional Headers:

Field	Params Type	Data Type	Mandatory	Format	Description
CHANNEL-ID	Header	String(5)	Y	95051	Channel' Identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String(32)	Y	-	Partner client id using KlikBCA Bisnis's Corporate

ID					
X-EXTERNAL-ID	Header	String(32)	Y	Alphanumeric	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Mandatory	Format	Description
virtualAccountNo	String (28)	Y	Alphanumeric	Send by BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digits) In BCA, virtualAccountNo max length is 26 (partnerServiceId (8 digits) + customerNo (18 digits)).
partnerReferenceNo	String (128)	Y	-	Send by BCA. Unique identifier for this Payment. Generated by Partner. In BCA, partnerReferenceNo max length is 64 digits.
trxDateTime	Date (25)	N	-	Send by BCA. PJP internal system datetime with timezone, which follows the ISO-8601 standard
paymentStatus	String (20)	N	Alphanumeric	Send by BCA. Status of payment request
paymentFlagReason	Objects	N	-	Reason for Payment Status multi language
english	String (200)	N	Alphanumeric	Send by BCA. Reason for Payment Status in English
indonesia	String (200)	N	Alphanumeric	Send by BCA. Reason for Payment Status in Bahasa

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String (150)	Max	Y	-	Response description
virtualAccountData	Object		Y		
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA according to request input. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digits). In BCA, virtualAccountNo max length is 26 (partnerServiceId (8 digits) + customerNo (18 digits)).
partnerReferenceNo	String (128)	Max	Y	-	Mandatory in BCA according to request input. From Payment request

The following structure should be returned only when not-success with additional related HTTP status of the response if applicable.

The copartners define the responseCode by themselves. For the multi-languageresponseMessage, it allowed to use same value if multi-language are not possible

```
{
  "responseCode" : "Error Code",
  "responseMessage" : "Error Message",
  "virtualAccountData":
  {
    "virtualAccountNo": "",
    "partnerReferenceNo": ""
  }
}
```



```
curl -X POST https://copartners.com/openapi/v1.0/transfer-va/notify-payment-intrabank
```

Request



```
1  -H 'CHANNEL-ID': '95051'
2  -H 'X-PARTNER-ID': 'KBCABCINDO'
3  -H 'X-EXTERNAL-ID': '41807553358950093184162180797837'
4  -d '
5  {
6    "virtualAccountNo": " 8889912345678901234567890",
7    "partnerReferenceNo": "12345678",
8    "trxDateTime": "2020-12-21T10:30:24+07:00",
9    "paymentStatus": "Success",
10   "paymentFlagReason": {
11     "english": "Success",
12     "indonesia": "Sukses"
13   }
14 }
```

```
curl -X POST https://copartners.com/openapi/v1.0/transfer-va/notify-payment-intrabank
```

Response



```
1  {
2    "responseCode": 2003400,
3    "responseMessage": "Successful",
4    "virtualAccountData": {
5      "virtualAccountNo": " 8889912345678901234567890",
6      "partnerReferenceNo": "12345678"
7    }
8  }
```

3. SNAP Virtual Account Payment to VA from Intrabank

This service is used to VA transfer.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Format	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	95051	Channel' Identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String(32)	Max	Y		Partner client id using KlikBCA Bisnis's WSID (95051)

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit) In BCA, virtualAccountNo max length is 26 (partnerServiceId(8 digits)+customerNo(18 digits)).
virtualAccountEmail	String (255)	Max	N	-	Optional BCA Customer email with max length is 255 digits.
sourceAccountNo	String (32)	Max	N	Numeric	Source account number
partnerReferenceNo	String (128)	Max	Y	-	Mandatory in BCA. Unique identifier for this Payment. Generated by PJP
paidAmount	Object		Y		
value	String (16.2)	Max	Y		Mandatory in BCA. Paid amount with 2 decimal In BCA, partnerReferenceNumber max length is 13.2 digits
currency	String (3)	Fixed	Y	ISO-4217	Mandatory in BCA. Currency of amount based on ISO 4217
trxDateTime	Date (25)	Fixed	N	-	Mandatory in BCA. PJP internal system datetime with timezone, which follows the ISO-8601 standard

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String (150)	Max	Y	-	Response message description
virtualAccountData	Object		Y		
virtualAccountNo	String (28)	Max	Y	Alphanumeric	partnerServiceId (8 digit left padding space) + customerNo (up to 20 digits)
virtualAccountName	String (255)	Max	Y	Alphanumeric	Customer name
virtualAccountEmail	String (255)	Max	N		Customer email
sourceAccountNo	String (32)	Max	N	-	Source account number
partnerReferenceNo	String (128)	Max	Y	-	From Payment request
referenceNo	String (128)	Max	N	Numeric	Generated by PJP
paidAmount	Object		N		-
value	String (16.2)	Max	Y		Send by BCA according to the request input. From Payment request with max length (13.2).
currency	String (3)	Fixed	Y	ISO-4217	Send by BCA according to the request input. Currency from Payment request.
paidAmount	Object		N		
value	String (16.2)	Max	Y		Send by BCA according to the request input. From Payment request with max

					length (13.2).
currency	String (3)	Fixed	Y	ISO-4217	Send by BCA. Currency
trxDateTime	Date (25)	Max	N		From Payment Request
billDetails	Array of Objects		N		Array with maximum 24 Objects
billDescription	JSON Object		N		Bill Description
english	String (18)	Max	N	Alphanumeric	Bill Description in English
indonesia	String (18)	Max	N	Alphanumeric	Bill Description in Bahasa
billAmount	Array of Objects		N		
value	String (16.2)		N		Send by BCA. Nominal inputted by Customer with 2 decimal In BCA, billAmount max length is (13.2) digits.
currency	String (3)	Max	Y	ISO-4217	Currency
freeTexts	Array of Objects		N	-	From Inquiry response
english	String (32)	Max	N	Alphanumeric	From Inquiry response
indonesia	String (32)	Max	N	Alphanumeric	From Inquiry response
feeAmount	Object		N		
value	String (16.2)	Max	Y		Send by BCA. Nominal inputted by customer with 2 decimal. In BCA, totalAmount max length is 13.2 digits.

currency	String (3)	Fixed	Y	ISO-4217	Send by BCA. Currency
productName	String (30)	Max	N	Alphanumeric	Send by BCA. Product category

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
400	4003300	Bad request
400	4003301	Invalid Field Format {field name}
400	4003302	Invalid Mandatory Field {field name}
401	4013300	Unauthorized. [Reason]
401	4013301	Invalid token (B2B)
403	4033301	Feature Not Allowed
403	4033302	Exceeds Transaction Amount Limit
403	4033304	Activity Count Limit Exceeded
404	4043312	Invalid Bill
404	4043314	Paid Bills
409	4093311	Conflict
429	4293300	Too Many Requests
500	5003301	Internal Server Error
500	5003300	General Error
504	5043300	Timeout

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-va/payment-intrabank
```

Request



```
1  -H 'CHANNEL-ID': '95051'
2  -H 'X-PARTNER-ID': 'KBCABCINDO'
3  -H 'X-EXTERNAL-ID': '41807553358950093184162180797837'
4  -d '
5  {
6    "virtualAccountNo": "00088999123456789012345678900008899912345678901234567890",
7    "virtualAccountEmail": "john@email.com",
8    "sourceAccountNo": "1234567890",
9    "partnerReferenceNo": "12345678",
10   "paidAmount": {
11     "value": "50000.00",
12     "currency": "IDR"
13   }
14   "trxDateTime": "2020-12-21T10:30:24+07:00"
15 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-va/payment-intrabank
```

Response



```
1  {
2    "responseCode": 2023300,
3    "responseMessage": "Request In Progress",
4    "virtualAccountData":
5    {
6      "virtualAccountNo": "0008889912345678901234567890",
7      "virtualAccountName": "Jokul Doe",
8      "virtualAccountEmail": "john@email.com",
9      "sourceAccountNo": "1234567890",
10     "partnerReferenceNo": "12345678",
11     "referenceNo": "12345678901234",
12     "paidAmount":
13     {
14       "value": "55000.00",
15       "currency": "IDR"
16     }
17   }
18 }
```

ECR EDC

1. ECR EDC BCA Inquiry Status

With ECR EDC BCA Inquiry Status, users can record and keep users' payment status when doing transaction with EDC BCA.

ECR EDC BCA Inquiry Status can be used to check current status of transactions below:

- Purchase
- QRIS
- QRIS Tap
- Flazz Payment

- QRIS Refund
- Void
- Settlement
- Top Up Flazz
- Cash Top Up Flazz
- Get Card Info
- Cardver / Pre-auth
- Top Up Cardver
- Release Cardver
- Offline
- Register Token

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier u EDC's WSID (95251)
X-PARTNER-ID	Header	String (36)	Max	Y	Unique ID for partner Merchant Direct: Gro Code / MID / Partner I Partner Id used for pa type partnerships, wh the integration or agreem established at the pai level rather than individual merchants. Group Code used for regular merchant wh merchant operates multiple bra under one group. This identifies the group a whole. Merchant Id used for regular merchant partnerships where the merchant has onl single branch. This ID uniquely

					identifies that single merchant.
X-EXTERNAL-ID	Header	String (36)	Max	Y	A unique identifier for API request sent by merchant (per hit/request). Must be unique for every request (including retries).
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that requested: - 42 Inquiry Status Purchase / Void / Settlement / QRIS Tap / Flazz Payment / QRIS Refund / Top Up Cash Top Up Flazz / Gift Card Info/ Cardver / Top Up Cardver / Release Card Offline / Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicator to be used later
originalPartnerReferenceNo	String(64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a unique transaction generated by the merchant when Request Payment. Format: Include character "-". Example: 1. EA-012432342asea for originalPartnerReference that use character "-" 2. PEG34820938408 for originalPartnerReference that don't use character

Result of the request will contains following information:

Response:

Inquiry Status Purchase / Void / Settlement / QRIS / QRIS Tap / Flazz Payment / QRIS Refund / Flazz

Top Up / Cash Top Up Flazz / Get Card Info/ Cardver / Top Up Cardver / Release Cardver / Offline / Register Token (Pending)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
merchantId	String (9)	Max	Y	Numeric	MID Merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction request type - 42 = In Purchase Settlement Tap / Flazz Refund , Cash To Card Info Up Cardver Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a unique identifier generated when Register. Format: “_“. Example 1. EA-01 for originalPartnerReferenceNo that use 2. PEG3 for originalPartnerReferenceNo that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Server create Date

Inquiry Status Purchase / Void / Settlement / QRIS / QRIS Tap / Flazz Payment / QRIS Refund / Flazz Top Up / Cash Top Up Flazz / Get Card Info / Cardver / Top Up Cardver / Release Cardver / Offline / Register Token (Suspend)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Error Message with code - Get Card Honor. - Other Request
merchantId	String (9)	Max	Y	Numeric	MID Merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction request - 42 = Immediate Purchase Settlement Tap / Flash QRIS Recharge Cash To / Get Card Top Up (Cardver Token).
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a unique generated when Request Format: “-“. Example 1. EA-01 originalPartnerReferenceNo that use 2. PEG3. originalPartnerReferenceNo for originalPartnerReferenceNo that don't use
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Server create Date

Inquiry Status Purchase / Void (Success) for Debit / Credit Transaction

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Trans
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction Type - 42 = In-Store - 43 = Online - 44 = QRIS - 45 = Tap / Flash - 46 = QRIS Recharge - 47 = Cash To Bank - 48 = Get Cash - 49 = Top Up Card - 50 = Cardver - 51 = Token
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	Original Partner Reference Number is a unique identifier generated when Request is created. Format: "____". Example: 1. EA-01 for original partner that use 2. PEG3 for original partner that don't use character
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Server create Date
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get from transaction Date
additionalInfo	Object				Additional information by Card info detail

batchNumber	String (6)	Fixed	Y	Numeric	Batch tr
traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Numeric	When ar the EDC but the s pending the statu replies t
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of
cardholderName	String (150)	Max	Y	Alphanumeric	Cardhol Number Format i amount will be n
amount1	String (9.2)	Max	Y	Numeric	Value ar For rew and tip t amount' with am For DCC amount' replace convert always c in the or currenc convert reflecte dccAmc
amount2	String (9.2)	Max	N	Numeric	Value Tip BCA, an added v For DCC amount: replace convert always c in the or currenc convert

					reflecte dccAmc
originalAmount	String (9.2)	Max	N	Numeric	Paymen reward c used for paymen redemp The orig present Purchas transact redemp
redeemAmount	String (9.2)	Max	N	Numeric	Reward credit c with rev The rede will be r for rewa credit c transact Purchas transact type.
fxRate	String (12.7)	Max	N	Numeric	Represe convers convert amount merchal to the c currenc This fiel for DCC Notes: E strictly a merchal feature
currency	String (3)	Fixed	N	Alphanumeric	Represe chosen l during a This fiel for DCC Notes: E strictly a merchal feature
dccAmount1	String (9.2)	Max	N	Numeric	Represe payable currenc been ap

					DCC ex (FXRate applicat transact Transac available merchai feature
cardToken	String (32)	Max	C	Alphanumeric	Represe card nur based o submitt request. mandat that use feature. Token is only for have EC in EDC E

Inquiry Status Void (Success) for Debit / Credit Transaction

Field	Data Type	Length Type	Mandatory	Format	Descript
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code.
responseMessage	String (150)	Max	Y	Alphanumeric	Response descri
midTrans	String (15)	Max	Y	Numeric	MID Transaction I
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal Id Trans
transType	String (2)	Fixed	Y	Numeric	Transaction Type requested: - 42 = Inquiry Sta Purchase / Void / Settlement / QRI Tap / Flazz Payme Refund / Top Up I Cash Top Up Flaz Card Info / Cardv Up Cardver / Rel Cardver / Offline Token.
originalPartnerReferenceNo	String 64)	Max	Y	Alphanumeric	originalPartnerRe is a unique transa generated by the when Request Pa

					Format: Include c “-“. Example: 1. EA-012432342 originalPartnerRe that use character 2. PEG34820938 for originalPartnerRe that don't use ch
createdDate	String (25)	Fixed	Y	Date	Format(YYYY-MM DDTHH:MM:SS+(send response / create DB if succ
transDate	String (25)	Fixed	Y	Date	Format(YYYY-MM DDTHH:MM:SS+(from BCA's host transaction.
additionalInfo	Object				Additional info ca by Card/QRIS ad info detail.
batchNumber	String (6)	Fixed	Y	Numeric	Batch transaction
traceNo	String 16)	Max	Y	Numeric	Number for track destination bank
referenceNo	String (64)	Max	Y	Numeric	Reference numb transaction.
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code is generated and p EDC when transa status is success transaction statu success, Approv empty or null resq
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID.
cardType	String (255)	Max	Y	Alphanumeric	Type of Card.
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Name Number. Format based on amount name that will be
amount1	String (9.2)	Max	Y	Numeric	Value Amount Tr For reward, cash transactions, am

					netting value wit For void transact amount will start mark. For DCC transac amount1 must no replaced with the converted value. always contain th in the original rec currency, while th converted amou reflected in the dccAmount1 field
amount2	String (9.2)	Max	N	Numeric	Value Tips / Cash For Cash BCA, ar added with Cash For void transact amount will start mark. For DCC transac amount2 must nc replaced with the converted value. always contain th in the original rec currency, while th converted amou reflected in the dccAmount1 field
originalAmount	String (9.2)	Max	N	Numeric	Payment amount reward deductio credit card paym reward redempti The originalAmou present only for c Purchase or Void transactions with redemption appl For void transact originalAmount v with minus mark.

redeemAmount	String (9.2)	Max	N	Numeric	Reward amount to be returned to the credit card payer for reward redemption. The redeemAmount will be returned to the credit card payer for reward redemption credit card transaction with a Purchase credit card transaction type.
fxRate	String (12.7)	Max	N	Numeric	Represents the conversion ratio to convert the transaction amount from the merchant's local currency to the cardholder's currency. This field is applicable for DCC transaction. Notes: DCC Transaction is strictly available for merchants that have the feature in EDC Backend.
currency	String (3)	Fixed	N	Alphanumeric	Represent the currency chosen by the cardholder during a DCC transaction. This field is applicable for DCC transaction. Notes: DCC Transaction is strictly available for merchants that have the feature in EDC Backend.
dccAmount1	String (9.2)	Max	N	Numeric	Represents the final payable amount after currency conversion has been applied, based on the DCC exchange rate (FXRate). This field is applicable for DCC transaction. Notes: DCC Transaction is strictly available for merchants that have the feature in EDC Backend.

Inquiry Status Purchase (Success) for Flazz Transaction

Field	DataType	Length Type	Mandatory	Format
-------	----------	----------------	-----------	--------

responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Trans
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction Type request - 42 = In Purchas Settlem Tap / Fl QRIS Re Cash To / Get C Top Up C Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a uniq generat when Re Format: “-“. Example 1. EA-01 originalPartnerReferenceNo that use 2. PEG3 for originalPartnerReferenceNo that dor character
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Since created
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get from
additionalInfo	Object				Additional Information by Card
batchNumber	String (6)	Fixed	Y	Numeric	Batch number

traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Numeric	Approva generat EDC wh status is transact success empty c
amount1	String (9.2)	Max	Y	Numeric	Value ar

Inquiry Status Settlement (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response
responseMessage	String (150)	Max	Y	Alphanumeric	Response
merchantId	String (9)	Max	Y	Numeric	MID Mer
terminalId	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fla Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalf is a uniq generat when Re Format: “-“. Example 1. EA-01

					for original that use 2. PEG3, for original that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Array of Object				
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
midTrans	String (15)	Max	Y	Alphanumeric	MID Tra
settleTrans	String (10)	Max	Y	Alphanumeric	DEBIT, C
batchNumber	String (6)	Fixed	Y	Numeric	Transac recorde
totalCount	String (3)	Max	Y	Numeric	Value cc
totalAmount	String (10.2)	Max	Y	Numeric	Value ar

Inquiry QRIS / QRIS Tap (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
midTrans	String (15)	Max	Y	Numeric	MID Tra
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem

					Tap / Fle Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalF is a uniq generat when Re Format: “-“. Example 1. EA-01 for originalF that use 2. PEG3. for originalF that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Time Se create E
transDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Object				Additior by Card info det.
batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr
referenceNo	String (64)	Max	Y	Numeric	Referen transact
rrn	String (12)	Max	Y	Alphanumeric	QRIS RR the issu
traceNo	String (16)	Max	Y	Numeric	Number destinat
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approva generat EDC wh status is transact success

					empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
issuerName	String (12)	Max	Y	Alphanumeric	Issuer N
customerPan	String (19)	Fixed	Y	Numeric	Buyer cã (custom used to transact Mandate requires paymen
merchantPan	String (19)	Fixed	Y	Numeric	Merchar example 936000
personalNumber	String (16)	Max	Y	Numeric	Will be f receive number. Format: last 2 dig else ma
cardholderName	String (150)	Max	Y	Alphanumeric	Cardhol Number Format i amount will be n
amount1	String (9.2)	Max	Y	Numeric	Value ar
amount2	String (9.2)	Max	N	Numeric	Value ar Note: Fc transact filled

Inquiry QRIS Refund (Success)

Field	DataType	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina

transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fle Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalF is a uniq generat when Re Format: “-“. Example 1. EA-01 originalF that use 2. PEG3. for originalF that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Object				Additior by Card info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr
referenceNo	String (64)	Max	Y	Numeric	Referen transact
rrn	String (12)	Max	Y	Alphanumeric	QRIS Re generat from the RRN.
traceNo	String (16)	Max	Y	Numeric	Number destinat

approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code generated by EDC when transaction status is successful. If empty, cardholder must enter approval code.
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
issuerName	String (12)	Max	Y	Alphanumeric	Issuer Name
customerPan	String (19)	Fixed	Y	Numeric	Buyer card number (customer's card used to transact). Mandatory if requires payment.
merchantPan	String (19)	Fixed	Y	Numeric	Merchant card number. Example: 936000
personalNumber	String (16)	Max	Y	Numeric	Will be filled if receive number. Format: last 2 digits, else max 16 digits.
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Name. Format: last 100 characters, amount will be filled.
amount1	String (9.2)	Max	Y	Numeric	Value amount. For QRIS transaction, start with 0.
originalDate	String (8)	Fixed	Y	Numeric	Only for transaction. Original Format: YYYYMMDD
originalRrn	String (12)	Max	Y	Alphanumeric	Only for transaction. Original Format: 12 alphanumeric
remainingRefundAmount	String (9.2)	Max	N	Numeric	Only for transaction. Format: last 10 characters, amount will be filled.

Remaini
amount.

Inquiry Status Flazz Top Up (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response
responseMessage	String (150)	Max	Y	Alphanumeric	Response
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fla Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalP is a uniq generat when Re Format: “- “. Example 1. EA-01 originalP that use 2. PEG3 for originalP that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-	Get fron

DDTHH:MM:SS+07:00)					
additionalInfo	Object				Addition by Card info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr
traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approva generat EDC wh status is transact success empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of
amount1	String (9.2)	Max	Y	Numeric	Value Ar
flazzBalance	String (9.2)	Max	Y	Numeric	Flazz Ba
pan	String (20)	Max	Y	Numeric	Flazz ca

Inquiry Status Cash Top Up Flazz (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request

					- 42 = In Purchas Settlem Tap / Fl Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalF is a uniq generat when Re Format: “-“. Example 1. EA-01 originalF that use 2. PEG3. for originalF that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Get fron
additionalInfo	Object				Additior by Card info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr
traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact

approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code generated by EDC when transaction is successful, empty if not
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of card
amount1	String (9.2)	Max	Y	Numeric	Value Amount 1
flazzBalance	String (9.2)	Max	Y	Numeric	Flazz Balance
pan	String (20)	Max	Y	Numeric	Flazz card number
panCashierCard	String (20)	Max	Y	Numeric	Access Card number

Inquiry Status Get Card Info (Success)

Field	Data Type	Length	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
merchantId	String (9)	Max	Y	Numeric	MID Merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal ID

transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fle Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalF is a uniq generat when Re Format: “-“. Example 1. EA-01 originalF that use 2. PEG3. for originalF that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY- MM- DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Object				Additior by Card info det
pan	String (20)	Max	Y	Numeric	Card nu
flazzBalance	String (9.2)	Max	Y	Numeric	Flazz Ba card).
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of

Inquiry Status Card Verification (Cardver) / Pre-Auth (Success)

Field	DataType	Length Type	Mandatory	Format	
responseCode	String(7)	Fixed	Y	Alphanumeric	Respor
responseMessage	String(150)	Max	Y	Alphanumeric	Respor
midTrans	String(15)	Max	Y	Numeric	MID Tra
tidTrans	String(8)	Max	Y	Alphanumeric	Termin
transType	String(2)	Fixed	Y	Numeric	Transa reques - 42 = I Purcha Settler Tap / F Refunc Cash T Card Ir Up Car Cardve Token.
originalPartnerReferenceNo	String(64)	Max	Y	Alphanumeric	origina is a uni genera when F Format “-“. Examp 1. EA-0 origina that us 2. PEG: for origina that dc
createdDate	String(25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time se create
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get frc transac
additionalInfo	Object				Additic by Car info de
batchNumber	String (6)	Fixed	Y	Numeric	Batch t

traceNo	String (16)	Max	Y	Numeric	Number of destination
referenceNo	String (64)	Max	Y	Numeric	Reference transaction
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval generated EDC with status in transaction successful or empty
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of card
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Name. Format amount will be
amount1	String (9.2)	Max	Y	Numeric	Card value represents temporary verify transaction and authorization capability
fxRate	String (12.7)	Max	N	Numeric	Represents conversion amount merchant to the current currency. This field for DCI. Notes: strictly merchant feature
currency	String (3)	Fixed	N	Alphanumeric	Represents chosen during transaction. This field for DCI. Notes: strictly

					merch: feature
dccAmount1	String (9.2)	Max	N	Numeric	Repres payabl curren been a DCC e: (FXRat This fie for DC Notes: strictly merch: feature
cardToken	String (32)	Max	C	Alphanumeric	Repres card n based submit reques This fie merch: API Tok Notes: strictly merch: API Tok BCA.

Inquiry Status Top Up Cardver (Success)

Field	DataType	Length Type	Mandatory	Format	Descrip
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code
responseMessage	String (150)	Max	Y	Alphanumeric	Response descri
midTrans	String (15)	Max	Y	Numeric	MID Transactor
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal Id Tran
transType	String (2)	Fixed	Y	Numeric	Transaction Typ requested: - 42 = Inquiry St Purchase / Void / QRIS / QRIS Ta Payment / QRIS Up Flazz / Cash / Get Card Info Top Up Cardver

					Cardver / Offlin Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerF is a unique trans generated by th when Request F Format: Include “_”. Example: 1. EA-01243234 originalPartnerF that use charac 2. PEG3482093 for originalPartnerF that don't use c
createdDate	String (25)	Fixed	Y	Date	Format(YYYY-MM-DDTHH:MM:SS+ send response / DB if successful
transDate	String (25)	Fixed	Y	Date	Format(YYYY-MM-DDTHH:MM:SS+ from BCA's hos transaction.
additionalInfo	Object				Additional info c by Card/QRIS a detail.
batchNumber	String (6)	Fixed	Y	Numeric	Batch transacti
traceNo	String (16)	Max	Y	Numeric	Number for trac destination ban
referenceNo	String (64)	Max	Y	Numeric	Reference numl transaction.
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code and printed on E transaction stat success. If trans status is not suc Approval Code null response.
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID.
cardType	String (255)	Max	Y	Alphanumeric	Type of Card.

cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Name. Format based on amount name that will be
previousCardverAmount	String (9.2)	Max	Y	Numeric	Previous cardver Represents the was already blo previous Card V transactions.
amount1	String (9.2)	Max	Y	Numeric	Top up cardver top up amount t to the block limi previous cardve does not the tot accumulated lin
totalCardverAmount	String (9.2)	Max	Y	Numeric	Total cardver ar (previousCardv totalCardverAn Represents the total block limit Top-Up Card Ve transaction.
fxRate	String (12.7)	Max	N	Numeric	Represents the conversion ratio convert the tra amount from th local currency t cardholder's bil currency. This field is appl for DCC transac Notes: DCC Tra strictly available merchants that feature in EDC E
currency	String (3)	Fixed	N	Alphanumeric	Represent the c chosen by the c during a DCC tr This field is appl for DCC transac Notes: DCC Tra strictly available merchants that feature in EDC E
previousCardverDccAmount	String (9.2)	Max	N	Numeric	Represent the p cardver amount currency conve

					been applied, based on the DCC exchange rate (FXRate).
dccAmount1	String (9.2)	Max	N	Numeric	Represents the amount after conversion has been applied, based on the exchange rate (FXRate). This field is applicable for DCC transactions. Notes: DCC Transactions are strictly available for merchants that have enabled this feature in EDC E
totalCardverDccAmount	String (9.2)	Max	N	Numeric	Represent the final amount. This value is calculated as the sum of the previousCardver and dccAmount1 (current cardver amount).
cardToken	String (32)	Max	C	Alphanumeric	Represent the tokenized card number generated based on the PAN during the request. This field is mandatory for merchants that have enabled the API Token feature. Notes: The ECR is strictly available for merchants that have enabled the API Token feature in BCA.

Inquiry Status Release Cardver (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Transaction ID
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction Type

					request - 42 = Ir Purchas Settlerr Tap / Fl Refund Cash To Card Ini Up Carc Cardve Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	original is a unic generat when R Format: “-“. Exempl 1. EA-01 original that use 2. PEG3 for original that doi
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time se create I
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fro transac
additionalInfo	Object				Additio by Carc info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch tr
traceNo	String (16)	Max	Y	Numeric	Number destina
referenceNo	String (64)	Max	Y	Numeric	Referer transac

approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code generated by EDC when transaction is successful. Empty if not successful.
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of card
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Name. Format amount will be R
amount1	String (9.2)	Max	Y	Numeric	Release Amount. Represents the amount being released. If block limit is reached, previous Card Verification transaction Release will start
currency	String (3)	Fixed	N	Alphanumeric	Representing the currency chosen during a transaction. This field is required for DCC. Notes: 1. It is not strictly merchant feature
dccAmount1	String (9.2)	Max	N	Numeric	Representing the payable currency amount. It has been applied DCC exchange rate (FXRate)
cardToken	String (32)	Max	C	Alphanumeric	Representing the card number based on the card submission request. This field is merchant feature

API Tok
Notes: 1
strictly
mercha
API Tok
BCA.

Inquiry Status Offline (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response
responseMessage	String (150)	Max	Y	Alphanumeric	Response
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fla Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalP is a uniq generat when Re Format: “-“. Example 1. EA-01 originalP that use 2. PEG3. for originalP that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time sei create C

transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get from transaction
additionalInfo	Object				Additional by Card info detail
batchNumber	String (6)	Fixed	Y	Numeric	Batch transaction
traceNo	String (16)	Max	Y	Numeric	Number destination
referenceNo	String (64)	Max	Y	Numeric	Reference transaction
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval generated EDC when status is transaction successful empty card
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of card
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Number based on name the card
amount1	String (9.2)	Max	Y	Numeric	Offline amount the amount process limit that held during Verification For DCC amount replace convert always convert in the original currency convert reflect the dccAmount
fxRate	String (12.7)	Max	N	Numeric	Represent conversion

					convert amount merchant to the currency
currency	String (3)	Fixed	N	Alphanumeric	Represent chosen during a This field for DCC Notes: D strictly a merchant feature
dccAmount1	String (9.2)	Max	N	Numeric	Represent payable currency been ap DCC ex (FXRate
cardToken	String (32)	Max	C	Alphanumeric	Represent card number based on submit request. This field merchant API Token Notes: T strictly a merchant API Token BCA.

Inquiry Status Register Token (Success)

Field	DataType	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response
responseMessage	String (150)	Max	Y	Alphanumeric	Response
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request

					- 42 = In Purchas Settlem Tap / Fle Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalF is a uniq generat when Re Format: “- “. Example 1. EA-01 originalF that use 2. PEG3. for originalF that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time sei create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Object				Additior by Card info det
cardToken	String (32)	Max	C	Alphanumeric	Represe card nur based o submitt request. Notes: T strictly a merchai API Toke BCA.

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition	Partner Action
202	202IS00	Request In Progress	Request in progress	Unpaid Transaction – Please try the inquiry again / Transaction failed.
400	400IS00	Bad request	General request failed error	Re-checking the JSON request sent by the partner.
400	400IS01	Invalid Field Format {field}	The data you entered does not match the format requirements	Re-checking the JSON request sent by the partner.
400	400IS02	Invalid Mandatory Field {field}	Mandatory field should be fulfilled	Re-checking the JSON request sent by the partner.
401	401IS00	Unauthorized. [Reason]	Invalid signature/Unknown client/Connection not allowed	Re-checking the request header sent by the partner.
401	401IS01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid	Re-checking the request header “Authorization” sent by the partner.
403	403IS01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.	Contact BCA to check your partnership data.
403	403IS05	Do Not Honor	Transaction Error From Host	Transaction failed.
403	403IS15	Transaction Not Permitted. [transType Not Found]	transType not available in the list	Re-checking the JSON request sent by the partner.
404	404IS01	Transaction Not Found	originalPartnerReferenceNo Not Found	Re-checking the JSON request sent by the partner.
404	404IS08	Invalid Merchant	Invalid Merchant	Re-checking the JSON request sent by the partner.
409	409IS00	Conflict	X-EXTERNAL-ID duplicate	Re-checking the request header “X-EXTERNAL-ID” sent by the partner.

429	429IS00	Too Many Requests	Maximum transaction limit exceeded	Please try again.
500	500IS00	General Error	Wrong request field input	Please try again.
500	500IS01	Internal Server Error	Unknown internal server failure, please retry the process again	Please try again.
504	504IS00	Timeout	Your transaction timeout	Please try again.

With ECR EDC BCA Inquiry Status, users can record and keep users' payment status when doing transaction with EDC BCA.

ECR EDC BCA Inquiry Status can be used to check current status of transactions below:

- Purchase
- QRIS
- QRIS Tap
- Flazz Payment
- QRIS Refund
- Void
- Settlement
- Top Up Flazz
- Cash Top Up Flazz
- Get Card Info
- Cardver / Pre-auth
- Top Up Cardver
- Release Cardver
- Offline
- Register Token

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier u EDC's WSID (95251)
X-PARTNER-ID	Header	String (36)	Max	Y	Unique ID for partner Merchant Direct: Gro Code / MID / Partner I Partner Id used for pa type partnerships, wr the

					integration or agreement established at the partner level rather than individual merchants. Group Code used for regular merchant where merchant operates multiple branches under one group. This identifies the group as a whole. Merchant Id used for regular merchant partnerships where the merchant has only single branch. This ID uniquely identifies that single merchant.
X-EXTERNAL-ID	Header	String (36)	Max	Y	A unique identifier for API request sent by merchant (per hit/request). Must be unique for every request (including retries).
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that requested: - 42 Inquiry Status Pull / Void / Settlement / QRIS Tap / Flazz Payment / QRIS Refund / Top Up Cash Top Up Flazz / G Card Info/ Cardver / Top Cardver / Release Cardver / Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicator to be used later
originalPartnerReferenceNo	String(64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a unique transaction identifier generated by the merchant

when Request Payme
Format: Include chara
“-“.
Example:
1. EA-012432342asea
for
originalPartnerRefere
that use character "-"
2. PEG34820938408:
for
originalPartnerRefere
that don't use charac

Result of the request will contains following information:

Response:

Inquiry Status Purchase / Void / Settlement / QRIS / QRIS Tap / Flazz Payment / QRIS Refund / Flazz Top Up / Cash Top Up Flazz / Get Card Info/ Cardver / Top Up Cardver / Release Cardver / Offline / Register Token (Pending)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response
responseMessage	String (150)	Max	Y	Alphanumeric	Response
merchantId	String (9)	Max	Y	Numeric	MID Mer
terminalId	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fla Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalP is a uniq generat when Re Format: “-“.

					Example 1. EA-01 for originalf that use 2. PEG3 for originalf that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C

Inquiry Status Purchase / Void / Settlement / QRIS / QRIS Tap / Flazz Payment / QRIS Refund / Flazz Top Up / Cash Top Up Flazz / Get Card Info / Cardver / Top Up Cardver / Release Cardver / Offline / Register Token (Suspend)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response
responseMessage	String (150)	Max	Y	Alphanumeric	Error Me with cor - Get C Honor. - Other Request
merchantId	String (9)	Max	Y	Numeric	MID Mer
terminalId	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = Ir Purchas Settlem Tap / Fla QRIS Re Cash To / Get C Top Up C Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalf is a uniq generat when Re Format:

					“_“. Example 1. EA-01 originalf that use 2. PEG3. for originalf that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C

Inquiry Status Purchase / Void (Success) for Debit / Credit Transaction

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fl QRIS Re Cash To / Get C Top Up C Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalf is a uniq generat when Re Format: “_“. Example 1. EA-01 for originalf that use

					2. PEG3, for original that dor character
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Object				Additior by Card info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch tr
traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Numeric	When ar the EDC but the s pending the stati replies t
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of
cardholderName	String (150)	Max	Y	Alphanumeric	Cardhol Number Format i amount will be n
amount1	String (9.2)	Max	Y	Numeric	Value ar For rew and tip t amount' with am For DCC amount' replace convert always c

					in the or currenc; convert reflecte dccAmc
amount2	String (9.2)	Max	N	Numeric	Value Tip BCA, an added v For DCC amount: replace convert always c in the or currenc; convert reflecte dccAmc
originalAmount	String (9.2)	Max	N	Numeric	Paymen reward c used for paymen redemp The orig present Purchas transact redemp
redeemAmount	String (9.2)	Max	N	Numeric	Reward credit c with rev The rede will be r for rewa credit c transact Purchas transact type.
fxRate	String (12.7)	Max	N	Numeric	Represe convert amount merchar to the c currenc; This fiel for DCC Notes: E strictly a

					mercha feature
currency	String (3)	Fixed	N	Alphanumeric	Represe chosen l during a This field for DCC Notes: D strictly a mercha feature
dccAmount1	String (9.2)	Max	N	Numeric	Represe payable currenc been ap DCC ex (FXRate applicat transact Transac available mercha feature
cardToken	String (32)	Max	C	Alphanumeric	Represe card nur based o submitte request. mandate that use feature. Token is only for have EC in EDC E

Inquiry Status Void (Success) for Debit / Credit Transaction

Field	Data Type	Length Type	Mandatory	Format	Descript
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code.
responseMessage	String (150)	Max	Y	Alphanumeric	Response descri
midTrans	String (15)	Max	Y	Numeric	MID Transaction I
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal Id Trans

transType	String (2)	Fixed	Y	Numeric	Transaction Type requested: - 42 = Inquiry Sta Purchase / Void / Settlement / QRI Tap / Flazz Payme Refund / Top Up I Cash Top Up Flaz Card Info / Cardv Up Cardver / Rel Cardver / Offline Token.
originalPartnerReferenceNo	String 64)	Max	Y	Alphanumeric	originalPartnerRe is a unique transa generated by the when Request Pa Format: Include c “-“. Example: 1. EA-012432342 originalPartnerRe that use characte 2. PEG34820938 for originalPartnerRe that don't use ch
createdDate	String (25)	Fixed	Y	Date	Format(YYYY-MM DDTHH:MM:SS+(send response / create DB if succ
transDate	String (25)	Fixed	Y	Date	Format(YYYY-MM DDTHH:MM:SS+(from BCA's host transaction.
additionalInfo	Object				Additional info co by Card/QRIS ad info detail.
batchNumber	String (6)	Fixed	Y	Numeric	Batch transaction
traceNo	String 16)	Max	Y	Numeric	Number for track destination bank
referenceNo	String (64)	Max	Y	Numeric	Reference numb transaction.
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code is generated and p EDC when transa

					status is success transaction statu success, Approv empty or null res
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID.
cardType	String (255)	Max	Y	Alphanumeric	Type of Card.
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Name Number. Format based on amount name that will be
amount1	String (9.2)	Max	Y	Numeric	Value Amount Tr For reward, cash transactions, am netting value wit For void transact amount will start mark. For DCC transac amount1 must no replaced with the converted value. always contain th in the original rec currency, while th converted amou reflected in the dccAmount1 field
amount2	String (9.2)	Max	N	Numeric	Value Tips / Cash For Cash BCA, ar added with Cash For void transact amount will start mark. For DCC transac amount2 must nc replaced with the converted value. always contain th in the original rec currency, while th converted amou reflected in the dccAmount1 field
originalAmount	String (9.2)	Max	N	Numeric	Payment amount reward deductio credit card paym reward redempti

					The originalAmount present only for credit Purchase or Void transactions with redemption applied. For void transaction originalAmount value with minus mark.
redeemAmount	String (9.2)	Max	N	Numeric	Reward amount of credit card payment reward redemption. The redeemAmount will be returned of reward redemption credit card transaction with a Purchase credit transaction type.
fxRate	String (12.7)	Max	N	Numeric	Represents the credit conversion ratio to convert the transaction amount from the merchant's local to the cardholder's currency. This field is applicable for DCC transaction. Notes: DCC Transaction strictly available merchants that have feature in EDC BCA.
currency	String (3)	Fixed	N	Alphanumeric	Represent the currency chosen by the cardholder during a DCC transaction. This field is applicable for DCC transaction. Notes: DCC Transaction strictly available merchants that have feature in EDC BCA.
dccAmount1	String (9.2)	Max	N	Numeric	Represents the final payable amount after currency conversion has been applied, based on DCC exchange rate (FXRate). This field is applicable for DCC transaction. Notes: DCC Transaction strictly available merchants that have

feature in EDC BC

Inquiry Status Purchase (Success) for Flazz Transaction

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Transaction
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction Type Transac request - 42 = In Purchas Settlem Tap / Flaz QRIS Re Cash To / Get Cæ Top Up (C Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a uniq generat when Re Format: “-“. Example 1. EA-01 originalf that use 2. PEG3. for originalf that dor charact
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Since create EDC
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get from

additionalInfo	Object				Addition by Card addition
batchNumber	String (6)	Fixed	Y	Numeric	Batch tr
traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Numeric	Approva generat EDC wh status is transact success empty c
amount1	String (9.2)	Max	Y	Numeric	Value ar

Inquiry Status Settlement (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
merchantId	String (9)	Max	Y	Numeric	MID Mer
terminalId	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fla Refund / Cash To Card Inf Up Card Cardver Token.

originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a unique identifier generated when Request is created. Format: “_“. Example: 1. EA-01 for originalPartnerReferenceNo that use 2. PEG3 for originalPartnerReferenceNo that do not use
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Server create Request
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get from transaction
additionalInfo	Array of Object				
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
midTrans	String (15)	Max	Y	Alphanumeric	MID Trans ID
settleTrans	String (10)	Max	Y	Alphanumeric	DEBIT, CREDIT
batchNumber	String (6)	Fixed	Y	Numeric	Transaction record number
totalCount	String (3)	Max	Y	Numeric	Value count
totalAmount	String (10.2)	Max	Y	Numeric	Value amount

Inquiry QRIS / QRIS Tap (Success)

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message

midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fl Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalf is a uniq generat when Re Format: “-“. Example 1. EA-01 for originalf that use 2. PEG3. for originalf that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Object				Additior by Card info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr
referenceNo	String (64)	Max	Y	Numeric	Referen transact
rrn	String (12)	Max	Y	Alphanumeric	QRIS RR the issu

traceNo	String (16)	Max	Y	Numeric	Number destinat
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approva generat EDC wh status is transact success empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
issuerName	String (12)	Max	Y	Alphanumeric	Issuer N
customerPan	String (19)	Fixed	Y	Numeric	Buyer c (custom used to transact Mandate requires paymen
merchantPan	String (19)	Fixed	Y	Numeric	Merchar example 936000
personalNumber	String (16)	Max	Y	Numeric	Will be f receive number. Format: last 2 di else ma
cardholderName	String (150)	Max	Y	Alphanumeric	Cardhol Number Format i amount will be n
amount1	String (9.2)	Max	Y	Numeric	Value ar
amount2	String (9.2)	Max	N	Numeric	Value ar Note: Fc transact filled

Inquiry QRIS Refund (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Trans
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction Type - 42 = In Purchas Settlement Tap / Fl Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a unique identifier generated when Request is created. Format: “_”. Example 1. EA-01 originalPartnerReferenceNo that use 2. PEG3- for originalPartnerReferenceNo that don't use
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Server create Date
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get from transaction Date
additionalInfo	Object				Additional information by Card info detail

batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr
referenceNo	String (64)	Max	Y	Numeric	Referen transact
rrn	String (12)	Max	Y	Alphanumeric	QRIS Re generat from the RRN.
traceNo	String (16)	Max	Y	Numeric	Number destinat
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approva generat EDC wh status is transact success empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
issuerName	String (12)	Max	Y	Alphanumeric	Issuer N
customerPan	String (19)	Fixed	Y	Numeric	Buyer ca (custom used to transact Mandate requires paymen
merchantPan	String (19)	Fixed	Y	Numeric	Merchar example 936000
personalNumber	String (16)	Max	Y	Numeric	Will be f receive number. Format: last 2 dig else ma
cardholderName	String (150)	Max	Y	Alphanumeric	Cardhol Number Format i amount will be n
amount1	String (9.2)	Max	Y	Numeric	Value ar For QRIS transact

					start wit
originalDate	String (8)	Fixed	Y	Numeric	Only for transact Original Format:
originalRrn	String (12)	Max	Y	Alphanumeric	Only for transact Original
remainingRefundAmount	String (9.2)	Max	N	Numeric	Only for transact Remaini amount.

Inquiry Status Flazz Top Up (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fl Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalF is a uniq generat when Re Format: “- “. Example 1. EA-01 originalF

					that use 2. PEG3. for original that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fron
additionalInfo	Object				Additior by Card info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr
traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approva generat EDC wh status is transact success empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of
amount1	String (9.2)	Max	Y	Numeric	Value Ar
flazzBalance	String (9.2)	Max	Y	Numeric	Flazz Ba
pan	String (20)	Max	Y	Numeric	Flazz ca

Inquiry Status Cash Top Up Flazz (Success)

Field	DataType	Length	Mandatory	Format
-------	----------	--------	-----------	--------

Type					
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Trans
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction Type request - 42 = In Purchas Settlem Tap / Fle Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a uniq generat when Re Format: “-“. Example 1. EA-01 originalf that use 2. PEG3. for originalf that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fron
additionalInfo	Object				Additior by Card info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch Tr

traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approva generat EDC wh status is transact success empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of
amount1	String (9.2)	Max	Y	Numeric	Value Ar
flazzBalance	String (9.2)	Max	Y	Numeric	Flazz Ba
pan	String (20)	Max	Y	Numeric	Flazz ca
panCashierCard	String (20)	Max	Y	Numeric	Access

Inquiry Status Get Card Info (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
merchantId	String (9)	Max	Y	Numeric	MID Mer
terminalId	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fla

					Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalf is a uniq generat when Re Format: “-“. Example 1. EA-01 originalf that use 2. PEG3, for originalf that dor
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Se create C
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fron transact
additionalInfo	Object				Additior by Card info det
pan	String (20)	Max	Y	Numeric	Card nu
flazzBalance	String (9.2)	Max	Y	Numeric	Flazz Ba card).
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of

Inquiry Status Card Verification (Cardver) / Pre-Auth (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String(7)	Fixed	Y	Alphanumeric	Respor

responseMessage	String(150)	Max	Y	Alphanumeric	Response message
midTrans	String(15)	Max	Y	Numeric	MID Trans
tidTrans	String(8)	Max	Y	Alphanumeric	Termin
transType	String(2)	Fixed	Y	Numeric	Transa reques - 42 = I Purcha Settler Tap / F Refunc Cash T Card Ir Up Car Cardve Token.
originalPartnerReferenceNo	String(64)	Max	Y	Alphanumeric	origina is a uni genera when F Format “-“. Examp 1. EA-0 origina that us 2. PEG: for origina that dc
createdDate	String(25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time se create
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fro transac
additionalInfo	Object				Additic by Car info de
batchNumber	String (6)	Fixed	Y	Numeric	Batch t
traceNo	String (16)	Max	Y	Numeric	Numbe destina
referenceNo	String (64)	Max	Y	Numeric	Refere transac

approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code generated by EDC when transaction is successful. If transaction is not successful, the value will be empty.
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of card
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Name. Format: Full Name. Amount will be in Indonesian Rupiah (IDR).
amount1	String (9.2)	Max	Y	Numeric	Cardholder's temporary verification amount and authorization capability.
fxRate	String (12.7)	Max	N	Numeric	Represents the conversion rate of the merchant's currency to the current currency. This field is for DCC. Notes: strictly merchant feature.
currency	String (3)	Fixed	N	Alphanumeric	Represents the chosen currency during the transaction. This field is for DCC. Notes: strictly merchant feature.
dccAmount1	String (9.2)	Max	N	Numeric	Represents the payable amount in the current currency.

						been a DCC e. (FXRat This fie for DC Notes: strictly merch feature
cardToken	String (32)	Max	C	Alphanumeric		Repres card nu based submit reques This fie merch API Tok Notes: strictly merch API Tok BCA.

Inquiry Status Top Up Cardver (Success)

Field	Data Type	Length Type	Mandatory	Format	Descript
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code
responseMessage	String (150)	Max	Y	Alphanumeric	Response descri
midTrans	String (15)	Max	Y	Numeric	MID Transactor
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal Id Tran
transType	String (2)	Fixed	Y	Numeric	Transaction Typ requested: - 42 = Inquiry St Purchase / Void / QRIS / QRIS Ta Payment / QRIS Up Flazz / Cash / Get Card Info Top Up Cardver Cardver / Offlin Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerF is a unique trans generated by th

					when Request F Format: Include “- “. Example: 1. EA-01243234 originalPartnerF that use charac 2. PEG3482093 for originalPartnerF that don't use c
createdDate	String (25)	Fixed	Y	Date	Format(YYYY-MM-DDTHH:MM:SS+ send response / DB if successful
transDate	String (25)	Fixed	Y	Date	Format(YYYY-MM-DDTHH:MM:SS+ from BCA's hos transaction.
additionalInfo	Object				Additional info c by Card/QRIS a detail.
batchNumber	String (6)	Fixed	Y	Numeric	Batch transacti
traceNo	String (16)	Max	Y	Numeric	Number for trac destination ban
referenceNo	String (64)	Max	Y	Numeric	Reference numl transaction.
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approval Code and printed on E transaction stat success. If trans status is not suc Approval Code null response.
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID.
cardType	String (255)	Max	Y	Alphanumeric	Type of Card.
cardholderName	String (150)	Max	Y	Alphanumeric	Cardholder Nan Number. Format based on amou name that will b

previousCardverAmount	String (9.2)	Max	Y	Numeric	Previous cardver Represents the was already blo previous Card V transactions.
amount1	String (9.2)	Max	Y	Numeric	Top up cardver top up amount t to the block limi previous cardve does not the tot accumulated lin
totalCardverAmount	String (9.2)	Max	Y	Numeric	Total cardver ar (previousCardv totalCardverAn Represents the total block limit Top-Up Card Ve transaction.
fxRate	String (12.7)	Max	N	Numeric	Represents the conversion ratio convert the trar amount from th local currency t cardholder's bil currency. This field is appl for DCC transac Notes: DCC Tra strictly available merchants that feature in EDC E
currency	String (3)	Fixed	N	Alphanumeric	Represent the c chosen by the c during a DCC tr This field is appl for DCC transac Notes: DCC Tra strictly available merchants that feature in EDC E
previousCardverDccAmount	String (9.2)	Max	N	Numeric	Represent the p cardver amount currency conve been applied, b DCC exchange (FXRate).

dccAmount1	String (9.2)	Max	N	Numeric	Represents the amount after currency conversion has been applied, based on the current exchange rate (USD to IDR). This field is applicable for DCC transactions. Notes: DCC Transactions are strictly available for merchants that feature in EDC E
totalCardverDccAmount	String (9.2)	Max	N	Numeric	Represent the final amount. This value is calculated as the sum of the previousCardver and dccAmount1 (current cardver amount).
cardToken	String (32)	Max	C	Alphanumeric	Represent the tokenized card number generated based on the PAN during the request. This field is mandatory for merchants that support API Token feature. Notes: The ECR is strictly available for merchants that support API Token feature BCA.

Inquiry Status Release Cardver (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Transaction ID
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction request type - 42 = Immediate Purchase Settlement

					Tap / Fl Refund Cash To Card Int Up Carc Cardve Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	original is a unic generat when R Format: “-“. Exempl 1. EA-01 original that use 2. PEG3 for original that doi
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time se create I
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get fro transac
additionalInfo	Object				Additio by Carc info det
batchNumber	String (6)	Fixed	Y	Numeric	Batch tr
traceNo	String (16)	Max	Y	Numeric	Number destina
referenceNo	String (64)	Max	Y	Numeric	Referer transac
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approv generat EDC wh status is transac success empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID

cardType	String (255)	Max	Y	Alphanumeric	Type of
cardholderName	String (150)	Max	Y	Alphanumeric	Cardho Number Format amount will be r
amount1	String (9.2)	Max	Y	Numeric	Release Represent being re block lin previou Card Ve transac Release will star
currency	String (3)	Fixed	N	Alphanumeric	Represent chosen during a This fiel for DCC Notes: I strictly mercha feature
dccAmount1	String (9.2)	Max	N	Numeric	Represent payable currenc been ap DCC ex (FXRate
cardToken	String (32)	Max	C	Alphanumeric	Represent card nu based c submitt request This fiel mercha API Tok Notes: I strictly mercha API Tok BCA.

Inquiry Status Offline (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Response Code
responseMessage	String (150)	Max	Y	Alphanumeric	Response Message
midTrans	String (15)	Max	Y	Numeric	MID Trans
tidTrans	String (8)	Max	Y	Alphanumeric	Terminal ID
transType	String (2)	Fixed	Y	Numeric	Transaction type - 42 = In Purchas Settlement Tap / Flash Refund , Cash To Card Inf Up Card Cardver Token.
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	originalPartnerReferenceNo is a unique identifier generated when Request Format: “_”. Example 1. EA-01 originalPartnerReferenceNo that use 2. PEG3- for originalPartnerReferenceNo that don't use
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time server create Date
transDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Get from transaction Date
additionalInfo	Object				Additional by Card info detail
batchNumber	String (6)	Fixed	Y	Numeric	Batch number

traceNo	String (16)	Max	Y	Numeric	Number destinat
referenceNo	String (64)	Max	Y	Numeric	Referen transact
approvalCode	String (6)	Fixed	Y	Alphanumeric	Approva generat EDC wh status is transact success empty c
issuerId	String (2)	Fixed	Y	Numeric	Issuer ID
cardType	String (255)	Max	Y	Alphanumeric	Type of
cardholderName	String (150)	Max	Y	Alphanumeric	Cardhol Number based o name th
amount1	String (9.2)	Max	Y	Numeric	Offline a the amo process limit tha held dur Verifica For DCC amount' replace convert always c in the or currenc convert reflecte dccAmc
fxRate	String (12.7)	Max	N	Numeric	Represe converts convert amount merchai to the c currenc
currency	String (3)	Fixed	N	Alphanumeric	Represe chosen I during a This fiel

					for DCC Notes: D strictly a merchal feature
dccAmount1	String (9.2)	Max	N	Numeric	Represe payable currenc been ap DCC ex (FXRate
cardToken	String (32)	Max	C	Alphanumeric	Represe card nur based o submitt request. This fiel merchal API Toke Notes: T strictly a merchal API Toke BCA.

Inquiry Status Register Token (Success)

Field	Data Type	Length Type	Mandatory	Format	
responseCode	String (7)	Fixed	Y	Alphanumeric	Respons
responseMessage	String (150)	Max	Y	Alphanumeric	Respons
midTrans	String (15)	Max	Y	Numeric	MID Tran
tidTrans	String (8)	Max	Y	Alphanumeric	Termina
transType	String (2)	Fixed	Y	Numeric	Transac request - 42 = In Purchas Settlem Tap / Fl Refund , Cash To Card Inf Up Card Cardver Token.

Here is the list of error codes that can be returned.

8/6/26, 22:35

400	400IS00	Bad request	General request failed error	Re-checking the JSON request sent by the partner.
400	400IS01	Invalid Field Format {field}	The data you entered does not match the format requirements	Re-checking the JSON request sent by the partner.
400	400IS02	Invalid Mandatory Field {field}	Mandatory field should be fulfilled	Re-checking the JSON request sent by the partner.
401	401IS00	Unauthorized. [Reason]	Invalid signature/Unknown client/Connection not allowed	Re-checking the request header sent by the partner.
401	401IS01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid	Re-checking the request header "Authorization" sent by the partner.
403	403IS01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.	Contact BCA to check your partnership data.
403	403IS05	Do Not Honor	Transaction Error From Host	Transaction failed.
403	403IS15	Transaction Not Permitted. [transType Not Found]	transType not available in the list	Re-checking the JSON request sent by the partner.
404	404IS01	Transaction Not Found	originalPartnerReferenceNo Not Found	Re-checking the JSON request sent by the partner.
404	404IS08	Invalid Merchant	Invalid Merchant	Re-checking the JSON request sent by the partner.
409	409IS00	Conflict	X-EXTERNAL-ID duplicate	Re-checking the request header "X-EXTERNAL-ID" sent by the partner.
429	429IS00	Too Many Requests	Maximum transaction limit exceeded	Please try again.
500	500IS00	General Error	Wrong request field input	Please try again.
500	500IS01	Internal Server Error	Unknown internal server failure, please retry the process again	Please try again.

504	504IS00	Timeout	Your transaction timeout	Please try again.
-----	---------	---------	--------------------------	-------------------

Appendix Issuer Id

The Issuer Id value is the type of card that used by Cardholder on payment. The list of values as below:

Code	Description
00	Debit BCA
01	Visa
02	Mastercard
03	AMEX
04	Diners Club
05	JCB
06	Union Pay
07	BCA Card
08	Other
09	AMEX BCA
10	BCA Syariah
11	Cash BCA
12	Smartcash
13	Debit MC BCA
14	Flazz BCA
15	JCB BCA
16	Maestro
17	Master BCA
18	Unionpay BCA
19	Visa BCA
20	Visa SQ
NA	Unknown

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/ecr/inquiry-status
```

Request



```
1  REQUEST CODE
2  -H 'Content-type: application/json'
3  -H 'Authorization: Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpvIJbU1mMU4a11MNDZ7Sg5u9a'
4  -H 'X-TIMESTAMP: 2024-03-25T15:50:04+07:00'
5  -H 'X-SIGNATURE:
6  85be817c55b2c135157c7e89f52499bf0c25ad6eebe04a986e8c862561b19a5'
7  -H 'ORIGIN: www.hostname.com'
8  -H 'CHANNEL-ID: 95251'
9  -H 'X-PARTNER-ID: 821508239'
10 -H 'X-EXTERNAL-ID: 418075539'
11 -d '
12 {
13   "merchantId": "000002872",
14   "terminalId": "C2AAC101",
15   ...
16 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/ecr/inquiry-status
```

Response



```
1  Response Inquiry Status Purchase / Void / Settlement / QRIS / QRIS Tap / Flazz Payment / QRIS
2  Refund / Flazz Top Up / Cash Top Up Flazz / Get Card Info (Pending)
3  -H 'Content-Type: application/json'
4  -H 'X-TIMESTAMP: 2024-03-25T15:50:04+07:00'
5  {
6    "merchantId": "123456789",
7    "terminalId": "C2AAC101",
8    "transType": "42",
9    "originalPartnerReferenceNo": "MIZ-26022025-1-001",
10   "createdDate": "2024-03-25T15:50:04+07:00",
11   "responseCode": "202IS00",
12   "responseMessage": "Request In Progress"
13 }
14
```

2. ECR EDC BCA Request Payment

With ECR EDC BCA Request Payment, users can request users' payment method through EDC BCA

ECR EDC BCA Request Payment can only request payment to EDC BCA for the transaction below:

- Purchase
- QRIS
- QRIS Tap
- Flazz Payment
- QRIS Refund
- Void
- Settlement

- Top Up Flazz
- Cash Top Up Flazz
- Get Card Info
- Cardver (Card Verification)/ Pre-auth
- Top Up Cardver
- Release Cardver
- Offline
- Register Token

To use ECR EDC BCA Request Payment, please generate new transaction id because transaction id cannot be duplicate.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier using EDC's WSID (95251)
X-PARTNER-ID	Header	String (36)	Max	Y	Unique ID for a partner. Merchant Direct: Group Code / MID Partnership: Partner Id Partner Id used for partner-type partnerships, where the integration or agreement is established at the partner level rather than individual merchants. Group Code used for regular merchant where a merchant operates multiple branches under one group. This code identifies the group as a whole. Merchant Id used for regular merchant partnerships where the merchant has only a single branch. This ID uniquely identifies that single merchant
X-EXTERNAL-ID	Header	String (36)	Max	Y	A unique identifier for each API request sent by merchant (per hit/request). Must be unique for every request (including retries).

Payload:**Request Payment Purchase (Debit/Credit/QRIS Tap/Flazz Payment)**

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	A unique transaction identifier in the partner/merchant system. Format: include character “-”. Example: 1. EA-012432342asea30 for partnerReferenceNo that use character “-” 2. PEG3482093840820091 for partnerReferenceNo that don't use character “_”
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Tok
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. will be used later
additionalInfo	Object		C		Mandatory for all transType except 16 (settlement).

amount1	String (9.2)	Max	Y	Numeric	Value amount transaction. (Amount Sale + amount2). Format: 9 digit of transaction nominal, 2 digit for (.00).
amount2	String (9.2)	Max	N	Numeric	Value Amount Transaction (amount2 only). Format: 9 digit of transaction nominal, 2 digit for (.00). Notes: - For QRIS Tap, Flazz Top Up, and Cash Top Up Transaction, amount2 should not be filled or filled by value "0". - For Debit transaction, amount 2 is only for cash. - For Credit transaction, amount 2 is only for tip.
rewardFlag	String (1)	Fixed	N	ENUM [Y, N, null]	For credit card's reward redeem. Format: Y/N
pan	String (32)	Max	C	Alphanumeric	Primary Account Number (PAN). Represents the card number used in Card Not Present transactions. For Card Not Present or Manual Key-In methods, this field may contain either a token or a plain PAN: • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be

					processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA
expiryDate	String (4)	Fixed	C	Numeric	Primary Account Number (PAN). Represents the card number used in Card Not Present transactions. For Card Not Present or Manual Key-In methods, this field may contain either a token or a plain PAN: • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA.

Request Payment QRIS

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character "-". Example: 1. EA-012432342asea30 for partnerReferenceNo that use character "-"

					2. PEG3482093840820091 for partnerReferenceNo that don't use character "_"
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Toke
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. will be used later
additionalInfo	Object		C		Mandatory for all transType except 16 (settlement).
amount1	String (9.2)	Max	Y	Numeric	Value Amount Transaction (Amount Sale + amount 2). Format: 9 digit of transaction nominal, 2 digit for (.00)
amount2	String (9.2)	Max	N	Numeric	Transaction Tips. Format: 9 digit of transaction nominal, 2 digit for (.00).

Request Payment QRIS Refund

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character “-”. Example: 1. EA-012432342asea30 for partnerReferenceNo that use character “-” 2. PEG3482093840820091 for partnerReferenceNo that don't use character “-”
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. will be used later
additionalInfo	Object		C		Mandatory for all transType except 16 (settlement).

amount1	String (9.2)	Max	Y	Numeric	Value Amount Transaction (Amount Sale + amount 2). Format: 9 digit of transaction nominal, 2 digit for (.00).
originalDate	String (8)	Fixed	Y	Numeric	Only for QRIS Refund transactions. Original payment date. Format: DDMMYYYY
originalRrn	String (12)	Max	Y	Alphanumeric	Only for QRIS Refund transactions. Original payment's RRN.

Request Payment Void

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier service consumer & Format: include character "-". Example: 1. EA-012432342as partnerReferenceNo use character "-" 2. PEG3482093840 for partnerReferenceNo that don't use character
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identifier
transType	String (2)	Fixed	Y	Numeric	Transaction Type that requested: - 01 = Purchase (Debit Credit/QRIS Tap/Flazz Payment) - 04 = Release Card - 05 = Cardver (Card Verification)/ Pre-authorized - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Card - 21 = Top Up Flazz

						- 22 = Cash Top Up - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Toki
partnerType	String (2)	Fixed	N		Alphanumeric	For general/special cooperation indicator to be used later
additionalInfo	Object		C			Mandatory for all transactions except 16 (settlement)
originalPartnerReferenceNo	String (64)	Max	Y		Alphanumeric	originalPartnerReferenceNo is a unique transaction generated by the merchant when Request Payment

Request Payment Settlement

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character "-". Example: 1. EA-012432342asea30 for partnerReferenceNo that use character "-" 2. PEG3482093840820091 for partnerReferenceNo that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth

					- 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
--	--	--	--	--	--

partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. will be used later
-------------	---------------	-------	---	--------------	--

Request Payment Top Up Flazz

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character "-". Example: 1. EA-012432342asea30 for partnerReferenceNo that use character "-" 2. PEG3482093840820091 for partnerReferenceNo that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void

					- 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. will be used later
additionalInfo	Object		C		Mandatory for all transType except 16 (settlement).
amount1	String (9.2)	Max	Y	Numeric	Top Up amount. Format: 9 digit of transaction nominal, 2 digit for (.00).

Request Payment Cash Top Up Flazz

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character "-". Example: 1. EA-012432342asea30 for partnerReferenceNo that use character "-" 2. PEG3482093840820091 for partnerReferenceNo that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz

					Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. will be used later
additionalInfo	Object		C		Mandatory for transType 01,08,21,22,31,35.
amount1	String (9.2)	Max	Y	Numeric	Top Up Amount. Format: 9 digit of transaction nominal, 2 digit for (.00).

Request Payment Get Card Info

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character “_”. Example: 1. EA-012432342asea30 for partnerReferenceNo that use character “-” 2. PEG3482093840820091 for partnerReferenceNo that don't use character “_”
merchantId	String (9)	Max	Y	Numeric	MID merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification

transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. will be used later

Request Payment Cardver (Card Verification)/ Pre-auth

Field	Params Type	Data Type	Length Type	Mandatory	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier service consumer system. Format: include character "-". Example: 1. EA-012432342asea for partnerReference that use character "-" 2. PEG3482093840820 for partnerReference that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID Merchant.
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment)

					- 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicator. Will be used later.
additionalInfo	Object	-	C	-	Mandatory for all transType except 16 (settlement).
amount1	String (9.2)	Max	Y	Numeric	Cardver Amount. This value represents the amount temporarily blocked to verify the card's validity and authorization capabilities.
pan	String (32)	Max	C	Alphanumeric	Primary Account Number (PAN). Represents the card number used in Card Present transactions. Card Not Present or Manual Key-In method, this field may contain either a token or a plain PAN: • If tokenization is applied: ◦ Send the PAN to be tokenized to the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In method is not supported for Card Present transactions.

					In is strictly available only for merchants that have manual key in feature in EDC BCA
Field	Data Type	LengthType	Mandatory	Format	Description
amount1	String (9.2)	Max	Y	Numeric	Cardver Amount. This value represents the amount temporarily blocked to verify the card's validity and authorization capabilities.
pan	String (32)	Max	C	Alphanumeric	Primary Account Number (PAN). Represents the card number used in Card Not Present transactions. Card Not Present or Manual Key-In method, this field may contain either a token or a plain PAN: - If tokenization is applied: - Send the PAN to be tokenized to the system, or - Send the token if it has been issued. - If tokenization is not applied, send the PAN and it will be processed as a plain card number (non tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA
expiryDate	String (4)	Fixed	C	Numeric	Represents card expiry date used in Card Not Present transactions. Card expiry date in MMY format. For Card Not Present Manual Key-In method, this field may contain either a plain card exp

date or left empty(space)

- If tokenization is applied:
 - Send the PAN be tokenized in the system, or
 - Send the token if it has been issued.
- If tokenization is not applied, send the PAN and it will be processed as a plain card number (non tokenized).

Notes: The Manual Key In is strictly available only for merchants that have manual key in feature in EDC BCA

Request Payment Top Up Cardver

Field	Params Type	Data Type	Length Type	Mandatory	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character "-". Example: 1. EA-012432342asea30 for partnerReferenceNo that use character "-" 2. PEG3482093840820091 for partnerReferenceNo that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID Merchant.
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification.
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline

					- 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. Will be used later.
additionalInfo	Object	-	C	-	Mandatory for all transType except 16 (settlement).
amount1	String (9.2)	Max	Y	Numeric	Top up cardver amount. The top up amount that adds to the block limit of a previous cardver. This value not the total accumulated limit.
pan	String (32)	Max	C	Alphanumeric	Primary Account Number (PAN). Represents the card number used in Card Not Present transactions. For Card Not Present or Manual Key-In methods, this field may contain either a token or a plain PAN: • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA
expiryDate	String (4)	Fixed	C	Numeric	Represents card expiry date used in Card Not Present transactions. Card expiry date in MMYYY format. For Card Not Present or Manual Key-In methods, this

					field may contain either a plain card expiry date or left empty(space) • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA
approvalCode	String (6)	Max	N	Alphanumeric	Approval Code is the authorization code from the original cardver transaction (first). This code can be found on the receipt of the original cardver transaction. If the approval code is not included in the request, the value may be entered manually on the EDC.
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character "-". Example: 1. EA-012432342asea30 for partnerReferenceNo that use character "-" 2. PEG3482093840820091 for partnerReferenceNo that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID Merchant.
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification.
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card

					Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. Will be used later.
additionalInfo	Object	-	C	-	Mandatory for all transType except 16 (settlement).
amount1	String (9.2)	Max	Y	Numeric	Release cardver amount. Represents the amount being released from the block limit that was previously held during a cardver transaction. The release amount must be equal to the full amount from the original cardver transaction.
pan	String (32)	Max	C	Alphanumeric	Primary Account Number (PAN). Represents the card number used in Card Not Present transactions. For Card Not Present or Manual Key-In methods, this field may contain either a token or a plain PAN: • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA

expiryDate	String (4)	Fixed	C	Numeric	Represents card expiry date used in Card Not Present transactions. Card expiry date in MMYT format. For Card Not Present or Manual Key-In methods, this field may contain either a plain card expiry date or left empty(space) - If tokenization is applied: - Send the PAN to be tokenized by the system, or - Send the token if it has been issued. - If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA
approvalCode	String (6)	Max	N	Alphanumeric	Approval Code is the authorization code from the original cardver transaction (first). This code can be found on the receipt of the original cardver transaction. If the approval code is not included in the request, the value may be entered manually on the EDC.
originalDate	String (4)	Max	N	Numeric	Cardver original transaction date. This field will be filled with cardver original transaction date (DD/MM).

Request Payment Offline

Field	Params Type	Data Type	Length Type	Mandatory	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character “-“. Example: 1. EA-012432342asea30 for partnerReferenceNo that use

					character "-" 2. PEG3482093840820091 for partnerReferenceNo that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID Merchant.
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification.
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. Will be used later.
additionalInfo	Object	-	C	-	Mandatory for all transType except 16 (settlement).
amount1	String (9.2)	Max	Y	Numeric	Offline amount. Represents the amount being processed from the block limit that was previously held during a Card Verification transaction.
pan	String (32)	Max	C	Alphanumeric	Primary Account Number (PAN). Represents the card number used in Card Not Present transactions. For Card Not Present or Manual Key-In methods, this field may contain either a token or a plain PAN: - If tokenization is applied: - Send the PAN to be tokenized by the

					system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA
expiryDate	String (4)	Fixed	C	Numeric	Represents card expiry date used in Card Not Present transactions. Card expiry date in MMY format. For Card Not Present or Manual Key-In methods, this field may contain either a plain card expiry date or left empty(space) • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA .
approvalCode	String (6)	Max	N	Alphanumeric	Approval Code is the authorization code from the original cardver transaction (first). This code can be found on the receipt of the original cardver transaction. If the approval code is not included in the request, the value may be entered manually on the EDC.

Request Registration Token

Field	Params Type	Data Type	Length Type	Mandatory	Description
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction identifier on service consumer system. Format: include character "-". Example: 1. EA-012432342asea30 for partnerReferenceNo that use character "-" 2. PEG3482093840820091 for partnerReferenceNo that don't use character "-"
merchantId	String (9)	Max	Y	Numeric	MID Merchant.
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification.
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/ Credit/QRIS Tap/Flazz Payment) - 04 = Release Cardver - 05 = Cardver (Card Verification)/ Pre-auth - 07 = Offline - 08 = Void - 10 = Settlement - 16 = Top Up Cardver - 21 = Top Up Flazz - 22 = Cash Top Up Flazz

					- 23 = Get Card - 31 = QRIS - 35 = QRIS Refund - 41 = Register Token
partnerType	String (2)	Fixed	N	Alphanumeric	For general/special cooperation indicators. Will be used later.
additionalInfo	Object	-	C	-	Mandatory for all transType except 16 (settlement).
pan	String (32)	Max	C	Alphanumeric	Primary Account Number (PAN). Represents the card number used in Card Not Present transactions. For Card Not Present or Manual Key-In methods, this field may contain either a token or a plain PAN: • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not applied, send the PAN and it will be processed as a plain card number (non-tokenized). Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA .
expiryDate	String (4)	Fixed	C	Numeric	Represents card expiry date used in Card Not Present transactions. Card expiry date in MMYYY format. For Card Not Present or Manual Key-In methods, this field may contain either a plain card expiry date or left empty(space) • If tokenization is applied: ◦ Send the PAN to be tokenized by the system, or ◦ Send the token if it has been issued. • If tokenization is not

applied, send the PAN and it will be processed as a plain card number (non-tokenized).

Notes: The Manual Key-In is strictly available only for merchants that have manual key in feature in EDC BCA.

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code
responseMessage	String (150)	Max	Y	Alphanumeric	Response description
merchantId	String (9)	Max	Y	Numeric	MID Merchant
terminalId	String (8)	Max	Y	Alphanumeric	Terminal Identification
transType	String (2)	Fixed	Y	Numeric	Transaction Type that are requested: - 01 = Purchase (Debit/Credit/Cash) - 02 = Tap/Flazz Paymen - 08 = Void - 10 = Settlement - 21 = Top Up Flazz - 22 = Cash Top Up - 23 = Get Card - 31 = QRIS - 35 = QRIS Refund
PartnerReferenceNo	String (64)	Max	Y	Alphanumeric	PartnerReferenceNo is a unique transaction ID generated by the merchant when Request Payment
createdDate	String (25)	Fixed	Y	Date Format(YYYY-MM-DDTHH:MM:SS+07:00)	Time Send Response/ Time create DB if successful

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition	Partner Action
400	400RP00	Bad request	General request failed error	Re-checking the JSON request sent by the partner.
400	400RP01	Invalid Field Format {field}	The data you entered does not match the format requirements	Re-checking the JSON request sent by the partner.
400	400RP02	Invalid Mandatory Field {field}	Mandatory field should be fulfilled	Re-checking the JSON request sent by the partner.
401	401RP00	Unauthorized. [Reason]	Invalid signature/Unknown client/Connection not allowed	Re-checking the request header sent by the partner.
401	401RP01	Invalid token (B2B)	Access Token Not Exist/ Access Token Expired/Token is Invalid	Re-checking the request header "Authorization" sent by the partner.
403	403RP01	Feature Not Allowed. [Reason]	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.	Contact BCA to check your partnership data.
403	403RP15	Transaction Not Permitted. transType Not Found	transType not available in the list	Re-checking the JSON request sent by the partner.
404	404RP01	Transaction Not Found	originalPartnerReferenceNo Not Found	Re-checking the JSON request sent by the partner.
404	404RP08	Invalid Merchant	Invalid Merchant	Re-checking the JSON request sent by the partner.
409	409RP00	Conflict	X-EXTERNAL-ID duplicate	Re-checking the request header "X-EXTERNAL-ID" sent by the partner.
409	409RP01	Duplicate partnerReferenceNo	Duplicate partnerReferenceNo	Re-checking the JSON request sent by the partner.


```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/ecr/payment
```

Response



```
1  Response General Request Sample
2  -H 'Content-Type: application/json'
3  -H 'X-TIMESTAMP: 2024-03-25T15:30:04+07:00'
4  {
5    "terminalId": "C2AAC101",
6    "merchantId": "123456789",
7    "transType": "0201",
8    "partnerReferenceNo": "MIZ-26022025-1-001",
9    "createdDate": "2024-03-25T13:50:04+07:00",
10   "responseCode": "200RP00",
11   "responseMessage": "Successful"
12 }
13
14 Response Payment Register Token
--
```

QRIS MPM

1. SNAP QR MPM Generate QR

This service is used to generate QRIS.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel identifier. Using EDC's WSID (95251)
X-PARTNER-ID	Header	String(36)	Max	Y	Unique ID for merchant - Merchant Reguler: MerchantID (9) - Merchant Partnership: Partner Name (36)
X-EXTERNAL-ID	Header	String(36)	Max	Y	ID that should be unique per partner per service in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String(64)	Max	Y	Alphanumeric	Transaction ID provided by the

					partner
amount	Object		Y		
value	String (13.2)	Max	Y	Numeric	Net amount of the transaction (exclude convenience fee) Example : IDR 10.000,- will be placed with 10000.00
currency	String (3)	Fixed	Y	Alphanumeric	Currency code (IDR)
merchantId	String (9)	Max	Y	Numeric	Merchant identifier that is unique per each merchant. For merchant aggregator, filled with aggregator's merchantID
subMerchantId	String (9)	Max	C	Alphanumeric	Mandatory applied to merchant aggregator, filled with submerchantID
terminalId	String (8)	Fixed	Y	Numeric	Terminal ID Can be : - TID provided by BCA (merchant reguler) - TID provided by partner (merchant partnership)
validityPeriod	String (25)	Max	N	YYYY-MM-DD Thh:mm:ssTZ D	The time when the QRIS valid Minimum : created time + 5 mins Maximum : created time + 120 mins Default value 60 minutes will be applied if validityPeriod not provided

additionalInfo	Object		N		Additional Information
convenienceFee	String (10.2)	Max	N	Numeric	Convenience fee or tips
partnerMerchantType	String (4)	Max	C	Alphanumeric	Mandatory applied to merchant partnership, filled with partner identifier
terminalLocationName	String (25)	Max	C	Alphanumeric	Mandatory applied to merchant aggregator, filled with submerchant name
qrOption	String (1)	Fixed	N	Alphabet	Choice of QR content or QR image format as response Value : (case non sensitive) C = QR Content I = QR Image A = QR Content & QR Image Default QR Image format will be applied if not stated in request / other than the above values

Result of the request will contains following information:

Response:

Field	DataType	Length Type	Mandatory	Format	Description
responseCode	String(7)	Fixed	Y	Numeric	Response code to identify generate QRIS request status, refer to the list of response code Format: AAABBCC AAA : HTTP Code BB : Service Code

					CC : Case Code Service Code Generate QRIS : 47 Example : 2004700
responseMessage	String (150)	Max	Y	Alphanumeric	Error message in English Example : successful
referenceNo	String (36)	Max	N	Alphanumeric	Transaction ID provided by BCA Mandatory applied only if the request from merchant is valid
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID provided by the partner
qrContent	String (512)	Max	N	Alphanumeric	QR String MPM
qrUrl	String (256)	Max	N	Alphanumeric	URL for download QR Image Not Used in BCA
qrImage	String	Max	N	Alphanumeric	Length = unlimited Encode string (Base64) from QR image QR String MPM Mandatory applied only if QR successfully generated
redirectUrl	String (512)	Max	N	Alphanumeric	Redirect URL to PJSP page to process the payment Not used in BCA
merchantName	String (25)	Max	N	Alphanumeric	Merchant name for print receipt For merchant aggregator, filled with the submerchant's outlet name Mandatory applied only if QR successfully generated

storeId	String (64)	Max	N	Alphanumeric	Unique shop id Not used in BCA
terminalId	String (8)	Max	N	Alphanumeric	Terminal ID Can be: - TID provided by BCA (merchant regular) - TID provided by partner (merchant partnership) Mandatory applied only if QR successfully generated
additionalInfo	Object		N		Additional Information

Error

HTTP Code	Error Code	Error Message	Condition
400	4004700	Bad request	Generate request failed error
400	4004701	Invalid Field Format {Field}	The data you entered does not match the format requirements
400	4004702	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled
401	4014700	Unauthorized. [Reason]	Invalid Signature/Unknown Client/ Connection Not Allowed/Invalid API/ Company is not authorized
401	4014701	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid
403	4034701	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data
403	4034706	Feature Not Allowed At This Time	The feature is not allowed at this time. Please try again
404	4044701	Transaction Not Found	Transaction not found.
404	4044708	Invalid Merchant	Invalid merchant
404	4044718	Inconsistent Request [X-PARTNER-ID & merchantID not match]	merchantID and X-PARTNER-ID value are not match. These fields should consist of same value

2. SNAP QR MPM Inquiry

This service is used to inquiry transaction status.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier using EDC's WSID (95251)
X-PARTNER-ID	Header	String (36)	Max	Y	Unique ID for a merchant - Merchant Regular : MerchantID (9) - Merchant Partnership: Partner Name (36)
X-EXTERNAL-ID	Header	String (36)	Max	Y	ID that should be unique per partner per service in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
originalReferenceNo	String (36)	Max	Y	Alphanumeric	Transaction ID provided by the partner Taken from response API Generate QR 'referenceNo' Field
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID provided by the partner
serviceCode	String (2)	Fixed	Y	Numeric	Transaction type indicator (service code of the original transaction request) Filled with serviceCode generate QR = 47

merchantId	String (9)	Max	Y	Numeric	Merchant identifier that is unique per each merchant For merchant aggregator, filled with aggregator's merchantID
subMerchantId	String (9)	Max	C	Alphanumeric	Mandatory applied to merchant aggregator, filled with submerchantID
additionalInfo	Object		N		Additional Information
partnerMerchantType	String (4)	Max	C	Alphanumeric	Mandatory applied to merchant aggregator, filled with partner identifier
terminalId	String (8)	Max	Y	Alphanumeric	Terminal ID Can be : - TID provided by BCA (merchant regular) - TID provided by partner (merchant partnership)

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Descripti
responseCode	String (7)	Fixed	Y	Numeric	Response code inquiry request to the list of res Response code from transactio (latestTransact

					field) format : AAABB AAA : HTTP Coc BB : Service Co CC : Case Code Service Code Ir Payment QRIS : Example: 2005'
responseMessage	String (150)	Max	Y	Alphanumeric	Response mess English, refer to response code Example: succe
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID p the partner
originalReferenceNo	String (36)	Max	Y	Alphanumeric	Transaction ID p BCA
originalExternalId	String (36)	Fixed	Y	Numeric	Original Externa header messag
serviceCode	String (2)	Fixed	Y	Numeric	Transaction typ (service code o transaction req Filled with servi generate QR = '
latestTransactionStatus	String (2)	Fixed	Y	Numeric	Transaction Sta 00 - Success : t paid 03 - Pending : ti recorded, but s 04 - Refunded : is successfully r 06 - Failed : tra failed, because
transactionStatusDesc	String (50)	Max	Y	Alphanumeric	Show descriptio transaction stat Example: - Success (trans Success) - Pending (Unpa Transaction) - Failed (QR Exp - Refunded (Par available amour - Refunded (Full - Refunded (Ma

paidTime	String (25)	Max	N	YYY-MM-DDThh:mm:ssTZD	Transaction date Example: 2020-12-21T10: Mandatory append the transaction
amount	Object		N		Mandatory append the transaction
value	String (13.2)	Max	Y	Numeric	Net amount of the transaction (excluding convenience fee) Example: IDR 100,000.00 be placed with
currency	String (3)	Fixed	Y	Alphanumeric	Currency code
feeAmount	Object		N		
value	String (16.2)	Max	Y	Numeric	Default in BCA : 0.00
currency	String (3)	Fixed	Y	Alphanumeric	Currency code
terminalId	String (8)	Max	N	Alphanumeric	Terminal ID. Card - TID provided by merchant (merchant registered) - TID provided by merchant (merchant partner) Mandatory append the transaction
additionalInfo	Object		N		Mandatory append the transaction
referenceNumber	String (12)	Fixed	Y	Alphanumeric	Unique ID for transaction
approvalCode	String (6)	Fixed	N	Alphanumeric	Approval code for successful transaction Mandatory append the transaction
payerPhoneNumber	String (13)	Max	N	Alphanumeric	Masked buyer phone number
batchNumber	String (6)	Fixed	N	Numeric	Transaction batch number Mandatory append the transaction

convenienceFee	String (10.2)	Max	N	Numeric	Convenience fee
customerPan	String (19)	Max	N	Numeric	Buyer card number (customer_pan)
issuerReferenceNumber	String (12)	Max	N	Numeric	RRN QRIS Mandatory append the transaction
payerName	String (30)	Max	N	Alphanumeric	Buyer name Mandatory append the transaction
issuerName	String (26)	Max	N	Alphanumeric	Issuer name Mandatory append the transaction
acquirerName	String (3)	Fixed	N	Alphanumeric	Filled with 'BCA' Mandatory append the transaction
merchantInfo	Object		N		
merchantId	String (15)	Max	N	Numeric	Merchant identifier unique per each Format: 000 88 digit) For merchant acquired filled with subMerchant Mandatory append the transaction
merchantPan	String (19)	Max	N	Numeric	Merchant PAN Mandatory append the transaction
name	String (25)	Max	N	Alphanumeric	Merchant name
city	String (13)	Max	N	Alphanumeric	Merchant city Mandatory append the transaction
postalCode	String (10)	Max	N	Numeric	Merchant postal code Mandatory append the transaction
country	String (2)	Fixed	N	Alphanumeric	Merchant location Mandatory append the transaction

email	String (30)	Max	N	Alphanumeric	Merchant e-ma
paymentChannelName	String (10)	Max	N	Alphanumeric	- Sakuku - Debit - Switching - Paylater - Credit Mandatory app the transaction

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	4005100	Bad request	General request failed error
400	4005101	Invalid Field Format {Field}	The data you entered does not match the format requirements
400	4005102	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled
401	4015100	Unauthorized. [Reason]	Invalid Signature/Unknown Client/ Connection Not Allowed/Invalid API/ Company is not authorized
401	4015101	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid
403	4035100	Transaction Expired	QR has expired
403	4035101	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data
403	4035106	Feature Not Allowed At This Time	The feature is not allowed at this time. Please try again
404	4045101	Transaction Not Found	Transaction not found
404	4045108	Invalid Merchant	Invalid merchant
404	4045118	Inconsistent Request [X-PARTNER-ID & merchantID not match]	merchantID and X-PARTNER-ID value are not match. These fields should consist of same value
409	4095100	Conflict	X-EXTERNAL-ID duplicate
429	4295100	Too Many Requests	Maximum request limit exceeded
500	5005100	General Error	General Error

500	5005101	Internal Server Error	Unknown internal server failure, please retry the process again
504	5045100	Timeout	Your request timeout

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qr/qr-mpm-query
```

```
1 Merchant Reguler
2
3 curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qr/qr-mpm-query
4 -H 'Authorization:Bearer iNrWtmeHe7t3h16x4i6o1kV9yj575H77iB9daG3kKXcE7MOHU2ubaS'
5 -H 'X-TIMESTAMP:2024-09-01T08:45:00+07:00'
6 -H 'X-
7 SIGNATURE:HTcmQDWBXwBvzkiPCYYxOvV+rzFjEEgpnMBP28Jydfi+HMJZsmek70Ix7VDibQbAves
8 -H 'Content-type:application/json'
9 -H 'CHANNEL-ID:95251'
10 -H 'X-PARTNER-ID:123456789'
11 -H 'X-EXTERNAL-ID: 41807553358950093184162180797839
12 -d '
13 {
14   "originalPartnerReferenceNo": "202409010000000000000001",
15   "channelId": "95251",
16   "partnerId": "123456789",
17   "externalId": "41807553358950093184162180797839",
18   "timestamp": "2024-09-01T08:45:00+07:00",
19   "signature": "HTcmQDWBXwBvzkiPCYYxOvV+rzFjEEgpnMBP28Jydfi+HMJZsmek70Ix7VDibQbAves"
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/gr/gr-mpm-query
```

```
1 Merchant Reguler - Transaction status success
2
3 -H 'Content-type:application/json'
4 -H 'X-TIMESTAMP:2024-09-01T08:45:05+07:00'
5 {
6   "responseCode": "2005100",
7   "responseMessage": "Success",
8   "originalPartnerReferenceNo": "202409010000000000000001",
9   "originalReferenceNo": "43057a74-e179-49ed-b119-b004a3d522ec",
10  "originalExternalId": "41807553358950093184162180797839",
11  "serviceCode": "47",
12  "latestTransactionStatus": "00",
13  "transactionStatusDesc": "Success (transaction Success)",
14  "paidTime": "2024-09-01T08:43:11+07:00",
15  "..."
16 }
```

3. SNAP QR MPM Refund

This service is used to request refund.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier. Using EDC's WSID (95251)
X-PARTNER-ID	Header	String (36)	Max	Y	Unique ID for a merchant - Merchant Regular : MerchantID (9) - Merchant Partnership: Partner Name (36)
X-EXTERNAL-ID	Header	String (36)	Max	Y	ID that should be unique per partner per service in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
merchantId	String (9)	Max	Y	Numeric	Merchant identifier unique per each merchant For merchant aggregation, filled with aggregated merchantID
subMerchantId	String (9)	Max	C	Alphanumeric	Mandatory applied merchant aggregation with submerchantID
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID provided by the partner
originalReferenceNo	String (36)	Max	Y	Alphanumeric	Transaction ID provided by BCA Taken from response Generate QR 'reference' field
partnerRefundNo	String (12)	Max	Y	Alphanumeric	Reference Number Taken from Service Inquiry / Payment Notification 'issuerReferenceNo'

					field
refundAmount	Object		N		
value	String (13.2)	Max	Y	Numeric	Refund amount Example: IDR 10.00 be placed with 100
currency	String (3)	Fixed	Y	Alphanumeric	Currency code (IDR
additionalInfo	Object		N		Additional Informat
terminalId	String (8)	Max	Y	Alphanumeric	Terminal ID
transactionDate	String (25)	Fixed	Y	YYYY-MM-DD Thh:mm:ssTZ D	Transaction date Example: 2020-12-21T10:30: Taken from Service Inquiry 'paidTime' fi Payment Notificatio 'transactionDate' fi
partnerMerchantType	String (4)	Max	C	Alphanumeric	Mandatory applied merchant partnersh with partner identif
issuerName	String (26)	Max	N	Alphanumeric	Issues name Taken from Service Inquiry / Payment Notification 'issuerI field

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Descriptio
responseCode	String (7)	Fixed	Y	Numeric	Response code to i refund request stat to the list of respor format : AAABBCC AAA : HTTP Code BB : Service Code CC : Case Code Service Code Inqui Payment QRIS : 78 Example: 2007800

responseMessage	String (150)	Max	Y	Alphanumeric	Response message Example: successful
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID provided by the partner
originalReferenceNo	String (36)	Max	Y	Alphanumeric	Transaction ID provided by BCA
originalExternalId	String (36)	Fixed	Y	Numeric	Original External-ID header message received
refundNo	String (12)	Max	N	Alphanumeric	Refund ID provided by the bank Mandatory applied the refund transaction successful
partnerRefundNo	String (12)	Max	Y	Alphanumeric	Reference Number taken from Service Inquiry / Payment Notification 'issuerReferenceNumber' field
refundAmount	Object		N		Mandatory applied the refund transaction successful
value	String (13.2)	Max	Y	Numeric	Refund amount Example: IDR 10.000 be placed with 1000
currency	String (3)	Fixed	Y	Alphanumeric	Currency code (IDR)
refundTime	String (25)	Fixed	N	YYYY-MM-DD Thh:mm:ssTZD	Refund Time Example: 2020-10-20T17:56:00 Mandatory applied the refund transaction successful
additionalInfo	Object		N		Additional Information
merchantId	String (15)	Max	N	Numeric	Merchant identifier unique per each merchant Format: 000 885 + 12 digit) For merchant aggregation, the merchant ID must be filled with submerchant ID Mandatory applied the transaction is successful

terminalId	String (8)	Max	N	Alphanumeric	Terminal ID Mandatory applied the refund transaction successful
referenceNumber	String (12)	Fixed	Y	Alphanumeric	Unique ID for tracing
availableAmount	Object		N		Mandatory applied the refund transaction successful
value	String (13.2)	Max	Y	Numeric	Available amount for
currency	String (3)	Fixed	Y	Alphanumeric	Currency code (IDF)
refundCounter	String (1)	Fixed	N	Numeric	Mandatory applied the transaction is successful counter refund received this transaction

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	4007800	Bad request	General request failed error
400	4007801	Invalid Field Format {Field}	The data you entered does not match the format requirements
400	4007802	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled
401	4017800	Unauthorized. [Reason]	Invalid Signature/Unknown Client/ Connection Not Allowed/Invalid API/ Company is not authorized
401	4017801	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid
403	4037801	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data
403	4037805	Do not honor	Do not honor
403	4037806	Feature Not Allowed At This Time	The feature is not allowed at this time. Please try again

403	4037815	Transaction Not Permitted [Reason]	Transaction data does not meet the refund's criteria/Refund payment is failed because Payment transaction status has been settled
404	4047801	Transaction Not Found	Transaction not found
404	4047808	Invalid Merchant	Invalid merchant
404	4047813	Invalid Amount	Refund nominal is greater than the remaining transaction nominal
404	4047818	Inconsistent Request [X- PARTNER-ID & merchantID not match]	merchantID and X-PARTNER-ID value are not match. These fields should consist of same value
405	4057801	Requested operation to refund transaction is not allowed at this time	The issuer used for refund does not support refund
409	4097800	Conflict	X-EXTERNAL-ID duplicate
429	4297800	Too Many Requests	Maximum request limit exceeded
500	5007800	General Error	General Error
500	5007801	Internal Server Error	Unknown internal server failure, please retry the process again
504	5047800	Timeout	Your request timeout

curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qr/qr-mpm-refund

Request



```
1 curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qr/qr-mpm-refund
2 -H 'Authorization:Bearer iNrWtmeHe7t3h16x4i6o1kV9yj575H77iB9daG3kKXcE7MOHU2ubaS'
3 -H 'X-TIMESTAMP:2024-09-03T14:48:25+07:00'
4 -H 'X-
5 SIGNATURE:HTcmQDWBXwBvzkIPCYyXOvV+rzFjEEgpnMBP28Jydfi+HMJZsmek70lx7VDibQbAves
6 -H 'Content-type:application/json'
7 -H 'CHANNEL-ID:95251'
8 -H 'X-PARTNER-ID:123456789'
9 -H 'X-EXTERNAL-ID: 41807553358950093184162180797840'
10 -d '
11 {
12   "merchantId": "123456789",
13   "originalPartnerReferenceNo": "202409010000000000000001",
14   "originalReferenceNo": "43057a74-e179-49ed-b119-b004a3d522ec",
15   "merchantReferenceNo": "00000000000000000000000000000000"
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qr/qr-mpm-refund
```

Response



```
1  Refund payment status success
2
3  -H 'Content-type:application/json'
4  -H 'X-TIMESTAMP:2024-09-03T14:48:30+07:00'
5  {
6    "responseCode": "2007800",
7    "responseMessage": "Successful",
8    "originalPartnerReferenceNo": "202409010000000000000001",
9    "originalReferenceNo": "43057a74-e179-49ed-b119-b004a3d522ec",
10   "originalExternalId": "41807553358950093184162180797840",
11   "refundNo": "21E4172823",
12   "partnerRefundNo": "000013101103",
13   "refundAmount": {
14     "value": "10000.00",
15   }
```

4. SNAP QRIS Notification

This service is used to Notification QRIS.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier using EDC's WSID (95251)
X-PARTNER-ID	Header	String (36)	Max	Y	Unique ID for a partner - Merchant Regular: MerchantID (15) - Merchant Partnership : Partner Name (36)
X-EXTERNAL-ID	Header	String (36)	Max	Y	ID that should be unique per co-partner per service in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format
-------	-----------	-------------	-----------	--------

originalReferenceNo	String (36)	Max	Y	Alphanumeric	Transaction Reference No BCA
originalPartnerReferenceNo	String (64)	Max	N	Alphanumeric	Transaction Reference No the partner
latestTransactionStatus	String (2)	Fixed	Y	Numeric	Transaction Status 00 - Successful 03 - Pending 06 - Failed, Invalid
transactionStatusDesc	String (50)	Max	Y	Alphanumeric	Transaction Status Description Example: - Successful - Pending - Failed, Invalid
customerNumber	String (19)	Max	N	Numeric	Customer Number (customer's Mandate the transaction)
accountType	String (25)	Max	N	Alphanumeric	Account Type Not used
destinationNumber	String (19)	Max	N	Numeric	Merchant Number Mandate the transaction
destinationAccountName	String(25)	Max	N	Alphanumeric	Merchant Name Mandate the transaction
amount	Object		N		Mandate Amount the transaction
value	String (13.2)	Max	Y	Numeric	Net Amount transaction conversion Example: be placed
currency	String (3)	Fixed	Y	Alphanumeric	Currency Code
bankCode	String (8)		N	Numeric	Bank Code Not used

additionalInfo	Object		N		Additic
referenceNumber	String (12)	Fixed	Y	Alphanumeric	Unique
transactionDate	String (25)	Fixed	N	YYYY-MM:DDThh:mm:ssTZD	Transac Examp 2020-1 Manda the tra
approvalCode	String (6)	Fixed	N	Alphanumeric	Approv succes Manda the tra
payerPhoneNumber	String (13)	Max	N	Alphanumeric	Maske
batchNumber	String(6)	Fixed	N	Numeric	Transac Manda the tra
convenienceFee	String(10.2)	Max	N	Numeric	Conver
issuerReferenceNumber	String(12)	Max	N	Numeric	RRN QF Manda the tra
payerName	String(30)	Max	N	Alphanumeric	Buyer r Manda the tra
issuerName	String(26)	Max	N	Alphanumeric	Issuer r Manda the tra
acquirerName	String(3)	Fixed	N	Alphanumeric	Filled w Manda the tra
merchantInfo	Array of Object		N		
terminalId	String(8)	Max	N	Alphanumeric	Termin Can be - TID pr (merch - TID pr (merch Manda the tra
merchantId	String(15)	Max	N	Numeric	Merche unique

						Format digit) For me filled w Manda the trai
city	String(13)	Max	N		Alphanumeric	Mercha Manda the trai
postalCode	String(10)	Max	N		Numeric	Mercha Manda the trai
country	String(2)	Fixed	N		Alphanumeric	Mercha Manda the trai
email	String (30)	Max	N		Alphanumeric	Mercha
paymentChannelName	String(10)	Max	N		Alphanumeric	- Sakuk - Debit - Switc - Payla - Credi Manda the trai

Result of the request will contains following information:

Response:

Field	DataType	Length Type	Mandatory	Format	Description
responseCode	String(7)	Fixed	Y	Alphanumeric	Response code to identify Notification request status Response code is different from transaction status ('latestTransactionStatus' field) Format: AAABBCC AAA : HTTP BB : Service Code CC : Case Code Service Code Notification Payment QRIS : 52 Example: 2005200

					Response from copartner
responseMessage	String (150)	Max	Y	Alphanumeric	Error message in English Example : successful

Error List

Here is the list of error codes that can be returned

HTTP Code	Error Code	Error Message	Condition
400	4005200	Bad request	Generate request failed error
400	4005201	Invalid Field Format {Field}	The data you entered does not match the format requirements
400	4005202	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled
401	4015200	Unauthorized. [Reason]	Invalid Signature/Unknown Client/ Connection Not Allowed/Invalid API/ Company is not authorized
401	4015201	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid
403	4035200	Transaction Expired	QR has expired
403	4035201	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data
403	4035206	Feature Not Allowed At This Time	The feature is not allowed at this time. Please try again
404	4045201	Transaction Not Found	Transaction not found.
404	4045208	Invalid Merchant	Invalid merchant
404	4045218	Inconsistent Request [X-PARTNER-ID & merchantID not match]	merchantID and X-PARTNER-ID value are not match. These fields should consist of same value
409	4095200	Conflict	X-EXTERNAL-ID duplicate
429	4295200	Too Many Requests	Maximum request limit exceeded
500	5005200	General Error	General Error
504	5045200	Timeout	Your request timeout

```
1 Merchant Reguler
2
3 curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qv-mpm-notify
4 -H 'Content-type: application/json'
5 -H 'Authorization: Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUplJbU1mMU4a1MNDZ7Sg5u9a'
6 -H 'X-TIMESTAMP: 2024-09-01T08:43:11+07:00'
7 -H 'X-SIGNATURE:
8 85be817c55b2c135157c7e89f52499bf0c25ad6eeeb04a986e8c862561b19a5'
9 -H 'CHANNEL-ID: 95251'
10 -H 'X-PARTNER-ID: 000885123456789'
11 -H 'X-EXTERNAL-ID: 41807553358950093184162180797837'
12 -d '{
13   "originalReferenceNo": "43057a74-e179-49ed-b119-b004a3d522ec",
14   "merchantId": "00000000000000000000000000000000"
```



```
1 -H 'Content-Type: application/json'
2 -H 'X-TIMESTAMP: 2024-09-01T08:43:11+07:00'
3 {
4   "responseCode": "2005200",
5   "responseMessage": "Successful"
6 }
```

1. SNAP QR CPM Cancel Payment

This feature is not yet available to be accessed via Sandbox

Field	Params Type	Data Type	Length Type	Mandatory	Description
-------	----------------	--------------	----------------	-----------	-------------

CHANNEL-ID	Header	String (5)	Fixed	Y	Channel's identifier using EDC's WSID (95251)
X-PARTNER-ID	Header	String (36)	Max	Y	Unique ID for merchant - Merchant Regular: MerchantID (9) - Merchant Partnership : Partner Name (36)
X-EXTERNAL-ID	Header	String (36)	Max	Y	ID that should be unique per co- partner per service in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID provided by the partner Format : include character '-'
merchantId	String (9)	Max	Y	Numeric	Merchant identifier that is unique per each merchant
SubMerchantId	String (9)	Max	C	Alphanumeric	Mandatory applied to merchant aggregator, filled with sub merchant ID
additionalInfo	Object		N		Additional Information
terminalId	String (8)	Max	Y	Alphanumeric	Terminal ID Can be : - TID generated by BCA (merchant reguler) - TID generated by partner (merchant

					partnership)
partnerMerchantType	String(4)	Max	C	Alphanumeric	Mandatory applied to merchant aggregator, filled with partner identifier

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Desc
responseCode	String (7)	Fixed	Y	Numeric	Response code cancel payment status, refer to response code. Response code from transaction ('latestTransactionId' field) Format: AAAB AAA : HTTP Code BB : Service Code CC : Case Code Service Code Payment QRIS Example : 200
responseMessage	String (150)	Max	Y	Alphanumeric	Response message Example : success
originalReferenceNo	String (36)	Max	Y	Alphanumeric	Transaction ID BCA Taken from request Payment QRIS 'referenceNo'
originalPartnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID the partner Format : include
originalExternalId	String (36)	Fixed	Y	Numeric	Original External header message
cancelTime	String (25)	Max	N	yyyy-MM-dd HH:mm:ssTZD	Cancel time Example: 2024-09-01T1

					Mandatory ap cancel transac successful
transactionDate	String (25)	Max	N	yyyy-MM- ddHH:mm:ssTZD	Transaction da Example: 2024-09-01T1 Mandatory ap request from r valid and the t successful
additionalInfo	Object		N		Additional Info
merchantId	String (15)	Max	N	Numeric	Merchant ider unique per eac For merchant : filled with sub Format : 000 & digit) Mandatory ap request from r valid
terminalId	String (8)	Max	N	Alphanumeric	Terminal ID Mandatory ap request from r valid
referenceNumber	String (12)	Fixed	N	Alphanumeric	Unique ID for t Mandatory ap request from r valid

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	4006200	Bad request	General request failed error
400	4006201	Invalid Field Format {field}	The data you entered does not match the format and length requirement
400	4006202	Invalid Mandatory Field {field}	Mandatory field should be fulfilled
401	4016200	Unauthorized. [Reason]	Invalid signature/Unknown client/Connection not allowed
401	4016201	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/ Token is Invalid

403	4036201	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
403	4036206	Feature Not Allowed At This Time	The feature is not allowed at this time. Please try again
403	4036215	Transaction Not Permitted. [Reason]	Payment transaction status has failed/Payment transaction status has been settled
404	4046201	Transaction Not Found	Transaction Not Found
404	4046208	Invalid Merchant	Invalid Merchant
404	4046218	Inconsistent Request [Reason]	merchantID and X-PARTNER-ID value are not match. These fields should consist of same value
409	4096200	Conflict	X-EXTERNAL-ID duplicate
429	4296200	Too Many Requests	Maximum transaction limit exceeded
500	5006200	General Error	Wrong request field input
500	5006201	Internal Server Error	Unknown internal server failure, please retry the process again
504	5046200	Timeout	Your transaction timeout

POST /openapi/v1.0/qr/qr-cpm-cancel

Request



```
1  curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qr/qr-cpm-cancel
2  -H 'Content-type: application/json'
3  -H 'X-TIMESTAMP: 2024-09-01T09:05:23+07:00'
4  -H 'Authorization: Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpviJbU1mMU4a11MNDZ7Sg5u9a'
5  -H 'X-SIGNATURE:
6  85be817c55b2c135157c7e89f52499bf0c25ad6eebe04a986e8c862561b19a5'
7  -H 'ORIGIN: www.hostname.com'
8  -H 'X-PARTNER-ID: 123456789'
9  -H 'X-EXTERNAL-ID: 41807553358950093184162180797837'
10 -H 'CHANNEL-ID: 95251'
11 -d '
12 {
13   "originalPartnerReferenceNo": "202409010000000000000001",
14   "merchantId": "123456789",
15   ...
16 }
```

```
1 Merchant Regular - Success
2
3 H'Content-type: application/json'
4 -H 'X-TIMESTAMP: 2024-09-01T09:05:26+07:00'
5 {
6   "responseCode": "2006200",
7   "responseMessage": "Success",
8   "originalReferenceNo": "43057a74-e179-49ed-b119-b004a3d522ec",
9   "originalPartnerReferenceNo": "2024090100000000000001",
10  "originalExternalId": "41807553358950093184162180797838",
11  "cancelTime": "2024-09-01T09:05:25+07:00",
12  "transactionDate": "2024-09-01T08:43:11+07:00",
13  "additionalInfo": {
14    "merchantId": "000885123456789",
```

This service is used to process payment for CPM QR Codes.

Additional Headers:

Payload:

Field	Data Type	Length	Mandatory	Format	Description
-------	-----------	--------	-----------	--------	-------------

partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID provided by the partner Format : include character '-'
qrContent	String (512)	Max	Y	Alphanumeric	QR String CPM Format : include character '+', '=', and '/'
amount	Object		Y		Mandatory applied only if the transaction is successful
value	String (13.2)	Max	Y	Numeric	Net amount of the transaction (exclude convenience fee) Example : IDR 10.000,- will be placed with 10000.00
currency	String (3)	Fixed	Y	Alphanumeric	Currency code (IDR)
merchantId	String (9)	Max	Y	Numeric	Merchant identifier that is unique per each merchant
subMerchantId	String (9)	Max	C	Alphanumeric	For merchant aggregator, filled with submerchantID
acquirerName	String (3)	Max	Y	Alphanumeric	Filled with BCA
terminalId	String (8)	Max	Y	Alphanumeric	Terminal ID Can be : - TID generated by BCA (merchant reguler) - TID generated by partner (merchant partnership)
additionalInfo	Object		N		Additional Information
convenienceFee	String (10.2)	Max	N	Numeric	Convenience fee or tips
partnerMerchantType	String(4)	Max	C	Alphanumeric	Mandatory applied to merchant

aggregator, filled
with partner
identifier

Result of the request will contains following information:

Response:

Field	DataType	Length Type	Mandatory	Format	Descript
responseCode	String (7)	Fixed	Y	Numeric	Response code to payment request to the list of respo Response code is from transaction (latestTransactio field) Format: AAABBC AAA : HTTP Code BB : Service Code CC : Case Code Service Code Not Payment QRIS CP Example: 200600
responseMessage	String (150)	Max	Y	Alphanumeric	Response messa Example : succes
referenceNo	String (36)	Max	N	Alphanumeric	Transaction ID pro BCA Mandatory applie request from mer valid
partnerReferenceNo	String (64)	Max	Y	Alphanumeric	Transaction ID pro the partner
transactionDate	String (25)	Max	N	yyyy-MM- ddHH:mm:ssTZD	Transaction date Example: 2024-09-01T10:3 Mandatory applie transaction is suc
additionalInfo	Object		N		Additional Inform
latestTransactionStatus	String (2)	Fixed	Y	Numeric	Transaction Statu 00 - Success : tra paid 06 -Failed : trans failed, because Q

transactionStatusDesc	String (50)	Max	Y	Alphanumeric	Show description transaction status Example: - Success (transa Success) - Failed (QR Expir
amount	Object		Y		
value	String (13.2)	Max	Y	Numeric	Net amount of the transaction (exclude conveni Example: IDR 10.0 be placed with 1C
currency	String (3)	Fixed	Y	Alphanumeric	Currency code (ID
convenienceFee	String (10.2)	Max	N	Numeric	Convenience fee
terminalId	String (8)	Max	N	Alphanumeric	Terminal ID Mandatory applie request from mer valid
referenceNumber	String (12)	Fixed	N	Alphanumeric	Unique ID for trac Mandatory applie request from mer valid
approvalCode	String (6)	Fixed	N	Alphanumeric	Approval code fro success transacti Mandatory applie transaction is suc
payerPhoneNumber	String (13)	Max	N	Alphanumeric	Masked buyer pho
batchNumber	String (6)	Fixed	N	Numeric	Transaction batch Mandatory applie transaction is suc
customerPan	String (19)	Max	N	Numeric	Buyer card numbe (customer_pan) Mandatory applie request from mer valid
issuerReferenceNumber	String (12)	Max	N	Alphanumeric	RRN QRIS Mandatory applie transaction is suc
payerName	String (30)	Max	N	Alphanumeric	Buyer name Mandatory applie

					request from merchant valid
issuerName	String (26)	Max	N	Alphanumeric	Issuer name Mandatory applied only if the transaction is successful
acquirerName	String (3)	Fixed	N	Alphanumeric	Filled with 'BCA' Mandatory applied only if the from merchant is successful
paymentChannelName	String (10)	Max	N	Alphanumeric	- Debit - Switching Mandatory applied transaction is successful
merchantInfo	Object		N		
merchantId	String (15)	Max	N	Numeric	Merchant identifier unique per each request Format : 000 885 digit) Mandatory applied request from merchant valid
merchantPan	String (19)	Max	N	Numeric	Merchant PAN Mandatory applied request from merchant valid
name	String (25)	Max	N	Alphanumeric	Merchant name
city	String (13)	Max	N	Alphanumeric	Merchant city Mandatory applied request from merchant valid
postalCode	String (10)	Max	N	Numeric	Merchant postal code Mandatory applied request from merchant valid
country	String (2)	Fixed	N	Alphanumeric	Merchant location Mandatory applied request from merchant valid
email	String (30)	Max	N	Alphanumeric	Merchant e-mail address

The following is the data that must be informed on the proof of the transaction to the customer:

- transactionDate
- latestTransactionStatus
- amount
- convenienceFee
- customerPan
- issuerReferenceNumber
- payerName
- issuerName
- acquirerName
- merchantPan

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	4006000	Bad request	General request failed error
400	4006001	Invalid Field Format {field}	The data you entered does not match the format and length requirement
400	4006002	Invalid Mandatory Field {field}	Mandatory field should be fulfilled
401	4016000	Unauthorized. [Reason]	Invalid signature/Unknown client/Connection not allowed
401	4016001	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid
403	4036000	Transaction Expired	QR has expired
403	4036001	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
403	4036002	Exceeds Transaction Amount Limit	Exceeds Transaction Amount Limit
403	4036006	Feature Not Allowed At This Time	The feature is not allowed at this time. Please try again
403	4036015	Transaction Not Permitted. [Reason]	Transaction Not Permitted. Please try again
404	4046001	Transaction Not Found	Transaction Not Found
404	4046008	Invalid Merchant	Invalid Merchant
404	4046014	Paid Bill	QR already used

404	4046018	Inconsistent Request [Reason]	merchantID and X-PARTNER-ID value are not match. These fields should consist of same value
409	4096000	Conflict	X-EXTERNAL-ID duplicate
409	4096001	Duplicate partnerReferenceNo	partnerReferenceNo duplicate
429	4296000	Too Many Requests	Maximum transaction limit exceeded
500	5006000	General Error	Wrong request field input
500	5006001	Internal Server Error	Unknown internal server failure, please retry the process again
504	5046000	Timeout	Your transaction timeout

POST /openapi/v1.0/qr/qr-cpm-payment

Request



```
1  curl -X POST https://sandbox.bca.co.id/openapi/v1.0/qr/qr-cpm-payment
2  -H 'Content-type: application/json'
3  -H 'Authorization: Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpvIJbU1mMU4a11MNDZ7Sg5u9a'
4  -H 'X-TIMESTAMP: 2024-09-01T08:43:10+07:00'
5  -H 'X-SIGNATURE:
6  85be817c55b2c135157c7e89f52499bf0c25ad6eebe04a986e8c862561b19a5'
7  -H 'ORIGIN: www.hostname.com'
8  -H 'X-PARTNER-ID: 123456789'
9  -H 'X-EXTERNAL-ID: 41807553358950093184162180797837'
10 -H 'CHANNEL-ID: 95251'
11 -d '
12 {
13   "partnerReferenceNo": "202409010000000000000001",
14   "qrContent": "hduvY...",
15   ...
16 }
```

```

1 Transaction Status Success
2
3 -H 'Content-Type: application/json'
4 -H 'X-TIMESTAMP: 2024-09-01T08:43:12+07:00'
5 {
6   "responseCode": "2006000",
7   "responseMessage": "Success",
8   "referenceNo": "43057a74-e179-49ed-b119-b004a3d522ec",
9   "partnerReferenceNo": "202409010000000000000001",
10  "transactionDate": "2024-09-01T08:43:11+07:00",
11  "additionalInfo": {
12    "latestTransactionStatus": "00",
13    "transactionStatusDesc": "Success (transaction Success)",
14    "amount": {

```

Additional Headers:

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit). In BCA, virtualAccountNo

					max length is 26 (partnerServiceId(8 digits) + customerNo(18 digits)).
inquiryRequestId	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Unique identifier for inquiry. Generated by BCA from inquiry response.

Note:

- Transaction can be queried between D-day (hari H) until D-1 day (H-1 / yesterday).
- paymentRequestID is the same value with inquiryRequestId from BCA for each transaction.
- For inquiry payment status, can use just one keyword (customerNo or inquiryRequestId/
paymentRequestID) as filter criteria.

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Numeric	Mandatory in BCA. Response code: HTTP Code + Service Code + Case Code
responseMessage	String (150)	Max	Y	Alphanumeric	Mandatory in BCA. Response description
paymentRequestId	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Unique identifier for payment. Generated by BCA and has the same value with inquiryRequestI d.
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit) In BCA, virtualAccountNo max length is 9 (partnerServiceId(8 digits)+customerNo(18 digits)).
paymentFlagReason	Object	-	N	-	Mandatory in BCA. Reason for Payment Status from Biller in

					multi language
english	String (64)	Max	N	Alphanumeric	Reason for inquiry status in English
indonesia	String (64)	Max	N	Alphanumeric	Reason for inquiry status in Bahasa
inquiryRequestId	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Inquiry identifier for inquiry. Generated by BCA from inquiry response.
paidAmount	Objects	-	N	-	Mandatory in BCA.
value	String (16,2)	Max	Y	Decimal	Paid amount with 2 decimal. In BCA, totalAmount max length is 13.2 digits
currency	String (3)	Fixed	Y	ISO-4217	Currency of amount based on ISO 4217
trxDateTime	Date(25)	Fixed	N	ISO-8601	Mandatory in BCA. BCA internal system datetime with timezone, which follows the ISO-8601 standard
transactionDate	Date(25)	Fixed	N	ISO-8601	Mandatory in BCA. Payment datetime when the payment happened
paymentFlagStatus	String (2)	Fixed	N	Numeric	Mandatory in BCA. Status for payment flag, This field may vary with these values: 00 : success transaction 01 : transaction in progress 99 : failed transaction
billDetails	Array of Objects	-	N	-	Array with maximum 24 Objects
billNo	String (18)	Max	N	Alphanumeric	Bill number that customer choose to pay. From Payment Request

billDescription	Object	-	N	-	Bill Description
english	String (18)	Max	N	Alphanumeric	Bill Description in English
indonesia	String (18)	Max	N	Alphanumeric	Bill Description in Bahasa
billSubCompany	String (5)	Max	N	Alphanumeric	Biller's product code
billAmount	Objects	-	N	-	
value	String (16,2)	Max	Y	Decimal	Transaction amount for specific bill. Nominal inputted by Customer with 2 decimal In BCA, billAmount max length is 13.2 digits.
currency	String (3)	Fixed	Y	ISO-4217	Currency
additionalInfo	Object	-	N	-	Additional Information for customer use for each bill
freeTexts	Array of Objects	-	N	-	Array with maximum 9 Objects send by BCA.
english	String (32)	Max	N	Alphanumeric	Will be shown in Channel
indonesia	String (32)	Max	N	Alphanumeric	Will be shown in Channel

Note:

- The final status of payment flag is not determined by responseCode and responseMessage.
- Status for payment flag will be defined in paymentFlagStatus and paymentFlagReason field. This field may vary with these values:
00 = success transaction
01 = transaction in progress
99 = failed transaction
- If the paymentFlagStatus is 01, the result will be defined after reconciliation process.
- If the reconciliation results show that the transaction was successfully settled, the paymentFlagStatus will contains 00.
- If the reconciliation results show a refund transaction, the paymentFlagStatus will contains 99.
- ResponseCode 4042601 shows request inquiry status is failed, because the transaction data is not available/not recorded at BCA, the paymentFlagStatus will be empty.

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2002600	Successful
400	4002601	Invalid Field Format {Field Name}
400	4002602	Invalid Mandatory Field {Field Name}
400	4002600	Bad request
401	4012600	Unauthorized. [Reason]
401	4012601	Invalid token (B2B)
403	4032601	Feature Not Allowed
404	4042601	Transaction Not Found
404	4042616	Partner Not Found
409	4092600	Conflict
500	5002600	General Error
500	5002601	Internal Server Error

/openapi/shared-biller/v1.0/transfer-va/status

Request



```
1 curl -X POST https://sandbox.bca.co.id/openapi/shared-biller/v1.0/transfer-va/status
2 -H 'CHANNEL-ID': '95391'
3 -H 'X-PARTNER-ID': '676767'
4 -H 'X-EXTERNAL-ID': '123456789'
5 -d '
6 {
7   "partnerServiceId": "03013",
8   "customerNo": "123456789012345678",
9   "virtualAccountNo": "00003013123456789012345678",
10  "inquiryRequestId": "202209161033070301300001197441"
11 }'
```

```

1 {
2   "responseCode": "2002600",
3   "responseMessage": "Successful",
4   "virtualAccountData": {
5     "paymentFlagReason": {
6       "english": "Transaction Success",
7       "indonesia": "Transaksi Berhasil"
8     },
9     "partnerServiceId": "21180",
10    "customerNo": "22203",
11    "virtualAccountNo": "2118022203",
12    "inquiryRequestId": "202307311953292118000043785288",
13    "paymentRequestId": "202307311953292118000043785288",
14    "paidAmount": {

```

This service is used for billing inquiry to biller.

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Mandatory in BCA. Channel' Identifier using WSID Shared Biller (95391)
X-PARTNER-ID	Header	String(32)	Max	Y	Mandatory in BCA. Partner ID (Mitra ID)
X-EXTERNAL-ID	Header	String(36)	Max	Y	Mandatory in BCA. Reference number that should be unique in the same day

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Unique identifier for this Payment. Generated by Mitra (channel-transactionID)

virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit). In BCA, virtualAccountNo max length is 26 (partnerServiceId(8 digits) + customerNo(18 digits)).
trxDateTime	Date(25)	Max	N	ISO-8601	Mandatory in BCA. Mitra internal system datetime with timezone, which follows the ISO-8601 standard
additionalInfo	Object	-	N	-	Optional in BCA. Additional Information for custom use

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Numeric	Mandatory in BCA. Response code: HTTP Code + Service Code + Case Code
responseMessage	String (150)	Max	Y	Alphanumeric	Mandatory in BCA. Response description
virtualAccountData	Object	-	Y	-	
partnerReferenceNo	String (128)	Max	N	Alphanumeric	Mandatory in BCA. From Inquiry Request (channeltransaction-ID)
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit) In BCA virtualAccountNo max length is 26. 9 (partnerServiceId(8

					digits)+customerNo(1 digits)).
virtualAccountName	String (255)	Max	Y	Alphanumeric	Mandatory in BCA. Customer name
inquiryRequestId	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Unique identifier for inquiry. Generated by BCA.
totalAmount	Objects	-	N	-	
value	String (16,2)	Max	Y	Decimal	Mandatory in BCA. Send by BCA. Total amount with 2 decimal In BCA, totalAmount max length is 13.2 digits.
currency	String(3)	Fixed	Y	ISO-4217	Mandatory in BCA. Currency of amount Send by BCA. Currency of amount based on ISO 4217. Currency only available for IDR
billDetails	Array of Objects	-	N	-	Optional in BCA. Array with maximum 24 Objects
billNo	String (18)	Max	N	Alphanumeric	Bill number from Biller
billDescription	Object	-	N	-	Send by BCA. Bill Description
english	String (18)	Max	N	Alphanumeric	Send by BCA. Bill Description in English
indonesia	String(18)	Max	N	Alphanumeric	Send by BCA. Bill Description in Bahasa
billSubCompany	String(5)	Max	N	Alphanumeric	Biller's product code
billAmount	Object	-	N	-	
value	String (16,2)	Max	Y	Decimal	Send by BCA. Transaction amount for specific bill. Nominal inputted by Customer with 2 decimal In BCA, billAmount max lengtl

					is 13.2 digits
currency	String (3)	Fixed	Y	ISO-4217	Currency
additionalInfo	Object	-	N	-	Additional Information for custom use for each bill
freeTexts	Array of Objects	-	N	-	Optional in BCA. Array with maximum 5 Objects send by BCA.
english	String (32)	Max	N	Alphanumeric	Will be shown in Channel
indonesia	String (32)	Max	N	Alphanumeric	Will be shown in Channel
virtualAccountTrxType	String(1)	Fixed	N	Alphanumeric	Mandatory in BCA. Type of Virtual Account. BCA will response virtualAccountTrxType value only for one of these value: - O - Open Payment - C - Closed Payment - V - Bill Variable - I - Partial - W - Multi Bill Variable
productName	String(30)	Max	N	Alphanumeric	Mandatory in BCA. Send by BCA. Product Category

Note:

1. BCA will response virtualAccountTrxType value only for one of these value:

- O (Open Payment) = (non Multi Bill - No Bill) Bill amount is not displayed, customer may enter paid amount freely

- C (Closed Payment) = (non Multi Bill - Fixed Bill)

 Bill amount is displayed, customer must pay according to the displayed amount

 If more than one bill is displayed, customer must pay all displayed bills & total amount for all bills

- V (Bill Variable) = (non Multi Bill - Variable Bill) Bill amount is displayed, customer may enter paid amount freely

- I (Partial) = (Flexible Multi Bill - Fixed Bill)

 More than one bill may be displayed, customer may choose more than one of the displayed bills to pay

 Bill amount is displayed, customer must pay according to the displayed amount in each bill

 Total of paid amount is equal to the sum of chosen bills

- W (Variable Multi Bill) = (Multi Bill - Fixed Bill)

 More than one bill may be displayed, customer may choose only one of the displayed bills to pay

 Bill amount is displayed, customer must pay according to the displayed amount of the chosen bill

2. Currency only available for IDR

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2003200	Successful
400	4003201	Invalid Field Format {Field Name}
400	4003202	Invalid Mandatory Field {Field Name}
400	4003200	Bad request
401	4013200	Unauthorized. [Reason]
401	4013201	Invalid token (B2B)
403	4033201	Feature Not Allowed
404	4043208	Invalid Merchant
404	4043212	Invalid Bill. [Reason] (Reason is defined by Biller)
404	4043214	Paid Bills
404	4043216	Partner Not Found
404	4043218	Inconsistent Request
409	4093200	Conflict
500	5003200	General Error
500	5003201	Internal Server Error

/openapi/shared-biller/v1.0/transfer-va/inquiry-intrabank

Request



```
1 curl -X POST https://sandbox.bca.co.id/openapi/shared-biller/v1.0/transfer-va/inquiry-
intrabank
2 -H 'CHANNEL-ID': '95391'
3 -H 'X-PARTNER-ID': '676767'
4 -H 'X-EXTERNAL-ID': '123456789'
5 -d '
6 {
7   "partnerServiceId": " 03013",
8   "customerNo": "123456789012345678",
9   "partnerReferenceNo": "1122334455",
10  "virtualAccountNo": " 00003013123456789012345678",
11  "trxDateTime": "2022-09-16T10:33:07+07:00"
12 }'
```

/openapi/shared-biller/v1.0/transfer-va/inquiry-intrabank

Response



```
1  {
2    "responseCode": "2003200",
3    "responseMessage": "Successful",
4    "virtualAccountData": {
5      "inquiryStatus": "",
6      "inquiryReason": {
7        "english": "",
8        "indonesia": ""
9      },
10     "partnerServiceId": " 21180",
11     "partnerReferenceNo": "90903200114",
12     "customerNo": "22203",
13     "virtualAccountNo": " 2118022203",
14     "virtualAccountName": "Customer Name",
15     "virtualAccountType": "VA"
```

3. SNAP Shared Biller Payment to VA from Intrabank

This service is to make payment to biller

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Mandatory in BCA. Channel' Identifier using WSID Shared Biller (95391)

X-PARTNER-ID	Header	String(32)	Max	Y	Mandatory in BCA. Partner ID (Mitra ID)
X-EXTERNAL-ID	Header	String(36)	Max	Y	Mandatory in BCA. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Unique identifier for this Payment. Generated by Mitra (channel-transactionID)
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit). In BCA, virtualAccountNo max length is 26 (partnerServiceId(8 digits) + customerNo(18 digits)).
inquiryRequestId	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Inquiry identifier for inquiry. Generated by BCA from inquiry response.
paidAmount	Objects	-	Y	-	
value	String (16,2)	Max	Y	Decimal	Mandatory in BCA. Paid amount with 2 decimal. In BCA, totalAmount max length is 13.2 digits.
currency	String (3)	Fixed	Y	ISO-4217	Mandatory in BCA. Currency of amount based on ISO 4217 Currency only available for IDR

trxDateTime	Date(25)	Max	N	ISO-8601	Mandatory in BCA. Mitra internal system datetime with timezone, which follows the ISO-8601 standard
billDetails	Array of Objects	-	N	-	Array with maximum 24 Objects
billNo	String (18)	Max	N	Alphanumeric	Bill number that customer choose to pay
billDescription	Object	-	N	-	From Inquiry Response
english	String (18)	Max	N	Alphanumeric	From Inquiry Response
indonesia	String (18)	Max	N	Alphanumeric	From Inquiry Response
billSubCompany	String (5)	Max	N	Alphanumeric	From Inquiry Response
billAmount	Objects	-	N	-	From Inquiry Response
value	String (16,2)	Max	Y	Decimal	From Inquiry Response
currency	String (3)	Fixed	Y	ISO-4217	From Inquiry Response
additionalInfo	Object	-	N	-	From Inquiry Response
freeText	Array of Objects	-	N	-	From Inquiry Response
english	String (32)	Max	N	Alphanumeric	From Inquiry Response
indonesia	String (32)	Max	N	Alphanumeric	From Inquiry Response

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
-------	-----------	-------------	-----------	--------	-------------

responseCode	String (7)	Fixed	Y	Numeric	Mandatory in BCA. Response code: HTTP Code + Service Code + Case Code
responseMessage	String (150)	Max	Y	Alphanumeric	Mandatory in BCA. Response description
paymentRequestId	String (128)	Max	N	Alphanumeric	Mandatory in BCA. Unique identifier for payment. Generated by BCA and has the same value with inquiryRequestId.
partnerReferenceNo	String (128)	Max	N	Alphanumeric	Mandatory in BCA. From Inquiry Request (channeltransaction-ID)
virtualAccountNo	String (28)	Max	Y	Alphanumeric	Mandatory in BCA. partnerServiceId (8 digit left padding space) + customerNo (up to 20 digit) In BCA, virtualAccountNo max length is 26 Tech. Doc. OpenAPI-Shared-Biller API v1.1 PT. Bank Central Asia, Tbk. 9 (partnerServiceId(8 digits)+customerNo(18 digits)).
billDetails	Array of Objects	-	N	-	Array with maximum 24 Objects
billNo	String (18)	Max	N	Alphanumeric	Bill number that customer choose to pay
billDescription	Object	-	N	-	From Inquiry Response
english	String (18)	Max	N	Alphanumeric	From Inquiry Response
indonesia	String (18)	Max	N	Alphanumeric	From Inquiry Response
billSubCompany	String (5)	Max	N	Alphanumeric	From Inquiry Response
billAmount	Objects	-	N	-	From Inquiry Response

value	String (16,2)	Max	Y	Decimal	From Inquiry Response
currency	String (3)	Fixed	Y	ISO-4217	From Inquiry Response
additionalInfo	Object	-	N	-	From Inquiry Response
freeTexts	Array of Objects	-	N	-	Optional in BCA. Array with maximum 9 Objects send by BCA.
english	String (32)	Max	N	Alphanumeric	Will be shown in Channel
indonesia	String (32)	Max	N	Alphanumeric	Will be shown in Channel

Note:

1. currency only available for IDR

2. paymentRequestID is the same value with inquiryRequestID from BCA for each transaction.

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2003300	Successful
202	2023300	Request In Progress
400	4003301	Invalid Field Format {Field Name}
400	4003302	Invalid Mandatory Field {Field Name}
400	4003300	Bad request
401	4013300	Unauthorized. [Reason]
401	4013301	Invalid token (B2B)
403	4033201	Feature Not Allowed
403	4033302	Exceeds Transaction Amount Limit
403	4033316	Suspend Transaction
404	4043208	Invalid Merchant
404	4043313	Invalid Amount
404	4043212	Invalid Bill. [Reason] (Reason is defined by Biller)
404	4043214	Paid Bills

/openapi/shared-biller/v1.0/transfer-va/payment-intrabank

Response



```
1  {
2    "responseCode": "2003300",
3    "responseMessage": "Successful",
4    "virtualAccountData": {
5      "paymentFlagReason": {
6        "english": "",
7        "indonesia": ""
8      },
9      "partnerServiceId": " 21180",
10     "customerNo": "22203",
11     "virtualAccountNo": " 2118022203",
12     "virtualAccountName": "",
13     "virtualAccountEmail": "",
14     "virtualAccountPhone": "",
15     "virtualAccountAddress": ""
16   }
```

Transfer Dana

1. SNAP Banking External Account Inquiry

This service is used to inquiry account external.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel ID using KlikBCA Bisnis's WSID (95051)
X-PARTNER-ID	Header	String(10)	Fixed	Y	Partner client id using KlikBCA Bisnis's Corporate ID
X-EXTERNAL-ID	Header	String(32)	Max	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	-	Mandatory in BCA. Transaction identifier on service consumer system

beneficiaryBankCode	String (8)	Max	Y	Alphanumeric	Mandatory in BCA. Beneficiary bank code. In BCA using SWIFT Code or 3 digit bank code (if destination doesn't have SWIFT Code). Beneficiary Bank Code can be checked on KBB menu: Miscellaneous > Information > Bank Code List
beneficiaryAccountNo	String (34)	Max	Y	Alphanumeric	Mandatory in BCA. Beneficiary Account If inquiryService = 1 (Switcher) max length = 28 If inquiryService = 2 (BI-FAST) max length = 34
additionalInfo	Object		Y		
sourceAccountNo	String (10)	Fixed	C	Numeric	Mandatory in BCA if inquiry using BI-FAST Source Account
inquiryService	String (1)	Fixed	Y	Numeric	Fill in according to the transfer transaction that will be used 1: Inquiry via Switcher 2: Inquiry via BI-FAST
amount	object		C		
value	String (13,2)	Max	C	Decimal	This field conditional and will mandatory if inquiryService = 2 (BI-FAST) Net amount of the transaction. if it's IDR then value includes 2 decimal digits. In BCA, max length = 13.2
currency	String(3)	Fixed	C	ISO-4217	This field conditional and will mandatory if

					inquiryService = 2 (BI-FAST) Currency (IDR)
purposeCode	String (5)	Max	C	Numeric	This field conditional and will mandatory if inquiryService = 2 (BI-FAST) Purpose Code 01 = Investment / Investasi 02 = Transfer of Wealth / Pemindahan Dana 03 = Purchase / Pembelian 99 = Others / Lainnya

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	-	Send by BCA according to the request input. Transaction identifier on service consumer system
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code to identify transaction status. Format : AAABBCC AAA : HTTP BB : Service Code CC : Case Code Example: 2001600
responseMessage	String (150)	Max	Y	Alphanumeric	Response description
referenceNo	String (64)	Max	C	Numeric	Send by BCA. Transaction identifier on service provider system. Must be filled upon successful transaction Unique each day from

						BCA. Must be filled upon successful transaction.
beneficiaryAccountName	String (100)	Max	Y	-		Send by BCA. Beneficiary Account Name
beneficiaryAccountNo	String (34)	Max	Y	-		Send by BCA according to the request input. Beneficiary account number
beneficiaryBankCode	String (8)	Max	Y	-		Send by BCA according to the request input. Beneficiary Bank Code. In BCA using SWIFT Code or 3 digit bank code (if destination doesn't have SWIFT Code) Beneficiary Bank Code can be checked on KBB menu: Miscellaneous > Information > Bank Code Lis

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
200	2001600	Successful	Transaction successful.
400	4001601	Invalid Field Format {field}	The data you entered does not match the format requirements.
400	4001602	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled.
401	4011600	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.
401	4011601	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.
403	4031601	Feature Not Allowed	Feature Not Allowed. Please make sure you registered this feature in your partnership data.

403	4031602	Exceeds Transaction Amount Limit	Your transaction amount exceeds your company limit
404	4041611	Invalid Account	The account used in transaction not valid
409	4091600	Conflict	Cannot use same X-EXTERNAL-ID in the same day.
500	5001600	General Error	General Error.
504	5041600	Timeout	Transaction timeout.

curl -X POST https://sandbox.bca.co.id/openapi/v2.0/account-inquiry-external

Request



```
1 curl -X POST https://sandbox.bca.co.id/openapi/v2.0/account-inquiry-external
2 -H 'Content-type:application/json'
3 -H 'Authorization:Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpvlJbU1mMU4a11MNDZ7Sg5u9a'
4 -H 'X-TIMESTAMP:2020-12-21T10:30:24+07:00'
5 -H 'X-
6 SIGNATURE:85be817c55b2c135157c7e89f52499bf0c25ad6eebe04a986e8c862561b19a5'
7 -H 'ORIGIN:www.hostname.com'
8 -H 'X-PARTNER-ID:KBCABCINDO'
9 -H 'X-EXTERNAL-ID:28910000006578499987546738976812'
10 -H 'CHANNEL-ID:95051'
11 -d '
12 {
13   "beneficiaryBankCode": "BRINIDJA",
14   "beneficiaryAccountNo": "888801000157508",
15   "beneficiaryName": "PT. ABCD",
16   "beneficiaryAddress": "Jl. Sudirman No. 123, Jakarta 10110, Indonesia"
17 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v2.0/account-inquiry-external
```

Response



```
1  -H 'Content-type:application/json'
2  -H 'X-TIMESTAMP:2020-12-21T10:30:24+07:00'
3  {
4    "partnerReferenceNo": "202010290000000000000001",
5    "responseCode": "2001600",
6    "responseMessage": "Successful",
7    "referenceNo": "202010297777000000000009",
8    "beneficiaryAccountName": "Yories Yolanda",
9    "beneficiaryAccountNo": "888801000157508",
10   "beneficiaryBankCode": "BRINIDJA"
11 }
12
13 SNAP Banking External Account Inquiry V2 uses following error sample schema:
14 -H 'Content-type:application/json'
15 ... ..
```

2. SNAP Banking Interbank Transfer

Introduction

With SNAP Banking Interbank transfer, you can perform fund transfer to other domestic bank by using Switcher/BI-FAST service. The source of fund transfer must be from your own account on your KlikBCA Bisnis. SNAP Banking Interbank Transfer transaction amount limit will follow KlikBCA Bisnis's rules about transaction amount limit in the following menu: Miscellaneous > Information > Transaction Limit Usage > Funds Transfer to Domestic BCA thru LLG, ONLINE and BI FAST Maximum Limit per day per corporate SNAP Banking Interbank Transfer frequency limit will follow KlikBCA Bisnis's rules about frequency limit in the following menu: Miscellaneous > Information > Transaction Limit Usage > Funds Transfer to Domestic Bank thru LLG, ONLINE and BI FAST Maximum Number of Transaction per day per corporate

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String(10)	Fixed	Y	KlikBCA Bisnis's Corporate ID
X-EXTERNAL-ID	Header	String(32)	Max	Y	Numeric String. Reference number that should be unique in the same day.

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
-------	-----------	-------------	-----------	--------	-------------

partnerReferenceNo	String (64)	Max	Y	-	Transaction identifier on service consumer system
amount	Object		Y		-
value	String (13.2)	Max	Y	Decimal	Net amount of the transaction. If it's IDR then value includes 2 decimal digits.
currency	String (3)	Fixed	Y	ISO-4217	Currency
beneficiaryAccountName	String (100)	Max	Y	-	Beneficiary Account Name
beneficiaryAccountNo	String (34)	Max	Y	-	Beneficiary Account
beneficiaryBankCode	String(8)	Max	Y	SWIFT Code/3 digit bank code	Beneficiary Bank Code. In BCA using SWIFT Code or 3 digit bank code (if destination doesn't have SWIFT Code). Beneficiary Bank Code can be checked on KBB menu : Miscellaneous > Information > Bank Code List
beneficiaryEmail	String(50)	Max	N	abc@domain.com	Beneficiary Email. Only one email address can be submitted.
sourceAccountNo	String (10)	Fixed	Y	Numeric	This response will be sent according to

					the request input. Source Account.
transactionDate	String (25)	Max	Y	ISO-8601	Mandatory in BCA. Transaction date
additionalInfo	Object		Y		
transferType	String (1)	Fixed	Y		1 = Transfer via switcher 2 = Transfer via BIFAST
purposeCode	String (5)	Max	N		Mandatory if transferType = 2 Purpose Code as defined in techdoc BI 01 = Investment/ Investasi 02 = Transfer of Wealth/ Pemindahan Dana 03 = Purchase/ Pembelian 99 = Others/ Lainnya

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String(64)	Max	N	Numeric	This response will be sent according to the request input. Transaction identifier on service consumer system.

responseCode	String (7)	Fixed	Y	Numeric	Response code
responseMessage	String(150)	Max	Y	Alphanumeric	Response description
referenceNo	String (64)	Max	C	Numeric	Will be sent when the transaction is successful as transaction identifier on service provider system. referenceNo = timestamp(6, yymmdd) + prefix menu(2) + sequence(6). prefix menu=kode fitur=02. sequence number unique each day.
amount	Object		Y		
value	String (13.2)	Max	Y	Decimal	This response will be sent according to the request input. Net amount of the transaction. If it's IDR then value includes 2 decimal digits.
currency	String (3)	Fixed	Y	ISO-4217	This response will be sent according to the request input. Currency.
beneficiaryAccountNo	String (34)	Max	Y	Numeric	This response will be sent according to the request input. Beneficiary account number.
beneficiaryBankCode	String (8)	Max	N	SWIFT Code/3 digit bank code	This response will be sent according to the request input. Beneficiary Bank Code. In BCA using SWIFT Code or 3 digit bank code (if destination

					doesn't have SWIFT Code). Beneficiary Bank Code can be checked on KBB menu : Miscellaneous > Information > Bank Code List
sourceAccountNo	String (19)	Max	N	-	Send by BCA according to the request input. Source account
additionalInfo					
bifastId	String (18)	Fixed	C	Alphanumeric	Will be sent when the transaction is successful and transferType = 2.

Error List:

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition	Transaction Status
400	4001800	Bad request	General request failed error.	
400	4001801	Invalid Field Format {field name}	The data you entered does not match the format requirements.	
400	4001802	Invalid Mandatory Field {Field Name}	Mandatory field should be fulfilled.	
401	4011800	Unauthorized. [Reason]	Invalid Signature/Unknown Client/ Connection Not Allowed.	
401	4011801	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.	
403	4031802	Exceeds Transaction Amount Limit	Your transaction amount exceeds your company limit. Please check your Company Limit at KlikBCA Bisnis.	
403	4031804	Activity Count Limit Exceeded	Too many request, Exceeds Transaction Frequency Limit. Please check your Company Limit at KlikBCA Bisnis.	

403	4031814	Insufficient Funds	Your balance in source account less than the amount of transfer you perform.
403	4031801	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
403	4031815	Transaction not permitted	BI-FAST service for selected Beneficiary Bank is currently unavailable. Please choose another transfer service.
404	4041803	Bank Not Supported By Switch	Bank not supported by BI-FAST.
404	4041811	Invalid Account	The account used in transaction not valid (do not exist/closed/cant be used for transactions).
404	4041813	Invalid Amount	Wrong amount input.
404	4041802	Invalid Routing	Connection problem to Switcher.
409	4091800	Conflict	X-EXTERNAL-ID duplicate.
429	4291800	Too Many Requests	Maximum transaction limit exceeded.
500	5001800	General Error	Wrong request field input. Internal system/external BI-FAST service is currently under maintenance. Please use other BCA transfer services.
500	5001801	Internal Server Error	Unknown internal server failure, please retry the process again.
504	5041800	Timeout	Your transaction timeout

If you get responseCode 5001801 (Unknown Error/Unknown internal server failure, please retry the process again) from BCA, please make sure to check your account statement before retry the transaction.


```
curl -X POST https://sandbox.bca.co.id/openapi/v2.0/transfer-interbank
```

Request



```
1 Request Interbank Transfer via Switcher Sample
2 -H 'CHANNEL-ID': '95051'
3 -H 'X-PARTNER-ID': 'KBBABCINDO'
4 -H 'X-EXTERNAL-ID': '28910000006578499987546738976812'
5 -d '
6 {
7   "partnerReferenceNo": "202010290000000000000001",
8   "amount": {
9     "value": "10000.00",
10    "currency": "IDR"
11  },
12  "beneficiaryAccountName": "Yories Yolanda",
13  "beneficiaryAccountNo": "888801000157508",
14  "beneficiaryBankCode": "BRINIDJA",
15  ...
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v2.0/transfer-interbank
```

Response



```
1 Response Sample
2
3 {
4   "responseCode": "2001800",
5   "responseMessage": "Successful",
6   "referenceNo": "202010297770000000000009",
7   "partnerReferenceNo": "202010290000000000000001",
8   "amount": {
9     "value": "10000.00",
10    "currency": "IDR"
11  },
12  "beneficiaryAccountNo": "888801000157508",
13  "beneficiaryBankCode": "BRINDIJA",
14  "sourceAccountNo": "0123456789"
15 }
```

3. SNAP Banking Internal Account Inquiry

This service is used to inquiry BCA account.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's identifier using WSID KlikBCA Bisnis (95051)

X-PARTNER-ID	Header	String(10)	Fixed	Y	Unique ID for a partner BCA using KlikBCA Bisnis's Corporate ID with Fix Length 10 digits.
X-EXTERNAL-ID	Header	String(32)	Max	Y	Numeric String. Reference number that should be unique in the same day.

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	Numeric	Transaction identifier on service consumer systems. The partnerReferenceNo used in the inquiry transaction must be reused when transferring to the account inquired. partnerReferenceNo mus not contain the following special characters: " : ; \$ < > .
beneficiaryAccountNo	String (10)	Fixed	Y	Numeric	Beneficiary Account

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Numeric	Response code
responseMessage	String (150)	Max	Y	Alphanumeric	Response description
referenceNo	String (64)	Max	Y	Numeric	This response will be sent as transaction identifier on service provider system. Must be filled upon successful transaction.

partnerReferenceNo	String (64)	Max	N	Numeric	This response will be sent according to the request input. Transaction identifier on service consumer system
beneficiaryAccountName	String (100)	Max	Y	Alphanumeric & Special Character	This response will be sent according to the request input. Beneficiary Account Name. The name returned is the name displayed on the channel, which have 24 digit characters. There is no special character validation, but the special characters displayed are: @ # \$ % ~ & * () _ + - = ¢ ! \ { }] ; : , . / < > ? ` ^
beneficiaryAccountNo	String (10)	Fixed	Y	Numeric	This response will be sent according to the request input. Beneficiary account number.

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	4001500	Bad request	General request failed error.
400	4001501	Invalid Field Format {field name}	The data you entered does not match the format requirements.
400	4001502	Invalid Mandatory Field {field name}	Mandatory field should be fulfilled.
401	4011500	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.

401	4011501	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/ Token is Invalid.
403	4031501	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
409	4091500	Conflict	X-EXTERNAL-ID duplicate.
403	4031518	Inactive Account	Indicates inactive account
404	4041511	Invalid Account	The account used in transaction not valid (do not exist/can't be used for transactions).
500	5001500	General Error	Wrong request field input.
500	5001501	Internal Server Error	Unknown internal server failure, please retry the process again.
504	5041500	Timeout	Your transaction timeout.

curl -X POST https://sandbox.bca.co.id/openapi/v1.0/account-inquiry-internal

Request



```
1  -H 'Content-type': 'application/json'
2  -H 'Authorization': 'Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpviJbU1mMU4a11MNDZ7Sg5u9a'
3  -H 'X-TIMESTAMP': '2020-12-17T13:50:04+07:00'
4  -H 'X-SIGNATURE':
   '85be817c55b2c135157c7e89f52499bf0c25ad6eeeb04a986e8c862561b19a5'
5  -H 'ORIGIN': 'www.hostname.com'
6  -H 'CHANNEL-ID': '95051'
7  -H 'X-PARTNER-ID': 'KBBABCINDO'
8  -H 'X-EXTERNAL-ID': '28910000006578499987546738976812'
9  -d '
10 {
11   "partnerReferenceNo": "20201029000000000001",
12   "beneficiaryAccountNo": "8010001575"
13 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/account-inquiry-internal
```

Response



```
1  -H 'Content-type': 'application/json'
2  -H 'X-TIMESTAMP': '2020-12-17T13:50:04+07:00'
3  {
4    "responseCode": "2001500",
5    "responseMessage": "Successful",
6    "referenceNo": "202010297777000009",
7    "partnerReferenceNo": "202010290000000001",
8    "beneficiaryAccountName": "Yories Yolanda",
9    "beneficiaryAccountNo": "8010001575"
10 }
```

4. SNAP Banking Intrabank Transfer

This service is used to transfer BCA.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String(32)	Max	Y	Partner client id using KlikBCA Bisnis's Corporate ID
X-EXTERNAL-ID	Header	String(32)	Max	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Info
partnerReferenceNo	String (64)	Max	Y	-	Transaction identifier system
amount	Object		Y		Net transfer
value	String	Max	Y	Numeric	If it's

	(13.2)				valu dec
currency	String (3)	Fixed	Y	ISO-4217	Cur
beneficiaryAccountNo	String (10)	Max	Y	Numeric	Ben Acc reg
beneficiaryEmail	String (50)	Max	N	abc@domain.com	Ben Opt
remark	String (36)	Max	N		Ren tion For is 30 in 2 with rem digi spe
sourceAccountNo	String (10)	Max	Y	Numeric	sou reg
transactionDate	String (25)	Max	Y	ISODateTime ISO-8601	dat
additionalInfo	Object		N		Adc info
economicActivity	String (60)	Max	Y (if the beneficiaryAccountNumber are WNA citizenship)	-	Che det in WNA Dev BCA
transactionPurpose	String (2)	Fixed	Y (if the currency of beneficiaryAccountNumber are in SGD or USD)	Numeric	Che det in WNA Dev BCA

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Desc
-------	--------------	----------------	-----------	--------	------

responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String (150)	Max	Y	-	Response description
referenceNo	String (64)	Max	N	Numeric	Transaction identifier service system *according to the request input
partnerReferenceNo	String (64)	Max	Y	-	Send by according to the request input. Transaction identifier service custom system each data partner
amount	Decimal				
value	String (13.2)	Max	Y	Numeric	If it's ID value in decimal
currency	String (3)	Fixed	Y	ISO-4217	Currency
beneficiaryAccountNo	String (10)	Max	Y	Numeric	Beneficiary account number
sourceAccountNo	String (10)	Max	Y	Numeric	Source number
transactionDate	String (25)	Max	Y	ISODateTime ISO-8601	Transaction date
additionalInfo	Object				
economicActivity	String (60)	Max	Y (if the beneficiaryAccountNumber are WNA citizenship)	-	Check detail information in Web Developer BCA

transactionPurpose	String (2)	Fixed	Y (if the currency of beneficiaryAccountNumber are in SGD or USD)	Numeric	Check detail informa in Web Develop BCA
--------------------	---------------	-------	---	---------	---

Choose one of the economic activities according to the transaction needs.

Error List:

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
200	2001700	Successful	Successful
400	4001700	Bad request	General request failed error.
400	4001702	Invalid Mandatory Field {Field}	Field format is Invalid.
400	4001701	Invalid Field Format {Field}	Mandatory field should be fulfilled.
401	4011700	Unauthorized. [Reason]	Invalid signature/Unknown client/Connection not allowed.
401	4011701	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/ Token is Invalid.
403	4031701	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
403	4031702	Exceeds Transaction Amount Limit	Exceeds Transaction Amount Limit
403	4031704	Activity Count Limit Exceeded	Too many request, Exceeds Transaction Frequency Limit
403	4031714	Insufficient Funds	Insufficient Funds.
403	4031715	Transaction Mot Permitted	X-PARTNER-ID is registered as a Securities company. but source account and beneficiary account are not whitelisted
403	4031718	Inactive Account	Indicates inactive account.
404	4041711	Invalid Amount	The account used in transaction not valid (do not exist/closed/cant be used for transactions).

404	4041713	Invalid Account	Wrong amount input.
409	4091700	Conflict	X-EXTERNAL-ID duplicate
429	4291700	Too Many Requests	Maximum transaction limit exceeded.
500	5001700	General Error	Wrong request field input.
500	5001701	Internal Server Error	Unknown internal server failure, please retry the process again
504	5041700	Timeout	Your transaction timeout.

If you get responseCode 5001701 (Internal Server Error) from BCA, please make sure to check your account statement before retry the transaction.

curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-intrabank

Request



```
1  -H 'Content-type: application/json'
2  -H 'Authorization: Bearer gp9HjjEj813Y9JGoqwOeOPWbnt4CUpvIJbU1mMU4a11MNDZ7Sg5u9a'
3  -H 'X-TIMESTAMP: 2024-03-25T13:50:04+07:00'
4  -H 'X-SIGNATURE:
    85be817c55b2c135157c7e89f52499bf0c25ad6eeeb04a986e8c862561b19a5'
5  -H 'ORIGIN: www.hostname.c
6  -H 'CHANNEL-ID: 95051'
7  -H 'X-PARTNER-ID: KBCABCINDO'
8  -H 'X-EXTERNAL-ID: 41807553358950093184162180797837'
9  -d '
10 {
11   "partnerReferenceNo": "202010290000000000000001",
12   "amount": {
13     "value": "10000.00",
14     "currency": "IDR"
15   }
16 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-intrabank
```

Response



```
1  RESPONSE CODE
2
3  -H "Content-type: application/json"
4  -H "X-TIMESTAMP: 2020-12-21T10:30:24+07:00"
5  {
6    "responseCode": "2001700",
7    "responseMessage": "Successful",
8    "referenceNo": "2020102977700000000009",
9    "partnerReferenceNo": "2020102900000000000001",
10   "amount": {
11     "value": "10000.00",
12     "currency": "IDR"
13   },
14   "beneficiaryAccountNo": "8888010001",
15   "beneficiaryName": "XXXXXXXXXXXX"
```

5. SNAP Banking Notify RTGS

This service is used to Transfer RTGS Notification.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel' Identifier
X-PARTNER-ID	Header	String(32)	Max	Y	Corporate ID

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
originalPartnerReferenceNo	String (64)	Max	N	-	Sent by BCA Original transaction identifier on service consumer system
originalReferenceNo	String (64)	Max	N	-	Sent by BCA Original transaction identifier on service provider system

originalExternalId	String (19)	Max	N	-	Sent by BCA Original Customer Reference Number
latestTransactionStatus	String (2)	Fixed	Y		Sent by BCA. BCA only notifies rejection from transactions that have been successfully processed by BCA 00 - Success 01 - Initiated 02 - Paying 03 - Pendin 04 - Refunded 05 - Canceled 06 - Failed 07 - Not found
amount	Object		Y		
value	String (16.2)	Max	Y	Decimal	Sent by BCA Net amount of the transaction. If it's IDR then value includes 2 decimal digits. In BCA, max length = 13.2
currency	String (3)	Fixed	Y	ISO-4217	Sent by BCA. Currency
beneficiaryAccountName	String (100)	Max	Y	-	Sent by BCA Beneficiary Account Name
beneficiaryAccountNo	String (34)	Max	Y	-	Sent by BCA Beneficiary Account
beneficiaryBankCode	String(8)	Max	Y	-	Sent by BCA. Beneficiary Bank Code. In BCA using SWIFT Code or 3 digit bank code (if destination doesn't have SWIFT Code)
sourceAccountNo	String (19)	Max	Y	-	Sent by BCA Source Account. 10 digits for BCA Account.

transactionDate	String (25)	Max	Y	ISO-8601	Mandatory in BCA. Transaction Date, which follows the ISO-8601 standard
additionalInfo	Object	-	Y	-	Sent by BCA Additional Info
rejectStatusID	String (100)	Max	Y	-	Sent by BCA Reject Description in Indonesian
rejectStatusEN	String (100)	Max	Y	-	Sent by BCA Reject Description in English
traceNo	String (100)	Max	Y	-	Sent by BCA Number for tracking to destination bank. In BCA traceNo=ppu_num ber with prefix “(“

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String(150)	Max	Y	-	Response description

```
curl -X POST https://copartners.com/openapi/v1.0/transfer-rtgs/notify
```

Request



```
1  -H 'CHANNEL-ID':'95051'
2  -H 'X-PARTNER-ID': 'KBCABCINDO'
3  -d '
4  {
5    "originalPartnerReferenceNo": "202010290000000000000001",
6    "originalReferenceNo": "202010297777000000000009",
7    "originalExternalId": "10052019",
8    "latestTransactionStatus": "00",
9    "amount": {
10   "value": "10000.00",
11   "currency": "IDR"
12  },
13   "beneficiaryAccountName": "Yories Yolanda",
14   "beneficiaryAccountNo": "888801000003301",
15   "beneficiaryAccountType": "KORPRI"
```

```
curl -X POST https://copartners.com/openapi/v1.0/transfer-rtgs/notify
```

Response



```
1  {
2    "responseCode": "2007600",
3    "responseMessage": "Successful"
4  }
```

6. SNAP Banking Notify SKNBI

This service is used to Transfer SKN Notification.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Y	Channel' Identifier
X-PARTNER-ID	Header	String(32)	Y	Corporate ID

Payload:

Field	Data	Length	Mandatory	Format	Description
-------	------	--------	-----------	--------	-------------

	Type	Type			
originalPartnerReferenceNo	String (64)	Max	N	-	Sent by BCA Original transaction identifier on service consumer system
originalReferenceNo	String (64)	Max	N	-	Sent by BCA Original transaction identifier on service provider system
originalExternalId	String (19)	Max	N	-	Sent by BCA Original Customer Reference Number
latestTransactionStatus	String (2)	Fixed	Y		Sent by BCA. BCA only notifies rejection from transactions that have been successfully processed by BCA 00 - Success 01 - Initiated 02 - Paying 03 - Pendin 04 - Refunded 05 - Canceled 06 - Failed 07 - Not found
amount	Object		Y		
value	String (16.2)	Max	Y	Decimal	Sent by BCA Net amount of the transaction. If it's IDR then value includes 2 decimal digits. In BCA, max length = 13.2
currency	String (3) ISO 4217	Fixed	Y	-	Sent by BCA. Currency
beneficiaryAccountName	String (100)	Max	Y	-	Sent by BCA Beneficiary Account Name

beneficiaryAccountNo	String (34)	Max	Y	-	Sent by BCA Beneficiary Account
beneficiaryBankCode	String(8)	Max	Y	-	Sent by BCA. Beneficiary Bank Code. In BCA using SWIFT Code or 3 digit bank code (if destination doesn't have SWIFT Code)
sourceAccountNo	String (19)	Max	Y	-	Sent by BCA Source Account. 10 digits for BCA Account.
transactionDate	String (25)	Max	Y	ISO-8601	Mandatory in BCA. Transaction Date, which follows the ISO-8601 standard
additionalInfo	Object	-	Y	-	Sent by BCA Additional Info
rejectStatusID	String (100)	Max	Y	-	Sent by BCA Reject Description in Indonesian
rejectStatusEN	String (100)	Max	Y	-	Sent by BCA Reject Description in English
traceNo	String (100)	Max	Y	-	Sent by BCA Number for tracking to destination bank. In BCA traceNo=ppu_num ber with prefix “(“

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String(150)	Max	Y	-	Response description

```
1 -H 'CHANNEL-ID':'95051'  
2 -H 'X-PARTNER-ID':'KBCABCINDO'  
3 -d '  
4 {  
5   "originalPartnerReferenceNo": "202010290000000000000001",  
6   "originalReferenceNo": "202010297777000000000009",  
7   "originalExternalId": "10052019",  
8   "latestTransactionStatus": "00",  
9   "amount": {  
10    "value": "10000.00",  
11    "currency": "IDR"  
12  },  
13  "beneficiaryAccountName": "Yories Yolanda",  
14  "beneficiaryAccountNo": "8888010000003301",  
15  "beneficiaryBranch": "0000"
```

```
1 {
2   "responseCode": "2007500",
3   "responseMessage": "Successful"
4 }
```

This service is used to transfer RTGS.

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String(32)	Max	Y	Corporate ID

272 of 429

Field	Data Type	Length Type	Mandatory	Format	Descrip
partnerReferenceNo	String (64)	Max	Y	-	Mandatory in BCA. Transaction identifier service consumer system
amount	Object		Y		
value	String (16.2) ISO4217	Max	Y	Decimal	Mandatory in BCA. It's amount the transaction. If it's IDR then value includes decimal digits. In BCA, max length = 13.2
currency	String (3)	Fixed	Y	-	Mandatory in BCA. Currency
beneficiaryAccountName	String (100)	Max	Y	-	Mandatory in BCA. Beneficiary Account Name
beneficiaryAccountNo	String (34)	Max	Y	-	Mandatory in BCA. Beneficiary Account
beneficiaryAddress	String (100)	Max	N	-	Mandatory in BCA. Beneficiary Address
beneficiaryBankCode	String(8)	Max	Y	-	Mandatory in BCA. Beneficiary Bank Code. In BCA use SWIFT Code

beneficiaryCustomerResidence	String (1)	Fixed	Y	Numeric	Mandatory in BCA. Beneficiary Customer Residence 1. Indonesian 2. Non Indonesian
beneficiaryCustomerType	String (1)	Fixed	Y	Numeric	Mandatory in BCA. Beneficiary Customer Type 1. Individual 2. Corporate 3. Government
beneficiaryEmail	String(50)	Max	N	abc@domain.com	Optional in BCA. Beneficiary Email
remark	String (50)	Max	N	-	Optional in BCA. Remark, transaction description For BCA remark is divided into two parts The maximum length of each part is 18.
sourceAccountNo	String (19)	Max	Y	-	Mandatory in BCA. Source Account Number For BCA length of account number is 19 digit.
transactionDate	String (25)	Max	Y	ISO-8601	Mandatory in BCA. Transaction date

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String(64)	Max	N	-	Send by BCA according to the request input. Transaction identifier on service consumer system
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String(150)	Max	Y	-	Response description
referenceNo	String (64)	Max	N	Numeric	Send by BCA. Transaction identifier on service provider system. Must be filled upon successful transaction.
amount	Object		Y		
value	String (16.2)	Max	Y	Decimal	Send by BCA according to the request input. Net amount of the transaction. If it's IDR then value includes 2 decimal digits. In BCA, max length = 13.2
currency	String (3)	Fixed	Y	ISO-4217	Send by BCA according to the request input. Currency
beneficiaryAccountName	String (100)	Max	Y	-	Send by BCA according to the request input. Beneficiary Account Name
beneficiaryAccountNo	String (34)	Max	Y	-	Send by BCA

					according to the request input. Beneficiary account
beneficiaryBankCode	String (8)	Max	Y	BCA : SWIFT	Send by BCA according to the request input. Beneficiary Bank Code
sourceAccountNo	String (19)	Max	N	-	Send by BCA according to the request input. Source account. For BCA account 10 digits
traceNo	String (16)	Max	N	-	Send by BCA. Number for tracking to destination bank. In BCA, traceNo = ppu_number with prefix "(" and the length is 5
transactionDate	String (25)	Max	Y	ISO-8601	Send by BCA according to the request input. Transaction date
transactionStatus	String (2)	Fixed	Y	Numeric	Transfer status code that send by BCA is the highlighted status code 00 - Success 01 - Initiated 02 - Paying 03 - Pending 04 - Refunded 05 - Canceled 06 - Failed 07- Not Found

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Transacti on Status
400	4002200	Bad request	06

400	4002201	Invalid Field Format {field}	06
400	4002202	Invalid Mandatory Field {Field}	06
401	4012200	Unauthorized. [Reason]	06
401	4012201	Invalid token (B2B)	06
403	4032201	Feature Not Allowed	06
403	4032202	Exceeds Transaction Amount Limit	06
403	4032204	Activity Count Limit Exceeded	06
403	4032206	Feature Not Allowed At This Time. The transaction has exceeded time limit for today processing	06
403	4032206	Feature Not Allowed At This Time. Transfer service to other bank is temporarily closed	06
403	4032214	Insufficient Funds	06
403	4032215	Transaction Not Permitted	06
403	4032218	Inactive Account	06
404	4042211	Invalid Account	06
404	4042213	Invalid Amount	06
409	4092200	Conflict	06
500	5002201	Internal Server Error	06 or 03
504	5042200	Timeout	03

If you get responseCode 5002201 (Unknown Error/Unknown internal server failure, please retry the process again) from BCA, please make sure to check your account statement before retry the transaction.

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-rtgs
```

Request



```
1  -H 'CHANNEL-ID':'95051'
2  -H 'X-PARTNER-ID': 'KBBABCINDO'
3  -d '
4  {
5    "partnerReferenceNo": "202010290000000000000001",
6    "amount": {
7      "value": "10000.00",
8      "currency": "IDR"
9    },
10   "beneficiaryAccountName": "Yories Yolanda",
11   "beneficiaryAccountNo": "888801000157508",
12   "beneficiaryAddress": "Palembang",
13   "beneficiaryBankCode": "002",
14   "beneficiaryCustomerResidence": "1",
15   "sourceAccountNo": "1234567899",
16   "sourceAccountName": "KlikBCA Bisnis"
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-rtgs
```

Response



```
1  RESPONSE
2  {
3    "responseCode": "2002200",
4    "responseMessage": "Request has been processed successfully",
5    "referenceNo": "202010297777000000000009",
6    "partnerReferenceNo": "202010290000000000000001",
7    "amount": {
8      "value": "10000.00",
9      "currency": "IDR"
10   },
11   "beneficiaryAccountName": "Yories Yolanda",
12   "beneficiaryAccountNo": "888801000157508",
13   "beneficiaryBankCode": "002",
14   "sourceAccountNo": "1234567899",
15   "sourceAccountName": "KlikBCA Bisnis"
```

8. SNAP Banking SKNBI Transfer

This service is used to transfer SKN.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's identifier using WSID KlikBCA Bisnis (95051)

X-PARTNER-ID	Header	String(10)	Fixed	Y	KlikBCA Bisnis's Corporate ID.
X-EXTERNAL-ID	Header	String(32)	Max	Y	Numeric String. Reference number that should be unique in the same day

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (64)	Max	Y	-	Transaction identifier service consumer system.
amount	Object		Y		
value	String (13.2)	Max	Y	Decimal	Net amount of the transaction. If it's IDF value include 2 decimal digits
currency	String (3)	Fixed	Y	ISO-4217	Currency
beneficiaryAccountName	String (100)	Max	Y	-	Beneficiary Account Name
beneficiaryAccountNo	String (34)	Max	Y	-	Beneficiary Account Number
beneficiaryAddress	String (100)	Max	Y	-	Beneficiary Address
beneficiaryBankCode	String(8)	Max	Y	SWIFT Code	Beneficiary Bank Code BCA user SWIFT Code Beneficiary Bank Code can be checked KBB menu Miscellaneous > Inform

						> Bank C List
beneficiaryCustomerResidence	String (1)	Fixed	Y		Numeric	Benefici Custom Residen 1. Indone 2. Non Indones
beneficiaryCustomerType	String (1)	Fixed	Y		Numeric	Benefici Custom Type : 1. Indivic 2. Corpora 3. Governr
beneficiaryEmail	String(50)	Max	N		abc@domain.com	Benefici Email
remark	String (50)	Max	N		-	Remark, transact descript For BCA remark i divided two parti The max length o each pa 18.
sourceAccountNo	String (10)	Max	Y		-	Source Account
transactionDate	String (25)	Max	Y		ISO-8601	Transac Date

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String(64)	Max	Y	-	This response will be sent according to the request input Transaction identifier on service

					consumer system.
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String(150)	Max	Y	-	Response description
referenceNo	String (64)	Max	N	Numeric	This response will be sent according to the request input Transaction identifier on service provider system. Must be filled upon successful transaction.
amount	Object		Y		
value	String (13.2)	Max	Y	Decimal	Net amount of the transaction. If it's IDR then value includes 2 decimal digits.
currency	String (3)	Fixed	Y	ISO-4217	This response will be sent according to the request input. Currency.
beneficiaryAccountName	String (100)	Max	Y	-	This response will be sent according to the request input. Beneficiary Account Name.
beneficiaryBankCode	String (8)	Max	Y	BCA : SWIFT	Send by BCA according to the request input. This response will be sent according to the request input. Beneficiary Bank Code. In BCA using SWIFT Code. Beneficiary Bank Code can be checked on KBB menu : Miscellaneous > Information > Bank Code List

sourceAccountNo	String (10)	Max	N	-	This response will be sent according to the request input. Source Account.
traceNo	String (5)	Max	N	-	This response will be sent according to the request input Number for tracking to destination bank. In BCA, traceNo = ppu_number with prefix “(“
transactionDate	String (25)	Max	Y	ISO-8601	This response will be sent according to the request input Transaction date
transactionStatus	String (2)	Fixed	Y	Numeric	BCA only notifies rejection from transactions that have been successfully processed by BCA. 00 – Success 03 – Pending 06 – Failed
transactionStatusDesc	String (50)	Max	N	-	Description status transaction

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Description	Transaction Status
400	4002300	Bad request	General request failed error.	Considered to be failed
400	4002301	Invalid Field Format {field namer}	The data you entered does not match the format requirements.	
400	4002302	Invalid Mandatory Field {field name}	Mandatory field should be fulfilled.	

401	4012300	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.	
401	4012301	Invalid token (B2B)	Access Token Not Exist/ Access Token Expired/ Token is Invalid.	
403	4032301	Feature Not Allowed		
403	4032302	Exceeds Transaction Amount Limit	Your transaction amount exceeds your company limit. Please check your Company Limit at KlikBCA Bisnis.	
403	4032304	Activity Count Limit Exceeded	Too many request, Exceeds Transaction Frequency Limit. Please check your Company Limit at KlikBCA Bisnis.	
403	4032306	Feature Not Allowed At This Time [Reason]	The transaction has exceeded time limit for today processing	
403	4032314	Insufficient Funds	Your balance in source account less than the amount of transfer you perform.	
403	4032315	Transaction Not Permitted	X-PARTNER-ID is registered as a securities company, but source account and beneficiary account are not whitelisted.	
403	4032318	Inactive Account	Indicates inactive account.	
404	4042311	Invalid Account	The account used in transaction not valid (do not exist/closed/can't be used for transactions).	
404	4042313	Invalid Amount	Wrong amount input.	
409	4092300	Conflict	X-EXTERNAL-ID duplicate.	
500	5002200	General Error	Wrong request field input.	Considered to be in

If you get responseCode 5002301 (Unknown Error/Unknown internal server failure, please retry the process again) from BCA, please make sure to check your account statement before retry the transaction.

Request

10 " " " " " "

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer-skn
```

Response



```
1  RESPONSE SAMPLE
2  -H 'Content-type': 'application/json'
3  -H 'X-TIMESTAMP': '2020-12-17T13:50:04+07:00'
4
5  {
6    "responseCode": "2002300",
7    "responseMessage": "Request has been processed successfully",
8    "referenceNo": "2020102977770000000009",
9    "partnerReferenceNo": "2020102900000000000001",
10   "amount": {
11     "value": "10000.00",
12     "currency": "IDR"
13   },
14   "beneficiaryAccountName": "Yories Yolanda",
15   "beneficiaryAccountNo": "2020102900000000000001"
```

9. SNAP Banking Transaction Status Inquiry

This service is used to transfer BCA.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	Channel's identifier using WSID KlikBCA Bisnis (95051)
X-PARTNER-ID	Header	String(32)	Max	Y	Corporate ID
X-EXTERNAL-ID	Header	String(32)	Max	Y	Numeric String. Reference number that should be unique in the same day.

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
originalPartnerReferenceNo	String (64)	Max	N	-	Original transaction identifier on service from partner

originalExternalId	String (32)	Max	Y	Numeric	Original External-ID on header message
serviceCode	String (2)	Fixed	Y	Numeric	Transaction type indicator (service code of the original transaction request) Service code of original transaction that can be requested 17 : Service Intrabank Transfer 18 : Service Interbank Transfer 22 : Service Interbank Transfer RTGS 23 : Service Interbank Transfer SKN 33 : Service Payment to VA from Intrabank
transactionDate	String (25)	Max	Y	ISODateTime ISO-8601	Transfer Transaction date

Note : Transaction Status Inquiry can only make inquiries on the status of the transaction below via Open API.

- Intrabank Transfer
- Interbank Transfer
- RTGS Transfer
- SKNBI Transfer
- Payment to VA from Intrabank

Transaction that can be inquired are only valid for the past 31 days.

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code

responseMessage	String(150)	Max	Y	-	Response description
originalReferenceNo	String (64)	Max	N	Numeric	Original transaction identifier on service provider system. Only mandatory if original transaction is successful.
originalPartnerReferenceNo	String (64)	Max	N	-	This response will be sent according to the request input. Original transaction identifier on service customer system
originalExternalId	String (32)	Max	N	Numeric	This response will be sent according to the request input. Original External-ID on header message
serviceCode	String (2)	Fixed	Y	Numeric	This response will be sent according to the request input. Transaction type indicator (service code of the original transaction request) Service code of original transaction that can be checked

					17 : Service Intrabank Transfer 18 : Service Interbank Transfer 22 : Service Interbank Transfer RTGS 23 : Service Interbank Transfer SKN 33 : Service Payment to VA
transactionDate	String (25)	Max	N	ISODateTime ISO-8601	This response will be sent according to the request input. Transaction date
amount	Object	-	Y	-	Net amount of the transaction
value	String (13.2)	Max	Y	Numeric	If it's IDR then value includes 2 decimal digits. BCA will send response amount with format value Numeric (13.2)
currency	String (3)	Fixed	Y	ISO-4217	Currency of the amount
beneficiaryAccountNo	String (34)	Max	Y	Numeric	Beneficiary account number
beneficiaryBankCode	String (8)	Max	N	SWIFT Code/ 3 digit bank code	Beneficiary Bank Code. In BCA using SWIFT Code or 3 digit bank code (if destination doesn't have SWIFT Code).

					Beneficiary Bank Code can be checked on KBB menu : Miscellaneous > Information > Bank Code List
referenceNumber	String (30)	Max	N	Numeric	Transaction identifier on service provider system. Unique each day from BCA Must be filled upon successful transaction.
sourceAccountNo	String (10)	Max	Y	Numeric	Source Account Number.
latestTransactionStatus	String (2)	Fixed	Y	Numeric	Transfer status code that sent is the highlighted status code. 00 - Success 03 - Pending 06 - Failed
transactionStatusDesc	String(50)	Max	N		Description status transaction 00 : Transaction Success 03 : Transaction In Progress 06 : Response message from failed transaction

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	4003600	Bad request	General request failed error.
400	4003601	Invalid Field Format {field}	The data you entered does not match the format requirements.
400	4003602	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled.
401	4013600	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.
401	4013601	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.
403	4033601	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
404	4043601	Transaction not found	Transaction not found.
409	4093600	Conflict	X-EXTERNAL-ID duplicate.
429	4293600	Too Many Requests	Maximum transaction limit exceeded.
500	5003600	General Error	Wrong request field input.
500	5003601	Internal Server Error	Unknown internal server failure, please retry the process again.
504	5043600	Timeout	Your transaction timeout.

curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer/status

Request



```
1 -H 'CHANNEL-ID': '95051'
2 -H 'X-PARTNER-ID': 'KBBABCINDO'
3 -H 'X-EXTERNAL-ID': '28910000006578499987546738976812'
4 -d '
5 {
6   "originalPartnerReferenceNo": "202010290000000000000001",
7   "originalExternalId": "30443786930722726463280097920912",
8   "serviceCode": "17",
9   "transactionDate": "2023-02-02T00:00:00+07:00"
10 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/transfer/status
```

Response



```
1 Inquiry Successful Status Transaction
2
3 -H 'Content-type': 'application/json'
4 -H 'X-TIMESTAMP': '2020-12-17T13:50:04+07:00'
5 {
6   "responseCode": "2003600",
7   "responseMessage": "Successful",
8   "originalReferenceNo": "2010297777000009",
9   "originalPartnerReferenceNo": "202010290000000000000001",
10  "originalExternalId": "30443786930722726463280097920912",
11  "serviceCode": "17",
12  "transactionDate": "2023-02-02T00:00:00+07:00",
13  "amount": {
14    "value": "10000.00",
15    "currency": "IDR"
16  }
```

Collection

1. Account Debiting Consent Notification

Service for BCA to notify Account Authorization Registration Status.

This feature is not yet available to be accessed via Sandbox

Your Request must contain following information:

Request

Field	Data Type	Mandatory	Length Type	Format	Description
request_id	String(33)	Y	Fix	-	Request ID
customer_id_merchant	String(15)	Y	Max Length	Number	CustomerID Merchant
customer_name	String(30)	Y	Max Length	-	Customer Name
db_account_no	String(10)	Y	Fix	Number	Mandatory if the status is 01 and 03
status	String(2)	Y	Fix	Number	SKPR Registration Status "01" = Success Register "02" = Failed

					Register "03" = Success Delete "04" = Failed Delete
Reason	Object	-	-	-	-
english	String(50)	N	Max Length	-	
indonesia	String(50)	N	Max Length	-	

Response

Field	Data Type	Mandatory	Description
request_id	String(33)	Y (if SKPR Digital)	Request ID if SKPR Digital
response_ws	String(1)	Y	Response 0 = Success 1 = Failed

POST https://copartners.com/account-authorization/notification

Request



```
1 SKPR Digital Success
2
3 POST https://copartners.com/account-authorization/notification
4 -d '{
5   "request_id": "A2AAB46BE91573E6E05400144FFED17AB",
6   "customer_id_merchant": "0818181818181",
7   "customer_name": "nama pelanggan",
8   "db_account_no": "0611112221",
9   "status": "01"
10  }'
```

```
11
12 Request for registration SKPR Digital (failed)
13 POST https://copartners.com/account-authorization/notification
14 -d '{
15   "request_id": "A2AAB46BE91573E6E05400144FFED17AB",
16   "customer_id_merchant": "0818181818181",
17   "customer_name": "nama pelanggan",
18   "db_account_no": "0611112221",
19   "status": "01"
20  }'
```

POST https://copartners.com/account-authorization/notification

Response



```
1  Response for SKPR Digital
2  {
3    "request_id": "A2AAB46BE91573E6E05400144FFED17AB",
4    "response_ws": "0"
5  }
6
7  Response for SKPR Conventional
8  {
9    "response_ws": "0"
10 }
```

2. Add Fund Collection

This service is used to collect some amount of money from your destination bank account that have been blocked before.

This feature is not yet available to be accessed via Sandbox

Your Request must contain following information:

Additional headers

Field	DataType	Mandatory	Description
ChannelID	String(5)	Y	Channel's identifier. Fill it with "95051".
CredentialID	String(10)	Y	Channel's credential (KlikBCA Bisnis Corporate ID)

Request

Field	DataType	Mandatory	Description
TransactionID	String(18)	Y	Unique data from Corporate. Format: Numeric.
ReferenceNumber	String(14)	Y	Sender's Transaction Reference ID. Format: Numeric.
RequestType	String(2)	Y	B = With Blocking, NB = Without Blocking. Format: B or NB.
DebitedAccount	String(10)	O	Account to be debited, please make sure you have authority to debit the account. Mandatory ONLY IF RequestType = NB (Without Blocking). Otherwise must left empty. Format: Numeric.

Amount	String(16)	Y	Maximum length is 16, include decimal amount. Format: Numeric, 13.2
Currency	String(3)	Y	Currently is IDR only.
CreditedAccount	String(10)	Y	Account to be credited. Must be registered as own account at KlikBCA Bisnis.
EffectiveDate	String(10)	Y	Transaction Effective Date. Max : 366 days. Format: yyyy-MM-dd.
TransactionDate	String(10)	Y	The date of the Transaction. Format: yyyy-MM-dd.
Remark1	String(18)	Y	Transfer remark for receiver.
Remark2	String(18)	Y	Transfer remark for receiver.
Email	String(254)	Y	Email address of beneficiary (blocked account's owner).

Response

Field	DataType	Description
TransactionID	String(18)	Unique data from Corporate. Format: Numeric.
ReferenceNumber	String(14)	Sender's Transaction Reference ID. Format: Numeric.
RequestType	String(2)	B = With Blocking, NB = Without Blocking. Format: B or NB.
DebitedAccount	String(10)	Account to be debited, must registered at KlikBCA Bisnis.Mandatory ONLY IF RequestType = NB (Without Blocking). Otherwise must left empty. Format: Numeric.
Amount	String(16)	Maximum length is 16, include decimal amount. Format: Numeric, 13.2
Currency	String(3)	Currently is IDR only.
CreditedAccount	String(10)	Account to be credited
EffectiveDate	String(10)	Transaction Effective Date. Max : 366 days. Format: yyyy-MM-dd.
TransactionDate	String(10)	The date of the Transaction Performed get by system. Format: yyyy-MM-dd.
Status	String(10)	Transaction status

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)	Additional Information
400	ESB-07-575	Sistem BCA sedang dalam pemeliharaan	BCA system on maintenance	System under maintenance.
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch	Please check generate signature process.
400	ESB-14-002	Permintaan tidak valid	Invalid request	Invalid request.
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp	Invalid timestamp format.
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance	System under maintenance.
401	ESB-14-008	client_id/ client_secret/grant_type tidak valid	Invalid client_id/ client_secret/ grant_type	Invalid client_id/ client_secret/grant_type.
401	ESB-14-009	Tidak berhak	Unauthorized	Invalid Signature/Unknown Client/Connection Not Allowed.
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded	Limit request exceeded.
404	ESB-14-011	Service tidak ada	Service doesn't exist	Invalid service, please check service's URI.
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
401	ESB-14-014	ChannelID/ CredentialID tidak valid	Invalid ChannelID/ CredentialID	Channel ID : 95051 Credential ID : KlikBCA Bisnis Corporate ID.
400	ESB-14-015	Content Type tidak valid	Invalid Content Type	Invalid Content Type
400	ESB-14-016	Format JSON tidak valid	Invalid JSON format	Invalid JSON format.

504	ESB-14-023	Koneksi Timeout. Silakan cek transaksi kembali untuk memastikan keberhasilan transaksi Anda.	Connection timeout. Please reinquiry your transaction to ensure transaction status.	Please check your account statement before retry the transaction.
400	ESB-82-003	TransactionID tidak unik	TransactionID not unique	Please provide unique TransactionID.
400	ESB-82-006	Nominal Transaksi melebihi Limit Maksimum	Transaction amount is greater than Maximum Limit Allowed	Your transaction amount exceeds your company limit. Please check your Company Limit at KlikBCA Bisnis.
400	ESB-82-007	Tanggal efektif lebih kecil dari tanggal hari ini	Effective Date is smaller than today	Effective Date is smaller than today.
400	ESB-82-015	Nominal transaksi kurang dari Limit Minimum	Transaction amount is smaller than Minimum Limit Allowed	Your transaction amount below your company limit. Please check your Company Limit at KlikBCA Bisnis.
400	ESB-82-019	Saldo tidak cukup	Insufficient fund	Account balance insufficient for the transaction.
400	ESB-82-027	Amount harus lebih dari nol	Amount must be greater than zero	Amount must be greater than zero
400	ESB-82-030	Untuk Request Type: B, field DebitedAccount tidak diperlukan	For Request Type: B, field DebitedAccount is not necessary	DebitedAccount field only for Request type : NB.
400	ESB-82-031	Frekuensi transaksi telah melebihi batas maksimum	Transaction frequency has exceeded the maximum number	Too many request, Exceeds Transaction Frequency Limit. Please check your Company Limit at KlikBCA Bisnis.
400	ESB-82-177	Tidak memiliki kuasa debet atas rekening debet	Not authorized to debit the debited account	Authorization to debit the debited account is not found in the system. Please make sure you have authority to debit the account.
400	ESB-82-178	Rekening tidak aktif	Inactive Account	The credited or debited account cannot be used for

				transaction. The account may be closed or blocked.
400	ESB-99-009	Field (0) harus diisi	Missing mandatory field (0)	Mandatory field must be filled.
400	ESB-99-022	2 Format alamat email tidak sesuai	Email address format is not valid	Check your email address format. Valid email address example : example@email.com.
400	ESB-99-040	Tipe isian field (0) tidak valid	Input type for field (0) not valid	Please refer to request format above.
400	ESB-99-112	Input string JSON tidak valid	Invalid JSON string input	Please check JSON string input
400	ESB-99-128	Panjang field (0) melebihi ketentuan	Field (0) exceed limit	Please refer to request format above.
400	ESB-99-155	Mata uang harus IDR	Currency must in IDR	The currency must in IDR.
400	ESB-99-173	Format tanggal tidak sesuai	Invalid date format	Valid date format : yyyy-MM-dd
400	ESB-99-211	Panjang field (0) tidak valid	Invalid (0) field length	Please check field length according to request-response format above.
400	ESB-99-376	Format (0) tidak sesuai	Invalid field (0) format	Amount format is not valid. Please refer to request format above.
400	ESB-99-407	Nomor rekening tidak terdaftar sebagai rekening operasional	Account number not registered as operational account	Please make sure the credited account already registered as operational account in KlikBCA Bisnis.
400	ESB-99-524	ReferenceID sudah ada	ReferenceID already exists	ReferenceID already exists.
400	ESB-99-533	Field (0) harus numerik	Field (0) should be numeric	Only use numeric format.
400	ESB-99-573	TransactionDate harus diisi dengan tanggal hari ini	Transaction Date must be filled with today's date	Transaction Date must be filled with today's date.
400	ESB-99-670	Jenis transaksi tidak diijinkan	Transaction Type not allowed	Please make sure your KlikBCA Bisnis package has AutoCollection Satuan features.

POST /fund-collection/v2

Response



```
1  {
2    "TransactionID" : "0000000001",
3    "ReferenceID" : "111111110",
4    "DebitedAccount" : "1234567890",
5    "Amount" : "100200300.00",
6    "Currency" : "IDR",
7    "CreditedAccount" : "1234567891",
8    "EffectiveDate" : "2018-02-15",
9    "TransactionDate" : "2018-02-15"
10   "Status" : "TRAN SUCCESSFUL",
11 }
```

3. Inquiry Status Kuasa Pendebetan Rekening

This service is used to get account authorization status based on the customer id.

This feature is not yet available to be accessed via Sandbox

Your Request must contain following information:

Additional headers and URI Params

Field	Params Type	Data Type	Mandatory	Description
ChannelID	Header	String(5)	Y	Channel ID (BCA channel's identifier).Ex: "95051".
CredentialID	Header	String(10)	Y	Company Code Auto-Collection
customer_id_merchant	Path	String(15)	Y	Customer ID in number. Account authorization status that can be inquired is 7 days back from the inquiry date

Response

Field	Data Type	Description
customer_id_merchant	String(15)	Customer id from input
skpr_pending	Object	Account authorization pending list. Shows list of on process/ failed account authorization registration
request_id	String(33)	Request ID. ID when request registration

status	String(2)	Registration status: 02 = Failed 03 = On process
failed_date	String(10)	Account authorization failed date (only when status = 02) Format: yyyy-MM-dd
skpr_active	Object	Account authorization active list. Shows list of active account authorization registration
skpr_id	String(33)	SKPR ID. ID when request registration
db_account_no	String(10)	Account number registered
active_date	String(10)	SKPR active date Format: yyyy-MM-dd

Here is the list of error codes that can be returned:

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	3-2-100	ID pelanggan harus diisi	Customer ID cannot be empty
400	3-2-100	ID pelanggan tidak valid	Invalid customer ID
400	3-2-100	Nama pelanggan harus diisi	Customer name cannot be empty
400	3-2-100	Nama pelanggan tidak valid	Invalid customer name
400	3-2-100	Tipe debit harus diisi	Debit type cannot be empty
400	3-2-100	Tipe debit tidak valid	Invalid debit type
400	3-2-100	Jumlah pembayaran harus diisi	Amount cannot be empty
400	3-2-100	Jumlah pembayaran tidak valid	Invalid amount
400	3-2-101	Kode perusahaan tidak valid	Invalid company code
400	3-2-300	Registrasi Kuasa Debet telah melebihi batas maksimal. Silahkan hubungi Halo BCA untuk informasi lebih lanjut	Account Authorization registrastion already exceed the limit. Please contact Halo BCA for the further information
400	3-2-307	ID pelanggan sudah aktif	Customer ID already active
400	3-2-325	Data pelanggan tidak ditemukan	Customer data not found
400	3-2-300	Transaksi tidak dapat diproses. Silahkan ulangi beberapa saat lagi	Transaction cannot be completed. Please try again later

400	3-2-998	Transaksi gagal. Silahkan ulangi beberapa saat lagi	Transaction failed. Please try again later.
400	3-2-999	Transaksi tidak dapat diproses. Silahkan ulangi beberapa saat lagi	Transaction cannot be completed. Please try again later

GET /account-authorization/inquiry/{customer_id_merchant}

Request



```
1 GET /account-authorization/inquiry/0818181818181 HTTP/1.1
2 Host: sandbox.bca.co.id
3 Authorization: Bearer [access_token]
4 Content-Type: application/json
5 Origin: [yourdomain.com]
6 X-BCA-Key: [api_key]
7 X-BCA-Timestamp: [timestamp]
8 X-BCA-Signature: [signature]
9 ChannelID: [channelID]
10 CredentialID: [credentialID]
```

GET /account-authorization/inquiry/{customer_id_merchant}

Response



```
1 {
2   "customer_id_merchant": "0818181818181",
3   "skpr_pending": [
4     {
5       "request_id": "A9DB1D7A9CE804C5E05400144FFED17A",
6       "status": "03"
7     },
8     {
9       "request_id": "A9DB1D7A9CE704C5E05400144FFED17A",
10      "status": "02",
11      "failed_date": "2020-07-06"
12    }
13  ],
14  "skpr_active": [
15    -
16  ]
17 }
```

4. Pencabutan Kuasa Pendebetan Rekening

Delete your registration Account Authorization.

This feature is not yet available to be accessed via Sandbox

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String(5)	Y	Channel ID KlikBCA Bisnis 95051
credential-id	Header	String(8)	Y	Company Code Auto-Collection
customer_id_merchant	Path	String(15)	Y	Customer ID Merchant
db_account_no	Path	String(10)	Y	Customer Account No

Response

Field	DataType	Mandatory	Description
customer_id_merchant	String(15)	Y	Customer ID Merchant
db_account_no	String(10)	Y	Customer Account No
status	String(11)	Y	Default status "In Progress"

Here is the list of error codes that can be returned:

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	3-2-100	ID pelanggan harus diisi	Customer ID cannot be empty
400	3-2-100	ID pelanggan tidak valid	Invalid customer ID
400	3-2-100	Nama pelanggan harus diisi	Customer name cannot be empty
400	3-2-100	Nama pelanggan tidak valid	Invalid customer name
400	3-2-100	Tipe debit harus diisi	Debit type cannot be empty
400	3-2-100	Tipe debit tidak valid	Invalid debit type
400	3-2-100	Jumlah pembayaran harus diisi	Amount cannot be empty
400	3-2-100	Jumlah pembayaran tidak valid	Invalid amount

400	3-2-101	Kode perusahaan tidak valid	Invalid company code
400	3-2-300	Registrasi Kuasa Debet telah melebihi batas maksimal. Silahkan hubungi Halo BCA untuk informasi lebih lanjut	Account Authorization registrastion already exceed the limit. Please contact Halo BCA for the further information
400	3-2-307	ID pelanggan sudah aktif	Customer ID already active
400	3-2-325	Data pelanggan tidak ditemukan	Customer data not found
400	3-2-300	Transaksi tidak dapat diproses. Silahkan ulangi beberapa saat lagi	Transaction cannot be completed. Please try again later
400	3-2-998	Transaksi gagal. Silahkan ulangi beberapa saat lagi	Transaction failed. Please try again later.
400	3-2-999	Transaksi tidak dapat diproses. Silahkan ulangi beberapa saat lagi	Transaction cannot be completed. Please try again later

DELETE /accountauthorization/customer/832789861532974/account-number/51421329865

Request



```
1 curl -X DELETE https://sandbox.bca.co.id/accountauthorization/customer/832789861532974/
  account-number/51421329865
2 -H 'channel-id':'95051'
3 -H 'credential-id': '00000001'
```

DELETE /accountauthorization/customer/832789861532974/account-number/51421329865

Response



```
1 {
2   "customer_id_merchant": "832789861532974",
3   "db_account_no": "51421329865",
4   "status": "In Progress"
5 }
```

5. Pendaftaran Kuasa Pendebetan rekening

Get your request ID which will be required to access Account Authorization webview.

This feature is not yet available to be accessed via Sandbox

Your Request must contain following information:

Additional headers

Field	DataType	Mandatory	Description
ChannelID	String(5)	Y	Channel ID (BCA channel's identifier).Ex: "95051".
CredentialID	String(10)	Y	Company Code Auto-Collection

Request

Field	DataType	Mandatory	Description
customer_id_merchant	String(15)	Y	Customer id merchant in number.
identifications	Object	Y	Customer data
type	Numeric(1)	Y	Customer data type. Type contains numbers 1, 2, and 3. 1 = "Nama Pelanggan" 2 = "Tipe Debit" 3 = "Nominal Pembayaran"
identification	String(30)	Y	If "type" : "1" then "identification" : "customer name". Example : "identification" : "budi"
identification	String(1)	Y	If "type" : "2" then "identification" : "tipe_debit" (F : Fix / V : Variable). Example : "identification" : "V"
identification	Numeric(13)	Y	If "type" : "3" then "identification" : "nominal pembayaran". If tipe_debit = V then amount "0". If tipe_debit = F the amount "nominal transaksi". Example : "identification" : "0"
merchant_logo_url	String	N	Merchant logo URL to display on webview

Response

Field	DataType	Mandatory	Description
request_id	String(33)	Y	Registration token to open a webview
random_string	String(16)	Y	Random string used to generate String verification to open webview

expired_date	Long(13)	Y	Expired date in epoch
created_date	Long(13)	Y	Created date in epoch

Here is the list of error codes that can be returned:

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	3-2-100	ID pelanggan harus diisi	Customer ID cannot be empty
400	3-2-100	ID pelanggan tidak valid	Invalid customer ID
400	3-2-100	Nama pelanggan harus diisi	Customer name cannot be empty
400	3-2-100	Nama pelanggan tidak valid	Invalid customer name
400	3-2-100	Tipe debit harus diisi	Debit type cannot be empty
400	3-2-100	Tipe debit tidak valid	Invalid debit type
400	3-2-100	Jumlah pembayaran harus diisi	Amount cannot be empty
400	3-2-100	Jumlah pembayaran tidak valid	Invalid amount
400	3-2-101	Kode perusahaan tidak valid	Invalid company code
400	3-2-300	Registrasi Kuasa Debet telah melebihi batas maksimal. Silahkan hubungi Halo BCA untuk informasi lebih lanjut	Account Authorization registrastion already exceed the limit. Please contact Halo BCA for the further information
400	3-2-307	ID pelanggan sudah aktif	Customer ID already active
400	3-2-325	Data pelanggan tidak ditemukan	Customer data not found
400	3-2-300	Transaksi tidak dapat diproses. Silahkan ulangi beberapa saat lagi	Transaction cannot be completed. Please try again later
400	3-2-998	Transaksi gagal. Silahkan ulangi beberapa saat lagi	Transaction failed. Please try again later.
400	3-2-999	Transaksi tidak dapat diproses. Silahkan ulangi beberapa saat lagi	Transaction cannot be completed. Please try again later

1. SNAP OneKlik Account Binding

This feature is not yet available to be accessed via Sandbox

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)		Y	Channel's identifier (95221)

X-PARTNER-ID	Header	String(36)	Y	Partner/Merchant Unique ID
X-EXTERNAL-ID	Header	String (36)	Y	Reference Number from Partner/Merchant
X-DEVICE-ID	Header	String (400)	Y	Customer Device Info Format: {device-id} {user-agent} {OS type} {OS version} device-id : - Android ID (Android) - UUID (iOS) - "WEB" (browser) user-agent : user agent device / browser (max 300 characters) OS type : Operating system type of device (Android,Iphone,Web) OS version : Operating system version of device with format (x.y.z or x.y)
X-IP-ADDRESS	Header	String (15)	Y	Customer IP Address (IPv4 Format)

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
merchantId	String (5)		Y		Partner/Merchant Unique ID
additionalData	Object		Y		
userId	String (18)		Y		Customer Id from Merchant
additionalInfo	Object		Y		
additionalInfo	String (50)		Y		Additional information about customer (phone/email/etc)
merchantLogoUrl	String (300)		N		Merchant logo URL to show in OneKlik Registration Web

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y		Response code
responseMessage	String (150)		Y		Response message description
referenceNo	String (32)		Y		Response reference number from OneKlik
additionalInfo	Object		C		Filled upon transaction with responseCode success
requestId	String (32)		Y		Request ID to open OneKlik Registration Web
randomString	String (16)		Y		Random String to generate token to open OneKlik Registration Web

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2000700	Successful
400	4000700	Bad request
400	4000701	Invalid Field Format {Field}
400	4000702	Invalid Mandatory Field {Field}
401	4010701	Invalid token (B2B)
401	4010700	Unauthorized. [Reason]
403	4030701	Feature Not Allowed
403	4030704	Activity Count Limit Exceeded
404	4040708	Invalid Merchant
500	5000700	General Error
500	5000700	Internal Server Error
504	5040700	Timeout

```
curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-account-binding
```

Request



```
1  DEVICE WEB
2
3  -H 'CHANNEL-ID': '95221'
4  -H 'X-PARTNER-ID': '61123'
5  -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
6  -H 'X-IP-ADDRESS': '123.123.123.123'
7  -H 'X-DEVICE-ID': 'WEB||Mozilla/5.0 (Windows NT 10.0; Win64; x64)
8  AppleWebKit/537.36 (KHTML, like Gecko) Chrome/95.0.4638.69 Safari/537.36||Web||95.0'
9  -d '
10 {
11   "merchantId": "61123",
12   "additionalData": {
13     "userId": "customer01"
14   },
15   "channelId": "95221"
```

```
curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-account-binding
```

Response



```
1  {
2    "responseCode": "2000700",
3    "responseMessage": "Successful",
4    "referenceNo": "37f89370b5034db0a283130c231dd27b",
5    "additionalInfo": {
6      "requestId": "2c90c800702d1234017033ab9a060003",
7      "randomString": "g4BoEz43jfjVvAvN"
8    }
9  }
```

2. SNAP OneKlik Account Binding Inquiry

This service is used to inquiry OneKlik Account Binding Status.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)		Y	Channel's identifier (95221)

X-PARTNER-ID	Header	String(36)	Y	Partner/Merchant Unique ID
X-EXTERNAL-ID	Header	String (36)	Y	Reference Number from Partner/Merchant

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
additionalInfo	Object		Y		Must only fill one field : requestIds or userId
requestIds	>Array of String [1..10]@32		C	Alphanumeric	Request ID to search registration status. Can be filled up to 10 strings
userId	String (18)		C	Alphanumeric	Customer id from merchant
merchantId	String (5)		C	Numeric	Merchant unique ID. Mandatory for IT Gateway integration only

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y		Response code
responseMessage	String (150)		Y		Response message description
referenceNo	String (32)		C		Response reference number from OneKlik Filled if response success
additionalInfo	Object		C		Filled upon transaction with responseCode success
accountData	Array of Object		C		List of account. Sent if inquiry data successful. If input filled with requestId

				then Registration datas. If input filled with userId then Active account datas
requestId	String (32)	C		Request ID used when registering account. Only show up when inquiry registration data
xcold	String (32)	C		Valid OneKlik Identifier when credential successfully registered to BCA. Only show up when data already active
credentialType	String (2)	C		Credential type. DC = Debit card CC = Credit card
credentialNumber	String (16)	C		Customer credential number (masked)
maxLimit	String (9)	C		OneKlik max daily limit registered
userId	String (18)	C		Customer id from merchant
merchantId	String (5)	C		Partner/Merchant Unique ID
createdDate	String	C	DateTime	Request Id created date. Format: ISO 8601 Note: registration data can only be inquired maximum of 7 days
status	String (3)	Y		Registration Status REG = Registration in progress EXP = Expired ACT = Already activated (** does not define the latest account status) -= not found/already past 7 days Account Status ACT = Active BLK = Temporarily Blocked

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2000800	Successful
400	4000800	Bad request
400	4000801	Invalid Field Format {Field}
400	4000802	Invalid Mandatory Field {Field}
401	4010801	Invalid token (B2B)
401	4010800	Unauthorized. [Reason]
403	4030801	Feature Not Allowed
404	4040808	Invalid Merchant
500	5000800	General Error
500	5000800	Internal Server Error
504	5040800	Timeout

With userId: `curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-account-inquiry`
With requestId: `curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-accountbinding`

Request



```
1  WITH userId - with merchantId
2
3  curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-account-inquiry
4  -H 'CHANNEL-ID': '95221'
5  -H 'X-PARTNER-ID': '61123'
6  -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
7  -d '
8  {
9    "additionalInfo": {
10     "userId": "customer01",
11     "merchantId": "61123",
12   }
13 }'
```


With userId: curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-account-inquiry
With requestIds: curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-accountbinding

Response



```
1  WITH userId filled
2
3  {
4    "responseCode": "2000800",
5    "responseMessage": "Successful",
6    "referenceNo": "37f89370b5034db0a283130c231dd27b",
7    "additionalInfo": {
8      "accountData": [
9        {
10         "xcold": "a6fe3266cafd4cddbe3d77e1a9855634",
11         "credentialType": "DC",
12         "credentialNumber": "*****1234",
13         "maxLimit": "1000000",
14         "userId": "customer01",
15         "password": "*****"
```

3. SNAP OneKlik Account Unbinding

This service is used to unbinding OneKlik Account.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)		Y	Channel's identifier (95221)
X-PARTNER-ID	Header	String(36)		Y	Partner/Merchant Unique ID
X-EXTERNAL-ID	Header	String (36)		Y	Reference Number from Partner/Merchant

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
merchantId	String (5)		Y		Partner/Merchant Unique ID

additionalInfo	Object	Y	
xcold	String (32)	Y	Valid OneKlik Identifier when credential successfully registered to BCA

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y		Response code
responseMessage	String (150)		Y		Response message description
referenceNo	String (32)		C		Response reference number from OneKlik Filled if response success
unlinkResult	String (32)		C		Result of Unlinking process. "success"/"failed"
additionalInfo	Object		C		Filled upon transaction with responseCode success
xcold	String (32)		Y		Valid OneKlik Identifier when credential successfully registered to BCA. Only show up when data already active.

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2000900	Successful
400	4000900	Bad request
400	4000901	Invalid Field Format {Field}
400	4000902	Invalid Mandatory Field {Field}
401	4010901	Invalid token (B2B)
401	4010900	Unauthorized. [Reason]

403	4030901	Feature Not Allowed
404	4040911	Invalid Card/Account/Customer
500	5000900	General Error
500	5000900	Internal Server Error
504	5040900	Timeout

curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-account-unbinding

Request



```
1  -H 'CHANNEL-ID': '95221'
2  -H 'X-PARTNER-ID': '61123'
3  -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
4  -d '
5  {
6    "merchantId": "61123",
7    "additionalInfo": {
8      "xcold": "a6fe3266cafd4cddb3d77e1a9855634"
9    }
10 }
```

curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/registration-account-unbinding

Response



```
1  {
2    "responseCode": "2000900",
3    "responseMessage": "Successful",
4    "referenceNo": "37f89370b5034db0a283130c231dd27b",
5    "unlinkResult": "success",
6    "additionalInfo": {
7      "xcold": "a6fe3266cafd4cddb3d77e1a9855634"
8    }
9  }
```

4. SNAP OneKlik Direct Debit Payment

This service is used to pre-processing OneKlik Registration by Generating OneKlik Registration Web Token.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)		Y	Channel's identifier (95221)
X-PARTNER-ID	Header	String(36)		Y	Partner/Merchant Unique ID
X-EXTERNAL-ID	Header	String (36)		Y	Reference Number from Partner/Merchant
X-IP-ADDRESS	Header	String (15)		Y	Customer IP Address (IPv4 Format)
X-DEVICE-ID	Header	String (400)		Y	Customer Device Info Format: {device-id} {user-agent} device-id : - Android ID (Android) - UUID (iOS) - "WEB" (browser) user-agent : user agent device / browser (max 300 characters)

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
partnerReferenceNo	String (18)		Y		Transaction ID from Partner/Merchant
chargeToken	String (40)		C		Token to validate OTP. Received from Generate OTP service (service code 81). Mandatory if otp field filled
otp	String (6)		N		OTP from SMS to validate transaction (used on different device / on merchant's accord)

merchantId	String (5)	Y		Partner/Merchant Unique ID
payOptionDetails	Array of Object (1)	Y		Payment options used for this payment
payMethod	String (64)	Y		Payment method. Fill with "ONEKLIK"
payOption	String (64)	Y		Payment option. Fill with "ONEKLIK_BCA"
transAmount	Object	Y		Total billed amount from customer (transaction amount + fee amount)
value	String (16.2)	Y	Numeric	TransAmount value
currency	String (3)	Y		TransAmount currency
feeAmount	Object	Y		Fee/Admin Fee for BCA
value	String (16.2)	Y	Numeric	FeeAmount value
currency	String (3)	Y		FeeAmount currency
additionalInfo	Object	Y		
userId	String (18)	Y		Customer Id from Merchant
customerName	String (18)	Y		Customer name from Merchant. If sent more than 18 characters, it will be trimmed to 18 in BCA side
description	String (100)	Y		Transaction description
paymentType	String (7)	Y		Payment Type: FULL = full payment PARTIAL = partial payment

transactionTime	String	Y	DateTime	Transaction date and time from merchant. Format yyyy-MMddTHH:mm:ssTZD format (ISO 8601 format)
xcold	String (32)	Y		Valid OneKlik Identifier when credential successfully registered to BCA
billDetails	Array of Object (5)	Y		Bill distributed to specified details
subBillAmount	String (16.2)	Y	Numeric	Sub Bill amount that will be credited to the specified subCompanyCode
subCompanyCode	String (5)	Y		Sub Company Code. Filled with "00000" if none
transferDetail	Object	C		Mandatory for payment transfer only
beneficiaryName	String(100)	C		Beneficiary Name. Filled for payment transfer only
beneficiaryAccount	String(32)	C		Beneficiary Account. Filled for payment
bankCode	String(10)	C		Bank Code. Filled for payment transfer only

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y		Response code
responseMessage	String (150)		Y		Response message description
referenceNo	String (32)		C		Response reference number from OneKlik appear only on

				success transaction
partnerReferenceNo	String (18)	Y		Transaction ID from merchant
additionalInfo	Object	C		Filled upon transaction with responseCode success
status	String (50)	Y		Transaction status. “SUCCESS” = transaction success “DEVICE IS DIFFERENT” = OTP verification is required
billAmount	String (16.2)	C	Numeric	Total bill amount from merchant. Appear if status = "SUCCESS"
paidAmount	String (16.2)	C	Numeric	Total paid amount from customer. Appear if status = "SUCCESS"
msisdnList	Array of Object	C		List of phone number to send OTP. Appear if status = “DEVICE IS DIFFERENT”
phoneNumber	String (15)	Y		Masked customer phone number
phoneId	String (32)	Y		Phone id
paymentRequestId	String(30)	C		VA Transaction ID. Appear if status = “SUCCESS”

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2005400	Successful
202	2025400	Request In Progress
400	4005400	Bad request
400	4005401	Invalid Field Format {Field}

400	4005402	Invalid Mandatory Field {Field}
401	4015400	Unauthorized. [Reason]
401	4015401	Invalid token (B2B)
403	4035401	Feature Not Allowed
403	4035414	Insufficient Funds
403	4035402	Exceeds Transaction Amount Limit
403	4035412	OTP Lifetime Expired
403	4035415	Transaction Not Permitted. [Reason]
403	4035418	Inactive Card/Account/Customer
404	4045411	Invalid Card/Account/Customer
404	4045408	Invalid Merchant
404	4045406	Need to Request OTP
404	4045412	Invalid Bill/Virtual Account total additionalInfo billDetails subBillAmount does not match transAmount.value
404	4045412	Invalid Bill/Virtual Account adminFee.value does not match
404	4045412	Invalid Bill/Virtual Account transAmount.value below transaction amount limit
404	4045412	Invalid Bill/Virtual Account transAmount.value above transaction amount limit
409	4095400	Cannot use same X-EXTERNAL-ID in same day
409	4095401	Duplicate partnerReferenceNo
429	4295400	Too Many Requests
500	5005400	General Error
500	5005400	Internal Server Error
504	5045400	Timeout


```

1 Without OTP - without Subcompany - without transferDetail - device type WEB
2
3 -H 'CHANNEL-ID': '95221'
4 -H 'X-PARTNER-ID': '61123'
5 -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
6 -H 'X-IP-ADDRESS': '123.123.123.123'
7 -H 'X-DEVICE-ID': 'WEB|Mozilla/5.0 (Windows NT 10.0; Win64; x64)
8 AppleWebKit/537.36 (KHTML, like Gecko) Chrome/95.0.4638.69 Safari/537.36'
9 -d '
10 {
11   "partnerReferenceNo": "2020102900000000001",
12   "merchantId": "61123",
13   "payOptionDetails": [
14     {
15       "payOptionId": "PAYMENT"
16     }
17   ]
18 }
19 '
20
21 curl -X POST -H 'Content-Type: application/json' -d '
22 {
23   "partnerReferenceNo": "2020102900000000001",
24   "merchantId": "61123",
25   "payOptionDetails": [
26     {
27       "payOptionId": "PAYMENT"
28     }
29   ]
30 }
31 '
32
33 curl -X POST -H 'Content-Type: application/json' -d '
34 {
35   "partnerReferenceNo": "2020102900000000001",
36   "merchantId": "61123",
37   "payOptionDetails": [
38     {
39       "payOptionId": "PAYMENT"
40     }
41   ]
42 }
43 '
44
45 curl -X POST -H 'Content-Type: application/json' -d '
46 {
47   "partnerReferenceNo": "2020102900000000001",
48   "merchantId": "61123",
49   "payOptionDetails": [
50     {
51       "payOptionId": "PAYMENT"
52     }
53   ]
54 }
55 '
56
57 curl -X POST -H 'Content-Type: application/json' -d '
58 {
59   "partnerReferenceNo": "2020102900000000001",
60   "merchantId": "61123",
61   "payOptionDetails": [
62     {
63       "payOptionId": "PAYMENT"
64     }
65   ]
66 }
67 '
68
69 curl -X POST -H 'Content-Type: application/json' -d '
70 {
71   "partnerReferenceNo": "2020102900000000001",
72   "merchantId": "61123",
73   "payOptionDetails": [
74     {
75       "payOptionId": "PAYMENT"
76     }
77   ]
78 }
79 '
80
81 curl -X POST -H 'Content-Type: application/json' -d '
82 {
83   "partnerReferenceNo": "2020102900000000001",
84   "merchantId": "61123",
85   "payOptionDetails": [
86     {
87       "payOptionId": "PAYMENT"
88     }
89   ]
90 }
91 '
92
93 curl -X POST -H 'Content-Type: application/json' -d '
94 {
95   "partnerReferenceNo": "2020102900000000001",
96   "merchantId": "61123",
97   "payOptionDetails": [
98     {
99       "payOptionId": "PAYMENT"
100     }
101   ]
102 }
103 '
104
105 curl -X POST -H 'Content-Type: application/json' -d '
106 {
107   "partnerReferenceNo": "2020102900000000001",
108   "merchantId": "61123",
109   "payOptionDetails": [
110     {
111       "payOptionId": "PAYMENT"
112     }
113   ]
114 }
115 '
116
117 curl -X POST -H 'Content-Type: application/json' -d '
118 {
119   "partnerReferenceNo": "2020102900000000001",
120   "merchantId": "61123",
121   "payOptionDetails": [
122     {
123       "payOptionId": "PAYMENT"
124     }
125   ]
126 }
127 '
128
129 curl -X POST -H 'Content-Type: application/json' -d '
130 {
131   "partnerReferenceNo": "2020102900000000001",
132   "merchantId": "61123",
133   "payOptionDetails": [
134     {
135       "payOptionId": "PAYMENT"
136     }
137   ]
138 }
139 '
140
141 curl -X POST -H 'Content-Type: application/json' -d '
142 {
143   "partnerReferenceNo": "2020102900000000001",
144   "merchantId": "61123",
145   "payOptionDetails": [
146     {
147       "payOptionId": "PAYMENT"
148     }
149   ]
150 }
151 '
152
153 curl -X POST -H 'Content-Type: application/json' -d '
154 {
155   "partnerReferenceNo": "2020102900000000001",
156   "merchantId": "61123",
157   "payOptionDetails": [
158     {
159       "payOptionId": "PAYMENT"
160     }
161   ]
162 }
163 '
164
165 curl -X POST -H 'Content-Type: application/json' -d '
166 {
167   "partnerReferenceNo": "2020102900000000001",
168   "merchantId": "61123",
169   "payOptionDetails": [
170     {
171       "payOptionId": "PAYMENT"
172     }
173   ]
174 }
175 '
176
177 curl -X POST -H 'Content-Type: application/json' -d '
178 {
179   "partnerReferenceNo": "2020102900000000001",
180   "merchantId": "61123",
181   "payOptionDetails": [
182     {
183       "payOptionId": "PAYMENT"
184     }
185   ]
186 }
187 '
188
189 curl -X POST -H 'Content-Type: application/json' -d '
190 {
191   "partnerReferenceNo": "2020102900000000001",
192   "merchantId": "61123",
193   "payOptionDetails": [
194     {
195       "payOptionId": "PAYMENT"
196     }
197   ]
198 }
199 '
200
201 curl -X POST -H 'Content-Type: application/json' -d '
202 {
203   "partnerReferenceNo": "2020102900000000001",
204   "merchantId": "61123",
205   "payOptionDetails": [
206     {
207       "payOptionId": "PAYMENT"
208     }
209   ]
210 }
211 '
212
213 curl -X POST -H 'Content-Type: application/json' -d '
214 {
215   "partnerReferenceNo": "2020102900000000001",
216   "merchantId": "61123",
217   "payOptionDetails": [
218     {
219       "payOptionId": "PAYMENT"
220     }
221   ]
222 }
223 '
224
225 curl -X POST -H 'Content-Type: application/json' -d '
226 {
227   "partnerReferenceNo": "2020102900000000001",
228   "merchantId": "61123",
229   "payOptionDetails": [
230     {
231       "payOptionId": "PAYMENT"
232     }
233   ]
234 }
235 '
236
237 curl -X POST -H 'Content-Type: application/json' -d '
238 {
239   "partnerReferenceNo": "2020102900000000001",
240   "merchantId": "61123",
241   "payOptionDetails": [
242     {
243       "payOptionId": "PAYMENT"
244     }
245   ]
246 }
247 '
248
249 curl -X POST -H 'Content-Type: application/json' -d '
250 {
251   "partnerReferenceNo": "2020102900000000001",
252   "merchantId": "61123",
253   "payOptionDetails": [
254     {
255       "payOptionId": "PAYMENT"
256     }
257   ]
258 }
259 '
260
261 curl -X POST -H 'Content-Type: application/json' -d '
262 {
263   "partnerReferenceNo": "2020102900000000001",
264   "merchantId": "61123",
265   "payOptionDetails": [
266     {
267       "payOptionId": "PAYMENT"
268     }
269   ]
270 }
271 '
272
273 curl -X POST -H 'Content-Type: application/json' -d '
274 {
275   "partnerReferenceNo": "2020102900000000001",
276   "merchantId": "61123",
277   "payOptionDetails": [
278     {
279       "payOptionId": "PAYMENT"
280     }
281   ]
282 }
283 '
284
285 curl -X POST -H 'Content-Type: application/json' -d '
286 {
287   "partnerReferenceNo": "2020102900000000001",
288   "merchantId": "61123",
289   "payOptionDetails": [
290     {
291       "payOptionId": "PAYMENT"
292     }
293   ]
294 }
295 '
296
297 curl -X POST -H 'Content-Type: application/json' -d '
298 {
299   "partnerReferenceNo": "2020102900000000001",
300   "merchantId": "61123",
301   "payOptionDetails": [
302     {
303       "payOptionId": "PAYMENT"
304     }
305   ]
306 }
307 '
308
309 curl -X POST -H 'Content-Type: application/json' -d '
310 {
311   "partnerReferenceNo": "2020102900000000001",
312   "merchantId": "61123",
313   "payOptionDetails": [
314     {
315       "payOptionId": "PAYMENT"
316     }
317   ]
318 }
319 '
320
321 curl -X POST -H 'Content-Type: application/json' -d '
322 {
323   "partnerReferenceNo": "2020102900000000001",
324   "merchantId": "61123",
325   "payOptionDetails": [
326     {
327       "payOptionId": "PAYMENT"
328     }
329   ]
330 }
331 '
332
333 curl -X POST -H 'Content-Type: application/json' -d '
334 {
335   "partnerReferenceNo": "2020102900000000001",
336   "merchantId": "61123",
337   "payOptionDetails": [
338     {
339       "payOptionId": "PAYMENT"
340     }
341   ]
342 }
343 '
344
345 curl -X POST -H 'Content-Type: application/json' -d '
346 {
347   "partnerReferenceNo": "2020102900000000001",
348   "merchantId": "61123",
349   "payOptionDetails": [
350     {
351       "payOptionId": "PAYMENT"
352     }
353   ]
354 }
355 '
356
357 curl -X POST -H 'Content-Type: application/json' -d '
358 {
359   "partnerReferenceNo": "2020102900000000001",
360   "merchantId": "61123",
361   "payOptionDetails": [
362     {
363       "payOptionId": "PAYMENT"
364     }
365   ]
366 }
367 '
368
369 curl -X POST -H 'Content-Type: application/json' -d '
370 {
371   "partnerReferenceNo": "2020102900000000001",
372   "merchantId": "61123",
373   "payOptionDetails": [
374     {
375       "payOptionId": "PAYMENT"
376     }
377   ]
378 }
379 '
380
381 curl -
```

```

1  {
2    "responseCode": "2005400",
3    "responseMessage": "Successful",
4    "referenceNo": "37f89370b5034db0a283130c231dd27b",
5    "partnerReferenceNo": "202010290000000001",
6    "additionalInfo": {
7      "status": "SUCCESS",
8      "billAmount": "100000.00",
9      "paidAmount": "100000.00"
10     "paymentRequestId": "202409250226156100100921955639"
11   }
12
13
14  DEVICE IS DIFFERENT
15

```

This service is used to inquiry OneKlik transaction status.

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
-------	-------------	-----------	-------------	-----------	-------------

CHANNEL-ID	Header	String(5)	Y	Channel's identifier (95221)
X-PARTNER-ID	Header	String(36)	Y	Partner/Merchant Unique ID
X-EXTERNAL-ID	Header	String (36)	Y	Reference Number from Partner/Merchant

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
originalPartnerReferenceNo	String (18)		Y	Alphanumeric	Transaction ID from Partner/ Merchant
serviceCode	String (2)		Y	Numeric	Original transaction service code. Fill with "54"
merchantId	String (5)		C	Numeric	Merchant unique ID. Mandatory for IT Gateway integration only

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y		Response code
responseMessage	String (150)		Y		Response message description
originalReferenceNo	String (32)		C		Original Response reference number from OneKlik. Filled if response success
originalPartnerReferenceNo	String (18)		Y		Transaction ID from merchant
serviceCode	String		Y		Original transaction

	(2)			service code. Filled with "54" (Direct Debit OneKlik)
latestTransactionStatus	String (2)	C	Numeric	00 - Success 01 - Initiated 02 - Paying 06 - Failed 07 - Not found
transAmount	Object	C		Total billed amount from customer (transaction amount + fee amount)
value	String (16.2)	Y	Numeric	TransAmount value
currency	String (3)	Y		TransAmount currency
feeAmount	Object	C		Fee/Admin Fee for BCA
value	String (16.2)	Y	Numeric	FeeAmount value
currency	String (3)	Y		FeeAmount currency
paidTime	String	C	DateTime	Timestamp when the payment done. Sent in yyyy-MMddTHH:mm:ssTZD format (ISO 8601 format)
additionalInfo	Object	C		Filled upon transaction with responseCode success
paidAmount	String (16.2)	C	Numeric	Total paid amount from customer.
isTimeout	String (1)	C	Y"/"N"	Indicates if status 06 is Timeout or not
chargeToken	String (32)	C		Charge token after Generate OTP for status 01

paymentRequestId	String (30)	C	VA Transaction ID. Appear if latestTransactionStatus = 00
------------------	----------------	---	--

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2005500	Successful
400	4005500	Bad request
400	4005501	Invalid Field Format {Field}
400	4005502	Invalid Mandatory Field {Field}
401	4015501	Invalid token (B2B)
401	4015500	Unauthorized. [Reason]
403	4035501	Feature Not Allowed
403	4035518	Inactive Card/Account/Customer
404	4045511	Invalid Card/Account/Customer
404	4045508	Invalid Merchant
409	4095500	Cannot Use Same X-EXTERNAL-ID in same day
500	5005500	General Error
500	5005500	Internal Server Error
504	5045500	Timeout

```
curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/debit/status
```

Request



```
1 -H 'CHANNEL-ID':'95221'
2 -H 'X-PARTNER-ID': '61123'
3 -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
4 -d '
5 {
6   "originalPartnerReferenceNo": "202010290000000001",
7   "serviceCode": "54",
8   "merchantId": "61123"
9 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/debit/status
```

Response



```
1 {
2   "responseCode": "2005500",
3   "responseMessage": "Successful",
4   "originalReferenceNo": "37f89370b5034db0a283130c231dd27b",
5   "originalPartnerReferenceNo": "202010290000000001",
6   "serviceCode": "54",
7   "latestTransactionStatus": "00",
8   "transAmount": {
9     "value": "100000.00",
10    "currency": "IDR"
11  },
12  "feeAmount": {
13    "value": "1000.00",
14    "currency": "IDR"
15  },
16 }
```

6. SNAP OneKlik Inquiry OTP

This service is used to inquiry list of phone numbers that can be used to send OTP.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)		Y	Channel's identifier (95221)
X-PARTNER-ID	Header	String(36)		Y	Partner/Merchant Unique ID

X-EXTERNAL-ID	Header	String (36)	Y	Reference Number from Partner/Merchant
---------------	--------	-------------	---	--

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
merchantId	String (5)		Y		Partner/Merchant Unique ID
additionalInfo	Object		Y		
xcold	String (32)		Y		Valid OneKlik Identifier when credential successfully registered to BCA
userId	String (18)		Y		Customer Id from Merchant

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y		Response code
responseMessage	String (150)		Y		Response message description
additionalInfo	Object		C		Filled upon transaction with responseCode success
msisdnList	Array of Object		Y		List of phone number to send OTP.
phoneNumber	String (15)		Y		Masked customer phone number
phoneId	String (32)		Y		Phone id

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
-----------	------------	---------------

200	2008500	Successful
400	4008500	Bad request
400	4008501	Invalid Field Format {Field}
400	4008502	Invalid Mandatory Field {Field}
401	4018501	Invalid token (B2B)
401	4018500	Unauthorized. [Reason]
403	4038501	Feature Not Allowed
403	4038518	Inactive Card/Account/Customer
404	4048511	Invalid Card/Account/Customer
500	5008500	General Error
500	5008500	Internal Server Error
504	5048500	Timeout

curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/payment/inquiry-phone-number

Request



```
1  -H 'CHANNEL-ID': '95221'
2  -H 'X-PARTNER-ID': '61123'
3  -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
4  -d '
5  {
6    "merchantId": "61123",
7    "additionalInfo": {
8      "xcold": "a6fe3266cafd4cddbe3d77e1a9855634",
9      "userId": "customer01"
10   }
11  }'
```

```
curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/payment/inquiry-phone-number
```

Response



```
1  {
2    "responseCode": "2008500",
3    "responseMessage": "Successful",
4    "additionalInfo": {
5      "msisdnList": [
6        {
7          "phoneld": "b5da903138c748a38264cea0424a191e",
8          "phoneNumber": "0812XXXXXX29"
9        },
10       {
11         "phoneld": "2648cd3b308d4037bf4a3e75cc8988c9",
12         "phoneNumber": "0817XXXXXX55"
13       }
14     ]
15   }
```

7. SNAP OneKlik Notify Registration/Delete

This service is used to inquiry list of phone numbers that can be used to send OTP.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Format	Mandatory	Description
CHANNEL-ID	Header	String(5)	Numeric	Y	Channel's identifier
X-PARTNER-ID	Header	String(32)	Alphanumeric	Y	BCA Unique ID
X-EXTERNAL-ID	Header	String (32)	Alphanumeric	Y	Reference Number from BCA

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
additionalInfo	Object		Y		
requestId	String (32)		C	Alphanumeric	Request ID used when registering account. Only show up when notifying

activation data				
xcold	String (32)	Y	Alphanumeric	Valid OneKlik Identifier when credential successfully registered to BCA.
credentialType	String (2)	C	Alphanumeric	Credential type. DC = Debit card CC = Credit card
credentialNumber	String (16)	C	Alphanumeric	Customer credential number (masked)
maxLimit	String (9)	C	Numeric	OneKlik max daily limit registered
userId	String (18)	Y	Alphanumeric	Customer id from merchant
createdDate	String	Y	DateTime	Created / Deleted date. Format: ISO-8601
status	String (3)	Y	Alphanumeric	OneKlik Account Notification Status ACT = Activated DEL = Deleted
merchantId	String (5)	Y	Numeric	Merchant Unique ID

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y	Numeric	Response code
responseMessage	String (150)		Y	Alphanumeric	Response message description
referenceNo	String (32)		C	Alphanumeric	Response reference from copartner. Filled if the response was success
additionalInfo	Object		C		Filled upon transaction with responseCode success

xcold	String (32)	Y	Alphanumeric	XCO ID
responseWs	String (16)	Y	Alphanumeric	Response: 0 = Success 1 = Failed

POST https://copartners.com/oneklik/v2.0/notification

Request



```
1 Request (Activation Notification)
2
3 -H 'CHANNEL-ID': '95221'
4 -H 'X-PARTNER-ID': '61123'
5 -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
6 -d '{
7   "additionalInfo": {
8     "requestd": "2c909de773e578f80173e600b7950018",
9     "xcold": "2c909de773e578f80173e600b7950019",
10    "createdDate": "2022-01-03T01:02:03+07:00",
11    "credentialNumber": "*****1234",
12    "credentialType": "DC",
13    "maxLimit": "100000",
14    "userId": "customer01",
15  }
```

POST https://copartners.com/oneklik/v2.0/notification

Response



```
1 Response (Success)
2
3 {
4   "responseCode": "2008600",
5   "responseMessage": "Successful",
6   "referenceNo": "37f89370b5034db0a283130c231dd27b",
7   "additionalInfo": {
8     "xcold": "2c90c800702d1234017033ab9a060003",
9     "responseWs": "0"
10  }
11 }
12
13 Response (Failed)
14
15 -
```

8. SNAP OneKlik OTP

This service is used to generate and send OTP to customer phone to authorize payment.

This feature is not yet available to be accessed via Sandbox

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)		Y	Channel's identifier (95221)
X-PARTNER-ID	Header	String(36)		Y	Partner/Merchant Unique ID
X-EXTERNAL-ID	Header	String (36)		Y	Reference Number from Partner/Merchant

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
journeyId	String (32)		Y		Journey Identifier. Must be equal with X-EXTERNAL-ID header
bankCardToken	String (32)		Y		Card Token for Payment. Fill with XCROID
merchantId	String (5)		Y		Partner/Merchant Unique ID
partnerReferenceNo	String (18)		Y		Transaction ID from Partner/ Merchant
trxDateTime	String		Y	DateTime	Transaction date and time from merchant. Format yyyy-MMddTHH:mm:ssTZD format (ISO 8601 format)
additionalInfo	Object		Y		
userId	String (18)		Y		Customer Id from Merchant
transAmount	Object		Y		Total billed amount from customer (transaction

				amount + fee amount)
value	String (16.2)	Y	Numeric	TransAmount value
currency	String (3)	Y		TransAmount currency
phoneId	String (32)	Y		Phone id

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)		Y		Response code
responseMessage	String (150)		Y		Response message description
chargeToken	String (32)		Y		String code for OTP verification. Sent when response code success / timeout
additionalInfo	Object		C		Filled upon transaction with responseCode success
xcold	String (32)		Y		Valid Identifier when credential successfully registered to BCA
phoneId	String (32)		Y		Phone id
merchantId	String (5)		Y		Partner/Merchant Unique ID

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message
200	2008100	Successful
400	4008100	Bad request
400	4008101	Invalid Field Format {Field}

400	4008102	Invalid Mandatory Field {Field}
401	4018101	Invalid token (B2B)
401	4018100	Unauthorized. [Reason]
403	4038101	Feature Not Allowed
403	4038118	Inactive Card/Account/Customer
404	4048111	Invalid Card/Account/Customer
404	4048108	Invalid Merchant
429	4298100	Too Many Requests
500	5005100	General Error
500	5008500	Internal Server Error
504	5048500	Timeout

curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/otp

Request



```
1  -H 'CHANNEL-ID': '95221'
2  -H 'X-PARTNER-ID': '61123'
3  -H 'X-EXTERNAL-ID': 'ef343939477c4f19b01c7600ca487bc8'
4  -d '
5  {
6    "journeyId": "ef343939477c4f19b01c7600ca487bc8",
7    "bankCardToken": "a6fe3266cafd4cddbe3d77e1a9855634",
8    "merchantId": "61123",
9    "partnerReferenceNo": "202010290000000001",
10   "trxDateTime": "2020-10-29T00:00:01+07:00",
11   "additionalInfo": {
12     "userId": "customer01",
13     "transAmount": {
14       "value": "100000.00",
15       "currency": "IDR"
16     }
17   }
18 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/oneklik/v1.0/otp
```

Response



```
1  SUCCESS
2
3  {
4    "responseCode": "2008100",
5    "responseMessage": "Successful",
6    "chargeToken": "1a6418f60dad46b9bdb2216d1a641186",
7    "additionalInfo": {
8      "xcolId": "a6fe3266cafd4cddbe3d77e1a9855634",
9      "phonelId": "b5da903138c748a38264cea0424a191e",
10     "merchantId": "61123"
11   }
12 }
13
14  TIMEOUT
--
```

Valuta Asing

1. DealFX

Application is used for the customer side.

This service will process the transaction, as an orchestrator this service perform multiple function including account validation (cin and balance), checking limit 25k, reserve limit, and settlement, and recording.

Your request must contain following information:

Note :

This feature is not yet available to be accessed via Sandbox

Additional Headers and URI Params

Field	Params Type	Data Type	Format	Mandatory	Description
CHANNEL-ID	Header	String(5)	Numeric	Y	Channel's identifier
X-PARTNER ID	Header	String (32)	Alphanumeric	Y	Unique identifier for each request.
X-EXTERNAL ID	Header	String (32)	Alphanumeric	Y	Numeric string. Reference number should be unique in the same day.

ID must comply with format :
Client ID (first 5
char)+YYYYMMDD+0000000
(Sequence). Must be unique
throughout the day

Request:

Field	Data Type	Mandatory	Format	Description
sourceDealId	String (17)	Y	Alphanumeric	Id from channel/client, Format : Only Number
identityTypeLabel	String (1)	Y	Alphanumeric	Identity type (1= norek, 5=npwp)
identityNumber	String (20)	Y	Alphanumeric	Identity number based on identity_type_label (no ktp, no rek, no npwp)
amount1	Number (13.2)	Y	Numeric	Currency Pair : CCY1/CCY2 -> Amount CCY1
amount2	Number (13.2)	Y	Numeric	Currency Pair : CCY1/CCY2 -> Amount CCY2
fxRate	Number (11.4)	Y	Numeric	Rate can be obtain from RateFX or from a self-maintained rate source
transactionType	String (1)	Y	Alphanumeric	Buy or Sell (Customer Side)
dealPurposeId	String (2)	Y	Alphanumeric	Deal Purpose
customerName	String (50)	Y	Alphanumeric	Customer Name Rekening Debit
branchCode	Number (4)	Y	Numeric	Branch Code : Jvalas – Counterparty branch, Others – Branch Code Rekening Debit
currencyPair	String (7)	Y	Alphanumeric	Currency pair, example : USD/IDR, SGD/IDR

documentCodeId	String (3)	Y	Alphanumeric	Document code id
documentDescription	String (100)	N	Alphanumeric	Document description
npwp	String (15)	N	Alphanumeric	Npwp
counterpartyShortName	String (10)	Y	Alphanumeric	Counterparty shortname
Typology	String (7)	Y	Alphanumeric	Typology
userShortName	String (20)	Y	Alphanumeric	User shortname
tradeTime	String (6)	Y	Alphanumeric	Trade Time, Format: “hh24mmss”
tradeDate	String (8)	Y	Alphanumeric	Trade Date, Format: “yyyyMMdd”
maturityDate	String (8)	Y	Alphanumeric	Maturity Date, Format: “yyyyMMdd”
Disclaimer	String (1)	Y	Alphanumeric	Disclaimer (Y/N)
specialTransaction	String (2)	Y	Alphanumeric	LCS Transaction status (00/01) – put “01” for lcs transaction
documentFlag	String (1)	Y	Alphanumeric	Document Flag (Y/N) Put Y if enclose document underlying
underlyingDocuments	List Object	N	List Object	List of Underlying Documents
underlyingDocuments	Object	N	Object	Underlying Document Details
Id	Numb er	N	Numeric	Document Id

documentNumber	String (20)	N	Alphanumeric	Document Number
institutionNumber	String (30)	N	Alphanumeric	Institution Name
documentDate	String (8)	N	Alphanumeric	Document Date from SUD, Format: “yyyyMMdd”
linkAmount	Number	N	Numeric	Amount that want to be used
sourceAccount	String (10)	Y	Alphanumeric	Source account
destinationAccount	String (10)	Y	Alphanumeric	Destination account
cin	String (11)	Y	Alphanumeric	CIN
settlementOption	String (1)	Y	Alphanumeric	Settlement option A/M : Auto/Manual
equivalentMarginAmountIdr	Number	N	Numeric	Equivalent margin amount idr
equivalentMarginCurrency	Number	N	Numeric	Equivalent margin currency
customerPic	String (50)	N	Alphanumeric	Customer pic
mrrType	String (50)	N	Alphanumeric	Mrr type
riskCurrency	String (50)	N	Alphanumeric	Risk currency
riskAmount	Number	N	Numeric	Risk amount

sourceAction	String (50)	N	Alphanumeric	Source action
eventReason	String (500)	N	Alphanumeric	Event reason
fixingParent	String (50)	N	Alphanumeric	Fixing parent
dealStatus	String (20)	N	Alphanumeric	Deal status
tradedCurrency	String (50)	Y	Alphanumeric	Traded currency
refSpot	Numb er	Y	Numeric	Ref spot
netSpot	Numb er	Y	Numeric	Net spot
forward	Numb er	Y	Numeric	Forward
clientSwapNearLeg	Numb er	Y	Numeric	Client swap near leg
internalSwapFarLeg	Numb er	Y	Numeric	Internal swap near leg
clientSwapFarLeg	Numb er	Y	Numeric	Client swap far leg
internalSwapFarLeg	Numb er	Y	Numeric	Internal swap far leg
isAggregate	String (1)	Y	Alphanumeric	Is aggregate
captureDate	String (15)	Y	Alphanumeric	Capture date, Format: “yyyyMMdd hh24mmss”

amount1Leg2	Number	N	Numeric	Amount 1 far leg for swap transaction
amount2Leg2	Number	N	Numeric	Amount 2 far leg for swap transaction
rate2Leg2	Number	N	Numeric	Rate far leg for swap transaction
transactionCode	String (3)	Y	Alphanumeric	Transaction code
userId	String (8)	Y	Alphanumeric	User Journal Id
wsid	String (5)	Y	Alphanumeric	WSID
comments	String (36)	N	Alphanumeric	Comments
capturedAmount	Number	Y	Numeric	Captured amount
valueDate	String (15)	Y	Alphanumeric	Value date, Format: “yyyyMMdd hh24mmss”
sessionId	String (4000)	Y	Alphanumeric	Session Id from RateFX
additionalData	String (500)	N	Alphanumeric	Additional Data
settlementType	String (15)	Y	Alphanumeric	Settlement Type

Response

Field	Data Type	Mandatory	Format	Description
responseCode	String (7)	Y	Alphanumeric	Response code from SUD. If responseCode = 00 then Success else Failed.

responseMessage	String (150)	Y	Alphanumeric	Response message. Description of response code
additionalInfo	Object			
requestId	String (20)	Y	Alphanumeric	GeneDeald request id from APIFX
data	Object			
mssId	String	Y	Alphanumeric	Mss Id from DealFX
message	String	Y	Alphanumeric	Message from DealFX
Status	String	Y	Alphanumeric	Status from DealFX

Error

HTTP Code	Error Code	Error Message (Indonesian)
200	200FX00	Successful
202	202FX00	Request In Progress
400	400FX00	Bad request
400	400FX00	invalid timestamp format [X-TIMESTAMP]
400	400FX02	Invalid mandatory field [Field]
401	401FX00	Unauthorized. [Reason]
401	401FX01	Invalid token (B2B)
403	403FX14	Insufficient Funds
403	403FX15	Transaction Not Permitted (Reason)
403	403FX18	Inactive Card/Account/Customer
403	403FX23	Account Limit Exceed
403	403FX00	Transaction Expired
403	403FX01	Feature not allowed
404	404FX11	Invalid Card/Account/Customer(info)/Virtual Account
404	404FX01	Transaction Not Found
404	404FX11	Invalid Card/Account/Customer (info)/Virtual Account

409	409FX01	Duplicate partner Reference No
500	500FX00	General error
500	500FX01	Internal Server Error
500	500FX02	External Server Error
504	504FX00	Timeout

curl -X POST <https://sandbox.bca.co.id/openapi/v1.0/deal/transaction/manual-rate>

Request



```
1  -H 'CHANNEL-ID': 'API'
2  -H 'X-PARTNER-ID': 'F363F47C90C964EDDD4226DE3678C50F'
3  -H 'X-EXTERNAL-ID': 'F363F080820220000003'
4  -d {
5    "sourceDealId": "202205200193",
6    "amount1": 1.1,
7    "amount2": 14495.1,
8    "capturedAmount": "1",
9    "transactionType": "B",
10   "tradeDate": "20190416",
11   "tradeTime": "140202",
12   "valueDate": "20220520 185335",
13   "maturityDate": "20220320",
14   "captureDate": "20220520 185335",
--  .. .. .. .. ..
```

curl -X POST <https://sandbox.bca.co.id/openapi/v1.0/deal/transaction/manual-rate>

Response



```
1  {
2    "responseCode": "200FX00",
3    "responseMessage": "Successful",
4    "additionalInfo": {
5      "requestId": "bea4fdb359aa1509",
6      "data": {
7        "mssId": null,
8        "message": "success",
9        "status": "success"
10     }
11   }
12 }
13 GENERAL ERROR
14 {
--  .. .. .. .. ..
```

2. Info Kurs

Using API Info Kurs, by inputting the currency pair and rate type that you want to inquire you will get the rate detail such as buy rate, sell rate, mid rate, and last update.

This feature is not yet available to be accessed via Sandbox

Your request must contain following information:

Additional Headers:

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	BCA Channel identifier. Use (95057).
X-PARTNER-ID	Header	String(32)	Max	Y	Authorized Client Identifier for Kurs TR p
X-EXTERNAL-ID	Header	String(32)	Max	Y	Unique identifier for each request. ID must comply with format : X-PARTNER-ID (First 5 char)+YYYYMMDD+0000000000000000 Must be unique throughout the day.

Payload:

Field	Data Type	Length Type	Mandatory	Description
rate	Array		Y	Rate type for inquiry rate. List rate : ERATE, BC06, TR06.
currency	Array		Y	Currency pair for inquiry rate. List Currency

List Currency:

Here is the list of currency for each rate.

ERATE	TR06	BC06
USDIDR	USDIDR	USDIDR
SGDIDR	SGDIDR	AUDIDR
HKDIDR	HKDIDR	CNYIDR

CHFIDR	CHFIDR	EURIDR
GBPIDR	GBPIDR	GBPIDR
AUDIDR	AUDIDR	HKDIDR
JPYIDR	JPYIDR	JPYIDR
SEKIDR	SEKIDR	SGDIDR
DKKIDR	DKKIDR	CHFIDR
CADIDR	CADIDR	SEKIDR
EURIDR	EURIDR	DKKIDR
SARIDR	SARIDR	CADIDR
NZDIDR	NZDIDR	SARIDR
CNHIDR	CNHIDR	NZDIDR
CNYIDR	CNYIDR	THBIDR
MYRIDR	MYRIDR	KRWIDR
THBIDR	THBIDR	TWDIDR
		PHPIDR
		BNDIDR
		NOKIDR

Result of the request will contains following information:

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code.
responseMessage	String (150)	Max	Y	Alphanumeric	Response description.
additionalInfo	Object				

requestId	String (36)	Fixed	Y	Alphanumeric	Transaction status (success or failed).
data	Object		Y		
rates	Array of Object		Y		
rate	String (10)	Max	Y	Alphanumeric	Rate type.
rateDetail	Array of Object		Y		
mid	Number (13.2)	Max	Y	Numeric	Mid price.
currency	String (6)	Fixed	Y	Alphabet	Currency.
buy	Number (13.2)	Max	Y	Numeric	Buy/Bid price.
sell	Number (13.2)	Max	Y	Numeric	Sell/Ask Price.
lastUpdate	String (25)	Fixed	Y	Date	Last update date. Format ISO 8601: yyyy-MM-ddThh:mm:ss+GMT

Error List

Here is the list of currency for each rate.

HTTP Code	Error Code	Error Message	Condition
400	400FX00	Bad request	General request failed error.
400	400FX01	Invalid Field Format {Field}	The data you entered does not match the format requirements.
400	400FX02	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled.
401	401FX00	Unauthorized. [Reason]	Invalid Signature/Unknown Client/ Connection Not Allowed/CIN Is Not Allowed.
401	401FX01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.

403	403FX01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
403	403FX15	Transaction Not Permitted. [Currency Pair Does Not Exist In rate]	Currency pair does not exist in rate.
403	403FX15	Transaction Not Permitted. [X-EXTERNAL-ID Date Value Invalid]	X-EXTERNAL-ID date value invalid.
403	403FX15	Transaction not permitted. [Currency pair is currently not available for transaction]	Currency pair is not available for transactions.
403	403FX15	Transaction not permitted. [One of the currency pair is currently not available for transaction]	One of the currency pairs is not available for transactions.
409	409FX00	Conflict	X-EXTERNAL-ID duplicate.
429	429FX00	Too Many Requests	Maximum transaction limit exceeded.
500	500FX00	General Error	Wrong request field input.
500	500FX01	Internal Server Error	Unknown internal server failure, please retry the process again.
504	504FX00	Timeout	Your transaction timeout.

curl -X POST https://sandbox.bca.co.id/openapi/v1.0/info-kurs

Request



```
1 -H 'Authorization:Bearer iNrWtmeHe7t3h16x4i6o1kV9yj575H77iB9daG3kKXcE7MOHU2ubaS'
2 -H 'X-TIMESTAMP:2024-05-06T14:48:25+07:00'
3 -H 'X-SIGNATURE:HTcmQDWBXwBvzkIPCYYxOvV+rzFjEEgpnMBP28Jydfi+HMJZsmek70Ix7VDibQbAvesv
4 -H 'Content-Type:application/json'
5 -H 'CHANNEL-ID:95057'
6 -H 'X-PARTNER-ID:54271AE2C2D1691B68F67F6AECBFC209'
7 -H 'X-EXTERNAL-ID:54271202401050000000000000000000' -d '
8 {
9   "rate":[
10     "ERATE"
11   ],
12   "currency":[
13     "AUDIDR",
14     "AUDIDR"
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/info-kurs
```

Response



```
1  SUCCESS
2
3  -H 'Content-type:application/json'
4  -H 'X-TIMESTAMP:2024-05-15T14:48:30+07:00'
5  {
6    "responseCode": "200FX00",
7    "responseMessage": "Successful",
8    "additionalInfo": {
9      "requestId": "33b47293-201d-4478-acc5-8b7ee90de265",
10     "data": {
11       "rates": [
12         {
13           "rate": "ERATE",
14           "rateDetail": [
15             -
```

3. Inquiry Deal

API Inquiry Deal is used for checking the status of transaction that has been enacted previously. The status includes “Success”, “Failed”, and “Pending”.

This feature is not yet available to be accessed via Sandbox

Your request must contain following information:

Additional Headers and URI Params

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	BCA Channel identifier. Use (95057).
X-PARTNER-ID	Header	String(32)	Max	Y	Authorized Client Identifier for Kurs TR p
X-EXTERNAL-ID	Header	String(32)	Max	Y	Unique identifier for each request. ID must comply with format : X-PARTNER-ID (First 5 char)+YYYYMMDD+0000000000000000 Must be unique throughout the day.

Payload:

Field	Data Type	Length Type	Mandatory	Format	Description
-------	-----------	-------------	-----------	--------	-------------

sourceDealId	String (17)	Max	N	Numeric	Deal Id to inquire.
--------------	-------------	-----	---	---------	---------------------

Response:

Field	Data Type	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	-	Response code
responseMessage	String (150)	Max	Y	-	Response description
additionalInfo	Object				
requestId	String (16)	Fixed	Y	Alphanumeric	Generate req ID from API FX.
data	Object				
mssId	Number (21)	Fixed	Y	Numeric	mss ID.
					Success inquiry status.
status	String (100)	Max	Y	Alphanumeric	Status list: Success, Failed, Pending

Error List

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	400FX00	Bad request	General request failed error.
400	400FX01	Invalid Field Format {Field}	The data you entered does not match the format requirements.
400	400FX02	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled.
401	401FX00	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.
401	401FX01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.

403	403FX01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
409	409FX00	Conflict	X-EXTERNAL-ID duplicate.
429	429FX00	Too Many Requests	Maximum transaction limit exceeded.
500	500FX00	General Error	Wrong request field input.
500	500FX01	Internal Server Error	Unknown internal server failure, please retry the process again.
504	504FX00	Timeout	Your transaction timeout.

curl -X POST https://sandbox.bca.co.id/openapi/v1.0/inquiry-deal

Request



```
1  -H 'Authorization:Bearer iNrWtmeHe7t3h16x4i6o1kV9yj575H77iB9daG3kKXcE7MOHU2ubaS'
2  -H 'X-TIMESTAMP:2024-05-06T14:48:25+07:00'
3  -H 'X-
4  SIGNATURE:HTcmQDWBXwBvzkiPCYYxOvV+rzFjEEgpnMBP28Jydfi+HMJZsmek70Ix7VDibQbAves
5  -H 'CHANNEL-ID:95057'
6  -H 'X-PARTNER-ID:FAB8639F2F613C416B93B47F6151E461'
7  -H 'X-EXTERNAL-ID:FAB863908202200000001'
8  -d '
9  {
10  "sourceDealId": "11065320218137814"
11  }'
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/inquiry-deal
```

Response



```
1  -H 'Content-type:application/json'
2  -H 'X-TIMESTAMP:2024-05-06T14:48:30+07:00'
3  {
4    "responseCode": "200FX00", "responseMessage": "Successful", "additionalInfo": {
5      "requestId": "cea4fdb359aa1509", "data": {
6        "mssld": 123456789012345678901,
7        "status": "Success"
8      }
9    }
10 }
11 ERROR SAMPLE
12 -H 'Content-type:application/json'
13 -H 'X-TIMESTAMP:2024-05-06T14:48:30+07:00'
14 {
15   "responseCode": "200FX00", "responseMessage": "Successful", "additionalInfo": {
16     "requestId": "cea4fdb359aa1509", "data": {
17       "mssld": 123456789012345678901,
18       "status": "Success"
19     }
20   }
21 }
```

4. RateFX

API RateFX is used to get the rate of exchange for foreign currency transaction. Rate from RateFX will be locked and is valid for the next 90 second.

This feature is not yet available to be accessed via Sandbox

Additional Headers and URI Params

Field	Params Type	Data Type	Length Type	Mandatory	Description
CHANNEL-ID	Header	String(5)	Fixed	Y	BCA Channel identifier. Use (95057).
X-PARTNER-ID	Header	String(32)	Max	Y	Authorized API Client ID.
X-EXTERNAL-ID	Header	String(32)	Max	Y	Unique identifier for each request. ID must comply with format : Client ID (First 5 char)+YYYYMMDD+00000000(Sequence). Must be unique throughout the day.

Payload

Field	DataType	Length Type	Mandatory	Format	Description
cin	String (11)	Fixed	Y	Numeric	CIN Customer for inquiry rate.
currencyPair	String (6)	Fixed	Y	Alphabet	Currency for dealing. Currency list: 1. USDIDR 2. JPYIDR 3. EURIDR 4. THBIDR 5. SGDIDR 6. AUDIDR 7. HKDIDR 8. GBPIDR 9. CNYIDR 10. MYRIDR

Response:

Field	DataType	Length Type	Mandatory	Format	Description
responseCode	String (7)	Fixed	Y	Alphanumeric	Response code
responseMessage	String (150)	Max	Y	Alphanumeric	Response description
additionalInfo	Object				
requestId	String (16)	Fixed	Y	Alphanumeric	API trace id. Used for tracing and troubleshooting generated by kurs TR..
data	Object				
currencyPair	String (6)	Fixed	Y	Alphabet	Currency pair for deal.
buy	Number (7.4)	Max	Y	Numeric	Buy rate
sell	Number (7.4)	Max	Y	Numeric	Sell rate
sessionExpiredTime	String (19)	Max	Y	Date Time	Deal valid period

sessionId	String (512)	Max	Y	Alphanumeric	Session ID for deal.
-----------	-----------------	-----	---	--------------	----------------------

Error List

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message	Condition
400	400FX00	Bad request	General request failed error.
400	400FX01	Invalid Field Format {Field}	The data you entered does not match the format requirements.
400	400FX02	Invalid Mandatory Field {Field}	Mandatory field should be fulfilled.
401	401FX00	Unauthorized. [Reason]	Invalid Signature/Unknown Client/Connection Not Allowed.
401	401FX01	Invalid token (B2B)	Access Token Not Exist/Access Token Expired/Token is Invalid.
403	403FX01	Feature Not Allowed	The feature is not allowed to use. Please make sure you registered this feature in your partnership data.
409	409FX00	Conflict	X-EXTERNAL-ID duplicate.
429	429FX00	Too Many Requests	Maximum transaction limit exceeded.
500	500FX00	General Error	Wrong request field input.
500	500FX01	Internal Server Error	Unknown internal server failure, please retry the process again.
504	504FX00	Timeout	Your transaction timeout.

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/rate-fx
```

Request



```
1  REQUEST
2  -H 'Authorization:Bearer iNrWtmeHe7t3h16x4i6o1kV9yj575H77iB9daG3kKXcE7MOHU2ubaS'
3  -H 'X-TIMESTAMP:2024-05-06T14:48:25+07:00'
4  -H 'X-
SIGNATURE:HTcmQDWBXwBvzkIPCYYxOvV+rzFjEEgpnMBP28Jydfi+HMJZsmek70Ix7VDibQbAves
5  -H 'Content-type:application/json'
6  -H 'CHANNEL-ID:95057'
7  -H 'X-PARTNER-ID:44302678175932178121426447374079'
8  -H 'X-EXTERNAL-ID:4430220240515000000001'
9  -d '
10 {
11   "cin": "12345678901",
12   "currencyPair": "USDIDR"
13 }
```

```
curl -X POST https://sandbox.bca.co.id/openapi/v1.0/rate-fx
```

Response



```
1  RESPONSE
2  -H 'Content-type:application/json'
3  -H 'X-TIMESTAMP:2024-05-15T14:48:30+07:00'
4  {
5    "responseCode": "200FX00",
6    "responseMessage": "Successful",
7    "additionalInfo": {
8      "requestId": "381c7d0ffa882637",
9      "data": {
10        "currencyPair": "USDIDR",
11        "buy": "15780.0000",
12        "sell": "15780",
13        "sessionExpiredTime": "2024/05/15 15:50:00",
14        "sessionId": "OIXe9brOwXkbODSLRQZf0/dSUwY/...
```

Informasi Umum

1. Lokasi ATM BCA

Inquiry ATM information, such as, locate the nearest ATM to user or find by ATM Type, Name, Address or City.

This feature is not yet available to be accessed via Sandbox

Query String Parameters:

Field	DataType	Mandatory	Description
Latitude	String	Y	In format number((-)3.12) Latitude of client location, possible for minus signed value.
Longitude	String	Y	In format number((-)3.12) Longitude of client location, possible for minus signed value.
Count	String	N	Number of branches to search, in Integer. Maximum value = 20.
SearchBy	String	N	Possible values: Address/City/Type/Name
Radius	String	N	Branch distance (in meters) from client location, in Integer. *default = 500
Value	String	N	Value should be filled in : - String; If SearchBy = Address or City or Name - ATM, ANT, or CRM; If SearchBy = Type

Result of the request will contains following information:

Response:

Field	DataType	Description
atm_details	Array of Object	The object that hold information of the ATM.
WSID	String	ATM wsid
Type	String	ATM type eg: ATM Tarik Tunai ATM Non-Tunai ATM Setor Tarik
Name	String	ATM name
Address	String	ATM full address
City	String	ATM city
Country	String	ATM country
Latitude	String	ATM latitude
Longitude	String	ATM longitude
Distance	String	ATM distance from client location in meters

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
404	ESB-07-271	Tidak ada transaksi	No transaction
400	ESB-07-279	Tanggal awal lebih kecil dari tanggal buka rekening	Start date less than account open date
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	parameter input tidak valid	Invalid input parameter
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	ESB-99-009	Field Latitude harus diisi	Missing Mandatory field Latitude
400	ESB-99-009	Field Longitude harus diisi	Missing Mandatory field Longitude
400	ESB-99-039	Isian input field Count tidak valid	Input for field Count not valid
400	ESB-99-040	Tipe isian field Count tidak valid	Input type for field Count not valid
400	ESB-99-040	Tipe isian field Latitude tidak valid	Input type for field Latitude not valid

400	ESB-99-040	Tipe isian field Longitude tidak valid	Input type for field Longitude not valid
400	ESB-99-040	Tipe isian field Radius tidak valid	Input type for field Radius not valid
400	ESB-99-132	Data tidak ditemukan	No Data Found
400	ESB-99-335	Mata uang tidak valid	Invalid CurrencyCode
400	ESB-99-339	Tipe Kurs tidak valid	Invalid RateType
400	ESB-99-392	Nilai SearchBy tidak valid	Invalid SearchBy value
400	ESB-99-460	Panjang input Value tidak valid	Input Value minimal length invalid
500	ESB-99-999	Sistem sedang tidak tersedia	System unavaliabe

GET /general/info-bca/atm?SearchBy= &Latitude=&Longitude=&Value=&Radius=&Count=

Request



- 1 GET /general/info-bca/atm?Latitude=6.1900718&Longitude=106.797190 HTTP/1.1
- 2 Host: sandbox.bca.co.id
- 3 Authorization: Bearer [access_token]
- 4 Content-Type: application/json
- 5 Origin: [yourdomain.com]
- 6 X-BCA-Key: [api_key]
- 7 X-BCA-Timestamp: [timestamp]
- 8 X-BCA-Signature: [signature]

GET /general/info-bca/atm?SearchBy= &Latitude=&Longitude=&Value=&Radius=&Count=

Response



```
1  {
2    "atm_details": [
3      {
4        "WSID": "69715",
5        "Type": "ATM",
6        "Name": "221U-Mayapada Tower 2"
7        "Address": "Jl. Jend. Sudirman Kav.28, Jakarta 12920",
8        "City": "Jakarta Selatan",
9        "Country": "INDONESIA",
10       "Latitude": "-6.2112194",
11       "Longitude": "106.8201026",
12       "Distance": ""8243.97"
13     },
14     {
15       "WSID": "69715"
```

2. Lokasi Cabang BCA

Get information about nearest branch location by distance, address, city or branch type.

Query String Parameters:

Field	Data Type	Mandatory	Description
Latitude	String	Y	In format number((-)3.12) Latitude of client location, possible for minus signed value.
Longitude	String	Y	In format number((-)3.12) Longitude of client location, possible for minus signed value.
Count	String	N	Number of branches to search, in Integer. Maximum value = 20.
Radius	String	N	Branch distance (in meters) from client location, in Integer. *default = 500
SearchBy	String	N	Possible values: Address/City/Type
Value	String	N	If SearchBy = Address or City, value should be filled in : String; If SearchBy = Type, value should be filled with: kcu , kcp, e-branch, weekendbanking

Result of the request will contains following information:

Response:

Field	Data Type	Description
BranchDetails	Array of Object	The object that hold information of the branch.
Type	String	Branch type eg. KCU, KCP
Name	String	Branch name
Address	String	Branch full address
City	String	Branch city
Country	String	Branch country
Latitude	String	Branch latitude
Longitude	String	Branch longitude
Distance	String	Branch distance from client location in meters
E-Branch	String	“Y” if e-branch reservation is available otherwise it will be set to “N”
WeekendBankingOperation	String	The name of the day of weekend, “Saturday”, “Sunday” and “Saturday&Sunday”

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
404	ESB-07-271	Tidak ada transaksi	No transaction
400	ESB-07-279	Tanggal awal lebih kecil dari tanggal buka rekening	Start date less than account open date
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	parameter input tidak valid	Invalid input parameter
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance

504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	ESB-99-009	Field Latitude harus diisi	Missing Mandatory field Latitude
400	ESB-99-009	Field Longitude harus diisi	Missing Mandatory field Longitude
400	ESB-99-039	Isian input field Count tidak valid	Input for field Count not valid
400	ESB-99-040	Tipe isian field Count tidak valid	Input type for field Count not valid
400	ESB-99-040	Tipe isian field Latitude tidak valid	Input type for field Latitude not valid
400	ESB-99-040	Tipe isian field Longitude tidak valid	Input type for field Longitude not valid
400	ESB-99-040	Tipe isian field Radius tidak valid	Input type for field Radius not valid
400	ESB-99-132	Data tidak ditemukan	No Data Found
400	ESB-99-335	Mata uang tidak valid	Invalid CurrencyCode
400	ESB-99-339	Tipe Kurs tidak valid	Invalid RateType
400	ESB-99-392	Nilai SearchBy tidak valid	Invalid SearchBy value
400	ESB-99-460	Panjang input Value tidak valid	Input Value minimal length invalid
500	ESB-99-999	Sistem sedang tidak tersedia	System unavaliabe

GET /general/info-bca/branch

Request



```
1 GET /general/info-bca/branch?Latitude=-6.137235&Longitude=106.824928 HTTP/1.1
2 Host: sandbox.bca.co.id
3 Authorization: Bearer [access_token]
4 Content-Type: application/json
5 Origin: [yourdomain.com]
6 X-BCA-Key: [api_key]
7 X-BCA-Timestamp: [timestamp]
8 X-BCA-Signature: [signature]
```

GET /general/info-bca/branch

Response



```
1  {
2    "BranchDetails": [
3      {
4        "Type": "KCP",
5        "Name": "Mangga Dua Mal",
6        "Address": "Mangga Dua Mal No. RM. 49, Jl. Mangga Dua Raya,,,",
7        "City": "Jakarta Pusat",
8        "Country": "INDONESIA",
9        "Latitude": "-6.137235",
10       "Longitude": "106.824928",
11       "Distance": "0"
12       "E-Branch": "N"
13       "WeekendBankingOperation": "Saturday&Sunday"
14     },
15   ]
16 }
```

Financing

1. Batal Faktur

You can cancel your invoice data which had been sent to BCA using this service, at least 1(one) day before disburse date.

Cut-off time: 08.00 P.M - 04.00 A.M (using UTC+07 Time Zone)

Your Request must contain following information:

Additional Headers

Field	Data Type	Mandatory	Description
ChannelID	String(5)	Y	Channel's identifier. Fill it with "95051".

CredentialID	String(10)	Y	Channel's credential (KlikBCA Bisnis Corporate ID)
--------------	------------	---	--

Request

Field	Data Type	Mandatory	Description
TransactionID	String(20)	Y	Transaction ID unique per request (using UTC+07 Time Zone format). Must be 20 in length
TransactionDate	String(10)	Y	Transaction date. Format: yyyyMM-dd. Must be today's date
ReferenceID	String(30)	Y	Sender's invoice number. Must be same as previous created sender's invoice number.
DistributorCode	String(20)	Y	Distributor Code. Format: Alphanumeric and Special Character
Amount	String(16)	Y	Transfer Amount. Format: Number, 13.2. Must be same as previous created invoice transfer amount
CurrencyCode	String(3)	Y	Currency Code. Format: Alphanumeric
PrincipalCode	String(11)	Y	Principal Code. Must be 11 in length. Format: Numeric
SubPrincipalCode	String(11)	Y	Sub Principal Code. Must be 11 in length. Disbursement to Sub Principal only. Format: Numeric.
DisburseDate	String(10)	Y	Transaction date. Format: yyyy-MM-dd. Must be same as previous created invoice disburse date

Response

Field	DataType	Description
TransactionID	String(20)	Transaction ID unique per request (using UTC+07 Time Zone format). Must be 20 in length
TransactionDate	String(10)	Transaction date. Format: yyyy-MM-dd. Must be today's date
ReferenceID	String(30)	Sender's invoice number. Must be unique
DistributorCode	String(20)	Distributor Code. Format: Alphanumeric and Special Character
Amount	String(16)	Transfer Amount. Format: Number, 13.2
CurrencyCode	String(3)	Currency Code. Format: Alphanumeric

PrincipalCode	String(11)	Principal Code. Must be 11 in length. Format: Numeric
SubPrincipalCode	String(11)	Sub Principal Code. Must be 11 in length. Disbursement to Sub Principal only. Format: Numeric.
DisburseDate	String(10)	Transaction date. Format: yyyy-MM-dd

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-01-005	Data tidak ditemukan	No Data Found
400	ESB-11-005	Kode mata uang tidak valid	Currency not valid
400	ESB-11-038	Prinsipal tidak aktif	Principal is inactive
400	ESB-11-040	Distributor tidak aktif	Distributor is not active
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
504	ESB-14-013	Timeout. Silakan melakukan transaksi kembali	Timeout. Please retry your transaction
400	ESB-14-015	Content Type tidak valid	Invalid Content Type
400	ESB-14-016	Format JSON tidak valid	Invalid JSON format
400	ESB-82-002	Corporate ID tidak valid	Invalid Corporate ID

400	ESB-82-003	TransactionID tidak unik	TransactionID not unique
400	ESB-82-026	Lewat batas waktu cut off	Cut off time is exceeded
400	ESB-99-009	Field (0) harus diisi	Missing mandatory field (0)
400	ESB-99-113	Transaksi ditolak	Transaction rejected
400	ESB-99-128	Panjang field (0) melebihi ketentuan	Field (0) exceed limit
400	ESB-99-284	(0) tidak valid	Invalid (0)
400	ESB-99-524	ReferenceID sudah diproses pada tanggal (entry_date)	ReferenceID already processed by (entry_date)
400	ESB-99-559	Timeout. Silakan melakukan transaksi kembali	Timeout. Please retry your transaction
400	ESB-99-568	SubprincipalCode tidak terdaftar	SubprincipalCode is not registered
400	ESB-99-569	Tidak terdaftar untuk fitur Distributor Financing	Not registered for Distributor Financing features
400	ESB-99-573	TransactionDate harus diisi dengan tanggal hari ini	Transaction Date must be filled with today's date
400	ESB-99-655	Subprinsipal tidak aktif	Subprincipal is inactive

PUT /df/invoice

Request



```
1  PUT df/invoice HTTP/1.1
2  Host: sandbox.bca.co.id
3  Authorization: Bearer [access_token]
4  Content-Type: application/json
5  Origin: [yourdomain.com]
6  X-BCA-Key: [api_key]
7  X-BCA-Timestamp: [timestamp]
8  X-BCA-Signature: [signature]
9  ChannelID: [channelID]
10 CredentialID: [credentialID]
11
12 {
13   "TransactionID": "ABCDEFGHJI0123456789",
14   "TransactionDate": "2018-02-15",
15   "TransactionID": "XXXXXXXXXXXX"
```

PUT /df/invoice

Response



```
1  {
2    "TransactionID" : "ABCDEF GHIJ0123456789",
3    "TransactionDate" : "2018-02-15",
4    "ReferenceID"" : "INV00000001",
5    "DistributorCode" : "ABCDE-12345",
6    "Amount" : "1000000000.00",
7    "CurrencyCode" : "IDR",
8    "PrincipalCode" : "000000000001",
9    "SubPrincipalCode" : "",
10   "DisburseDate" : "2018-02-30"
11 }
```

2. Kirim Faktur

You can send your invoice data to BCA using this service.

Cut-off time: 08.00 P.M - 04.00 A.M (using UTC+07 Time Zone)

Your Request must contain following information:

Additional Headers

Field	Data Type	Mandatory	Description
ChannelID	String(5)	Y	Channel's identifier. Fill it with "95051".
CredentialID	String(10)	Y	Channel's credential (KlikBCA Bisnis Corporate ID)

Payload

Field	Data Type	Mandatory	Description
TransactionID	String(20)	Y	Transaction ID unique per request (using UTC+07 Time Zone format). Must be 20 in length
TransactionDate	String(10)	Y	Transaction date. Format: yyyyMM-dd. Must be today's date
ReferenceID	String(30)	Y	Sender's invoice number. Must be unique
DistributorCode	String(20)	Y	Distributor Code. Format: Alphanumeric and Special Character
Amount	String(16)	Y	Transfer Amount. Format: Number, 13.2
CurrencyCode	String(3)	Y	Currency Code. Format: Alphanumeric

PrincipalCode	String(11)	Y	Principal Code. Must be 11 in length. Format: Numeric
SubPrincipalCode	String(11)	Y	Sub Principal Code. Must be 11 in length. Disbursement to Sub Principal only. Format: Numeric.
DisburseDate	String(10)	Y	Transaction date. Format: yyyyMM-dd

Response

Field	DataType	Description
TransactionID	String(20)	Transaction ID unique per request (using UTC+07 Time Zone format). Must be 20 in length
TransactionDate	String(10)	Transaction date. Format: yyyy-MM-dd. Must be today's date
ReferenceID	String(30)	Sender's invoice number. Must be unique
DistributorCode	String(20)	Distributor Code. Format: Alphanumeric and Special Character
Amount	String(16)	Transfer Amount. Format: Number, 13.2
CurrencyCode	String(3)	Currency Code. Format: Alphanumeric
PrincipalCode	String(11)	Principal Code. Must be 11 in length. Format: Numeric
SubPrincipalCode	String(11)	Sub Principal Code. Must be 11 in length. Disbursement to Sub Principal only. Format: Numeric.
DisburseDate	String(10)	Transaction date. Format: yyyy-MM-dd

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-01-005	Data tidak ditemukan	No Data Found
400	ESB-11-005	Kode mata uang tidak valid	Currency not valid
400	ESB-11-038	Prinsipal tidak aktif	Principal is inactive
400	ESB-11-040	Distributor tidak aktif	Distributor is not active
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request

400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
504	ESB-14-013	Timeout. Silakan melakukan transaksi kembali	Timeout. Please retry your transaction
400	ESB-14-015	Content Type tidak valid	Invalid Content Type
400	ESB-14-016	Format JSON tidak valid	Invalid JSON format
400	ESB-82-002	Corporate ID tidak valid	Invalid Corporate ID
400	ESB-82-003	TransactionID tidak unik	TransactionID not unique
400	ESB-82-026	Lewat batas waktu cut off	Cut off time is exceeded
400	ESB-99-009	Field (0) harus diisi	Missing mandatory field (0)
400	ESB-99-113	Transaksi ditolak	Transaction rejected
400	ESB-99-128	Panjang field (0) melebihi ketentuan	Field (0) exceed limit
400	ESB-99-284	(0) tidak valid	Invalid (0)
400	ESB-99-524	ReferenceID sudah diproses pada tanggal (entry_date)	ReferenceID already processed by (entry_date)
400	ESB-99-559	Timeout. Silakan melakukan transaksi kembali	Timeout. Please retry your transaction
400	ESB-99-568	SubprincipalCode tidak terdaftar	SubprincipalCode is not registered
400	ESB-99-569	Tidak terdaftar untuk fitur Distributor Financing	Not registered for Distributor Financing features

400	ESB-99-573	TransactionDate harus diisi dengan tanggal hari ini	Transaction Date must be filled with today's date
400	ESB-99-655	Subprinsipal tidak aktif	Subprincipal is inactive

POST /df/invoice

Request



```
1 POST df/invoice HTTP/1.1
2 Host: sandbox.bca.co.id
3 Authorization: Bearer [access_token]
4 Content-Type: application/json
5 Origin: [yourdomain.com]
6 X-BCA-Key: [api_key]
7 X-BCA-Timestamp: [timestamp]
8 X-BCA-Signature: [signature]
9 ChannelID: [channelID]
10 CredentialID: [credentialID]
11
12 {
13   "TransactionID" : "ABCDEFGHJIJ0123456789",
14   "TransactionDate" : "2018-02-15",
15   "ReferenceID" : "INV00000001",
16   "DistributorCode" : "ABCDE-12345",
17   "Amount" : "100000000.00",
18   "CurrencyCode" : "IDR",
19   "PrincipalCode" : "000000000001",
20   "SubPrincipalCode" : "",
21   "DisburseDate" : "2018-02-30"
22 }
```

POST /df/invoice

Response



```
1 {
2   "TransactionID" : "ABCDEFGHJIJ0123456789",
3   "TransactionDate" : "2018-02-15",
4   "ReferenceID" : "INV00000001",
5   "DistributorCode" : "ABCDE-12345",
6   "Amount" : "100000000.00",
7   "CurrencyCode" : "IDR",
8   "PrincipalCode" : "000000000001",
9   "SubPrincipalCode" : "",
10  "DisburseDate" : "2018-02-30"
11 }
```

3. Notifikasi Pembayaran Faktur

Service for BCA to send notification of disbursement.

This feature is not yet available to be accessed via Sandbox

Additional Headers

Field	DataType	Mandatory	Description
X-Pass-Signature	String(5)	Y	This is a header field, use to replace the “Pass” field on everybody payload that contains signature. This field occurred on every BCA request to Copartner’s API.

Request

Field	Data Type	Mandatory	Description
TransactionID	String(20)	Y	UUID as unique ID for every request
TransactionDate	String(10)	Y	Transaction date. Format: yyyyMM-dd. Must be today’s date
ReferenceID	String(30)	Y	Invoice number. Must be unique
DistributorCode	String(20)	Y	Distributor Code. Format: Alphanumeric and Special Character
Amount	String(16)	Y	Transfer Amount. Format: Number, 13.2
CurrencyCode	String(3)	Y	Currency Code. Format: Alphanumeric
PrincipalCode	String(11)	Y	Principal Code. Must be 11 in length. Format: Numeric
SubPrincipalCode	String(11)	Y	Sub Principal Code. Format : Numeric
DisburseDate	String(10)	Y	Transaction date. Format: yyyy-MM-dd

Response

Field	DataType	Description
TransactionID	String(20)	Same TransactionID from request. It’s a UUID
TransactionDate	String(10)	Transaction date. Format: yyyy-MM-dd. Must be today’s date
ReferenceID	String(30)	Invoice number. Must be unique
DistributorCode	String(20)	Distributor Code. Format: Alphanumeric and Special Character
Amount	String(16)	Transfer Amount. Format: Number, 13.2
CurrencyCode	String(3)	Currency Code. Format: Alphanumeric
PrincipalCode	String(11)	Principal Code. Must be 11 in length. Format: Numeric

SubPrincipalCode	String(11)	Sub Principal Code. Must be 11 in length. Disbursement to Sub Principal only. Format: Numeric.
DisburseDate	String(10)	Transaction date. Format: yyyy-MM-dd

POST https://www.copartners.com/bca-df/disbursement/notification

Request



```
1 POST https://www.copartners.com/bca-df/disbursement/notification HTTP/1.1
2 X-Pass-Signature: b9125ab10816f6929d214c96ffca77dfd5a1ea13856362b85eeae70155
3
4 {
5   "TransactionID": "65d5dd3474b44c5abbb0ce1cb5ff563f",
6   "TransactionDate": "2018-02-15",
7   "ReferenceID": "INV001923",
8   "PrincipalCode": "000000000001",
9   "SubPrincipalCode": "",
10  "DistributorCode": "ABCDE-12345",
11  "Amount": "100000000.00",
12  "CurrencyCode": "IDR",
13 }
14
```

POST https://www.copartners.com/bca-df/disbursement/notification

Response



```
1 {
2   "TransactionID": "65d5dd3474b44c5abbb0ce1cb5ff563f",
3   "TransactionDate": "2018-02-15",
4   "ReferenceID": "INV001923",
5   "PrincipalCode": "000000000001",
6   "SubPrincipalCode": "000000000001",
7   "DistributorCode": "ABCDE-12345",
8   "Amount": "100000000.00",
9   "CurrencyCode": "IDR",
10 }
```

4. Notifikasi Pembayaran Pinjaman

Service for BCA to send notification of transaction limit update.

This feature is not yet available to be accessed via Sandbox

Additional Headers

Field	DataType	Mandatory	Description
X-Pass-Signature	String(5)	Y	This is a header field, use to replace the “Pass” field on everybody payload that contains signature. This field occurred on every BCA request to Copartner’s API.

Request

Field	Data Type	Mandatory	Description
TransactionID	String(32)	Y	UUID as unique ID for every request
DistributorCode	String(20)	Y	Distributor Code. Format: Alphanumeric and Special Character
PrincipalCode	String(11)	Y	Principal Code. Format: Numeric
Amount	String(16)	Y	Transfer Amount. Minus sign (-) is applied for corrective payment. Format: Number, 13.2.
TransactionDate	String(10)	Y	Transaction date. Format: yyyy-MM-dd

Response

Field	DataType	Description
TransactionID	String(32)	Same TransactionID from request. It’s a UUID
DistributorCode	String(20)	Same Distributor Code from request.

POST https://www.copartners.com/bca-df/txn-limit/notification

Request



```
1 POST https://www.copartners.com/bca-df/txn-limit/notification HTTP/1.1
2 X-Pass-Signature: b9125ab10816f6929d214c96ffca77dfd5a1ea13856362b85eeae70155
3
4 {
5   "TransactionID" : "65d5dd3474b44c5abbb0ce1cb5ff563f",",
6   "PrincipalCode"" : "000000000001",
7   "DistributorCode"" : "ABCDE-12345",
8   "Amount" : "100000000.00",
9   "TransactionDate" : "2018-02-15",
10 }
```

POST https://www.copartners.com/bca-df/txn-limit/notification

Response



```
1 {
2   "TransactionID" : "65d5dd3474b44c5abbb0ce1cb5ff563f",",
3   "DistributorCode" : "ABCDE-12345",
4 }
```

5. Notifikasi Status Fasilitas Kredit

Service for BCA to send notification of transaction limit update.

This feature is not yet available to be accessed via Sandbox

Additional Headers

Field	Data Type	Mandatory	Description
X-Pass-Signature	String(5)	Y	This is a header field, use to replace the “Pass” field on everybody payload that contains signature. This field occurred on every BCA request to Copartner’s API.

Request

Field	Data Type	Mandatory	Description
TransactionID	String(32)	Y	UUID as unique ID for every request

DistributorCode	String(20)	Y	Distributor Code. Format: Alphanumeric and Special Character
PrincipalCode	String(11)	Y	Principal Code. Must be 11 in length. Format: Numeric
StopSupplyFlag	String(1)	Y	0 : Stop (Distributor Non-Aktif/Wanprestasi); 1: Open (Distributor Aktif)
TransactionDate	String(10)	Y	Transaction date. Format: yyyy-MM-dd

Response

Field	DataType	Description
TransactionID	String(32)	Same TransactionID from request. It's a UUID
DistributorCode	String(20)	Same Distributor Code from request.

POST https://www.copartners.com/bca-df/stop-supply/notification

Request



```
1 POST https://www.copartners.com/bca-df/stop-supply/notification HTTP/1.1
2 X-Pass-Signature: b9125ab10816f6929d214c96ffca77dfd5a1ea13856362b85eeae70155
3
4 {
5   "TransactionID" : "65d5dd3474b44c5abbb0ce1cb5ff563f",",
6   "DistributorCode"" : "ABCDE-12345",
7   "PrincipalCode"" : "000000000001",
8   "TransactionDate" : "2018-02-15",
9   "StopSupplyFlag"" : "1",
10 }
```

POST https://www.copartners.com/bca-df/stop-supply/notification

Response



```
1 {
2   "TransactionID" : "65d5dd3474b44c5abbb0ce1cb5ff563f",",
3   "DistributorCode" : "ABCDE-12345",
4 }
```

FIRE

1. Amandemen Kiriman Uang Tunai

Provides service for Amendment “Cash Transfer” to Non account holder. Yout request must contain following information:

Payload

Field	DataType	Mandatory	Description
Authentication			
CorporatelD	String(6)	Y	Agen code used to connect to FIRe system
AccessCode	String(20)	Y	Password that will be read by system for each transaction request
BranchCode	String(8)	Y	FI branch code of API client
UserID	String(12)	Y	User ID
LocalID	String(15)	Y	Branch code from FI sub branch of API client
AmendmentDetails			
SenderDetails			
FirstName	String(35)	Y	Sender's first name
LastName	String(35)	N	Sender's last name
DateOfBirth	String(8)	N	Sender's date of birth. Format : ddmmyyyy
Address1	String(35)	Y	Sender's first address
Address2	String(35)	N	Sender's second address
City	String(18)	Y	Sender's city
StateID	String(2)	N	State ID
PostalCode	String(10)	N	Sender's postal code
CountryID	String(2)	Y	Sender's country initial code. Example : Indonesia =ID
Mobile	String(20)	N	Sender's mobile phone number
IdentificationType	String(2)	N	Sender's identity type
IdentificationNumber	String(24)	N	Sender's identity number
BenficiaryDetails			

Name	String(35)	Y	Beneficiary's name
DateOfBirth	String(8)	N	Beneficiary's date of birth. Format : ddmmyyyy
Address1	String(35)	N	Beneficiary's first address
Address2	String(35)	N	Beneficiary's second address
City	String(35)	N	Beneficiary's city
StateID	String(2)		State ID
PostalCode	String(10)	N	Beneficiary's postal code
CountryID	String(2)	N	Beneficiary's country initial code. Example : Indonesia =ID
Mobile	String(20)	N	Beneficiary's mobile phone number
IdentificationType	String(2)	N	Beneficiary's identity type
IdentificationNumber	String(24)	N	Beneficiary's identity number
NationalityID	String(2)	N	Country initial code of beneficiary's nationality. Example : Indonesia =ID
Occupation	String(30)	N	Beneficiary occupation
TransactionDetails			
Description1	String(35)	N	First Description
Description2	String(35)	N	Second Description
SecretQuestion	String(100)	N	Question
SecretAnswer	String(100)	N	Answer
TransactionDetails			
FormNumber	String(16)	Y	FI Ref

Result of the request will contains following information:

Response

Field	DataType	Mandatory	Description
StatusTransaction	String(4)	Y	ResponseCode and Sub-ResponseCode of transaction

StatusMessage	String(100)	Y	Description of StatusTransaction
SenderDetails			
FirstName	String(35)	N	Sender's first name
LastName	String(35)	N	Sender's last name
DateOfBirth	String(8)	N	Sender's date of birth. Format : ddmmyyyy
Address1	String(35)	N	Sender's first address
Address2	String(35)	N	Sender's second address
City	String(18)	N	Sender's city
StateID	String(2)	N	State ID
PostalCode	String(10)	N	Sender's postal code
CountryID	String(2)	N	Sender's country initial code. Example : Indonesia =ID
Mobile	String(20)	N	Sender's mobile phone number
IdentificationType	String(2)	N	Sender's identity type
IdentificationNumber	String(24)	N	Sender's identity number
BeneficiaryDetails			
Name	String(35)	N	Beneficiary's name
DateOfBirth	String(8)	N	Beneficiary's date of birth. Format : ddmmyyyy
Address1	String(35)	N	Beneficiary's first address
Address2	String(35)	N	Beneficiary's second address
City	String(35)	N	Beneficiary's city
StateID	String(2)	N	State ID
PostalCode	String(10)	N	Beneficiary's postal code
CountryID	String(2)	N	Beneficiary's country initial code. Example : Indonesia =ID
Mobile	String(20)	N	Beneficiary's mobile phone number

IdentificationType	String(2)	N	Beneficiary's identity type. (PP = Passport, ID = Identity, DR = Dr. License)
IdentificationNumber	String(24)	N	Beneficiary's identity number
NationalityID	String(2)	N	Country initial code of beneficiary's nationality. Example : Indonesia =ID
Occupation	String(30)	N	Beneficiary occupation
TransactionDetails			
Description1	String(35)	N	First description
Description2	String(35)	N	Second description
SecretQuestion	String(100)	N	Question
SecretAnswer	String(100)	N	Answer
FormNumber	String(16)	N	FI Ref

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	Parameter input tidak valid	Invalid input parameter
503	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded

404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	0101	Field [fieldName] is required	Field [fieldName] is required
400	0102	Field [fieldName] is larger than expected	Field [fieldName] is larger than expected
400	0103	Data type is invalid at field [fieldName]	Data type is invalid at field [fieldName]
409	0201	Ref pengirim sama	Same Sender Ref
409	0202	PIN sudah pernah dipakai	PIN already in used
400	0203	Format mata uang tidak valid	Invalid Currency format
400	0204	BIC Code tidak valid	Invalid BIC Code
400	0205	ABA Code tidak valid	Invalid ABA Code
400	0206	CHIPS Code tidak valid	Invalid CHIPS Code
400	0207	NID Code tidak valid	Invalid NID Code
400	0208	Country Code untuk NID Code tidak valid	Invalid Country Code for NID Code
401	0302	Access Code salah	Wrong Access Code
400	0303	Branch Code tidak ditemukan	Unknown Branch Code
400	0304	User ID tidak ditemukan	Unknown User ID
401	0306	Tidak berhak	Not Authorized Privilege
400	0401	PRODUK/MATA UANG TIDAK DITEMUKAN	PRODUCT/CURRENCY NOT FOUND
400	0402	LIMIT PRODUK TIDAK CUKUP	PRODUCT LIMIT NOT ENOUGH
400	0403	LIMIT RELEASER TIDAK CUKUP	LIMIT RELEASER NOT ENOUGH
400	0404	ERROR PDN LIMIT	ERROR PDN LIMIT
400	0405	GAGAL VALIDASI REKENING PENERIMA	FAILED TO VALIDATE BENEFICIARY ACCOUNT
400	0406	REKENING PENERIMA TIDAK VALID	INVALID BENEFICIARY ACCOUNT

400	0407	SALDO TIDAK CUKUP	INSUFFICIENT FUND
404	0408	TRANSAKSI TIDAK DITEMUKAN	TRANSACTION NOT FOUND
400	0409	REKENING PENERIMA TUTUP	CLOSED BENEFICIARY ACCOUNT
500	0410	TRANSAKSI TIDAK DAPAT DIPROSES	TRANSACTION CAN NOT BE PROCESSED
400	0412	BUKAN MEMBER SWITCHING	NON SWITCHING MEMBER
400	0413	REKENING TIDAK VALID	INVALID ACCOUNT NUMBER
400	0414	DITOLAK KARENA SALDO TIDAK CUKUP	REJECT DUE INSUFFICIENT FUND
503	0415	DITOLAK KARENA CUT OFF SISTEM BCA	REJECT DUE TO CUT OFF SYSTEM BCA
500	0901	Error Database	Error Database
503	0902	Sistem sedang dalam maintenance	System Under Maintenance
503	0903	Awal hari error	Begin of Day Error
500	0999	Error sistem	System error

PUT https://sandbox.bca.co.id/fire/transaction/cash-transfer/amend

Request



```
1 POST /fire/transactions/cash-transfer/amend HTTP/1.1
2 Host: sandbox.bca.co.id
3 Authorization: Bearer [access_token]
4 Content-Type: application/json
5 Origin: [yourdomain.com]
6 X-BCA-Key: [api_key]
7 X-BCA-Timestamp: [timestamp]
8 X-BCA-Signature: [signature]
9
10 {
11   "Authentication":{
12     "CorporateID":"ABCDE",
13     "AccessCode":"k1oawj8tygkrY9tBVkt",
14     "BranchCode":"BCAAPI01",
15     ...
```

PUT https://sandbox.bca.co.id/fire/transaction/cash-transfer/amend

Response



```
1  {
2    "SenderDetails":
3    {
4      "FirstName":"ERIK HERNANDEZ CORTES",
5      "LastName": "",
6      "DateOfBirth": "",
7      "Address1":"4TH AVENUE MANHATTAN",
8      "Address2": "",
9      "City":"NEW YORK",
10     "StateID": "",
11     "PostalCode": "",
12     "CountryID":"US",
13     "Mobile": "",
14     "IdentificationType": "",
15     "IdentificationType": ""
16   }
17 }
```

2. Informasi Rekening Penerima

Provides service to Inquiry BCA's Account name or Other Bank Switching's Account name.
Your request must contain following information:

Payload

Field	DataType	Mandatory	Description
Authentication			
CorporateID	String(6)	Y	Agent code used to connect to FIRe system
AccessCode	String(20)	Y	Password that will be read by system for each transaction request
BranchCode	String(8)	Y	FI branch code of API client
UserID	String(12)	Y	UserID
LocalID	String(15)	Y	Branch code from FI sub branch of API client
BeneficiaryDetails			
BankCodeType	String(3)	Y	Beneficiary's SWIFT code type from PY04 table. (BIC, NID, CHP (CHIPS), ABA, NAM(NAME))
BankCodeValue	String(23)	Y	
AccountNumber	String(34)	Y	Beneficiary bank's account number

Result of the request will contains following information:

Response

Field	DataType	Mandatory	Description
BeneficiaryDetails			
ServerBeneAccountName	String(35)	N	Name of beneficiary according to application (bank / switcher)
StatusTransaction	String(4)	Y	ResponseCode and Sub-ResponseCode of transaction
StatusMessage	String(100)	Y	Description of StatusTransaction

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	Parameter input tidak valid	Invalid input parameter
503	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	0101	Field [fieldName] is required	Field [fieldName] is required

400	0102	Field [fieldName] is larger than expected	Field [fieldName] is larger than expected
400	0103	Data type is invalid at field [fieldName]	Data type is invalid at field [fieldName]
409	0201	Ref pengirim sama	Same Sender Ref
409	0202	PIN sudah pernah dipakai	PIN already in used
400	0203	Format mata uang tidak valid	Invalid Currency format
400	0204	BIC Code tidak valid	Invalid BIC Code
400	0205	ABA Code tidak valid	Invalid ABA Code
400	0206	CHIPS Code tidak valid	Invalid CHIPS Code
400	0207	NID Code tidak valid	Invalid NID Code
400	0208	Country Code untuk NID Code tidak valid	Invalid Country Code for NID Code
401	0302	Access Code salah	Wrong Access Code
400	0303	Branch Code tidak ditemukan	Unknown Branch Code
400	0304	User ID tidak ditemukan	Unknown User ID
401	0306	Tidak berhak	Not Authorized Privilege
400	0401	PRODUK/MATA UANG TIDAK DITEMUKAN	PRODUCT/CURRENCY NOT FOUND
400	0402	LIMIT PRODUK TIDAK CUKUP	PRODUCT LIMIT NOT ENOUGH
400	0403	LIMIT RELEASER TIDAK CUKUP	LIMIT RELEASER NOT ENOUGH
400	0404	ERROR PDN LIMIT	ERROR PDN LIMIT
400	0405	GAGAL VALIDASI REKENING PENERIMA	FAILED TO VALIDATE BENEFICIARY ACCOUNT
400	0406	REKENING PENERIMA TIDAK VALID	INVALID BENEFICIARY ACCOUNT
400	0407	SALDO TIDAK CUKUP	INSUFFICIENT FUND
404	0408	TRANSAKSI TIDAK DITEMUKAN	TRANSACTION NOT FOUND
400	0409	REKENING PENERIMA TUTUP	CLOSED BENEFICIARY ACCOUNT

500	0410	TRANSAKSI TIDAK DAPAT DIPROSES	TRANSACTION CAN NOT BE PROCESSED
400	0412	BUKAN MEMBER SWITCHING	NON SWITCHING MEMBER
400	0413	REKENING TIDAK VALID	INVALID ACCOUNT NUMBER
400	0414	DITOLAK KARENA SALDO TIDAK CUKUP	REJECT DUE INSUFFICIENT FUND
503	0415	DITOLAK KARENA CUT OFF SISTEM BCA	REJECT DUE TO CUT OFF SYSTEM BCA
500	0901	Error Database	Error Database
503	0902	Sistem sedang dalam maintenance	System Under Maintenance
503	0903	Awal hari error	Begin of Day Error
500	0999	Error sistem	System error

POST https://sandbox.bca.co.id/fire/accounts

Request



```
1  POST /fire/accounts HTTP/1.1
2  Host: sandbox.bca.co.id
3  Authorization: Bearer [access_token]
4  Content-Type: application/json
5  Origin: [yourdomain.com]
6  X-BCA-Key: [api_key]
7  X-BCA-Timestamp: [timestamp]
8  X-BCA-Signature: [signature]
9
10 {
11   "Authentication":{
12     "CorporatelD":"POSTID",
13     "AccessCode":"jSvazuvEnz2mavv1wj6L",
14     "BranchCode":"POSTID01",
15     ...
```

POST https://sandbox.bca.co.id/fire/accounts

Response



```
1 {
2   "BeneficiaryDetails":
3   {
4     "ServerBeneAccountName":"ERWINA TAUFIK"
5   },
6   "StatusTransaction":"0000",
7   "StatusMessage":"Success"
8 }
```

3. Informasi Saldo Rekening Mitra

Provides service to Inquiry balance for Vostro's Account.

Your request must contain following information:

Payload

Field	DataType	Mandatory	Description
Authentication			
CorporateID	String(6)	Y	Agent code used to connect to FIRE system
AccessCode	String(20)	Y	Password that will be read by system for each transaction request
BranchCode	String(8)	Y	FI branch code of API client
UserId	String(12)	Y	User ID
LocalId	String(15)	Y	Branch code from FI sub branch of API client
FIDetails			
AccountNumber	String(34)	Y	FI sender's account number thar registered in FIRE

Result of the request will contains following information:

Response

Field	DataType	Mandatory	Description
StatusTransaction	String(4)	Y	ResponseCode and Sub-ResponseCode of transaction
StatusMessage	String(100)	Y	Description of StatusTransaction

FI Details

CurrencyID	String(3)	Y	FI sender's currency that registered in FIRE
AccountBalance	String(20)	Y	FI sender's account balance that registered in FIRE. Format : number(17.2)

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	Parameter input tidak valid	Invalid input parameter
503	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/grant_type tidak valid	Invalid client_id/client_secret/grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	0101	Field [fieldName] is required	Field [fieldName] is required
400	0102	Field [fieldName] is larger than expected	Field [fieldName] is larger than expected
400	0103	Data type is invalid at field [fieldName]	Data type is invalid at field [fieldName]
409	0201	Ref pengirim sama	Same Sender Ref

409	0202	PIN sudah pernah dipakai	PIN already in used
400	0203	Format mata uang tidak valid	Invalid Currency format
400	0204	BIC Code tidak valid	Invalid BIC Code
400	0205	ABA Code tidak valid	Invalid ABA Code
400	0206	CHIPS Code tidak valid	Invalid CHIPS Code
400	0207	NID Code tidak valid	Invalid NID Code
400	0208	Country Code untuk NID Code tidak valid	Invalid Country Code for NID Code
401	0302	Access Code salah	Wrong Access Code
400	0303	Branch Code tidak ditemukan	Unknown Branch Code
400	0304	User ID tidak ditemukan	Unknown User ID
401	0306	Tidak berhak	Not Authorized Privilege
400	0401	PRODUK/MATA UANG TIDAK DITEMUKAN	PRODUCT/CURRENCY NOT FOUND
400	0402	LIMIT PRODUK TIDAK CUKUP	PRODUCT LIMIT NOT ENOUGH
400	0403	LIMIT RELEASER TIDAK CUKUP	LIMIT RELEASER NOT ENOUGH
400	0404	ERROR PDN LIMIT	ERROR PDN LIMIT
400	0405	GAGAL VALIDASI REKENING PENERIMA	FAILED TO VALIDATE BENEFICIARY ACCOUNT
400	0406	REKENING PENERIMA TIDAK VALID	INVALID BENEFICIARY ACCOUNT
400	0407	SALDO TIDAK CUKUP	INSUFFICIENT FUND
404	0408	TRANSAKSI TIDAK DITEMUKAN	TRANSACTION NOT FOUND
400	0409	REKENING PENERIMA TUTUP	CLOSED BENEFICIARY ACCOUNT
500	0410	TRANSAKSI TIDAK DAPAT DIPROSES	TRANSACTION CAN NOT BE PROCESSED
400	0412	BUKAN MEMBER SWITCHING	NON SWITCHING MEMBER
400	0413	REKENING TIDAK VALID	INVALID ACCOUNT NUMBER
400	0414	DITOLAK KARENA SALDO TIDAK CUKUP	REJECT DUE INSUFFICIENT FUND

503	0415	DITOLAK KARENA CUT OFF SISTEM BCA	REJECT DUE TO CUT OFF SYSTEM BCA
500	0901	Error Database	Error Database
503	0902	Sistem sedang dalam maintenance	System Under Maintenance
503	0903	Awal hari error	Begin of Day Error
500	0999	Error sistem	System error

POST https://sandbox.bca.co.id/fire/accounts/balance

Request



```
1 POST /fire/accounts/balance HTTP/1.1
2 Host: sandbox.bca.co.id
3 Authorization: Bearer [access_token]
4 Content-Type: application/json
5 Origin: [yourdomain.com]
6 X-BCA-Key: [api_key]
7 X-BCA-Timestamp: [timestamp]
8 X-BCA-Signature: [signature]
9
10 {
11   "Authentication":{
12     "CorporatID":"POSTID",
13     "AccessCode":"jSvazuvEnz2mavv1wj6L",
14     "BranchCode":"POSTID01",
15     "..."
16   }
```

POST https://sandbox.bca.co.id/fire/accounts/balance

Response



```
1 {
2   "FIDetails":
3   {
4     "CurrencyID":"USD",
5     "AccountBalance":"228277.56"
6   },
7   "StatusTransaction":"0000",
8   "StatusMessage":"Success"
9 }
```

4. Informasi Status Kiriman Uang

Provides service to Inquiry Transaction that has been submitted before. Your request must contain following information:

Request

Field	DataType	Mandatory	Description
Authentication			
CorporateID	String(6)	Y	Agent code used to connect to FIRE system
AccessCode	String(20)	Y	Password that will be read by system for each transaction request
BranchCode	String(8)	Y	FI branch code of API client
UserID	String(12)	Y	User ID
LocalID	String(15)	Y	Branch code from FI sub branch of API client
TransactionDetails			
InquiryBy	String(1)	Y	N : PIN NON F : Form Number B : BCARef Number
InquiryValue	String(35)	Y	Value for PIN NON/Form Number/ BCARef Number

Result of the request will contains following information:

Response

Field	DataType	Mandatory	Description
StatusTransaction	String(4)	Y	ResponseCode and Sub-ResponseCode of transction
StatusMessage	String(100)	Y	Description of StatusTransaction
SenderDetails			
FirstName	String(35)	N	Sender's first name
LastName	String(35)	N	Sender's last name
BeneficiaryDetails			
Name	String(35)	N	Beneficiary's name
BankCodeType	String(3)	N	Beneficiary's SWIFT code type from PY04 table. (BIC, NID, CHP(CHIPS), ABA, NAM(NAME))

BankCodeValue	String(23)	N	Value for SWIFT code type
AccountNumber	String(34)	N	Beneficiary bank's account number
TransactionDetails			
AmountPaid	String(20)	N	Transaction value.
Format: Number(17.2)			
CurrencyID	String(3)	N	Currency code
ReleaseDateTime	String(24)	N	Transaction request time by FI
LocalID	String(15)	N	Local ID of Last Processed Non-Inquiry Transaction
FormNumber	String(16)	N	FI Ref
ReferenceNumber	String(25)	N	Ref number FI/BCA
PIN	String(35)	N	Personal Identification Number for encashment
Description1	String(35)	N	First Description
Description2	String(35)	N	Second description

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	Parameter input tidak valid	Invalid input parameter
503	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement

504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/ grant_type tidak valid	Invalid client_id/client_secret/ grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	0101	Field [fieldName] is required	Field [fieldName] is required
400	0102	Field [fieldName] is larger than expected	Field [fieldName] is larger than expected
400	0103	Data type is invalid at field [fieldName]	Data type is invalid at field [fieldName]
409	0201	Ref pengirim sama	Same Sender Ref
409	0202	PIN sudah pernah dipakai	PIN already in used
400	0203	Format mata uang tidak valid	Invalid Currency format
400	0204	BIC Code tidak valid	Invalid BIC Code
400	0205	ABA Code tidak valid	Invalid ABA Code
400	0206	CHIPS Code tidak valid	Invalid CHIPS Code
400	0207	NID Code tidak valid	Invalid NID Code
400	0208	Country Code untuk NID Code tidak valid	Invalid Country Code for NID Code
401	0302	Access Code salah	Wrong Access Code
400	0303	Branch Code tidak ditemukan	Unknown Branch Code
400	0304	User ID tidak ditemukan	Unknown User ID
401	0306	Tidak berhak	Not Authorized Privilege
400	0401	PRODUK/MATA UANG TIDAK DITEMUKAN	PRODUCT/CURRENCY NOT FOUND
400	0402	LIMIT PRODUK TIDAK CUKUP	PRODUCT LIMIT NOT ENOUGH

400	0403	LIMIT RELEASER TIDAK CUKUP	LIMIT RELEASER NOT ENOUGH
400	0404	ERROR PDN LIMIT	ERROR PDN LIMIT
400	0405	GAGAL VALIDASI REKENING PENERIMA	FAILED TO VALIDATE BENEFICIARY ACCOUNT
400	0406	REKENING PENERIMA TIDAK VALID	INVALID BENEFICIARY ACCOUNT
400	0407	SALDO TIDAK CUKUP	INSUFFICIENT FUND
404	0408	TRANSAKSI TIDAK DITEMUKAN	TRANSACTION NOT FOUND
400	0409	REKENING PENERIMA TUTUP	CLOSED BENEFICIARY ACCOUNT
500	0410	TRANSAKSI TIDAK DAPAT DIPROSES	TRANSACTION CAN NOT BE PROCESSED
400	0412	BUKAN MEMBER SWITCHING	NON SWITCHING MEMBER
400	0413	REKENING TIDAK VALID	INVALID ACCOUNT NUMBER
400	0414	DITOLAK KARENA SALDO TIDAK CUKUP	REJECT DUE INSUFFICIENT FUND
503	0415	DITOLAK KARENA CUT OFF SISTEM BCA	REJECT DUE TO CUT OFF SYSTEM BCA
500	0901	Error Database	Error Database
503	0902	Sistem sedang dalam maintenance	System Under Maintenance
503	0903	Awal hari error	Begin of Day Error
500	0999	Error sistem	System error

LastName	String(35)	N	Sender's last name
DateOfBirth	String(8)	N	Sender's date of birth. Format : ddmmyyyy
Address1	String(35)	Y	Sender's first address
Address2	String(35)	N	Sender's second address
City	String(18)	Y	Sender's city
StateID	String(2)	N	State ID
PostalCode	String(10)	N	Sender's postal code
CountryID	String(2)	Y	Sender's country initial code. Example: Indonesia =ID
Mobile	String(20)	N	Sender's mobile phone number
IdentificationType	String(2)	N	Sender's identity type (PP = Passport, ID = identity, DR = Dr. License)
IdentificationNumber	String(24)	N	Sender's identity number
AccountNumber	String(34)	N	Sender's account number
BeneficiaryDetails			
Name	String(35)	Y	Beneficiary's name
DateOfBirth	String(8)	N	Beneficiary's date of birth. Format : ddmmyyyy
Address1	String(35)	N	Beneficiary's first address
Address2	String(35)	N	Beneficiary's second address
City	String(35)	N	Beneficiary's city
StateID	String(2)	N	Beneficiary's state ID
PostalCode	String(10)	N	Beneficiary's postal code
CountryID	String(2)	Y	Beneficiary's country initial code. Example : Indonesia =ID
Mobile	String(20)	N	Beneficiary's mobile phone number
IdentificationType	String(2)	N	Beneficiary's identity type. (PP = Passport, ID = identity, DR = Dr. License)
IdentificationNumber	String(24)	N	Beneficiary's identity number

NationalityID	String(2)	N	Country initial code of beneficiary's nationality. Example = Indonesia =ID
Occupation	String(30)	N	Beneficiary occupation
BankCodeType	String(3)	Y	Beneficiary's SWIFT code type from PY04 table. (BIC, NID, CHP(CHIPS), ABA, NAM(NAME))
BankCodeValue	String(23)	Y	Value of SWIFT Code
BankCountryID	String(2)	Y	Beneficiary bank's country code
BankAddress	String(35)	N	Beneficiary bank's address
BankCity	String(35)	N	Beneficiary bank's city
AccountNumber	String(34)	Y	Beneficiary bank's account number
TransactionDetails			
CurrencyID	String(3)	Y	Transaction currency between FI and FIRE based on contract (setting FI Country in TPS)
Amount	String(20)	Y	Transaction nominal. Format: Number, 17.2
PurposeCode	String(3)	Y	Transaction purpose: 011 EXPORT 012 IMPORT 030 BUSINESS/PRIVATE TRIP 040 EDUCATION 150 WORKER'S REMMITANCE 161 TAX AND FINE 162 GRANT 999 OTHERS
Description1	String(35)	N	First description
Description2	String(35)	N	Second description
DetailOfCharges	String(3)	Y	Charges(SHA / OUR)
SourceOfFund	String(100)	N	Source of transaction fund
FormNumber	String(16)	Y	FI Ref

Result of the request will contains following information:

Response

Field	DataType	Mandatory	Description
-------	----------	-----------	-------------

BeneficiaryDetails			
Name	String(35)	N	Beneficiary's name
AccountNumber	String(34)	N	Beneficiary bank's account number
ServerBeneAccountName	String(35)	N	Name of beneficiary according to application (bank / switcher)
TransactionDetails			
CurrencyID	String(3)	N	Transaction currency between FI and FIRE based on contract (setting FI Country in TPS)
Amount	String(20)	N	Transaction nominal. Format: Number 17.2
Description1	String(35)	N	First Description
Description2	String(35)	N	Second Description
FormNumber	String(16)	N	FI Ref
ReferenceNumber	String(25)	N	FI Ref
ReleaseDateTime	String(24)	N	Transaction release time. Format : YYYY-MM-DDThh:mm:ssTZD
StatusTransaction	String(4)	Y	ResponseCode and Sub-ResponseCode of transaction
StatusMessage	String(100)	Y	Description of StatusTransaction

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	Parameter input tidak valid	Invalid input parameter
503	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance

504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/ grant_type tidak valid	Invalid client_id/client_secret/ grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	0101	Field [fieldName] is required	Field [fieldName] is required
400	0102	Field [fieldName] is larger than expected	Field [fieldName] is larger than expected
400	0103	Data type is invalid at field [fieldName]	Data type is invalid at field [fieldName]
409	0201	Ref pengirim sama	Same Sender Ref
409	0202	PIN sudah pernah dipakai	PIN already in used
400	0203	Format mata uang tidak valid	Invalid Currency format
400	0204	BIC Code tidak valid	Invalid BIC Code
400	0205	ABA Code tidak valid	Invalid ABA Code
400	0206	CHIPS Code tidak valid	Invalid CHIPS Code
400	0207	NID Code tidak valid	Invalid NID Code
400	0208	Country Code untuk NID Code tidak valid	Invalid Country Code for NID Code
401	0302	Access Code salah	Wrong Access Code
400	0303	Branch Code tidak ditemukan	Unknown Branch Code
400	0304	User ID tidak ditemukan	Unknown User ID
401	0306	Tidak berhak	Not Authorized Privilege
400	0401	PRODUK/MATA UANG TIDAK DITEMUKAN	PRODUCT/CURRENCY NOT FOUND

400	0402	LIMIT PRODUK TIDAK CUKUP	PRODUCT LIMIT NOT ENOUGH
400	0403	LIMIT RELEASER TIDAK CUKUP	LIMIT RELEASER NOT ENOUGH
400	0404	ERROR PDN LIMIT	ERROR PDN LIMIT
400	0405	GAGAL VALIDASI REKENING PENERIMA	FAILED TO VALIDATE BENEFICIARY ACCOUNT
400	0406	REKENING PENERIMA TIDAK VALID	INVALID BENEFICIARY ACCOUNT
400	0407	SALDO TIDAK CUKUP	INSUFFICIENT FUND
404	0408	TRANSAKSI TIDAK DITEMUKAN	TRANSACTION NOT FOUND
400	0409	REKENING PENERIMA TUTUP	CLOSED BENEFICIARY ACCOUNT
500	0410	TRANSAKSI TIDAK DAPAT DIPROSES	TRANSACTION CAN NOT BE PROCESSED
400	0412	BUKAN MEMBER SWITCHING	NON SWITCHING MEMBER
400	0413	REKENING TIDAK VALID	INVALID ACCOUNT NUMBER
400	0414	DITOLAK KARENA SALDO TIDAK CUKUP	REJECT DUE INSUFFICIENT FUND
503	0415	DITOLAK KARENA CUT OFF SISTEM BCA	REJECT DUE TO CUT OFF SYSTEM BCA
500	0901	Error Database	Error Database
503	0902	Sistem sedang dalam maintenance	System Under Maintenance
503	0903	Awal hari error	Begin of Day Error
500	0999	Error sistem	System error

POST https://sandbox.bca.co.id/fire/transactions/to-account

Request



```
1  POST /fire/transactions/to-account HTTP/1.1
2  Host: sandbox.bca.co.id
3  Authorization: Bearer [access_token]
4  Content-Type: application/json
5  Origin: [yourdomain.com]
6  X-BCA-Key: [api_key]
7  X-BCA-Timestamp: [timestamp]
8  X-BCA-Signature: [signature]
9
10 {
11   "Authentication": {
12     "CorporatelD": "CORP1",
13     "AccessCode": "Ya9wn025GgaKkcbDsTvR",
14     "BranchCode": "BRANCH01",
15     "ServerBeneAccountName": "monica gupt"
```

POST https://sandbox.bca.co.id/fire/transactions/to-account

Response



```
1  {
2    "BeneficiaryDetails":
3    {
4      "Name": "monica gupt",
5      "AccountNumber": "0106666011",
6      "ServerBeneAccountName": "monica gupt"
7    },
8    "TransactionDetails":
9    {
10     "CurrencyID": "IDR",
11     "Amount": "10000000",
12     "Description1": "",
13     "Description2": "",
14     "FormNumber": "7632605701245868",
15     "ServerBeneAccountName": "monica gupt"
```

6. Pembatalan Kiriman Uang Tunai

Provides service for Cancellation “Cash Transfer” to Non account holder. Your request must contain following information:

Payload

Field	Data Type	Mandatory	Description
Authentication			
CorporatelD	String(6)	Y	Agent code used to connect to FIRE system

AccessCode	String(20)	Y	Password that will be read by system for each
BranchCode	String(8)	Y	FI branch code of API client
UserID	String(12)	Y	User ID
LocalID	String(15)	Y	Branch code from FI sub branch of API client
TransactionDetails			
FormNumber	String(16)	Y	FI Ref
Amount	String(20)	Y	Transaction nominal. Format: Number, 17.2
CurrencyID	String(3)	N	Currency code

Result of the request will contains following information:

Response

Field	DataType	Mandatory	Description
StatusTransaction	String(4)	Y	RespponseCode and Sub-ResponseCode of transaction
StatusMessage	String(100)	Y	Description of StatusTransaction
TransactionDetails			
FormNumber	String(16)	N	FI Ref
ReleaseDateTime	String(24)		Transaction release time. Format : YYYY-MM-DDThh:mm:ssTZD

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	Parameter input tidak valid	Invalid input parameter

503	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement
504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/ grant_type tidak valid	Invalid client_id/client_secret/ grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	0101	Field [fieldName] is required	Field [fieldName] is required
400	0102	Field [fieldName] is larger than expected	Field [fieldName] is larger than expected
400	0103	Data type is invalid at field [fieldName]	Data type is invalid at field [fieldName]
409	0201	Ref pengirim sama	Same Sender Ref
409	0202	PIN sudah pernah dipakai	PIN already in used
400	0203	Format mata uang tidak valid	Invalid Currency format
400	0204	BIC Code tidak valid	Invalid BIC Code
400	0205	ABA Code tidak valid	Invalid ABA Code
400	0206	CHIPS Code tidak valid	Invalid CHIPS Code
400	0207	NID Code tidak valid	Invalid NID Code
400	0208	Country Code untuk NID Code tidak valid	Invalid Country Code for NID Code
401	0302	Access Code salah	Wrong Access Code
400	0303	Branch Code tidak ditemukan	Unknown Branch Code
400	0304	User ID tidak ditemukan	Unknown User ID
401	0306	Tidak berhak	Not Authorized Privilege

400	0401	PRODUK/MATA UANG TIDAK DITEMUKAN	PRODUCT/CURRENCY NOT FOUND
400	0402	LIMIT PRODUK TIDAK CUKUP	PRODUCT LIMIT NOT ENOUGH
400	0403	LIMIT RELEASER TIDAK CUKUP	LIMIT RELEASER NOT ENOUGH
400	0404	ERROR PDN LIMIT	ERROR PDN LIMIT
400	0405	GAGAL VALIDASI REKENING PENERIMA	FAILED TO VALIDATE BENEFICIARY ACCOUNT
400	0406	REKENING PENERIMA TIDAK VALID	INVALID BENEFICIARY ACCOUNT
400	0407	SALDO TIDAK CUKUP	INSUFFICIENT FUND
404	0408	TRANSAKSI TIDAK DITEMUKAN	TRANSACTION NOT FOUND
400	0409	REKENING PENERIMA TUTUP	CLOSED BENEFICIARY ACCOUNT
500	0410	TRANSAKSI TIDAK DAPAT DIPROSES	TRANSACTION CAN NOT BE PROCESSED
400	0412	BUKAN MEMBER SWITCHING	NON SWITCHING MEMBER
400	0413	REKENING TIDAK VALID	INVALID ACCOUNT NUMBER
400	0414	DITOLAK KARENA SALDO TIDAK CUKUP	REJECT DUE INSUFFICIENT FUND
503	0415	DITOLAK KARENA CUT OFF SISTEM BCA	REJECT DUE TO CUT OFF SYSTEM BCA
500	0901	Error Database	Error Database
503	0902	Sistem sedang dalam maintenance	System Under Maintenance
503	0903	Awal hari error	Begin of Day Error
500	0999	Error sistem	System error

POST https://sandbox.bca.co.id/fire/transactions/cash-transfer/cancel

Request



```
1  POST /fire/transactions/cash-transfer/cancel HTTP/1.1
2  Host: sandbox.bca.co.id
3  Authorization: Bearer [access_token]
4  Content-Type: application/json
5  Origin: [yourdomain.com]
6  X-BCA-Key: [api_key]
7  X-BCA-Timestamp: [timestamp]
8  X-BCA-Signature: [signature]
9
10 {
11   "Authentication":{
12     "CorporatelD":"BCAAPI",
13     "AccessCode":"k6re8tG35hgNODSg3Y",
14     "BranchCode":"BCA01",
15     "AccessCode":"k6re8tG35hgNODSg3Y"
```

POST https://sandbox.bca.co.id/fire/transactions/cash-transfer/cancel

Response



```
1  {
2    "TransactionDetails":
3    {
4      "FormNumber":"CT293_IDR2D",
5      "ReleaseDateTime":"2016-04-20T04:00:23+07:00"
6    },
7    "StatusTransaction":"0000",
8    "StatusMessage":"Success"
9  }
```

7. Transaksi Kiriman Uang Tunai

Provides service for transaction “Cash Transfer” to Non account holder.

Your request must contain following information:

Payload

Field	DataType	Mandatory	Description
Authentication			
CorporatelD	String(6)	Y	Agent code used to connect to FIRe system
AccessCode	String(20)	Y	Password that will be read by system for each transaction request

BranchCode	String(8)	Y	FI branch code of API client
UserID	String(12)	Y	User ID
LocalID	String(15)	Y	Branch code from FI sub branch of API client
SenderDetails			
FirstName	String(35)	Y	Sender's first name
LastName	String(35)	N	Sender's last name
DateOfBirth	String(8)	N	Sender's date of birth. Format : ddmmyyyy
Address1	String(35)	Y	Sender's first address
Address2	String(35)	N	Sender's second address
City	String(18)	Y	Sender's city
StateID	String(2)	N	Sender's state ID
PostalCode	String(10)	N	Sender's postal code
CountryID	String(2)	Y	Sender's country initial code. Example : Indonesia = ID
Mobile	String(20)	N	Sender's mobile phone number
IdentificationType	String(2)	N	Sender's identity type. (PP = Passport, ID = Identity, DR = Dr. License)
IdentificationNumber	String(24)	N	Sender's identity number
BeneficiaryDetails			
Name	String(35)	Y	Beneficiary's name
DateOfBirth	String(8)	N	Beneficiary's date of birth. Format : ddmmyyyy
Address1	String(35)	N	Beneficiary's first address
Address2	String(35)	N	Beneficiary's second address
City	String(35)	N	Beneficiary's city
StateID	String(2)	N	Beneficiary's state ID
PostalCode	String(10)	N	Beneficiary's postal code
CountryID	String(2)	Y	Beneficiary's country initial code. Example : Indonesia = ID

Mobile	String(20)	N	Beneficiary's mobile phone number
IdentificationType	String(2)	N	Beneficiary's identity type. (PP = Passport, ID = Identity, DR = Dr. License)
IdentificationNumber	String(24)	N	Beneficiary's identity number
NationalityID	String(2)	N	Country initial code of beneficiary's nationality. Example : Indonesia = ID
Occupation	String(30)	N	Beneficiary occupation
TransactionDetails			
PIN	String(35)	N	Transaction PIN number. If not available, BCA will provide it
SecretQuestion	String(100)	N	Questions
SecretAnswer	String(100)	N	Answers
CurrencyID	String(3)	Y	Transaction currency between FI and FIRe based on contract (setting FI Country in TPS)
Amount	String(20)	Y	Transaction nominal. Format: number(17,2)
PurposeCode	String(3)	Y	Transaction purpose. 011 EXPORT 012 IMPORT 030 BUSINESS/PRIVATE TRIP 040 EDUCATION 150 WORKER'S REMMITANCE 161 TAX AND FINE 162 GRANT 999 OTHERS
Description1	String(35)	N	First description
Description2	String(35)	N	Second description
DetailOfCharges	String(3)	Y	Charges (SHA / OUR)
SourceOfFund	String(100)	Y	Source of transaction fund
FormNumber	String(16)	Y	FI Ref

Response

Field	DataType	Mandatory	Description
-------	----------	-----------	-------------

StatusTransaction	String(4)	Y	ResponseCode and Sub- ResponseCode of transaction
StatusMessage	String(100)	Y	Description of StatusTransaction
BeneficiaryDetails			
Name	String(35)	N	Beneficiary's name
TransactionDetails			
PIN	String(35)	N	Transaction PIN number. If not available, BCA will provide it
CurrencyID	String(3)	N	Transaction currency between FI and FIRe based on contract (setting FI Country in TPS)
Amount	String(20)	N	Transaction nominal
Description1	String(35)	N	First description
Description2	String(35)	N	Second description
FormNumber	String(16)	N	FI Ref
ReferenceNumber	String(25)	N	FI Ref
ReleaseDateTime	String(24)	N	Transaction release time. Format : YYYY-MM-DDThh:mm:ssTZD

Error

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch
400	ESB-14-002	Permintaan tidak valid	Invalid request
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp
400	ESB-14-004	Parameter input tidak valid	Invalid input parameter
503	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance
504	ESB-14-006	Timeout, silakan periksa mutasi rekening	Timeout, please check your account statement

504	ESB-14-007	Timeout	Timeout
401	ESB-14-008	client_id/client_secret/ grant_type tidak valid	Invalid client_id/client_secret/ grant_type
401	ESB-14-009	Tidak berhak	Unauthorized
429	ESB-14-010	Jumlah permintaan melebihi limit	Limit request exceeded
404	ESB-14-011	Service tidak ada	Service doesn't exist
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service
400	0101	Field [fieldName] is required	Field [fieldName] is required
400	0102	Field [fieldName] is larger than expected	Field [fieldName] is larger than expected
400	0103	Data type is invalid at field [fieldName]	Data type is invalid at field [fieldName]
409	0201	Ref pengirim sama	Same Sender Ref
409	0202	PIN sudah pernah dipakai	PIN already in used
400	0203	Format mata uang tidak valid	Invalid Currency format
400	0204	BIC Code tidak valid	Invalid BIC Code
400	0205	ABA Code tidak valid	Invalid ABA Code
400	0206	CHIPS Code tidak valid	Invalid CHIPS Code
400	0207	NID Code tidak valid	Invalid NID Code
400	0208	Country Code untuk NID Code tidak valid	Invalid Country Code for NID Code
401	0302	Access Code salah	Wrong Access Code
400	0303	Branch Code tidak ditemukan	Unknown Branch Code
400	0304	User ID tidak ditemukan	Unknown User ID
401	0306	Tidak berhak	Not Authorized Privilege
400	0401	PRODUK/MATA UANG TIDAK DITEMUKAN	PRODUCT/CURRENCY NOT FOUND
400	0402	LIMIT PRODUK TIDAK CUKUP	PRODUCT LIMIT NOT ENOUGH

400	0403	LIMIT RELEASER TIDAK CUKUP	LIMIT RELEASER NOT ENOUGH
400	0404	ERROR PDN LIMIT	ERROR PDN LIMIT
400	0405	GAGAL VALIDASI REKENING PENERIMA	FAILED TO VALIDATE BENEFICIARY ACCOUNT
400	0406	REKENING PENERIMA TIDAK VALID	INVALID BENEFICIARY ACCOUNT
400	0407	SALDO TIDAK CUKUP	INSUFFICIENT FUND
404	0408	TRANSAKSI TIDAK DITEMUKAN	TRANSACTION NOT FOUND
400	0409	REKENING PENERIMA TUTUP	CLOSED BENEFICIARY ACCOUNT
500	0410	TRANSAKSI TIDAK DAPAT DIPROSES	TRANSACTION CAN NOT BE PROCESSED
400	0412	BUKAN MEMBER SWITCHING	NON SWITCHING MEMBER
400	0413	REKENING TIDAK VALID	INVALID ACCOUNT NUMBER
400	0414	DITOLAK KARENA SALDO TIDAK CUKUP	REJECT DUE INSUFFICIENT FUND
503	0415	DITOLAK KARENA CUT OFF SISTEM BCA	REJECT DUE TO CUT OFF SYSTEM BCA
500	0901	Error Database	Error Database
503	0902	Sistem sedang dalam maintenance	System Under Maintenance
503	0903	Awal hari error	Begin of Day Error
500	0999	Error sistem	System error

POST https://sandbox.bca.co.id/fire/transactions/cash-transfer

Request



```

1  POST /fire/transactions/cash-transfer HTTP/1.1
2  Host: sandbox.bca.co.id
3  Authorization: Bearer [access_token]
4  Content-Type: application/json
5  Origin: [yourdomain.com]
6  X-BCA-Key: [api_key]
7  X-BCA-Timestamp: [timestamp]
8  X-BCA-Signature: [signature]
9
10 {
11   "Authentication": {
12     "CorporateID": "PYTHSG",
13     "AccessCode": "wArjfChZjj9dC3eJqz0X",
14     "BranchCode": "PYTHSG01",
15     "..."

```

POST https://sandbox.bca.co.id/fire/transactions/cash-transfer

Response



```

1  {
2    "BeneficiaryDetails":
3    {
4      "Name": "TEST"
5    },
6    "TransactionDetails":
7    {
8      "PIN": "477634423",
9      "CurrencyID": "IDR",
10     "Amount": "150000.00",
11     "Description1": "",
12     "Description2": "",
13     "FormNumber": "477634423",
14     "ReferenceNumber": "CITIID01000NON16040000099",
15     "..."

```

Top Up Flazz

1. Top Up Flazz Mobile Operating System

Banking service to make Flazz top up transaction by using Merchant's device/reader/application.

To be able to use this feature, the following 5 API services must be accessed by the client:

a. Get Session Key

API service to request session key. Session key is formed by randomly generated key to ensure session security during communication between Merchant and BCA Host.

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction
request_data	String(198)	Y	Request data stream

Response

Field	DataType	Mandatory	Description
response_data	String(198)	N	Response data stream
transaction_id	String (16)	N	transaction_id

b. Send topup request from merchant

API service to send Flazz balance top up requests.

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction
request_data	String(448)	Y	Request data stream

topup_amount	Numeric(8)	O	Amount top up from merchant. If top up amount sent is less than 8 digits, it will be rejected. Example : “00200000”
--------------	------------	---	---

Response

Field	DataType	Mandatory	Description
response_data	String(350)	N	Response data stream
ref_no	String(6)	N	ref no
transaction_id	String (16)	N	transaction_id

c. Reversal

API service to send reversal request of Flazz top up

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction
request_data	String(544)	Y	Request data stream

Response

Field	DataType	Mandatory	Description
response_data	String	N	Response data stream
transaction_id	String (16)	N	transaction_id

d.ACK

API service to send ACK requests (Acknowledge) for successful / failed / lost-contact transactions of Flazz top up

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction
request_data	String(544)	Y	Request data stream

Response

Field	DataType	Mandatory	Description
response_data	String	N	Response data stream
transaction_id	String (16)	N	transaction_id

e.Card Verification

API service to send Card Verification requests

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction
request_data	String(16)	Y	Request data from online merchants to check Flazz card number

Response

Field	Data Type	Mandatory	Description
response_data	String(17)	N	Flazz card number

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)	Description	Error Appear In Service
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch	400	- Card Verification - Session Key - Top Up - Reversal - ACK
400	ESB-14-002	Permintaan tidak valid	Invalid request	400	- Card Verification - Session Key - Top Up - Reversal - ACK
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp	400	- Card Verification - Session Key - Top Up - Reversal - ACK
400	ESB-14-004	parameter input tidak valid	Invalid input parameter	400	- Card Verification - Session

					Key - Top Up - Reversal - ACK
500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance	500	- Card Verification - Session Key - Top Up - Reversal - ACK
504	ESB-14-007	Timeout	Timeout	504	- Card Verification - Session Key - ACK
401	ESB-14-008	Client_Id/ Client_Secret / Grant_Type tidak valid	Invalid Client_Id/ Client_Secret / Grant_Type	401	- Card Verification - Session Key - Top Up - Reversal - ACK
401	ESB-14-009	Tidak berhak	Unauthorized	401	- Card Verification - Session Key - Top Up - Reversal - ACK
404	ESB-14-011	Service tidak tersedia	Service doesn't exist	404	- Card Verification - Session Key - Top Up - Reversal - ACK
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service	401	- Card Verification - Session Key - Top Up - Reversal - ACK

401	ESB-14-014	ChannelID/ CredentialID tidak valid	Invalid ChannelID/ CredentialID	401	- Card Verification - Session Key - Top Up - Reversal - ACK
400	ESB-14-015	Content Type tidak valid	Invalid Content Type	400	- Card Verification - Session Key - Top Up - Reversal - ACK
400	ESB-14-016	Format JSON tidak valid	Invalid JSON format	400	- Card Verification - Session Key - Top Up - Reversal - ACK
403	ESB-14-019	Koneksi tidak diperbolehkan	Connection not allowed	403	- Card Verification - Session Key - Top Up - Reversal - ACK
400	ESB-14-021	API Key tidak valid	Invalid API Key	400	- Card Verification - Session Key - Top Up - Reversal - ACK
400	ESB-14-022	API Key/API Secret tidak cocok	API Key/API Secret mismatch	400	- Card Verification - Session Key - Top Up - Reversal - ACK
504	ESB-14-023	Koneksi Timeout. Silakan cek transaksi kembali untuk memastikan keberhasilan	Connection timeout. Please reinquiry your transaction to ensure	504	- Top Up - Reversal

		transaksi Anda	transaction status		
400	0002	Transaksi Gagal	Transaction Failed	Copartner is not registered	- Session Key - Top Up - Reversal - ACK
400	0012	Transaksi Gagal	Transaction Failed	Copartner is blocked	- Card Verification - Session Key - Top Up - Reversal - ACK
400	0022	Transaksi Gagal	Transaction Failed	Copartner max retry exceeded	- Card Verification - Session Key - Top Up - Reversal - ACK
400	0032	Transaksi Gagal	Transaction Failed	Copartner session key not exist	- Top Up - Reversal - ACK
400	1012	Kartu Error	Card Error	Check expired date failed	- Top Up
400	1022	Transaksi gagal, nominal Top Up kurang dari minimum	Transaction failed, Top Up amount less than minimum	Check min amount failed	- Top Up
400	1032	Transaksi gagal, nominal Top Up melebihi saldo maksimum	Transaction failed, Top Up amount exceeds maximum balance	Check max balance failed	- Top Up
400	1052	Transaksi gagal	Transaction failed	Check mandatory field failed	- Card Verification - Session Key - Top Up - Reversal - ACK
400	1062	Transaksi gagal	Transaction failed	Parse request data failed	- Card Verification - Session

					Key - Top Up - Reversal - ACK
400	1102	Transaksi gagal	Transaction failed	Duplicate transaction	- Top Up - Reversal - ACK
400	1122	Transaksi gagal	Transaction failed	Check original data failed	- Reversal - ACK
400	1132	Transaksi gagal	Transaction failed	Check tid failed	- Session Key - Top Up - Reversal - ACK
400	1142	Transaksi gagal	Transaction failed	Check mid failed	- Session Key - Top Up - Reversal - ACK
400	1152	Kartu error	Card error	Card blacklisted	- Top Up
400	1202	Transaksi gagal	Transaction failed	TID and MID doesn't exist	- Session Key - Top Up - Reversal - ACK
400	1222	Transaksi gagal, nilai top up berbeda	Transaction failed, amount mismatch	Amount merchant not match	-.Top Up
400	3023	Transaksi gagal	Transaction failed	Request topup debit timeout failed	- Top Up - Reversal - ACK
400	3045	Transaksi gagal	Transaction failed	Check atuf timeout failed	-. Top up
400	4009	Field (0) harus diisi	Missing mandatory field (0)	Field (0) harus diisi	- Top Up - Reversal - ACK
400	4038	Panjang field (0) tidak valid	Field (0) length not valid	Panjang field (0) tidak valid	- Top Up - Reversal - ACK

400	4039	Isian input (0) tidak valid	Input for field (0) not valid	Isian input (0) tidak valid	- Top Up - Reversal - ACK
400	4045	Maaf, transaksi anda tidak dapat diproses	Sorry, your transaction can not be processed	Identifier Channel tidak diizinkan mengakses	- Top Up - Reversal - ACK
400	4112	Inputan String JSON tidak valid	Invalid JSON String input	Format JSON input invalid	- Top Up - Reversal - ACK
400	4113	Transaksi ditolak	Transaction rejected	ClientID tidak dapat mengakses ke service	- Top Up - Reversal - ACK
400	4414	Transaksi gagal	Transaction failed	Gagal saat konversi(format data yang diterima tidak sesuai)	- Top Up - Reversal - ACK
400	4415	Transaksi gagal	Transaction failed	Record yang ingin dihapus tidak ada.	- Top Up - Reversal - ACK
400	4416	Transaksi gagal	Transaction failed	File Limit TopUp tidak ada	- Top Up - Reversal - ACK
400	4417	Transaksi gagal	Transaction failed	File Limit TopUp tidak bisa dibuka	- Top Up - Reversal - ACK
400	4418	Transaksi gagal	Transaction failed	File Limit TopUp tidak bisa dibaca	- Top Up - Reversal - ACK
400	4419	Transaksi gagal	Transaction failed	Record sudah ada ketika tambah record baru	- Top Up - Reversal - ACK
400	4420	Transaksi gagal	Transaction failed	Record tidak ada ketika Change/ Update	- Top Up - Reversal - ACK
400	4421	Transaksi gagal	Transaction failed	Gagal menulis record	- Top Up - Reversal - ACK
400	4422	Transaksi gagal	Transaction failed	Gagal hapus record	- Top Up - Reversal - ACK

400	4423	Transaksi gagal	Transaction failed	FIID yang dikirimkan tidak sesuai/data FIID tidak ada	- Top Up - Reversal - ACK
400	4424	Transaksi gagal	Transaction failed	Transaksi code tidak sesuai(sesuai dengan data element 91)	- Top Up - Reversal - ACK
400	4425	Transaksi gagal	Transaction failed	FIID tidak terdaftar	- Top Up - Reversal - ACK
400	4426	Transaksi gagal	Transaction failed	File request tidak sesuai(sesuai dengan data element 101)	- Top Up - Reversal - ACK
400	4427	Transaksi gagal	Transaction failed	ATUF Flazz Type Error.	- Top Up - Reversal - ACK
400	4428	Transaksi gagal	Transaction failed	Gagal ketika mencoba mencari nomor kartu	- Top Up - Reversal - ACK
400	4429	Transaksi gagal, jumlah top up melebihi limit bulanan	Transaction failed, Top Up amount exceeds monthly limit	Limit kartu akses/ bulanan habis.	- Top Up - Reversal - ACK
400	4430	Transaksi gagal	Transaction failed	Unik id tidak ditemukan	- Top Up - Reversal - ACK
400	4431	Transaksi gagal	Transaction failed	Koneksi saat dari atau ke b24 terputus	- Top Up - Reversal - ACK
400	4432	Transaksi gagal	Transaction failed	Koneksi saat dari atau ke b24 ditolak	- Top Up - Reversal - ACK
400	4433	Status kartu inactive	Card status inactive	Status kartu inactive	- Top Up - Reversal - ACK
400	4434	Limit harian kartu akses telah mencapai batas	Access card limit daily has been reached	Limit harian akses telah mencapai batasan	- Top Up - Reversal - ACK

400	4435	Kartu akses salah	Incorrect access card	Kartu akses salah	- Top Up - Reversal - ACK
400	4436	Kode akses terblokir	Max incorrect access code	Kode akses terblokir	- Top Up - Reversal - ACK
400	4437	MID tidak cocok	MID unmatched	MID tidak cocok	- Top Up - Reversal - ACK
400	4662	Transaksi tidak dapat diproses. Silahkan coba beberapa saat lagi.	Transaction cannot be processed. Please try again later	Error dari sistem apabila terjadi koneksi timeout.	- Top Up - Reversal - ACK
400	0000	Transaksi Berhasil	Transaction Success	Transaksi berhasil	- Top Up - Reversal - ACK
400	5202	Transaksi 0 rupiah	Transaction amount 0	Transaksi 0 Rupiah	- Top Up
400	5204	Maaf saldo tidak mencukupi	Sorry your balance is not enough	Maaf saldo tidak mencukupi	- Top Up
400	5206	Rekening ditolak	Account Rejected	Rekening ditolak	- Top Up
400	5700	Maaf transaksi harus IDR	Sorry, currency must IDR	Maaf transaksi harus IDR	- Top Up
400	5701	Rekening ditolak	Account Rejected	Rekening ditolak	- Top Up
400	5702	Maaf rekening sudah tidak aktif	Sorry, your account is dormant	Maaf rekening sudah tidak aktif	- Top Up
400	5711	Maaf rekening anda masuk daftar hitam	Sorry, your account is blacklist	Rekening anda diblokir/masuk daftar hitam	- Top Up
400	5999	Sistem sedang tidak tersedia	System unavailable	Sistem sedang tidak tersedia	- Top Up - Reversal

POST /flazz/

Request



```

1  REQUEST FOR GET SESSION KEY
2
3  POST https://sandbox.bca.co.id/flazz/v2/getKey
4  -H channel-id 95381
5  -H credential-id 00ESBY0001
6  -H Authorization Bearer LYQG93kCXeQCwUWbhYcv5fnrRHum1esgN7nlll3xmOWhfPluicXzb9
7  -H X-BCA-Key fd2bd8c5-ff4d-41b6-8905-f0264f5c6b4f
8  -H X-BCA-Signature 652ce6723d7a0272c40d5812b3b16ecdaa689b74a04d6d859ed5ffcd7b233e
9  -H X-BCA-TimeStamp 2020-02-18T09:27:31.198+07:00
10 -d {
11   "reference_id": "123456789012",
12   "request_data":
13   "01010100202108201115134258594E45584953454D424341303032885000015999313233343536
14   303030303030303030845E0B020602844E18271B1B6E024B1C820B6E06825E1C274E845E020B4E
15   .....

```

POST /flazz/

Response



```

1  RESPONSE FOR GET SESSION KEY
2
3  {
4   "response_data": ""01010000202001171513224553594230303031454D424341303031885000C
5   "transaction_id": "12345678000000000"
6  }
7
8  RESPONSE FOR REQUEST TOP UP
9
10 {
11   "response_data":
12   "012401450028000000038000000100000000000160230202002191019275D5D6E5DB05D6D7A
13   "ref_no": "777777",
14   "transaction_id": "0000112233445566"
15 }

```

2. Top Up Flazz Non Mobile Operating System

Banking service to make Flazz top up transaction by using Merchant's device/reader.

To be able to use this feature, the following 4 API services must be accessed by the client:

a. Get Session Key

API service to request session key. Session key is formed by randomly generated key to ensure session security during communication between Merchant and BCA Host.

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction

request_data	String(166)	Y	Request data stream
--------------	-------------	---	---------------------

Response

Field	DataType	Mandatory	Description
response_data	String(166)	N	Response data stream

b. Send topup request from merchant

API service to send Flazz balance top up requests.

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction

request_data	String(416)	Y	Request data stream
--------------	-------------	---	---------------------

Response

Field	DataType	Mandatory	Description
response_data	String(350)	N	Response data stream

c. Reversal

API service to send reversal request of Flazz top up

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction
request_data	String(512)	Y	Request data stream

Response

Field	DataType	Mandatory	Description
response_data	String	N	Response data stream

d.ACK

API service to send ACK requests (Acknowledge) for successful / failed / lost-contact transactions of Flazz top up

Your Request must contain following information:

Request Headers and URI Params

Field	Params Type	DataType	Mandatory	Description
channel-id	Header	String	Y	95381 (WSID FLAZZ)
credential-id	Header	String(36)	Y	Copartner-id

Payload (Form Data)

Field	Data Type	Mandatory	Description
reference_id	String(12)	Y	Reference ID is datetime transaction in milisecond (unix time), requires only the first 12 digits and the same reference_id must be carried in 1 service API set for Top Up Flazz. Ex : 969677130000 Unique per transaction
request_data	String(512)	Y	Request data stream

Response

Field	DataType	Mandatory	Description
response_data	String	N	Response data stream

Here is the list of error codes that can be returned.

HTTP Code	Error Code	Error Message (Indonesian)	Error Message (English)	Description	Errors appears in Service
400	ESB-14-001	HMAC tidak cocok	HMAC mismatch	400	- Session Key - Top Up - Reversal - ACK
400	ESB-14-002	Permintaan tidak valid	Invalid request	400	- Session Key - Top Up - Reversal - ACK
400	ESB-14-003	Timestamp tidak valid	Invalid timestamp	400	- Session Key - Top Up - Reversal - ACK
400	ESB-14-004	parameter input tidak valid	Invalid input parameter	400	- Session Key - Top Up - Reversal - ACK

500	ESB-14-005	Sistem sedang dalam maintenance	System under maintenance	500	- Session Key - Top Up - Reversal - ACK
504	ESB-14-007	Timeout	Timeout	504	- Session Key - ACK
401	ESB-14-008	Client_Id/ Client_Secret / Grant_Type tidak valid	Invalid Client_Id/ Client_Secret / Grant_Type	401	- Session Key - Top Up - Reversal - ACK
401	ESB-14-009	Tidak berhak	Unauthorized	401	- Session Key - Top Up - Reversal - ACK
404	ESB-14-011	Service tidak tersedia	Service doesn't exist	404	- Session Key - Top Up - Reversal - ACK
401	ESB-14-012	Tidak berhak mengakses service ini	Not allowed to access this service	401	- Session Key - Top Up - Reversal - ACK
401	ESB-14-014	ChannelID/ CredentialID tidak valid	Invalid ChannelID/ CredentialID	401	- Session Key - Top Up - Reversal - ACK
403	ESB-14-019	Koneksi tidak diperbolehkan	Connection not allowed	403	- Session Key - Top Up - Reversal - ACK
400	ESB-14-021	API Key tidak valid	Invalid API Key	400	- Session Key - Top Up - Reversal - ACK

400	ESB-14-022	API Key/API Secret tidak cocok	API Key/API Secret mismatch	400	- Session Key - Top Up - Reversal - ACK
400	ESB-14-023	Koneksi Timeout Silahkan cek transaksi kembali untuk memastikan keberhasilan transaksi anda	Connection Timeout Please reinquiry your transaction to ensure transaction status	504	- Top Up - Reversal
400	0002	Transaksi Gagal	Transaction Failed	Copartner is not registered	- Session Key - Top Up - Reversal - ACK
400	0012	Transaksi Gagal	Transaction Failed	Copartner is blocked	- Session Key - Top Up - Reversal - ACK
400	0022	Transaksi Gagal	Transaction Failed	Copartner max retry exceeded	- Session Key - Top Up - Reversal - ACK
400	0032	Transaksi Gagal	Transaction Failed	Copartner session key not exist	- Top Up - Reversal - ACK
400	1012	Kartu Error	Card Error	Check expired date failed	- Top Up
400	1022	Transaksi gagal, nominal Top Up kurang dari minimum	Transaction failed, Top Up amount less than minimum	Check min amount failed	- Top Up
400	1032	Transaksi gagal, nominal Top Up melebihi saldo maksimum	Transaction failed, Top Up amount exceeds maximum balance	Check max balance failed	- Top Up
400	1052	Transaksi gagal	Transaction failed	Check mandatory field failed	- Session Key - Top Up

					- Reversal - ACK
400	1062	Transaksi gagal	Transaction failed	Parse request data failed	- Session Key - Top Up - Reversal - ACK
400	1102	Transaksi gagal	Transaction failed	Duplicate transaction	- Top Up - Reversal - ACK
400	1122	Transaksi gagal	Transaction failed	Check original data failed	- Reversal - ACK
400	1132	Transaksi gagal	Transaction failed	Check tid failed	- Session Key - Top Up - Reversal - ACK
400	1142	Transaksi gagal	Transaction failed	Check mid failed	- Session Key - Top Up - Reversal - ACK
400	1152	Kartu error	Card error	Card blacklisted	- Top Up
400	1202	Transaksi Gagal	Transaction Failed	TID and MID doesn't exist	- Session Key - Top Up - Reversal - ACK
400	1222	Transaksi Gagal, nilai topup berbeda	Transaction Failed Amount mismatch	Amount merchant not match	- Top Up
400	3023	Transaksi gagal	Transaction failed	Request topup debit timeout failed	- Top Up - Reversal - ACK
400	3045	Transaksi gagal	Transaction failed	Check atuf timeout failed	- Top Up
400	4009	Field (0) harus diisi	Missing mandatory field (0)	Field (0) harus diisi	- Top Up - Reversal - ACK

400	4038	Panjang field (0) tidak valid	Field (0) length not valid	Panjang field (0) tidak valid	- Top Up - Reversal - ACK
400	4039	Isian input (0) tidak valid	Input for field (0) not valid	Isian input (0) tidak valid	- Top Up - Reversal - ACK
400	4045	Maaf, transaksi anda tidak dapat diproses	Sorry, your transaction can not be processed	Identifier Channel tidak diizinkan mengakses	- Top Up - Reversal - ACK
400	4112	Inputan String JSON tidak valid	Invalid JSON String input	Format JSON input invalid	- Top Up - Reversal - ACK
400	4113	Transaksi ditolak	Transaction rejected	ClientID tidak dapat mengakses ke service	- Top Up - Reversal - ACK
400	4414	Transaksi gagal	Transaction failed	Gagal saat konversi(format data yang diterima tidak sesuai)	- Top Up - Reversal - ACK
400	4415	Transaksi gagal	Transaction failed	Record yang ingin dihapus tidak ada.	- Top Up - Reversal - ACK
400	4416	Transaksi gagal	Transaction failed	File Limit TopUp tidak ada	- Top Up - Reversal - ACK
400	4417	Transaksi gagal	Transaction failed	File Limit TopUp tidak bisa dibuka	- Top Up - Reversal - ACK
400	4418	Transaksi gagal	Transaction failed	File Limit TopUp tidak bisa dibaca	- Top Up - Reversal - ACK
400	4419	Transaksi gagal	Transaction failed	Record sudah ada ketika tambah record baru	- Top Up - Reversal - ACK
400	4420	Transaksi gagal	Transaction failed	Record tidak ada ketika Change/ Update	- Top Up - Reversal - ACK
400	4421	Transaksi gagal	Transaction failed	Gagal menulis record	- Top Up - Reversal - ACK

400	4422	Transaksi gagal	Transaction failed	Gagal hapus record	- Top Up - Reversal - ACK
400	4423	Transaksi gagal	Transaction failed	FIID yang dikirimkan tidak sesuai/data FIID tidak ada	- Top Up - Reversal - ACK
400	4424	Transaksi gagal	Transaction failed	Transaksi code tidak sesuai(sesuai dengan data element 91)	- Top Up - Reversal - ACK
400	4425	Transaksi gagal	Transaction failed	FIID tidak terdaftar	- Top Up - Reversal - ACK
400	4427	Transaksi gagal	Transaction failed	ATUF Flazz Type Error	- Top Up - Reversal - ACK
400	4426	Transaksi gagal	Transaction failed	File request tidak sesuai(sesuai dengan data element 101)	- Top Up - Reversal - ACK
400	4428	Transaksi gagal	Transaction failed	Gagal ketika mencoba mencari nomor kartu	- Top Up - Reversal - ACK
400	4429	Transaksi gagal, jumlah top up melebihi limit bulanan	Transaction failed, Top Up amount exceeds monthly limit	Limit kartu akses bulanan habis.	- Top Up - Reversal - ACK
400	4430	Transaksi gagal	Transaction failed	Unik id tidak ditemukan	- Top Up - Reversal - ACK
400	4431	Transaksi gagal	Transaction failed	Koneksi saat dari atau ke b24 terputus	- Top Up - Reversal - ACK
400	4432	Transaksi gagal	Transaction failed	Koneksi saat dari atau ke b24d itolak	- Top Up - Reversal - ACK
400	4433	Status kartu inactive	Card status inactive	Status kartu inactive	- Top Up - Reversal - ACK
400	4434	Limit harian kartu akses telah	Access card limit daily has been	Limit harian kartu akses telah	- Top Up - Reversal

		mencapai batas	reached	mencapai batas	- ACK
400	4435	Kartu akses salah	Incorrect access card	Kartu akses salah	- Top Up - Reversal - ACK
400	4436	Kode akses terblokir	Max incorrect access code	Kode akses terblokir	- Top Up - Reversal - ACK
400	4437	MID tidak cocok	MID unmatched	MID tidak cocok	- Top Up - Reversal - ACK
400	4662	Transaksi tidak dapat diproses. Silahkan coba beberapa saat lagi	Transaction cannot be processed. Please try again later	Error dari EAI apabila terjadi koneksi timeout saat memanggil ke service lain	- Top Up - Reversal - ACK
400	0000	Transaksi Berhasil	Transaction Success	Transaksi berhasil	- Top Up - Reversal - ACK
400	5202	Transaksi 0 rupiah	Transaction amount 0	Transaksi 0 Rupiah	- Top Up
400	5204	Maaf saldo tidak mencukupi	Sorry your balance is not enough	Maaf saldo tidak mencukupi	- Top Up
400	5206	Rekening ditolak	Account Rejected	Rekening ditolak	- Top Up
400	5700	Maaf transaksi harus IDR	Sorry, currency must IDR	Maaf transaksi harus IDR	- Top Up
400	5701	Rekening ditolak	Account Rejected	Rekening ditolak	- Top Up
400	5702	Maaf rekening sudah tidak aktif	Sorry, your account is dormant	Maaf rekening sudah tidak aktif	- Top Up
400	5711	Maaf rekening anda masuk daftar hitam	Sorry, your account is blacklist	Rekening anda diblokir/masuk daftar hitam	- Top Up
400	5999	Sistem sedang tidak tersedia	System unavailable	Sistem sedang tidak tersedia	- Top Up - Reversal

POST /flazz/

Request



```
1  REQUEST FOR GET SESSION KEY
2
3  POST /flazz/getKey HTTP/1.1
4  Host: sandbox.bca.co.id
5  Authorization: Bearer [access_token]
6  Content-Type: application/json
7  Origin: [yourdomain.com]
8  X-BCA-Key: [api_key]
9  X-BCA-Timestamp: [timestamp]
10 X-BCA-Signature: [signature]
11 ChannelID: [channelID]
12 CredentialID: [credentialID]
13 {
14   "reference_id": "123456789012",
15   ...
```

POST /flazz/

Response



```
1  RESPONSE FOR GET SESSION KEY
2
3  {
4    "response_data": ""01010000202001171513224553594230303031454D424341303031885000C
5  }
6
7  RESPONSE FOR REQUEST TOP UP
8
9  {
10   "response_data":
11   "01240145002800000038000000100000000000160230202002191019275D5D6E5DB05D6D7A
12 }
13 RESPONSE FOR REVERSAL
14 ...
```

Kantor Pusat

Menara BCA, Grand Indonesia
Jl. MH Thamrin No. 1
Jakarta 10310

 [Lokasi BCA Lainnya](#)

Hubungi Kami

 (021) 235 88000

 +62 811 1500 998

 API Support

 Hubungi Kami

Media Sosial

 GoodLife BCA

 @BankBCA

 @goodlifebca

 Solusi BCA

[Lihat Semua Media Sosial](#)

BCA berizin dan diawasi oleh Otoritas Jasa Keuangan & Bank Indonesia

BCA merupakan peserta penjaminan LPS. Maksimum nilai simpanan yang dijamin LPS per Nasabah per Bank adalah Rp2 miliar. Untuk cek Tingkat Bunga Penjaminan LPS, klik [di sini](#).

[Kebijakan](#) | [Syarat penggunaan](#) | [Informasi Produk](#)