



# SYMBIOSIS INSTITUTE OF TECHNOLOGY, PUNE

## Symbiosis International (Deemed University)

(Established under section 3 of the UGC Act, 1956)

Re-accredited by NAAC with 'A' grade (3.58/4) | Awarded Category – I by UGC

Founder: Prof. Dr. S. B. Mujumdar, M. Sc., Ph. D. (Awarded Padma Bhushan and Padma Shri by President of India)

### Assignment No. 10

<b>Subject:</b>	Compiler Construction Lab
<b>Name of Student</b>	<b>Onkar Mendhapurkar</b>
<b>PRN No.</b>	<b>22070122135</b>
<b>Branch</b>	CSE B2, Batch (2022-26)
<b>Academic Year &amp; Semester</b>	2022-26
<b>Date of Performance</b>	09/10/2025
<b>Title of Assignment:</b>	Parser for Intermediate code (IC) generator for arithmetic expression.
<b>Practice Questions</b>	<ol style="list-style-type: none"><li>1. YACC program for Intermediate code (IC) generator for arithmetic expression.</li><li>2. YACC program for IC generation for the expression involving parenthesis.</li></ol> <p><b>PostLab Question</b></p> <ol style="list-style-type: none"><li>3. YACC program for IC generation for the expression involving programming constructs.</li></ol>
<b>Source Code</b>	<pre>1. ic.l (Lex) %{ #include "ic.tab.h" %}  %%  [0-9]+          { yylval.ival = atoi(yytext); return NUMBER; } [a-zA-Z_][a-zA-Z0-9_]* { yylval.sval = strdup(yytext); return ID; } "+"            { return '+'; } "-"            { return '-'; }</pre>

```

"*"          { return '*'; }
"/"          { return '/'; }
"("          { return '('; }
")"          { return ')'; }
","          { return ','; }
"\n"         { return '\n'; }
[ \t]+       { /* ignore whitespace */ }
.            { printf("Unknown character: %s\n", yytext); }

%%

int yywrap() { return 1; }

ic.y

%{
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

int tempCount = 0;
char tempName[10];

int yylex();
void yyerror(const char *s);

char* newTemp() {
    sprintf(tempName, "t%d", tempCount++);
    return strdup(tempName);
}

%}

%union {
    char* sval;
    int ival;
}

%token <sval> ID
%token <ival> NUMBER

%left '+' '-'
%left '*' '/'

%type <sval> expr

```

%%

program:

```
    expr '\n' { printf("Final Result: %s\n", $1); }  
    | expr ';' { printf("Final Result: %s\n", $1); }  
    ;
```

expr:

```
    expr '+' expr {  
        char* t = newTemp();  
        printf("%s = %s + %s\n", t, $1, $3);  
        $$ = t;  
    }  
    | expr '-' expr {  
        char* t = newTemp();  
        printf("%s = %s - %s\n", t, $1, $3);  
        $$ = t;  
    }  
    | expr '*' expr {  
        char* t = newTemp();  
        printf("%s = %s * %s\n", t, $1, $3);  
        $$ = t;  
    }  
    | expr '/' expr {  
        char* t = newTemp();  
        printf("%s = %s / %s\n", t, $1, $3);  
        $$ = t;  
    }  
    | '(' expr ')' { $$ = $2; }  
    | ID {  
        char* t = newTemp();  
        printf("%s = %s\n", t, $1);  
        $$ = t;  
    }  
    | NUMBER {  
        char* t = newTemp();  
        printf("%s = %d\n", t, $1);  
        $$ = t;  
    }  
    ;
```

%%

```
void yyerror(const char *s) {
    fprintf(stderr, "Syntax Error: %s\n", s);
}
```

```
int main() {
    printf("Enter arithmetic expression:\n");
    while(!feof(stdin)) yyparse();
    return 0;
}
```

## 2.

### LEX File (ic\_paren.l)

```
%{
#include "ic_paren.tab.h"
}%

%%

[0-9]+      { yylval.ival = atoi(yytext); return NUMBER; }
[a-zA-Z_][a-zA-Z0-9_]* { yylval.sval = strdup(yytext); return ID; }
"+"         { return '+'; }
"-"         { return '-'; }
"*"         { return '*'; }
"/"         { return '/'; }
"("         { return '('; }
")"         { return ')'; }
";"         { return ';'; }
"\n"        { return '\n'; }
[ \t]+      { /* ignore whitespace */ }
.           { printf("Unknown character: %s\n", yytext); }

%%
```

```
int yywrap() { return 1; }
```

### IC Generator with Parentheses (ic\_paren.y)

```
%{
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

int tempCount = 0;
char tempName[10];
```

```

int yylex();
void yyerror(const char *s);

// Function to create new temporary variable
char* newTemp() {
    sprintf(tempName, "t%d", tempCount++);
    return strdup(tempName);
}
%}

%union {
    char* sval;
    int ival;
}

%token <sval> ID
%token <ival> NUMBER

%left '+' '-'
%left '*' '/'
%type <sval> expr

%%

program:
    expr '\n' { printf("Final Result: %s\n", $1); }
    | expr ';' { printf("Final Result: %s\n", $1); }
    ;

expr:
    expr '+' expr {
        char* t = newTemp();
        printf("%s = %s + %s\n", t, $1, $3);
        $$ = t;
    }
    | expr '-' expr {
        char* t = newTemp();
        printf("%s = %s - %s\n", t, $1, $3);
        $$ = t;
    }
    | expr '*' expr {
        char* t = newTemp();
        printf("%s = %s * %s\n", t, $1, $3);
        $$ = t;
    }

```

```

    }
| expr '/' expr {
    char* t = newTemp();
    printf("%s = %s / %s\n", t, $1, $3);
    $$ = t;
}
| '(' expr ')' { $$ = $2; } // Handle parentheses
| ID {
    char* t = newTemp();
    printf("%s = %s\n", t, $1);
    $$ = t;
}
| NUMBER {
    char* t = newTemp();
    printf("%s = %d\n", t, $1);
    $$ = t;
}
;

%%

void yyerror(const char *s) {
    fprintf(stderr, "Syntax Error: %s\n", s);
}

int main() {
    printf("Enter arithmetic expression (with parentheses allowed):\n");
    while(!feof(stdin)) yyparse();
    return 0;
}

```

### 3. PostLab Experiment

#### ic\_constructs.l – LEX File

```

%{
#include "ic_constructs.tab.h"
}%

%%

"if"           { return IF; }
"while"        { return WHILE; }
[0-9]+         { yylval.ival = atoi(yytext); return NUMBER; }
[a-zA-Z_][a-zA-Z0-9_]* { yylval.sval = strdup(yytext); return ID; }

```

```

"="          { return '='; }
";"          { return ';'; }
"\"          { return '('; }
"\"          { return ')'; }
"\"          { return '{'; }
"\"          { return '}'; }

"+"          { return '+'; }
"_"          { return '-'; }
"*"          { return '*'; }
"/"          { return '/'; }

[ \\t\\n]+    { /* ignore whitespace */ }

.             { printf("Unknown character: %s\\n", yytext); }

%%

```

```

int yywrap() { return 1; }

```

### **ic\_constructs.y – YACC File**

```

%{
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

int tempCount = 0;
int labelCount = 0;

char tempName[10];
char labelName[10];

int yylex();
void yyerror(const char *s);

// Generate new temporary variable
char* newTemp() {
    sprintf(tempName, "t%d", tempCount++);
    return strdup(tempName);
}

// Generate new label

```

```

char* newLabel() {
    sprintf(labelName, "L%d", labelCount++);
    return strdup(labelName);
}
%}

%union {
    char* sval;
    int ival;
}

%token <sval> ID
%token <ival> NUMBER
%token IF WHILE

%left '+' '-'
%left '*' '/'
%type <sval> expr stmt program

%%

program:
    /* empty */
    | program stmt
    ;

stmt:
    ID '=' expr ';' {
        printf("%s = %s\n", $1, $3);
    }
    | IF '(' expr ')' '{' program '}' {
        char* L1 = newLabel();
        printf("if %s == 0 goto %s\n", $3, L1);
        // Statements inside IF already printed
        printf("%s:\n", L1);
    }
    | WHILE '(' expr ')' '{' program '}' {
        char* L1 = newLabel();
        char* L2 = newLabel();
        printf("%s:\n", L1);
        printf("if %s == 0 goto %s\n", $3, L2);
        // Statements inside WHILE already printed
        printf("goto %s\n", L1);
        printf("%s:\n", L2);
    }

```

```




    }
    | expr ';' { /* just evaluate expression */ }
;

expr:
    expr '+' expr {
        char* t = newTemp();
        printf("%s = %s + %s\n", t, $1, $3);
        $$ = t;
    }
    | expr '-' expr {
        char* t = newTemp();
        printf("%s = %s - %s\n", t, $1, $3);
        $$ = t;
    }
    | expr '*' expr {
        char* t = newTemp();
        printf("%s = %s * %s\n", t, $1, $3);
        $$ = t;
    }
    | expr '/' expr {
        char* t = newTemp();
        printf("%s = %s / %s\n", t, $1, $3);
        $$ = t;
    }
    | '(' expr ')' { $$ = $2; }
    | ID {
        char* t = newTemp();
        printf("%s = %s\n", t, $1);
        $$ = t;
    }
    | NUMBER {
        char* t = newTemp();
        printf("%s = %d\n", t, $1);
        $$ = t;
    }
;

%%

void yyerror(const char *s) {
    fprintf(stderr, "Syntax Error: %s\n", s);
}

```

	<pre>int main() {     printf("Enter statements (assignments, if, while):\n");     while(!feof(stdin)) yyparse();     return 0; }</pre>
Output Screenshot	<p>1.</p>  <pre>battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ gedit ic.y battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ gedit ic.l battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ bison -d ic.y battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ flex ic.l battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ gcc lex.yy.c ic.tab.c -o ic -lfl battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ ls ic* ic.l ic.tab.c ic.tab.h ic.y lex.yy.c battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ ./ic Enter arithmetic expression: a + b * c t0 = a t1 = b t2 = c t3 = t1 * t2 t4 = t0 + t3 Final Result: t4 battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$  </pre> <p>2.</p>  <pre>battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ nano ic_paren.y battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ nano ic_paren.l battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ bison -d ic_paren.y battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ flex ic_paren.l battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ gcc lex.yy.c ic_paren.tab.c -o ic_paren -lfl battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ ls ic ic.l ic.tab.c ic.tab.h ic.y ic_paren ic_paren.l ic_paren.tab.c ic_paren.tab.h ic_paren.y lex.yy.c battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ ./ic_paren Enter arithmetic expression (with parentheses allowed): (a + b) * c t0 = a t1 = b t2 = t0 + t1 t3 = c t4 = t2 * t3 Final Result: t4 battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$  </pre> <p>3. PostLab Experiment</p>  <pre>battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ nano ic_constructs.l battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ nano ic_constructs.y battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ bison -d ic_constructs.y battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ flex ic_constructs.l battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ gcc lex.yy.c ic_constructs.tab.c -o ic_constructs -lfl battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ ls ic ic.tab.c ic.y ic_constructs.l ic_constructs.tab.c ic_constructs.y ic_paren ic_paren.l ic_paren.tab.c ic_paren.y ic.l ic.tab.h ic_constructs ic_constructs.tab.c ic_constructs.y ic_paren.l ic_paren.tab.h lex.yy.c battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$ ./ic_constructs Enter statements (assignments, if, while): a=2;b=3;c=a+b;if(c){d=c*2;} t0 = 2 a = t0 t1 = 3 b = t1 t2 = a t3 = b t4 = t2 + t3 c = t4 t5 = c t6 = c t7 = 2 t8 = t6 * t7 d = t8 if t5 == 0 goto L0 L0: battlemachine@DESKTOP-FU1975B:~/CCL/Exp10\$  </pre>

Conclusion	These experiments demonstrate the use of YACC and LEX to parse, evaluate, and generate intermediate code for arithmetic expressions and programming constructs, highlighting syntax checking, expression evaluation, and three-address code generation in a single integrated workflow.
------------	---