BrainAI

ProSuite Industrial

PROSUITE INDUSTRIAL

PRODUCT DOCUMENTATION

BrainAI (Inhaber: Sascha Alexander Köhne)

BrainAI Inhaber: Sascha Alexander Köhne	PROSUITE INDUSTRIAL	🟢 PUBLIC CLASSIFICATION
Core Architecture & Development	**Technical Documentation**	Access Level: Public / Beta

---

Edition Matrix & Competitive Advantages

Version	Status	Target Audience	Focus
1.0.0	Stable	Enterprise & OT Security	Compliance & Performance

1. Technical Edition Limitations

The differentiation of the versions is hardcoded via the `ProEDC_Status` structure and edition flags during the build process. The following threshold limits are active for the encryption process:

Feature	TRIAL	INDUSTRIAL	PRO
Max. Data Volume	**100 MB** total data throughput	**10 GB** total data throughput	**Unlimited**
Kernel Bypass (Ring-0)	Disabled (Software only)	Disabled (Software only)	**Active via ProKM**
Audit Logging (Pairing)	Basic Log (Name only)	Basic Log (Name only)	**Full (In/Out Hashes)**
Secure Wiping (-D)	Not supported	Not supported	**Active (7-Pass Shredding)**
Support Interface	Community	Business	**Priority (Real-time)**

Note: Upon reaching the volume limits, the API returns the status `PEDC_ERR_LIMIT_REACHED` (-7), and further encryption processes are strictly blocked.

2. Strategic Advantages (The ProSuite Advantage)

ProEDC fundamentally differentiates itself from standard solutions through the rigorous implementation of the Zero-Trust philosophy at the code level:

2.1 Mathematically Provable Integrity

- **Hash Pairing:** Unlike tools that merely report a successful operation, ProEDC (PRO) persistently stores the pair consisting of the original hash and the ciphertext hash. This is the only way to unequivocally prove the unadulterated state of the data chain during a compliance audit (e.g., GDPR or TISAX).
- **ProHash Standard:** We do not rely on generic hashing procedures. Instead, we utilize the optimized ProHash algorithm, which has been specifically engineered and tested for side-channel resistance.

2.2 Physical Sovereignty

- **Kernel-Direct I/O:** By communicating directly with the `ProKM` driver, the PRO edition bypasses the file system latencies of the operating system. Data is passed directly to the kernel for the encryption process, effectively minimizing the attack surface in volatile memory (RAM).
- **Autonomous Entropy:** The suite does not rely on the operating system's standard random number generator. By integrating **ProKey**, hardware-level jitter is utilized for key generation, providing robust protection against state-sponsored backdoors often found in standard APIs.

2.3 Compliance & Anti-Forensics

- **Secure Wipe:** While standard delete commands merely remove the file pointer from the OS index, ProEDC (PRO) actively overwrites the source file's physical sectors with zeros. Even with advanced forensic methods, recovering the original data after executing the `-D` command is rendered impossible.

3. Market Comparison

Feature	Standard (OpenSSL / GPG)	Cloud-Provider Tools	ProEDC Suite
Architecture	Ring-3 (User)	API-Based	**Hybrid (Ring-0 & 3)**
Data Control	Local (Software)	External (Provider)	**Hardware Sovereign**
License Stop	No	Subscription Model	**Volume-based (-7)**
Audit Trail	External / Manual	Proprietary	**Native In/Out Hashes**

© 2026 Sascha Köhne	✉️ **Contact:** koehne83@googlemail.com	🛡️ **ProTU-Verified**
CEO / System Architect	BrainAI Inhaber : Sascha Alexander Köhne	We don't need **BRUTEFORCE**, we know **PHYSICS**