

<u>Dashboard</u> / <u>RDBMS</u> / <u>Joins & Subquery</u> / <u>Post-Quiz</u>

Started on	Monday, 16 March 2020, 4:46 PM
State	Finished
Completed on	Monday, 16 March 2020, 4:50 PM
Time taken	4 mins 6 secs
Marks	9.50/10.00
Grade	95.00 out of 100.00
Feedback	Congratulations!!! You have passed by securing more than 80%

Question **1**

Correct

Mark 1.00 out of 1.00

In which two cases would you use the USING clause? (Choose two)

Select one or more:

- a. You want to create a nonequijoin.

- d. The tables to be joined have multiple NULL columns.

Your answer is correct.

The correct answers are: The tables to be joined have columns of the same name and different data types., The tables to be joined have columns with the same name and compatible data types.

Question **2**

Correct

Mark 1.00 out of 1.00

Which SELECT statement displays all the employees who do not have any subordinates?

Select one:

a. SELECT e.ename
 FROM emp e
 WHERE e.mgr IS NOT NULL;

b. SELECT e.ename

FROM emp e
WHERE e.empno NOT IN (SELECT m.mgr
FROM emp m
WHERE m.mgr IS NOT NULL); ✓

c. SELECT e.ename
 FROM emp e
 WHERE e.empno IN (SELECT m.mgr
 FROM emp m);

d. SELECT e.ename
 FROM emp e
 WHERE e.empno NOT IN (SELECT m.mgr
 FROM emp m);

Your answer is correct.

The correct answer is: SELECT e.ename FROM emp e
WHERE e.empno NOT IN (SELECT m.mgr FROM emp m
WHERE m.mgr IS NOT NULL);



Correct Mark 1.00 out of 1.00 WHERE salary IN (SELECT salary FROM employee WHERE dept_no = 3 OR dept_no = 5); Which values are displayed?

Select one:

- a. last name and first name of all employees except those working in department 3 or 5
- b. last name and first name of only the employees whose salary falls in the range of salaries from department 3 or 5
- c. last name and first name of only the employees in department number 3 or 5
- d. last name and first name of all employees with the same salary as employees in department 3 or 5

Your answer is correct.

The correct answer is: last name and first name of all employees with the same salary as employees in department 3 or 5

Question **4**

Correct

Mark 1.00 out of 1.00

Consider the below tables:

Employee Table

Column Name	DataType	Constraint
Name	Varchar2(20)	
Empno	Number(10)	PK
salary	Number(10,2)	

Tax Table

Column Name	DataType	Constraint
Taxgrade	Number	
Lowsal	Number(10)	
highsal	Number(10,2)	

We want to create a report that displays the employee details along with the tax category of each employee. The tax category is determined by comparing the salary of the employee from the EMP table to the lower and upper salary values in the TAX table.

Which SELECT statement produces the required results?

Select one:

- a. SELECT e.name, e.salary, t.taxgrade
 FROM emp e, tax t
 WHERE e.salary IN t.lowsal AND t.highsal;
- b. SELECT e.name, e.salary, t.taxgrade
 FROM emp e, tax t
 WHERE e.salary BETWEEN t.lowsal AND t.highsal;
- c. SELECT e.name, e.salary, t.taxgrade
 FROM emp e, tax t
 WHERE e.salary <= t.lowsal AND e.salary >= t.highsal;
- d. SELECT e.name, e.salary, t.taxgrade
 FROM emp e, tax t
 WHERE e.salary >= t.lowsal AND <= t.highsal;

Your answer is correct.

The correct answer is: SELECT e.name, e.salary, t.taxgrade FROM emp e, tax t
WHERE e.salary BETWEEN t.lowsal AND t.highsal;



Correct Mark 1.00 out of 1.00 FROM employee
WHERE commission =
(SELECTcommission
FROMemployee
WHEREUPPER(first_name) = 'SCOTT')

What would cause this statement to fail?

Select one:

- a. The FIRST_NAME values in the database are in lowercase.
- b. There is more than one employee with the first name Scott.
- c. Scott has a NULL commission value.
- d. There is no employee with the first name Scott.
- e. Scott has a zero commission value.

Your answer is correct.

The correct answer is: There is more than one employee with the first name Scott.

Question **6**

Correct

Mark 1.00 out of 1.00

To display the names of employees who earns more than the average salary of all employees.

SELECT last_name, first_name

FROMemployee

WHEREsalary > AVG(salary);

Which change should you make to achieve the desired results?

Select one:

- a. Change the function in the WHERE clause.
- b. Move the function to the SELECT clause and add a GROUP BY clause and a HAVING clause.
- d. Move the function to the SELECT clause and add a GROUP BY clause.

Your answer is correct.

The correct answer is: Use a subquery in the WHERE clause to compare the average salary value.

Question **7**

Correct

Mark 1.00 out of 1.00

Which operator is NOT appropriate in the join condition of a non-equi join SELECT statement?

Select one:

- a. BETWEEN x AND y operator
- b. IN operator
- c. LIKE operator
- d. equal operator
- e. greater than or equal to operator

Your answer is correct.

The correct answer is: equal operator

Partially correct Mark 0.50 out of 1.00

>

Product Table

Column Name	DataType	Constraint
prod_name	Varchar2(20)	
prod_id	Number(10)	PK

Customer Table

Column Name	DataType	Constraint
cust_last_name	Varchar2(20)	
cust_id	Number(10)	PK
cust_city	Varchar2(20)	

Sales Table

Column Name	DataType	Constraint
prod_id	Number(10)	FK
cust_id	Number(10)	FK
quantity_sold	Number(10,2)	

Generate a report that gives details of the customer's last name, name of the product and the quantity sold for all customers in 'Tokyo'.

Which two queries give the required result? (Choose two.)

Select one or more:

a. SELECT c.cust_last_name,p.prod_name,s.quantity_sold

FROM products p JOIN sales s

ON(p.prod_id=s.prod_id)

JOIN customers c

ON(s.cust_id=c.cust_id)

WHERE c.cust_city='Tokyo';

■ b. SELECT c.cust_last_name,p.prod_name,s.quantity_sold

FROM products p JOIN sales s JOIN customers c

ON(p.prod_id=s.prod_id)

ON(s.cust_id=c.cust_id)

WHERE c.cust_city='Tokyo';

c. SELECT c.cust_last_name,p.prod_name,s.quantity_sold

FROM products p JOIN sales s

USING (prod_id)

ON(p.prod_id=s.prod_id)

JOIN customers c

USING(cust_id)

WHERE c.cust_city='Tokyo';

d. SELECT c.cust_last_name,p.prod_name,s.quantity_sold

FROM sales s JOIN products p

USING (prod_id)

JOIN customers c

USING (cust_id)

WHERE c.cust_city='Tokyo'; ✓

Your answer is partially correct.

You have correctly selected 1.

The correct answers are: SELECT c.cust_last_name,p.prod_name,s.quantity_sold

FROM sales s JOIN products p

USING (prod_id)

JOIN customers c

USING (cust_id)

WHERE c.cust_city='Tokyo';, SELECT c.cust_last_name,p.prod_name,s.quantity_sold

FROM products p JOIN sales s

ON(p.prod_id=s.prod_id)

JOIN customers c

Question **9**

Correct

Mark 1.00 out of 1.00

In which cases would you use an outer join?

Select one:

- $\hfill \bigcirc$ a. The tables being joined have NOT NULL columns.
- b. The tables being joined have only matched data.
- c. The tables being joined have both matched and unmatched data.
- od. Only when the tables have a primary key/foreign key relationship.
- e. The tables being joined have only unmatched data.

Your answer is correct.

The correct answer is: The tables being joined have both matched and unmatched data.

Question 10

Correct

Mark 1.00 out of 1.00

The NOT operator can be used with _____ operators.

Select one or more:

- a. >
- ø b. ANY

 ✓
- ✓ c. ALL ✓
- ✓ d. IN ✓

Your answer is correct.

The correct answers are: IN, ANY, ALL