

HighLevel Page Builder — Complete Developer Schema Reference

Purpose: This document provides an exhaustive, developer-grade reference for every element, container, property, value type, default, and constraint in the HighLevel Funnel & Website Page Builder. It is intended to give a developer building a HighLevel-compatible page everything they need to replicate the builder's output faithfully.

Table of Contents

1. [Page Architecture & Nesting Hierarchy](#)
2. [Page-Level Settings](#)
3. [Common Base Properties \(Shared by All Elements & Containers\)](#)
4. [Advanced Styling Properties \(Shared\)](#)
5. [Animation Properties \(Shared\)](#)
6. [Layout Containers](#)
 - 6.1 Section
 - 6.2 Row
 - 6.3 Column
7. [Basic Elements](#)
 - 7.1 Headline / Sub Headline
 - 7.2 Paragraph
 - 7.3 Rich Text
 - 7.4 Bullet List
 - 7.5 Image
 - 7.6 Video
 - 7.7 Button
 - 7.8 Divider / Separator
 - 7.9 Spacer
 - 7.10 Custom HTML / Code Block
8. [Form & Conversion Elements](#)
 - 8.1 Form (Embed)

- 8.2 Survey (Embed)
- 8.3 Order Form (Two-Step)
- 8.4 Calendar (Embed)

9. Advanced Widget Elements

- 9.1 Image Slider
- 9.2 Countdown Timer
- 9.3 Pricing Table
- 9.4 Testimonials
- 9.5 Social Media Icons
- 9.6 Number Counter
- 9.7 Logo Showcase
- 9.8 Photo Gallery
- 9.9 Blog Post Feed
- 9.10 QR Code
- 9.11 Navigation Menu
- 9.12 FAQ / Accordion
- 9.13 Progress Bar
- 9.14 Map

10. Interactive Behavior

- 10.1 Show / Hide Element on Button Click
- 10.2 Scroll to Element / Section
- 10.3 Popup

11. Universal (Global) Elements

12. Responsive & Mobile Overrides

13. Global Page Styles & Brand Board

1. Page Architecture & Nesting Hierarchy

Every HighLevel page is structured as a strict tree. Understanding this hierarchy is mandatory before placing any element.

Plain Text

Page

- └ Section (full-width horizontal band)
 - └ Row (horizontal flex container inside section)
 - └ Column (vertical flex cell inside row)
 - └ Element (leaf node – text, image, button, widget, etc.)

Rules:

- Elements **cannot** be placed directly inside a Section or Page — they must be inside a Column.
- Columns **cannot** exist outside a Row.
- Rows **cannot** exist outside a Section.
- Nesting depth beyond Column → Element is not supported natively (except via Custom HTML).
- A Row can contain 1–6 Columns. Column widths within a Row must sum to 100%.

2. Page-Level Settings

These settings live in the **SEO Meta Data** panel and **Page Settings** panel at the top of the builder. They are not elements but are required for a complete page definition.

2.1 SEO & Meta Properties

Property	Type	Max Length	Notes
seo_title	string	60 chars recommended	Rendered as <code><title></code> tag
seo_description	string	160 chars recommended	Rendered as <code><meta name="description"></code>
seo_keywords	string	Comma-separated	Rendered as <code><meta name="keywords"></code>
og_title	string	60 chars	Open Graph title for social sharing
og_description	string	160 chars	Open Graph description

<code>og_image_url</code>	<code>string (URL)</code>	—	Open Graph image (1200×630px recommended)
<code>canonical_url</code>	<code>string (URL)</code>	—	Prevents duplicate content indexing
<code>robots_meta</code>	<code>string</code>	—	e.g. <code>noindex</code> , <code>nofollow</code> , <code>noindex, nofollow</code>
<code>author</code>	<code>string</code>	—	Author meta tag value
<code>favicon_url</code>	<code>string (URL)</code>	—	<code>.ico</code> , <code>.png</code> , or <code>.svg</code>
<code>lang_attribute</code>	<code>string</code>	2–5 chars	HTML <code>lang</code> attribute, e.g. <code>en</code> , <code>en-US</code>
<code>custom_meta_tags</code>	<code>array of objects</code>	Up to many	Each object: <code>{ name: string, content: string }</code>

2.2 Custom Code Injection

Property	Type	Notes
<code>head_tracking_code</code>	<code>string (HTML/JS)</code>	Injected inside <code><head></code> — for pixels, analytics
<code>body_tracking_code</code>	<code>string (HTML/JS)</code>	Injected at end of <code><body></code>
<code>footer_code</code>	<code>string (HTML/JS)</code>	Additional footer scripts

2.3 Page Behavior Settings

Property	Type	Default	Notes
<code>page_background_color</code>	<code>string (hex/rgba)</code>	<code>#ffffff</code>	Page-level background
<code>page_font_family</code>	<code>string</code>	Inherited from brand board	Global font override

page_max_width	number (px)	1170	Max content width
hide_nav	boolean	false	Hides navigation on funnel steps

3. Common Base Properties

These properties are available on **every** element and container (Section, Row, Column, and all leaf elements) unless explicitly noted otherwise.

3.1 Visibility

Property	Type	Values	Default	Notes
visible_desktop	boolean	true / false	true	Show/hide on desktop
visible_mobile	boolean	true / false	true	Show/hide on mobile

Important: Setting both `visible_desktop` and `visible_mobile` to `false` hides the element from the canvas. It can still be accessed via the Layers panel and targeted by Show/Hide button actions.

3.2 Spacing (Padding & Margin)

All spacing values accept a number and a unit. Units supported: `px`, `%`, `em`, `rem`, `vh`, `vw`, `auto`.

Property	Type	Default	Notes
padding_top	number + unit	0px	Inner top spacing
padding_right	number + unit	0px	Inner right spacing
padding_bottom	number + unit	0px	Inner bottom spacing
padding_left	number + unit	0px	Inner left spacing
margin_top	number + unit	0px	Outer top spacing

margin_right	number + unit	auto	Outer right spacing
margin_bottom	number + unit	0px	Outer bottom spacing
margin_left	number + unit	auto	Outer left spacing

Each of these has a corresponding mobile override: padding_top_mobile , margin_bottom_mobile , etc.

3.3 Container Size

Property	Type	Units	Default	Notes
width	number + unit	px , % , em , rem , vw , auto	auto	Element width
height	number + unit	px , % , em , rem , vh , auto	auto	Element height
width_mobile	number + unit	Same as above	auto	Mobile-specific width
height_mobile	number + unit	Same as above	auto	Mobile-specific height

Negative values and 0 are not supported for width/height. Use auto to revert to natural size.

3.4 Identification & Custom Styling

Property	Type	Notes
element_id	string	Auto-generated unique ID. Used as CSS selector for scroll-to and show/hide targeting. Format: #section_abc12
custom_css_class	string	User-defined CSS class name(s), space-separated

custom_css_id	string	User-defined CSS ID for custom targeting
---------------	--------	--

4. Advanced Styling Properties

These properties are available in the **Advanced** tab of the right-hand sidebar for most elements and containers.

4.1 Border

Property	Type	Values	Default
border_style	string	none , solid , dashed , dotted , double	none
border_width_top	number (px)	0–100	0
border_width_right	number (px)	0–100	0
border_width_bottom	number (px)	0–100	0
border_width_left	number (px)	0–100	0
border_color	string (hex/rgba)	Any valid color	#000000
border_radius_top_left	number (px)	0–500	0
border_radius_top_right	number (px)	0–500	0
border_radius_bottom_right	number (px)	0–500	0
border_radius_bottom_left	number (px)	0–500	0

4.2 Box Shadow

Multiple box shadows can be stacked on a single element. Each shadow object has the following structure:

Property	Type	Values	Default
shadow_type	string	outer , inner	outer
shadow_x	number (px)	Any integer	0
shadow_y	number (px)	Any integer	4
shadow_blur	number (px)	0–100	10
shadow_spread	number (px)	Any integer	0
shadow_color	string (hex/rgba)	Any valid color	rgba(0,0,0,0.25)

4.3 Text Shadow (Typography Elements Only)

Property	Type	Values	Default
text_shadow_x	number (px)	Any integer	0
text_shadow_y	number (px)	Any integer	2
text_shadow_blur	number (px)	0–100	4
text_shadow_color	string (hex/rgba)	Any valid color	rgba(0,0,0,0.3)

4.4 Background (Containers: Section, Row, Column)

Backgrounds are applied at the container level. Three background types are available, selectable via tabs:

Color Background:

Property	Type	Values	Default
bg_type	string	color , image , video	color
bg_color	string (hex/rgba)	Any valid color	transparent
bg_gradient_enabled	boolean	true / false	false
bg_gradient_type	string	linear , radial , angular	linear

bg_gradient_angle	number (degrees)	0–360	90 (N/A for radial)
bg_gradient_stops	array of objects	Max 10 stops	[]
bg_blur_enabled	boolean	true / false	false
bg_blur_intensity	number (px)	0–100	10

Each gradient stop object: { color: "hex/rgba", position: 0–100 } (position is a percentage along the gradient).

Image Background:

Property	Type	Values	Default
bg_image_url	string (URL)	—	""
bg_image_position	string	center center , top left , top center , top right , center left , center right , bottom left , bottom center , bottom right	center center
bg_image_size	string	cover , contain , auto , 100% 100%	cover
bg_image_repeat	string	no-repeat , repeat , repeat-x , repeat-y	no-repeat
bg_image_attachment	string	scroll , fixed (parallax)	scroll
bg_overlay_color	string (hex/rgba)	Any valid color	transparent
bg_overlay_opacity	number	0–1	0

Video Background:

Property	Type	Values	Default
bg_video_url	string (URL)	YouTube, Vimeo, or direct .mp4 URL	""

bg_video_fit	string	fill , cover , contain	cover
bg_video_autoplay	boolean	true / false	true
bg_video_loop	boolean	true / false	true
bg_video_muted	boolean	true / false	true
bg_video_overlay_color	string (hex/rgba)	Any valid color	transparent
bg_video_overlay_opacity	number	0–1	0
bg_video_fallback_image	string (URL)	Shown on mobile (video BG disabled on mobile)	""

5. Animation Properties

Animation settings are available in the **Animations** tab of the right-hand sidebar for any element. Only one entrance animation can be applied per element.

5.1 Entrance Animation

Property	Type	Values	Default
animation_enabled	boolean	true / false	false
animation_type	string	See table below	none
animation_scale	number	0.5–2.0 (step 0.1)	1.0
animation_duration	number (seconds)	0.1–3.0 (step 0.1)	0.5
animation_delay	number (seconds)	0–5.0 (step 0.1)	0
animation_easing	string	linear , ease_in , ease_out , ease_in_out	ease_out

Available Animation Types:

Category	Values
Fade	fade_in , fade_in_up , fade_in_down , fade_in_left , fade_in_right
Slide	slide_in_up , slide_in_down , slide_in_left , slide_in_right
Bounce	bounce_in , bounce_in_up , bounce_in_down , bounce_in_left , bounce_in_right
Zoom	zoom_in , zoom_in_up , zoom_in_down , zoom_in_left , zoom_in_right
Flip	flip_in_x , flip_in_y
Rotate	rotate_in , rotate_in_down_left , rotate_in_down_right
Special	pulse , shake , wobble , swing , jello , heartbeat

Delay behavior: Elements remain fully hidden during the configured delay period and only become visible once the animation begins. This prevents flash-of-content issues.

6. Layout Containers

6.1 Section

A Section is the outermost layout container — a full-width horizontal band spanning the page.

Property	Type	Values	Default	Notes
section_id	string	Auto-generated	—	Used as CSS selector for scroll-to
full_width	boolean	true / false	false	Stretches content to viewport edge
content_max_width	number (px)	600–2560	1170	Max inner content width

<code>min_height</code>	number + unit	<code>px</code> , <code>vh</code>	<code>auto</code>	Minimum section height
<code>sticky</code>	boolean	<code>true</code> / <code>false</code>	<code>false</code>	Sticks section to top on scroll
<code>column_gap</code>	number (px)	0–100	0	Gap between columns inside rows
<code>row_gap</code>	number (px)	0–100	0	Gap between rows inside section
<code>overflow</code>	string	<code>visible</code> , <code>hidden</code>	<code>visible</code>	Clips child elements if <code>hidden</code>
<code>z_index</code>	number	Any integer	0	Stacking order
All background properties	—	See § 4.4	—	Color, image, or video background
All base properties	—	See § 3	—	Padding, margin, visibility, etc.

6.2 Row

A Row is a horizontal flex container inside a Section. It holds one or more Columns.

Property	Type	Values	Default	Notes
<code>column_layout</code>	string	<code>1</code> , <code>1-1</code> , <code>1-1-1</code> , <code>1-1-1-1</code> , <code>2-1</code> , <code>1-2</code> , <code>1-2-1</code> , <code>3-1</code> , <code>1-3</code> , <code>2-1-1</code> , <code>1-1-2</code>	<code>1</code>	Preset column width ratios
<code>vertical_align</code>	string	<code>top</code> , <code>middle</code> , <code>bottom</code> , <code>stretch</code>	<code>top</code>	Vertical alignment of columns

<code>reverse_on_mobile</code>	boolean	<code>true</code> / <code>false</code>	<code>false</code>	Reverses column order on mobile
<code>stack_on_mobile</code>	boolean	<code>true</code> / <code>false</code>	<code>true</code>	Stacks columns vertically on mobile
All background properties	—	See § 4.4	—	
All base properties	—	See § 3	—	

6.3 Column

A Column is a vertical flex cell inside a Row. It holds elements.

Property	Type	Values	Default	Notes
<code>width_percent</code>	number	8.33–100	Determined by row layout	Must sum to 100% with sibling columns
<code>width_percent_mobile</code>	number	8.33–100	100	Mobile column width
<code>vertical_align</code>	string	<code>top</code> , <code>middle</code> , <code>bottom</code>	<code>top</code>	Vertical alignment of content
<code>horizontal_align</code>	string	<code>left</code> , <code>center</code> , <code>right</code>	<code>left</code>	Horizontal alignment of content
All background properties	—	See § 4.4	—	
All base properties	—	See § 3	—	

7. Basic Elements

7.1 Headline / Sub Headline

Used for H1–H6 heading text. "Headline" defaults to H1/H2; "Sub Headline" defaults to H3/H4.

Property	Type	Values	Default	Notes
text	string	Any text	"Headline"	Supports inline HTML
heading_tag	string	h1 , h2 , h3 , h4 , h5 , h6	h2 (Headline), h3 (Sub Headline)	Semantic HTML tag
font_family	string	Any loaded font name	Inherited from global	
font_weight	string	100 , 200 , 300 , 400 , 500 , 600 , 700 , 800 , 900 , bold , normal	700	
font_size	number (px)	8–200	36	
font_size_mobile	number (px)	8–200	28	
font_color	string (hex/rgba)	Any valid color	#000000	
text_align	string	left , center , right , justify	left	
text_align_mobile	string	Same as above	center	
line_height	number	0.5–5.0	1.4	Unitless multiplier
letter_spacing	number (px)	-10–50	0	
text_transform	string	none , uppercase , lowercase , capitalize	none	

<code>link_url</code>	<code>string (URL)</code>	—	<code>""</code>	Makes entire heading a hyperlink
<code>link_target</code>	<code>string</code>	<code>_self</code> , <code>_blank</code>	<code>_self</code>	
All base properties	—	See § 3	—	
All advanced styling	—	See § 4	—	Shadow, border, animation

7.2 Paragraph

Used for body text blocks.

Property	Type	Values	Default	Notes
<code>text</code>	<code>string</code>	Any text	<code>"Paragraph text..."</code>	Supports inline HTML and links
<code>font_family</code>	<code>string</code>	Any loaded font	Inherited	
<code>font_weight</code>	<code>string</code>	<code>100 – 900</code> , <code>bold</code> , <code>normal</code>	<code>400</code>	
<code>font_size</code>	<code>number (px)</code>	<code>8–100</code>	<code>16</code>	
<code>font_size_mobile</code>	<code>number (px)</code>	<code>8–100</code>	<code>14</code>	
<code>font_color</code>	<code>string (hex/rgba)</code>	Any valid color	<code>#333333</code>	
<code>text_align</code>	<code>string</code>	<code>left</code> , <code>center</code> , <code>right</code> , <code>justify</code>	<code>left</code>	
<code>line_height</code>	<code>number</code>	<code>0.5–5.0</code>	<code>1.6</code>	
<code>letter_spacing</code>	<code>number (px)</code>	<code>-10–50</code>	<code>0</code>	
<code>text_transform</code>	<code>string</code>	<code>none</code> , <code>uppercase</code> , <code>lowercase</code> , <code>capitalize</code>	<code>none</code>	

All base properties	—	See § 3	—	
All advanced styling	—	See § 4	—	

7.3 Rich Text

A more powerful text element supporting headings, quotes, code blocks, nested lists, and text highlighting within a single element.

Property	Type	Values	Default	Notes
<code>content</code>	<code>string (HTML)</code>	Full HTML content	<code>""</code>	Supports H1–H6, p, blockquote, code, pre, ul, ol, li, mark, strong, em, a
<code>font_family</code>	<code>string</code>	Any loaded font	Inherited	
<code>font_size</code>	<code>number (px)</code>	<code>8–100</code>	<code>16</code>	Base font size
<code>font_color</code>	<code>string (hex/rgba)</code>	Any valid color	<code>#333333</code>	Base text color
<code>line_height</code>	<code>number</code>	<code>0.5–5.0</code>	<code>1.6</code>	
<code>list_item_spacing</code>	<code>number (px)</code>	<code>0–100</code>	<code>8</code>	Vertical gap between list items
<code>text_align</code>	<code>string</code>	<code>left</code> , <code>center</code> , <code>right</code> , <code>justify</code>	<code>left</code>	

Supported List Types:

List Type	Marker Options
Unordered	<code>disc</code> (•), <code>circle</code> (○), <code>square</code> (■)

Ordered	decimal (1 2 3), lower-alpha (a b c), upper-alpha (A B C), lower-roman (i ii iii), upper-roman (I II III)
---------	---

Markdown/Keyboard Shortcuts (in editor):

Shortcut	Result
<code>></code> + Enter	Block quote
<code>` text `</code>	Inline code
<code>```</code> + Enter	Full code block
<code>*</code> + Space	Unordered list
Tab	Indent list (nested)
Shift+Tab	Outdent list

7.4 Bullet List

A dedicated list element with custom icon/marker support.

Property	Type	Values	Default	Notes
items	array of strings	—	["Item 1", "Item 2"]	Each item is a text string
list_type	string	unordered , ordered , icon	icon	
icon_type	string	check , arrow , star , dot , custom	check	Used when list_type = icon
icon_color	string (hex/rgba)	Any valid color	#000000	
icon_size	number (px)	8–100	16	
font_family	string	Any loaded font	Inherited	
font_size	number (px)	8–100	16	
font_color	string (hex/rgba)	Any valid color	#333333	

line_height	number	0.5–5.0	1.6	
list_item_spacing	number (px)	0–100	8	Vertical gap between items
text_align	string	left , center , right	left	
All base properties	—	See § 3	—	

7.5 Image

Property	Type	Values	Default	Notes
src	string (URL)	—	""	Image source URL
alt_text	string	—	""	SEO and accessibility alt text
image_width	number (px) or %	—	auto	Rendered width
image_height	number (px) or %	—	auto	Rendered height
object_fit	string	fill , contain , cover , none , scale-down	contain	
alignment	string	left , center , right	center	
lazy_load	boolean	true / false	true	Defers loading until in viewport
click_action	string	none , open_url , open_popup , open_lightbox	none	

<code>click_url</code>	<code>string (URL)</code>	—	<code>""</code>	Used when <code>click_action = open_url</code>
<code>open_in_new_tab</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>false</code>	
<code>popup_id</code>	<code>string</code>	—	<code>""</code>	Used when <code>click_action = open_popup</code>
<code>caption</code>	<code>string</code>	—	<code>""</code>	Optional caption text below image
All base properties	—	See § 3	—	
All advanced styling	—	See § 4	—	Border, shadow, animation

7.6 Video

Property	Type	Values	Default	Notes
<code>video_type</code>	<code>string</code>	<code>youtube</code> , <code>vimeo</code> , <code>wistia</code> , <code>html5</code> , <code>hosted</code>	<code>youtube</code>	
<code>video_url</code>	<code>string (URL)</code>	—	<code>""</code>	YouTube/Vimeo /Wistia URL or direct <code>.mp4</code> URL
<code>autoplay</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>false</code>	
<code>loop</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>false</code>	
<code>muted</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>false</code>	Required for autoplay in most browsers
<code>controls</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	Show/hide player controls

thumbnail_url	string (URL)	—	""	Custom thumbnail image
start_time	number (seconds)	0–86400	0	Start playback at this timestamp
aspect_ratio	string	16:9 , 4:3 , 1:1 , 9:16	16:9	
width	number (px) or %	—	100%	
All base properties	—	See § 3	—	
All advanced styling	—	See § 4	—	Border, shadow, animation

7.7 Button

The Button element is one of the most configurable elements in the builder.

General Properties:

Property	Type	Values	Default	Notes
label	string	—	"Click Here"	Primary button text
sub_text	string	—	""	Secondary text below label
icon_left	string	Icon name or URL	""	Icon displayed left of label
icon_right	string	Icon name or URL	""	Icon displayed right of label
full_width	boolean	true / false	false	Stretches button to column width
alignment	string	left , center , right	center	

Styling Properties:

Property	Type	Values	Default
<code>bg_color</code>	string (hex/rgba)	Any valid color	<code>#FF6B00</code>
<code>text_color</code>	string (hex/rgba)	Any valid color	<code>#ffffff</code>
<code>font_family</code>	string	Any loaded font	Inherited
<code>font_size</code>	number (px)	8–100	18
<code>font_weight</code>	string	100 – 900	700
<code>border_radius</code>	number (px)	0–500	4
<code>padding_top</code>	number (px)	0–200	16
<code>padding_right</code>	number (px)	0–200	32
<code>padding_bottom</code>	number (px)	0–200	16
<code>padding_left</code>	number (px)	0–200	32

Hover State Properties:

Property	Type	Default
<code>hover_bg_color</code>	string (hex/rgba)	Darkened version of <code>bg_color</code>
<code>hover_text_color</code>	string (hex/rgba)	Same as <code>text_color</code>
<code>hover_border_color</code>	string (hex/rgba)	Same as <code>border_color</code>
<code>hover_transition_duration</code>	number (seconds)	0.3

Button Action (Link To) — `button_action` property:

Action Value	Description	Additional Properties Required
<code>url</code>	Navigate to a URL	<code>action_url</code> : string , <code>open_in_new_tab</code> : boolean

phone	Click-to-call	phone_number: string
sms	Click-to-text	sms_number: string , sms_body: string
email	Click-to-email	email_address: string , email_subject: string
submit_form	Submit the form on the page	—
next_step	Go to next funnel step	—
open_popup	Open a popup	popup_id: string
close_popup	Close the current popup	—
scroll_to_element	Smooth scroll to section	scroll_target_id: string (CSS selector)
show_elements	Show hidden elements	show_element_ids: array of strings
hide_elements	Hide visible elements	hide_element_ids: array of strings
download_file	Download a file	file_url: string
upsell	Accept upsell on order form	—
downsell	Decline upsell	—
calendar	Open calendar booking	calendar_id: string
custom_js	Execute custom JavaScript	custom_js_code: string

7.8 Divider / Separator

Property	Type	Values	Default
line_style	string	solid , dashed , dotted , double , none	solid
line_color	string (hex/rgba)	Any valid color	#cccccc
line_width	number (%)	1-100	100

<code>line_thickness</code>	<code>number (px)</code>	<code>1–50</code>	<code>1</code>
<code>alignment</code>	<code>string</code>	<code>left</code> , <code>center</code> , <code>right</code>	<code>center</code>
All base properties	—	See § 3	—

7.9 Spacer

Property	Type	Values	Default
<code>height</code>	<code>number (px)</code>	<code>0–500</code>	<code>40</code>
<code>height_mobile</code>	<code>number (px)</code>	<code>0–500</code>	<code>20</code>
<code>visible_desktop</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>
<code>visible_mobile</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>

7.10 Custom HTML / Code Block

Property	Type	Notes
<code>html_content</code>	<code>string (HTML)</code>	Raw HTML, CSS, and JavaScript
<code>execute_scripts</code>	<code>boolean</code>	Whether <code><script></code> tags are executed on render

8. Form & Conversion Elements

8.1 Form (Embed)

Embeds a HighLevel Form created in the Forms builder.

Property	Type	Values	Default	Notes
<code>form_id</code>	<code>string</code>	HighLevel Form ID	<code>""</code>	Required

redirect_type	string	url , next_step , same_page , popup	next_step	On submit action
redirect_url	string (URL)	—	""	Used when redirect_type = url
popup_id	string	—	""	Used when redirect_type = popup
inline_message	string	—	""	Message shown on same page after submit
double_opt_in	boolean	true / false	false	
style_override	boolean	true / false	false	Use custom CSS for form styling

Form Field Schema (per field inside the Form builder):

Property	Type	Values	Notes
field_type	string	text , email , phone , textarea , select , radio , checkbox , date , file , hidden , signature , address , full_name , first_name , last_name	
label	string	—	Display label
placeholder	string	—	Placeholder text
required	boolean	true / false	
default_value	string	—	Pre-filled value
options	array of strings	—	For select , radio , checkbox
custom_css_class	string	—	

width	string	full , half	Field width in the form grid
field_name	string	—	CRM field mapping key

8.2 Survey (Embed)

Embeds a HighLevel Survey. Properties are identical to Form Embed (§ 8.1) with `survey_id` replacing `form_id` .

8.3 Order Form (Two-Step)

Property	Type	Values	Default	Notes
product_id	string	HighLevel Product ID	""	Required
step_1_label	string	—	"Contact Info"	Label for step 1 tab
step_2_label	string	—	"Payment Info"	Label for step 2 tab
show_order_summary	boolean	true / false	true	
coupon_enabled	boolean	true / false	false	
bump_offer_enabled	boolean	true / false	false	Order bump below form
bump_offer_product_id	string	—	""	
redirect_url	string (URL)	—	""	On successful purchase
upsell_page_id	string	—	""	Next funnel step for upsell

8.4 Calendar (Embed)

Property	Type	Values	Default	Notes
<code>calendar_id</code>	<code>string</code>	HighLevel Calendar ID	<code>""</code>	Required
<code>style</code>	<code>string</code>	<code>inline</code> , <code>popup</code>	<code>inline</code>	
<code>redirect_url</code>	<code>string (URL)</code>	—	<code>""</code>	On booking confirmation

9. Advanced Widget Elements

9.1 Image Slider

Property	Type	Values	Default	Notes
<code>slides</code>	<code>array of objects</code>	—	<code>[]</code>	Each slide: { <code>image_url</code> , <code>alt_text</code> , <code>caption</code> , <code>link_url</code> , <code>link_target</code> }
<code>transition_style</code>	<code>string</code>	<code>slide</code> , <code>fade</code>	<code>slide</code>	
<code>autoplay</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	
<code>autoplay_speed</code>	<code>number (ms)</code>	500–10000	3000	
<code>loop</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	
<code>show_arrows</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	
<code>show_pagination</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	Dot indicators
<code>pause_on_hover</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	
<code>image_fit</code>	<code>string</code>	<code>cover</code> , <code>contain</code> , <code>fill</code>	<code>cover</code>	
<code>aspect_ratio</code>	<code>string</code>	<code>16:9</code> , <code>4:3</code> , <code>1:1</code> , <code>3:2</code> , <code>custom</code>	<code>16:9</code>	
<code>custom_height</code>	<code>number (px)</code>	—	400	Used when <code>aspect_ratio</code> =

				custom
All base properties	—	See § 3	—	

9.2 Countdown Timer

Property	Type	Values	Default	Notes
timer_type	string	fixed , evergreen , daily	fixed	
end_date	string (ISO 8601)	—	""	Used for fixed type
end_time	string (HH:MM)	—	""	Used for fixed and daily types
timezone	string	IANA timezone string	"America/New_York"	
duration_minutes	number	1–525600	60	Used for evergreen type
evergreen_reset	string	never , on_revisit , on_session_end	never	
daily_reset_time	string (HH:MM)	—	"00:00"	Used for daily type
show_days	boolean	true / false	true	
show_hours	boolean	true / false	true	
show_minutes	boolean	true / false	true	
show_seconds	boolean	true / false	true	
label_days	string	—	"Days"	
label_hours	string	—	"Hours"	
label_minutes	string	—	"Minutes"	

label_seconds	string	—	"Seconds"	
number_color	string (hex/rgba)	Any valid color	#000000	
label_color	string (hex/rgba)	Any valid color	#666666	
bg_color	string (hex/rgba)	Any valid color	transparent	Per-unit box background
number_font_size	number (px)	12–200	48	
label_font_size	number (px)	8–100	14	
separator_char	string	":", ""	":"	Character between units
expire_action	string	none , redirect_url , show_element , hide_element	none	
expire_redirect_url	string (URL)	—	""	Used when expire_action = redirect_url
expire_element_id	string	—	""	Used for show/hide on expire
All base properties	—	See § 3	—	

9.3 Pricing Table

Property	Type	Values	Default	Notes
plans	array of objects	—	[]	See plan object schema below
columns	number	1–4	3	Number of plan columns
highlight_plan_index	number	0–3	1	Which plan is visually highlighted

Plan Object Schema:

Property	Type	Default	Notes
plan_name	string	"Basic"	
plan_price	string	"\$0"	Displayed as-is (string, not number)
price_period	string	"/month"	e.g. /year , /one-time
description	string	""	Short plan description
features	array of strings	[]	Each string is one feature line
button_label	string	"Get Started"	
button_url	string (URL)	""	
button_color	string (hex/rgba)	#FF6B00	
is_highlighted	boolean	false	Adds visual emphasis
ribbon_text	string	""	e.g. "Most Popular" — shown as a badge
ribbon_color	string (hex/rgba)	#FF6B00	
highlight_color	string (hex/rgba)	#FF6B00	Border/accent color for highlighted plan

9.4 Testimonials

Property	Type	Values	Default	Notes
testimonials	array of objects	—	[]	See testimonial object schema below
layout	string	grid , carousel , list	grid	

columns	number	1–4	3	Used for grid layout
autoplay	boolean	true / false	false	Used for carousel layout
autoplay_speed	number (ms)	1000–10000	4000	
show_arrows	boolean	true / false	true	
show_pagination	boolean	true / false	true	

Testimonial Object Schema:

Property	Type	Default	Notes
author_name	string	"John Doe"	
author_title	string	""	e.g. "CEO, Acme Corp"
author_avatar_url	string (URL)	""	
quote	string	""	The testimonial text
star_rating	number	1–5	5
show_stars	boolean	true / false	true
star_color	string (hex/rgba)	#FFD700	
bg_color	string (hex/rgba)	#ffffff	Card background
text_color	string (hex/rgba)	#333333	

9.5 Social Media Icons

Property	Type	Values	Default	Notes
icons	array of objects	—	[]	See icon object schema below
display_type	string	icon_only , text_only , icon_and_text	icon_only	

icon_style	string	filled , outline , minimal	filled	
icon_shape	string	circle , square , rounded_square , none	circle	
icon_size	number (px)	16–100	32	
icon_color	string (hex/rgba)	Any valid color or brand	brand	brand uses platform's official color
icon_bg_color	string (hex/rgba)	Any valid color	transparent	
gap	number (px)	0–100	8	Space between icons
alignment	string	left , center , right	center	
All base properties	—	See § 3	—	

Supported Platforms and Icon Object Schema:

Platform	platform value
Facebook	facebook
Instagram	instagram
Twitter / X	twitter
LinkedIn	linkedin
YouTube	youtube
TikTok	tiktok
Pinterest	pinterest
Snapchat	snapchat
WhatsApp	whatsapp
Telegram	telegram

Email

email

Each icon object: { platform: string, url: string, open_in_new_tab: boolean }

9.6 Number Counter

Property	Type	Values	Default	Notes
counters	array of objects	—	[]	See counter object schema below
columns	number	1–6	3	
animate_on_scroll	boolean	true / false	true	Triggers count-up when in viewport
animation_duration	number (seconds)	0.5–10	2	Duration of count-up animation

Counter Object Schema:

Property	Type	Default	Notes
start_value	number	0	
end_value	number	100	
prefix	string	""	e.g. "\$"
suffix	string	""	e.g. "+", "%", "K"
decimal_places	number	0	0–4
label	string	""	Text below the number
number_color	string (hex/rgba)	#000000	
label_color	string (hex/rgba)	#666666	
number_font_size	number (px)	48	

label_font_size	number (px)	16	
icon_url	string (URL)	""	Optional icon above number

9.7 Logo Showcase

Property	Type	Values	Default	Notes
mode	string	ticker , carousel	ticker	
logos	array of objects	—	[]	Each: { image_url, alt_text, link_url }
Ticker Mode Properties				
scroll_speed	number	1–10	5	
smooth_scroll	boolean	true / false	true	
pause_on_hover	boolean	true / false	true	
Carousel Mode Properties				
logos_per_slide	number	1–8	4	
auto_animation	boolean	true / false	true	
interval_timing	number (ms)	500–10000	3000	
infinite_loop	boolean	true / false	true	
pause_on_hover	boolean	true / false	true	
animation_style	string	slide , fade	slide	
show_arrows	boolean	true / false	true	
show_pagination	boolean	true / false	false	
Shared Properties				

logo_spacing	number (px)	0–100	20	Space between logos
logo_height	number (px)	20–200	60	Max logo height
grayscale	boolean	true / false	false	Renders logos in grayscale
All base properties	—	See § 3	—	

9.8 Photo Gallery

Property	Type	Values	Default	Notes
images	array of objects	—	[]	See image object schema below
layout	string	grid , masonry_vertical , masonry_horizontal	grid	
columns	number	1–6	3	
columns_mobile	number	1–3	1	
spacing	number (px)	0–50	8	Gap between images
lightbox_enabled	boolean	true / false	true	
heading	string	—	""	Optional heading above gallery
lazy_load	boolean	true / false	true	
All base properties	—	See § 3	—	

Gallery Image Object Schema:

Property	Type	Default	Notes
image_url	string (URL)	""	
alt_text	string	""	
caption	string	""	
description	string	""	Shown in lightbox
click_action	string	lightbox	lightbox or url
click_url	string (URL)	""	Used when click_action = url
open_in_new_tab	boolean	false	
watermark_enabled	boolean	false	
watermark_text	string	""	
watermark_position	string	bottom_right	top_left , top_right , bottom_left , bottom_right , center

9.9 Blog Post Feed

Property	Type	Values	Default	Notes
blog_site_id	string	HighLevel Blog ID	""	Required
display_style	string	grid , list , featured	grid	
sort_by	string	recent , recent_by_category , recent_by_author	recent	
category_filter	array of strings	Category IDs	[]	Used when sort_by = recent_by_category

author_filter	string	Author ID	""	Used when sort_by = recent_by_autho r
posts_per_page	number	1–50	6	
show_pagination	boolean	true / false	true	
show_featured_image	boolean	true / false	true	
show_excerpt	boolean	true / false	true	
show_author	boolean	true / false	true	
show_date	boolean	true / false	true	
show_category	boolean	true / false	true	
button_text	string	—	"Read More"	
button_color	string (hex/rgba)	Any valid color	#FF6B00	
button_text_color	string (hex/rgba)	Any valid color	#ffffff	
All base properties	—	See § 3	—	

9.10 QR Code

Property	Type	Values	Default	Notes
qr_code_id	string	HighLevel QR Code ID	""	Selected from QR library
destination_url	string (URL)	—	""	Read-only display of QR destination
size	number (px)	50–500	200	Rendered QR code size
alignment	string	left , center , right	center	

All base properties	—	See § 3	—	
---------------------	---	---------	---	--

9.11 Navigation Menu

Property	Type	Values	Default	Notes
logo_url	string (URL)	—	""	
logo_alt_text	string	—	""	
logo_width	number (px)	20–500	150	
logo_link_url	string (URL)	—	"/"	
menu_items	array of objects	—	[]	See menu item schema below
layout	string	horizontal , vertical	horizontal	
alignment	string	left , center , right , space_between	space_between	
sticky	boolean	true / false	false	Sticks to top on scroll
sticky_bg_color	string (hex/rgba)	Any valid color	#ffffff	Background when sticky
text_color	string (hex/rgba)	Any valid color	#000000	
hover_color	string (hex/rgba)	Any valid color	#FF6B00	
active_color	string (hex/rgba)	Any valid color	#FF6B00	
font_size	number (px)	8–100	16	
font_weight	string	100 – 900	500	
mobile_menu_style	string	hamburger , full_screen , slide_in	hamburger	

<code>mobile_breakpoint</code>	number (px)	320–1200	768	Breakpoint to switch to mobile menu
<code>bg_color</code>	string (hex/rgba)	Any valid color	<code>#ffffff</code>	Nav bar background
All base properties	—	See § 3	—	

Menu Item Object Schema:

Property	Type	Default	Notes
<code>label</code>	string	"Menu Item"	
<code>go_to</code>	string	url	<code>url</code> , <code>scroll_to_element</code> , <code>phone</code> , <code>email</code>
<code>url</code>	string (URL)	""	
<code>open_in_new_tab</code>	boolean	false	
<code>css_selector</code>	string	""	Used when <code>go_to</code> = <code>scroll_to_element</code>
<code>children</code>	array of menu items	[]	Sub-menu items (mega menu support)
<code>icon</code>	string	""	Optional icon
<code>is_button</code>	boolean	false	Renders as a CTA button
<code>button_color</code>	string (hex/rgba)	<code>#FF6B00</code>	Used when <code>is_button</code> = <code>true</code>

9.12 FAQ / Accordion

Property	Type	Values	Default	Notes
<code>items</code>	array of objects	—	[]	See FAQ item schema below

allow_multiple_open	boolean	true / false	false	
default_open_index	number	-1 to n	-1	-1 = all closed by default
icon_type	string	plus_minus , chevron , arrow , none	plus_minus	
icon_position	string	left , right	right	
header_bg_color	string (hex/rgba)	Any valid color	#f5f5f5	
header_text_color	string (hex/rgba)	Any valid color	#000000	
header_font_size	number (px)	8–100	18	
content_bg_color	string (hex/rgba)	Any valid color	#ffffff	
content_text_color	string (hex/rgba)	Any valid color	#333333	
content_font_size	number (px)	8–100	16	
border_color	string (hex/rgba)	Any valid color	#dddddd	
All base properties	—	See § 3	—	

FAQ Item Object Schema:

Property	Type	Notes
question	string	Header/question text
answer	string (HTML)	Body/answer content (supports rich text)
is_open	boolean	Whether this item is open by default

9.13 Progress Bar

Property	Type	Values	Default	Notes
<code>label</code>	<code>string</code>	—	<code>"Progress"</code>	
<code>value</code>	<code>number</code>	<code>0–100</code>	<code>75</code>	Fill percentage
<code>show_percentage</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	
<code>animate_on_scroll</code>	<code>boolean</code>	<code>true</code> / <code>false</code>	<code>true</code>	
<code>animation_duration</code>	<code>number</code> (seconds)	<code>0.5–5</code>	<code>1.5</code>	
<code>bar_color</code>	<code>string</code> (hex/rgba)	Any valid color	<code>#FF6B00</code>	
<code>track_color</code>	<code>string</code> (hex/rgba)	Any valid color	<code>#eeeeee</code>	
<code>bar_height</code>	<code>number</code> (px)	<code>4–50</code>	<code>20</code>	
<code>bar_radius</code>	<code>number</code> (px)	<code>0–100</code>	<code>10</code>	
<code>label_color</code>	<code>string</code> (hex/rgba)	Any valid color	<code>#000000</code>	
<code>label_font_size</code>	<code>number</code> (px)	<code>8–100</code>	<code>16</code>	
All base properties	—	See § 3	—	

9.14 Map

Property	Type	Values	Default	Notes
<code>address</code>	<code>string</code>	—	<code>""</code>	Full address string
<code>zoom_level</code>	<code>number</code>	<code>1–21</code>	<code>14</code>	Google Maps zoom level
<code>map_type</code>	<code>string</code>	<code>roadmap</code> , <code>satellite</code> , <code>hybrid</code> , <code>terrain</code>	<code>roadmap</code>	

<code>show_marker</code>	boolean	true / false	true	
<code>marker_label</code>	string	—	""	
<code>height</code>	number (px)	100–1000	400	
<code>width</code>	string	% or px	100%	
All base properties	—	See § 3	—	

10. Interactive Behavior

10.1 Show / Hide Element on Button Click

This is a **Button Action** (see § 7.7), not a standalone element. The target element must be configured first.

Configuration on the target element (element to be shown/hidden):

Property	Type	Values	Notes
<code>visible_desktop</code>	boolean	true / false	Set to <code>false</code> to hide initially
<code>visible_mobile</code>	boolean	true / false	Set to <code>false</code> to hide initially

Configuration on the Button element:

Property	Type	Values	Notes
<code>button_action</code>	string	<code>show_elements</code> or <code>hide_elements</code>	
<code>show_element_ids</code>	array of strings	CSS selector IDs	Elements to show on click
<code>hide_element_ids</code>	array of strings	CSS selector IDs	Elements to hide on click

Supported targets for show/hide: Any element, Section, Row, or Column (identified by their `element_id`).

Editing hidden elements: Use the **Layers Panel** (top-left icon in builder) to select and restore visibility of elements hidden from both views.

10.2 Scroll to Element / Section

This is a **Button Action** or **Navigation Menu Item** configuration.

Property	Type	Values	Notes
<code>button_action</code>	<code>string</code>	<code>scroll_to_element</code>	Set on button
<code>scroll_target_id</code>	<code>string</code>	CSS selector (e.g. <code>#section_abc12</code>)	The target section's <code>element_id</code>

How to get the CSS selector: Select the target section → Advanced tab → copy the **CSS Selector** field value.

Scroll behavior: Always smooth scroll. No additional configuration required. Works on same page only (cross-page scroll not supported).

Method via URL: Append CSS selector to page URL:

`https://yourdomain.com/page#section_abc12`

10.3 Popup

Popups are page-level overlay containers. Multiple popups can exist per page.

Property	Type	Values	Default	Notes
<code>popup_id</code>	<code>string</code>	Auto-generated	—	Referenced by button actions
<code>trigger_type</code>	<code>string</code>	<code>button_click</code> , <code>time_delay</code> , <code>exit_intent</code> , <code>scroll_percent</code>	<code>button_click</code>	
<code>trigger_delay_seconds</code>	<code>number</code>	0–300	5	Used when <code>trigger_type</code> = <code>time_delay</code>
<code>trigger_scroll_percent</code>	<code>number</code>	0–100	50	Used when <code>trigger_type</code> =

				scroll_percent
show_once_per_session	boolean	true / false	true	
show_overlay	boolean	true / false	true	
overlay_color	string (hex/rgba)	Any valid color	rgba(0,0,0,0.7)	
close_on_overlay_click	boolean	true / false	true	
show_close_button	boolean	true / false	true	
position	string	center , top , bottom , left , right , top_left , top_right , bottom_left , bottom_right	center	
width	number (px) or %	—	600px	
max_width	number (px)	—	90%	
bg_color	string (hex/rgba)	Any valid color	#ffffff	
border_radius	number (px)	0–100	8	
animation_in	string	fade , slide_up , slide_down , zoom_in , none	fade	
content	array	Sections/Rows/Columns/Elements	[]	Full page builder tree inside popup

11. Universal (Global) Elements

Universal Elements are linked instances of a saved element template that update everywhere simultaneously when edited.

Property	Type	Notes
<code>universal_asset_id</code>	<code>string</code>	ID of the global template. All instances share this ID.
<code>is_universal</code>	<code>boolean</code>	<code>true</code> if this element is a linked global instance
<code>override_allowed</code>	<code>boolean</code>	Whether local overrides are permitted on this instance

Supported element types for Universal: Any element type, but most commonly used for Navigation Menus, Footers, and CTA sections.

Behavior: Editing any instance of a Universal Element propagates changes to all other instances across all pages and funnel steps that use the same `universal_asset_id`.

12. Responsive & Mobile Overrides

HighLevel uses a two-breakpoint responsive system: **Desktop** ($\geq 768\text{px}$) and **Mobile** ($< 768\text{px}$). There is no native tablet breakpoint.

Properties that support mobile overrides (append `_mobile` to the property name):

Base Property	Mobile Override
<code>font_size</code>	<code>font_size_mobile</code>
<code>text_align</code>	<code>text_align_mobile</code>
<code>padding_top/right/bottom/left</code>	<code>padding_top_mobile</code> etc.
<code>margin_top/right/bottom/left</code>	<code>margin_top_mobile</code> etc.
<code>width</code>	<code>width_mobile</code>
<code>height</code>	<code>height_mobile</code>
<code>columns</code> (gallery, counter, etc.)	<code>columns_mobile</code>
<code>visible_desktop</code>	<code>visible_mobile</code>
<code>width_percent</code> (Column)	<code>width_percent_mobile</code>

Row-level mobile behavior:

Property	Type	Default	Notes
stack_on_mobile	boolean	true	Stacks columns vertically on mobile
reverse_on_mobile	boolean	false	Reverses column order on mobile

Mobile breakpoint: 768px (fixed, not configurable per page).

13. Global Page Styles & Brand Board

The Brand Board defines global defaults that cascade to all elements unless overridden locally.

Property	Type	Notes
primary_color	string (hex)	Main brand color — used as default for buttons, accents
secondary_color	string (hex)	Secondary accent color
text_color	string (hex)	Default body text color
heading_color	string (hex)	Default heading text color
link_color	string (hex)	Default hyperlink color
body_font_family	string	Default font for paragraphs and body text
heading_font_family	string	Default font for headings
body_font_size	number (px)	Default body font size
heading_font_size_h1	number (px)	Default H1 size
heading_font_size_h2	number (px)	Default H2 size
heading_font_size_h3	number (px)	Default H3 size
page_background_color	string (hex)	Default page background

button_color	string (hex)	Default button background
button_text_color	string (hex)	Default button text color
button_border_radius	number (px)	Default button corner radius

Custom Fonts: Custom fonts can be loaded via Google Fonts URL or uploaded font files. Once loaded, the font name becomes available in all `font_family` properties.

Document compiled from HighLevel official support documentation. Last updated: March 2026.

Sources: [HighLevel Support Portal](#), official feature release notes, and developer documentation.