

Advance Programming Techniques (APT)

Lecture # 10

Ehtisham Rasheed

Department of Computer Science
University of Gurjat, Gurjat


Exceptions

- An exception is an **unexpected event** during program execution
- Exception **disturb** the normal flow of instructions
- In C#, all exceptions are **objects** derived from the base class `System.SystemException`
- Examples
 - Dividing a number by zero
 - Accessing an invalid array index
 - Opening a file that doesn't exist
 - Database connection failure

Exceptions

- All exceptions in C# derive from the **System.Exception** class

System.Object



Types of Exceptions

1. System-defined (built-in) exceptions

- System exceptions are **built-in exception classes** provided by the **.NET Framework** inside the **System namespace**
- They represent **common runtime errors** that occur due to incorrect logic or system-level issues

2. User-defined (custom or application) exceptions

- User-defined exceptions are **custom exception classes** that you create yourself, derived from the **System.Exception class**.
- They are used when you want to handle **application-specific errors** — things that the system cannot automatically detect

Common System-Defined Exceptions

Exception	Description
DivideByZeroException	Thrown when dividing a number by zero
IndexOutOfRangeException	Accessing invalid array index
NullReferenceException	Accessing a null object
InvalidCastException	Casting object to incompatible type
FormatException	Converting invalid format (e.g., string → int)
FileNotFoundException	When a specified file is not found
IOException	Input/output operation failure

User-Defined Exceptions

- We create custom exceptions when:
 - We need to enforce business rules (e.g., invalid marks, negative balance, age limit)
 - We want to give a **meaningful message** for custom errors
 - We want to control **how** exceptions are thrown and handled in your application
- Example
 - Suppose we want to create an exception in an application that does not allow the age of a participant to be more than **18**
 - Let's name that exception – **InvalidAgeException**
 - To create **InvalidAgeException** exception, we derive it from **Exception**

Application Exceptions

- The **throw** keyword is used to manually raise an exception
- The modern professional way (recommended by Microsoft) is to inherit from **Exception** class rather than **ApplicationException** class

```
// user-defined exception class derived from
// the ApplicationException base class
class InvalidAgeException : ApplicationException
{
    // constructor for the InvalidAgeException class
    InvalidAgeException()
    {
        Console.WriteLine("Exception occurred: Invalid Age");
    }
}
```

Exception Handling

- C# provides built-in blocks to handle exceptions. They are ***try..catch*** and ***finally***

```
try
{
    // code that may raise an exception
}
catch (Exception e)
{
    // code that handles the exception
}
```

Exception Handling

- Finally
 - The **finally** statement lets you execute code, after **try..catch**, regardless of result

```
try
{
    // code that may raise an exception
}
catch (Exception e)
{
    // code that handles the exception
}
finally
{
    // this code is always executed
}
```

Prepa

Example with Exception

```
Console.WriteLine("Enter numerator: ");
int numerator = Convert.ToInt32(Console.ReadLine());
Console.WriteLine("Enter denominator: ");
int denominator = Convert.ToInt32(Console.ReadLine());

int result = numerator / denominator;
Console.WriteLine("Result: {0} / {1} = {2}",
    numerator, denominator, result);
```