

Cisco Nº29





```
Router0
                           Physical
                                    Config
                                           CLI
                                                Attributes
                                IOS Command Line Interface
      Dytes of hon-volatile confiduration memory
249856K bytes of ATA System CompactFlash 0 (Read/Write)
          --- System Configuration Dialog ---
Would you like to enter the initial configuration dialog? [yes/no]: n
Press RETURN to get started!
Router>
Router>
Router>
Router>en
Router#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#int fa0/0
Router(config-if) #ip address 10.3.0.1 255.255.255.0
Router(config-if) #no sh
Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed
state to up
Router(config-if)#
Command+F6 to exit CLI focus
                                                                     Copy
                                                                             Paste
```

```
Router(config-if) #ip dhcp excluded-address 10.3.0.1
Router(config) #ip dhcp pool Telephony
Router(dhcp-config) #network 10.3.0.0 255.255.255.0
Router(dhcp-config) #default-router 10.3.0.1
Router(dhcp-config) #option 150 ip 10.3.0.1
Router(dhcp-config) #
```

```
Router(dhcp-config) #telephony-service
Router(config-telephony) #max-ephones 10
Router(config-telephony) #max-dn 10
Router(config-telephony) #ip source-address 10.3.0.1 port 2000
Router(config-telephony) #auto assign 1 to 10
```

