Cisco N16


```
1sw(config-if)#int vlan 1
1sw(config-if)#no sh

1sw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

1sw(config-if)#ip address 192.168.0.2 255.255.255.0
1sw(config-if)#exit
1sw(config)#
```

```
2sw(config-if)#int vlan 1
2sw(config-if)#no sh
2sw(config-if)#ip address 192.168.0.3 255.255.255.0
2sw(config-if)#exit
2sw(config)#
```

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.0.3

Pinging 192.168.0.3 with 32 bytes of data:

Request timed out.
Reply from 192.168.0.3: bytes=32 time<1ms TTL=255
Reply from 192.168.0.3: bytes=32 time<1ms TTL=255
Reply from 192.168.0.3: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.0.3:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
```

```
1sw(config)#line vty 0 4
1sw(config-line)#pass 111
1sw(config-line)#enable secret 123
1sw(config)#
```

```
2sw(config)#line vty 0 4
2sw(config-line)#pass 111
2sw(config-line)#enable secret 123
2sw(config)#
```

```
[Connection to 192.168.0.3 closed by foreign host]
C:\>telnet 192.168.0.3
Trying 192.168.0.3 ...Open


User Access Verification

Password:
2sw>en
Password:
2sw#
```

```
C:\>telnet 192.168.0.2
Trying 192.168.0.2 ...Open


User Access Verification

Password:
1sw>telnet 192.168.0.3
Trying 192.168.0.3 ...Open


User Access Verification

Password:
2sw>
```