

WEEK1

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 520, y: 329

Root 20:11:00

Simulation Panel

Event List

Vis	Time(sec)	Last Device
	14.819	PC1
Visible	14.820	Switch0
Visible	14.820	

Reset Simulation Constant Delay Captured to: 14.820 s

Play Controls

Event List Filters - Visible Events

ACL Filter, ARP, BGP, Bluetooth, CAPWAP, CDP, DHCP, DHCPv6, DNS, DTP, EAPOL, EIGRP, EIGRPv6, FTP, H, 323, HSRP, HSRPv6, HTTP, HTTPS, ICMP, ICMPv6, IPsec, ISAKMP, IoT, IoT TCP, LACP, LLDP, Meraki, NDP, NETFLOW, NTP, OSPF, OSPFv6, Rstp, POP3, PPP, PPPoE, PTP, RADIUS, REP, RIP, RIPng, RTP, SCCP, SMTP, SNMP, SSH, STP, Syslog, TACACS, TCP, TFTP, Telnet, UDP, USB, VTP

Edit Filters Show All/None

Time: 01:13:32.829 PLAY CONTROLS

Scenario 0

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	In Progress	PC0	PC1	ICMP		14.816	N	0	(edit)

New Delete Toggle PDU List Window

Copper Straight-Through

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 381, y: 103

Root 04:17:00

PC0

Physical Config Desktop Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 192.168.2.10

Subnet Mask 255.255.255.0

Default Gateway 192.168.2.3

DNS Server 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

IPv6 Address

Link Local Address FE80:250:FFF:FE0C:A2B7

Default Gateway

DNS Server

802.1X

☐ Use 802.1X Security

Authentication MD5

Username

Password

Top

Time: 00:08:23

Realtime Simulation

Type	Color	Time(sec)	Periodic	Num	Edit
------	-------	-----------	----------	-----	------

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x 38, y: 9

192.168.1.3 192.168.1.4

192.168.2.3

192.168.2.10 192.168.2.11

192.168.3.10

Time: 01:07:49.788

PLAY CONTROLS

PC Laptop Server Network Controller Printer IP Phone VoIP Device

Router3

Physical Config CLI Attributes

IOS Command Line Interface

Press RETURN to get started.

```
Router>
Router#enable
Router#configure terminal
Router(config)#interface FastEthernet0/0
Router(config-if)#ip address 192.168.3.3 255.255.255.0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#ip address 192.168.1.4 255.255.255.0
Router(config-if)#
Router(config-if)#conf t
Router(config)#
Router#conf t
Router(config)#ip route 192.168.3.0 255.255.255.0 192.168.1.3
```

Copy Paste

Simulation

Num	Edit
0	(ec)
1	(ec)
2	(ec)
3	(ec)

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x 446, y: 5

192.168.1.3 192.168.1.4

192.168.2.3

192.168.2.10 192.168.2.11

192.168.3.10 192.168.3.11

Time: 01:24:29

PC Laptop Server Network Controller Printer IP Phone VoIP Device Phone

PC0

Physical Config Desktop Programming Attributes

Command Prompt

Cisco Packet Tracer PC Command Line 1.0

C:\>ping 192.168.3.10

Pinging 192.168.3.10 with 32 bytes of data:

Request timed out.

Reply from 192.168.3.10: bytes=32 time=10ms TTL=126

Reply from 192.168.3.10: bytes=32 time=10ms TTL=126

Reply from 192.168.3.10: bytes=32 time=10ms TTL=126

Ping statistics for 192.168.3.10:

Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),

Approximate round trip times in milli-seconds:

Minimum = 10ms, Maximum = 10ms, Average = 10ms

C:\>

Simulation

Num	Edit
0	(ec)
1	(ec)
2	(ec)
3	(ec)

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 215, y: 329

Root 03:04:30

192.168.1.3 192.168.1.4

192.168.2.3 192.168.3.3

2960-24TT Switch0 2960-24TT Switch1

PC-PT PC0 PC-PT PC1

Device Name: PC1
Device Model: PC-PT

Port	Link	IP Address	IPv6 Address	MAC Address
FastEthernet0	Up	192.168.2.11/24	<not set>	0002.1748.0458
Bluetooth	Down	<not set>	<not set>	0001.42BD.1469

Gateway: 192.168.2.3
DNS Server: <not set>
Line Number: <not set>

Physical Location: Intercity > Home City > Corporate Office > PC1

Time: 02:07:40.093 PLAY CONTROL

Event List

Vis	Time(sec)	Last Device

Reset Simulation Constant Delay Captured to: 0.000 s

Play Controls

Event List Filters - Visible Events

None

Edit Filters Show All/None

Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
In Progress	PC0	PC1	ICMP	Blue	0.000	N	0	(edit)
Successful	PC0	PC1	ICMP	Orange	450.436	N	1	(edit)

File Edit Options View Tools Extensions Window Help

Logical Physical x: 558, y: 4

Root 12:47:00

PC-PT PC0

Fa0/1

2960-24TT Switch0

G0/0

2911 Router0

Fa0/3

Fa0/2

PC-PT PC1

2001:db8:3c4d
IPv6 add

Time: 09:25:20

Realtime Simulation

Scenario 0

New Delete

Toggle PDU List Window

Copper Straight-Through

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
------	-------------	--------	-------------	------	-------	-----------	----------	-----	------

File Edit Options View Tools Extensions Window Help

Logical Physical x 377, y: 00

PC-PT PC0

PC-PT PC1

2960-24TT Switch0

Fa0/1

Fa0/2

G0/0

2001:c

IPv6 add

Time: 00:27:42

Cooper Straight-Through

Cisco Packet Tracer - C:\Users\Elizabeth\Pictures\Screenshots\NET FA3

File Edit Options View Tools Extensions Window Help

Logical Physical x 385, y: 152

PC-PT PC0

PC-PT PC1

Time: 00:33:37

PC0

Physical Config Desktop Programming Attributes

GLOBAL

Settings

Algorithm Settings

INTERFACE

FastEthernet0

Bluetooth

FastEthernet0

Port Status ☒ On

Bandwidth 100 Mbps 10 Mbps ☒ Auto

Duplex ☐ Half Duplex ☒ Full Duplex ☒ Auto

MAC Address 0030.F2EA.A355

IP Configuration

☐ DHCP

☒ Static

IPv4 Address

Subnet Mask

IPv6 Configuration

☐ Automatic

☒ Static

IPv6 Address 2001:db8:3c4d::2 /

Link Local Address: FE80::230:F2FF:FEEA:A355

PC1

Physical Config Desktop Programming Attributes

GLOBAL

Settings

Algorithm Settings

INTERFACE

FastEthernet0

Bluetooth

FastEthernet0

Port Status ☒ On

Bandwidth 100 Mbps 10 Mbps ☒ Auto

Duplex ☐ Half Duplex ☒ Full Duplex ☒ Auto

MAC Address 00E0.F729.88C2

IP Configuration

☐ DHCP

☒ Static

IPv4 Address

Subnet Mask

IPv6 Configuration

☐ Automatic

☒ Static

IPv6 Address 2001:DB8:3C4D::1 / 64

Link Local Address: FE80::2E0:F7FF:FE29:88C2

Root

Realtime Simulation

Type Color Time(sec) Periodic Num Edit

Cisco Packet Tracer - C:\Users\Elizabeth\Pictures\Screenshots\NET FA3

File Edit Options View Tools Extensions Window Help

Logical Physical x: 250, y: 323

Time: 00:34:26

PC1

Physical Config Desktop Programming Attributes

Command Prompt

Cisco Packet Tracer PC Command Line 1.0

C:\>ping 2001:db8:3c4d::2

Pinging 2001:db8:3c4d::2 with 32 bytes of data:

Reply from 2001:DB8:3C4D::2: bytes=32 time=1ms TTL=128

Reply from 2001:DB8:3C4D::2: bytes=32 time=1ms TTL=128

Reply from 2001:DB8:3C4D::2: bytes=32 time=1ms TTL=128

Ping statistics for 2001:DB8:3C4D::2:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>

PC0

PC1

Time: 00:34:26

Realtime Simulation

Type Color Time(sec) Periodic Num Edit

File Edit Options View Tools Extensions Window Help

Logical Physical x: 782, y: 137

Time: 00:24:52

PC-PT PC0

PC-PT PC1

2960-24TT Switch0

2911 Router0

Fa0/1

Fa0/2

G0/0

Fa0/0

2001:db8:3c4d

IPv6 add

Copper Straight-Through

Router0

Physical Config CLI Attributes

IOS Command Line Interface

```
% Invalid input detected at '^' marker.

Router(config)#g0/0

% Invalid input detected at '^' marker.

Router(config)#
Router(config)#conf t
%Invalid hex value
Router(config)#exit
Router#
%SYS-5-CONFIG_I: Configured from console by console

Router#enable
Router#conf t
Enter configuration commands, one per line. End with
CTRL/Z.
Router(config)#int g0/0
Router(config-if)#no sh

Router(config-if)#
%LINK-6-CHANGED: Interface GigabitEthernet0/0, changed
state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface
GigabitEthernet0/0, changed state to up
exit
Router(config)#ipv6 uni
Router(config)#ipv6 unicast-routing
Router(config)#int g0/0
Router(config-if)#ipv6 add
% Incomplete command.
Router(config-if)#ipv6 address 2001:db8:3c4d:1/64
% Incomplete command.
Router(config-if)#ipv6 address 2001:db8:3c4d:1/64
Router(config-if)#
```

Copy Paste

Simulation

Num Edit

3

Cisco Packet Tracer - C:\Users\Elizabeth\Pictures\Screenshots\NET FA3

File Edit Options View Tools Extensions Window Help

Logical Physical x 392, y: 203

192.168.1.3
192.168.2.3
192.168.2.10
192.168.2.11
192.168.3.10

Time: 00:02:32

PC0

Physical Config Desktop Programming Attributes

Command Prompt

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.1.1
Ping request could not find host 192.168.1.1. Please check the name and try again.
C:\>ping 192.168.9
Ping request could not find host 192.168.9. Please check the name and try again.
C:\>192.168.2.11
Invalid Command.
C:\>192.168.2.9
Invalid Command.
C:\>ping 192.168.2.11

Pinging 192.168.2.11 with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 192.168.2.11:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping 192.168.2.9

Pinging 192.168.2.9 with 32 bytes of data:
Reply from 192.168.2.9: bytes=32 time=2ms TTL=128
Reply from 192.168.2.9: bytes=32 time<1ms TTL=128
Reply from 192.168.2.9: bytes=32 time<1ms TTL=128
Reply from 192.168.2.9: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.2.9:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 2ms, Average = 0ms
C:\>
```

Root 01:19:30

Realtime Simulation

Type	Color	Time(sec)	Periodic	Num	Edt
ICMP	Blue	0.000	N	0	(edt)
ICMP	Orange	450.436	N	1	(edt)
ICMP	Green	0.000	N	2	(edt)

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x 189, y: 1

192.168.1.3
192.168.2.3
192.168.2.10
192.168.2.11
192.168.3.10
192.168.3.11
192.168.1.4
192.168.3.3

Time: 02:17:40.578

Scenario 0

New Delete

Toggle PDU List Window

Server-PT

Event List Realtime Simulation

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edt
Successful	PC0	PC1	ICMP	Blue	0.000	N	0	(edt)	
Successful	PC0	PC1	ICMP	Orange	450.436	N	1	(edt)	
Successful	PC0	PC1	ICMP	Green	0.000	N	2	(edt)	

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical

Physical

Server-PT
Server4

211
Router2

260-247
Switch0

PC-PT
PC0

Time: 01:09:38

Realtime

Simulation

Type Color Time(sec) Periodic Num Edit

PC0

Physical Config Desktop Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☒ DHCP

☐ Static

IPv4 Address 192.168.1.10

Subnet Mask 255.255.255.0

Default Gateway 0.0.0.0

DNS Server 192.168.1.4

IPv6 Configuration

☐ Automatic

☒ Static

IPv6 Address

Link Local Address FE80::20A:41FF:FE03:D45C

Default Gateway

DNS Server

802.1X

☐ Use 802.1X Security

Authentication MD5

Username

Password

☐ Top

Server4

Physical Config Services Desktop Programming Attributes

SERVICES

HTTP

DHCP

DHCPv6

TFTP

DNS

SYSLOG

AAA

NTP

EMAIL

FTP

IoT

VM Management

Radius EAP

DHCP

Interface FastEthernet0

Service ☒ On ☐ Off

Pool Name serverPool

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

Start IP Address 192 168 1 10

Subnet Mask 255 255 255 0

Maximum Number of Users 248

TFTP Server 0.0.0.0

WLC Address 0.0.0.0

Add Save Remove

Pool Name	Default Gateway	DNS Server	Start IP Address	Subnet Mask	Max User	TFTP Server	WLC Address
serverPool	0.0.0.0	0.0.0.0	192.168...	255.255...	248	0.0.0.0	0.0.0.0

☐ Top