

---

MODULE *Southbound*

---

INSTANCE *Naturals*

INSTANCE *FiniteSets*

LOCAL INSTANCE *TLC*

---

An empty constant  
CONSTANT *Nil*

A record of target states  
VARIABLE *target*

The set of all nodes  
CONSTANT *Nodes*

The state of nodes  
VARIABLE *node*

---

This section models node and target states.

$Start \triangleq$   
 $\wedge \neg target.running$   
 $\wedge target' = [target \text{ EXCEPT } !.incarnation = target.incarnation + 1,$   
 $\hspace{15em} !.running = TRUE]$   
 $\wedge \text{UNCHANGED } \langle node \rangle$

$Stop \triangleq$   
 $\wedge target.running$   
 $\wedge target' = [target \text{ EXCEPT } !.running = FALSE,$   
 $\hspace{15em} !.values = [p \in \{\} \mapsto [value \mapsto Nil]]]$   
 $\wedge \text{UNCHANGED } \langle node \rangle$

$Connect(n) \triangleq$   
 $\wedge \neg node[n].connected$   
 $\wedge target.running$   
 $\wedge node' = [node \text{ EXCEPT } ![n].incarnation = node[n].incarnation + 1,$   
 $\hspace{15em} ![n].connected = TRUE]$   
 $\wedge \text{UNCHANGED } \langle target \rangle$

$Disconnect(n) \triangleq$   
 $\wedge node[n].connected$   
 $\wedge node' = [node \text{ EXCEPT } ![n].connected = FALSE]$   
 $\wedge \text{UNCHANGED } \langle target \rangle$

---

$InitSouthbound \triangleq$   
 $\wedge target = [incarnation \mapsto 0,$   
 $\quad \quad \quad running \mapsto FALSE,$   
 $\quad \quad \quad values \mapsto [p \in \{\} \mapsto [value \mapsto Nil]]]$   
 $\wedge node = [n \in Nodes \mapsto [incarnation \mapsto 0, connected \mapsto FALSE]]$

$NextSouthbound \triangleq$   
 $\vee Start$   
 $\vee Stop$   
 $\vee \exists n \in Nodes : Connect(n)$   
 $\vee \exists n \in Nodes : Disconnect(n)$

---

ASSUME  $\wedge IsFiniteSet(Nodes)$   
 $\wedge \forall n \in Nodes :$   
 $\quad \wedge n \in STRING$

---

$\backslash$  \* Modification History  
 $\backslash$  \* Last modified Sun Feb 20 09:09:52 PST 2022 by jordanhalterman  
 $\backslash$  \* Created Sun Feb 20 03:13:26 PST 2022 by jordanhalterman