

EXTENDS *Transactions*

INSTANCE *Naturals*

INSTANCE *FiniteSets*

INSTANCE *Sequences*

LOCAL INSTANCE *TLC*

This section models configuration changes and rollbacks. Changes are appended to the transaction log and processed asynchronously.

$$\begin{aligned}
 & \text{Value}(s, t, p) \triangleq \\
 & \quad \text{LET } \text{value} \triangleq \text{CHOOSE } v \in s : v.\text{target} = t \wedge v.\text{path} = p \\
 & \quad \text{IN} \\
 & \quad \quad [value \mapsto \text{value.value}, \\
 & \quad \quad \text{delete} \mapsto \text{value.delete}] \\
 & \text{Paths}(s, t) \triangleq \\
 & \quad [p \in \{v.\text{path} : v \in \{v \in s : v.\text{target} = t\}\} \mapsto \text{Value}(s, t, p)] \\
 & \text{Changes}(s) \triangleq \\
 & \quad [t \in \{v.\text{target} : v \in s\} \mapsto \text{Paths}(s, t)] \\
 & \text{ValidValues}(t, p) \triangleq \\
 & \quad \text{UNION } \{ \{ [value \mapsto v, \text{delete} \mapsto \text{FALSE}] : v \in \text{Target}[t].\text{values}[p] \}, \{ [value \mapsto \text{Nil}, \text{delete} \mapsto \text{TRUE}] \} \} \\
 & \text{ValidPaths}(t) \triangleq \\
 & \quad \text{UNION } \{ \{ v @ @ [path \mapsto p] : v \in \text{ValidValues}(t, p) \} : p \in \text{DOMAIN } \text{Target}[t].\text{values} \} \\
 & \text{ValidTargets} \triangleq \\
 & \quad \text{UNION } \{ \{ p @ @ [target \mapsto t] : p \in \text{ValidPaths}(t) \} : t \in \text{DOMAIN } \text{Target} \}
 \end{aligned}$$

The set of all valid sets of changes to all targets and their paths.

The set of possible changes is computed from the *Target* model value.

$$\begin{aligned}
 & \text{ValidChanges} \triangleq \\
 & \quad \text{LET } \text{changeSets} \triangleq \{ s \in \text{SUBSET } \text{ValidTargets} : \\
 & \quad \quad \forall t \in \text{DOMAIN } \text{Target} : \\
 & \quad \quad \forall p \in \text{DOMAIN } \text{Target}[t].\text{values} : \\
 & \quad \quad \quad \text{Cardinality}(\{ v \in s : v.\text{target} = t \wedge v.\text{path} = p \}) \leq 1 \} \\
 & \quad \text{IN} \\
 & \quad \{ c \in \{ \text{Changes}(s) : s \in \text{changeSets} \} : \\
 & \quad \quad \text{DOMAIN } c \neq \{ \} \wedge \forall t \in \text{DOMAIN } c : \text{DOMAIN } c[t] \neq \{ \} \}
 \end{aligned}$$

Add a set of changes 'c' to the transaction log

$RequestChange(c) \triangleq$
 LET $index \triangleq Len(transaction) + 1$
 IN $\exists isolation \in \{ReadCommitted, Serializable\} :$
 $\wedge transaction' = transaction @@ (index :> [type \mapsto TransactionChange,$
 $isolation \mapsto isolation,$
 $change \mapsto c,$
 $targets \mapsto [t \in \{\} \mapsto 0],$
 $phase \mapsto TransactionInitialize,$
 $state \mapsto TransactionInProgress,$
 $status \mapsto TransactionPending])$

Add a rollback of transaction 't' to the transaction log
 $RequestRollback(i) \triangleq$
 LET $index \triangleq Len(transaction) + 1$
 IN $\exists isolation \in \{ReadCommitted, Serializable\} :$
 $\wedge transaction' = transaction @@ (index :> [type \mapsto TransactionRollback,$
 $isolation \mapsto isolation,$
 $rollback \mapsto i,$
 $targets \mapsto [t \in \{\} \mapsto 0],$
 $phase \mapsto TransactionInitialize,$
 $state \mapsto TransactionInProgress,$
 $status \mapsto TransactionPending])$

$RequestSet \triangleq$
 $\vee \exists c \in ValidChanges :$
 $RequestChange(c)$
 $\vee \exists i \in DOMAIN transaction :$
 $RequestRollback(i)$

Formal specification, constraints, and theorems.

$InitNorthbound \triangleq TRUE$

$NextNorthbound \triangleq$
 $\vee RequestSet$

\ * Modification History
 \ * Last modified Sun Feb 20 10:10:06 PST 2022 by jordanhalterman
 \ * Created Sun Feb 20 03:08:25 PST 2022 by jordanhalterman