

---

MODULE *Config*

---

INSTANCE *Naturals*

INSTANCE *FiniteSets*

INSTANCE *Sequences*

INSTANCE *TLC*

---

*GenerateTestCases*  $\triangleq$  FALSE

*Nil*  $\triangleq$  "<nil>"

*Change*  $\triangleq$  "Change"

*Rollback*  $\triangleq$  "Rollback"

*Commit*  $\triangleq$  "Commit"

*Apply*  $\triangleq$  "Apply"

*Pending*  $\triangleq$  "Pending"

*Complete*  $\triangleq$  "Complete"

*Aborted*  $\triangleq$  "Aborted"

*Failed*  $\triangleq$  "Failed"

*Done*  $\triangleq$  { *Complete*, *Aborted*, *Failed* }

*Node*  $\triangleq$  { "node1" }

*NumTransactions*  $\triangleq$  3

*NumTerms*  $\triangleq$  2

*NumConns*  $\triangleq$  2

*NumStarts*  $\triangleq$  2

*Path*  $\triangleq$  { "path1" }

*Value*  $\triangleq$  { "value1", "value2" }

---

A transaction *log*. Transactions may either request a set of changes to a set of targets or rollback a prior change.

VARIABLE *transaction*

A record of per-target proposals

VARIABLE *proposal*

A record of per-target configurations

VARIABLE *configuration*

A record of target masterhips

VARIABLE *mastership*

A record of node connections to the target

VARIABLE *conn*

The target state

VARIABLE *target*

A sequence of state changes used for model checking.

VARIABLE *history*

$\text{vars} \triangleq \langle \text{transaction}, \text{proposal}, \text{configuration}, \text{mastership}, \text{conn}, \text{target}, \text{history} \rangle$

---

LOCAL *Transaction*  $\triangleq$  INSTANCE *Transaction*

LOCAL *Configuration*  $\triangleq$  INSTANCE *Configuration*

LOCAL *Mastership*  $\triangleq$  INSTANCE *Mastership*

LOCAL *Target*  $\triangleq$  INSTANCE *Target*

---

$\text{AppendChange}(p, v) \triangleq$   
 $\wedge \text{Transaction!AppendChange}(p, v)$

$\text{RollbackChange}(i) \triangleq$   
 $\wedge \text{Transaction!RollbackChange}(i)$

$\text{ReconcileTransaction}(n, i) \triangleq$   
 $\wedge i \in \text{DOMAIN } \text{transaction}$   
 $\wedge \text{Transaction!ReconcileTransaction}(n, i)$   
 $\wedge \text{GenerateTestCases} \Rightarrow$   
    LET  $\text{context} \triangleq [\text{node} \mapsto n, \text{index} \mapsto i]$   
    IN  $\text{Transaction!Test!Log}(\text{context})$

$\text{ReconcileConfiguration}(n) \triangleq$   
 $\wedge \text{Configuration!ReconcileConfiguration}(n)$   
 $\wedge \text{UNCHANGED } \langle \text{transaction}, \text{proposal}, \text{history} \rangle$   
 $\wedge \text{GenerateTestCases} \Rightarrow \text{Configuration!Test!Log}([\text{node} \mapsto n])$

$\text{ReconcileMastership}(n) \triangleq$   
 $\wedge \text{Mastership!ReconcileMastership}(n)$   
 $\wedge \text{UNCHANGED } \langle \text{transaction}, \text{proposal}, \text{configuration}, \text{target}, \text{history} \rangle$   
 $\wedge \text{GenerateTestCases} \Rightarrow \text{Mastership!Test!Log}([\text{node} \mapsto n])$

$\text{ConnectNode}(n) \triangleq$   
 $\wedge \text{Target!Connect}(n)$

$$\begin{aligned}
& \wedge \text{UNCHANGED } \langle \text{transaction}, \text{proposal}, \text{configuration}, \text{mastership}, \text{history} \rangle \\
\text{DisconnectNode}(n) & \triangleq \\
& \wedge \text{Target!Disconnect}(n) \\
& \wedge \text{UNCHANGED } \langle \text{transaction}, \text{proposal}, \text{configuration}, \text{mastership}, \text{history} \rangle \\
\text{StartTarget} & \triangleq \\
& \wedge \text{Target!Start} \\
& \wedge \text{UNCHANGED } \langle \text{transaction}, \text{proposal}, \text{configuration}, \text{mastership}, \text{history} \rangle \\
\text{StopTarget} & \triangleq \\
& \wedge \text{Target!Stop} \\
& \wedge \text{UNCHANGED } \langle \text{transaction}, \text{proposal}, \text{configuration}, \text{mastership}, \text{history} \rangle
\end{aligned}$$


---

Formal specification, constraints, and theorems.

$$\begin{aligned}
\text{Init} & \triangleq \\
& \wedge \text{transaction} = [ \\
& \quad i \in \{\} \mapsto [ \\
& \quad \quad \text{phase} \mapsto \text{Nil}, \\
& \quad \quad \text{change} \mapsto [ \\
& \quad \quad \quad \text{proposal} \mapsto 0, \\
& \quad \quad \quad \text{revision} \mapsto 0, \\
& \quad \quad \quad \text{values} \mapsto [ \\
& \quad \quad \quad \quad p \in \{\} \mapsto [ \\
& \quad \quad \quad \quad \quad \text{index} \mapsto 0, \\
& \quad \quad \quad \quad \quad \text{value} \mapsto \text{Nil}]]], \\
& \quad \quad \text{rollback} \mapsto [ \\
& \quad \quad \quad \text{proposal} \mapsto 0, \\
& \quad \quad \quad \text{revision} \mapsto 0, \\
& \quad \quad \quad \text{values} \mapsto [ \\
& \quad \quad \quad \quad p \in \{\} \mapsto [ \\
& \quad \quad \quad \quad \quad \text{index} \mapsto 0, \\
& \quad \quad \quad \quad \quad \text{value} \mapsto \text{Nil}]]]]], \\
& \wedge \text{proposal} = [ \\
& \quad i \in \{\} \mapsto [ \\
& \quad \quad \text{transaction} \mapsto 0, \\
& \quad \quad \text{commit} \mapsto \text{Nil}, \\
& \quad \quad \text{apply} \mapsto \text{Nil}] \\
& \wedge \text{configuration} = [ \\
& \quad \text{state} \mapsto \text{Pending}, \\
& \quad \text{term} \mapsto 0, \\
& \quad \text{committed} \mapsto [ \\
& \quad \quad \text{index} \mapsto 0, \\
& \quad \quad \text{revision} \mapsto 0,
\end{aligned}$$

$$\begin{aligned}
& \text{values} \mapsto [ \\
& \quad p \in \{\} \mapsto [ \\
& \quad \quad \text{index} \mapsto 0, \\
& \quad \quad \text{value} \mapsto \text{Nil}]]], \\
& \text{applied} \mapsto [ \\
& \quad \text{target} \mapsto 0, \\
& \quad \text{index} \mapsto 0, \\
& \quad \text{revision} \mapsto 0, \\
& \quad \text{values} \mapsto [ \\
& \quad \quad p \in \{\} \mapsto [ \\
& \quad \quad \quad \text{index} \mapsto 0, \\
& \quad \quad \quad \text{value} \mapsto \text{Nil}]]]] \\
& \wedge \text{target} = [ \\
& \quad \text{id} \mapsto 1, \\
& \quad \text{running} \mapsto \text{TRUE}, \\
& \quad \text{values} \mapsto [ \\
& \quad \quad p \in \{\} \mapsto [ \\
& \quad \quad \quad \text{index} \mapsto 0, \\
& \quad \quad \quad \text{value} \mapsto \text{Nil}]]] \\
& \wedge \text{mastership} = [ \\
& \quad \text{master} \mapsto \text{CHOOSE } n \in \text{Node} : \text{TRUE}, \\
& \quad \text{term} \mapsto 1, \\
& \quad \text{conn} \mapsto 1] \\
& \wedge \text{conn} = [ \\
& \quad n \in \text{Node} \mapsto [ \\
& \quad \quad \text{id} \mapsto 1, \\
& \quad \quad \text{connected} \mapsto \text{TRUE}] \\
& \wedge \text{history} = \langle \rangle \\
& \text{Next} \triangleq \\
& \quad \vee \exists p \in \text{Path}, v \in \text{Value} : \\
& \quad \quad \text{AppendChange}(p, v) \\
& \quad \vee \exists i \in \text{DOMAIN transaction} : \\
& \quad \quad \text{RollbackChange}(i) \\
& \quad \vee \exists n \in \text{Node} : \\
& \quad \quad \exists i \in \text{DOMAIN transaction} : \\
& \quad \quad \quad \text{ReconcileTransaction}(n, i) \\
& \quad \vee \exists n \in \text{Node} : \\
& \quad \quad \text{ReconcileConfiguration}(n) \\
& \quad \vee \exists n \in \text{Node} : \\
& \quad \quad \text{ReconcileMastership}(n) \\
& \quad \vee \exists n \in \text{Node} : \\
& \quad \quad \vee \text{ConnectNode}(n) \\
& \quad \quad \vee \text{DisconnectNode}(n) \\
& \quad \vee \text{StartTarget}
\end{aligned}$$

$$\begin{aligned}
& \vee \textit{StopTarget} \\
\textit{Spec} & \triangleq \\
& \wedge \textit{Init} \\
& \wedge \Box[\textit{Next}]_{\textit{vars}} \\
& \wedge \forall p \in \textit{Path}, v \in \textit{Value} : \\
& \quad \text{WF}_{\langle \textit{transaction}, \textit{proposal}, \textit{configuration}, \textit{mastership}, \textit{conn}, \textit{target}, \textit{history} \rangle}(\textit{Transaction!AppendChange}(p, v)) \\
& \wedge \forall i \in 1 \dots \textit{NumTransactions} : \\
& \quad \text{WF}_{\langle \textit{transaction}, \textit{proposal}, \textit{configuration}, \textit{mastership}, \textit{conn}, \textit{target}, \textit{history} \rangle}(\textit{Transaction!RollbackChange}(i)) \\
& \wedge \forall n \in \textit{Node}, i \in 1 \dots \textit{NumTransactions} : \\
& \quad \text{WF}_{\langle \textit{transaction}, \textit{proposal}, \textit{configuration}, \textit{mastership}, \textit{conn}, \textit{target}, \textit{history} \rangle}(\textit{Transaction!ReconcileTransaction}(n, i)) \\
& \wedge \forall n \in \textit{Node} : \\
& \quad \text{WF}_{\langle \textit{configuration}, \textit{mastership}, \textit{conn}, \textit{target} \rangle}(\textit{Configuration!ReconcileConfiguration}(n)) \\
& \wedge \forall n \in \textit{Node} : \\
& \quad \text{WF}_{\langle \textit{mastership}, \textit{conn} \rangle}(\textit{Mastership!ReconcileMastership}(n)) \\
& \wedge \forall n \in \textit{Node} : \\
& \quad \text{WF}_{\langle \textit{conn}, \textit{target} \rangle}(\textit{Target!Connect}(n) \vee \textit{Target!Disconnect}(n)) \\
& \wedge \text{WF}_{\langle \textit{conn}, \textit{target} \rangle}(\textit{Target!Start} \vee \textit{Target!Stop}) \\
\textit{Alias} & \triangleq [ \\
& \textit{log} \mapsto [ \\
& \quad i \in \text{DOMAIN } \textit{transaction} \mapsto [ \\
& \quad \textit{change} \mapsto \\
& \quad \quad \text{IF } \textit{transaction}[i].\textit{change.proposal} \neq 0 \text{ THEN} \\
& \quad \quad \quad [\textit{commit} \mapsto \textit{proposal}[\textit{transaction}[i].\textit{change.proposal}].\textit{commit}, \\
& \quad \quad \quad \textit{apply} \mapsto \textit{proposal}[\textit{transaction}[i].\textit{change.proposal}].\textit{apply}, \\
& \quad \quad \quad \textit{values} \mapsto \textit{transaction}[i].\textit{change.values}] \\
& \quad \quad \text{ELSE} \\
& \quad \quad \quad [\textit{commit} \mapsto \textit{Nil}, \\
& \quad \quad \quad \textit{apply} \mapsto \textit{Nil}, \\
& \quad \quad \quad \textit{values} \mapsto \textit{transaction}[i].\textit{change.values}], \\
& \quad \textit{rollback} \mapsto \\
& \quad \quad \text{IF } \textit{transaction}[i].\textit{rollback.proposal} \neq 0 \text{ THEN} \\
& \quad \quad \quad [\textit{commit} \mapsto \textit{proposal}[\textit{transaction}[i].\textit{rollback.proposal}].\textit{commit}, \\
& \quad \quad \quad \textit{apply} \mapsto \textit{proposal}[\textit{transaction}[i].\textit{rollback.proposal}].\textit{apply}, \\
& \quad \quad \quad \textit{values} \mapsto \textit{transaction}[i].\textit{rollback.values}] \\
& \quad \quad \text{ELSE} \\
& \quad \quad \quad [\textit{commit} \mapsto \textit{Nil}, \\
& \quad \quad \quad \textit{apply} \mapsto \textit{Nil}, \\
& \quad \quad \quad \textit{values} \mapsto \textit{transaction}[i].\textit{rollback.values}] @@ \\
& \quad \textit{transaction}[i], \\
& \textit{transaction} \mapsto \textit{transaction}, \\
& \textit{proposal} \mapsto \textit{proposal}, \\
& \textit{configuration} \mapsto \textit{configuration}, \\
& \textit{mastership} \mapsto \textit{mastership},
\end{aligned}$$

$conn \quad \mapsto conn,$   
 $target \quad \mapsto target,$   
 $history \quad \mapsto history]$

---

$LimitTransactions \triangleq Len(transaction) \leq NumTransactions$

$LimitTerms \triangleq$   
 $\quad \vee mastership.term < NumTerms$   
 $\quad \vee \wedge mastership.term = NumTerms$   
 $\quad \wedge mastership.master \neq Nil$

$LimitConns \triangleq$   
 $\quad \forall n \in DOMAIN \ conn :$   
 $\quad \vee conn[n].id < NumConns$   
 $\quad \vee \wedge conn[n].id = NumConns$   
 $\quad \wedge conn[n].connected$

$LimitStarts \triangleq$   
 $\quad \vee target.id < 2$   
 $\quad \vee \wedge target.id = 2$   
 $\quad \wedge target.running$

---

$TypeOK \triangleq$   
 $\quad \wedge Transaction! TypeOK$   
 $\quad \wedge Configuration! TypeOK$   
 $\quad \wedge Mastership! TypeOK$

$LOCAL \ IsOrderedChange(p, i) \triangleq$   
 $\quad \wedge history[i].type = Change$   
 $\quad \wedge history[i].phase = p$   
 $\quad \wedge \neg \exists j \in DOMAIN \ history :$   
 $\quad \quad \wedge j < i$   
 $\quad \quad \wedge history[j].type = Change$   
 $\quad \quad \wedge history[j].phase = p$   
 $\quad \quad \wedge history[j].index \geq history[i].index$

$LOCAL \ IsOrderedRollback(p, i) \triangleq$   
 $\quad \wedge history[i].type = Rollback$   
 $\quad \wedge history[i].phase = p$   
 $\quad \wedge \exists j \in DOMAIN \ history :$   
 $\quad \quad \wedge j < i$   
 $\quad \quad \wedge history[j].type = Change$   
 $\quad \quad \wedge history[j].index = history[i].index$   
 $\quad \wedge \neg \exists j \in DOMAIN \ history :$

$$\begin{aligned}
& \wedge j < i \\
& \wedge \text{history}[j].\text{type} = \text{Change} \\
& \wedge \text{history}[j].\text{phase} = p \\
& \wedge \text{history}[j].\text{index} > \text{history}[i].\text{index} \\
& \wedge \neg \exists k \in \text{DOMAIN } \text{history} : \\
& \quad \wedge k > j \\
& \quad \wedge k < i \\
& \quad \wedge \text{history}[k].\text{type} = \text{Rollback} \\
& \quad \wedge \text{history}[k].\text{phase} = p \\
& \quad \wedge \text{history}[k].\text{index} = \text{history}[j].\text{index}
\end{aligned}$$

$\text{Order} \triangleq$

$$\begin{aligned}
& \wedge \forall i \in \text{DOMAIN } \text{history} : \\
& \quad \vee \text{IsOrderedChange}(\text{Commit}, i) \\
& \quad \vee \text{IsOrderedChange}(\text{Apply}, i) \\
& \quad \vee \text{IsOrderedRollback}(\text{Commit}, i) \\
& \quad \vee \text{IsOrderedRollback}(\text{Apply}, i) \\
& \wedge \forall i \in \text{DOMAIN } \text{transaction} : \\
& \quad \wedge \text{transaction}[i].\text{change.proposal} \neq 0 \\
& \quad \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} = \text{Failed} \\
& \quad \wedge \text{transaction}[i].\text{rollback.proposal} \neq 0 \Rightarrow \\
& \quad \quad \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{apply} \neq \text{Complete} \\
& \quad \Rightarrow \forall j \in \text{DOMAIN } \text{transaction} : (j > i \Rightarrow \\
& \quad \quad (\text{transaction}[j].\text{change.proposal} \neq 0 \Rightarrow \\
& \quad \quad \quad \text{proposal}[\text{transaction}[j].\text{change.proposal}].\text{apply} \neq \text{Complete}))
\end{aligned}$$

$\text{LOCAL } \text{IsChangeCommitted}(i) \triangleq$

$$\begin{aligned}
& \wedge \text{transaction}[i].\text{change.proposal} \neq 0 \\
& \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{commit} = \text{Complete} \\
& \wedge \text{transaction}[i].\text{rollback.proposal} \neq 0 \Rightarrow \\
& \quad \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{commit} \neq \text{Complete}
\end{aligned}$$

$\text{LOCAL } \text{IsChangeApplied}(i) \triangleq$

$$\begin{aligned}
& \wedge \text{transaction}[i].\text{change.proposal} \neq 0 \\
& \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} = \text{Complete} \\
& \wedge \text{transaction}[i].\text{rollback.proposal} \neq 0 \Rightarrow \\
& \quad \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{apply} \neq \text{Complete}
\end{aligned}$$

$\text{Consistency} \triangleq$

$$\begin{aligned}
& \wedge \forall i \in \text{DOMAIN } \text{transaction} : \\
& \quad \wedge \text{IsChangeCommitted}(i) \\
& \quad \wedge \neg \exists j \in \text{DOMAIN } \text{transaction} : \\
& \quad \quad \wedge j > i \\
& \quad \quad \wedge \text{IsChangeCommitted}(j) \\
& \Rightarrow \forall p \in \text{DOMAIN } \text{transaction}[i].\text{change.values} : \\
& \quad \wedge \text{configuration.committed.values}[p] = \text{transaction}[i].\text{change.values}[p]
\end{aligned}$$

$$\begin{aligned}
& \wedge \forall i \in \text{DOMAIN } \text{transaction} : \\
& \quad \wedge \text{IsChangeApplied}(i) \\
& \quad \wedge \neg \exists j \in \text{DOMAIN } \text{transaction} : \\
& \quad \quad \wedge j > i \\
& \quad \quad \wedge \text{IsChangeApplied}(j) \\
& \Rightarrow \forall p \in \text{DOMAIN } \text{transaction}[i].\text{change.values} : \\
& \quad \wedge \text{configuration.applied.values}[p] = \text{transaction}[i].\text{change.values}[p] \\
& \quad \wedge \wedge \text{target.running} \\
& \quad \wedge \text{configuration.applied.target} = \text{target.id} \\
& \quad \wedge \text{configuration.state} = \text{Complete} \\
& \quad \Rightarrow \text{target.values}[p] = \text{transaction}[i].\text{change.values}[p]
\end{aligned}$$

$$\text{Safety} \triangleq \Box(\text{Order} \wedge \text{Consistency})$$

$$\text{THEOREM } \text{Spec} \Rightarrow \text{Safety}$$

$$\text{Terminates}(i) \triangleq$$

$$\begin{aligned}
& \wedge i \in \text{DOMAIN } \text{transaction} \wedge \text{transaction}[i].\text{phase} = \text{Change} \rightsquigarrow \\
& \quad \wedge i \in \text{DOMAIN } \text{transaction} \\
& \quad \wedge \text{transaction}[i].\text{change.proposal} \neq 0 \\
& \quad \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{commit} \in \text{Done} \\
& \quad \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} \in \text{Done} \\
& \wedge i \in \text{DOMAIN } \text{transaction} \wedge \text{transaction}[i].\text{phase} = \text{Rollback} \rightsquigarrow \\
& \quad \wedge i \in \text{DOMAIN } \text{transaction} \\
& \quad \wedge \text{transaction}[i].\text{rollback.proposal} \neq 0 \\
& \quad \wedge \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{commit} \in \text{Done} \\
& \quad \wedge \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{apply} \in \text{Done}
\end{aligned}$$

$$\text{Termination} \triangleq$$

$$\forall i \in 1 \dots \text{NumTransactions} : \Diamond \text{Terminates}(i)$$

$$\text{Liveness} \triangleq \text{Termination}$$

$$\text{THEOREM } \text{Spec} \Rightarrow \text{Liveness}$$

---