

---

MODULE *Transaction*

---

INSTANCE *Naturals*  
 INSTANCE *FiniteSets*  
 INSTANCE *Sequences*  
 INSTANCE *TLC*

---

An empty constant  
 CONSTANT *Nil*

Transaction phase constants  
 CONSTANTS  
     *Change*,  
     *Rollback*

Proposal phase constants  
 CONSTANTS  
     *Commit*,  
     *Apply*

Status constants  
 CONSTANTS  
     *Pending*,  
     *Complete*,  
     *Aborted*,  
     *Failed*

$Status \triangleq \{Pending, Complete, Aborted, Failed\}$   
 $Done \triangleq \{Complete, Aborted, Failed\}$

The set of all nodes  
 CONSTANT *Node*  
 $Empty \triangleq [p \in \{\} \mapsto Nil]$

---

Variables defined by other modules.  
 VARIABLES  
     *configuration*,  
     *mastership*,  
     *conn*,  
     *target*

A transaction log. Transactions may either request a set of changes to a set of targets or rollback a prior change.

VARIABLE *transaction*

A proposal log.

VARIABLE *proposal*

A sequence of configuration changes used for model checking.

VARIABLE *history*

$TransactionOK \triangleq$

$$\begin{aligned} & \forall i \in \text{DOMAIN } transaction : \\ & \quad \wedge transaction[i].phase \in \{Change, Rollback\} \\ & \quad \wedge transaction[i].change.proposal \in Nat \\ & \quad \wedge transaction[i].change.revision \in Nat \\ & \quad \wedge \forall p \in \text{DOMAIN } transaction[i].change.values : \\ & \quad \quad transaction[i].change.values[p] \neq Nil \Rightarrow \\ & \quad \quad transaction[i].change.values[p] \in \text{STRING} \\ & \quad \wedge transaction[i].rollback.proposal \in Nat \\ & \quad \wedge transaction[i].rollback.revision \in Nat \\ & \quad \wedge \forall p \in \text{DOMAIN } transaction[i].rollback.values : \\ & \quad \quad transaction[i].rollback.values[p] \neq Nil \Rightarrow \\ & \quad \quad transaction[i].rollback.values[p] \in \text{STRING} \end{aligned}$$

$ProposalOK \triangleq$

$$\begin{aligned} & \forall i \in \text{DOMAIN } proposal : \\ & \quad \wedge proposal[i].transaction \in Nat \\ & \quad \wedge proposal[i].commit \in Status \\ & \quad \wedge proposal[i].apply \in Status \end{aligned}$$

$TypeOK \triangleq TransactionOK \wedge ProposalOK$

$LOCAL \ State \triangleq [$

$$\begin{aligned} & \quad transactions \mapsto [i \in \text{DOMAIN } transaction \mapsto transaction[i] @@ [index \mapsto i]], \\ & \quad proposals \mapsto [i \in \text{DOMAIN } proposal \mapsto proposal[i] @@ [index \mapsto i]], \\ & \quad configuration \mapsto configuration] \end{aligned}$$

$LOCAL \ Transitions \triangleq$

LET

$$\begin{aligned} & \quad transactions \triangleq \{i \in \text{DOMAIN } transaction' : \\ & \quad \quad i \in \text{DOMAIN } transaction \Rightarrow transaction'[i] \neq transaction[i]\} \\ & \quad proposals \triangleq \{i \in \text{DOMAIN } proposal' : \\ & \quad \quad i \in \text{DOMAIN } proposal \Rightarrow proposal'[i] \neq proposal[i]\} \end{aligned}$$

IN

$$\begin{aligned} & [transactions \mapsto [i \in transactions \mapsto transaction'[i] @@ [index \mapsto i]], \\ & \quad proposals \mapsto [i \in proposals \mapsto proposal'[i] @@ [index \mapsto i]]] \end{aligned}$$

$Test \triangleq \text{INSTANCE } Test \text{ WITH}$   
 $File \leftarrow \text{"Transaction.log"}$

---

This section models configuration changes and rollbacks. Changes are appended to the transaction log and processed asynchronously.

Add a set of changes 'c' to the transaction log  
 $AppendChange(p, v) \triangleq$   
 $\wedge transaction' = Append(transaction, [$   
 $\quad phase \mapsto Change,$   
 $\quad change \mapsto [$   
 $\quad \quad proposal \mapsto 0,$   
 $\quad \quad revision \mapsto Len(transaction) + 1,$   
 $\quad \quad values \mapsto (p :> v)],$   
 $\quad rollback \mapsto [$   
 $\quad \quad proposal \mapsto 0,$   
 $\quad \quad revision \mapsto 0,$   
 $\quad \quad values \mapsto Empty])]$   
 $\wedge \text{UNCHANGED } \langle proposal, configuration, mastership, conn, target, history \rangle$

Add a rollback of transaction 't' to the transaction log  
 $RollbackChange(i) \triangleq$   
 $\wedge i \in \text{DOMAIN } transaction$   
 $\wedge transaction[i].phase = Change$   
 $\wedge transaction[i].change.proposal \neq 0$   
 $\wedge proposal[transaction[i].change.proposal].commit \neq Pending$   
 $\wedge transaction' = [transaction \text{ EXCEPT } ![i].phase = Rollback]$   
 $\wedge \text{UNCHANGED } \langle proposal, configuration, mastership, conn, target, history \rangle$

---

$ReconcileChange(n, i) \triangleq$   
 $\wedge transaction[i].phase = Change$   
 $\quad \text{The change proposal has not yet been created.}$   
 $\wedge \vee \wedge transaction[i].change.proposal = 0$   
 $\quad \text{The prior transaction must have created a change proposal.}$   
 $\wedge i - 1 \in \text{DOMAIN } transaction \Rightarrow transaction[i - 1].change.proposal \neq 0$   
 $\wedge proposal' = Append(proposal, [transaction \mapsto i, commit \mapsto Pending, apply \mapsto Pending])$   
 $\wedge transaction' = [transaction \text{ EXCEPT } ![i].change.proposal = Len(proposal')]$   
 $\wedge \text{UNCHANGED } \langle configuration, target, history \rangle$   
 $\quad \text{The change proposal has been created.}$   
 $\vee \wedge transaction[i].change.proposal \neq 0$   
 $\quad \text{The change is pending commit. Validate and commit the change once the prior change has been committed.}$   
 $\wedge \vee \wedge proposal[transaction[i].change.proposal].commit = Pending$

The prior proposal has been committed.  
 $\wedge \text{transaction}[i].\text{change.proposal} - 1 \in \text{DOMAIN } \text{proposal} \Rightarrow$   
 $\text{proposal}[\text{transaction}[i].\text{change.proposal} - 1].\text{commit} \in \text{Done}$   
 The prior change has been committed.  
 $\wedge \text{configuration.committed.index} = i - 1$   
 Valid change is committed to the configuration.  
 $\wedge \vee \wedge \text{transaction}' = [\text{transaction } \text{EXCEPT } ![i].\text{rollback.revision} = \text{configuration.committed.revision}$   
 $\quad \quad \quad ![i].\text{rollback.values} = [$   
 $\quad \quad \quad p \in \text{DOMAIN } \text{transaction}[i].\text{change.values} \mapsto$   
 $\quad \quad \quad \text{IF } p \in \text{DOMAIN } \text{configuration.committed.values}$   
 $\quad \quad \quad \text{configuration.committed.values}[p]$   
 $\quad \quad \quad \text{ELSE}$   
 $\quad \quad \quad \text{Nil}]$   
 $\wedge \text{configuration}' = [\text{configuration } \text{EXCEPT } !.\text{committed.index} = i,$   
 $\quad \quad \quad !.\text{committed.revision} = i,$   
 $\quad \quad \quad !.\text{committed.values} = \text{transaction}[i].\text{change.values}$   
 $\quad \quad \quad \text{configuration.committed.values}]$   
 $\wedge \text{proposal}' = [\text{proposal } \text{EXCEPT } ![\text{transaction}[i].\text{change.proposal}].\text{commit} = \text{Complete}]$   
 $\wedge \text{history}' = \text{Append}(\text{history}, [\text{type} \mapsto \text{Change}, \text{phase} \mapsto \text{Commit}, \text{index} \mapsto i])$   
 The change is invalid. Increment the committed index and mark the change *Failed*.  
 $\vee \wedge \text{configuration}' = [\text{configuration } \text{EXCEPT } !.\text{committed.index} = i]$   
 $\wedge \text{proposal}' = [\text{proposal } \text{EXCEPT } ![\text{transaction}[i].\text{change.proposal}].\text{commit} = \text{Failed}]$   
 $\wedge \text{UNCHANGED } \langle \text{transaction}, \text{history} \rangle$   
 $\wedge \text{UNCHANGED } \langle \text{target} \rangle$   
 The change apply is pending.  
 $\vee \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} = \text{Pending}$   
 The prior proposal has been applied.  
 $\wedge \text{transaction}[i].\text{change.proposal} - 1 \in \text{DOMAIN } \text{proposal} \Rightarrow$   
 $\text{proposal}[\text{transaction}[i].\text{change.proposal} - 1].\text{apply} \in \text{Done}$   
 The prior change has been applied.  
 $\wedge \text{configuration.applied.index} = i - 1$   
 If the transaction proposal was committed, attempt to apply the transaction.  
 $\wedge \vee \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{commit} = \text{Complete}$   
 $\wedge \text{configuration.state} = \text{Complete}$   
 $\wedge \text{configuration.term} = \text{mastership.term}$   
 $\wedge \text{conn}[n].\text{id} = \text{mastership.conn}$   
 $\wedge \text{conn}[n].\text{connected}$   
 $\wedge \text{target.running}$   
 The change is successfully applied to the target.  
 $\wedge \vee \wedge \text{target}' = [\text{target } \text{EXCEPT } !.\text{values} = \text{transaction}[i].\text{change.values} @@ \text{target.values}]$   
 $\wedge \text{configuration}' = [\text{configuration } \text{EXCEPT } !.\text{applied.revision} = i,$   
 $\quad \quad \quad !.\text{applied.values} = \text{transaction}[i].\text{change.values}$   
 $\quad \quad \quad \text{configuration.applied.values}]$   
 $\wedge \text{proposal}' = [\text{proposal } \text{EXCEPT } ![\text{transaction}[i].\text{change.proposal}].\text{apply} = \text{Complete}]$   
 $\wedge \text{history}' = \text{Append}(\text{history}, [\text{type} \mapsto \text{Change}, \text{phase} \mapsto \text{Apply}, \text{index} \mapsto i])$

The change fails being applied to the target.

The configuration's applied index is not incremented here to block applying subsequent changes until the failed change is rolled back.

$$\vee \wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![transaction[i].change.proposal].apply = Failed] \\ \wedge \text{UNCHANGED } \langle configuration, target, history \rangle$$

If the transaction proposal failed commit, abort applying the transaction.

$$\vee \wedge \text{proposal}[transaction[i].change.proposal].commit = Failed \\ \wedge \text{configuration}' = [configuration \text{ EXCEPT } !.applied.index = i] \\ \wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![transaction[i].change.proposal].apply = Aborted] \\ \wedge \text{UNCHANGED } \langle target, history \rangle \\ \wedge \text{UNCHANGED } \langle transaction \rangle$$

*ReconcileRollback*( $n, i$ )  $\triangleq$

$$\wedge \text{transaction}[i].phase = Rollback$$

The rollback proposal has not yet been created.

$$\wedge \vee \wedge \text{transaction}[i].rollback.proposal = 0$$

The subsequent transaction must have created a rollback proposal.

$$\wedge i + 1 \in \text{DOMAIN } transaction \Rightarrow \text{transaction}[i + 1].rollback.proposal \neq 0 \\ \wedge \text{proposal}' = \text{Append}(\text{proposal}, [transaction \mapsto i, commit \mapsto Pending, apply \mapsto Pending]) \\ \wedge \text{transaction}' = [transaction \text{ EXCEPT } ![i].rollback.proposal = Len(\text{proposal}')] \\ \wedge \text{UNCHANGED } \langle configuration, target, history \rangle$$

The rollback proposal has been created.

$$\vee \wedge \text{transaction}[i].rollback.proposal \neq 0$$

The rollback commit is pending.

$$\wedge \vee \wedge \text{proposal}[transaction[i].rollback.proposal].commit = Pending$$

The change has been committed. Commit the rollback.

$$\wedge \vee \wedge \text{proposal}[transaction[i].change.proposal].commit \in Done$$

If the change proposal completed, commit the rollback proposal.

$$\wedge \vee \wedge \text{proposal}[transaction[i].change.proposal].commit = Complete \\ \wedge \text{configuration.committed.revision} = i \\ \wedge \text{configuration}' = [configuration \text{ EXCEPT } !.committed.revision = transaction[i].rollback \\ !.committed.values = transaction[i].rollback \\ configuration.committed.revision = i]$$

$$\wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![transaction[i].rollback.proposal].commit = Complete]$$

$$\wedge \text{history}' = \text{Append}(\text{history}, [type \mapsto Rollback, phase \mapsto Commit, index \mapsto i])$$

If the change proposal failed, complete the rollback commit.

$$\vee \wedge \text{proposal}[transaction[i].change.proposal].commit = Failed \\ \wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![transaction[i].rollback.proposal].commit = Complete] \\ \wedge \text{UNCHANGED } \langle configuration, history \rangle$$

The change has not been committed. Abort the change once the prior change is committed.

$$\vee \wedge \text{proposal}[transaction[i].change.proposal].commit = Pending$$

$$\wedge i - 1 \in \text{DOMAIN } transaction \Rightarrow$$

$$\text{proposal}[transaction[i - 1].change.proposal].commit \in Done$$

$$\wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![transaction[i].change.proposal].commit = Aborted]$$

$$\wedge \text{UNCHANGED } \langle configuration, history \rangle$$

$\wedge \text{UNCHANGED } \langle \text{target} \rangle$   
 The rollback commit is complete, increment the configuration's committed index if necessary.  
 $\vee \wedge \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{commit} = \text{Complete}$   
 $\wedge \text{configuration.committed.index} = i - 1$   
 $\wedge \text{configuration}' = [\text{configuration} \text{ EXCEPT } !.\text{committed.index} = i]$   
 $\wedge \text{UNCHANGED } \langle \text{proposal}, \text{target}, \text{history} \rangle$   
 The rollback apply is pending.  
 $\vee \wedge \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{apply} = \text{Pending}$   
 The change has been applied and the rollback has been committed.  
 Apply the rollback.  
 $\wedge \vee \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} \in \text{Done}$   
 $\wedge \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{commit} = \text{Complete}$   
 If the change apply was completed or failed, apply the rollback.  
 Rollbacks are applied when change apply failed to account for  
 partial failures in changes to the target.  
 $\wedge \vee \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} \in \{ \text{Complete}, \text{Failed} \}$   
 $\wedge \text{configuration.applied.revision} = i$   
 $\wedge \text{configuration.state} = \text{Complete}$   
 $\wedge \text{configuration.term} = \text{mastership.term}$   
 $\wedge \text{conn}[n].\text{id} = \text{mastership.conn}$   
 $\wedge \text{conn}[n].\text{connected}$   
 $\wedge \text{target.running}$   
 Rollbacks are applied until successful.  
 $\wedge \text{target}' = [\text{target} \text{ EXCEPT } !.\text{values} = \text{transaction}[i].\text{rollback.values} @@ \text{target.values}]$   
 $\wedge \text{configuration}' = [\text{configuration} \text{ EXCEPT } !.\text{applied.target} = \text{target.id},$   
 $\quad !.\text{applied.revision} = \text{transaction}[i].\text{rollback.revision},$   
 $\quad !.\text{applied.values} = \text{transaction}[i].\text{rollback.values} @@ \text{configuration.applied.values}]$   
 $\wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![\text{transaction}[i].\text{rollback.proposal}].\text{apply} = \text{Complete}]$   
 $\wedge \text{history}' = \text{Append}(\text{history}, [\text{type} \mapsto \text{Rollback}, \text{phase} \mapsto \text{Apply}, \text{index} \mapsto i])$   
 If the change apply was aborted, complete the rollback apply without changes to the target.  
 $\vee \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} = \text{Aborted}$   
 $\wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![\text{transaction}[i].\text{rollback.proposal}].\text{apply} = \text{Complete}]$   
 $\wedge \text{UNCHANGED } \langle \text{configuration}, \text{target}, \text{history} \rangle$   
 The change has not been applied. Abort the change once the prior change is applied.  
 $\vee \wedge \text{proposal}[\text{transaction}[i].\text{change.proposal}].\text{apply} = \text{Pending}$   
 $\wedge i - 1 \in \text{DOMAIN } \text{transaction} \Rightarrow$   
 $\quad \text{proposal}[\text{transaction}[i - 1].\text{change.proposal}].\text{apply} \in \text{Done}$   
 $\wedge \text{proposal}' = [\text{proposal} \text{ EXCEPT } ![\text{transaction}[i].\text{change.proposal}].\text{apply} = \text{Aborted}]$   
 $\wedge \text{UNCHANGED } \langle \text{configuration}, \text{target}, \text{history} \rangle$   
 The rollback apply is complete, increment the configuration's applied index if necessary.  
 $\vee \wedge \text{proposal}[\text{transaction}[i].\text{rollback.proposal}].\text{apply} = \text{Complete}$   
 $\wedge \text{configuration.applied.index} = i - 1$   
 $\wedge \text{configuration}' = [\text{configuration} \text{ EXCEPT } !.\text{applied.index} = i]$   
 $\wedge \text{UNCHANGED } \langle \text{proposal}, \text{target}, \text{history} \rangle$

$$\begin{aligned}
& \wedge \text{UNCHANGED } \langle \textit{transaction} \rangle \\
\textit{ReconcileTransaction}(n, i) & \triangleq \\
& \wedge i \in \text{DOMAIN } \textit{transaction} \\
& \wedge \vee \textit{ReconcileChange}(n, i) \\
& \quad \vee \textit{ReconcileRollback}(n, i) \\
& \wedge \text{UNCHANGED } \langle \textit{mastership}, \textit{conn} \rangle
\end{aligned}$$


---