This drawing belongs to LGE. Those who drain away illegally shall be punished according to the relevant rules and the company standards.

NOTE

This part contain Eco-hazardous substances (Pb,Cd,Hg,Cr6+,PBB,PBDE,etc.) within LG standard level.
Details should be followed Eco-SCM management standard [LG(56)-A-2524] .
Especially, Part should be followed and controlled the following specification.
(1) Eco-hazardous substances test report should be submitted when Part certification test and First Mass Production.
(2) Especially, Don't use or contain lead(Pb) and cadmium(Cd) in ink.

1. 입고 방식 : Sheet Type / 종이포장
2. 양산 전 설계의 승인을 득할 것.

1. Packing method when delivering : Sheet type
2. Submit samples and get approval of the engineering department before mass production.

DIMENSIONAL TOLERANCE

SECTION / GRADE	4 ~ BELOW	5 ~ 12	13 ~ 36	37 ~ 110	111 ~ 330	331 ~ 1000	331 ~ 1000	1000 ~ OVER
1	0.10	0.15	0.20	0.30	0.45	0.70	0.70	1.0
2	0.15	0.20	0.30	0.45	0.70	1.0	1.0	1.5
3	0.20	0.30	0.45	0.70	1.0	1.5	1.5	2.0
4	0.30	0.45	0.70	1.0	1.5	2.0	2.0	3.0
5	0.45	0.70	1.0	1.5	2.0	3.0	3.0	4.0

ANGULAR 90° ±
UNLESS OTHERWISE SEPCIFIED

REV. NO	MM/DD/YY	SIGNATURE	CHANGED NO	CHANGED CONTENTS

THIRD ANGLE PROJECT

SCALE	UNIT
1/1	mm

DRAWN	AUG./09/20	B. W. CHOI
CHECKED	AUG./09/20	J. Y. BANG
APPROVED	AUG./09/20	J. O. KIM

LG

CIC LABEL
~LED OUTSOURCING~
MEZ688335(01P)

PACKING METHOD WHEN DELIVERING	PRINTING COLOR	MATERIAL(VENDOR)/ADHESIVE	SIZE W(±0.2)	SIZE H(±0.2)	REMARK	ITEM NO
	BLACK	YUPO R-80(WHITE PP 80㎛) Permanent Type 3.5 kg·f/cm2 ~ + UV Coating	40	52	TV (Vietnam)	01
						02
						03
						04
						05
						06
						07
						08
						09
						10
						11
						12
						13
						14
						15
						16
						17
						18
						19
						20
						21
						22
						23
						24
						25
						26
						27
						28
						29
						30
						31
						32
						33

NOTE

This part contain Eco-hazardous substances (Pb,Cd,Hg,Cr6+,PBB,PBDE,etc.) within LG standard level.
Details should be followed Eco-SCM management standard [LG(56)-A-2524] .
Especially, Part should be followed and controlled the following specification.
(1) Eco-hazardous substances test report should be submitted when Part certification test and First Mass Production.
(2) Especially, Don't use or contain lead(Pb) and cadmium(Cd) in ink.

1. 입고 방식 : Sheet Type / 종이포장
2. 양산 전 설계의 승인은 득할 것.

1. Packing method when delivering : Sheet type
2. Submit samples and get approval of the engineering department before mass production.

DIMENSIONAL TOLERANCE

GRADE \ SECTION	4 ~ BELOW	5 ~ 12	13 ~ 36	37 ~ 110	111 ~ 330	331 ~ 1000	331 ~ 1000	1000 ~ OVER
1	0.10	0.15	0.20	0.30	0.45	0.70	0.70	1.0
2	0.15	0.20	0.30	0.45	0.70	1.0	1.0	1.5
3	0.20	0.30	0.45	0.70	1.0	1.5	1.5	2.0
4	0.30	0.45	0.70	1.0	1.5	2.0	2.0	3.0
5	0.45	0.70	1.0	1.5	2.0	3.0	3.0	4.0

ANGULAR 90° ±
UNLESS OTHERWISE SEPCIFIED

This drawing belongs to LGE. Those who drain away illegally shall be punished according to the relevant rules and the company standards.

THIRD ANGLE PROJECT

SCALE	UNIT
1/1	mm

LG

DRAWN	AUG./09/20	B. W. CHOI
CHECKED	AUG./09/20	J. Y. BANG
APPROVED	AUG./09/20	J. O. KIM

CIC LABEL
~LED OUTSOURCING~
MEZ688335(02P)

[ITEM NO. "01"] TV (Vietnam)

4-R1.5

LG

Báo bảo hành?
Cần sửa chữa?
Hướng dẫn sử dụng?

Vui lòng gọi:

1800 1503

(Miễn cước cuộc gọi)

Cutting Line

MEZ68833501(REV00)

★ MEZ68833501(REV00)

★ Barcode information. 바코드 정보.
- 128 code
- Size : W 35 mm(±2) X H 5.5 mm(±2)

[ex] MEZ68833501(REV00)
1) Part number 품번 : MEZxxxxxxxx
2) REV No. of each Part Number 각 품번의 REV No. : (REVxx)
- Use (REV00) ~ (REV99).

- 업체에서 인쇄하여 입고

GUIDE FOR BACK OF LABEL

"Vui lòng giữ lại tem này
và dán ở vị trí dễ nhìn
để Quí khách tiện liên hệ
khi cần dịch vụ!"

NOTE

This part contain Eco-hazardous substances (Pb,Cd,Hg,Cr6+,PBB,PBDE,etc.) within LG standard level.
Details should be followed Eco-SCM management standard [LG(56)-A-2524] .
Especially, Part should be followed and controlled the following specification.
(1) Eco-hazardous substances test report should be submitted when Part certification test and First Mass Production.
(2) Especially, Don't use or contain lead(Pb) and cadmium(Cd) in ink.

1. 입고 방식 : Sheet Type / 종이포장
2. 양산 전 설계의 승인은 득할 것.

1. Packing method when delivering : Sheet type
2. Submit samples and get approval of the engineering department before mass production.

DIMENSIONAL TOLERANCE

GRADE \ SECTION	4 ~ BELOW	5 ~ 12	13 ~ 36	37 ~ 110	111 ~ 330	331 ~ 1000	331 ~ 1000	1000 ~ OVER
1	0.10	0.15	0.20	0.30	0.45	0.70	0.70	1.0
2	0.15	0.20	0.30	0.45	0.70	1.0	1.0	1.5
3	0.20	0.30	0.45	0.70	1.0	1.5	1.5	2.0
4	0.30	0.45	0.70	1.0	1.5	2.0	2.0	3.0
5	0.45	0.70	1.0	1.5	2.0	3.0	3.0	4.0

ANGULAR 90° ±

UNLESS OTHERWISE SEPCIFIED

This drawing belongs to LGE. Those who drain away illegally shall be punished according to the relevant rules and the company standards.

THIRD ANGLE PROJECT

SCALE	UNIT
1/1	mm

DRAWN	AUG./09/20	B. W. CHOI
CHECKED	AUG./09/20	J. Y. BANG
APPROVED	AUG./09/20	J. O. KIM

LG

CIC LABEL
~LED OUTSOURCING~

MEZ688335(03P)