

```
curl --location --request POST 'https://<DLP Manager  
IP>:<DLP Manager port>/dlp/rest/v1/incidents/' \  
--header 'Authorization: Bearer <access token> ' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
    "sort_by": "INSERT_DATE",  
    "type" : "INCIDENTS",  
    "from_date" : "01/08/2021 16:00:00",  
    "to_date" : "12/08/2021 20:00:00",  
    "detected_by" : "Endpoint Agent",  
    "analyzed_by": "Policy Engine 100190120a",  
    "event_id" : 5121411628328991975,  
    "destination" : "Windows Portable Device (WPD)",  
    "policies" : "PCI",  
    "action" : "BLOCKED",  
    "source" : "DESKTOP-3NG4NN6\\Lenovo",  
    "status" : "NEW",  
    "severity" : "MEDIUM",  
    "endpoint_type" : "LAPTOP",  
    "channel" : "ENDPOINT_REMOVABLE_MEDIA",  
    "assigned_to" : "admin",  
    "tag" : "Vadim tag"  
}'
```

Response output for the Get Incidents API



Note

The output parameters listed in this section cannot be used as input parameters. To send a request using specific filters (parameters), use the input parameters above ([Input parameters for the Get Incidents API, page 10](#)).

Root output

The following parameters are shown in the response. For examples of responses, see [Response example for the Get Incidents API](#), page 17.

Name	Supported	Comments
total_count	INCIDENTS DISCOVERY	Total number of incidents that found by the provided filters.
total_returned	INCIDENTS DISCOVERY	Number of incidents returned on response.
not_found_ids	INCIDENTS DISCOVERY	List of IDs that were provided on API input but were not found in the database. This list is returned along with the custom error code 420.
incidents	INCIDENTS DISCOVERY	Array of incident objects.

Object properties for incidents

The following objects are included in the response for the `incidents` parameter.

Name	Supported	Comments
id	INCIDENTS DISCOVERY	
severity	INCIDENTS DISCOVERY	
action	INCIDENTS DISCOVERY	
tag	INCIDENTS	
status	INCIDENTS	
destination	INCIDENTS	
details	INCIDENTS	
released_incident	INCIDENTS	
event_id	INCIDENTS DISCOVERY	
maximum_matches	INCIDENTS DISCOVERY	
transaction_size	INCIDENTS DISCOVERY (by ID only)	

Name	Supported	Comments
assigned_to	INCIDENTS DISCOVERY (by ID only)	
analyzed_by	INCIDENTS DISCOVERY (by ID only)	
ignored_incidents	INCIDENTS	
event_time	INCIDENTS	
incident_time	INCIDENTS DISCOVERY	
channel	INCIDENTS DISCOVERY (by filter only)	
policies	INCIDENTS DISCOVERY	
partition_index	INCIDENTS	
detected_by	INCIDENTS	
endpoint_type	INCIDENTS	
violation_triggers	INCIDENTS DISCOVERY (by ID only)	Number of violation triggers.
file_name	INCIDENTS	
file_path	DISCOVERY	

Object properties for source

The following objects are included in the response for the `source` parameter.

Name	Supported	Comments
manager	INCIDENTS	
department	INCIDENTS	
ip_address	INCIDENTS	
login_name	INCIDENTS	
host_name	INCIDENTS DISCOVERY (by ID only)	
email_address	INCIDENTS	
dn	INCIDENTS	
nt_domain	INCIDENTS	

Name	Supported	Comments
risk_level	INCIDENTS	Set only if a value > 0
business_unit	INCIDENTS	

Response example for the Get Incidents API

This section shows an example of a response from this API. For more information about each parameter shown in the response, see [Response output for the Get Incidents API](#), page 15.

```
{
  "incidents": [
    {
      "id": 373623,
      "severity": "HIGH",
      "action": "RELEASED",
      "tag": "Tag",
      "status": "Closed",
      "source": {
        "email_address": test2@aaa.com
      },
      "event_id": "7728775614896485765",
      "maximum_matches": 13,
      "transaction_size": 2632,
      "analyzed_by": "Policy Engine 1272021",
      "ignored_incidents": false,
      "event_time": "19/10/2021 10:12:02",
      "incident_time": "19/10/2021 10:12:02",
      "channel": "EMAIL",
      "policies": "Credit Cards; PCI",
      "partition_index": 20211019,
      "destination": aaa@aaa.net,
      "detected_by": "Protector on 1272021",
      "details": "Automatic Email Subject with
<keyword>",
      "released_incident": true,
      "violation_triggers": 2,
      "file_name": "visa.txt - 1.09 KB"
    }
  ],
  "total_count": 1,
}
```

```
    "total_returned": 1  
  }
```

If no incidents were found, the response returns a 420 error code along with a response similar to the following:

```
{  
  "incidents": [],  
  "total_count": 0,  
  "total_returned": 0,  
  "not_found_ids": [  
    373623111  
  ]  
}
```

Status and error codes for Get Incidents API

Code	Message
200	Success
400	Bad request (no valid input)
403	Forbidden (authentication failed)
420	No incidents were found

Update Incidents API

Forcepoint DLP REST API Guide | Dec 2021

The **update** API updates the incidents retrieved during the **incidents** API call.

POST `https://<DLP Manager IP>:<DLP Manager port>/dlp/rest/v1/incidents/update`

In this section

- [Header parameters for the Update Incidents API, page 20](#)
- [Input parameters for the Update Incidents API, page 21](#)
- [Request examples for the Update Incidents API, page 23](#)
- [Response output for the Update Incidents API, page 25](#)
- [Response example for the Update Incidents API, page 25](#)
- [Status and error codes for the Update Incidents API, page 26](#)

Header parameters for the Update Incidents API

The following two header parameters are required: Authorization and Content-Type.

Parameter	Authorization
Valid Values	The JWT used to authenticate requests.
Example	Authorization: Bearer <access token>

Parameter	Content-Type
Valid Values	application/json
Example	Content-Type: application/json

Input parameters for the Update Incidents API

Root parameters

The following parameters are shown in the request. For examples of requests, see [Request examples for the Update Incidents API, page 23](#).

Name	Required/ Optional	Supported	Valid values
type	Required	INCIDENTS, DISCOVERY	INCIDENTS DISCOVERY
action_type	Required	INCIDENTS, DISCOVERY	STATUS SEVERITY ASSIGN_TO ADD_COMMENT TAG RELEASE (not supported for DISCOVERY) FALSE_POSITIVE
value	Required Optional (ADD_COMMENT, RELEASE)	INCIDENTS, DISCOVERY	STATUS: NEW, IN_PROCESS, CLOSE, FALSE_POSITIVE, ESCALATED, custom status SEVERITY: HIGH, MEDIUM, LOW ASSIGN_TO: admin name to be assigned to TAG: tag name (maximum 100 chars) FALSE_POSITIVE: 1 (ignore), 0 (include)
comment	Optional Required for ADD_COMMENT	INCIDENTS, DISCOVERY	Supported for the following actions: ADD_COMMENT ASSIGN_TO TAG RELEASE (not supported for DISCOVERY) FALSE_POSITIVE
scan_partitions	Optional (default value is NONE)	INCIDENTS (relevant only if incident_keys is populated)	Parameter to identify if partition_index was provided on each event key. ALL: Scans all partitions to get incidents and fetches their partition_index that is required for an update. NONE: Assumes partition_index is provided. If partition_index is missing on any key, then an exception is thrown. LAST_ACTIVE: Sets last 2 partitions and sends update with them. If the incident is not located on those 2 partitions, then update does not execute.

Name	Required/ Optional	Supported	Valid values
event_ids	Required when update by event ids	INCIDENTS, DISCOVERY	Array of the Event IDs to be updated. If event_ids is provided, then it is required to perform a lookup for incidents by event ID to get incident_id and partition_index. Currently, there is no API to avoid searching over all partitions. The number of provided IDs is limited to 1,000. Error code 400 is returned if violated.
incident_keys	Required when update by incident keys	INCIDENTS, DISCOVERY	Array of Incident Key objects on which the action should be performed. The number of provided IDs is limited to 1,000. Error code 400 is returned if violated.

Object properties for incident_keys

The following objects are included in the request for the `incident_keys` parameter.

Name	Required/ Optional	Supported	Valid values
incident_id	Required	INCIDENTS, DISCOVERY	Incident ID to be updated.
partition_index	Optional	INCIDENTS	Partition Index from the incidents table that are required to build a query. If this field is not provided on an INCIDENTS request, then the system should look up this parameter internally. In this case, the API will require more resources to complete the update action.