


Recommendation Generation for Performance Improvement by using Cross-Organizational Process Mining

Onur Yılmaz Supervisor: Assoc. Prof. Pınar Karagöz

September 1, 2015



Onur Yılmaz





Agenda

- 1 Introduction
- 2 Related Work
- 3 Background
- 4 Methodology

- Results & Discussions
- 6 Conclusion & Future Work
- 7 Demonstration

Introduction

Process Mining



Relatively young and developing research area and main idea is to

- discover,
- monitor and;
- improve processes by extracting information
 from event logs. [1]







Competitive business life

Introduction

Cross-Organizational Process Mining



Cloud computing and shared infrastructures



Event logs of multiple organizations [2]



Analyze the big picture

Work together to execute the same process



Execute the same task on shared infrastructure [3]

Introduction

Focus of this Study




- A hybrid approach
 - Using different process mining subfields to create a new point of view
- Cross-organizational process mining
 - Processes are executed on several organizations,
 - Unsupervised learning using performances of organizations

Agenda


- 1 Introduction
- 2 Related Work
- Background
- 4 Methodology

- Results & Discussions
- 6 Conclusion & Future Work
- 7 Demonstration

State of the Art in Process Mining



State of the Art in Process Mining



Contributions of This Study



- Cross-organizational process mining approach for process performance improvement
- Generic, noise-capable process mining method for mining process models of different organizations
- Clustering of organizations based on their performance indicators
 - Unlike the clustering methods based on process structures in the literature [9]

Contributions of This Study



- Mismatch analysis for spotting differences between processes of organizations
 - Formulation and implementation of patterns and analyzers
- Recommendation generation to show how organizations can learn from other organizations which perform better
- Open-source, extensible and configurable set of plugins in ProM framework



Agenda

- 1 Introduction
- 2 Related Work
- 3 Background
- 4 Methodology

- Results & Discussions
- 6 Conclusion & Future Work
- 7 Demonstration


Event Log



 Outputs of the software systems like Enterprise Resource Planning (ERP) or Business Process Management (BPM)


Event Log				
		Attributes		
	Event	Date	Time	Transition
Case #1	Register Application	16.04.2013	14:37:27	Complete
	Check Credit	16.04.2013	14:41:19	Complete
	Check System	16.04.2013	14:47:35	Complete
	Calculate Capacity	16.04.2013	14:50:21	Complete
	Accept	16.04.2013	14:53:22	Complete
	Send decision e-mail	16.04.2013	14:55:11	Complete
Case #2	Register Application	16.04.2013	16:28:19	Complete
	Check Credit	16.04.2013	16:36:22	Complete

Event Log



Process Modeling


- Workflow Net
 - Petri net with a start node, end node and connectedness



Mathematical background

Process Modeling

- Business Process Modelling Notation (BPMN)
 - Standardized and easy to understand by stakeholders



Business oriented


Process Discovery




- One of the most challenging tasks is to construct a process model based on the behavior in the event logs
- Inductive Miner Infrequent (IMi) is used since it is simple, highly applicable and configurable to handle noise [20]
 - Block-structured Workflow Nets
 - Rediscoverability

Process Performance Analysis

 Discover relationships between event logs and process models for conformance and performance analysis [21]



Mismatch Patterns in Process Models



Patterns for frequent mismatches between the similar process models by Dijkman [14]



Authorization



Activity

- Skipped Activity
- Refined Activity




Control Flow

- Activities at Different Moments in Processes
- Different Conditions for Occurrence
- Different Dependencies
- Additional Dependencies


Mismatch Patterns in Process Models

Activity Mismatch Patterns [14]

Skipped Activity




Refined Activity




Mismatch Patterns in Process Models

Control Flow Mismatch Patterns [14]

Activities at Different Moments in Processes




Different Conditions for Occurrence




Mismatch Patterns in Process Models

Control Flow Mismatch Patterns [14]

Different Dependencies



Additional Dependencies



Agenda


- 1 Introduction
- 2 Related Work
- Background
- 4 Methodology

- Results & Discussions
- 6 Conclusion & Future Work
- 7 Demonstration

Approach Overview




Approach Overview



Process Model Mining

Applied for each organization:



Performance Indicator Analysis



Two steps:

Replay and Performance Indicator Calculation

Performance Indicator Clustering

- Performance Indicators:
 - Average Time Between Activities




Standard Deviation of Time
 Between Activities




Performance Indicator Analysis - Replay and Performance Indicator Calculation

Applied for each organization:




Performance Indicator Analysis - Performance Indicator Clustering




Mismatch Pattern Analysis

- Spot the differences between process models of different organizations as mismatch patterns
- BPMN used since notation is more appropriate to formulate mismatch patterns



Mismatch Pattern Analysis

Mismatch patterns and analyzers are developed




Recommendation Generation



- Providing a set of mismatch patterns for each organization to enhance their processes.
 - Mismatch patterns between organizations, which are performing better in terms of their performance indicator values.

Recommendation = (Organization, A_{start} , A_{end} , Mismatch Patterns)

Recommendation Generation



Recommendation Generation

```
RecommendationGeneration

input: O organization, C Cluster Analysis Data, P performance

difference threshold

output: Recommendations a set of recommendations

Recommendations 
{}

i 
Cluster of organization O

for each centroid for cluster i

Get other cluster j with the centroids of A<sub>start</sub> and A<sub>end</sub>; and

value difference larger than P

for each organization O' in the cluster j

MismatchPatterns 
Mismatch Pattern Analysis (O, O', A<sub>start</sub>, A<sub>end</sub>)

Recommendations 
Recommendation (O, A<sub>start</sub>, A<sub>end</sub>, MismatchPatterns)
```


Agenda

- 1 Introduction
- 2 Related Work
- Background
- 4 Methodology

- Results & Discussions
- 6 Conclusion & Future Work
- 7 Demonstration

Results & Discussions

Evaluation Metrics



Dataset Selection



Loan Application Process [26]

- Synthetically generated
- 4 variants of a simple loan application in a financial institute

Environmental Permit Application Process [27]

- Real-life event log from "Configurable Services for Local Governments (CoSeLoG)" project [13]
- «Environmental Permit Application Process» of 5 municipalities in Netherlands


Loan Application Process

	Cases	Events	Percentage
Variant #1	100	590	24 %
Variant #2	70	420	17 %
Variant #3	200	800	33 %
Variant #4	105	630	26 %

Cases Events **2440**

These variants are used as organizational logs


Loan Application Process - Process Model Mining




Variant #1	Variant #2	Variant #3	Variant #4
100 % (Fitness)	100 % (Fitness)	100 % (Fitness)	100 % (Fitness)
84.2 % (Avg. App.)	100 % (Avg. App.)	100 % (Avg. App.)	99.1 % (Avg. App.)


Loan Application Process - Performance Indicator Analysis

Clustering:






Loan Application Process - Mismatch Pattern Analysis



Correlation between graph-edit similarity and number of mismatch patterns

Loan Application Process - Recommendation Generation



 Responsiveness and degree of helping the user to focus on the performance improvement

Environmental Permit Application Process


	Cases	Events	Percentage
Municipality #1	54	131	6.1 %
Municipality #2	302	586	27.3 %
Municipality #3	37	73	3.4 %
Municipality #4	340	507	23.7 %
Municipality #5	481	845	39.4 %

Cases Events **1214 2142**

- Preprocessing is undertaken on the raw dataset [28]
- These municipalities are used as organizational logs

Environmental Permit Application Process - Process Model Mining


10 to 20 times simplified process models



Municipality #1	Municipality #2	Municipality #3	Municipality #4	Municipality #5
86 % (Fitness)	100 % (Fitness)	92.3 % (Fitness)	96.8 % (Fitness)	94.5 % (Fitness)
76 % (Avg. App.)	100 % (Avg. App.)	69.1 % (Avg. App.)	64.9 % (Avg. App.)	49.3 % (Avg. App.)

Environmental Permit Application Process - Performance Indicator Analysis

Clustering:






Cluster #3

Cluster #1


Environmental Permit Application Process – Mismatch Pattern Analysis



Correlation between graph-edit similarity and number of mismatch patterns except
 Municipality #4 and #5

Environmental Permit Application Process – Recommendation Generation

(with 3 clusters)



- Learning opportunities increases as number of cluster increases
- Number of mismatch patterns to check significantly decreases with performance clustering

Discussions



- Mismatch analysis stage:
 - Differences in accordance with similarity metrics
 - Information value of mismatch patterns are not equal
- Recommendation generation stage:
 - Performance clustering helps to focus on differences
 - 3 times less in Loan Application Process Dataset
 - 100 times less in Environmental Permit Application Process Dataset

Discussions



- Business value of generated recommendations:
 - Results may be
 - important or
 - infeasible and irrelevant for business environment
 - Some insights about results can be provided but business environment and case related assessment is important.

Discussions


In Loan Application Process,

Variant #4 performs better

- 27 % on average time and
- 12 % on standard deviation time

between activities

Calculate Capacity → Accept



Process models between activities «Calculate Capacity» and «Accept»


Discussions

In Environmental Permit Application Process, Municipality #3 performs worse

- 40 % on average time and
- 53 % on standard deviation time

between activities

01_HOOFD_010 → 01_HOOFD_015



Simplified process models between activities «01_HOOFD_010» and «01 HOOFD 015»

Agenda

- 1 Introduction
- 2 Related Work
- 3 Background
- 4 Methodology

- Results & Discussions
- 6 Conclusion & Future Work
- 7 Demonstration



- Cross-organizational process mining is applied
 - Unsupervised learning with predictor variables as performances of organizations
 - In an environment where processes are executed on several organizations
- Results show that it is possible to use cross-organizational process mining and mismatch patterns for performance improvement recommendations

A four-stage solution is presented and their performances are explained



Future Work



- Process mining stage:
 - Different techniques can be used to mine complex process models
- Performance indicator stage:
 - New indicators based on business environment and needs

Future Work



- Mismatch pattern analysis:
 - New patterns can be introduced
- Recommendation generation:
 - Domain or BPM expertise to assess the quality of recommendations

Agenda

- 1 Introduction
- 2 Related Work
- Background
- 4 Methodology

- Results & Discussions
- 6 Conclusion & Future Work
- 7 Demonstration

ProM Implementation






- ProM, extensible framework that supports a wide variety of process mining techniques in form of plugins [24]
- Widely accepted in industry and academia with an active community
- Developed set of plugins are packaged with the name of «CrossOrgProcMin» and published on Github.



onuryilmaz/cross-orc-proc-min

ProM Implementation



Demonstration





Also available on YouTube http://youtu.be/T92UrRfl3r0

- [1] W. M. P. van der Aalst, A. Adriansyah, A.K.A. de Medeiros, and et al. Process mining manifesto. In Business process management workshops, pages 169–194. Springer, 2012.
- [2] J. C. Buijs, B. F. van Dongen, and W. M. P. van der Aalst. Towards crossorganizational process mining in collections of process models and their executions. In Business Process Management Workshops, pages 2–13. Springer, 2012.
- [3] W. M. P. van der Aalst. Intra-and inter-organizational process mining: Discovering processes within and between organizations. In The Practice of Enterprise Modeling, pages 1–11. Springer, 2011.
- [4] W. M. P. van der Aalst. Process mining: discovery, conformance and enhancement of business processes. Springer Science & Business Media, 2011.
- [5] A. K. A. de Medeiros, B. F. van Dongen, W. M. P. van der Aalst, and A. J. M. M. Weijters. Process mining: Extending the -algorithm to mine short loops. 2004.
- [6] W. M. P. van der Aalst, T.Weijters, and L. Maruster. Workflow mining: Discovering process models from event logs. Knowledge and Data Engineering, IEEE Transactions on, 16(9):1128–1142, 2004.
- [7] J. Herbst. Dealing with concurrency in workflow induction. In European Concurrent Engineering Conference. SCS Europe. Citeseer, 2000.

- [8] J. Herbst and D. Karagiannis. Integrating machine learning and workflow management to support acquisition and adaptation of workflow models. In Database and Expert Systems Applications, 1998. Proceedings. Ninth International Workshop on, pages 745–752. IEEE, 1998.
- [9] G. Greco, A. Guzzo, and L. Pontieri. Mining hierarchies of models: From abstract views to concrete specifications. In Business Process Management, pages 32–47. Springer, 2005.
- [10] W. M. P. van der Aalst, A.K.A. de Medeiros, and A. J. M. M. Weijters. Genetic process mining. In Applications and theory of Petri nets 2005, pages 48–69. Springer, 2005.
- [11] E. Esgin, P. Senkul, and C. Cimenbicer. A hybrid approach for process mining: using from-to chart arranged by genetic algorithms. In Hybrid Artificial Intelligence Systems, pages 178–186. Springer, 2010.
- [12] E. Esgin and R. Senkul. A hybrid approach to process mining: Finding immediate successors of a process by using from-to chart. In Machine Learning and Applications, 2009. ICMLA'09. International Conference on, pages 664–668. IEEE, 2009.
- [13] W. M. P. van der Aalst. Business process configuration in the cloud: how to support and analyze multi-tenant processes? In Web Services (ECOWS), 2011 Ninth IEEE European Conference on, pages 3–10. IEEE, 2011.

- [14] R. Dijkman. Mismatch Patterns in Similar Business Processes. Beta, Research School for Operations Management and Logistics, 2007.
- [15] R. Dijkman, M. Dumas, B. van Dongen, R. Käärik, and J. Mendling. Similarity of business process models: Metrics and evaluation. Information Systems, 36(2):498–516, 2011.
- [16] J. C. Buijs and H. A. Reijers. Comparing business process variants using models and event logs. In Enterprise, Business-Process and Information Systems Modeling, pages 154–168. Springer, 2014.
- [17] E. Esgin and P. Karagoz. Sequence alignment adaptation for process diagnostics and delta analysis. In Hybrid Artificial Intelligent Systems, pages 191–201. Springer, 2013.
- [18] E. Esgin and P. Senkul. Delta analysis: a hybrid quantitative approach for measuring discrepancies between business process models. In Hybrid Artificial Intelligent Systems, pages 296–304. Springer, 2011.
- [19] S. J. J. Leemans, D. Fahland, and W. M. P. van der Aalst. Discovering blockstructured process models from event logs-a constructive approach. In Application and Theory of Petri Nets and Concurrency, pages 311–329. Springer, 2013.
- [20] S. J. J. Leemans, D. Fahland, and W. M. P. van der Aalst. Discovering block-structured process models from event logs containing infrequent behaviour. In Business Process Management Workshops, pages 66–78. Springer, 2014.

- [21] W. M. P. van der Aalst, A. Adriansyah, and B. van Dongen. Replaying history on process models for conformance checking and performance analysis. Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery, 2(2):182–192, 2012.
- [22] D. Arthur and S. Vassilvitskii. k-means++: the advantages of carefull seeding. In Proceedings of the eighteenth annual ACM-SIAM symposium on Discrete algorithms, pages 1027–1035, 2007.
- [23] M. Hall, E. Frank, G. Holmes, B. Pfahringer, P. Reutemann, and I. H. Witten. The weka data mining software: An update. SIGKDD Explor. Newsl., 11(1):10–18, November 2009.
- [24] H. M. W. Verbeek, J. C Buijs, B. F. van Dongen, and W. M. P. van der Aalst. Prom 6: The process mining toolkit. Proc. of BPM Demonstration Track, 615:34–39, 2010.
- [25] A. Rozinat and W. M. P. van der Aalst. Conformance checking of processes based on monitoring real behavior. Information Systems, 33(1):64–95, 2008.
- [26] J. C. Buijs. Loan application example, 2013.
- [27] J.C. Buijs. Environmental permit application process ('wabo'), coselog project, 2014.
- [28] J. C. Buijs. Flexible Evolutionary Algorithms for Mining Structured Process Models. PhD thesis, PhD thesis. Eindhoven, The Netherlands: Technische Universiteit Eindhoven, 2014 (cit. on p. 179), 2014.

Questions & Comments



Thank you for your attention!



Recommendation Generation for Performance Improvement by using Cross-Organizational Process Mining

Onur Yılmaz Supervisor: Assoc. Prof. Pınar Karagöz

September 1, 2015

