

While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Normally the first step in debugging is to attempt to reproduce the problem. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Scripting and breakpointing is also part of this process. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Programs were mostly entered using punched cards or paper tape. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Normally the first step in debugging is to attempt to reproduce the problem. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Programmable devices have existed for centuries. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Whatever the approach to development may be, the final program must satisfy some fundamental properties. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages.