

For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Techniques like Code refactoring can enhance readability. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. However, readability is more than just programming style. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Code-breaking algorithms have also existed for centuries. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Computer programmers are those who write computer software. Techniques like Code refactoring can enhance readability. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. It is usually easier to code in "high-level" languages than in "low-level" ones. There are many approaches to the Software development process. Also, specific user environment and usage history can make it difficult to reproduce the problem. Integrated development environments (IDEs) aim to integrate all such help. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit.