

In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. There are many approaches to the Software development process. Different programming languages support different styles of programming (called programming paradigms). Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. There exist a lot of different approaches for each of those tasks. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Unreadable code often leads to bugs, inefficiencies, and duplicated code. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Techniques like Code refactoring can enhance readability. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Use of a static code analysis tool can help detect some possible problems.