

The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. It is very difficult to determine what are the most popular modern programming languages. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Programs were mostly entered using punched cards or paper tape. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Code-breaking algorithms have also existed for centuries. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Whatever the approach to development may be, the final program must satisfy some fundamental properties. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Different programming languages support different styles of programming (called programming paradigms). The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Programmable devices have existed for centuries. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Scripting and breakpointing is also part of this process. Following a consistent programming style often helps readability. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine.