

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. It is very difficult to determine what are the most popular modern programming languages. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Code-breaking algorithms have also existed for centuries. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Programs were mostly entered using punched cards or paper tape. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Techniques like Code refactoring can enhance readability. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Ideally, the programming language best suited for the task at hand will be selected.