

In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Whatever the approach to development may be, the final program must satisfy some fundamental properties. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. There exist a lot of different approaches for each of those tasks. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Different programming languages support different styles of programming (called programming paradigms). It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. It is usually easier to code in "high-level" languages than in "low-level" ones. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). However, readability is more than just programming style. Normally the first step in debugging is to attempt to reproduce the problem. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Ideally, the programming language best suited for the task at hand will be selected. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses.