

It affects the aspects of quality above, including portability, usability and most importantly maintainability. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Following a consistent programming style often helps readability. Computer programmers are those who write computer software. Integrated development environments (IDEs) aim to integrate all such help. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Following a consistent programming style often helps readability. Programmable devices have existed for centuries. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. It is usually easier to code in "high-level" languages than in "low-level" ones.