

Many applications use a mix of several languages in their construction and use. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Different programming languages support different styles of programming (called programming paradigms). Ideally, the programming language best suited for the task at hand will be selected. Code-breaking algorithms have also existed for centuries. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Use of a static code analysis tool can help detect some possible problems. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Many applications use a mix of several languages in their construction and use. Ideally, the programming language best suited for the task at hand will be selected. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Also, specific user environment and usage history can make it difficult to reproduce the problem. Programmable devices have existed for centuries. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers.