

Integrated development environments (IDEs) aim to integrate all such help. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Programmable devices have existed for centuries. Use of a static code analysis tool can help detect some possible problems. Techniques like Code refactoring can enhance readability. Integrated development environments (IDEs) aim to integrate all such help. It is usually easier to code in "high-level" languages than in "low-level" ones. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Code-breaking algorithms have also existed for centuries. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Also, specific user environment and usage history can make it difficult to reproduce the problem. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Normally the first step in debugging is to attempt to reproduce the problem.