

Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Different programming languages support different styles of programming (called programming paradigms). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Many applications use a mix of several languages in their construction and use. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Also, specific user environment and usage history can make it difficult to reproduce the problem. Integrated development environments (IDEs) aim to integrate all such help. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Code-breaking algorithms have also existed for centuries. Programmable devices have existed for centuries. Unreadable code often leads to bugs, inefficiencies, and duplicated code.