

Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. One approach popular for requirements analysis is Use Case analysis. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Techniques like Code refactoring can enhance readability. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Normally the first step in debugging is to attempt to reproduce the problem. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. It is very difficult to determine what are the most popular modern programming languages. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Use of a static code analysis tool can help detect some possible problems. Programs were mostly entered using punched cards or paper tape. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug.