

Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Also, specific user environment and usage history can make it difficult to reproduce the problem. Whatever the approach to development may be, the final program must satisfy some fundamental properties. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Programming languages are essential for software development. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. There are many approaches to the Software development process. Scripting and breakpointing is also part of this process. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Also, specific user environment and usage history can make it difficult to reproduce the problem. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Integrated development environments (IDEs) aim to integrate all such help. There exist a lot of different approaches for each of those tasks. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research.