

For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. There exist a lot of different approaches for each of those tasks. Programs were mostly entered using punched cards or paper tape. It is usually easier to code in "high-level" languages than in "low-level" ones. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. It is very difficult to determine what are the most popular modern programming languages. There are many approaches to the Software development process. Techniques like Code refactoring can enhance readability. Many applications use a mix of several languages in their construction and use. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Scripting and breakpointing is also part of this process. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages.