

Many applications use a mix of several languages in their construction and use. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Ideally, the programming language best suited for the task at hand will be selected. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Many applications use a mix of several languages in their construction and use. Ideally, the programming language best suited for the task at hand will be selected. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Ideally, the programming language best suited for the task at hand will be selected. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. It is usually easier to code in "high-level" languages than in "low-level" ones. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers.