

He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Use of a static code analysis tool can help detect some possible problems. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Programmable devices have existed for centuries. Programs were mostly entered using punched cards or paper tape. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Different programming languages support different styles of programming (called programming paradigms). It is very difficult to determine what are the most popular modern programming languages. Also, specific user environment and usage history can make it difficult to reproduce the problem. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Normally the first step in debugging is to attempt to reproduce the problem. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Scripting and breakpointing is also part of this process.