

There are many approaches to the Software development process. It affects the aspects of quality above, including portability, usability and most importantly maintainability. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Unreadable code often leads to bugs, inefficiencies, and duplicated code. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Unreadable code often leads to bugs, inefficiencies, and duplicated code. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Normally the first step in debugging is to attempt to reproduce the problem. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. It is very difficult to determine what are the most popular modern programming languages. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs.