

Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Integrated development environments (IDEs) aim to integrate all such help. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Following a consistent programming style often helps readability. There are many approaches to the Software development process. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. It is usually easier to code in "high-level" languages than in "low-level" ones. Scripting and breakpointing is also part of this process. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability.