

Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Techniques like Code refactoring can enhance readability. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Programming languages are essential for software development. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Computer programmers are those who write computer software. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Many applications use a mix of several languages in their construction and use. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. It affects the aspects of quality above, including portability, usability and most importantly maintainability. There are many approaches to the Software development process. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. However, Charles Babbage had already written his first program for the Analytical Engine in 1837.